# EXPERIMENT : 05

## Aim:

Exercise on retrieving records from the table.
EMPLOYEES (Employee_Id, First_Name, Last_Name, Email, Phone_Number, Hire_Date,Job_Date Salary, Commission_Act, Manager_Id, Department_Id)

( a) Find out the employee id, names, salaries of all the employees
( b) List out the employees who works under manager 100
( c) Find the names of the employees who have a salary greater than or equal to 4800
( d) List out the employees whose last name is 'AUSTIN'
( e) Find the names of the employees who works in departments 60,70 and 80 ( f ) Display the unique Manager_Id.

## SQL QUERIES:

```sql
CREATE DATABASE ASSIGNMENT_5;

USE ASSIGNMENT_5;

CREATE TABLE Employees (
Employee_ID INT PRIMARY KEY,
First_Name VARCHAR(50),
Last_Name VARCHAR(50),
Email VARCHAR(100),
Phone_Number VARCHAR(10),
Hire_Date DATE,
Job_ID VARCHAR(20),
Salary DECIMAL,
Commission_Act INT,
Manager_ID int,
Department_ID int
);
```

```sql
INSERT INTO EMPLOYEES VALUES
(101, 'Akansha', '.', 'ayadav@gmail.com', '12345', '2020-01-10', 'IT_PROG', 5000, NULL, 100, 60),
(102, 'Dolly', 'Sharma', 'dolly@gmail.com', '67890', '2021-02-15', 'SALES', 4800, NULL, 100, 70),
(103, 'Priyanshi ', 'Patel', 'priyanshi@gmail.com', '54321', '2019-03-20', 'HR', 3000, NULL, 101, 80),
(104, 'Neha', 'Austin', 'neha@gmail.com', '98765', '2022-04-25', 'IT_PROG', 7000, NULL, 100, 60),
(105, 'Dhruv', 'Kumar', 'dhruv@gmail.com', '11223', '2023-05-30', 'HR', 4500, NULL, 102, 90);


SELECT Employee_ID, First_Name, Last_Name, Salary FROM Employees;


SELECT *
FROM EMPLOYEES
WHERE Manager_Id = 100;

SELECT First_Name, Last_Name FROM Employees
Where Salary >= 4800;

SELECT * FROM Employees
Where Last_Name = "Austin";


SELECT First_Name, Last_Name FROM Employees
Where Department_ID IN (60, 70, 80);


SELECT DISTINCT Manager_ID FROM Employees;
```

**RESULTS:**

Result Grid | Filter Rows: | Edit:

| Employee_ID | First_Name | Last_Name | Salary |
|---|---|---|---|
| 101 | Akansha | . | 5000 |
| 102 | Dolly | Sharma | 4800 |
| 103 | Priyanshi | Patel | 3000 |
| 104 | Neha | Austin | 7000 |
| 105 | Dhruv | Kumar | 4500 |
| NULL | NULL | NULL | NULL |

Employees 7 × | EMPLOYEES 8 | Employees 9 | Employees 10

Result Grid | Filter Rows: | Edit: | Export/Import: | Wrap Cell Content:

| Employee_ID | First_Name | Last_Name | Email | Phone_Number | Hire_Date | Job_ID | Salary | Commission_Act | Manager_ID | Department_ID |
|---|---|---|---|---|---|---|---|---|---|---|
| 101 | Akansha | . | ayadav@gmail.com | 12345 | 2020-01-10 | IT_PROG | 5000 | NULL | 100 | 60 |
| 102 | Dolly | Sharma | dolly@gmail.com | 67890 | 2021-02-15 | SALES | 4800 | NULL | 100 | 70 |
| 104 | Neha | Austin | neha@gmail.com | 98765 | 2022-04-25 | IT_PROG | 7000 | NULL | 100 | 60 |
| NULL | NULL | NULL | NULL | NULL | NULL | NULL | NULL | NULL | NULL | NULL |

Result Grid | Filter Rows

| First_Name | Last_Name |
|---|---|
| Akansha | . |
| Dolly | Sharma |
| Neha | Austin |

Result Grid | Filter Rows: | Edit: | Export/Import: | Wrap Cell Content:

| Employee_ID | First_Name | Last_Name | Email | Phone_Number | Hire_Date | Job_ID | Salary | Commission_Act | Manager_ID | Department_ID |
|---|---|---|---|---|---|---|---|---|---|---|
| 104 | Neha | Austin | neha@gmail.com | 98765 | 2022-04-25 | IT_PROG | 7000 | NULL | 100 | 60 |
| NULL | NULL | NULL | NULL | NULL | NULL | NULL | NULL | NULL | NULL | NULL |

Result Grid | Filter Rov

| First_Name | Last_Name |
|---|---|
| Akansha | . |
| Dolly | Sharma |
| Priyanshi | Patel |
| Neha | Austin |

Result Grid |

| Manager_ID |
|---|
| 100 |
| 101 |
| 102 |

**<u>Explanation:</u>** I created a table called Employees with various fields such as employee ID, name, email, salary, job role, manager ID, and department ID, where the employee ID is set as the primary key to uniquely identify each record.

After creating the table, multiple employee records are inserted into it. SELECT queries are then used to retrieve data, such as displaying specific columns, filtering employees based on manager ID, salary conditions, last name, and department IDs using the WHERE and IN clauses.

The DISTINCT keyword is used to display unique manager IDs, avoiding duplicate values.

# EXPERIMENT:06

Create Client_master with the following fields (ClientNO, Name, Address, City, State, bal_due)

( a ) Insert five records

( b ) Find the names of clients whose bal_due> 5000 .

( c ) Change the bal_due of ClientNO " C123" to Rs. 5100 ( d ) Change the name of Client_master to Client12.

( e ) Display the bal_due heading as "BALANCE"

**SQL QUERIES:**

```sql
CREATE DATABASE labex6;
CREATE TABLE Client (
    ClientNO VARCHAR(10),
    Name VARCHAR(50),
    Address VARCHAR(100),
    City VARCHAR(50),
    State VARCHAR(50),
    bal_due INT
);
INSERT INTO Client VALUES ('101', 'Rahul', 'Street 1', 'Delhi', 'Delhi', 6000);
INSERT INTO Client VALUES ('102', 'Amit', 'Street 2', 'Mumbai', 'Maharashtra', 3000);
INSERT INTO Client VALUES ('123', 'Neha', 'Street 3', 'Pune', 'Maharashtra', 4500);
INSERT INTO Client VALUES ('104', 'Priya', 'Street 4', 'Chennai', 'Tamil Nadu', 7000);
INSERT INTO Client VALUES ('105', 'Ravi', 'Street 5', 'Kolkata', 'West Bengal', 2000);

SELECT Name
FROM Client
WHERE bal_due > 5000;

UPDATE Client
SET bal_due = 5100
WHERE ClientNO = '123';

ALTER TABLE Client
RENAME TO Client12;

SELECT bal_due AS BALANCE
FROM Client12;
```

**RESULTS:**

Result Grid

| Name |
| --- |
| Rahul |
| Priya |

Result Grid

| BALANCE |
| --- |
| 6000 |
| 3000 |
| 4500 |
| 7000 |
| 2000 |

Client12 2