

GMXBUILDER User Manual

Document version	V1.0.1
Software	GMXBUILDER v0.8.7 or later
Author	Haochen Yang
Release date	2026-08-11
Status	Public release

This manual describes validated preparation of starting systems. Production simulation still requires minimization, sufficient equilibration, repeat sampling, and scientific review.

Contents

Select a section title or page number to follow the document link.

Change log	3
1. Introduction	4
1.1 Available workflows	4
1.2 Check, Viewer, and Build	4
1.3 Scientific responsibility	4
2. Installation and service startup	5
2.1 Requirements	5
2.2 Interactive local installation	5
2.3 Manual installation	5
2.4 Start and inspect the service	5
3. Web interface	6
3.1 Task ID and browser routes	6
3.2 Bilayer Builder	6
3.3 Pure Bilayer System	7
3.4 Solvator	7
3.5 Martini 3 Builder	7
4. Command-line interface	8
4.1 Discover commands and capabilities	8
4.2 YAML atomistic build	8
4.3 Martini 3 example	8
5. HTTP API	10
5.1 Discovery and error handling	10
5.2 Minimal Solvator sequence	10
5.3 Build, queue, and download	10
6. Output package and execution	12
6.1 Typical atomistic package	12
6.2 Run the generated package	12
7. Troubleshooting	13
7.1 A lipid is unavailable	13
7.2 Bilayer orientation or packing looks wrong	13
7.3 Automatic protein orientation is implausible	13
7.4 Water layers appear unequal	13
7.5 Ions cluster or water is missing from the Viewer	13
7.6 ZIP lacks MDP files or run_md.sh	13
7.7 A Task cannot be resumed	13
8. Getting help	14

Change log

Document version	Date	Change	Author
V1.0.1	2026-08-11	Updated task routes, Task ID copy and recovery, Martini 3, DNA/RNA, CLI/API usage, output layout, and deployment boundaries	Haochen Yang
V1.0.0	2026-07-26	Initial release	Haochen Yang

1. Introduction

GMXBUILDER prepares GROMACS input packages for atomistic membrane-protein, pure-bilayer, and aqueous systems, and for supported Martini 3 coarse-grained systems. The Web, CLI, and HTTP API use the same validation rules.

1.1 Available workflows

Workflow	Purpose
Bilayer Builder	Process and orient a membrane protein, build a bilayer, add water and ions
Pure Bilayer System	Build a protein-free dry or solvated bilayer
Solvator	Build aqueous protein, canonical linear DNA/RNA, protein nucleic-acid, and compatible ligand systems
Martini 3 Builder	Build supported standard-protein solution, flat membrane, or protein membrane CG systems

Cards that are disabled in the installed interface are not current product capabilities. Query the application instead of relying on a static molecule count.

1.2 Check, Viewer, and Build

Every Check validates the current step and saves one authoritative task checkpoint. The Viewer reloads the saved coordinates. Later steps consume that checkpoint, so a changed upstream setting invalidates downstream results.

Final Build does not reconstruct the membrane, water, or ions. It assigns the topology and packages the last confirmed coordinates with the selected MDP stages and launcher script.

1.3 Scientific responsibility

A successful build establishes structural and topology consistency under the implemented checks. It does not establish a correct biological orientation, protonation state, ligand chemistry, equilibrium phase, or converged production trajectory. Review the [scientific limitations](#) before simulation.

2. Installation and service startup

2.1 Requirements

Linux and Python 3.10 or later.

Git LFS for release-bundled lipid assets.

A working GROMACS installation.

CUDA-capable GROMACS only when GPU execution is required.

AmberTools/ACPYPE for new GAFF2 parameterization.

The pinned Martini 3 dependencies when using the CG workflow.

`uv` is recommended for a frozen, hash-checked installation.

2.2 Interactive local installation

```
git clone https://github.com/AkaseToshiyuki/GMX-BUILDER.git
cd GMX-BUILDER
./install-local.sh
```

The installer prompts for the listening address, port, CPU allocation, task thread limit, queue slots, and deployment mode. Defaults are loopback, `127.0.0.1:7788`, half of detected CPU threads, and a queue size derived from the allocation. One Task remains strictly serial; safe computation inside its current step may use multiple threads.

2.3 Manual installation

```
git lfs install
git lfs pull
uv sync --frozen --no-dev
source .venv/bin/activate

gmxbuilder --version
gmxbuilder prebuilt-assets status
gmxbuilder prebuilt-assets install
```

The asset installer verifies checksums and installs only missing cache entries. It does not overwrite a newer existing cache.

2.4 Start and inspect the service

```
gmxbuilder serve
```

Open `<http://127.0.0.1:7788/>`. Resource limits can be selected explicitly:

```
gmxbuilder serve \
  --host 127.0.0.1 --port 7788 \
  --cpu-cores 24 --task-threads 8 \
  --max-builds 3 --gpu-count 1
```

`--task-threads` must divide `--cpu-cores`. Set `CUDA_VISIBLE_DEVICES` before startup to expose a selected GPU subset or order. Use `--gpu-count 0` for a CPU-only service.

Useful checks:

```
curl -fsS http://127.0.0.1:7788/health
systemctl --user status gmxbuilder.service
```

3. Web interface

3.1 Task ID and browser routes

After upload or task creation, save the displayed Task ID using the copy button. Browser routes contain only the workflow and step, for example:

```
/BilayerBuilder/Step3  
/Solvator/Step2
```

The Task ID is deliberately not placed in the URL. Refreshing returns to the home page. Entering a saved Task ID resumes at the first incomplete visible step, or at Build when a completed package can be downloaded again.

Tasks expire according to the server retention policy. Task-private uploads, including custom lipid parameters, expire with the Task.

3.2 Bilayer Builder

Step 1 Input Structure

Upload PDB, mmCIF, or a supported gzip-compressed form. Review chains, retained small molecules, alternate locations, missing heavy atoms, modified residues, and warnings. Deselecting or renaming a component changes the saved input and requires another Check.

Step 2 Force Field

Select one coherent protein, membrane, ligand, and water-model combination. The UI disables incompatible combinations and the server repeats the check. Amber membranes use one complete Lipid21 or GAFF2 backend; CHARMM systems use compatible CHARMM lipids and CGenFF/CHARMM ligand parameters.

For GAFF2 ligands, confirm the integer net charge for the intended protonation state. For CHARMM ligands without an exact bundled template, upload the matching CGenFF MOL2 and STR files.

Step 3 Structure Processing

Compute protonation assignments at the selected pH, then review termini, modifications, and crosslinks. PROPKA is a static-structure suggestion, not constant-pH MD. Only force-field-specific atom-complete modifications can be selected. Unsupported chemistry remains visible and blocks export.

Step 4 Protein Orientation

Automatic orientation is an aid, not a biological annotation. Review the grey membrane-interface planes and all extracellular, intracellular, and transmembrane regions. Manual adjustments are saved by Check and used by the next step.

Step 5 Membrane Builder

Choose upper and lower leaflet compositions and lipid counts. Every lipid must be supported by the selected backend and have a valid conformer library entry. Review leaflet orientation, headgroups facing solvent, tails facing the bilayer core, packing around the protein, and the quality report.

Step 6 Solvent & Box

Z padding describes the requested water thickness outside the membrane interfaces; XY is inherited from the membrane. Check the box, water layers, atom counts, and that the membrane does not cross a periodic boundary.

Step 7 Ions and complete-system confirmation

Choose ion species, concentration, neutralization, exclusion radius, and placement method. Random replacement, electrostatic replacement, and Monte Carlo placement all replace water molecules. Check the total system, inspect water and ion distributions, then confirm the exact coordinates below the Viewer before continuing.

Step 8 Simulation Parameters and Build

Enable only the equilibration and production stages you want. Each stage owns its temperature, coupling, cutoffs, restraints, output intervals, COM removal, and duration. Hardware settings affect [run_md.sh](#), not MDP physics. Build packages the confirmed ion checkpoint and does not rerun coordinate generation.

3.3 Pure Bilayer System

This workflow starts with force-field and lipid selection. It uses an independent implementation of membrane, solvation, ions, and export. Clear solvation to export a dry, relaxed bilayer; the dry package intentionally omits water, ions, MDP files, and [run_md.sh](#).

3.4 Solvator

Solvator omits membrane construction and orientation. Box padding is measured from the full retained solute in all directions and pressure coupling defaults to isotropic.

Canonical linear DNA/RNA is displayed as polymer chains, not small molecules. Select CHARMM36m. Structure Processing uses native GROMACS/CHARMM36 data to construct hydrogens, 5' / 3' termini, polymer bonds, and exact charge. Modified, circular, or broken nucleic-acid chains are blocked.

3.5 Martini 3 Builder

Martini 3 is an independent coarse-grained workflow. Select an aqueous or flat- bilayer environment, optional standard protein mapping, supported lipids, regular W water and ions, and then inspect the exact final CG system. Ligands, PTMs, glycans, nucleic acids, custom CG molecules, curved surfaces, and backmapping are not silently discarded; they are unavailable.

Protein Mapping suggests a safe periodic box from the rotated CG envelope. CG Environment rejects any box or offset that makes COBY wrap protein beads. Simulation Parameters exposes separate minimization, optional NVT, optional NPT, production, output/COM-removal, and execution-hardware controls; stages remain strictly serial and retain Martini 3-compatible non-bonded defaults.

4. Command-line interface

4.1 Discover commands and capabilities

```
gmxbuilder --help
gmxbuilder build --help
gmxbuilder serve --help
gmxbuilder coarse-grained --help
gmxbuilder info --pdb protein.pdb
gmxbuilder list-ff
gmxbuilder list-water
gmxbuilder list-lipids
gmxbuilder lipid-library status
```

4.2 YAML atomistic build

```
system_name: membrane_system
output_dir: ./output
seed: 42
```

```
modules:
  input:
    pdb: ./protein.pdb
  forcefield:
    name: amber14sb
    lipid_ff: lipid21
    ligand_ff: none
    water_model: tip3p
  structure:
    pH: 7.0
    prepare_standard termini: true
  orient:
    method: ppm
  membrane:
    lipid_type: POPC
    box_padding: 2.0
  solvation:
    box_padding: 2.0
  ions:
    cation: NA
    anion: CL
    concentration: 0.15
    neutralize: true
    ion_method: random
  topology: {}
  simparams:
    hardware:
      mode: thread-mpi
      cpu_threads: 8
      mpi_ranks: 2
      use_gpu: true
      gpu_count: 1
      gpu_ids: [0]
      gmx_command: gmx
    export:
      write_mdp: true
```

```
gmxbuilder build --config build.yaml
gmxbuilder build --config build.yaml --output ./another-output
```

Every selected lipid and retained molecule must be valid for the complete force-field combination. CLI failures use non-zero exit status and do not silently ignore unknown keys.

4.3 Martini 3 example

```
gmxbuilder coarse-grained \
  --mode bilayer \
  --upper POPC:3 --upper CHOL:1 \
  --lower POPE:1 --lower POPG:1 \
  --box-xy 12 --box-z 14 --salt 0.15 \
  --threads 8 --mpi-ranks 1 --gpu-ids 0 \
  --output ./martini-system
```

Use `--pdb protein.pdb` for a protein bilayer system or `--mode solution --pdb protein.pdb` for an aqueous protein system.

5. HTTP API

5.1 Discovery and error handling

When the service is running:

Swagger UI: <<http://127.0.0.1:7788/docs>>

OpenAPI schema: <<http://127.0.0.1:7788/openapi.json>>

Useful discovery endpoints:

```
GET /health
GET /api/hardware
GET /api/task-types
GET /api/options
```

Clients must check both the HTTP status and the JSON body. **4xx** denotes invalid input, unavailable capability, missing prerequisite, or expired Task; **5xx** denotes a server-side failure. Do not continue after an error response.

5.2 Minimal Solvator sequence

```
API=http://127.0.0.1:7788

curl -sS -X POST "$API/api/upload-pdb" \
-F "file=@protein.pdb" \
-F "task_type=solvator"

TASK_ID=<returned-task-id>

curl -sS -X POST "$API/api/step/$TASK_ID/input" \
-H "Content-Type: application/json" -d '{"config":{}}'

curl -sS -X POST "$API/api/step/$TASK_ID/forcefield" \
-H "Content-Type: application/json" \
-d '{"config":{"name":"amber14sb","lipid_ff":"none","ligand_ff":"none","water_model":"tip3p"}}'

curl -sS -X POST "$API/api/step/$TASK_ID/structure" \
-H "Content-Type: application/json" \
-d '{"config":{"pH":7.0,"prepare_standard_termini":true}}'

curl -sS -X POST "$API/api/step/$TASK_ID/solvation" \
-H "Content-Type: application/json" \
-d '{"config":{"box_padding":2.0}}'

curl -sS -X POST "$API/api/step/$TASK_ID/ions" \
-H "Content-Type: application/json" \
-d '{"config":{"cation":"NA","anion":"CL","concentration":0.15,"neutralize":true,"ion_method":"random"}}'
```

Bilayer clients also execute **orient** and **membrane** before solvation. Inspect saved checkpoints with **GET /api/steps/{task_id}**.

5.3 Build, queue, and download

```
curl -sS -X POST "$API/api/build" \
-H "Content-Type: application/json" \
-d '{
  "task_id":"","TASK_ID",
  "task_type":"solvator",
  "system_name":"solution_system",
  "modules":{
    "simparams":{"schema_version":2},
    "export":{"write_mdp":true}
  }
}'

curl -sS "$API/api/build/$TASK_ID/queue-status"
curl -fL "$API/api/task/$TASK_ID/download" -o result.zip
```

Queue responses include position and an estimated start time. Save the Task ID before leaving the page. [GET /api/tasks](#) is an administrator endpoint and requires [X-Admin-Token](#).

6. Output package and execution

6.1 Typical atomistic package

```
input.gro
input.pdb          # optional for very large systems
topol.top
index.ndx
run_md.sh
README.txt
forcefield.itp
ffbonded.itp
ffnonbonded.itp
topol_Protein_chain_A.itp # only when present
<lipid-or-ligand>.itp    # only when present
<water-model>.itp
<ion-parameters>.itp
mdp/
  mini.mdp
  equili_<n>.mdp        # enabled stages only
  production.mdp
  production_<n>.mdp    # segmented production when requested
```

Exact filenames depend on the selected system. [topol.top](#) is the authoritative include list. Martini packages additionally use [toppar/](#), [manifest.json](#), and [CITATIONS.json](#).

6.2 Run the generated package

```
unzip result.zip -d simulation
cd simulation
chmod +x run_md.sh
./run_md.sh
```

Read [README.txt](#) and inspect every [grompp](#) and [mdrun](#) message. Do not suppress warnings without understanding their physical and topology implications.

7. Troubleshooting

7.1 A lipid is unavailable

The selected backend lacks either an exact topology or a conformer that passed the quality gates. Use the alternative shown by the UI or select another validated composition.

7.2 Bilayer orientation or packing looks wrong

Do not continue. Recheck protein orientation, leaflet assignment, conformer identity, composition, and the Step 5 quality report.

7.3 Automatic protein orientation is implausible

Treat the automatic score as a starting point. Use manual adjustment, Check again, and verify that the subsequent Viewer matches the saved orientation.

7.4 Water layers appear unequal

For membranes, padding is measured from the membrane interfaces. A protruding protein can make the visible solvent shape asymmetric without redefining the requested membrane-relative padding. Check numerical box and interface values.

7.5 Ions cluster or water is missing from the Viewer

Re-run Ion Check, verify the selected replacement method and exclusion radius, and inspect the exact complete-system Viewer. Do not proceed if coordinates do not match the reported counts.

7.6 ZIP lacks MDP files or run_md.sh

A dry bilayer intentionally omits them. For a solvated system, ensure that at least one simulation stage and MDP export were enabled, then rebuild from the confirmed checkpoint.

7.7 A Task cannot be resumed

Check the 32-character ID and the server retention period. Task-private custom lipids cannot be moved to another Task.

8. Getting help

```
gmxbuilder --help
gmxbuilder list-ff
gmxbuilder list-water
gmxbuilder list-lipids
gmxbuilder lipid-library status
curl -fsS http://127.0.0.1:7788/health
```

When reporting a problem, include the GMXBUILDER version, Task ID, workflow step, complete error text, and a screenshot or log excerpt that contains no sensitive structure data.

Appendix A. Deployment security

Run as a non-root service account and restrict task-directory permissions.

Keep a public deployment bound to loopback behind a trusted TLS reverse proxy and set `GMXBUILDER_DEPLOYMENT_MODE=public`.

Configure the exact HTTPS origin, trusted proxy CIDRs, and strong global Basic or Bearer authentication.

Configure a strong `GMXBUILDER_ADMIN_TOKEN`; never log Task IDs or tokens.

Retain both application and reverse-proxy rate limits.

Install locked dependencies with `uv sync --frozen --no-dev` and review third-party licenses before redistribution.