

Ex. No.: 11B

Roll no:231901004

Date: 15.04.2025

LRU Page Replacement

Aim:

To write a C program to implement LRU page replacement algorithm.

Algorithm:

1. Start the process.
2. Declare the size for page frames.
3. Get the number of pages and reference string.
4. Use a stack or counter array to track recent usage.
5. For each page:
 - If it is in memory → no page fault.
 - Else → check least recently used page and replace it.
6. Count page faults.
7. Display frame contents after each operation.
8. Stop the process.

C Program:

```
#include <stdio.h>
```

```
int findLRU(int time[], int n) {    int
i, minimum = time[0], pos = 0;
    for(i = 1; i < n; i++) {
if(time[i] < minimum) {
minimum = time[i];
    pos = i;
    }
}
```

```

    }
    return pos;
}

int main() {    int frames[10], pages[50], time[10], counter = 0,
pageFaults = 0;

    int n, f, i, j, pos, flag1, flag2;

    printf("Enter number of frames: ");
    scanf("%d", &f);

    printf("Enter number of pages: ");
    scanf("%d", &n);

    printf("Enter reference string: ");
    for(i = 0; i < n; i++)
    scanf("%d", &pages[i]);

    for(i = 0; i < f; i++)
frames[i] = -1;

    for(i = 0; i < n; i++) {
flag1 = flag2 = 0;

        for(j = 0; j < f; j++) {
if(frames[j] == pages[i]) {
counter++;          time[j] =

```

```

counter;          flag1 = flag2
= 1;          break;
    }
}

```

```

    if(flag1 == 0) {          for(j
= 0; j < f; j++) {
if(frames[j] == -1) {
counter++;
pageFaults++;
frames[j] = pages[i];
time[j] = counter;
flag2 = 1;          break;
    }
    }
}

```

```

    if(flag2 == 0) {          pos
= findLRU(time, f);
counter++;
pageFaults++;
frames[pos] = pages[i];
time[pos] = counter;
    }

```

```

    for(j = 0; j < f; j++) {
if(frames[j] != -1)
printf("%d ", frames[j]);

```

```
        else
printf("- ");
    }
    printf("\n");
}

printf("\nTotal Page Faults = %d\n", pageFaults);
return 0;
}
```

Sample Output:

Enter number of frames: 3

Enter number of pages: 6

Enter reference string: 5 7 5 6 7 3

5 - - 5

7 -

5 7 - 5

7 6

5 7 6

3 7 6

Total Page Faults = 4

Result:

Thus, the C program for LRU page replacement algorithm was written and executed successfully. The number of page faults was calculated and verified.