Inductive Consensus Clustering: Geometry-Calibrated Ensemble Distillation for High-Dimensional Noise Regimes

Akash Kundu[1*], Trinankur Guha[1], Rupankar Ghatak[1], Anubhab Naskar[1], Kalyan Kumar Das[1]

[1*]Department of Computer Science and Engineering, Techno India University, EM-4, Sector V, Bidhannagar, Kolkata, 700091, West Bengal, India.

*Corresponding author(s). E-mail(s):
akash231001001449@technoindiaeducation.com;
Contributing authors:
trinankur231001001450@technoindiaeducation.com;
rupankar231001001438@technoindiaeducation.com;
anubhab231001001443@technoindiaeducation.com;
kalyankumar.das@technoindiaeducation.com;

Abstract

Consensus clustering synthesizes base partitions to discover robust data groupings. However, existing methods face two primary challenges: (1) a transductive formulation requiring $\boldsymbol{O(N^2)}$ storage preventing out-of-sample inference, and (2) vulnerability to high-dimensional distractor noise ($\boldsymbol{D \gg N}$), where distance concentration degrades partition fidelity. We examine **Inductive Consensus Clustering (ICC-v2)**, designed for small-sample, high-dimensional regimes subject to isotropic noise. ICC-v2 incorporates: (1) an $\boldsymbol{O(N \cdot D)}$ linear feature screening filter using Sarle's Bimodality Coefficient (Bimodality-Gated Subspace Selection, BGSS) isolating multimodal dimensions; (2) a determinacy-based bipartite anchor consensus graph reducing auxiliary memory from $\boldsymbol{O(N^2)}$ to $\boldsymbol{O(N \cdot L)}$; and (3) stability-weighted centroid assignment for $\boldsymbol{O(K \cdot |\mathcal{F}_{\text{active}}|)}$ inductive inference. Across 13 multi-domain benchmarks (1,430 model fits), deep embedded clustering (DEC) [1] attains the lowest omnibus mean rank ($\boldsymbol{R = 4.31}$), followed by Standard Consensus ($\boldsymbol{R = 5.08}$), K-Means ($\boldsymbol{R = 5.31}$), Ward ($\boldsymbol{R = 5.31}$), and ICC-v2 ($\boldsymbol{R = 5.46}$). ICC-v2 attains the highest Grand

Mean ARI (0.160) across all benchmarks and attains Rank #1 ($\boldsymbol{R = 2.33}$) on the exploratory high-dimensional biomedical subgroup ($\boldsymbol{D/N > 20}$, with 0.680 on Leukemia and 0.538 on SRBCT, representing an absolute ARI improvement of $\boldsymbol{+0.388}$ over the strongest baseline, FastMVC at $\boldsymbol{0.150 \pm 0.060}$, on SRBCT), while reducing auxiliary consensus memory by 97.0% at $\boldsymbol{N = 10{,}000}$ and executing up to $\boldsymbol{N = 1{,}000{,}000}$ instances in 55.6 s.

Keywords: Cluster ensemble, consensus clustering, inductive learning, out-of-sample extension, anchor certification, high-dimensional data, noise robustness.

1 Introduction

Clustering ensembles, originally pioneered by Strehl and Ghosh [2] and Fred and Jain [3], aim to integrate multiple base clusterings into a singular consensus partition. By aggregating diverse hypothesis partitions generated through randomized initializations, varied clustering algorithms, or random feature projections, consensus clustering mitigates the sensitivity of individual algorithms to hyperparameter selection and initialization bias [4–6].

Despite wide adoption across bioinformatics, computer vision, and knowledge discovery, consensus clustering algorithms encounter two primary limitations:

1. **Transductive Formulation:** Conventional consensus formulations operate directly on the $N \times N$ co-association matrix $S \in [0,1]^{N \times N}$ via graph partitioning, spectral decomposition [7], or non-negative matrix factorization [8]. When new, unseen test instances $\mathcal{X}_{\text{test}}$ arrive, the consensus partition cannot be inductively assigned without recomputing the co-association matrix and solving an $O((N + |\mathcal{X}_{\text{test}}|)^2)$ optimization from scratch.
2. **Curse of High-Dimensional Distractors:** In modern datasets where ambient dimensionality D greatly exceeds the intrinsic manifold dimension $d^* \ll D$, uninformative nuisance features degrade pairwise Euclidean distances. The distance concentration phenomenon causes within-cluster and between-cluster distances to converge to identical expectations, leading to degradation of consensus graphs [9–11].

To address these limitations, this paper investigates the **Inductive Consensus Clustering (ICC)** framework (Fig. 1). We examine the finite-sample empirical breakdown of consensus stability under isotropic distractor noise (Section 3), illustrating how distance concentration generates consensus agreement on arbitrary noise boundaries. Motivated by these findings, we formulate **ICC-v2**, a four-stage framework:

- **Bimodality-Gated Subspace Selection (BGSS):** An $O(N \cdot D)$ linear feature screening mechanism utilizing Sarle's Bimodality Coefficient ($\hat{b}_d = \frac{\hat{\gamma}_d^2 + 1}{\hat{\kappa}_d + 3 \cdot \frac{(N-1)^2}{(N-2)(N-3)} + \epsilon}$) [12–14] to filter unimodal distractor noise prior to base ensemble fitting.




Fig. 1: Conceptual overview of the high-dimensional noise dilemma and the proposed Inductive Consensus Clustering (ICC-v2) framework. (a) Ground-truth cluster geometry with certified invariant anchors (stars) in a low-dimensional signal subspace ($d = 2$). (b) Collapse of pairwise geometry when submerged in high-dimensional distractor noise ($D = 2{,}000$), with the inset demonstrating the distance concentration phenomenon where relative distance spread $(d_{\max} - d_{\min})/d_{\min} \to 0$ as $D \to \infty$. (c) Bimodality-Gated Subspace Selection (BGSS) spectrum isolating informative signal dimensions from the sea of distractor noise. (d) Closed-form geometry-calibrated inductive projection assigning unseen query instances $\mathbf{x}_{\text{new}}$ directly in $O(K \cdot |\mathcal{F}_{\text{active}}|)$ time without recomputing the $O(N^2)$ consensus graph.

- **Determinacy-Based Bipartite Anchor Consensus:** Constructs a rectangular bipartite co-association graph $B \in [0,1]^{N \times L}$ over L core anchors selected via quadratic consensus determinacy ($\sigma_i = \frac{1}{N-1} \sum_{j \neq i} S_{ij}^2$), reducing auxiliary memory from $O(N^2)$ to $O(N \cdot L)$ and accelerating spectral decomposition onto an $L \times L$ core affinity space.
- **Stability-Weighted Subspace Centroid Assignment:** Provides closed-form inductive out-of-sample mapping that assigns unseen query instances in $O(K \cdot |\mathcal{F}_{\text{active}}|)$ time without recomputing the consensus graph.
- **Anchor-Space Perturbation Profiling (ASPP):** An optional diagnostic module that probes cluster structural resilience across five physical perturbation families

directly over certified anchor coordinates, providing perturbation sensitivity indices (PSI_k) and out-of-sample query confidence scores.

The remainder of this manuscript is structured as follows: Section 2 reviews related work. Section 3 presents our empirical analysis of distance concentration and consensus behavior. Section 4 details the mathematical architecture and complexity analysis of ICC-v2. Section 5 provides empirical evaluations across generalization, ablation, real-world benchmarks, and scalability, followed by an explicit discussion of limitations. Section 6 concludes the paper.

2 Related Work

2.1 Cluster Ensembles and Consensus Graphs

The consensus clustering paradigm constructs a co-association matrix S where $S_{ij} = \frac{1}{M}\sum_{m=1}^{M} \mathbf{1}\{\pi_m(\mathbf{x}_i) = \pi_m(\mathbf{x}_j)\}$ represents the empirical probability that objects $\mathbf{x}_i$ and $\mathbf{x}_j$ are co-clustered across M base partitions [3]. Classical approaches partition this matrix using Cluster-based Similarity Partitioning (CSPA), HyperGraph Partitioning Algorithm (HGPA), or Meta-Clustering Algorithm (MCLA) [2]. Subsequent works explore dense subgraph discovery [10], random walk probability trajectories [9], random projection ensembles [6], and bipartite graph modeling [5]. However, classical formulations remain fundamentally transductive, requiring quadratic $O(N^2)$ co-association storage.

2.2 Robust, Anchor, and Out-of-Sample Clustering


To mitigate noise and outliers, Li et al. [8] and Zhang et al. [15] investigated determinacy-guided ensemble clustering, partitioning samples into deterministic core points and boundary points based on co-association variance. In scalable spectral and ensemble clustering, anchor graph methods (e.g., Nie et al. [16], Huang et al. [17], and U-SPEC/U-SENC by Huang et al. [18]) utilize bipartite graphs to reduce spectral decomposition complexity from $O(N^3)$ to $O(NL^2 + L^3)$. For out-of-sample extension, generalized Nyström formulas [19] project unseen points using kernel evaluations. In high-dimensional regimes, sparse clustering methods (e.g., sparse k-means by Witten and Tibshirani [20]) optimize lasso-type penalties on feature weights, but require iterative global optimization. Similarly, non-parametric multimodality testing (e.g., the Dip Test by Hartigan and Hartigan [21] and Sarle's Bimodality Coefficient [12–14]) provides statistical screening criteria. As summarized in Table 1, ICC-v2 combines linear bimodality subspace gating, determinacy-based bipartite anchor consensus, and inductive centroid projection into a unified linear-time pipeline.

3 Empirical Motivation & Finite-Sample Falsification


Theoretical literature on random projection clustering often considers asymptotic recovery under the assumption of infinite samples ($N \to \infty$) or orthogonal noise. We conducted empirical simulations on finite-sample datasets to systematically test whether consensus averaging alone protects against high-dimensional distractor noise.

Table 1: Methodological Taxonomy and Comparison Across Consensus Paradigms


Method	Feature Gating	Core Filtering	Inductive Ext.	Aux. Memory	Noise ($D \gg N$)
Std Cons. [3]	None	None	No	$O(N^2)$	No
Li et al. [8]	None	Determinacy	No	$O(N^2)$	No
FCAG [16]	None	Anchors	No	$O(NL)$	No
FastMVC [17]	None	Anchors	No	$O(NL)$	No
U-SPEC [18]	None	Anchors	Nyström	$O(NL)$	No
ICC-v2 (Ours)	**BGSS (Linear)**	**Core Anchors**	**Centroid**	**O(NL)**	**Subspace-Gated**



(a) Clustering Accuracy (ARI vs. Ground Truth) and Ensemble Stability Across D_{noise}



(b) Stability−Accuracy Gap (Δ = Stability − ARI)



(c) Noise Distribution Sensitivity Matrix (D_{noise} = 1,000)

Fig. 2: Empirical examination of consensus stability under finite-sample isotropic noise. (a) Decrease in ARI stability as distractor dimensions grow, demonstrating that multi-clusterer averaging alone does not prevent degradation. (b) Gap metric indicating positive stability attractors ($\Delta > 0$) for graph-based spectral and Ward clustering. (c) Stability−ARI gap evaluated across diverse noise distributions.

Definition 1 (Within/Between Distance Ratio) Let $\mathcal{C}_k$ denote cluster k with centroid $\boldsymbol{\mu}_k$. For an empirical sample $X \subset \mathbb{R}^D$, the separation ratio is defined as:

$$\rho_{\text{sep}}(X) = \frac{\frac{1}{K}\sum_{k=1}^{K} \frac{1}{|\mathcal{C}_k|} \sum_{\mathbf{x}_i \in \mathcal{C}_k} \|\mathbf{x}_i - \boldsymbol{\mu}_k\|_2}{\frac{2}{K(K-1)} \sum_{k<l} \|\boldsymbol{\mu}_k - \boldsymbol{\mu}_l\|_2}. \tag{1}$$

As ambient distractor dimensions D_{noise} expand ($D \gg N$), pairwise Euclidean distances exhibit distance concentration [11], where the relative contrast of distances diminishes: $\lim_{D\to\infty} \frac{d_{\max}-d_{\min}}{d_{\min}} = 0$ and the coefficient of variation $\lim_{D\to\infty} \frac{\sqrt{\text{Var}(\|\mathbf{x}_i-\mathbf{x}_j\|_2)}}{\mathbb{E}[\|\mathbf{x}_i-\mathbf{x}_j\|_2]} = 0$. Consequently, the separation ratio $\rho_{\text{sep}}(X)$ approaches 1.0 (illustrated conceptually in Fig. 1(b) and evaluated in Fig. 2a), reducing pairwise distance discrimination. Under finite samples, base clusterers can capture random fluctuations in the noise dimensions. This induces an empirical stability trap: base partitions repeatedly converge on arbitrary noise boundaries with consensus agreement (Stability > 0.8), while true cluster recovery decreases (ARI $\to 0$, Fig. 2a). As shown in Fig. 2b, this stability−accuracy discrepancy (Δ = Stability − ARI > 0) is prominent for graph-based spectral clustering and agglomerative Ward linkage, whereas centroid partition methods (K-Means, FCM) experience simultaneous collapse of stability and accuracy. Across diverse distractor distributions (Fig. 2c), this discrepancy persists across Gaussian, Student-t, and correlated noise regimes (Fig. 2). Thus, ensemble averaging alone is empirically observed to be insufficient to eliminate uninformative subspace noise without explicit feature gating.

4 The Inductive Consensus Clustering Framework

The ICC-v2 framework (Algorithm 1) operates in four stages:

4.1 Bimodality-Gated Subspace Selection (BGSS)

Under isotropic noise in $D \gg N$ regimes, classical variance thresholding fails because distractor noise features often match or exceed signal feature variances. To detect latent cluster structures without labels, BGSS evaluates marginal multimodality using **Sarle's Bimodality Coefficient** (BC) [12–14] with finite-sample null correction:

$$\hat{b}_d = \frac{\hat{\gamma}_d^2 + 1}{\hat{\kappa}_d + 3 \cdot \frac{(N-1)^2}{(N-2)(N-3)} + \epsilon}, \tag{2}$$

where $\hat{\gamma}_d$ is the sample skewness (with finite-sample bias correction for $N \geq 3$), $\hat{\kappa}_d$ is Fisher's sample excess kurtosis (with finite-sample bias correction for $N \geq 4$), the denominator term adjusts excess kurtosis to Pearson's kurtosis under normal null expectations, and $\epsilon = 10^{-5}$ prevents division by zero with denominator clamped via $\max(\cdot, 10^{-5})$. Features with zero variance ($\text{Var}(\mathbf{f}_d) < 10^{-12}$) are assigned $\hat{b}_d = 0$.

Proposition 1 (Conditional Multimodality Separation Bound) *For a standard unimodal Gaussian distractor distribution, $\gamma = 0$ and $\kappa = 0$, yielding $\mathbb{E}[\hat{b}_d] \approx 1/3 \approx 0.333$. For a continuous uniform distribution, $b_d = 5/9 \approx 0.556$. For a balanced two-component Gaussian mixture $0.5\mathcal{N}(-\Delta, \sigma_0^2) + 0.5\mathcal{N}(\Delta, \sigma_0^2)$, Pearson kurtosis is $\beta_2 = \frac{3+6\theta+\theta^2}{(1+\theta)^2}$ where $\theta = (\Delta/\sigma_0)^2$. The coefficient satisfies $b_d > 5/9$ if and only if $\theta > \frac{3+\sqrt{15}}{2} \approx 3.436$, which corresponds to*

Algorithm 1 Inductive Consensus Clustering (ICC-v2)

Require: Data matrix $X \in \mathbb{R}^{N \times D}$, ensemble size M, target clusters K, anchor budget $L \ll N$ (default 40; recommended $\max(40, 10K)$), core quantile τ_{core}, candidate pool fraction α (default 0.15).

Ensure: Consensus labels $\mathbf{y} \in \{1, \ldots, K\}^N$, Anchors $\mathcal{A}_{\text{core}}$, Active Subspace $\mathcal{F}_{\text{active}}$, Centroids $\{\boldsymbol{\mu}_k\}_{k=1}^K$.

// Stage 1: Multimodality Subspace Gating (BGSS)

for each feature column $d \in \{1, \ldots, D\}$ **do**

  Compute finite-sample Sarle's Bimodality Coefficient:

  $b_d \leftarrow \frac{\hat{\gamma}_d^2 + 1}{\hat{\kappa}_d + 3 \cdot \frac{(N-1)^2}{(N-2)(N-3)} + \epsilon}$ (with $b_d \leftarrow 0$ if $\text{Var}(\mathbf{f}_d) < 10^{-12}$).

end for

Extract candidate pool $\mathcal{F}_{\text{active}}$ by sorting b_d descending and taking the top $\min(D, \max(K, \lfloor \alpha \cdot D \rfloor))$ features (with minimum cap $\min(100, D)$).

// Stage 2: Guided Subspace Ensemble Generation

for $m = 1$ to M **do**

  Draw random subspace $\mathcal{F}_m \subset \mathcal{F}_{\text{active}}$.

  Fit base partition $\pi_m \leftarrow \text{Clusterer}(X_{[:, \mathcal{F}_m]}, K)$.

end for

// Stage 3: Determinacy-Based Bipartite Anchor Consensus

Evaluate sample determinacy $\sigma_i \leftarrow \frac{1}{N-1} \sum_{j \neq i} S_{ij}^2$ via Proposition 2 in $O(M^2 N + M^2 K^2)$ time.

Identify core instances $\mathcal{C}_{\text{core}} \leftarrow \{i \mid \sigma_i \geq \text{Quantile}(\boldsymbol{\sigma}, \tau_{\text{core}})\}$.

Select $L = \min(40, |\mathcal{C}_{\text{core}}|)$ anchors $\mathcal{A}_{\text{core}}$ uniformly from $\mathcal{C}_{\text{core}}$.

Construct bipartite co-association matrix $B \in [0, 1]^{N \times L}$:

$B_{ia} \leftarrow \frac{1}{M} \sum_{m=1}^M \mathbf{1}\{\pi_m(\mathbf{x}_i) = \pi_m(\mathbf{x}_a)\}$.

Row-normalize $B_{\text{norm}} \leftarrow D_R^{-1} B$, where $D_R = \text{diag}(B \mathbf{1}_L)$.

Compute anchor affinity $W_{\text{anchor}} \leftarrow B_{\text{norm}}^T B_{\text{norm}} \in \mathbb{R}^{L \times L}$, and $D_A = \text{diag}(W_{\text{anchor}} \mathbf{1}_L)$.

Solve normalized Laplacian $L_{\text{anchor}} \leftarrow I - D_A^{-1/2} W_{\text{anchor}} D_A^{-1/2}$ for the K smallest eigenvectors $V \in \mathbb{R}^{L \times K}$ with eigenvalues $\boldsymbol{\lambda}$.

Compute embedding $U \leftarrow B_{\text{norm}} V \in \mathbb{R}^{N \times K}$ (or Transfer-Cut embedding $U \leftarrow B_{\text{norm}} D_A^{-1/2} V \, \text{diag}(\max(1 - \boldsymbol{\lambda}, 10^{-4}))^{-1/2}$) and row-normalize.

Extract consensus labels $\mathbf{y} \leftarrow \text{K-Means}(U, K)$.

// Stage 4: Stability-Weighted Centroid Induction

for $k = 1$ to K **do**

  $\boldsymbol{\mu}_k \leftarrow \frac{\sum_{i: y_i = k} \sigma_i \cdot \mathbf{x}_{i, [\mathcal{F}_{\text{active}}]}}{\sum_{i: y_i = k} \sigma_i}$.

end for

return $\mathbf{y}, \mathcal{A}_{\text{core}}, \mathcal{F}_{\text{active}}, \{\boldsymbol{\mu}_k\}_{k=1}^K$.

// Out-of-Sample Inference for Query $\mathbf{x}^* \in \mathbb{R}^D$:

predict$(\mathbf{x}^*)$: **return** $\arg\min_k \|\mathbf{x}^*_{[\mathcal{F}_{\text{active}}]} - \boldsymbol{\mu}_k\|_2$.

component separation:

$$\frac{\Delta}{\sigma_0} > \sqrt{\frac{3 + \sqrt{15}}{2}} \approx 1.854. \tag{3}$$

Computing $\hat{b}_d$ requires only empirical second, third, and fourth moments across instances, executing in strictly $O(N \cdot D)$ time. We state the underlying assumption and failure modes of BGSS:

Assumption 1 (Marginal Multimodality Prior and Failure Modes) Informative subspace dimensions separating ground-truth clusters exhibit marginal multimodality ($\hat{b}_d \geq 5/9$), whereas nuisance distractor dimensions are continuous and unimodal ($\hat{b}_d \leq 5/9$).

Remark 1 (Failure Modes and Mathematical Boundary Conditions of BGSS) Assumption 1 encounters boundary conditions in three distinct analytical settings:

1. **Bounded Support and Extremal Kurtosis:** Under Sarle's formulation, continuous unimodal distributions do not arbitrarily inflate the bimodality coefficient: standard skewed unimodal densities retain $BC < 5/9$ (e.g., exponential distributions yield $BC \approx 0.420$, while lognormal distributions with variance parameter $\sigma^2 = 1$ yield $BC \approx 0.344$). However, bounded uniform support achieves the critical threshold $BC = 5/9 \approx 0.556$, and bounded asymmetric power-law densities (e.g., Beta$(3, 1)$ with $BC \approx 0.562$) exceed the threshold despite being strictly unimodal.
2. **Discrete Sparsity and Zero-Inflation:** In highly sparse representations (e.g., scRNA-seq counts with $\geq 90\%$ zeros), the heavy discrete point mass at zero severely inflates sample kurtosis and skewness, causing spurious threshold crossings in the absence of biological sub-populations.
3. **Non-Linear Parity and XOR Interactions:** Cluster structures governed by non-linear orthogonal parity interactions (exemplified by the Madelon benchmark, where $D = 500$ with 5 informative, 15 redundant, and 480 distractor dimensions) project to Gaussian 1D marginals with $\hat{b}_d \leq 0.504 < 5/9$, evading detection via independent marginal projections.

In the implementation, rather than applying a strict analytical cutoff $\hat{b}_d \geq 5/9$ (which may produce an empty set on parity-like benchmarks), the default pipeline sorts features by $\hat{b}_d$ and selects the top candidate pool of size $\min(D, \max(K, \lfloor \alpha \cdot D \rfloor))$ with default $\alpha = 0.15$ and minimum cap $\min(100, D)$. On Leukemia ($D = 7{,}129$), an unconstrained threshold $\hat{b}_d \geq 5/9$ isolates 1,522 genes, whereas the default capped selection rule retains $\lfloor 0.15 \times 7{,}129 \rfloor = 1{,}069$ candidate genes.

4.2 Determinacy-Based Bipartite Anchor Consensus

Classical consensus methods construct a dense $N \times N$ co-association matrix S and perform graph partitioning in $O(N^2)$ to $O(N^3)$ time and $O(N^2)$ auxiliary memory. Rather than materializing all-pairs co-association, ICC-v2 evaluates exact sample determinacy $\sigma_i = \frac{1}{N-1} \sum_{j \neq i} S_{ij}^2$ using a contingency identity.

Proposition 2 (Exact Determinacy Identity) *Let $P \in \{0, \ldots, K-1\}^{M \times N}$ denote the ensemble partition matrix. Let $C_{m_1, m_2} \in \mathbb{N}^{K \times K}$ denote the contingency matrix between base*

partitions m_1 and m_2, where $C_{m_1,m_2}(c_1,c_2)=\sum_{j=1}^{N}\mathbf{1}\{\pi_{m_1}(j)=c_1\wedge\pi_{m_2}(j)=c_2\}$. Then for every sample i, the quadratic determinacy satisfies:

$$\sum_{j=1}^{N}S_{ij}^2=\frac{1}{M^2}\sum_{m_1=1}^{M}\sum_{m_2=1}^{M}C_{m_1,m_2}(\pi_{m_1}(i),\pi_{m_2}(i)),\tag{4}$$

which computes sample determinacy $\sigma_i=\frac{1}{N-1}\left(\sum_{j=1}^{N}S_{ij}^2-1\right)$ in $O(M^2N+M^2K^2)$ time and $O(N+K^2)$ working memory, without materializing the $N\times N$ matrix S.

Given sample determinacy $\boldsymbol{\sigma}\in[0,1]^N$, ICC-v2 extracts a core anchor set $\mathcal{A}_{\text{core}}=\{a_1,\ldots,a_L\}$ of size $L\ll N$ (default $L=40$) from samples exceeding stability quantile τ_{core}. ICC-v2 then constructs a rectangular bipartite co-association matrix $B\in[0,1]^{N\times L}$ where $B_{ia}=\frac{1}{M}\sum_{m=1}^{M}\mathbf{1}\{\pi_m(\mathbf{x}_i)=\pi_m(\mathbf{x}_a)\}$ in $O(N\cdot L)$ memory.

With row-normalized $B_{\text{norm}}=D_R^{-1}B$ where $D_R=\text{diag}(B\mathbf{1}_L)\in\mathbb{R}^{N\times N}$, the anchor affinity matrix is $W_{\text{anchor}}=B_{\text{norm}}^TB_{\text{norm}}\in\mathbb{R}^{L\times L}$ with degree matrix $D_A=\text{diag}(W_{\text{anchor}}\mathbf{1}_L)\in\mathbb{R}^{L\times L}$. Solving the normalized Laplacian eigensystem $L_{\text{anchor}}V=\lambda V$ (where $L_{\text{anchor}}=I-D_A^{-1/2}W_{\text{anchor}}D_A^{-1/2}$) for the K smallest eigenvectors $V\in\mathbb{R}^{L\times K}$ yields the dual sample embedding $U=B_{\text{norm}}V$ (or Transfer-Cut embedding $U=B_{\text{norm}}D_A^{-1/2}V\,\text{diag}(\max(1-\boldsymbol{\lambda},10^{-4}))^{-1/2}$) [16, 22], followed by K-Means clustering.

Theorem 3 (Computational and Memory Complexity of Bipartite ICC-v2) *Let N be the sample size, D ambient dimensionality, M ensemble size, L anchor budget ($L\ll N$), K cluster count, and I_{km} base K-Means iterations. Under bounded anchor budgets ($L=O(1)$), the overall time complexity of ICC-v2 is:*

$$\begin{aligned}T_{ICC\text{-}v2}=O\big(&ND+D\log D+M^2N+M^2K^2+MI_{km}N|\mathcal{F}_{sub}|K\\&+MNL+NL^2+L^3+NLK+I_{km}NK^2\big),\end{aligned}\tag{5}$$

which scales linearly with sample size $O(N)$ for fixed ensemble parameters. The auxiliary working memory complexity is $O(NL+L^2)$, representing an asymptotic $O(N)$ bound that eliminates the $O(N^2)$ storage requirement of dense consensus. We separate the $O(ND)$ data storage from the $O(NL+L^2)$ auxiliary consensus graph memory.

Proof Stage 1 (BGSS) evaluates feature moments in $O(ND)$ and ranks features in $O(D\log D)$. Computing quadratic sample determinacy via the contingency identity (Proposition 2) requires $O(M^2N+M^2K^2)$ time. Stage 2 generates M base clusterings on $|\mathcal{F}_{\text{sub}}|$ features in $O(MI_{\text{km}}N|\mathcal{F}_{\text{sub}}|K)$. Stage 3 computes bipartite co-association B in $O(MNL)$, anchor inner products $B_{\text{norm}}^TB_{\text{norm}}$ in $O(NL^2)$, eigensolving on $L\times L$ in $O(L^3)$, spectral projection $U=B_{\text{norm}}V$ in $O(NLK)$, and final clustering in $O(I_{\text{km}}NK^2)$. Storing B and W_{anchor} requires $NL+L^2$ auxiliary memory words, decoupled from the $O(ND)$ raw data storage. □

4.3 Stability-Weighted Active Subspace Centroid Assignment

Unlike transductive consensus frameworks, ICC-v2 extracts geometry-calibrated centroids in the active subspace weighted by point determinacy:

$$\boldsymbol{\mu}_k = \frac{\sum_{i:y_i=k} \sigma_i \cdot \mathbf{x}_{i,[\mathcal{F}_{\text{active}}]}}{\sum_{i:y_i=k} \sigma_i}, \quad k \in \{1, \ldots, K\}. \tag{6}$$

Weighting by σ_i pulls centroids toward core exemplars and attenuates boundary noise. For any new query instance $\mathbf{x}^* \in \mathbb{R}^D$, out-of-sample cluster assignment is computed in $O(K \cdot |\mathcal{F}_{\text{active}}|)$ time:

$$y^* = \arg\min_k \|\mathbf{x}^*_{[\mathcal{F}_{\text{active}}]} - \boldsymbol{\mu}_k\|_2, \tag{7}$$

with posterior probabilities given by softmax temperature scaling: $p(y^* = k \mid \mathbf{x}^*) = \frac{\exp(-\|\mathbf{x}^*_{[\mathcal{F}_{\text{active}}]} - \boldsymbol{\mu}_k\|_2/T)}{\sum_l \exp(-\|\mathbf{x}^*_{[\mathcal{F}_{\text{active}}]} - \boldsymbol{\mu}_l\|_2/T)}$, where $T > 0$ is a user-defined scaling temperature. This avoids recomputing the consensus graph upon arrival of new observations.

4.4 Anchor-Space Perturbation Profiling (ASPP)

Anchor-Space Perturbation Profiling (ASPP) is an optional diagnostic stability framework. In standard benchmark evaluations (Table 3), ASPP is treated as an optional post-hoc diagnostic tool to preserve linear runtime.


When enabled, ASPP evaluates cluster stability with respect to certified core anchors $\mathcal{A}_{\text{core}}$ across five perturbation operators $T_{p,r}(X)$: (1) sampling dropout without replacement ($\eta \in [0.1, 0.5]$), (2) feature subspace masking, (3) Gaussian or Student-t measurement noise, (4) synthetic batch effects, and (5) algorithmic jitter. For each cluster $\mathcal{C}_k$, ASPP computes composite stability $S_{k,p} = \frac{1}{2}(\text{Retention}(k,p) + \text{Coassoc}(k,p))$, where $\text{Retention}(k,p)$ measures the Jaccard overlap of cluster k instances under perturbation p, and $\text{Coassoc}(k,p)$ evaluates the mean pairwise anchor co-association stability. The aggregate Perturbation Sensitivity Index (PSI_k) is defined as:

$$\text{PSI}_k = 1 - \frac{1}{|\mathcal{P}|} \sum_{p \in \mathcal{P}} S_{k,p}, \quad \text{PSI}_k \in [0, 1]. \tag{8}$$


For an out-of-sample query $\mathbf{x}^* \in \mathbb{R}^D$, ASPP defines an empirical confidence score:

$$\text{Conf}(\mathbf{x}^*) = \left(\frac{d_{(2)}(\mathbf{x}^*) - d_{(1)}(\mathbf{x}^*)}{\max(d_{(2)}(\mathbf{x}^*), 10^{-9})} \right) \cdot (1 - \text{PSI}_{y^*}), \tag{9}$$

where $d_{(1)}$ and $d_{(2)}$ represent Euclidean distances to the closest and second-closest active subspace centroids.



(a) Downstream Generalization with Oracle True Labels (50% Core vs 100% Full Training)



(b) Downstream Generalization with Unsupervised Pseudo-Labels ($D_{\text{noise}} \leq 3{,}000$)


Fig. 3: Inductive generalization performance on held-out test splits (20%). (a) When trained on 50% certified core points, downstream classifiers achieve parity with 100% full-data training under low-to-moderate noise ($D_{\text{noise}} \leq 50$), while under high noise ($D_{\text{noise}} \geq 1{,}000$), core-only training exhibits a 5–21 percentage point deficit. (b) Under noise corruption ($D_{\text{noise}} = 3{,}000$), training on certified core pseudo-labels yields a +4.5% nominal accuracy difference over all pseudo-labels (33.3% vs. 28.8%), though both hover near chance accuracy (33.3% for $K = 3$).

5 Experimental Evaluation

5.1 Experiment 1: Inductive Generalization

In Exp 1, we evaluated the inductive utility of the certified core $\mathcal{C}_{\text{core}}$ (distinguished from the anchor subset $\mathcal{A}_{\text{core}}$ used for bipartite graph construction) when training downstream supervised classifiers on held-out test data (20% split). As shown in Fig. 3a, classifiers trained on 50% certified core points attain performance comparable to training on 100% of the data under low-to-moderate noise ($D_{\text{noise}} \leq 50$). Under elevated noise ($D_{\text{noise}} \geq 1{,}000$), training exclusively on core points exhibits a 5–21 percentage point drop relative to full training, as the reduced sample count limits classifier capacity in noise-corrupted regimes.

Under unsupervised pseudo-labeling in high-noise regimes ($D_{\text{noise}} = 3{,}000$, Fig. 3b), training on certified core pseudo-labels yields a nominal +4.5% accuracy difference over full pseudo-label training (33.3% vs. 28.8%). However, because random



(a) Ablation Variant ARI Curves

(b) Dual-Regime Ablation Waterfall

Fig. 4: Component ablation across 6 modular variants (V0 through V5). (a) Recovery curves as distractor dimensions D_{noise} increase from 0 to 5,000. (b) Waterfall charts quantifying component impact under zero noise ($D_{\text{noise}} = 0$) and intermediate noise ($D_{\text{noise}} = 50$).

Table 2: Ablation Variant Architecture Specification

Variant	BGSS Gating	Consensus Ensemble	Anchor Graph	Core Cert.
V0 (Std Cons)	No	**Yes** (Dense)	No	No
V1 (BGSS+KMeans)	**Yes**	No (Single Model)	No	No
V2 (BGSS+StdCons)	**Yes**	**Yes** (Dense)	No	No
V3 (Anchors Only)	No	**Yes**	**Yes**	**Yes**
V4 (BGSS+RandAnc)	**Yes**	**Yes**	**Yes**	No
V5 (Full ICC-v2)	**Yes**	**Yes**	**Yes**	**Yes**

chance accuracy for $K = 3$ clusters is 33.3%, this result hovers near chance level, rendering the statistical advantage in noise-dominated regimes inconclusive without prior feature gating. **Multi-Classifier Evaluation:** We extended this inductive evaluation across four classifier paradigms: Linear Support Vector Machine, Random Forest (100 trees), Multi-Layer Perceptron (100×50), and k-Nearest Neighbors ($k = 5$). At $D_{\text{noise}} = 3{,}000$, Linear SVM yielded 33.3% vs. 28.8%, Random Forest yielded a +3.8% advantage, and MLP yielded a +4.2% advantage.

5.2 Experiment 2: Component Ablation Study

To isolate the contribution of each algorithmic component, we evaluated 6 modular variants (Table 2):

1. **Synthetic Distractor Noise Resilience (Fig. 4):** Under synthetic distractor noise ($D_{\text{noise}} \in [0, 5{,}000]$), ambient models experience distance concentration: at $D_{\text{noise}} = 50$, standard dense consensus (V0) drops to ARI = 0.359 and ambient anchor consensus (V3) to 0.411; by $D_{\text{noise}} \geq 200$, both reach ARI ≤ 0.006. In contrast, BGSS-guided architectures (V1, V2, V4, V5) maintain cluster recovery (ARI ≥ 0.94).

2. **Genomics Controls (Leukemia & SRBCT):** Evaluating Control 1 (V1: BGSS + K-Means) and Control 2 (V2: BGSS + StdConsensus) on cancer genomics indicates that marginal feature screening alone is insufficient on complex biological manifolds. On Leukemia ($N = 72, D = 7{,}129, K = 2$), BGSS filters features down to candidate genes; direct K-Means on this subspace (V1) achieves only ARI $= 0.019 \pm 0.078$, which is below unguided K-Means on the full feature space (0.101 ± 0.088). Dense consensus on the filtered subspace (V2) yields 0.032 ± 0.136. In contrast, Full ICC-v2 achieves a benchmark ARI $= \mathbf{0.680} \pm 0.345$ across the 10-seed evaluation. In ablation re-runs, certified anchors achieve 0.621 ± 0.334 (V5), with uniform random anchors achieving 0.628 ± 0.331 (V4). Similarly, on SRBCT ($N = 83, D = 2{,}308, K = 4$), V1 achieves 0.176 ± 0.191 and V2 yields 0.361 ± 0.191, whereas ICC-v2 achieves benchmark ARI $= \mathbf{0.538} \pm 0.104$ (0.614 in ablation V5, and 0.650 in V4). This indicates that the real-world performance gain arises from the combination of subspace ensembling and bipartite spectral consensus rather than marginal feature screening alone.

5.3 BGSS Feature Saliency and Interpretability Audit (Exp 2.1)

To examine whether Bimodality-Gated Subspace Selection (BGSS) isolates discriminative dimensions, we conducted an interpretability audit on benchmarks with known feature relevance (Fig. 5):

- **Madelon Benchmark ($D = 500$):** Composed of 5 informative features on a hypercube with XOR labeling, 15 redundant linear combinations, and 480 continuous distractor noise dimensions, Madelon serves as a boundary test for marginal screening. Because XOR structures exhibit zero marginal bimodality ($b_d \leq 0.504 < 0.556$ across all features), BGSS identifies features with Recall@50 of 0.400 and Precision@50 of 0.156, confirming that 1D marginal gating cannot uncover non-linear interactions without marginal separation.
- **Synthetic Manifolds ($D = 10{,}000$):** With $D_{\text{signal}} = 50$ informative dimensions obscured by 9,950 Gaussian noise features, BGSS achieves PR-AUC $= \mathbf{0.974}$.
- **Additive Noise Sensitivity:** Across additive noise standard deviations ($\sigma \in [0.0, 2.0]$), BGSS maintains Recall@50 > 0.85 across moderate noise levels (Fig. 5(c)).

5.4 Experiment 3: Real-World Multi-Domain Benchmark Suite (13 Datasets)

We evaluated ICC-v2 across 13 multi-domain high-dimensional benchmarks spanning acoustic sensing, synthetic manifolds, cancer genomics (CNS, Colon, Leukemia, Prostate, SRBCT), mass spectrometry (Ovarian), text document clustering (20 Newsgroups [29]), spoken phoneme recognition (Isolet [30]), airborne hyperspectral imaging (Indian Pines [31]), face illumination manifolds (Extended Yale B [32]), and single-cell RNA sequencing (Zheng68k [33]). Here, ICC-v1 designates the baseline architecture applying bipartite anchor consensus directly on uncalibrated ambient




Fig. 5: Bimodality-Gated Subspace Selection (BGSS) interpretability audit (Exp 2.1). (a) Precision-Recall curve on Madelon ($D = 500, D_{\text{signal}} = 20$), showing BGSS achieving PR-AUC $= 0.892$ vs. 0.354 for uncalibrated variance. (b) Synthetic manifold ($D = 10{,}000, D_{\text{signal}} = 50$), where BGSS achieves PR-AUC $= 0.974$. (c) Noise curve across additive Gaussian noise ($\sigma \in [0.0, 2.0]$).




Fig. 6: Adjusted Rand Index (ARI) [23] benchmarking across 13 multi-domain real-world datasets spanning 11 candidate algorithms (1,430 total model fits). ICC-v2 attains top performance on genomic microarrays, while deep clustering (DEC) and classical hierarchical linkage perform strongly on text and acoustic domains.




Fig. 7: Demšar Critical Difference analysis [24] across 13 multi-domain benchmarks. Across all benchmarks, deep clustering (DEC) attains the lowest omnibus mean rank ($R = 4.31$), followed by Standard Consensus ($R = 5.08$), K-Means ($R = 5.31$), Ward ($R = 5.31$), and ICC-v2 ($R = 5.46$). Under the Nemenyi test ($k = 11, N = 13, \alpha = 0.05$), the critical difference is $CD = 4.19$, indicating no statistically significant separation across the omnibus collection.

features without BGSS gating. For massive datasets, standard benchmark protocols apply pre-specified stratified subsampling for tractable multi-seed matrix evaluation: 20 Newsgroups (=2,000$subset of$,846), Extended Yale B (=1,000$subset of$,414), and Zheng68k (=700, D=765, K=10$filtered subset of$.6k scRNA-seq profiles), as indicated in Table 3. Table 3, the benchmark matrix (Fig. 6), and the Demšar critical difference diagram (Fig. 7) summarize comparative performance across 1,430 individual model fits.

Regime Analysis & Performance Profiles:

- **Small-Sample, High-Dimensional Regimes ($D/N > 20$):** In cancer microarrays and mass spectrometry assays where $D \gg N$, ICC-v2 demonstrates competitive performance. On SRBCT ($D/N = 27.8, K = 4$), ICC-v2 achieves an ARI of $\mathbf{0.538} \pm 0.110$ (an absolute increase of $+0.498$ over Standard Consensus at 0.040 ± 0.012); on Leukemia ($D/N = 99.0$), it delivers $\mathbf{0.680} \pm 0.345$ (vs. 0.173 ± 0.063 for Standard Consensus and 0.148 ± 0.060 for DEC); and on Ovarian ($D = 15{,}154$), it achieves $\mathbf{0.052} \pm 0.153$ while accelerating consensus extraction by $17.0\times$ (3.41s vs. 57.98s). Deep clustering (DEC) struggles in these small-sample regimes ($N \leq 100$), yielding lower scores (0.086 ± 0.088 on SRBCT).
- **Large-Sample, Multi-Class Regimes ($K \geq 20$):** On large benchmarks with numerous categories, such as 20 Newsgroups ($N = 18.8\text{k}, K = 20$) and Isolet ($N = 7.8\text{k}, K = 26$), classical hierarchical Ward linkage (0.114 and 0.500) and DEC (0.496) outperform ICC-v2 (0.000 and 0.286). With a default anchor budget of $L = 40$, datasets with $K \geq 20$ classes allocate fewer than two anchors per category on average, under-sampling minority subtypes.
- **Near-Zero ARI Regimes:** On CNS, Colon, Prostate, and Ovarian, all evaluated methods (including ICC-v2) achieve low ARI values (≤ 0.052), reflecting the substantial difficulty of unsupervised partition recovery on these biological datasets.

Table 3: Empirical Adjusted Rand Index (ARI) Across 13 Multi-Domain Benchmarks (1,430 Model Fits, Mean ± Standard Deviation Across 10 Random Seeds)

	Part I: Classical and Early Ensemble Baselines			
Dataset (N, D, K)	**K-Means** [25, 26]	**Ward** [27]	**Spectral** [7]	**FCM** [28]
CNS $(60, 7.1\text{k}, 2)$	-0.027 ± 0.022	-0.022 ± 0.000	-0.004 ± 0.000	$+0.002 \pm 0.000$
Colon $(62, 2.0\text{k}, 2)$	$+0.032 \pm 0.057$	-0.016 ± 0.000	-0.023 ± 0.000	$+0.018 \pm 0.033$
Indian Pines $(10.2\text{k}, 200, 16)$	$+0.211 \pm 0.007$	$+0.223 \pm 0.007$	$\mathbf{+0.229 \pm 0.001}$	$+0.171 \pm 0.012$
Isolet $(7.8\text{k}, 617, 26)$	$+0.449 \pm 0.025$	$\mathbf{+0.500 \pm 0.004}$	$+0.417 \pm 0.000$	$+0.059 \pm 0.000$
Leukemia $(72, 7.1\text{k}, 2)$	$+0.101 \pm 0.088$	$+0.082 \pm 0.000$	$+0.139 \pm 0.000$	$+0.103 \pm 0.008$
Madelon $(500, 500, 2)$	$+0.034 \pm 0.020$	$+0.008 \pm 0.003$	$\mathbf{+0.038 \pm 0.000}$	$+0.018 \pm 0.014$
20 Newsgroups $(18.8\text{k}, 10\text{k}, 20)$	$+0.041 \pm 0.051$	$\mathbf{+0.114 \pm 0.012}$	$+0.000 \pm 0.000$	$+0.006 \pm 0.000$
Ovarian $(253, 15.1\text{k}, 2)$	$+0.008 \pm 0.005$	$+0.011 \pm 0.000$	$+0.019 \pm 0.001$	$+0.001 \pm 0.001$
Prostate $(102, 12.6\text{k}, 2)$	$+0.046 \pm 0.004$	$+0.026 \pm 0.000$	-0.003 ± 0.000	$+0.048 \pm 0.000$
Sonar $(208, 60, 2)$	$+0.005 \pm 0.011$	-0.001 ± 0.000	-0.005 ± 0.000	$\mathbf{+0.025 \pm 0.020}$
SRBCT $(83, 2.3\text{k}, 4)$	$+0.141 \pm 0.056$	$+0.109 \pm 0.000$	$+0.080 \pm 0.000$	$+0.102 \pm 0.019$
Yale B $(2.4\text{k}, 1.0\text{k}, 38)$	$+0.017 \pm 0.002$	$+0.049 \pm 0.000$	$+0.066 \pm 0.001$	-0.001 ± 0.000
Zheng68k $(68.6\text{k}, 2\text{k}, 11)$	$+0.483 \pm 0.095$	$+0.495 \pm 0.000$	$+0.413 \pm 0.001$	$+0.370 \pm 0.049$
Grand Mean ARI	0.119	0.121	0.105	0.071
Mean Rank (All 13)	5.31	5.31	6.54	6.92
Mean Rank ($D/N > 20$ Subgroup)	5.83	6.83	7.50	5.67
	Part II: Modern, Anchor, and Proposed Consensus Methods			
Dataset (N, D, K)	**DEC**	**FCAG**	**FastMVC**	**ICC-v1**
CNS $(60, 7.1\text{k}, 2)$	$+0.012 \pm 0.018$	-0.004 ± 0.000	$+0.007 \pm 0.006$	-0.007 ± 0.026
Colon $(62, 2.0\text{k}, 2)$	$\mathbf{+0.038 \pm 0.067}$	-0.016 ± 0.000	-0.016 ± 0.001	-0.000 ± 0.010
Indian Pines $(10.2\text{k}, 200, 16)$	$+0.207 \pm 0.009$	$+0.200 \pm 0.009$	$+0.198 \pm 0.009$	$+0.129 \pm 0.024$
Isolet $(7.8\text{k}, 617, 26)$	$+0.496 \pm 0.028$	$+0.433 \pm 0.025$	$+0.433 \pm 0.026$	$+0.367 \pm 0.024$
Leukemia $(72, 7.1\text{k}, 2)$	$+0.148 \pm 0.060$	$+0.323 \pm 0.000$	$+0.182 \pm 0.156$	$+0.133 \pm 0.078$
Madelon $(500, 500, 2)$	$+0.019 \pm 0.015$	$+0.000 \pm 0.000$	$+0.000 \pm 0.000$	$+0.031 \pm 0.006$
20 Newsgroups $(18.8\text{k}, 10\text{k}, 20)$	$+0.008 \pm 0.004$	$+0.045 \pm 0.010$	$+0.001 \pm 0.000$	$+0.059 \pm 0.005$
Ovarian $(253, 15.1\text{k}, 2)$	$+0.005 \pm 0.006$	-0.011 ± 0.007	-0.011 ± 0.007	$+0.017 \pm 0.009$
Prostate $(102, 12.6\text{k}, 2)$	$+0.014 \pm 0.007$	$+0.004 \pm 0.001$	$+0.001 \pm 0.001$	$+0.018 \pm 0.018$
Sonar $(208, 60, 2)$	$+0.016 \pm 0.022$	-0.004 ± 0.000	-0.003 ± 0.003	$+0.006 \pm 0.005$
SRBCT $(83, 2.3\text{k}, 4)$	$+0.086 \pm 0.088$	$+0.094 \pm 0.000$	$+0.150 \pm 0.060$	$+0.110 \pm 0.033$
Yale B $(2.4\text{k}, 1.0\text{k}, 38)$	$\mathbf{+0.131 \pm 0.014}$	$+0.041 \pm 0.003$	$+0.040 \pm 0.003$	$+0.007 \pm 0.003$
Zheng68k $(68.6\text{k}, 2\text{k}, 11)$	$+0.520 \pm 0.068$	$+0.352 \pm 0.105$	$+0.459 \pm 0.062$	$+0.484 \pm 0.063$
Grand Mean ARI	0.131	0.112	0.111	0.104
Mean Rank (All 13)	**4.31**	7.38	6.92	5.92
Mean Rank ($D/N > 20$ Subgroup)	5.00	7.17	6.17	5.33

Statistical Significance Analysis: Across the 13 benchmarks, Friedman omnibus testing [24] yields $\chi_F^2 = 11.34$, $p = 0.33$, indicating no statistically significant difference across the omnibus collection. Statistical comparisons were evaluated using the Demšar Critical Difference framework (Fig. 7). Under the two-tailed post-hoc Nemenyi test ($\alpha = 0.05, k = 11, N = 13$), the critical difference threshold is:

$$CD = q_\alpha \sqrt{\frac{k(k+1)}{6N}} = 3.219 \sqrt{\frac{11 \times 12}{6 \times 13}} = 4.19. \tag{10}$$

DEC ($R = 4.31$), Standard Consensus ($R = 5.08$), K-Means ($R = 5.31$), Ward ($R = 5.31$), and ICC-v2 ($R = 5.46$) occupy the top five ranks without statistically significant separation across the omnibus collection.

On the pre-specified high-dimensional biomedical subgroup ($D/N > 20$, comprising $N = 6$ datasets: CNS, Colon, Leukemia, Ovarian, Prostate, SRBCT), ICC-v2 attains mean rank $R = 2.33$ compared to $R = 5.00$ for DEC, $R = 6.33$ for Standard Consensus, $R = 5.83$ for K-Means, and $R = 7.83$ for Li et al., with a subgroup mean ARI of 0.238 and median ARI of 0.057. However, for $N = 6$ datasets, the Nemenyi threshold is $CD = 6.16$. Pairwise Wilcoxon tests [34] between ICC-v2 and baselines on this subgroup yield unadjusted $p = 0.031$ against FCAG, FastMVC, Li et al., and Spectral, but after Holm step-down adjustment across 10 baselines, the adjusted values are $p_{\text{adj}} \geq 0.3125$. Therefore, the subgroup ranking ($R = 2.33$) should be interpreted as exploratory and post-hoc.

Across all 1,430 model fits, ICC-v2 attains the highest Grand Mean ARI of **0.160** (compared to 0.131 for DEC, 0.127 for Standard Consensus, 0.121 for Ward, and 0.119 for K-Means), driven by performance gains on Leukemia and SRBCT.

5.5 Experiment 4: Computational Scalability, Sensitivity & Anchor Fidelity

To evaluate the complexity bounds of Theorem 3, Experiment 4 examined empirical scaling, hyperparameter sensitivity (Fig. 9), and anchor approximation fidelity (Fig. 8):

- **Measured Peak Memory:** In contrast to standard consensus which measured 1,709.6 MB peak process RSS at $N = 8{,}000$, ICC-v2 measured 1,040.5 MB (Fig. 9a), representing a 39.1% **measured peak memory reduction**. We note that a theoretical dense float64 matrix at $N = 8{,}000$ requires 512 MB, and measured process RSS includes Python runtime overhead and base model memory.
- **High-Dimensional Scaling:** Under $D = 20{,}000$, BGSS subspace gating reduces pairwise distance evaluation time from 1.523s to 0.964s (Fig. 9b), an acceleration of 36.7%.
- **Ensemble Size Tradeoff:** Consensus quality plateaus between $M = 25$ and $M = 50$ (Fig. 9c), with 95% of peak ARI achieved by $M = 25$.
- **Stability Landscape:** Grid searches over (L, τ_{core}) indicate a parameter plateau (ARI ≥ 0.85, Fig. 9d) across $\tau_{\text{core}} \in [0.4, 0.7]$.
- **Anchor Fidelity Tradeoff (Exp 4.3):** Evaluating ICC-v2-Reduced ($O(NL)$ bipartite anchor graph, $L = 40$) versus ICC-v2-Exact ($O(N^2)$ dense co-association) across 30 empirical trials ($N \in [200, 10{,}000]$) indicates that the fidelity gap $|\Delta\text{ARI}|$ exceeds 0.05 at intermediate sample sizes ($N \in [1{,}000, 5{,}000]$, Fig. 8(b)). At $N = 5{,}000$, Reduced scores 0.618 vs. 0.583 for Exact. At $N = 10{,}000$, Reduced requires 1.34s vs. 29.91s for Exact (22.4× speedup) and reduces auxiliary graph memory from 1,529.8 MB to 45.8 MB (97.0% **memory reduction**).





Fig. 8: Anchor graph approximation fidelity and computational complexity tradeoff (Exp 4.3). (a) Empirical ARI comparison between exact $O(N^2)$ consensus and reduced $O(NL)$ bipartite anchor consensus ($L = 40$) across sample sizes $N \in [200, 10{,}000]$. (b) Absolute fidelity gap $|\Delta\text{ARI}|$, showing divergence exceeding 0.05 at intermediate sample sizes. (c) Runtime scaling achieving an acceleration at $N = 10{,}000$ (1.34s vs. 29.91s). (d) Peak RAM scaling showing memory reduction at $N = 10{,}000$ (45.8 MB vs. 1,529.8 MB).

5.6 Experiment 5: Scalability & Stress Audits


1. Scalability Assessment: Evaluating ICC-v2 on large synthetic manifolds (Fig. 10) indicates linear empirical scaling: on $N = 1{,}000{,}000$ instances ($D = 100, K = 5$), where dense consensus requires $\approx$ 8 TB RAM, ICC-v2 completes in 55.6**s** with 3.05 **GB peak RAM** (ARI = 0.382 vs. 0.150 for MiniBatchKMeans, with overlapping confidence intervals at intermediate scales as shown in Fig. 10(d)). In high feature spaces ($D = 100{,}000, N = 1{,}000$), ICC-v2 executes in 8.28**s**.

2. Missing Data Audit (Exp 3.5): We evaluated ICC-v2 under Missing Completely At Random (MCAR) rates $\rho \in \{0.0, 0.10, 0.20, 0.30, 0.50, 0.70\}$ spanning Colon, Leukemia, and SRBCT across Mean, Median, k-Nearest Neighbors ($k = 5$), and Zero imputation (Fig. 11). On SRBCT, partition fidelity decreases as missingness increases, retaining ARI > 0.40 up to $\rho = 0.50$ under KNN imputation, while baseline methods drop below 0.10. On Colon and Leukemia, degradation is more rapid, reflecting domain-specific feature dependencies.


3. Cluster Count Misspecification (Exp 4.2): We evaluated model fits across Synthetic ($K_{\text{true}} = 3$), Sonar ($K_{\text{true}} = 2$), and SRBCT ($K_{\text{true}} = 4$) sweeping $K_{\text{input}} \in [2, 9]$. When $K_{\text{input}} > K_{\text{true}}$, partition recovery degrades: on Synthetic ($K_{\text{true}} = 3$), single K-Means drops from 0.98 at $K = 3$ to 0.41 at $K = 6$ and 0.23 at $K = 9$,



(a) Sample Complexity Scaling ($N \in [200, 8{,}000]$)



(b) Dimension Scaling ($D \in [100, 20{,}000]$) (c) Ensemble Size Plateau ($M \in [5, 100]$)



(d) Hyperparameter Stability Landscape (L, τ_{core})

Fig. 9: Scalability laws and hyperparameter sensitivity maps. (a) Memory consumption scales with $O(NL)$, showing a 39.1% peak RAM reduction at $N = 8{,}000$. (b) BGSS subspace gating yields a 36.7% runtime speedup at $D = 20{,}000$. (c) Consensus quality plateaus between $M = 25$ and 50. (d) Stability contour maps across (L, τ_{core}).

whereas ICC-v2 maintains ARI ≥ 0.72. On SRBCT, ICC-v2 maintains ARI > 0.40 up to $K = 9$.

5.7 Limitations

We document several explicit limitations of the proposed framework:

1. **Large Cluster Counts ($K \geq 20$):** With a fixed anchor budget of $L = 40$, datasets containing $K \geq 20$ clusters (e.g., 20 Newsgroups with $K = 20$ and Isolet with $K = 26$) allocate fewer than two anchors per cluster on average. This






Fig. 10: Scalability evaluation up to N = 1,000,000 instances and D = 100,000 dimensions (Exp 5). (a) Linear execution time scaling across sample sizes up to N = 1,000,000, completing in 55.6s. (b) Memory consumption scaling, requiring 3.05 GB peak RAM at N = 1,000,000. (c) High-dimensional runtime scaling up to D = 100,000 at N = 1,000 completing in 8.28s. (d) Partition recovery (ARI) as sample scale expands, showing performance relative to MiniBatchKMeans with overlapping error intervals.



(a) Missing Data Partition Degradation Curves ($\rho \in [0.0, 0.70]$)



(b) Imputation Strategy Heatmap

Fig. 11: Missing data robustness audit across 3,600 experimental conditions (Exp 3.5). (a) Partition stability (ARI) degradation curves as Missing Completely At Random (MCAR) dropout rate ρ increases from 0.0 to 0.70 across Colon, Leukemia, and SRBCT. (b) Relative ARI preservation across Mean, Median, KNN ($k = 5$), and Zero imputation strategies.

leads to under-sampling of minority clusters unless L is dynamically scaled (e.g., $L = \max(40, 10K)$) with stratified sampling.

2. **Sparse, Zero-Inflated, and Non-Linear Features:** BGSS evaluates marginal moments independently. Features with heavy point masses at zero (e.g., single-cell

RNA counts or sparse TF-IDF text features) or non-linear multi-feature interactions (e.g., XOR parity structures) can either spuriously inflate Sarleś Bimodality Coefficient or fail to manifest marginal bimodality, requiring multi-dimensional interaction screening in future architectures.

3. **Non-Linear Parity Interactions:** As demonstrated on Madelon, marginal 1D screening cannot detect feature interactions without marginal separation.
4. **Known Cluster Count K:** ICC-v2 assumes the number of clusters K is provided *a priori* and does not perform automated model order selection.
5. **Small Sample Size Variance:** For small sample sizes ($N < 30$), sample third and fourth moments have high statistical variance, which can impair feature ranking.
6. **Baseline Comparison Scope:** In the primary benchmark (Table 3), competing baselines were evaluated on the full ambient feature set without dedicated upstream feature selection.
7. **Sample Requirements for Deep Clustering:** Deep clustering (DEC) underperforms on small sample regimes ($N \leq 100$) due to insufficient training data for autoencoder representations.
8. **Near-Zero ARI Regimes:** On CNS, Colon, Prostate, and Ovarian, all evaluated methods achieve low ARI (≤ 0.052), indicating unresolved clustering challenges on these benchmarks.

6 Conclusion

This paper investigated Inductive Consensus Clustering (ICC), addressing the transductive formulation and noise vulnerability of classical cluster ensembles. Through empirical falsification, we showed that standard consensus stability can degrade under high-dimensional isotropic noise. The proposed ICC-v2 framework integrates Bimodality-Gated Subspace Selection (BGSS), determinacy-based bipartite anchor consensus, and stability-weighted centroid projection. Across 13 multi-domain benchmarks (1,430 model fits), DEC achieves the lowest omnibus mean rank ($R = 4.31$), with ICC-v2 ranking fifth ($R = 5.46$). ICC-v2 achieves the highest Grand Mean ARI of 0.160 and attains mean rank $R = 2.33$ on the exploratory high-dimensional biomedical subgroup ($D/N > 20$, with an absolute ARI improvement of +0.388 over the strongest baseline, FastMVC, on SRBCT), while reducing auxiliary consensus memory by 97.0% at $N = 10{,}000$ and executing up to $N = 1{,}000{,}000$ instances in 55.6s. Future work will explore automated anchor budget scaling and non-linear feature interaction screening.

Supplementary information. Supplementary data, extended sensitivity heatmaps, and ablation logs are provided in the reproducibility repository.

Acknowledgements. The authors thank the Department of Computer Science and Engineering, Techno India University, for computational infrastructure support.

Declarations

- **Funding:** No specific external grant funding was received for this study.

- **Conflict of interest/Competing interests:** The authors declare that they have no competing financial or non-financial interests directly or indirectly related to the work submitted for publication.
- **Ethics approval and consent to participate:** Not applicable. This study analyzes publicly available benchmark datasets and synthetic benchmark simulations involving no human subjects or animal experiments.
- **Consent for publication:** All authors reviewed and approved the final manuscript for submission.
- **Data availability:** All real-world benchmark datasets utilized in this study (CNS, Colon, Indian Pines, Isolet, Leukemia, Madelon, 20 Newsgroups, Ovarian, Prostate, Sonar, SRBCT, Extended Yale B, Zheng68k) are publicly accessible. Preprocessed benchmark arrays are mirrored at: https://github.com/AkashKundu114/icc-clustering (release tag `v2.0.0`).
- **Materials availability:** Not applicable.
- **Code availability:** The complete, fully reproducible Python implementation of ICC-v2, benchmark harnesses, validation scripts, and figure generation routines are released under the MIT License at: https://github.com/AkashKundu114/icc-clustering (release tag `v2.0.0`).
- **Author contribution:** A. Kundu conceived the framework, derived theoretical properties, implemented algorithms, performed empirical analyses, and drafted the manuscript. T. Guha, R. Ghatak, and A. Naskar designed baseline pipelines, contributed to computational scaling experiments, and validated code integrity. K. K. Das supervised the research, reviewed statistical methodologies, and edited the manuscript.
- **Use of Artificial Intelligence Disclosure:** In accordance with Springer Nature Editorial Policies regarding generative AI and large language models, the authors disclose that an AI coding assistant was used during the preparation of this work solely to assist with code optimization and automated grammar and syntax checks. No AI tools were used for the conception of research hypotheses, mathematical derivations, experimental designs, empirical analyses, scientific conclusions, or manuscript drafting. All intellectual work and manuscript content were produced and verified exclusively by the authors.

References

[1] Xie, J., Girshick, R., Farhadi, A.: Unsupervised deep embedding for clustering analysis. In: Proceedings of the 33rd International Conference on Machine Learning (ICML), pp. 478–487 (2016)

[2] Strehl, A., Ghosh, J.: Cluster ensembles—a knowledge reuse framework for combining multiple partitions. Journal of Machine Learning Research **3**, 583–617 (2002) https://doi.org/10.1162/153244303321897735

[3] Fred, A.L.N., Jain, A.K.: Combining multiple clusterings using evidence accumulation. IEEE Transactions on Pattern Analysis and Machine Intelligence **27**(6), 835–850 (2005) https://doi.org/10.1109/TPAMI.2005.113

[4] Topchy, A.P., Jain, A.K., Punch, W.F.: Clustering ensembles: Models of consensus and weak partitions. IEEE Transactions on Pattern Analysis and Machine Intelligence **27**(12), 1866–1881 (2005) https://doi.org/10.1109/TPAMI.2005.237

[5] Fern, X.Z., Brodley, C.E.: Solving cluster ensemble problems by bipartite graph partitioning. In: Proceedings of the Twenty-First International Conference on Machine Learning (ICML), pp. 36–43 (2004). https://doi.org/10.1145/1015330.1015414

[6] Fern, X.Z., Brodley, C.E.: Random projection for high dimensional data clustering: A cluster ensemble approach. In: Proceedings of the Twentieth International Conference on Machine Learning (ICML), pp. 186–193 (2003)

[7] von Luxburg, U.: A tutorial on spectral clustering. Statistics and Computing **17**(4), 395–416 (2007) https://doi.org/10.1007/s11222-007-9033-z

[8] Li, X., Zhang, H., Zhang, R.: Robust spectral ensemble clustering via determinacy core matrix decomposition. IEEE Transactions on Knowledge and Data Engineering **31**(8), 1540–1553 (2019) https://doi.org/10.1109/TKDE.2018.2866440

[9] Huang, D., Lai, J.-H., Wang, C.-D.: Robust ensemble clustering using probability trajectories. IEEE Transactions on Knowledge and Data Engineering **28**(5), 1314–1326 (2016) https://doi.org/10.1109/TKDE.2015.2503754

[10] Liu, H., Wang, T., Fu, Y.: Consensus clustering via dense subgraph discovery. IEEE Transactions on Knowledge and Data Engineering **30**(10), 1977–1989 (2018) https://doi.org/10.1109/TKDE.2017.2785795

[11] Beyer, K., Goldstein, J., Ramakrishnan, R., Shaft, U.: When is "nearest neighbor" meaningful? In: Proceedings of the International Conference on Database Theory (ICDT), pp. 217–235. Springer, Berlin, Heidelberg (1999). https://doi.org/10.1007/3-540-49257-7_15

[12] Sarle, W.S.: The Cubic Clustering Criterion. SAS Institute Inc., Cary, NC (1983). SAS Institute Inc.. SAS Technical Report A-108

[13] Ellison, A.M.: Effect of seed dimorphism on the density-dependent dynamics of experimental populations of Atriplex triangularis (Chenopodiaceae). American Journal of Botany **74**(8), 1280–1288 (1987) https://doi.org/10.1002/j.1537-2197.1987.tb08741.x

[14] Pfister, R., Schwarz, K.A., Janczyk, M., Dale, R., Freeman, J.B.: Good things peak in pairs: A note on the bimodality coefficient. Frontiers in Psychology **4**, 700 (2013) https://doi.org/10.3389/fpsyg.2013.00700

[15] Zhang, H., Huang, S., Li, X.: Clustering ensemble via diffusion on adaptive multiplex networks. IEEE Transactions on Knowledge and Data Engineering **36**(10),

5432–5445 (2024) https://doi.org/10.1109/TKDE.2024.3396752

[16] Nie, F., Xue, J., Yu, D., Li, X.: Fast clustering with anchor guidance. IEEE Transactions on Pattern Analysis and Machine Intelligence **46**(5), 3177–3190 (2024) https://doi.org/10.1109/TPAMI.2023.3318603

[17] Huang, D., Wang, C.-D., Lai, J.-H.: Fast multi-view clustering via ensembles: Towards scalability, superiority, and simplicity. IEEE Transactions on Knowledge and Data Engineering **35**(10), 10185–10198 (2023) https://doi.org/10.1109/TKDE.2023.3236698

[18] Huang, D., Wang, C.-D., Li, R.-H., Lai, J.-H.: Ultra-scalable spectral clustering and ensemble clustering. IEEE Transactions on Knowledge and Data Engineering **32**(6), 1212–1226 (2020) https://doi.org/10.1109/TKDE.2019.2903410

[19] Bengio, Y., Paiement, J.-F., Vincent, P., Delalleau, O., Roux, N.L., Ouimet, M.: Out-of-sample extensions for LLE, Isomap, MDS, eigenmaps, and spectral clustering. In: Advances in Neural Information Processing Systems (NeurIPS), vol. 16, pp. 177–184 (2004)

[20] Witten, D.M., Tibshirani, R.: A framework for feature selection in clustering. Journal of the American Statistical Association **105**(490), 713–726 (2010) https://doi.org/10.1198/jasa.2010.tm09415

[21] Hartigan, J.A., Hartigan, P.M.: The dip test of unimodality. The Annals of Statistics **13**(1), 70–84 (1985) https://doi.org/10.1214/aos/1176346585

[22] Li, Y., Yang, M., Xu, Z.: A transfer cut approach for cluster ensemble. IEEE Transactions on Knowledge and Data Engineering **27**(12), 3214–3226 (2015) https://doi.org/10.1109/TKDE.2015.2443779

[23] Hubert, L., Arabie, P.: Comparing partitions. Journal of Classification **2**(1), 193–218 (1985) https://doi.org/10.1007/BF01908075

[24] Demšar, J.: Statistical comparisons of classifiers over multiple data sets. Journal of Machine Learning Research **7**, 1–30 (2006)

[25] MacQueen, J.: Some methods for classification and analysis of multivariate observations. In: Proceedings of the Fifth Berkeley Symposium on Mathematical Statistics and Probability, vol. 1, pp. 281–297 (1967)

[26] Arthur, D., Vassilvitskii, S.: k-means++: The advantages of careful seeding. In: Proceedings of the Eighteenth Annual ACM-SIAM Symposium on Discrete Algorithms (SODA), pp. 1027–1035 (2007)

[27] Ward, J.H.: Hierarchical grouping to optimize an objective function. Journal of the American Statistical Association **58**(301), 236–244 (1963) https://doi.org/

10.1080/01621459.1963.10500845

[28] Bezdek, J.C.: Pattern Recognition with Fuzzy Objective Function Algorithms. Plenum Press, New York (1981)

[29] Lang, K.: Newsweeder: Learning to filter netnews. In: Proceedings of the Twelfth International Conference on Machine Learning (ICML), pp. 331–339 (1995)

[30] Fanty, M., Cole, R.: Spoken letter recognition. In: Advances in Neural Information Processing Systems (NIPS), vol. 3, pp. 433–440 (1990)

[31] Baumgardner, M.F., Biehl, L.L., Landgrebe, D.A.: 220 band AVIRIS hyperspectral image data set: June 12, 1992 Indian Pine test site 3. Technical Report 091192, Purdue University Laboratory for Applications of Remote Sensing (LARS) (1992)

[32] Georghiades, A.S., Belhumeur, P.N., Kriegman, D.J.: From few to many: Illumination cone models for face recognition under variable lighting and pose. IEEE Transactions on Pattern Analysis and Machine Intelligence **23**(6), 643–660 (2001) https://doi.org/10.1109/34.927464

[33] Zheng, G.X.Y., Terry, J.M., Belgrader, P., *et al.*: Massively parallel digital transcriptional profiling of single cells. Nature Communications **8**(1), 14049 (2017) https://doi.org/10.1038/ncomms14049

[34] Wilcoxon, F.: Individual comparisons by ranking methods. Biometrics Bulletin **1**(6), 80–83 (1945) https://doi.org/10.2307/3001968