

**Address.java**

```
package com.example.demo;

public class Address {
    private String city;
    private String state;
    private String country;
    public String getCity()
    {
        return city;
    }
    public void setCity(String city)
    {
        this.city = city;
    }
    public String getState()
    {
        return state;
    }
    public void setState(String state)
    {
        this.state = state;
    }
    public String getCountry()
    {
        return country;
    }
    public void setCountry(String country)
    {
        this.country = country;
    }
}
```

```
    }

    public String toString()
    {
        return city+" "+state+" "+country;
    }
}
```

### **Employee.java**

```
package com.example.demo;

public class Employee {
    private int id;
    private String name;
    private Address address;
    public int getId()
    {
        return id;
    }
    public void setId(int id)
    {
        this.id = id;
    }
    public String getName()
    {
        return name;
    }
    public void setName(String name)
    {

```

```
        this.name = name;
    }
    public Address getAddress()
    {
        return address;
    }
    public void setAddress(Address address)
    {
        this.address = address;
    }
    public String toString()
    {
        return id+" "+name+" "+address;
    }
}
```

### **PdApplication.java**

```
package com.example.demo;
import org.springframework.boot.SpringApplication;
import org.springframework.boot.autoconfigure.SpringBootApplication;
import org.springframework.context.support.ClassPathXmlApplicationContext;
```

```
@SpringBootApplication
```



```
public class PdApplication
```


```
{
    public static void main(String[] args)
    {
```

```
        //SpringApplication.run(Pd1Application.class, args);
        ClassPathXmlApplicationContext context=new
ClassPathXmlApplicationContext("emp.xml");
        System.out.println(context.getBean("e1"));
    }
}
```

## Emp.xml

```
<?xml version="1.0" encoding="UTF-8"?>
<beans xmlns="http://www.springframework.org/schema/beans"
    xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
    xsi:schemaLocation="
        http://www.springframework.org/schema/beans
        http://www.springframework.org/schema/beans/spring-beans.xsd">
    <bean id="a1" class="com.example.demo.Address">
        <property name="city" value="Bengaluru"/>
        <property name="state" value="Karnataka"/>
        <property name="country" value="INDIA"/>
    </bean>
    <bean id="e1" class="com.example.demo.Employee">
        <property name="id" value="30"/>
        <property name="name" value="Tom"/>
        <property name="address" ref="a1"/>
    </bean>
</beans>
```






The screenshot shows the Eclipse IDE with the 'Address.java' file open. The Project Explorer on the left shows a project structure with 'src/main/java/com/example/demo' containing 'Address.java', 'Employee.java', and 'PdApplication.java'. The main editor displays the following Java code:

```
1 package com.example.demo;
2
3 public class Address {
4     private String city;
5     private String state;
6     private String country;
7
8     public String getCity() {
9         return city;
10    }
11    public void setCity(String city) {
12        this.city = city;
13    }
14    public String getState() {
15        return state;
16    }
17    public void setState(String state) {
18        this.state = state;
19    }
20    public String getCountry() {
21        return country;
22    }
23    public void setCountry(String country) {
24        this.country = country;
25    }
26
27    public String toString()
28    {
29        return city+" "+state+" "+country;
30    }
31 }
32
```


The status bar at the bottom shows '24°C Mostly clear', a search bar, and system icons for Windows, taskbar, and date/time (21:13 09-10-2023).




The screenshot shows the Eclipse IDE with the 'Employee.java' file open. The Project Explorer on the left shows the same project structure as the previous screenshot, with 'Employee.java' selected. The main editor displays the following Java code:

```
1 package com.example.demo;
2
3 public class Employee {
4     private int id;
5     private String name;
6     private Address address;
7
8     public int getId() {
9         return id;
10    }
11    public void setId(int id) {
12        this.id = id;
13    }
14    public String getName() {
15        return name;
16    }
17    public void setName(String name) {
18        this.name = name;
19    }
20    public Address getAddress() {
21        return address;
22    }
23    public void setAddress(Address address) {
24        this.address = address;
25    }
26
27
28    public String toString()
29    {
30        return id+" "+name+" "+address;
31    }
32 }
```


The status bar at the bottom shows '24°C Mostly clear', a search bar, and system icons for Windows, taskbar, and date/time (21:13 09-10-2023).



```
1 package com.example.demo;
2
3 import org.springframework.boot.SpringApplication;
4
5 @SpringBootApplication
6 public class PdApplication {
7
8     public static void main(String[] args) {
9         //SpringApplication.run(PdApplication.class, args);
10
11         ClassPathXmlApplicationContext context=new ClassPathXmlApplicationContext("emp.xml");
12
13         System.out.println(context.getBean("e1"));
14
15     }
16 }
17
18
19
20
21
22
```



```
1 http://www.springframework.org/schema/beans/spring-beans.xsd (xsi:schemaLocation)
2 <?xml version="1.0" encoding="UTF-8"?>
3 <beans xmlns="http://www.springframework.org/schema/beans"
4       xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
5       xsi:schemaLocation="
6           http://www.springframework.org/schema/beans http://www.springframework.org/schema/beans/spring-beans.xsd">
7     <bean id="a1" class="com.example.demo.Address">
8         <property name="city" value="Bengaluru"/>
9         <property name="state" value="Karnataka"/>
10        <property name="country" value="INDIA"/>
11    </bean>
12
13    <bean id="e1" class="com.example.demo.Employee">
14        <property name="id" value="30"/>
15        <property name="name" value="Tom"/>
16        <property name="address" ref="a1"/>
17    </bean>
18
19
20 </beans>
```

**Output:-**A screenshot of the Eclipse IDE interface. The title bar reads 'eclipse-workspace - PD/src/main/resources/emp.xml - Eclipse IDE'. The menu bar includes File, Edit, Source, Navigate, Search, Project, Run, Design, Window, and Help. The toolbar contains various icons for file operations and development. The 'Console' tab is active, showing the output of a Java application. The output text is: '<terminated> PD - PdApplication [Spring Boot App] C:\Program Files\Java\jdk-17\bin\javaw.exe (09-Oct-2023, 9:30 Tom Bengaluru Karnataka INDIA'.

```
<terminated> PD - PdApplication [Spring Boot App] C:\Program Files\Java\jdk-17\bin\javaw.exe (09-Oct-2023, 9:30 Tom Bengaluru Karnataka INDIA
```