



[Tutorials](#) [Questions](#) [Learning Paths](#) [For Businesses](#) [For Developers](#) [Social Impact](#)



## RELATED

How To Install nginx on CentOS 6 with yum

[View](#)

How To Install nginx on Ubuntu 12.04 LTS (Precise Pangolin)

[View](#)

// Tutorial //

# How To Set Up Nginx Load Balancing

This site uses cookies and related technologies, as described in our [privacy policy](#), for purposes that may include site operation, analytics, enhanced user experience, or advertising. You may choose to consent to our use of these technologies, or manage your own preferences.

MANAGE CHOICES

AGREE & PROCEED



By [Etel Sverdlov](#)



## About Load Balancing

Loadbalancing is a useful mechanism to distribute incoming traffic around several capable Virtual Private

This site uses cookies and related technologies, as described in our [privacy policy](#), for purposes that may include site operation, analytics, enhanced user experience, or advertising. You may choose to consent to our use of these technologies, or manage your own preferences.

# Setup

The steps in this tutorial require the user to have root privileges on your VPS. You can see how to set that up in the [Users Tutorial](#).

Prior to setting up nginx loadbalancing, you should have nginx installed on your VPS. You can install it quickly with apt-get:

```
sudo apt-get install nginx
```

## Upstream Module

In order to set up a round robin load balancer, we will need to use the nginx upstream module. We will incorporate the configuration into the nginx settings.

Go ahead and open up your website's configuration (in my examples I will just work off of the generic default virtual host):

```
sudo nano /etc/nginx/sites-available/default
```

We need to add the load balancing configuration to the file.

First we need to include the upstream module which looks like this:

This site uses cookies and related technologies, as described in our [privacy policy](#), for purposes that may include site operation, analytics, enhanced user experience, or advertising. You may choose to consent to our use of these technologies, or manage your own preferences.

```
server { location / { proxy_pass http://backend; } }
```

Restart nginx:

```
sudo service nginx restart
```

As long as you have all of the virtual private servers in place you should now find that the load balancer will begin to distribute the visitors to the linked servers equally.

## Directives

The previous section covered how to equally distribute load across several virtual servers. However, there are many reasons why this may not be the most efficient way to work with data. There are several directives that we can use to direct site visitors more effectively.

### Weight

One way to begin to allocate users to servers with more precision is to allocate specific weight to certain machines. Nginx allows us to assign a number specifying the proportion of traffic that should be directed to each server.

A load balanced setup that included server weight could look like this:

```
upstream backend { server backend1 example.com weight=1; server backend2 example.com weight=2;
```

This site uses cookies and related technologies, as described in our [privacy policy](#), for purposes that may include site operation, analytics, enhanced user experience, or advertising. You may choose to consent to our use of these technologies, or manage your own preferences.

## Hash

IP hash allows servers to respond to clients according to their IP address, sending visitors back to the same VPS each time they visit (unless that server is down). If a server is known to be inactive, it should be marked as down. All IPs that were supposed to be routed to the down server are then directed to an alternate one.

The configuration below provides an example:

```
upstream backend { ip_hash; server backend1.example.com; server backend2.example.com; server backend3.example.com down; }
```

## Max Fails

According to the default round robin settings, nginx will continue to send data to the virtual private servers, even if the servers are not responding. Max fails can automatically prevent this by rendering unresponsive servers inoperative for a set amount of time.

There are two factors associated with the max fails: `max_fails` and `fail_timeout`. Max fails refers to the maximum number of failed attempts to connect to a server should occur before it is considered inactive. `Fail_timeout` specifies the length of time the server is considered inoperative. Once the time expires, new attempts to reach the server will start up again. The default timeout value is 10 seconds.

A sample configuration might look like this:

This site uses cookies and related technologies, as described in our [privacy policy](#), for purposes that may include site operation, analytics, enhanced user experience, or advertising. You may choose to consent to our use of these technologies, or manage your own preferences.

This has been a short overview of simple Round Robin load balancing. Additionally, there are other ways to speed and optimize a server:

- [How to Configure Nginx as a Front End Proxy for Apache](#)
- [How to Install and Configure Varnish with Apache on Ubuntu 12.04](#)
- [How to Install and Use Memcache on Ubuntu 12.04](#)

By Etel Sverdlov

Thanks for learning with the DigitalOcean Community. Check out our offerings for compute, storage, networking, and managed databases.

[Learn more about us →](#)

## Want to learn more? Join the DigitalOcean Community!

Join our DigitalOcean community of over a million developers for free! Get help and share knowledge in our Questions & Answers section, find tutorials and tools that will help you grow as a

This site uses cookies and related technologies, as described in our [privacy policy](#), for purposes that may include site operation, analytics, enhanced user experience, or advertising. You may choose to consent to our use of these technologies, or manage your own preferences.

## About the authors



[Etel Sverdlov](#)

Author

Still looking for an answer?

[Ask a question](#)

[Search for more help](#)

Was this helpful?

[Yes](#)

[No](#)



## Comments

This site uses cookies and related technologies, as described in our [privacy policy](#), for purposes that may include site operation, analytics, enhanced user experience, or advertising. You may choose to consent to our use of these technologies, or manage your own preferences.

Leave a comment...

This textbox defaults to using **Markdown** to format your answer.

You can type **!ref** in this text area to quickly search our full set of tutorials, documentation & marketplace offerings and insert the link!

[Sign In or Sign Up to Comment](#)

[ntuanphuc](#) • December 30, 2015



I followed this tutorial but a blank page appears. Do I have to config in backend servers or make any other configurations. I test with only one backend server. Here is my nginx config in http context

```
upstream backend { server s1.my_domain.us:80; }
```

```
server { listen 80; server_name my_demo_domain.com; location / { proxy_pass http://backend; } }
```

Please give me some advice,

Thanks.

This site uses cookies and related technologies, as described in our [privacy policy](#), for purposes that may include site operation, analytics, enhanced user experience, or advertising. You may choose to consent to our use of these technologies, or manage your own preferences.



[@marwan](#), this article is for nginx and not apache - to answer your questions, yes you do have to keep the same set of files on each of the server, and yes, a database (only) server sitting behind it

[Show replies](#) ▾ [Reply](#)

[C Cor](#) • July 13, 2020 ^

Is it possible combine least\_connect and max fails?

For example:

```
upstream backend { leastconn; server backend1.example.com maxfails=3 fail_timeout=15s;  
server backend2.example.com ; server backend3.example.com ;
```

[Reply](#)

[rs1882828](#) • October 1, 2019 ^

Do we need to do same NGNIX Config on rest slave servers?

[harveyjones282](#) • July 10, 2019 

I had my doubts about if Nginx was going to be helpful... and I was having difficulties setting it up. You solved my problem for setting it up and another helped me realize the benefits of [using Nginx for load balancing](#).

[Reply](#)

[neamati](#) • June 11, 2019 

Excellent Tutorial

[Reply](#)

[鹏鹏左](#) • February 28, 2019 

There are two factors associated with the max fails: max\_fails and fail\_timeout.

find a typo fail\_timeout should be fail\_timeout

[2432612431302469634d4e43793258](#) • November 14, 2016



Hello [@kamaln7](#), I've followed this tutorial thoroughly but am having trouble.

In short, when I pass my ip address directly into "proxy\_pass", the proxy works:

```
server {  
    location / {  
        proxy_pass http://01.02.03.04;  
    }  
}
```

When I visit my proxy computer, I can see the content from the proxy ip... but when I use an upstream directive, it doesn't

```
upstream backend {  
    server 01.02.03.04;  
}  
  
server {  
    location / {  
        proxy_pass http://backend;  
    }  
}
```

When I visit my proxy computer, I am greeted with the default Nginx server page

This site uses cookies and related technologies, as described in our [privacy policy](#), for purposes that may include site operation, analytics, enhanced user experience, or advertising. You may choose to consent to our use of these technologies, or manage your own preferences.

[Show replies](#) ▾ [Reply](#)

[2432612431302469634d4e43793258](#) • November 14, 2016 ^

This comment has been deleted

[Reply](#)

[averysmithproductions](#) • November 14, 2016 ^

This comment has been deleted

[Reply](#)

Load More Comments

This site uses cookies and related technologies, as described in our [privacy policy](#), for purposes that may include site operation, analytics, enhanced user experience, or advertising. You may choose to consent to our use of these technologies, or manage your own preferences.



This work is licensed under a Creative Commons Attribution-NonCommercial- ShareAlike 4.0 International License.



## Try DigitalOcean for free

Click below to sign up and get **\$200 of credit** to try our products over 60 days!

Sign up →



## Popular Topics

Ubuntu

Linux Basics

JavaScript

Python


MySQL

This site uses cookies and related technologies, as described in our [privacy policy](#), for purposes that may include site operation, analytics, enhanced user experience, or advertising. You may choose to consent to our use of these technologies, or manage your own preferences.

[All tutorials →](#)

---

[Free Managed Hosting →](#)



## Get our biweekly newsletter

Sign up for Infrastructure as a Newsletter.

[Sign up →](#)




## Hollie's Hub for Good

Working on improving health and education, reducing inequality, and spurring economic growth? We'd like to help.

[Learn more →](#)

This site uses cookies and related technologies, as described in our [privacy policy](#), for purposes that may include site operation, analytics, enhanced user experience, or advertising. You may choose to consent to our use of these technologies, or manage your own preferences.



## Become a contributor

You get paid; we donate to tech nonprofits.

[Learn more](#) →

## Featured on Community

[Kubernetes Course](#)

[Learn Python 3](#)

[Machine Learning in Python](#)

[Getting started with Go](#)

[Intro to Kubernetes](#)


## DigitalOcean Products

This site uses cookies and related technologies, as described in our [privacy policy](#), for purposes that may include site operation, analytics, enhanced user experience, or advertising. You may choose to consent to our use of these technologies, or manage your own preferences.

# Welcome to the developer cloud

DigitalOcean makes it simple to launch in the cloud and scale up as you grow – whether you're running one virtual machine or ten thousand.

Learn more →



## Company

[About](#)

## Products

[Products Overview](#)

## Community

[Tutorials](#)

## Solutions

[Website Hosting](#)

## Contact

[Support](#)


This site uses cookies and related technologies, as described in our [privacy policy](#), for purposes that may include site operation, analytics, enhanced user experience, or advertising. You may choose to consent to our use of these technologies, or manage your own preferences.



<a href="#">Partners</a>	<a href="#">Cloudways</a>	<a href="#">Hatch Startup Program</a>	<a href="#">VPN</a>
<a href="#">Channel Partners</a>	<a href="#">Managed Databases</a>	<a href="#">deploy by DigitalOcean</a>	<a href="#">SaaS Platforms</a>
<a href="#">Referral Program</a>	<a href="#">Spaces</a>	<a href="#">Shop Swag</a>	<a href="#">Cloud Hosting for Blockchain</a>
<a href="#">Affiliate Program</a>	<a href="#">Marketplace</a>	<a href="#">Research Program</a>	<a href="#">Startup Resources</a>
<a href="#">Press</a>	<a href="#">Load Balancers</a>	<a href="#">Open Source</a>	
<a href="#">Legal</a>	<a href="#">Block Storage</a>	<a href="#">Code of Conduct</a>	
<a href="#">Security</a>	<a href="#">Tools &amp; Integrations</a>	<a href="#">Newsletter Signup</a>	
<a href="#">Investor Relations</a>	<a href="#">API</a>	<a href="#">Meetups</a>	
<a href="#">DO Impact</a>	<a href="#">Pricing</a>		
	<a href="#">Documentation</a>		
	<a href="#">Release Notes</a>		
	<a href="#">Uptime</a>		

The DigitalOcean logo is a stylized 'd' made of binary code (0s and 1s). It is located in the bottom left corner of the footer area.

© 2023 DigitalOcean, LLC. All rights reserved.



This site uses cookies and related technologies, as described in our [privacy policy](#), for purposes that may include site operation, analytics, enhanced user experience, or advertising. You may choose to consent to our use of these technologies, or manage your own preferences.