

```

from flask import Flask, render_template, redirect, url_for, request, flash
from flask_sqlalchemy import SQLAlchemy
from flask_login import LoginManager, UserMixin, login_user, login_required, logout_user, current_user
from werkzeug.security import generate_password_hash, check_password_hash

app = Flask(__name__)
app.config['SECRET_KEY'] = 'secret123'
app.config['SQLALCHEMY_DATABASE_URI'] = 'sqlite:///database.db'

db = SQLAlchemy(app)

login_manager = LoginManager()
login_manager.init_app(app)
login_manager.login_view = "login"

class User(UserMixin, db.Model):
    id = db.Column(db.Integer, primary_key=True)
    role = db.Column(db.String(20))
    name = db.Column(db.String(100))
    email = db.Column(db.String(100), unique=True)
    password = db.Column(db.String(200))
    approved = db.Column(db.Boolean, default=False)

    drives = db.relationship('Drive', backref='company', lazy=True)
    applications = db.relationship('Application', backref='student', lazy=True)

class Drive(db.Model):
    id = db.Column(db.Integer, primary_key=True)
    job_title = db.Column(db.String(100))
    description = db.Column(db.String(200))
    deadline = db.Column(db.String(50))
    status = db.Column(db.String(20), default="Pending")

    company_id = db.Column(db.Integer, db.ForeignKey('user.id'))
    applications = db.relationship('Application', backref='drive', lazy=True)

class Application(db.Model):
    id = db.Column(db.Integer, primary_key=True)
    student_id = db.Column(db.Integer, db.ForeignKey('user.id'))
    drive_id = db.Column(db.Integer, db.ForeignKey('drive.id'))
    status = db.Column(db.String(20), default="Applied")

@login_manager.user_loader
def load_user(user_id):
    return db.session.get(User, int(user_id))

with app.app_context():
    db.create_all()

    admin = User.query.filter_by(role="admin").first()
    if not admin:
        admin = User(
            role="admin",
            name="Admin",
            email="admin@admin.com",
            password=generate_password_hash("admin123"),
            approved=True
        )
        db.session.add(admin)
        db.session.commit()

```

```
@app.route('/')
def home():
    return redirect(url_for('login'))
```

```
@app.route('/login', methods=['GET','POST'])
def login():
    if request.method == "POST":
        email = request.form['email']
        password = request.form['password']
        user = User.query.filter_by(email=email).first()

        if user and check_password_hash(user.password, password):

            if user.role == "company" and not user.approved:
                flash("Your company account is pending admin approval.")
                return redirect(url_for('login'))

            login_user(user)

            if user.role == "admin":
                return redirect(url_for('admin_dashboard'))
            elif user.role == "company":
                return redirect(url_for('company_dashboard'))
            else:
                return redirect(url_for('student_dashboard'))
        else:
            flash("Invalid credentials")

    return render_template("login.html")
```

```
@app.route('/logout')
@login_required
def logout():
    logout_user()
    return redirect(url_for('login'))
```

```
@app.route('/register_student', methods=['GET','POST'])
def register_student():
    if request.method == "POST":
        name = request.form['name']
        email = request.form['email']
        password = generate_password_hash(request.form['password'])

        if User.query.filter_by(email=email).first():
            flash("Email already registered")
            return redirect(url_for('register_student'))

        student = User(
            role="student",
            name=name,
            email=email,
            password=password,
            approved=True
        )
```

```

        db.session.add(student)
        db.session.commit()
        flash("Student registered successfully")
        return redirect(url_for('login'))

    return render_template("register_student.html")

@app.route('/register_company', methods=['GET','POST'])
def register_company():
    if request.method == "POST":
        name = request.form['name']
        email = request.form['email']
        password = generate_password_hash(request.form['password'])

        if User.query.filter_by(email=email).first():
            flash("Email already registered")
            return redirect(url_for('register_company'))

        company = User(
            role="company",
            name=name,
            email=email,
            password=password,
            approved=False
        )

        db.session.add(company)
        db.session.commit()
        flash("Registration successful. Waiting for admin approval.")
        return redirect(url_for('login'))

    return render_template("register_company.html")

@app.route('/admin')
@login_required
def admin_dashboard():

    if current_user.role != "admin":
        return redirect(url_for('login'))

    # ----- SEARCH LOGIC -----
    student_query = request.args.get("student_query")
    company_query = request.args.get("company_query")

    students_list = []
    companies_list = []

    if student_query:
        students_list = User.query.filter(
            User.role == "student",
            (User.name.contains(student_query)) |
            (User.email.contains(student_query)) |
            (User.id.like(f"%{student_query}%"))
        ).all()
    else:
        students_list = User.query.filter_by(role="student").all()

```

```

if company_query:
    companies_list = User.query.filter(
        User.role == "company",
        User.name.contains(company_query)
    ).all()
else:
    companies_list = User.query.filter_by(role="company").all()

students = User.query.filter_by(role="student").count()
companies = User.query.filter_by(role="company").count()
drives = Drive.query.count()
applications = Application.query.count()

pending_companies = User.query.filter_by(role="company", approved=False).all()
pending_drives = Drive.query.filter_by(status="Pending").all()

all_drives = Drive.query.all()

return render_template(
    "admin_dashboard.html",
    students=students,
    companies=companies,
    drives=drives,
    applications=applications,
    pending_companies=pending_companies,
    pending_drives=pending_drives,
    students_list=students_list,
    companies_list=companies_list,
    all_drives=all_drives
)

@app.route('/approve_company/<int:id>')
@login_required
def approve_company(id):

    if current_user.role == "admin":
        company = db.session.get(User, id)
        company.approved = True
        db.session.commit()

    return redirect(url_for('admin_dashboard'))

@app.route('/reject_company/<int:id>')
@login_required
def reject_company(id):

    if current_user.role == "admin":
        company = db.session.get(User, id)
        db.session.delete(company)
        db.session.commit()

    return redirect(url_for('admin_dashboard'))

```

```

@app.route('/blacklist_company/<int:id>')
@login_required
def blacklist_company(id):

    if current_user.role == "admin":
        company = db.session.get(User, id)
        company.approved = False
        company.role = "blacklisted_company"
        db.session.commit()

    return redirect(url_for('admin_dashboard'))

```

```

@app.route('/approve_drive/<int:id>')
@login_required
def approve_drive(id):

    if current_user.role == "admin":
        drive = db.session.get(Drive, id)
        drive.status = "Approved"
        db.session.commit()

    return redirect(url_for('admin_dashboard'))

```

```

@app.route('/reject_drive/<int:id>')
@login_required
def reject_drive(id):

    if current_user.role == "admin":
        drive = db.session.get(Drive, id)
        drive.status = "Rejected"
        db.session.commit()

    return redirect(url_for('admin_dashboard'))

```

```

@app.route('/blacklist_student/<int:id>')
@login_required
def blacklist_student(id):

    if current_user.role == "admin":
        student = db.session.get(User, id)
        student.role = "blacklisted_student"
        db.session.commit()

    return redirect(url_for('admin_dashboard'))

```

```

@app.route('/company')
@login_required
def company_dashboard():
    if current_user.role != "company":
        return redirect(url_for('login'))

    drives = Drive.query.filter_by(company_id=current_user.id).all()
    return render_template("company_dashboard.html", drives=drives)

```

```

@app.route('/create_drive', methods=['GET','POST'])
@login_required
def create_drive():
    if request.method == "POST":
        drive = Drive(
            job_title=request.form['title'],
            description=request.form['desc'],
            deadline=request.form['deadline'],
            company_id=current_user.id
        )
        db.session.add(drive)
        db.session.commit()
        flash("Drive created successfully")
        return redirect(url_for('company_dashboard'))

    return render_template("create_drive.html")


@app.route('/drive/<int:drive_id>/applications')
@login_required
def view_applications(drive_id):

    drive = Drive.query.get_or_404(drive_id)

    if current_user.role != "company" or current_user.id != drive.company_id:
        return redirect(url_for('company_dashboard'))

    applications = Application.query.filter_by(drive_id=drive_id).all()

    return render_template(
        "view_applications.html",
        drive=drive,
        applications=applications
    )


@app.route('/update_application/<int:app_id>/<string:status>')
@login_required
def update_application(app_id, status):

    application = Application.query.get_or_404(app_id)

    if current_user.role != "company" or \
        current_user.id != application.drive.company_id:
        return redirect(url_for('company_dashboard'))

    if status in ["Shortlisted", "Selected", "Rejected"]:
        application.status = status
        db.session.commit()
        flash("Application status updated")

    return redirect(url_for('view_applications',
        drive_id=application.drive_id))

```

```

@app.route('/student')
@login_required
def student_dashboard():
    if current_user.role != "student":
        return redirect(url_for('login'))

    drives = Drive.query.filter_by(status="Approved").all()

    applications = Application.query.filter_by(
        student_id=current_user.id
    ).all()

    selected_drives = [a for a in applications if a.status == "Selected"]

    return render_template(
        "student_dashboard.html",
        drives=drives,
        applications=applications,
        selected_drives=selected_drives
    )

@app.route('/apply/<int:drive_id>')
@login_required
def apply(drive_id):

    existing = Application.query.filter_by(
        student_id=current_user.id,
        drive_id=drive_id
    ).first()

    if not existing:
        application = Application(
            student_id=current_user.id,
            drive_id=drive_id
        )
        db.session.add(application)
        db.session.commit()
        flash("Applied successfully")

    return redirect(url_for('student_dashboard'))

if __name__ == "__main__":
    app.run(debug=True)

```

Base.html

```
<!DOCTYPE html>
<html>
<head>
  <title>Placement Portal</title>
  <link href="https://cdn.jsdelivr.net/npm/bootstrap@5.3.0/dist/css/bootstrap.min.css" rel="stylesheet">
</head>
<body class="container mt-4">
  <h2>Placement Portal</h2>
  <hr>
  {% block content %}{% endblock %}
</body>
</html>
```

Login.html

```
{% extends 'base.html' %}
{% block content %}
<div class="container mt-5">
<div class="row justify-content-center">
<div class="col-md-5">

<div class="card shadow-lg border-0">
<div class="card-header bg-primary text-white text-center fw-bold">
  Login
</div>

<div class="card-body">

<form method="POST">
<div class="mb-3">
  <label class="form-label">Email address</label>
  <input type="email" class="form-control" name="email" placeholder="Email" required>
</div>

<div class="mb-3">
  <label class="form-label">PassWord</label>
  <input type="password" class="form-control" name="password" placeholder="Password" required>
</div>

<div class="d-grid">
  <button class="btn btn-primary">Login</button>
</div>
</form>

<hr>

<div class="text-center">
  <p class="mb-1">New User?</p>
  <a href="{{ url_for('register_student') }}" class="btn btn-outline-success btn-sm">Register as Student</a>
  <a href="{{ url_for('register_company') }}" class="btn btn-outline-secondary btn-sm">Register as Company</a>
</div></div></div></div>
{% endblock %}
```


register_student.html

```
{% extends 'base.html' %}
{% block content %}
<div class="container mt-5">
<div class="row justify-content-center">
<div class="col-md-6 col-lg-5">
<div class="card shadow-lg border-0">
<div class="card-header bg-success text-white text-center fw-bold">Student Registration</div>
<div class="card-body">

{% with messages = get_flashed_messages() %}
{% for message in messages %}
<div class="alert alert-info alert-dismissible fade show">
  {{ message }}
  <button type="button" class="btn-close" data-bs-dismiss="alert"></button>
</div>
{% endfor %}
{% endwith %}

<form method="POST">
<div class="mb-3">
  <label class="form-label">Full Name</label>
  <input type="text" class="form-control" name="name" placeholder="Full Name" required>
</div>

<div class="mb-3">
  <label class="form-label">Email address</label>
  <input type="email" class="form-control" name="email" placeholder="Email Address" required>
</div>

<div class="mb-3">
  <label class="form-label">Password</label>
  <input type="password" class="form-control" name="password" placeholder="Password (min 6
characters)" minlength="6" required>
  <div class="form-text">Password must be at least 6 characters.</div>
</div>

<div class="d-grid">
  <button class="btn btn-success">Register</button>
</div>
</form>

<hr>
<div class="text-center">
  <p class="mb-1">Already have an account?</p>
  <a href="{{ url_for('login') }}" class="btn btn-outline-primary btn-sm">Go to Login</a>
</div></div></div></div></div>
{% endblock %}
```

register_company.html

```
{% extends 'base.html' %}
{% block content %}
<div class="container mt-5">
<div class="row justify-content-center">
<div class="col-md-6 col-lg-5">
<div class="card shadow-lg border-0">
<div class="card-header bg-secondary text-white text-center fw-bold">Company Registration</div>
<div class="card-body">

{% with messages = get_flashed_messages() %}
  {% for message in messages %}
    <div class="alert alert-warning alert-dismissible fade show">
      {{ message }}
      <button type="button" class="btn-close" data-bs-dismiss="alert"></button>
    </div>
  {% endfor %}
{% endwith %}

<form method="POST">
<div class="mb-3">
  <label class="form-label">Company Name</label>
  <input type="text" class="form-control" name="name" placeholder="Company Name" required>
</div>

<div class="mb-3">
  <label class="form-label">Official Email</label>
  <input type="email" class="form-control" name="email" placeholder="Official Email" required>
</div>

<div class="mb-3">
  <label class="form-label">Password</label>
  <input type="password" class="form-control" name="password" placeholder="Password (min 6
characters)" minlength="6" required>
  <div class="form-text">Minimum 6 characters required.</div>
</div>

<div class="d-grid">
  <button class="btn btn-secondary">Register Company</button>
</div>
</form>

<hr>
<div class="text-center">
  <p class="mb-1">Already registered?</p>
  <a href="{{ url_for('login') }}" class="btn btn-outline-primary btn-sm">Go to Login</a>
</div></div></div></div></div>
{% endblock %}
```

admin_dashboard.html

```
{% extends 'base.html' %}
{% block content %}
<div class="container mt-4">

<div class="d-flex justify-content-between mb-3">
  <h3 class="fw-bold">Admin Dashboard</h3>
  <a href="{{ url_for('logout') }}" class="btn btn-outline-danger btn-sm">Logout</a>
</div>

<div class="row text-center mb-4">
  {% for t,v,c in
  [('Students',students,'primary'),('Companies',companies,'success'),('Drives',drives,'warning'),('Application
  s',applications,'danger')] %}
    <div class="col-md-3 mb-3">
      <div class="card shadow-sm border-0 p-3">
        <h6 class="text-muted">{{ t }}</h6>
        <h3 class="text-{{ c }}">{{ v }}</h3>
      </div>
    </div>
  {% endfor %}
</div>

<div class="card shadow-sm border-0 mb-4">
  <div class="card-header bg-warning fw-bold text-center">Pending Company Approvals</div>
  <div class="card-body">
    {% if pending_companies %}
    <table class="table table-bordered table-hover">
      <tr><th>Name</th><th>Email</th><th>Actions</th></tr>
      {% for c in pending_companies %}
      <tr>
        <td>{{ c.name }}</td>
        <td>{{ c.email }}</td>
        <td class="d-flex gap-1">
          <a href="{{ url_for('approve_company', id=c.id) }}" class="btn btn-success btn-sm">Approve</a>
          <a href="{{ url_for('reject_company', id=c.id) }}" class="btn btn-danger btn-sm">Reject</a>
          <a href="{{ url_for('blacklist_company', id=c.id) }}" class="btn btn-dark btn-sm">Blacklist</a>
        </td>
      </tr>
      {% endfor %}
    </table>
    {% else %}
    <div class="alert alert-success text-center mb-0">No pending companies.</div>
    {% endif %}
  </div>
</div>

<div class="card shadow-sm border-0 mb-4">
  <div class="card-header bg-info fw-bold text-center">Pending Placement Drives</div>
  <div class="card-body">
    {% if pending_drives %}
    <table class="table table-bordered table-hover">
      <tr><th>Job Title</th><th>Company</th><th>Deadline</th><th>Actions</th></tr>
      {% for d in pending_drives %}
      <tr>
        <td>{{ d.job_title }}</td>
        <td>{{ d.company.name }}</td>
        <td>{{ d.deadline }}</td>
        <td class="d-flex gap-1">
```

```

        <a href="{{ url_for('approve_drive', id=d.id) }}" class="btn btn-success btn-sm">Approve</a>
        <a href="{{ url_for('reject_drive', id=d.id) }}" class="btn btn-danger btn-sm">Reject</a>
    </td>
</tr>
{% endfor %}
</table>
{% else %}
<div class="alert alert-info text-center mb-0">No pending drives.</div>
{% endif %}
</div>
</div>

<div class="card shadow-sm border-0 mb-4">
<div class="card-header bg-secondary text-white fw-bold text-center">All Placement Drives</div>
<div class="card-body">
{% if all_drives %}
<table class="table table-bordered table-hover">
<tr><th>Job Title</th><th>Company</th><th>Status</th></tr>
{% for d in all_drives %}
<tr>
<td>{{ d.job_title }}</td>
<td>{{ d.company.name }}</td>
<td>{{ d.status }}</td>
</tr>
{% endfor %}
</table>
{% endif %}
</div>
</div>

<div class="card shadow-sm border-0 mb-4">
<div class="card-header bg-primary text-white fw-bold text-center">Student Management</div>
<div class="card-body">
{% if students_list %}
<table class="table table-bordered table-hover">
<tr><th>ID</th><th>Name</th><th>Email</th><th>Action</th></tr>
{% for s in students_list %}
<tr>
<td>{{ s.id }}</td>
<td>{{ s.name }}</td>
<td>{{ s.email }}</td>
<td><a href="{{ url_for('blacklist_student', id=s.id) }}" class="btn btn-dark btn-sm">Deactivate</a></td>
</tr>
{% endfor %}
</table>
{% else %}
<div class="alert alert-success text-center mb-0">No students found.</div>
{% endif %}
</div>
</div>

</div>
{% endblock %}

```

student_dashboard.html

```
{% extends 'base.html' %}
{% block content %}

<div class="container mt-4">

<div class="d-flex justify-content-between align-items-center mb-4">
<h3 class="fw-bold">Student Dashboard</h3>
<a href="{{ url_for('logout') }}" class="btn btn-outline-danger btn-sm">Logout</a>
</div>

<div class="card shadow-sm border-0 mb-4">
<div class="card-header bg-primary text-white fw-bold">Available Placement Drives</div>
<div class="card-body">

{% if drives %}
<div class="row">
{% for d in drives %}
<div class="col-md-6 col-lg-4 mb-4">
<div class="card shadow-sm h-100 border-0">
<div class="card-body">
<h5 class="text-primary">{{ d.job_title }}</h5>
<p class="text-muted">{{ d.description }}</p>
<span class="badge bg-warning text-dark">Deadline: {{ d.deadline }}</span>
<div class="d-grid mt-2">
<a href="{{ url_for('apply', drive_id=d.id) }}" class="btn btn-success btn-sm">Apply Now</a>
</div></div></div></div></div>

{% endif %}
</div>
<div class="alert alert-info text-center">No approved drives available.</div>
</div>

<div class="card shadow-sm border-0 mb-4">
<div class="card-header bg-success text-white fw-bold">My Applications</div>
<div class="card-body">
{% if applications %}
<table class="table table-bordered table-hover">
<tr><th>Job Title</th><th>Status</th></tr>
{% for app in applications %}
<tr>
<td>{{ app.drive.job_title }}</td>
<td>
<span class="badge {% if app.status=='Applied' %}bg-secondary{% elif app.status=='Shortlisted' %}bg-
warning text-dark{% elif app.status=='Selected' %}bg-success{% else %}bg-danger{% endif %}">
{{ app.status }}
</span>
</td>
</tr>
</tr>
</div>
</div>
</div>
```

```
{% endfor %}
</table>
{% else %}
<div class="alert alert-info text-center">You have not applied to any drives yet.</div>
{% endif %}
</div>
</div>
```

```
<div class="card shadow-sm border-0">
<div class="card-header bg-dark text-white fw-bold">Placement History (Selected)</div>
<div class="card-body">
{% if selected_drives %}
<ul class="list-group">
{% for app in selected_drives %}
<li class="list-group-item d-flex justify-content-between">
{{ app.drive.job_title }}
<span class="badge bg-success">Placed</span>
</li>
{% endfor %}
</ul>
{% else %}
<div class="alert alert-warning text-center">No placements yet.</div>
{% endif %}
</div>
</div>

</div>
```

```
{% endblock %}
```

company_dashboard.html

```
{% extends 'base.html' %}
{% block content %}
<div class="container mt-4">

<div class="d-flex justify-content-between align-items-center mb-4">
  <h3 class="fw-bold">Company Dashboard</h3>
  <div>
    <a href="{{ url_for('create_drive') }}" class="btn btn-primary btn-sm me-2">+ Create Drive</a>
    <a href="{{ url_for('logout') }}" class="btn btn-outline-danger btn-sm">Logout</a>
  </div>
</div>

<h5 class="mb-3">Your Placement Drives</h5>

{% if drives %}
<div class="row">
{% for d in drives %}
  <div class="col-md-6 col-lg-4 mb-4">
    <div class="card shadow-sm border-0 h-100 p-3">
      <h5 class="text-primary">{{ d.job_title }}</h5>
      <p class="text-muted mb-1">{{ d.description }}</p>
      <p class="mb-2"><strong>Deadline:</strong> {{ d.deadline }}</p>
      <span class="badge bg-{{ '% if d.status=='Approved' %}}success{% else %}warning text-dark{% endif %}}">
        {{ d.status }}
      </span>
      <hr>
      <a href="{{ url_for('view_applications', drive_id=d.id) }}" class="btn btn-outline-dark btn-sm w-100">
        View Applications
      </a>
    </div>
  </div>
{% endfor %}
</div>
{% else %}
<div class="alert alert-info text-center">You have not created any drives yet.</div>
{% endif %}

</div>
{% endblock %}
```

view_applications.html

```
{% extends 'base.html' %}
{% block content %}
<div class="container mt-4">

<h4 class="mb-3">Applications for {{ drive.job_title }}/h4>

{% if applications %}
<table class="table table-bordered">
<tr><th>Student Name</th><th>Email</th><th>Status</th><th>Action</th></tr>

{% for app in applications %}
<tr>
<td>{{ app.student.name }}/td>
<td>{{ app.student.email }}/td>

<td>
<span class="badge bg-{% if app.status=='Applied' %}secondary{% elif app.status=='Shortlisted' %}warning{% elif app.status=='Selected' %}success{% elif app.status=='Rejected' %}danger{% endif %}">
{{ app.status }}
</span>
</td>
<td>
{% if app.status=="Applied" %}
<a href="{{ url_for('update_application', app_id=app.id, status='Shortlisted') }}" class="btn btn-warning btn-sm">Shortlist</a>
<a href="{{ url_for('update_application', app_id=app.id, status='Selected') }}" class="btn btn-success btn-sm">Select</a>
<a href="{{ url_for('update_application', app_id=app.id, status='Rejected') }}" class="btn btn-danger btn-sm" onclick="return confirm('Are you sure you want to reject this application?')">Reject</a>

{% elif app.status=="Shortlisted" %}
<a href="{{ url_for('update_application', app_id=app.id, status='Selected') }}" class="btn btn-success btn-sm">Select</a>
<a href="{{ url_for('update_application', app_id=app.id, status='Rejected') }}" class="btn btn-danger btn-sm">Reject</a>

{% elif app.status=="Selected" %}
<span class="text-success fw-bold">Final Selection Done</span>

{% elif app.status=="Rejected" %}
<span class="text-danger fw-bold">Application Rejected</span>
{% endif %}
</td></tr>
{% endfor %}
</table>

<a href="#" class="btn btn-danger float-end" onclick="history.back();return false;">Back</a>

{% else %}
<div class="alert alert-info text-center">No applications received yet.</div>
{% endif %}
</div>
{% endblock %}
```


create_drive.html

```
{% extends 'base.html' %}
{% block content %}
<div class="container mt-5">
<div class="row justify-content-center">
<div class="col-md-7 col-lg-6">

<div class="card shadow-lg border-0">
<div class="card-header bg-success text-white text-center fw-bold">Create Placement Drive</div>

<div class="card-body">

{% with messages = get_flashed_messages() %}
{% for message in messages %}
<div class="alert alert-success alert-dismissible fade show">
  {{ message }}
  <button type="button" class="btn-close" data-bs-dismiss="alert"></button>
</div>
{% endfor %}
{% endwith %}

<form method="POST">
<div class="mb-3">
  <label class="form-label">Job Title</label>
  <input type="text" class="form-control" name="title" placeholder="Job Title" required>
</div>

<div class="mb-3">
  <label class="form-label">Job Description</label>
  <textarea class="form-control" name="desc" rows="3" placeholder="Job Description"
required></textarea>
</div>

<div class="mb-3">
  <label class="form-label">Application Deadline</label>
  <input type="date" class="form-control" name="deadline" required>
</div>

<div class="d-grid">
  <button class="btn btn-success">Create Drive</button>
</div>
</form>

<hr>
<div class="text-center">
  <a href="{{ url_for('company_dashboard') }}" class="btn btn-outline-secondary btn-sm">Back to
Dashboard</a>
</div></div></div></div></div></div>
{% endblock %}
```

SQLite format 3???@ ".v?

```
###?tableapplicationapplication?CREATE TABLE application (  
  id INTEGER NOT NULL,  
  student_id INTEGER,  
  drive_id INTEGER,  
  status VARCHAR(20),  
  PRIMARY KEY (id),  
  FOREIGN KEY(student_id) REFERENCES user (id),  
  FOREIGN KEY(drive_id) REFERENCES drive (id)
```

)??

```
?????_tabledrivedrive?CREATE TABLE drive (  
  id INTEGER NOT NULL,
```

```
  job_title VARCHAR(100),  
  description VARCHAR(200),  
  deadline VARCHAR(50),  
  status VARCHAR(20),  
  company_id INTEGER,  
  PRIMARY KEY (id),  
  FOREIGN KEY(company_id) REFERENCES user (id)
```

)?Q?

```
?????tableuseruser?CREATE TABLE user (  
  id INTEGER NOT NULL,
```

```
  role VARCHAR(20),  
  name VARCHAR(100),  
  email VARCHAR(100),  
  password VARCHAR(200),  
  approved BOOLEAN,  
  PRIMARY KEY (id),  
  UNIQUE (email)
```

```
)'???;??iindexsqlite_autoindex_user_1user?
```

?

SQLite format 3??@.v?

```
tablecompanycompanyCREATE TABLE company (  
  id INTEGER NOT NULL,  
  name VARCHAR(100),  
  hr VARCHAR(100),  
  website VARCHAR(200),  
  status VARCHAR(20),  
  PRIMARY KEY (id),  
  FOREIGN KEY(id) REFERENCES user (id)
```

)

```
tablestudentstudent
```

```
CREATE TABLE student (  
  id INTEGER NOT NULL,  
  name VARCHAR(100),  
  phone VARCHAR(20),  
  PRIMARY KEY (id),  
  FOREIGN KEY(id) REFERENCES user (id)
```

)

```
tableapplicationapplicationCREATE TABLE application (  
  id INTEGER NOT NULL,
```

```
  student_id INTEGER,  
  drive_id INTEGER,  
  status VARCHAR(20),  
  PRIMARY KEY (id),  
  CONSTRAINT unique_application UNIQUE (student_id, drive_id)
```

)

```
tabledrivedriveCREATE TABLE drive (  
  id INTEGER NOT NULL,
```

```
  company_id INTEGER,  
  title VARCHAR(100),  
  description TEXT,  
  deadline DATE,  
  status VARCHAR(20),  
  PRIMARY KEY (id)
```

)

```
tableuseruserCREATE TABLE user (  
  id INTEGER NOT NULL,
```

```
  role VARCHAR(20),  
  email VARCHAR(100) NOT NULL,  
  password VARCHAR(200) NOT NULL,  
  active BOOLEAN,  
  PRIMARY KEY (id),  
  UNIQUE (email)
```

)