



- SETTINGS / AUTHENTICATION
- VIEWS
- Dashboard
- Jobs
- Schedules
- My View
- RESOURCES
- Templates
- Credentials
- Projects
- Inventories
- Inventory Scripts
- ACCESS
- Organizations
- Users
- Teams
- ADMINISTRATION
- Credential Types
- Notifications
- Management Jobs
- Instance Groups
- Applications
- Settings

AUTHENTICATION

- AZURE AD
- GITHUB
- GOOGLE OAUTH2
- LDAP
- RADIUS
- SAML
- TACACS+

LDAP SERVER Default

LDAP SERVER URI ?

REVERT

ldap://srv-ipa-101.ipa.gpext.local, ldap://srv-ipa-1

LDAP BIND DN ?

REVERT

uid=awxintegration,cn=users,cn=accounts,dc=ipa

LDAP BIND PASSWORD ?

SHOW

.....

LDAP USER DN TEMPLATE ?

REVERT

uid=%(user)s,cn=users,cn=accounts,dc=ipa,dc=g

LDAP GROUP TYPE ?

REVERT

NestedMemberDNGroupType

LDAP REQUIRE GROUP ?

REVERT

cn=awx,cn=groups,cn=accounts,dc=ipa,dc=gpext

LDAP DENY GROUP ?

REVERT

CN=Disabled Users,OU=Users,DC=example,DC=c

LDAP START TLS ?

✓

LDAP USER SEARCH ? REVERT

```
1 [
2   "cn=users, cn=accounts, dc=ipa, dc=gpext, dc=local",
3   "SCOPE_SUBTREE",
4   "(uid=%(user)s)"
5 ]
```

LDAP GROUP SEARCH ? REVERT

```
1 [
2   "cn=groups, cn=accounts, dc=ipa, dc=gpext, dc=local",
3   "SCOPE_SUBTREE",
4   "(objectClass=groupofnames)"
5 ]
```

LDAP USER ATTRIBUTE MAP ? REVERT

```
1 {
2   "first_name": "givenName",
3   "last_name": "sn",
4   "email": "mail"
5 }
```

LDAP GROUP TYPE PARAMETERS ? REVERT

```
1 {
2   "name_attr": "cn",
3   "member_attr": "member"
4 }
```

LDAP USER FLAGS BY GROUP ? REVERT

```
1 {
```



```
5 }
```

LDAP ORGANIZATION MAP

REVERT

```
1 {
2   "OGP": {
3     "remove_admins": false,
4     "admins": "cn=awxadmin,cn=groups,cn=accounts,dc=ipa,dc=gpxext,dc=local"
5   }
6 }
```

LDAP TEAM MAP

REVERT

```
1 {}
```