

```

#include <stdio.h>
#include <stdlib.h>
#include <unistd.h>
#include <sys/wait.h>

int main()
{
    char cmd[100];

    printf("Enter Linux command: ");
    scanf("%s", cmd);
    pid_t pid = fork();
    if(pid == 0)
    {
        printf("Child PID : %d\n", getpid());
        execlp(cmd, cmd, NULL);
        perror("Execution Failed");
    }
    else if(pid > 0)
    {
        printf("Parent PID : %d\n", getpid());
        wait(NULL);
        printf("Child process completed.\n");
    }
    else
    {
        printf("Fork Failed\n");
    }
    return 0;
}

```

```

akhil@Akhil:~/OS$ gcc week1-1.c -o week1-1
akhil@Akhil:~/OS$ ./week1-1
Enter Linux command: uname
Parent PID : 971
Child PID : 976
Linux
Child process completed.
akhil@Akhil:~/OS$ |

```

2. copying the contents from one file to another file

```
#include <stdio.h>
#include <fcntl.h>
#include <unistd.h>

int main()
{
    int src, dest;
    char buffer[1024];
    int bytes;

    src = open("input.txt", O_RDONLY);

    if(src < 0)
    {
        printf("Cannot open source file\n");
        return 1;
    }

    dest = open("output.txt", O_WRONLY | O_CREAT | O_TRUNC, 0644);

    while((bytes = read(src, buffer, sizeof(buffer))) > 0)
    {
        write(dest, buffer, bytes);
    }

    close(src);
    close(dest);

    printf("File copied successfully.\n");

    return 0;
}
```

```
akhil@Akhil:~/OS$ gcc week1-3.c -o week1-3
akhil@Akhil:~/OS$ ./week1-3
File copied successfully.
```