Linux Cross Reference

Free Electrons

Embedded Linux Experts

• source navigation • diff markup • identifier search • freetext search •

Version:

2.0.40 2.2.26 2.4.37 3.1 3.2 3.3 3.4 3.5 3.6 3.7 3.8 3.9 3.10 3.11 3.12 3.13 3.14 3.15 3.16 **3.17**

Linux/net/ipv4/tcp lp.c

```
23456789
    * TCP Low Priority (TCP-LP)
    * TCP Low Priority is a distributed algorithm whose goal is to utilize only
        the excess network bandwidth as compared to the ``fair share`` of
        bandwidth as targeted by TCP.
    * As of 2.6.13, Linux supports pluggable congestion control algorithms.
    * Due to the limitation of the API, we take the following changes from
<u> 10</u>
    * the original TCP-LP implementation:
<u>11</u>
        o We use newReno in most core CA handling. Only add some checking
12
          within cong avoid.
<u>13</u>
        o Error correcting in remote HZ, therefore remote HZ will be keeped
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
          on checking and updating.
        o Handling calculation of One-Way-Delay (OWD) within rtt sample, since
          OWD have a similar meaning as RTT. Also correct the buggy formular.
        o Handle reaction for Early Congestion Indication (ECI) within
           pkts_acked, as mentioned within pseudo code.
        o OWD is handled in relative format, where local time stamp will in
           tcp_time_stamp format.
    * Original Author:
        Aleksandar Kuzmanovic <akuzma@northwestern.edu>
    * Available from:
        http://www.ece.rice.edu/~akuzma/Doc/akuzma/TCP-LP.pdf
    * Original implementation for 2.4.19:
        http://www-ece.rice.edu/networks/TCP-LP/
    * 2.6.x module Authors:
        Wong Hoi Sing, Edison <a href="mailto:kwong3i@gmail.com">hswong3i@gmail.com</a>
        Hung Hing Lun, Mike <hlhung3i@gmail.com>
    * SourceForge project page:
        http://tcp-lp-mod.sourceforge.net/
<u>34</u>
35
36 #include <linux/module.h>
37 #include <net/tcp.h>
39 /* resolution of owd */
40 #define LP RESOL
                            1000
42
   * enum tcp_lp_state
```

```
* @LP_VALID_RHZ: is remote HZ valid?
 44
      * @LP_VALID_OWD: is OWD valid?
 <u>45</u>
      * @LP_WITHIN_THR: are we within threshold?
 <u>46</u>
 <u>47</u>
      * @LP_WITHIN_INF: are we within inference?
 <u>48</u>
 <u>49</u>
      * TCP-LP's state flags.
 <u>50</u>
      * We create this set of state flag mainly for debugging.
 <u>51</u>
      */
 52 enum tcp lp state {
 53
54
               LP_VALID_RHZ = (1 << 0),
               LP_VALID_OWD = (1 << 1),
 <u>55</u>
               LP_WITHIN_THR = (1 << 3),
 <u>56</u>
               LP WITHIN INF = (1 << 4),
 <u>57</u> };
 <u>58</u>
 59 /**
 <u>60</u>
      * struct lp
 <u>61</u>
      * @flag: TCP-LP state flag
 <u>62</u>
      * @sowd: smoothed OWD << 3
 63
      * @owd_min: min OWD
 <u>64</u>
      * @owd_max: max OWD
 <u>65</u>
      * @owd_max_rsv: resrved max owd
 <u>66</u>
      * @remote_hz: estimated remote HZ
 <u>67</u>
      * @remote_ref_time: remote reference time
      * @local_ref_time: local reference time
 <u>68</u>
      * @last_drop: time for last active drop
 <u>69</u>
 <u>70</u>
      * @inference: current inference
 71
72
73
      * TCP-LP's private struct.
      * We get the idea from original TCP-LP implementation where only left those we
 74
75
      * found are really useful.
      */
 <u>76</u>
    struct lp {
 77
               u32 flag;
 <u>78</u>
               u32 sowd;
 <u>79</u>
               u32 owd_min;
 <u>80</u>
               u32 owd_max;
 <u>81</u>
               u32 owd_max_rsv;
 <u>82</u>
               u32 remote_hz;
 <u>83</u>
               u32 remote_ref_time;
 <u>84</u>
               u32 local_ref_time;
 85
               u32 last_drop;
 <u>86</u>
               u32 inference;
 <u>87</u> };
 88
 89 /**
      * tcp_lp_init
 <u>90</u>
 <u>91</u>
 <u>92</u>
      * Init all required variables.
 <u>93</u>
      * Clone the handling from Vegas module implementation.
 <u>94</u>
 95 static void tcp lp init(struct sock *sk)
 96 {
 <u>97</u>
               struct <u>lp</u> *<u>lp</u> = <u>inet csk ca(sk);</u>
 <u>98</u>
 <u>99</u>
               lp \rightarrow flag = 0;
               \frac{1p}{>} sowd = 0;
100
101
               lp->owd_min = 0xffffffff;
102
               lp->owd_max = 0;
103
               lp->owd max rsv = 0;
<u> 104</u>
               lp->remote_hz = 0;
<u> 105</u>
               lp->remote_ref_time = 0;
<u> 106</u>
               lp->local_ref_time = 0;
107
               lp->last_drop = 0;
               lp->inference = 0;
<u> 108</u>
```

```
<u>109</u> }
110
<u>111</u> /**
<u>112</u>
       * tcp_lp_cong_avoid
<u> 113</u>
114
       * Implementation of cong_avoid.
<u>115</u>
       * Will only call newReno CA when away from inference.
116
       * From TCP-LP's paper, this will be handled in additive increasement.
<u>117</u>
118 static void tcp lp cong avoid(struct sock *sk, u32 ack, u32 acked)
<u>119</u> {
<u> 120</u>
                struct <u>lp</u> *<u>lp</u> = <u>inet csk ca</u>(sk);
<u> 121</u>
122
                if (!(lp->flag & LP_WITHIN_INF))
123
                           tcp reno cong avoid(sk, ack, acked);
<u>124</u> }
<u> 125</u>
<u> 126</u>
<u>127</u>
       * tcp_lp_remote_hz_estimator
<u> 128</u>
<u> 129</u>
       * Estimate remote HZ.
<u>130</u>
       * We keep on updating the estimated value, where original TCP-LP
<u>131</u>
       * implementation only guest it for once and use forever.
132
133 static u32 tcp lp remote hz estimator(struct sock *sk)
<u>134</u> {
<u> 135</u>
                struct \underline{tcp \ sock} \ *\underline{tp} = \underline{tcp \ sk}(sk);
<u> 136</u>
                struct <u>lp</u> *<u>lp</u> = <u>inet csk ca(sk);</u>
<u>137</u>
                s64 rhz = lp->remote_hz << 6; /* remote HZ << 6 */</pre>
138
                s64 m = 0;
<u>139</u>
<u> 140</u>
                /* not yet record reference time
<u> 141</u>
                 * go away!! record it before come back!! */
142
                if (<u>lp</u>->remote_ref_time == 0 || <u>lp</u>->local_ref_time == 0)
<u> 143</u>
                           goto out;
<u> 144</u>
<u> 145</u>
                /* we can't calc remote HZ with no different!! */
<u> 146</u>
                if (<u>tp</u>->rx_opt.rcv_tsval == <u>lp</u>->remote_ref_time ||
<u> 147</u>
                      tp->rx_opt.rcv_tsecr == lp->local_ref_time)
<u> 148</u>
                           goto out;
<u>149</u>
<u> 150</u>
                \underline{m} = \underline{HZ} * (\underline{tp} - rx_opt.rcv_tsval -
<u> 151</u>
                              lp->remote_ref_time) / (tp->rx_opt.rcv_tsecr -
152
                                                               lp->local ref time);
<u> 153</u>
                if (\underline{m} < 0)
<u> 154</u>
                           \underline{\mathbf{m}} = -\underline{\mathbf{m}};
<u> 155</u>
<u> 156</u>
                if (rhz > 0) {
                           m -= rhz >> 6; /* m is now error in remote HZ est */
<u> 157</u>
<u>158</u>
                                                 /* 63/64 old + 1/64 new */
                           rhz += \underline{m};
<u>159</u>
                } else
<u> 160</u>
                           rhz = \underline{m} << 6;
<u> 161</u>
<u> 162</u>
      out:
163
                /* record time for successful remote HZ calc */
164
                if ((rhz >> 6) > 0)
<u> 165</u>
                           lp->flag |= LP_VALID_RHZ;
<u> 166</u>
                else
167
                           lp->flag &= ~LP_VALID_RHZ;
168
169
                /* record reference time stamp */
170
                lp->remote_ref_time = tp->rx_opt.rcv_tsval;
171
                lp->local_ref_time = tp->rx_opt.rcv_tsecr;
172
173
                return rhz >> 6;
```

```
<u>174</u> }
175
<u>176</u> /**
<u> 177</u>
      * tcp_lp_owd_calculator
<u> 178</u>
<u>179</u>
      * Calculate one way delay (in relative format).
180
      * Original implement OWD as minus of remote time difference to local time
<u> 181</u>
       * difference directly. As this time difference just simply equal to RTT, when
182
       * the network status is stable, remote RTT will equal to local RTT, and result
183
      * OWD into zero.
<u> 184</u>
      * It seems to be a bug and so we fixed it.
<u> 185</u>
186 static u32 tcp lp owd calculator(struct sock *sk)
<u>187</u> {
<u> 188</u>
                struct \underline{\mathsf{tcp}}\ \mathsf{sock}\ *\underline{\mathsf{tp}}\ =\ \underline{\mathsf{tcp}}\ \mathsf{sk}(\mathsf{sk});
<u> 189</u>
                struct lp *lp = inet csk ca(sk);
<u> 190</u>
                \underline{\mathsf{s64}} owd = 0;
<u> 191</u>
<u> 192</u>
                lp->remote_hz = tcp lp remote hz estimator(sk);
<u> 193</u>
<u> 194</u>
                if (lp->flag & LP_VALID_RHZ) {
<u> 195</u>
                           owd =
<u> 196</u>
                                tp->rx_opt.rcv_tsval * (LP RESOL / lp->remote_hz) -
<u> 197</u>
                                tp->rx_opt.rcv_tsecr * (LP RESOL / HZ);
<u> 198</u>
                           if (owd < 0)
<u> 199</u>
                                      owd = -owd;
<u> 200</u>
                }
201
202
                if (owd > 0)
203
                           lp->flag |= LP_VALID_OWD;
204
                else
<u> 205</u>
                           lp->flag &= ~LP_VALID_OWD;
<u> 206</u>
<u> 207</u>
                return owd;
<u> 208</u> }
209
<u>210</u>
<u>211</u>
      * tcp_lp_rtt_sample
212
<u> 213</u>
      * Implementation or rtt_sample.
<u> 214</u>
       * Will take the following action,
215
            1. calc OWD,
            2. record the min/max OWD,
216
<u>217</u>
            3. calc smoothed OWD (SOWD).
<u>218</u>
      * Most ideas come from the original TCP-LP implementation.
<u> 219</u>
220 static void tcp lp rtt sample(struct sock *sk, u32 rtt)
<u>221</u> {
222
223
224
                struct <u>lp</u> *<u>lp</u> = <u>inet_csk_ca(sk);</u>
                s64 mowd = tcp_lp_owd_calculator(sk);
<u> 225</u>
                /* sorry that we don't have valid data */
226
227
                if (!(\frac{lp}{p}) + \frac{flag}{k} & LP_VALID_RHZ) \mid | !(\frac{lp}{k}) + \frac{flag}{k} & LP_VALID_OWD)
                           return;
228
229
                /* record the next min owd */
230
                if (mowd < \frac{lp}{p} - > owd_min)
231
                           lp->owd_min = mowd;
232
233
                /* always forget the max of the max
234
                 * we just set owd_max as one below it */
235
                if (mowd > \underline{lp} - > owd_max) {
236
                           if (mowd > \frac{lp}{s} - sowd_{max} - sv) {
237
                                      if (\underline{lp} - > owd_max_rsv == 0)
<u> 238</u>
                                                 lp->owd_max = mowd;
```

```
else
                                         \frac{1p}{}->owd_max = \frac{1p}{}->owd_max_rsv;
                                lp->owd_max_rsv = mowd;
                       } else
                                lp->owd max = mowd;
             }
             /* calc for smoothed owd */
             if (\frac{lp}{>} sowd != 0) {
                       mowd -= lp->sowd >> 3; /* m is now error in owd est */
                                                  /* owd = 7/8 owd + 1/8 new */
                       lp->sowd += mowd;
             } else
                       <u>lp</u>->sowd = mowd << 3; /* take the measured time be owd */
<u>252</u> }
254 /**
     * tcp_lp_pkts_acked
     * Implementation of pkts acked.
     * Deal with active drop under Early Congestion Indication.
     * Only drop to half and 1 will be handle, because we hope to use back
     * newReno in increase case.
     * We work it out by following the idea from TCP-LP's paper directly
263 static void tcp lp pkts acked(struct sock *sk, u32 num_acked, s32 rtt_us)
<del>264</del> {
             struct \underline{tcp \ sock} \ *\underline{tp} = \underline{tcp \ sk}(sk);
             struct <u>lp</u> *<u>lp</u> = <u>inet csk ca(sk);</u>
             if (rtt us > 0)
                       tcp lp rtt sample(sk, rtt_us);
             /* calc inference */
             if (tcp time stamp > tp->rx_opt.rcv_tsecr)
                       lp->inference = 3 * (tcp_time_stamp - tp->rx_opt.rcv_tsecr);
             /* test if within inference */
             if (lp->last_drop && (tcp time stamp - lp->last_drop < lp->inference))
                       lp->flag |= LP_WITHIN_INF;
             else
                       lp->flag &= ~LP WITHIN INF;
             /* test if within threshold */
             if (\frac{1p}{s} - sowd >> 3 <
                  \frac{lp}{dp}->owd min + 15 * (\frac{lp}{dp}->owd max - \frac{lp}{dp}->owd min) / 100)
                       lp->flag |= LP_WITHIN_THR;
             else
                       lp->flag &= ~LP_WITHIN_THR;
             pr debug("TCP-LP: %050|%5u|%5u|%15u|%15u|%15u\n", lp->flag,
                        tp->snd_cwnd, lp->remote_hz, lp->owd_min, lp->owd_max,
                        lp->sowd >> 3);
291
292
             if (lp->flag & LP_WITHIN_THR)
293
                       return;
294
295
             /* FIXME: try to reset owd_min and owd_max here
296
               * so decrease the chance the min/max is no longer suitable
297
               * and will usually within threshold when whithin inference */
298
             \frac{1p}{\sqrt{p}} owd min = \frac{1p}{\sqrt{p}} sowd >> 3;
299
             \frac{1p}{p}->owd_max = \frac{1p}{p}->sowd >> 2;
300
             \frac{1p}{p}->owd_max_rsv = \frac{1p}{p}->sowd >> 2;
301
302
             /* happened within inference
303
               * drop snd cwnd into 1 */
```

```
304
              if (lp->flag & LP_WITHIN_INF)
305
                        tp->snd cwnd = 1U;
<u> 306</u>
<u> 307</u>
              /* happened after inference
<u> 308</u>
               * cut snd_cwnd into half */
<u> 309</u>
              else
<u> 310</u>
                        tp->snd cwnd = max(tp->snd cwnd >> 1U, 1U);
<u>311</u>
312
              /* record this drop time */
<u>313</u>
              lp->last drop = tcp time stamp;
314 }
<u>315</u>
316 static struct tcp congestion ops tcp_lp read mostly = {
<u>317</u>
              .init = tcp lp init,
<u>318</u>
              .ssthresh = tcp reno ssthresh,
<u>319</u>
              .cong_avoid = tcp_lp_cong_avoid,
<u>320</u>
              .pkts_acked = tcp lp pkts acked,
<u> 321</u>
<u> 322</u>
              .owner = THIS MODULE,
323
              .name = "lp"
<u>324</u> };
<u> 325</u>
326 static int <u>init</u> tcp lp register(void)
<u>327</u> {
<u> 328</u>
              BUILD BUG ON(sizeof(struct lp) > ICSK CA PRIV SIZE);
<u> 329</u>
              return tcp register congestion control(&tcp_lp);
<u>330</u> }
<u>331</u>
332 static void <u>exit tcp lp unregister(void)</u>
333 {
334
              tcp unregister congestion control(&tcp lp);
<u>335</u> }
<u>336</u>
337 module init(tcp lp register);
338 module exit(tcp lp unregister);
<u>339</u>
340 MODULE AUTHOR("Wong Hoi Sing Edison, Hung Hing Lun Mike");
341 MODULE LICENSE("GPL");
342 MODULE DESCRIPTION("TCP Low Priority");
343
```

This page was automatically generated by <u>LXR</u> 0.3.1 (<u>source</u>). • Linux is a registered trademark of Linus Torvalds • <u>Contact us</u>

- Home
- <u>Development</u>
- Services
- Training
- Docs
- Community
- Company
- Blog