

Physical layer

From Wikipedia, the free encyclopedia

In the seven-layer OSI model of computer networking, the **physical layer** or **layer 1** is the first (lowest) layer.^[1] The implementation of this layer is often termed **PHY**.

The physical layer consists of the basic networking hardware transmission technologies of a network.^[2] It is a fundamental layer underlying the logical data structures of the higher level functions in a network. Due to the plethora of available hardware technologies with widely varying characteristics, this is perhaps the most complex layer in the OSI architecture.

The physical layer defines the means of transmitting raw bits rather than logical data packets over a physical link connecting network nodes. The bit stream may be grouped into code words or symbols and converted to a physical signal that is transmitted over a hardware transmission medium. The physical layer provides an electrical, mechanical, and procedural interface to the transmission medium. The shapes and properties of the electrical connectors, the frequencies to broadcast on, the modulation scheme to use and similar low-level parameters, are specified here.

Within the semantics of the OSI network architecture, the physical layer translates logical communications requests from the data link layer into hardware-specific operations to effect transmission or reception of electronic signals.

Contents

- 1 Physical signaling sublayer
- 2 List of services
- 3 List of protocols
- 4 Hardware equipment (network node) examples
- 5 Relation to TCP/IP model
- 6 See also
- 7 References
- 8 External links

Physical signaling sublayer

In a local area network (LAN) or a metropolitan area network (MAN) using open systems interconnection (OSI) architecture, the *physical signaling sublayer* is the portion of the physical layer that:^[3]^[4]

- interfaces with the data link layer's media access control (MAC) sublayer,
- performs character encoding, transmission, reception and decoding and,
- performs galvanic isolation.

List of services

The major functions and services performed by the physical layer are:

- Bit-by-bit or symbol-by-symbol delivery
- Providing a standardized interface to physical transmission media, including
 - Mechanical specification of electrical connectors and cables, for example maximum cable length
 - Electrical specification of transmission line signal level and impedance
 - Radio interface, including electromagnetic spectrum frequency allocation and specification of signal strength, analog bandwidth, etc.
 - Specifications for IR over optical fiber or a wireless IR communication link
- Modulation
- Line coding
- Bit synchronization in synchronous serial communication
- Start-stop signalling and flow control in asynchronous serial communication
- Circuit switching
- Multiplexing
 - Establishment and termination of circuit switched connections
- Carrier sense and collision detection utilized by some level 2 multiple access protocols
- Equalization filtering, training sequences, pulse shaping and other signal processing of physical signals
- Forward error correction^[5] for example bitwise convolutional coding
- Bit-interleaving and other channel coding

The physical layer is also concerned with

- Bit rate
- Point-to-point, multipoint or point-to-multipoint line configuration
- Physical network topology, for example bus, ring, mesh or star network
- Serial or parallel communication
- Simplex, half duplex or full duplex transmission mode
- Autonegotiation

List of protocols

- Telephone network modems- V.92
- IRDA physical layer
- USB physical layer
- EIA RS-232, EIA-422, EIA-423, RS-449, RS-485
- Ethernet physical layer Including 10BASE-T, 10BASE2, 10BASE5, 100BASE-TX, 100BASE-FX, 100BASE-T, 1000BASE-T, 1000BASE-SX and other varieties
- Varieties of 802.11 Wi-Fi physical layers
- DSL
- ISDN

- T1 and other T-carrier links, and E1 and other E-carrier links
- SONET/SDH
- Optical Transport Network (OTN)
- GSM Um air interface physical layer
- Bluetooth physical layer
- ITU Recommendations: see ITU-T
- IEEE 1394 interface
- TransferJet physical layer
- Etherloop
- ARINC 818 Avionics Digital Video Bus
- G.hn/G.9960 physical layer
- CAN bus (controller area network) physical layer
- Mobile Industry Processor Interface physical layer

Hardware equipment (network node) examples

- Network adapter
- Repeater
- Network hub
- Modem
- Fiber Media Converter


Relation to TCP/IP model

The TCP/IP model, defined in RFC 1122 and RFC 1123, is a high-level networking description used for the Internet and similar networks. It does not define an equivalent layer that deals exclusively with hardware-level specifications and interfaces, as this model does not concern itself directly with physical interfaces. Several RFCs mention a physical layer and data link layer, but that is in context of IEEE protocols. RFC 1122 and 1123 do not mention any physical layer functionality or physical layer standards.

See also

- Clock recovery
- Ethernet physical layer
- Data transmission
- Digital communication
- Digital modulation
- Line code
- Pulse shaping
- Bit synchronization
- Channel model

References

- [^] Banzal, Shashi (2007). *Data and Computer Network Communication* (http://books.google.com/books?id=UD0h_GqgbHgC&printsec=frontcover&dq=network%2B+guide+to+networks&src=bmrr#v=onepage&q&f=false). Firewall Media. p. 41.
- [^] Iyengar, Shisharama (2010). *Fundamentals of Sensor Network Programming* (http://books.google.com/books?id=UD0h_GqgbHgC&printsec=frontcover&dq=network%2B+guide+to+networks&src=bmrr#v=onepage&q&f=false). Wiley. p. 136.
- [^]  This article incorporates public domain material from the General Services Administration document "Federal Standard 1037C" (<http://www.its.bldrdoc.gov/fs-1037/fs-1037c.htm>).
- [^] "physical signaling sublayer (PLS)" (http://www.tiaonline.org/market_intelligence/glossary/index.cfm?term=%26%23TC%5DSR%3FN%0A). Retrieved 2011-07-29.
- [^] Bertsekas, Dimitri; Gallager, Robert (1992). *Data Networks*. Prentice Hall. p. 61. ISBN 0-13-200916-1.

External links

- Gorry Fairhurst (2001-01-01). "Physical Layer" (<http://replay.web.archive.org/20090618154921/http://www.erg.abdn.ac.uk/users/gorry/course/phy-pages/phy.html>). Archived from the original (<http://www.erg.abdn.ac.uk/users/gorry/course/phy-pages/phy.html>) on 2009-06-08.
- Physical Layer (Layer 1) (http://www.tcpipguide.com/free/t_PhysicalLayerLayer1.htm)

Retrieved from "http://en.wikipedia.org/w/index.php?title=Physical_layer&oldid=624002507"

Categories: Physical layer protocols | Computer networking

-
- This page was last modified on 3 September 2014 at 12:34.
 - Text is available under the Creative Commons Attribution-ShareAlike License; additional terms may apply. By using this site, you agree to the Terms of Use and Privacy Policy. Wikipedia® is a registered trademark of the Wikimedia Foundation, Inc., a non-profit organization.