Advertise here (468x60)

Circuits Gallery

Electronic Circuits and projects, DIY circuit diagrams, Robotics & Microcontroller Projects.....!

► Stepper Motor

▶ Circuit Diagram

▶ Microprocessor

► CNC Programming

Search



How to program stepper motor in microprocessor 8086 assembly language

By Jaseem 3 Comments



How to Control **stepper** motor using

Microprocessor 8086 by assembly language program? As we all know that stepper motor driver plays an important role in automatic control system. We can create a stepper motor controller using 8086 microprocessor and 8255 Programmable Peripheral Interface IC. Here is the assembly language program for 8086 microprocessor.

This stepper motor assembly language

program is guite simple and easy. Here we had described the functions of each code for better understanding.

Basically this assembly program is a beginner guide to those who like to study 8086

programming.

Read Also: Check Prime number is Assembly language



Notations used For representing different types of numbers

We are using some notations here.

B: - used to indicate Binary Number

H: – used to represent Hexa Decimal Number

CW used to represent Control Word register

You must know!

- Stepper motor is interfaced to 8086 with the help of 8255 IC (Programmable Peripheral Interface).
- 8255 has two modes of operation BSR (Bit Set Reset) mode & IO (Input Output) mode.
- The mode is determined by the Control Word (CW) register; (here the CW address is 26).

- Initialize the CW with (0000 0000)B=(00)H for BSR mode & (1000 0000)B=(80)H for IO
 mode
- Stepper motor is IO device so CW should be (80)H There are 4 poles in a typical stepper motor A1, A2, B1, B2
- Energize the poles for anticlockwise rotation we have to apply the following to the poles

A_1	A ₂	B ₁	B ₂	Hex Value
1	0	1	0	0A
0	1	1	0	06
0	1	0	1	05
1	0	0	1	09

So we, out these set of values to the IO port of 8255

8086 assembly language programming code for beginners

The below program shows the interfacing of Stepper motor

- 1 1000 MOV AL,80 /*Move 80(hex) to AL*/
- 2 1002 OUT 26,AL /*Move 80(Hex) to PPI, 26 is the CW of PPI*/
- 3 1004 MOV AL,0A /*Energizing the poles*/
- 4 1006 OUT 20,AL
- 5 1008 CALL 2000 /*Give some delay to rotate Motor*/
- 6 1010 MOV AL,06
- 7 1012 OUT 20,AL
- 8 1014 CALL 2000

```
9 1016 MOV AL,05

10 1018 OUT 20,AL

11 1020 CALL 2000

12 1022 MOV AL,09

13 1024 OUT 20,AL

14 1026 CALL 2000

15 1028 JMP 1004 /*Repeat the steps*/


16 1030 HLT
```

In the memory location 2000, we should give Delay program. You can choose any memory location other than 2000 as you like.

The delay Program is shown below



3 thoughts on "How to program stepper motor in microprocessor 8086 assembly language"



Rebiv

Leave a Reply

Your email address will not be published. Required fields are marked * Name * Email * Website Comment You may use these HTML tags and attributes: <abbr title=""> <acronym title=""> <blockquote cite=""> <cite> <code> <del datetime=""> <i> <q cite=""> <strike> Post Comment Notify me of follow-up comments by email. Notify me of new posts by email.

Buy Engineering Projects from CircuitsGallery.com



We are gald to inform you that we are selling **Engineering Projects** for Electronics students with extreme cheap rate.

Engineering Major Projects

Microcontroller Projects

GSM Projects

GPS Projects

<u>Free Mini Projects</u> Microcontroller Projects

School Projects

We are accepting PayPal & local Bank transfer payments



Get New Circuits



Enter email address...

Subscribe









About me



I am Jaseem, part time blogger & Graduated Engineer in Electronics and Communication

from reputed university in India. Computer and technology has been my passion since I was a child.

Professionally I am working in one of the Middle East country in the field of Telecommunication and system administration.

Now even after having a full time job... [Read More]





Follow

239 followers


Recent Posts

- Build Arduino Based Home Security System Using PIR Motion Sensor
- How to Interface GSM Module SIM300 with PIC 16F628A Microcontroller for sending SMS and making Calls
- Object Detecting Android Mobile Phone Controlled Bluetooth Robot Using PIC Microcontroller

16F877A

- Home Automation and Security System using Microcontroller ATMEGA8 with Arduino Programming
- Arduino Simulator: Simulate Arduino in Proteus Using Arduino Protius library

Categories



PIC Microcontroller PLC

Power Supplies Proteus

Radio Circuits Robotics

School Projects

Simple Electronic Projects

Timer / Counters Tutorials

Uncategorized Video Lab

Traffic Rank
circuitsgallery.com

274,785

Jan 12, 2015

Powered by Alexa

Powered by i-St@r Group of Technologies