

Advanced Java

Agenda

- Java Servlets
 - Life cycle - Revision
 - Startup Servlets
 - @WebServlet annotation
 - Servlet exception Handling
 - Inter-servlet communication
 - State management
 - HttpSession

Servlet Exception Handling

- void init(ServletConfig config) throws ServletException;
 - If initialization of servlet fails, it should throw ServletException; so that web-server will stop further processing of the servlet.
- void service(ServletRequest req, ServletResponse resp) throws ServletException, IOException;
 - If service() method fails, it should throw ServletException or IOException.
 - In this case, web server generates a default response indicating 500 - internal server error.
- code example:

```
public class DbServlet extends HttpServlet {
    public void init(ServletConfig config) throws ServletException {
        super.init(config); // attaches given config to current servlet "this" object
        try {
            // JDBC connection code e.g. DriverManager.getConnection();
        } catch(SQLException ex) {
            throw new ServletException(ex); // exception chaining
        }
    }
}
```

```
}  
// ...  
}
```

Servlet Init parameters

- ServletConfig may have some configurable values like JDBC url, username, password, etc.
- They can be attached to config using init-params using annotation or in web.xml.

```
@WebServlet(value="/mobile",  
    initParams = {  
        @WebInitParam(name="color", value="green"),  
        @WebInitParam(name="greeting", value="Hi")  
    },  
    name = "DMC")  
public class DmcServlet extends HttpServlet {  
    // ...  
}
```

- These init params can be accessed in servlet class using getInitParameter() method.

```
ServletConfig cfg = this.getServletConfig();  
String color = cfg.getInitParameter("color"); // returns "green"
```

```
String message = this.getInitParameter("greeting"); // returns "hi"
```

Load On Startup

- By default servlet is loaded and initialized on first request. If init() includes heavy processing, the first request will execute slower.
- Alternatively, servlets can be loaded while starting the web server. This can be done by marking servlet as load-on-startup using web.xml or annotation.

```
@WebServlet(value="/mobile",  
    loadOnStartup = 1,  
    name = "DMC")  
public class DmcServlet extends HttpServlet {  
    // ...  
}
```

- The number after "loadOnStartup" indicate the sequence of loading the servlets if multiple servlets are marked as load-on-startup.
- If multiple servlets load-on-startup number is same, web container arbitrarily choose the sequence.
- If number after "loadOnStartup" is negative, the servlet is not loaded at startup. It will be loaded on first request.

web.xml

- web.xml is deployment descriptor of web applications. It contains deployment information like servlet configs, jsp configs, session timeout, application security, etc.
- Servlet config in web.xml

```
<servlet>  
    <servlet-name>DMC</servlet-name>  
    <servlet-class>com.sunbeam.DmcServlet</servlet-class>  
    <init-param>  
        <param-name>color</param-name>  
        <param-value>pink</param-value>  
    </init-param>  
    <init-param>  
        <param-name>greeting</param-name>  
        <param-value>Good Afternoon</param-value>  
    </init-param>  
</servlet>
```

```
<load-on-startup>1</load-on-startup>
</servlet>
<servlet-mapping>
  <servlet-name>DMC</servlet-name>
  <url-pattern>/mobile</url-pattern>
</servlet-mapping>
```

HttpServletRequest

- Request Parameters
 - req.getParameter()
 - req.getParameterValues()
- Request Headers
 - req.getHeader()
 - req.getHeaderValues()
- Request upload
 - req.openInputStream()
- <https://docs.oracle.com/javaee/7/api/javax/servlet/http/HttpServletRequest.html>

HttpServletResponse

- Response content type
 - resp.setContentType()
- Response download
 - resp.openOutputStream()
- <https://docs.oracle.com/javaee/7/api/javax/servlet/http/HttpServletResponse.html>

Servlet communication/navigation

- HTTP redirection
 - resp.sendRedirect("url");

- Can navigate from one web component to another web component (within or outside the current application).
- `resp.sendRedirect()` sends a minimal response to the client which contain status code 302 and location (url) of next web component.
- The client (browser) receives this response and send new request to the next web component.
- In browser, URL is modified (i.e. client is aware of navigation).
- `RequestDispatcher`
 - <https://docs.oracle.com/javaee/7/api/javax/servlet/RequestDispatcher.html>
 - `RequestDispatcher rd = req.getRequestDispatcher("url");`
 - url is w.r.t. current request.
 - `RequestDispatcher rd = ctx.getRequestDispatcher("/url");`
 - url is w.r.t. application (context) root.
- `RequestDispatcher.forward()`
 - `rd.forward(req, resp);`
 - Forwards the current request to the given web component (within application only).
 - The next web component produces final response (to be sent to the client).
 - Note that new request & response objects are NOT created.
 - In browser, URL is not modified (i.e. client is not aware of navigation).
 - Faster than HTTP redirection.
 - Used in Spring MVC by the controller.
- `RequestDispatcher.include()`
 - `rd.include(req, resp);`
 - Calling given web component (within application only) to produce partial response.
 - The final response is generated by the current (first) web component itself.
 - Note that new request & response objects are NOT created.
 - In browser, URL is not modified (i.e. client is not aware of navigation).
 - Slower than `RequestDispatcher` "forward".
 - Mostly used for rendering header/footer in dynamic web pages.

State Management

- HTTP is stateless protocol.
- State management is maintaining information of the client.

- Client side state management
 - Cookie
 - QueryString
 - Hidden form fields
 - SessionStorage and LocalStorage -- Java Script.
- Server side state management
 - Session
 - ServletContext
 - Request

Session

- <https://docs.oracle.com/javaee/7/api/javax/servlet/http/HttpSession.html>
- Http Session is used to save data/state of user on server side in form of key-value pair.
- One session is created for each user/client for first call to req.getSession(). The subsequent calls returns the same session object (for that user).

```
HttpSession session = req.getSession();
```

- The data can stored in session as attributes -- (String)key-value(Object) pairs.

```
session.setAttribute("key", value);
```

- This data can be retrieved back (from same user session).

```
value = session.getAttribute("key");
```

- The session data can be destroyed while logout.

```
session.invalidate();
```

Assignment

1. Movie Review System -- Hackathon. Image will be shared on GIT.

SUNBEAM INFOTECH