

Vidyavardhini's College of Engineering & Technology  
Department of Artificial Intelligence and Data Science

|  |
|--|
| Experiment No. 7                                   |
| Implement Booth's algorithm<br>using c-programming |
| Name: Akhilesh Ravindra Patil                      |
| Roll Number: 40                                    |
| Date of Performance:                               |
| Date of Submission:                                |

# Vidyavardhini's College of Engineering & Technology

## Department of Artificial Intelligence and Data Science



## Vidyavardhini's College of Engineering & Technology

### Department of Artificial Intelligence and Data Science

---

Aim: To implement Booth's algorithm using c-programming.

Objective - 1. To understand the working of Booths algorithm.

2. To understand how to implement Booth's algorithm using c-programming.

Theory:


Booth's algorithm is a multiplication algorithm that multiplies two signed binary numbers in 2's complement notation. Booth used desk calculators that were faster at shifting than adding and created the algorithm to increase their speed. The algorithm works as per the following conditions :

1. If  $Q_n$  and  $Q_{n+1}$  are same i.e. 00 or 11 perform arithmetic shift by 1 bit.
2. If  $Q_n Q_{n+1} = 10$  do  $A = A - B$  and perform arithmetic shift by 1 bit.
3. If  $Q_n Q_{n+1} = 01$  do  $A = A + B$  and perform arithmetic shift by 1 bit.

Vidyavardhini's College of Engineering & Technology  
Department of Artificial Intelligence and Data Science

| Multiplicand (B) | 1          | Multiplier (Q) | 100 (4)       |
|------------------|------------|----------------|---------------|
| Steps            |            |                | Operation     |
|                  | 00 00      | 0 1 00         | Initial       |
| Step 1           | 00 00      | 0 0 1          | Shift right   |
| Step 2           | 00 0       | 0 0 0 1        | 0 Shift right |
| step 3           | 1 1        | 0 0 1          |               |
|                  | 1 0<br>1 1 | 1 0 0 0        | Shift right   |
| Step 4 :         | 00 1 0     | 0 0 0          | 1             |
|                  | 00 0       | 0 1 0 0        | Shift right   |
| Result           | 00 0       | = +20          |               |

Vidyavardhini's College of Engineering & Technology  
Department of Artificial Intelligence and Data Science



Program: `#include <stdio.h>`

`#include <math.h>`

`int a = 0, b = 0, c = 0, a1 = 0, b1 = 0, com[5] = { 1, 0, 0, 0, 0};`

`int anum[5] = {0}, anumcp[5] = {0}, bnum[5] = {0};`

`int acomp[5] = {0}, bcomp[5] = {0}, pro[5] = {0}, res[5] = {0};`

`void binary(){`

`a1 = fabs(a);`

`b1 = fabs(b);`

# Vidyavardhini's College of Engineering & Technology

## Department of Artificial Intelligence and Data Science

```
int r, r2, i, temp;
for (i = 0; i < 5; i++){
    r = a1 % 2;
    a1 = a1 / 2;
    r2 = b1 % 2;
    b1 = b1 / 2;
    anum[i] = r;
    anumcp[i] = r;
    bnum[i] = r2;
    if(r2 == 0){
        bcomp[i] = 1;
    }
    if(r == 0){
        acomp[i] = 1;
    }
}
c = 0;
for ( i = 0; i < 5; i++){
    res[i] = com[i]+ bcomp[i] + c;
    if(res[i] >= 2){
        c = 1;
    }
    else
        c = 0;
    res[i] = res[i] % 2;
}
for (i = 4; i >= 0; i--){
    bcomp[i] = res[i];
}
if (a < 0){
```

Vidyavardhini's College of Engineering & Technology  
Department of Artificial Intelligence and Data Science

```
c = 0;
for (i = 4; i >= 0; i--){
    res[i] = 0;
}
for ( i = 0; i < 5; i++){
    res[i] = com[i] + acomp[i] + c;
    if (res[i] >= 2){
        c = 1;
    }
    else
        c = 0;
    res[i] = res[i]%2;
}
for (i = 4; i >= 0; i--){
    anum[i] = res[i];
    anumcp[i] = res[i];
}

}
if(b < 0){
    for (i = 0; i < 5; i++){
        temp = bnum[i];
        bnum[i] = bcomp[i];
        bcomp[i] = temp;
    }
}
}
void add(int num[]){
    int i;
    c = 0;
```

# Vidyavardhini's College of Engineering & Technology

## Department of Artificial Intelligence and Data Science

```
for ( i = 0; i < 5; i++){
    res[i] = pro[i] + num[i] + c;
    if (res[i] >= 2){
        c = 1;
    }
    else{
        c = 0;
    }
    res[i] = res[i]%2;
}
for (i = 4; i >= 0; i--){
    pro[i] = res[i];
    printf("%d",pro[i]);
}
printf(":");
for (i = 4; i >= 0; i--){
    printf("%d", anumcp[i]);
}
}
void arshift(){//for arithmetic shift right
    int temp = pro[4], temp2 = pro[0], i;
    for (i = 1; i < 5 ; i++){//shift the MSB of product
        pro[i-1] = pro[i];
    }
    pro[4] = temp;
    for (i = 1; i < 5 ; i++){//shift the LSB of product
        anumcp[i-1] = anumcp[i];
    }
    anumcp[4] = temp2;
    printf("\nAR-SHIFT: ");//display together
```

# Vidyavardhini's College of Engineering & Technology

## Department of Artificial Intelligence and Data Science

```
        for (i = 4; i >= 0; i--){
            printf("%d",pro[i]);
        }
        printf(":");
        for(i = 4; i >= 0; i--){
            printf("%d", anumcp[i]);
        }
    }

void main(){
    int i, q = 0;
    printf("\t\tBOOTH'S MULTIPLICATION ALGORITHM");
    printf("\nEnter two numbers to multiply: ");
    printf("\nBoth must be less than 16");
    //simulating for two numbers each below 16
    do{
        printf("\nEnter A: ");
        scanf("%d",&a);
        printf("Enter B: ");
        scanf("%d", &b);
    }while(a >=16 || b >=16);

    printf("\nExpected product = %d", a * b);
    binary();
    printf("\n\nBinary Equivalentents are: ");
    printf("\nA = ");
    for (i = 4; i >= 0; i--){
        printf("%d", anum[i]);
    }
    printf("\nB = ");
```



# Vidyavardhini's College of Engineering & Technology

## Department of Artificial Intelligence and Data Science

```
for (i = 4; i >= 0; i--){
    printf("%d", bnum[i]);
}
printf("\nB' + 1 = ");
for (i = 4; i >= 0; i--){
    printf("%d", bcomp[i]);
}
printf("\n\n");
for (i = 0; i < 5; i++){
    if (anum[i] == q){
        printf("\n-->");
        arshift();
        q = anum[i];
    }
    else if(anum[i] == 1 && q == 0){
        printf("\n-->");
        printf("\nSUB B: ");
        add(bcomp);
        arshift();
        q = anum[i];
    }
    else{//add ans shift for 01
        printf("\n-->");
        printf("\nADD B: ");
        add(bnum);
        arshift();
        q = anum[i];
    }
}
```

# Vidyavardhini's College of Engineering & Technology

## Department of Artificial Intelligence and Data Science

```
printf("\nProduct is = ");
for (i = 4; i >= 0; i--){
    printf("%d", pro[i]);
}
for (i = 4; i >= 0; i--){
    printf("%d", anumcp[i]);
}
}
```

Output:

```
Both must be less than 16
Enter A: 2
Enter B: 4
Expected product = 8

Binary Equivalents are:
A = 00010
B = 00100
B'+ 1 = 11100

-->
AR-SHIFT: 00000:00001
-->
SUB B: 11100:00001
AR-SHIFT: 11110:00000
-->
ADD B: 00010:00000
AR-SHIFT: 00001:00000
-->
```

# Vidyavardhini's College of Engineering & Technology

## Department of Artificial Intelligence and Data Science

Conclusion - The aim of the experiment is to implement Booth's algorithm in C programming, a multiplication algorithm that efficiently and effectively multiplies two binary numbers using a sequential approach, reducing the number of partial products and improving computational speed.