

L3 Java Classes & Methods for



T24 Developers

Struggling to extend T24 functionalities?

This document provides a detailed breakdown of L3 Java classes and methods, empowering you to unlock T24's full customization potential.

L3 Java Routines for Version

Class	Routine Types	Java Method	Description
RecordLifecycle	Check ID Routine	checkId()	Hook to validate Record ID. It acts as a user exit to validate ids.
	Check Record Routine	defaultFieldValues()	This Routine check values or default values in the record is displayed to the user.
	Before Unauth Routine	ValidateRecord()	It will be invoked just prior to the final update of files at the unauthorised stage of a transaction.
	After Unauth Routine	updateLookupTable() and postUpdateRequest()	Basically, it acts as a user exiting from the screen and it is called after unauthorised-record-commit.
	Before Auth Routine	updateLookupTable() and updateCoreRecord()	It will be invoked just prior to the final update of files at the authorised stage of a transaction.
	After Auth Routine	updateLookupTable() and updateCoreRecord()	It will be invoked just prior to the final update of files at the authorised stage of a transaction.
	Default Routine	defaultFieldValues()	Record level hook to check values or default values in the core fields before the record is displayed to the user.

L3 Java Routines for ENQUIRY

Class	Routine Types	Java Method	Description
Enquiry	Build Routine	setFilterCriteria()	Modifying the dynamic selection box. The routine should update the parameter. Used to manipulate the 'Selection Criteria Box'.
	Conversion Routine	setValue() and setRecord()	Conversion Routine helps us to manipulate data in a field prior to display. Routine should be attached with @.
	NoFile Routine	SetIds()	It is used to generate records with the help of different applications .

L3 Java Routines for Activity Api

Class	Routine Types	Java Method	Description
ActivityLifecycle	Pre Routine	defaultFieldValues() and defaultFieldValuesInvoker()	Triggered before core validation of the record. The Pre Routine will be triggered before the required Action is triggered.
	Post Routine	defaultFieldValues() and defaultFieldValuesInvoker()	Triggered after the defined action takes place.
	Record Routine	defaultFieldValues() and defaultFieldValuesInvoker()	The Record Routine will be triggered when the given property is read before the action processing. Triggered when record opens.
	Pre Validation Routine	defaultFieldValues() and defaultFieldValuesInvoker()	Triggered before core validation of the record.
	Validation Routine	ValidateRecord() And validateRecordInvoker()	Validate routine will get triggered after core validation is complete.

L3 Java Routines for TSA Services

Class	Routine Types	Java Method	Description
ServiceLifecycle	SELECT routine	getIds()	This interface enables the implementer to return a list of Ids to the process, the RECORD routine (process/inputRecord) will then be invoked on all the ids in the list. This interface is invoked from BATCH.JOB.CONTROL in place of the SELECT routine BATCH.BUILD.LIST will be invoked for the prepared list of Ids. The EB.API hook used by this interface is BATCH.JOB.NAME.SELECT.HOOK.
	RECORD routine	updateRecord()	This interface enables the developer to update the records of any table and update will be attempted before control is returned to the service dispatcher BATCH.JOB.CONTROL. The EB.API hook used by this interface is BATCH.JOB.NAME.HOOK. The T24 field specifying the job name is the JOB.NAME field in BATCH.

