



VENDING MACHINE WORKING

AN EASY MANUAL FOR LAYMAN



NOVEMBER 29, 2025

AUTHOR: DILAWER KHAN

Table of Contents

How It Works: The Anatomy of a Vending Machine	3
Introduction	3
1. The User Interface (The Face)	3
A. The Input Mechanism (Keypad & Touchscreen).....	3
B. The Display System (The Feedback Loop).....	4
C. The Secure Window (Visibility & Protection).....	4
D. Accessibility Features	4
2. Payment and Authentication (The Wallet)	5
A. The Coin Validator (The "Bouncer")	5
B. The Bill Validator (The Scanner).....	5
C. Cashless Payment (Telemetry).....	6
3. The Central Control Unit (The Brain)	6
A. The VMC (Vending Machine Controller) Board	6
B. The Communication Language: MDB (Multi-Drop Bus)	7
C. The Logic Workflow (The Decision Tree)	7
D. The Accountant (DEX System)	8
4. Storage and Environment (The Shelf)	8
A. The Tray and Column System (The Warehouse)	8
B. The Refrigeration Deck (The Climate Control).....	9
C. Insulation (The Thermos Effect).....	9
5. Product Dispensing (The Muscle)	9
A. The Motor Assembly (The Driver).....	9
B. The Spiral Coil (The Auger).....	10
C. The Drop (Gravity's Role)	10
D. Specialized Mechanisms (For Fragile Items).....	10
6. Verification and Delivery (The Eyes)	11
A. The Drop Sensor System (The Invisible Net).....	11
B. The Logic (Did it Fall?)	11
C. The Retry and Refund Protocol.....	11
D. The Delivery Bin (Anti-Theft Mechanics).....	12
7. Power and Maintenance	12
A. The Power Supply Unit (The Transformer)	12

B. The Service Mode (The Technician's Interface)	12
C. Energy Efficiency (Green Technology)	13
D. Physical Security (The Vault)	13
Summary of the Workflow	13

The Anatomy of a Vending Machine

Introduction

A vending machine is essentially an automated retail store contained within a single cabinet. It combines precise mechanical engineering, sophisticated sensor technology, and computer logic to perform a complex exchange—accepting money and delivering a product—in a matter of seconds. This document breaks down the machine into its seven core systems to explain exactly what happens behind the glass.

The User Interface (The Face)

The User Interface (UI) serves as the bridge between the human customer and the machine's internal computer. It is responsible for two main tasks: capturing the user's intent (Input) and providing status updates (Output).

A. The Input Mechanism (Keypad & Touchscreen)

While it looks like a simple set of buttons, the input mechanism is designed for extreme durability and weather resistance.

- **The Matrix Keypad (Standard Buttons):**
 - **How it works:** Most traditional vending machines use a "membrane switch" system. Underneath the plastic buttons, there is a grid of wires (rows and columns).
 - **The "Battleship" Logic:** The computer doesn't have a separate wire for every single button. Instead, it monitors the grid. When you press "A," it connects Row 1 and Column 1. When you press "B," it connects Row 1 and Column 2. The computer detects which intersection was touched to identify the selection.
 - **Durability:** These keypads are often sealed to prevent spilled soda or rain (in outdoor machines) from damaging the electronics.
- **Capacitive Touchscreens (Modern Machines):**
 - Newer machines use screens similar to a smartphone. These screens detect the electrical charge from your fingertip. They allow for "digital shopping carts," letting users buy multiple items in one transaction—something standard keypads cannot easily do.

B. The Display System (The Feedback Loop)

The display screen is the machine's voice. It prevents confusion by confirming every step of the transaction.

- **Vacuum Fluorescent Displays (VFD):**
 - In classic machines, you often see glowing green or blue text. These are VFDs. They are preferred because they are incredibly bright and readable even in direct sunlight or total darkness.
- **LCD & LED Screens:**
 - Modern machines use LCD monitors to play advertisements or nutritional information.
- **The "Attract Mode":**
 - When the machine is idle, the computer runs a specific software loop called "Attract Mode." It flashes the lights or scrolls a "Have a Coke" message to catch a passerby's eye. As soon as a button is pressed or a coin is inserted, the software switches to "Transaction Mode."

C. The Secure Window (Visibility & Protection)

The clear front of a vending machine is an engineering marvel that balances visibility with high security.

- **Polycarbonate (Lexan) vs. Glass:**
 - Most "glass" fronts are actually **Polycarbonate** (often branded as Lexan). This is a transparent thermoplastic that is roughly 250 times stronger than glass. It is virtually shatterproof; if someone hits it with a hammer, it may bounce back or dent, but it will not shatter into dangerous shards.
- **Thermal Insulation (Double Glazing):**
 - For machines serving cold drinks, the window is usually **double-paned**.
 - **Argon Gas Fill:** The space between the two panes is often filled with Argon gas or is a vacuum. This acts as an insulator, preventing the outside heat from entering the cabinet and preventing condensation (fog) from forming on the glass, which would hide the products.

D. Accessibility Features

Standard vending design now includes features for differently-abled users, often mandated by law (like the ADA in the US).

- **Braille Identifiers:** Raised Braille dots are located next to the button selection or the coin slot.

- **Height Standards:** The "functional reach" zone ensures that buttons, coin slots, and the retrieval bin are located at a height accessible to someone sitting in a wheelchair (usually between 15 and 48 inches off the ground).
-

Payment and Authentication (The Wallet)

This section is the "security guard" of the machine. Its primary goal is to accept valid currency while rigorously rejecting slugs, washers, foreign coins, and photocopied bills.

A. The Coin Validator (The "Bouncer")

The coin mechanism (often called a "Coin Mech") is a mini-laboratory that performs multiple physics experiments on a coin in the fraction of a second it takes to fall through.

- **Step 1: The Size Check (Physical Sorting)**
 - **The Sieve:** The slot is the first line of defense. It is sized exactly to the largest accepted coin. Anything larger won't fit.
 - **Lasers/Light Beams:** As the coin enters, it breaks a light beam. The machine measures exactly how long the beam is broken to calculate the coin's diameter.
- **Step 2: The "Secret Handshake" (Electromagnetic Signature)**
 - **The Science:** This is how the machine detects fakes. Inside the chute are copper coils (inductors) that generate a magnetic field.
 - **The Test:** When a metal coin passes through this field, it disturbs it. This disturbance creates a unique electrical feedback known as an **"Electromagnetic Signature."**
 - **Materials Matter:** A quarter is made of a specific mix (Cupro-nickel). A steel washer or a plastic token has a completely different chemical structure. If the "signature" of the dropped item doesn't perfectly match the database of valid coins, the machine knows it is a fake—even if it is the exact same size as a quarter.
- **Step 3: Sorting and Change**
 - **Active Routing:** If the coin is valid, a small gate (solenoid) snaps open to guide it into the "Cash Box" (for profit) or into a "Coin Tube" (to be used later as change for other customers).
 - **Rejection:** If the sensor data fails any test, the gate remains closed, and the coin slides down the rejection path to the return tray.

B. The Bill Validator (The Scanner)

Handling paper money is harder because bills can be wrinkled, torn, or faded. The Bill Validator uses technology similar to a relentless photocopier.

- **Optical Scanning (The Eyes):**

- As you feed the bill, motorized rollers pull it in at a constant speed.
- **UV and IR Light:** The machine shines Ultraviolet (UV) and Infrared (IR) light through the paper. It looks for specific contrasts, watermarks, and paper density that normal photocopiers cannot reproduce.
- **Magnetic Heads (The Touch):**
 - Real currency (especially USD) is printed with **magnetic ink** (ferromagnetic ink).
 - The validator runs a magnetic head (similar to an old cassette tape player) over the bill to detect the iron in the ink. If you print a fake bill on your home printer, it will lack this magnetic property, and the machine will spit it out.

C. Cashless Payment (Telemetry)

When you swipe a card or use Apple Pay, the machine acts as a communication hub.

- **The MDB (Multi-Drop Bus):** This is the internal language the card reader uses to talk to the vending machine's computer.
- **The Process:**
 1. **Encryption:** The reader encrypts your card info.
 2. **Telemetry:** It uses a built-in cellular modem (like a mini smartphone) to send a signal to a payment server.
 3. **Authorization:** The bank confirms you have \$2.00.
 4. **The Signal:** The server sends a "Credit Approved" signal back to the machine, which effectively "inserts" virtual money into the computer's logic.

How Vending Machines Detect Fake Coins: <https://www.youtube.com/watch?v=jrmqy70EOFY>

The Central Control Unit (The Brain)


If the motors are the muscle and the sensors are the eyes, the **Vending Machine Controller (VMC)** is the brain. It is a specialized computer circuit board that coordinates every action the machine takes.

A. The VMC (Vending Machine Controller) Board

Physically, this is a printed circuit board (PCB) usually located inside the door or in a protected metal box within the cabinet. It doesn't run Windows or macOS; it runs specialized "embedded" software designed for reliability and speed.

- **The Hub:** Every component connects here. The keypad, the coin mechanism, the card reader, and every single motor all have wires running back to this one board.

- **The Processor:** A microcontroller (a small, low-power computer chip) constantly scans these wires for signals. It cycles through a "loop" thousands of times a second, asking: *Is a button pressed? Is money inserted? Is the door open?*



B. The Communication Language: MDB (Multi-Drop Bus)

Before the 1990s, every vending machine manufacturer used different plugs and wiring. Today, they use a universal standard called **MDB**.

- **What is it?** Think of MDB like "USB" for vending machines. It allows you to plug a coin mechanism from Brand A into a machine from Brand B, and they will understand each other perfectly.
- **Master/Slave Relationship:**
 - The **VMC is the Master**.
 - The **Coin Mech, Card Reader, and Bill Validator are Slaves**.
 - The VMC constantly polls the slaves ("Do you have money?"). The slaves cannot speak unless spoken to. This prevents data collisions and ensures the computer is always in charge.

C. The Logic Workflow (The Decision Tree)

When you press "B4", the VMC performs a rapid logic check before moving a muscle:

1. **Price Check:** It looks up the price of B4 in its memory (e.g., \$1.50).
2. **Credit Check:** It compares the price to the "Credit" variable (money currently inserted).
 - *If Credit < Price:* It sends a signal to the display: "Please Insert More Cash."
 - *If Credit ≥ Price:* It proceeds.
3. **Inventory Check:** It checks the virtual counter for coil B4.

- *If Count = 0*: It displays "Sold Out."
 - *If Count > 0*: It proceeds to dispense.
4. **Execution:** It sends a specific voltage (usually 24 Volts DC) to the motor at position B4.

D. The Accountant (DEX System)

The VMC doesn't just sell things; it keeps the books. This feature is called **DEX (Data Exchange)**.

- **The "Black Box" Recording:** The VMC records exactly what was sold and when. It knows that 5 Cokes and 2 Snickers were sold today.
 - **Data Retrieval:** When the route driver comes to refill the machine, they plug a handheld computer into a jack on the VMC (or use Bluetooth). The machine instantly uploads its sales history to the driver's device. This tells the vending company exactly how much cash should be in the box and what products need refilling, preventing theft and waste.
-

Storage and Environment (The Shelf)

This section covers how the machine stores hundreds of items of varying shapes and sizes while keeping drinks cold and chocolate from melting.

A. The Tray and Column System (The Warehouse)

The interior of a vending machine is modular. It is designed to be rearranged based on what products are being sold.

- **The Tilted Trays:** The shelves (trays) inside are not perfectly flat; they are often angled slightly downward toward the glass. This ensures that the products are always sliding toward the dispensing point and are clearly visible to the customer.
- **Adjustable "Pitch" (The Spirals):**
 - The metal coils (spirals) come in different sizes, known as "pitch."
 - **Small Pitch:** A coil with tight loops (e.g., 6 items per turn) is used for thin items like candy bars.
 - **Large Pitch:** A coil with wide loops (e.g., 4 items per turn) is used for thick items like bags of chips.
 - If a vendor switches from selling Snickers to Potato Chips, they simply swap the coil without needing a new motor.
- **Dual-Coil Motors:** For very wide items (like a large pastry or a boxed meal), two motors are electronically paired to turn two spirals simultaneously, pushing the item forward evenly from both sides so it doesn't twist and jam.

B. The Refrigeration Deck (The Climate Control)

For machines that sell cold sodas or perishable foods, the entire bottom section is a self-contained refrigerator.

- **The "Deck" Concept:**
 - Unlike a home fridge where the cooling coils are built into the walls, a vending machine uses a "slide-out deck." The Compressor, Condenser, and Evaporator fan are all mounted on one metal sled at the very bottom of the machine.
 - **Maintenance:** If the fridge breaks, a technician doesn't fix it on-site. They simply pull out the old deck and slide in a new one in 5 minutes, taking the broken one back to the shop for repairs.
- **Airflow Circulation:**
 - **The Plenum:** There is a hollow space (air duct) running up the back of the machine cabinet.
 - **The Cycle:** The fan at the bottom pushes cold air up this back duct. The air exits through vents at each shelf level, flowing over the products. As the air warms up, it sinks to the front/bottom of the cabinet, where it is sucked back into the deck to be re-cooled. This ensures the top shelf is just as cold as the bottom shelf.

C. Insulation (The Thermos Effect)

To keep electricity costs low, the cabinet acts like a giant cooler.

- **Polyurethane Foam:** The walls of the machine are injected with high-density polyurethane foam. This foam hardens to add structural strength to the cabinet and provides excellent thermal insulation.
- **Gaskets:** The door is lined with a magnetic rubber gasket (just like your home fridge) that creates an airtight seal when the door is locked, preventing cold air from leaking out.

Product Dispensing (The Muscle)

This section explains the mechanical action that physically moves the product from the shelf to the user. It relies on a combination of torque, precise timing, and simple gravity.

A. The Motor Assembly (The Driver)

Behind every single snack row sits a dedicated motor. However, this isn't just a simple motor like you'd find in a toy car; it is a **Geared Motor Unit**.

- **High Torque, Low Speed:**

- The motor runs on 24 Volts DC.
- It connects to a **Gearbox**—a set of plastic gears that slows down the spinning speed but massively increases the strength (torque). This allows a small, weak motor to push a heavy bottle of water or a large bag of chips without stalling.
- **The "Home" Switch (Stopping on Time):**
 - How does the motor know to stop after exactly one full turn? It doesn't use a timer.
 - Inside the motor casing, there is a physical switch riding on a cam. When the motor completes a 360-degree rotation, the switch falls into a notch on the cam. This physical "click" cuts the power or signals the computer to stop the motor immediately. This ensures the coil is always perfectly aligned for the next sale.

B. The Spiral Coil (The Auger)

The spiral wire is essentially an "Archimedes Screw"—an ancient machine used to pump water, adapted here to move snacks.

- **The Grip:** The product sits inside the "valleys" of the spiral. The coil holds the product in place, preventing it from sliding forward or backward during vibrations.
- **The Push:** As the motor turns the coil, the spiral rotates. Because the coil is anchored at the back, the rotational force is converted into linear motion. The spiral acts like a moving wall, slowly nudging the product forward toward the edge of the shelf.

C. The Drop (Gravity's Role)

- **The Tipping Point:** The shelf ends just a few inches before the glass front. Once the coil pushes the product's center of gravity past the edge of the shelf, physics takes over.
- **The Fall:** The product tumbles into the "delivery chute"—a wide space between the shelves and the glass window—and lands in the retrieval bin at the bottom.

D. Specialized Mechanisms (For Fragile Items)

For machines selling glass bottles or tech gadgets, dropping them 4 feet is not an option. These machines use robotic systems.

- **The X-Y Axis Robotic Arm:**
 - Instead of coils, the machine uses a "picker" cup.
 - **Movement:** The picker moves Left/Right (X-axis) and Up/Down (Y-axis) on rails, powered by belts and stepper motors.
 - **The Process:** The arm travels to the specific coordinate (e.g., Row C, Column 5), opens a small gate, grabs the bottle, carries it gently down to the retrieval port, and releases it. This prevents shaking (vital for carbonated sodas) and breaking.
-

Verification and Delivery (The Eyes)

This section covers the "satisfaction guarantee" technology. In older machines, if a bag of chips got stuck, you lost your money. Modern machines use invisible light beams to ensure you get what you paid for, or you get your money back.

A. The Drop Sensor System (*The Invisible Net*)

Located inside the delivery bin—the box at the bottom where you retrieve your item—is a sophisticated sensor array often branded as "SureVend," "iVend," or "Golden Eye."

- **Infrared (IR) Technology:**
 - **Transmitters:** On one side of the delivery bin wall, there is a row of LED lights that emit Infrared light (invisible to the human eye).
 - **Receivers:** On the opposite wall, there is a row of sensors (photodetectors) waiting to catch that light.
 - **The Grid:** These sensors create a continuous "net" or grid of invisible beams across the top of the retrieval box. Under normal idle conditions, the beams flow uninterrupted from one side to the other.

B. The Logic (*Did it Fall?*)

The computer monitors these beams 24/7. Here is the step-by-step logic used during a vend cycle:

1. **Monitoring:** The computer activates the motor for the selected item (e.g., A1).
2. **Detection:** It waits for a split-second interruption in the IR beam.
 - **Success:** When the heavy snack falls through the beam, it blocks the light for a fraction of a second. The sensor reports "Beam Broken" to the computer. The computer concludes "Sale Complete" and finalizes the transaction (collecting the money).
 - **Failure:** If the motor turns a full rotation but the light beam is *never broken*, the computer knows the product is stuck on the coil.

C. The Retry and Refund Protocol

If the sensor detects a failure (no drop), it triggers an automatic recovery sequence:

- **The "Jiggle" (Retry):** The computer commands the motor to turn slowly by small increments—usually 1/4 or 1/2 of a turn—and then reverse slightly. This shaking motion is designed to dislodge a bag of chips that might be hanging by a corner.
- **The Refund:** If the beams remain unbroken after the retry attempt, the computer assumes a total jam. It:
 1. Stops the motor to prevent damage.
 2. Restores the user's credit (the money is not deducted).
 3. Displays a message: "Selection Failed. Please Try Another Item."

D. The Delivery Bin (Anti-Theft Mechanics)

The physical box where you grab your item is designed with security in mind.

- **The Trap Door (The Hopper):**
 - The door you push inward to reach your snack is mechanically linked to a secondary internal flap.
 - **Anti-Fishing:** When you push the outer door *in* to reach your hand inside, the internal flap lifts *up* to seal off the chute where the products fall from. This prevents thieves from reaching their arm up the chute to pull down products from the bottom shelf.
-

Power and Maintenance

This final section explains the "life support" systems of the machine—how it powers its components, saves energy, and ensures safety for both the user and the technician.

A. The Power Supply Unit (The Transformer)

A vending machine plugs into a standard wall outlet (110V or 220V AC), but its internal components cannot handle that much raw power.

- **The Transformer/PSU:** A heavy box usually located at the bottom of the cabinet. It acts as an electrical refinery.
- **Voltage Conversion:** It takes the high-voltage AC from the wall and converts it into two main streams of low-voltage Direct Current (DC):
 - **24 Volts DC:** This "high power" stream runs the motors, the coin mechanism solenoids, and the bill validator motors.
 - **5 Volts DC:** This "low power" stream runs the delicate computer brain (VMC), the sensors, and the display screen.

B. The Service Mode (The Technician's Interface)

When a route driver opens the door, they need to communicate with the machine without buying a snack.

- **The Door Switch (Interlock):**
 - Located on the frame of the machine, this is a plunger switch (like on a refrigerator door).
 - **Safety:** When the door opens, the plunger pops out. In older machines, this cuts power to the motors to prevent the technician from getting their fingers pinched in a moving coil.
 - **Service:** The technician can pull the switch out manually to restore power while the door is open, allowing them to test the motors.
- **The Service Keypad:** Inside the door, there is often a secondary mini-keypad. Technicians use this to:

- **"Prime" a motor:** Turn a specific coil just enough to refill it properly.
- **Check Temperature:** See the exact reading of the internal thermometer.
- **Reset Errors:** Clear "Motor Jammed" alerts after fixing a stuck bag.

C. Energy Efficiency (Green Technology)

Modern machines are designed to burn less electricity than a household lightbulb when idle.

- **LED Lighting:** Old machines used fluorescent tubes that flickered and buzzed. New machines use LED strips that consume 70% less energy and produce less heat (which helps the refrigerator work less).
- **Intelligent Sleep Mode:**
 - The VMC tracks sales patterns. If the machine learns that nobody buys coffee between 3 AM and 6 AM, it can enter a "Low Power Mode."
 - It dims the lights and allows the refrigeration temperature to rise slightly (within safe limits) to save compressor cycles, then cools back down right before the morning rush.

D. Physical Security (The Vault)

A vending machine is essentially a safe full of cash left in public.

- **The T-Handle Lock:** The shiny handle on the front is a "T-Handle." When locked, the handle screws into a threaded rod inside the cabinet, pulling the door tight against the gasket.
- **Drill-Proof Cylinders:** The keyhole uses a tubular lock (circular key) designed to be difficult to pick or drill out.
- **The Cash Cage:** Inside, the bill validator stacks the paper money into a "stacker box." In high-risk areas, this box is encased in a secondary steel cage, so even if thieves break the glass, they cannot easily rip the cash box out.

Summary of the Workflow

1. **Selection:** User presses buttons; Computer checks price.
2. **Payment:** User inserts cash/card; Sensors validate it; Computer holds credit.
3. **Action:** Computer powers the specific motor; Coil turns.
4. **Delivery:** Item falls; Drop sensors confirm the fall.
5. **Completion:** Computer clears the transaction; Change is dispensed if necessary.

flowchart visualization of this process

