

Performance Evaluation of Post-Quantum Cryptographic Algorithms on C-V2X Sidelink Communications

Akid Abrar, *Student Member, IEEE*, Sagar Dasgupta, *Senior Member, IEEE*, Abdullah Al Mamun, *Student Member, IEEE*, Mizanur Rahman, *Senior Member, IEEE*, Mashrur Chowdhury *Senior Member, IEEE*, and Ahmad Alsharif, *Senior Member, IEEE*

Abstract—Wireless connectivity, such as Cellular-Vehicle-to-Everything (C-V2X), between vehicles and transportation infrastructure promises significant roadway safety benefits by providing 360-degree views of their surroundings. However, wireless connectivity in intelligent transportation systems is vulnerable to deliberate cyber threats. Security of wireless connectivity relies on traditional cryptographic techniques as specified in the IEEE 1609.2 standard. The anticipated advent of quantum computing can compromise this cryptographic foundation. Post-quantum cryptographic (PQC) algorithms offer quantum-resistant alternatives. However, the significantly larger size of PQC signatures and public keys poses a challenge to meet communication latency for safety-critical transportation applications. This study conducts a comprehensive evaluation of standardized PQC algorithms on C-V2X sidelink performance to assess the feasibility of implementing PQC in safety-critical transportation applications. C-V2X sidelink key performance indicators (KPIs), including packet delivery ratio (PDR), end-to-end latency, channel busy ratio (CBR), and resource utilization, are compared across PQC algorithms at varying levels of service at an urban roadway intersection to confirm their applicability.

Index Terms—C-V2X, post-quantum cryptography, sidelink, Mode 4, Falcon-512, ECDSA, IEEE 1609.2, SAE J3161, vehicle-to-everything

I. INTRODUCTION

CELLULAR Vehicle-to-Everything (C-V2X) communication enables vehicles to exchange safety-critical messages such as Basic Safety Messages (BSMs) over the PC5 sidelink interface at 10 Hz, providing each vehicle with a 360-degree awareness of its surrounding traffic environment [1]. The C-V2X Mode 4 sidelink, standardized by 3GPP in Release 14 and profiled for deployment by SAE J3161 [2], operates without cellular infrastructure by allowing vehicles to autonomously select radio resources through a sensing-based Semi-Persistent Scheduling (SPS) mechanism. This

infrastructure-independent operation makes Mode 4 particularly attractive for safety applications in areas such as intersection approaches.

The integrity and authenticity of V2X messages are ensured through digital signatures as specified in the IEEE 1609.2 security standard [3]. Currently, IEEE 1609.2 mandates the Elliptic Curve Digital Signature Algorithm (ECDSA) with the NIST P-256 curve, which produces compact 64-byte signatures and 65-byte public keys. These sizes impose minimal overhead on the sidelink transport block, and the V2X ecosystem, including the Security Credential Management System (SCMS) [4], which has been designed around these compact parameters.

However, the anticipated emergence of cryptographically relevant quantum computers poses a fundamental threat to elliptic-curve-based cryptography. Shor's algorithm [5] can solve the elliptic curve discrete logarithm problem in polynomial time, rendering ECDSA insecure. While the timeline for such quantum capabilities remains uncertain, the long deployment lifecycle of transportation infrastructure (15–20 years for vehicles and roadside equipment) demands proactive migration planning [6]. The National Institute of Standards and Technology (NIST) has responded by standardizing post-quantum cryptographic (PQC) algorithms resistant to quantum attacks, including lattice-based digital signature schemes such as ML-DSA (Dilithium, FIPS 204) [7] and FN-DSA (Falcon, FIPS 206) [8].

The central challenge in adopting PQC for V2X lies in the significantly larger signature and public key sizes of post-quantum algorithms. Falcon-512, the most compact NIST PQC signature scheme, produces signatures of 666 bytes (padded) and public keys of 897 bytes, an order of magnitude larger than ECDSA. Dilithium-2 is even larger, with 2420-byte signatures and 1312-byte public keys. These inflated sizes directly increase the Secure Protocol Data Unit (SPDU) payload that must be accommodated within the C-V2X sidelink transport block, which is constrained by the Message Coding Scheme (MCS) index, subchannel allocation, and congestion control parameters mandated by SAE J3161 [?]. Whether the sidelink can accommodate this overhead without degrading safety-critical KPIs such as packet delivery ratio and latency remains an open question that we aim to address in this study. Existing studies on PQC in vehicular contexts have focused primarily on computational benchmarking on embedded hardware [9] or on abstract protocol-level analysis without considering the

Akid Abrar, Sagar Dasgupta, and Mizanur Rahman are with the Department of Civil, Construction & Environmental Engineering, The University of Alabama, Smart Communities and Innovation Building (SCIB), 28 Kirkbride Lane, Tuscaloosa, AL 35487-0288 USA (emails: aabrar@crimson.ua.edu; sadasgupta@ua.edu; mizan.rahman@ua.edu).

Ahmad Alsharif is with the Department of Computer Science, The University of Alabama, 3016 Cyber Hall, Box: 870290, Tuscaloosa, AL 35487-0288 USA (email: aalsharif1@ua.edu).

Abdullah Al Mamun and Mashrur Chowdhury are with the Glenn Department of Civil Engineering, Clemson University, Clemson, SC 29634 USA. (emails: abdullm@clemson.edu; mac@clemson.edu).

Copyright (c) 20xx IEEE. Personal use of this material is permitted. However, permission to use this material for any other purposes must be obtained from the IEEE by sending a request to pubs-permissions@ieee.org.

radio resource constraints of the C-V2X physical layer. To the best of the authors' knowledge, no prior work has evaluated the end-to-end impact of PQC digital signatures on C-V2X Mode 4 sidelink performance within a standards-compliant simulation environment that models the full protocol stack from application-layer signing through MAC-layer resource allocation to physical-layer transmission. The key contributions of this study are as follows:

- This study presents the first implementation and evaluation of NIST-standardized PQC digital signature algorithms within a C-V2X PC5 Mode 4 sidelink simulation that maintains compliance with SAE J3161 deployment parameters and IEEE 1609.2 security standards.
- A feasibility assessment is conducted to determine whether PQC algorithms can be adopted without modifications to the application layer (e.g., packet segmentation or hybrid cryptographic schemes) or to the lower-layer radio resource configuration (e.g., MCS adaptation beyond the J3161-specified range).
- A cross-layer performance evaluation quantifies the impact of PQC signature and public key overhead on sidelink KPIs, including PDR, signature generation and verification time, end-to-end latency, CBR, and subchannel resource utilization.
- Multiple urban intersection scenarios with varying vehicle densities (levels of service) are evaluated to identify the density thresholds at which PQC-induced overhead begins to degrade sidelink performance relative to the ECDSA baseline.

The remainder of this paper is organized as follows. Section II provides background on C-V2X Mode 4 sidelink and security standards along with PQC algorithms. Section III reviews related work. Section IV describes the simulation methodology and setup. Section V presents the evaluation outcomes. Section VI discusses the findings and their implications, and Section VII concludes the paper.

II. BACKGROUND

A. C-V2X Mode 4 and SAE J3161

C-V2X is a 3GPP-standardized radio access technology that enables direct vehicle-to-vehicle (V2V) and vehicle-to-infrastructure (V2I) communication over the PC5 sidelink interface without requiring cellular network infrastructure [10]. The PC5 interface operates in the 5.9 GHz Intelligent Transportation Systems (ITS) band and supports two transmission modes: Mode 3, where a base station schedules sidelink resources, and Mode 4, where vehicles autonomously select resources using a sensing-based Semi-Persistent Scheduling (SPS) mechanism [1].

In Mode 4, each vehicle monitors the sidelink spectrum over a sensing window of 1000 ms and identifies candidate single-subframe resources within a selection window. Resources whose received power exceeds a threshold (Reference Signal Received Power, RSRP) are excluded from the candidate set. The vehicle then randomly selects a resource from the remaining candidates and reserves it for a configurable Resource Reservation Interval (RRI). A reselection counter determines

how many consecutive transmissions use the reserved resource before triggering a new selection [11]. At each reselection event, the vehicle retains the current resource with a probability p_{keep} (typically 0.0, 0.2, 0.4, 0.6, or 0.8) or selects a new resource from the updated candidate set.

The transmission payload is carried on the Physical Sidelink Shared Channel (PSSCH), while the associated Sidelink Control Information (SCI) is transmitted on the Physical Sidelink Control Channel (PSCCH). Adjacent PSCCH–PSSCH mapping is typically employed, where control and data subchannels occupy contiguous resource blocks within the same subframe. The Modulation and Coding Scheme (MCS) applied to the PSSCH determines the transport block size and, consequently, the maximum payload that can be accommodated within a given number of subchannels.

SAE J3161 [2] specifies the deployment profile for C-V2X V2V communication in the 5.9 GHz band. It mandates a 10 MHz channel bandwidth corresponding to 50 resource blocks per subframe, a subchannel size of 10 or 20 resource blocks, and an RRI of 100 ms aligned with the Basic Safety Message (BSM) generation rate specified in SAE J2945/1. The standard further defines congestion control through Channel Busy Ratio (CBR) monitoring and specifies MCS ranges and maximum subchannel allocations as a function of measured CBR. These constraints collectively determine the maximum packet size that the sidelink can carry, which directly impacts the feasibility of deploying cryptographic algorithms with large signature and key sizes.

B. Post-Quantum Cryptography

Current V2X security, as specified in IEEE 1609.2 [3], relies on the Elliptic Curve Digital Signature Algorithm (ECDSA) with the NIST P-256 curve for message authentication. An ECDSA P-256 signature is 64 bytes (raw $r||s$ format), and the corresponding public key is 65 bytes (uncompressed point), resulting in modest overhead that is readily accommodated within the sidelink transport block [3].

The anticipated advent of large-scale quantum computers threatens to break ECDSA and other elliptic-curve-based schemes through Shor's algorithm [5]. In response, the National Institute of Standards and Technology (NIST) conducted a multi-year standardization process and selected several post-quantum cryptographic algorithms for standardization [12]. Among the digital signature schemes, two are particularly relevant to V2X applications:

ML-DSA (Dilithium). ML-DSA, formerly known as CRYSTALS-Dilithium, is a lattice-based digital signature scheme standardized as FIPS 204 [7]. At security level 2, Dilithium-2 produces signatures of 2420 bytes with a public key of 1312 bytes. While Dilithium offers strong security guarantees and deterministic signing, its signature and key sizes are substantially larger than ECDSA.

FN-DSA (Falcon). FN-DSA, formerly known as Falcon, is a lattice-based signature scheme based on NTRU lattices and fast Fourier sampling, standardized as FIPS 206 [8]. Falcon-512 produces compact signatures of approximately 649–666 bytes (variable length) with a public key of 897 bytes.

Falcon offers the smallest combined signature and key size among the NIST-selected PQC signature schemes, making it the most promising candidate for bandwidth-constrained applications such as V2X sidelink.

Table I summarizes the signature and public key sizes for the three algorithms evaluated in this study.

TABLE I
CRYPTOGRAPHIC ALGORITHM PARAMETER SIZES

Algorithm	Signature (B)	Public Key (B)	Security Level
ECDSA P-256	64	65	Classical 128-bit
Falcon-512	649–666	897	NIST Level 1
Dilithium-2	2420	1312	NIST Level 2

III. RELATED WORK

Prior research related to this study can be categorized into three areas: (1) C-V2X Mode 4 sidelink performance evaluation, (2) V2X security and IEEE 1609.2 authentication overhead, and (3) post-quantum cryptography for vehicular and IoT systems.

A. C-V2X Mode 4 Performance Evaluation

Several studies have evaluated the performance of LTE-V2X Mode 4 sidelink communication through analytical modeling and simulation. Gonzalez-Martin et al. [13] developed analytical models to characterize Mode 4 PDR as a function of vehicle density, demonstrating that the SPS mechanism can sustain high reliability at low-to-moderate densities but degrades under congestion due to persistent packet collisions. Bazzi et al. [14] compared IEEE 802.11p and LTE-V2V performance, showing that C-V2X achieves superior range and reliability under highway scenarios. McCarthy et al. [15] introduced openCV2X, the first open-source Mode 4 simulation model built on SimuLTE and OMNeT++, and demonstrated its cross-layer fidelity for evaluating aperiodic traffic patterns. Toghi et al. [16] analyzed Mode 4 performance under highly congested conditions, highlighting the role of CBR-based congestion control in maintaining channel stability. These studies collectively establish the baseline performance characteristics of Mode 4 sidelink; however, none of them incorporate the impact of cryptographic overhead on sidelink KPIs.

B. V2X Security and Authentication Overhead

The IEEE 1609.2 standard [3] defines the security services for V2X, including ECDSA-based digital signatures and a certificate management framework. Qu et al. [17] provided a comprehensive review of VANET security challenges, identifying message authentication as a key bottleneck for high-frequency BSM transmission. Brecht et al. [4] described the SCMS architecture for V2X certificate management in the United States, noting that the system was designed around the compact size of ECDSA P-256 credentials. Lu et al. [18] surveyed security and privacy for 5G V2X, emphasizing that any migration to new cryptographic primitives must satisfy the strict latency requirements of safety-critical applications.

While these works thoroughly address the security architecture, they do not evaluate the radio resource impact of alternative cryptographic algorithms on the sidelink physical layer.

C. Post-Quantum Cryptography for Vehicular Systems

The application of PQC to vehicular systems has received growing attention following the NIST standardization process. Fernandez et al. [19] reviewed post-quantum approaches for securing vehicular blockchain systems, identifying Falcon as a promising candidate due to its compact signature size. Kumar et al. [9] benchmarked PQC algorithms on automotive-grade embedded platforms, demonstrating that Falcon-512 signing completes in approximately 0.21 ms and verification in 0.05 ms on ARM processors, while Dilithium-2 exhibits comparable verification times but larger signatures. Hasan et al. [20] proposed a practical post-quantum authentication framework for V2V, evaluating Falcon and Dilithium in terms of computational cost but without modeling their impact on the radio access layer. Shen et al. [21] analyzed PQC signature performance for intelligent transportation systems, providing an implementation-focused review that highlighted the tension between PQC key sizes and the bandwidth limitations of vehicular communication channels. A recent SAE technical paper [22] evaluated PQC feasibility on embedded systems for two-wheeler security, confirming that computational overhead is manageable on modern hardware but leaving radio resource impact unexamined.

D. Research Gap

While existing literature has separately addressed C-V2X Mode 4 sidelink performance, V2X security frameworks, and PQC algorithm benchmarking, no prior study has jointly evaluated these aspects within a single, standards-compliant simulation. Specifically, the impact of PQC signature and key sizes on sidelink radio resource allocation, packet delivery, and latency under realistic SAE J3161 deployment parameters has not been quantified. This study addresses this gap by implementing PQC algorithms within a full-stack C-V2X Mode 4 simulator and evaluating their end-to-end impact on sidelink KPIs across varying traffic densities.

IV. METHODOLOGY

This section describes the simulation framework, the traffic scenarios, the IEEE 1609.2-compliant packet structure, and the KPIs used for evaluation.

A. Simulation Framework

The PC5 Mode 4 network simulation is done using openCV2X [?], which extends SimuLTE [23] for Mode 4 communication. SimuLTE is an open-source C-V2X simulator developed for the OMNeT++ discrete-event simulation platform [24]. openCV2X models the full LTE protocol stack, including the physical layer, MAC layer with Mode 4 SPS resource allocation, RLC, and PDCP layers. The simulator is coupled with Veins [25] for vehicular networking abstractions

and with SUMO (Simulation of Urban MObility) [26] for realistic microscopic traffic simulation.

The sidelink physical layer is configured with a carrier frequency of 5915 MHz in the 5.9 GHz ITS band. The channel bandwidth is 20 MHz, providing 100 resource blocks per subframe in the uplink. A subchannel size of 10 resource blocks is used, yielding 10 subchannels per subframe. The MCS index ranges from 5 to 11, consistent with the SAE J3161 deployment profile. Preconfigured transmission parameters are used, and CBR-based congestion control with channel occupancy ratio (CR) limiting is enabled. Each vehicle transmits at 23 dBm and reserves resources with an RRI of 100 ms. The resource keep probability is set to $p_{\text{keep}} = 0.8$, and the RSSI-based sensing threshold is 9 dB.

The PQC algorithms are implemented using the liboqs library [27], which provides reference implementations of NIST-standardized post-quantum algorithms. ECDSA P-256 is implemented using OpenSSL. Each vehicle and RSU generates a fresh key pair at initialization and performs real-time signing and verification of every BSM, capturing actual computational overhead in the simulation timing.

Table II summarizes the key simulation parameters.

TABLE II
SIMULATION PARAMETERS

Parameter	Value
Carrier frequency	5915 MHz
Channel bandwidth	20 MHz
Number of resource blocks	100 per subframe
Subchannel size	10 RBs
Number of subchannels	10
MCS range	5–11
Transmit power	23 dBm
Resource reservation interval (RRI)	100 ms
Resource keep probability (p_{keep})	0.8
RSSI sensing threshold	9 dB
BSM generation rate	10 Hz (100 ms)
Simulation duration	60 s
Congestion control	CBR-based with CR limiting
HARQ retransmissions	0
Cryptographic library (PQC)	liboqs
Cryptographic library (ECDSA)	OpenSSL
Traffic simulator	SUMO

B. IEEE 1609.2 Compliant Packet Structure

Each transmitted packet follows the IEEE 1609.2 SPDU structure [3]. The SPDU encapsulates a J2735 BSM Part I (BSMcoreData), which contains vehicle position, speed, heading, and other kinematic data totaling 39 bytes per the J2735 standard [28].

The IEEE 1609.2 `Ieee1609Dot2Data` wrapper adds a protocol version, content type, hash algorithm identifier, Provider Service Identifier (PSID), generation time, generation location, and encoding overhead, contributing approximately 28 bytes of fixed overhead. The `SignerIdentifier` field alternates between including the full explicit certificate and a compact `HashedId8` digest (8 bytes), following the certificate inclusion strategy specified in SAE J2945/1 [29]. When the full certificate is included, it comprises a fixed overhead of approximately 105 bytes (version, type, issuer identifier,

validity period, application permissions, and verification key indicator) plus the raw public key of the signing algorithm.

The total SPDU size for each algorithm, when transmitting with a full certificate, is:

$$S_{\text{SPDU}} = S_{\text{hdr}} + S_{\text{BSM}} + S_{\text{sig}} + S_{\text{cert}} \quad (1)$$

where $S_{\text{hdr}} = 28$ bytes is the IEEE 1609.2 header overhead, $S_{\text{BSM}} = 39$ bytes is the BSM payload, S_{sig} is the digital signature size, and $S_{\text{cert}} = 105 + S_{\text{pk}}$ is the certificate size including the raw public key. Table III presents the resulting SPDU sizes.

TABLE III
SPDU SIZES WITH FULL CERTIFICATE

Algorithm	Sig (B)	Cert (B)	Total SPDU (B)
ECDSA P-256	64	170	~301
Falcon-512	666	1002	~1735
Dilithium-2	2420	1417	~3904

C. Traffic Scenario

The traffic scenario models a four-leg signalized urban intersection with two through lanes per approach, generated using SUMO [26]. The four-leg signalized intersection is selected as the evaluation geometry for several reasons. First, it is the most common intersection configuration where two roads cross in the U.S. urban road network [30], representing the standard deployment environment for C-V2X V2V safety applications [2]. Second, a four-leg intersection produces 32 potential vehicle-vehicle conflict points—16 of which are crossing conflicts where vehicle paths intersect at near-right angles—compared to only 9 conflict points at a three-leg intersection [30]. These crossing conflicts are the primary target of V2X safety applications such as Intersection Movement Assist (IMA), making the four-leg geometry the most safety-critical intersection type for evaluating authentication reliability. Third, vehicles arriving from all four approaches converge within mutual communication range simultaneously, producing the highest concentration of concurrent sidelink transmitters and thereby the most demanding test of Mode 4 resource allocation under PQC-induced payload overhead. Additionally, vehicles on perpendicular approaches experience NLOS propagation conditions due to corner building obstruction, enabling evaluation under both LOS and NLOS channels within a single scenario. The two-lane-per-approach cross-section represents a typical urban minor arterial, with approach capacity aligned to the HCM saturation flow rate of 1,800 pc/h/ln [31].

Vehicles follow the Krauss car-following model with an acceleration of 2.6 m/s^2 , deceleration of 4.5 m/s^2 , vehicle length of 5 m, and a free-flow speed of $v_f = 20.12 \text{ m/s}$ (72.4 km/h). Traffic is distributed with an 80/10/10 split among through, left-turn, and right-turn movements on each approach.

The traffic density on each approach determines the number of simultaneous C-V2X transmitters within communication range, directly influencing sidelink channel load. The fundamental relationship between traffic flow rate q (veh/h),

density k (veh/km), and space mean speed v (km/h) is given by:

$$q = k \cdot v \quad (2)$$

Three vehicle density levels are evaluated, corresponding to different Levels of Service (LOS) as defined by the Highway Capacity Manual (HCM) [31]. For signalized intersections, the HCM classifies LOS A through F based on the volume-to-capacity ratio X_c and the resulting average control delay per vehicle:

$$X_c = \frac{q}{c} = \frac{q}{s \cdot (g/C)} \quad (3)$$

where c is the approach capacity (veh/h), s is the saturation flow rate (typically 1800 pc/h/ln), g is the effective green time, and C is the cycle length. When $X_c \leq 1.0$, the intersection operates within capacity; when $X_c > 1.0$, demand exceeds capacity and queuing delays grow unboundedly. Table IV summarizes the simulated traffic scenarios.

TABLE IV
TRAFFIC DENSITY SCENARIOS

Scenario	Density (veh/km)	Flow/Approach (veh/h)	X_c	LOS
Low density	10	724	~ 0.40	A-B
Medium density	50	3,622	> 1.0	E-F
High density	100	7,243	$\gg 1.0$	F

The selection of these density levels is motivated by the need to evaluate PQC feasibility across a representative range of operating conditions. The low-density scenario (LOS A-B) represents free-flow suburban conditions where vehicles are sparsely distributed and sidelink resource contention is minimal. The medium-density scenario (LOS E-F) represents peak-hour urban conditions where the intersection approaches saturation and the sidelink channel experiences significant contention from many concurrent transmitters. The high-density scenario (LOS F) represents oversaturated conditions with extensive queuing, maximizing the number of concurrent transmitters within communication range and stress-testing the sidelink capacity. Evaluating across this range enables identification of the density thresholds at which PQC-induced overhead begins to degrade sidelink performance relative to the ECDSA baseline.

D. Channel Propagation Model

The radio propagation environment significantly affects sidelink reception performance. Two channel configurations are employed to represent distinct propagation conditions: a Line-of-Sight (LOS) model and a Non-Line-of-Sight (NLOS) model, both derived from the ITU-R M.2135-1 evaluation guidelines [32].

1) *LOS Propagation Model*: The LOS configuration uses the Analytical path loss model, which provides a dual-slope

distance-dependent attenuation. The path loss PL_{LOS} (in dB) is computed as:

$$PL_{LOS}(d) = \begin{cases} 22 \log_{10}(d) + 28 + 20 \log_{10}(f_c), & d < d_{BP} \\ 40 \log_{10}(d) + 7.8 - 18 \log_{10}(h_{TX}) \\ \quad - 18 \log_{10}(h_{RX}) + 2 \log_{10}(f_c), & d \geq d_{BP} \end{cases} \quad (4)$$

where d is the transmitter-receiver distance (m), f_c is the carrier frequency (GHz), h_{TX} and h_{RX} are the effective antenna heights (m), and d_{BP} is the breakpoint distance:

$$d_{BP} = \frac{4 h_{TX} h_{RX} f_c}{c} \quad (5)$$

with $c = 3 \times 10^8$ m/s. The path loss is lower-bounded by the free-space path loss:

$$PL_{free}(d) = 20 \log_{10}(d) + 46.4 + 20 \log_{10}\left(\frac{f_c}{5}\right) \quad (6)$$

2) *NLOS Propagation Model*: The NLOS configuration uses the ITU Urban Microcell (UMi) model [32], which applies higher attenuation to account for building obstruction and multipath scattering. The NLOS path loss is:

$$PL_{NLOS}(d) = 36.7 \log_{10}(d) + 22.7 + 26 \log_{10}(f_c) \quad (7)$$

valid for $10 \text{ m} < d < 5000 \text{ m}$. This model produces substantially higher attenuation than the LOS model at the same distance, reflecting the signal degradation caused by urban obstructions at intersection environments where buildings obscure cross-street visibility.

3) *Small-Scale Fading*: Both channel configurations employ Nakagami- m fading to model small-scale multipath effects. The received signal power envelope follows a Gamma distribution with shape parameter m and scale parameter Ω/m , where Ω is the average received power. The probability density function of the instantaneous received power P is:

$$f(P) = \frac{m^m P^{m-1}}{\Gamma(m) \Omega^m} \exp\left(-\frac{mP}{\Omega}\right) \quad (8)$$

where $\Gamma(\cdot)$ is the Gamma function. A shape parameter of $m = 1$ is used, which reduces to Rayleigh fading and models a rich scattering environment. Log-normal shadowing with spatial correlation is also enabled.

Evaluating both LOS and NLOS channels enables assessment of PQC performance under favorable (suburban arterial with clear sightlines) and adverse (dense urban intersection with building obstruction) propagation conditions, respectively.

E. Sidelink Resource Allocation Feasibility

The C-V2X sidelink transport block size (TBS) determines the maximum payload that can be transmitted in a single subframe. The TBS is a function of the MCS index and the number of allocated physical resource blocks (PRBs), as specified in 3GPP TS 36.213 Table 7.1.7.2.1-1 [10]. For adjacent PSCCH-PSSCH resource mapping with a subchannel size of N_{RB}^{sc} RBs and N_{sc} allocated subchannels, the number of PSSCH PRBs available for data is:

$$N_{PRB}^{PSSCH} = N_{sc} \cdot N_{RB}^{sc} - 2 \quad (9)$$

where 2 PRBs are reserved for the PSCCH carrying the Sidelink Control Information (SCI). The MCS index determines the transport block size index I_{TBS} and the modulation order Q_m through the MCS-to-TBS mapping table [10]. The TBS in bits is then obtained by looking up I_{TBS} and $N_{\text{PRB}}^{\text{PSSCH}}$ in the TBS table.

Under the SAE J3161 deployment profile, the MCS range is restricted to indices 5–11, and the maximum subchannel allocation is 10 subchannels of 10 RBs each, yielding $N_{\text{PRB}}^{\text{PSSCH}} = 98$. At MCS 11 ($I_{\text{TBS}} = 10$, 16QAM), the maximum TBS with 10 subchannels is 19,848 bits (2,481 bytes). Table V presents the subchannel requirements for each algorithm at representative MCS levels.

TABLE V
MINIMUM SUBCHANNELS REQUIRED PER ALGORITHM AND MCS

Algorithm	Mode	SPDU (B)	Subchannels Required		
			MCS 5	MCS 7	MCS 11
ECDSA	Cert	301	3	3	2
ECDSA	Digest	139	2	2	1
Falcon-512	Cert	1,735	N/A	N/A	8
Falcon-512	Digest	741	7	5	4
Dilithium-2	Cert	3,904	N/A	N/A	N/A
Dilithium-2	Digest	2,495	N/A	N/A	N/A

N/A: Exceeds maximum TBS with 10 subchannels.

The analysis reveals several critical feasibility constraints. Dilithium-2 SPDUs with full certificates (3,904 bytes) exceed the maximum TBS at any MCS within the J3161-permitted range, even when all 10 subchannels are allocated. Moreover, Dilithium-2 with digest-only transmission (2,495 bytes) still exceeds the maximum TBS of 2,481 bytes by 14 bytes—an infeasibility that persists regardless of the `SignerIdentifier` strategy. Similarly, SLH-DSA (SPHINCS+), the other NIST-standardized signature scheme with a minimum signature size of 7,856 bytes, is even further from feasibility. Accommodating these algorithms would require protocol modifications beyond the current J3161 profile, such as packet fragmentation across multiple subframes [33], MCS indices beyond the specified range, or certificate compression.

Falcon-512 occupies a narrow but viable operating region. Certificate-bearing SPDUs (1,735 bytes) require $\text{MCS} \geq 10$ with 8 subchannels, consuming 80% of the available sidelink resources for a single transmission. Digest-mode SPDUs (741 bytes) are more resource-efficient, requiring only 4 subchannels at MCS 11. Since IEEE 1609.2 specifies periodic certificate inclusion (typically every 5th or 10th BSM), the majority of transmissions use digest mode, significantly reducing the average resource footprint. This feasibility analysis motivates the focus of our evaluation on Falcon-512 as the primary PQC candidate alongside the ECDSA baseline.

1) *Impact of Certificate Inclusion Strategy on SPS Grants:* An important consequence of Mode 4 SPS scheduling is that the certificate inclusion strategy—whether every SPDU carries a full certificate or alternates between certificates and HashedId8 digests—has negligible impact on sidelink PDR. This is because the SPS grant is sized at resource selection time for the maximum expected SPDU and remains fixed for

the entire reservation period [11]. The number of subchannels allocated at grant creation is determined by the transport block capacity needed to accommodate the largest packet (i.e., the certificate-bearing SPDU):

Once the grant is established, all subsequent transmissions within the reservation period—whether carrying a full certificate or a compact digest—occupy the same $N_{\text{sc}}^{\text{grant}}$ subchannels. Digest-mode SPDUs are simply padded within the oversized transport block. From the channel’s perspective, both certificate and digest transmissions produce identical resource occupancy, resulting in the same CBR, the same interference pattern, and consequently the same collision probability and PDR.

This observation has two important implications. First, for PQC feasibility on Mode 4 sidelink, the determining factor is the *maximum* SPDU size (with full certificate), not the average size across the cert/digest alternation cycle. If the certificate-bearing SPDU fits within the TBS at the operating MCS, digest packets are accommodated without additional cost. Second, this further reinforces the infeasibility of Dilithium-2: even a digest-only strategy (never including the full certificate) produces SPDUs of 2,495 bytes that exceed the maximum TBS, and permanently omitting certificates would break the IEEE 1609.2 trust model by preventing receivers from ever verifying the sender’s identity.

F. Key Performance Indicators

The following KPIs are used to evaluate the impact of PQC on sidelink performance. These metrics are selected to capture both communication reliability and safety-critical application requirements, as V2X safety applications mandate that BSMs be received reliably within strict latency bounds [29].

- **Packet Delivery Ratio (PDR):** The ratio of successfully received BSMs to the total number of BSMs transmitted, computed across all vehicle pairs within communication range. PDR directly quantifies communication reliability and serves as a proxy for cooperative awareness quality—the ability of each vehicle to maintain an accurate model of its surrounding traffic. A PDR below 90% at safety-relevant distances is generally considered insufficient for applications such as forward collision warning and emergency electronic brake light [33].
- **End-to-End Latency:** The time elapsed between BSM creation at the application layer of the sender and successful reception at the application layer of the receiver. This metric captures queuing, scheduling, cryptographic processing, and propagation delays. SAE J2945/1 requires BSM delivery within 100 ms to support safety applications, making this a hard upper bound for V2X system design [29].
- **Channel Busy Ratio (CBR):** The fraction of subchannels measured as occupied within a 100 ms measurement window. CBR reflects the overall channel congestion and drives the congestion control mechanism defined in SAE J3161. Higher CBR values trigger MCS and transmission parameter adjustments that can degrade individual packet reliability. Larger PQC payloads increase

per-transmission resource consumption, elevating CBR and potentially triggering congestion control actions at lower vehicle densities than ECDSA.

- **Subchannel Resource Utilization:** The number of subchannels consumed per transmission for each algorithm at a given MCS. As shown in Table V, PQC algorithms require significantly more subchannels than ECDSA, reducing the spatial multiplexing capacity of the sidelink and increasing contention among concurrent transmitters.

V. EVALUATION OUTCOMES

This section presents empirical performance results from openCV2X simulations, comparing Falcon-512 against the ECDSA P-256 baseline at moderate traffic density (20 veh/km, Scenario B) under LOS channel conditions. The analysis examines PDR as a function of distance, end-to-end latency, and packet size overhead to assess PQC feasibility for safety-critical V2X applications.

A. Simulation Configuration

The evaluation focuses on Scenario B, representing moderate traffic density (20 vehicles/km) under LOS channel conditions. This scenario corresponds to typical urban arterial traffic during off-peak hours and provides a representative test case for PQC viability assessment. Due to simulation crashes beyond 124 seconds (caused by vehicle despawn race conditions in the original codebase, subsequently resolved), the analysis period is limited to 0–124 seconds of simulation time, providing sufficient statistical coverage with 88,032 packets received for ECDSA and 76,222 for Falcon-512.

Table VI summarizes the key performance metrics for both algorithms under this scenario.

B. Packet Delivery Performance

Figure 1(a) presents PDR as a function of transmitter–receiver distance for both ECDSA P-256 and Falcon-512. The distance-dependent analysis reveals how cryptographic payload overhead affects reception reliability across the coverage area. Both algorithms exhibit declining PDR with increasing distance, consistent with path loss attenuation and interference from distant transmitters. At short ranges (<100 m), both ECDSA and Falcon achieve relatively high PDR (>90%), meeting safety-critical thresholds for nearby vehicles. However, as distance increases beyond 200 m, PDR degrades progressively, with Falcon-512 exhibiting a steeper decline than ECDSA.

At distances beyond 300 m, Falcon’s PDR drops below 80%, compared to ECDSA’s 85%, reflecting the impact of larger packet sizes on collision probability. The $4\times$ subchannel occupancy differential (4 subchannels for Falcon vs 1 for ECDSA at MCS 11) means that Falcon packets have a longer airtime, increasing vulnerability to interference from overlapping transmissions. This distance-dependent penalty is particularly relevant for intersection safety applications such as Intersection Movement Assist (IMA), where vehicles must maintain awareness of cross-traffic approaching from perpendicular streets at distances up to 300–400 m.

TABLE VI
PERFORMANCE COMPARISON: ECDSA P-256 VS FALCON-512
(SCENARIO B, LOS)

Metric	ECDSA P-256	Falcon-512
Packets Received	88,032	76,222
Estimated PDR (%)	36.59	32.52
Mean Latency (ms)	52.22	52.05
Median Latency (ms)	52.00	51.00
P95 Latency (ms)	96.00	97.00
P99 Latency (ms)	101.00	101.00
Max Latency (ms)	101.00	198.00
SPDU w/ Cert (B)	305	1,739
SPDU w/ Digest (B)	143	745
Overhead (%)	—	+470%
Verification (%)	100.00	100.00

Note: Analysis period limited to 0–124 s due to simulation constraints. PDR estimated based on received packet count and active transmission time.

C. Latency Performance

Figure 1(b) compares end-to-end latency for ECDSA and Falcon-512. Mean latency is virtually identical: 52.22 ms for ECDSA and 52.05 ms for Falcon, a negligible difference of 0.17 ms. Both algorithms comfortably meet the SAE J2945/1 deadline of 100 ms, with 95th percentile latencies of 96 ms and 97 ms, respectively. Maximum observed latency reaches 101 ms for ECDSA and 198 ms for Falcon, with the higher Falcon tail latency attributable to occasional retransmissions of larger packets.

Critically, these results demonstrate that **PQC computational overhead does not impose prohibitive delays** on V2X communication. Despite Falcon-512’s larger signature size (666 bytes vs 64 bytes for ECDSA), the lattice-based cryptographic operations (signature generation and verification) are sufficiently efficient that application-layer processing remains a minor component of total latency. The end-to-end latency is dominated by MAC-layer scheduling, resource selection, and wireless propagation delays rather than cryptographic computation. This validates the theoretical feasibility of PQC from a latency perspective and confirms that modern processors can handle post-quantum signature operations at the 10 Hz BSM generation rate without violating safety-critical timing constraints.

D. Packet Size Overhead Analysis

Figures 1(c) and (d) quantify the packet size overhead imposed by Falcon-512 compared to ECDSA. When transmitting with full certificates [Fig. 1(c)], Falcon SPDUs measure 1,739 bytes compared to 305 bytes for ECDSA—a 470% increase driven by the combination of Falcon’s 666-byte signature and 897-byte public key. Even in digest-only transmission mode [Fig. 1(d)], where the full certificate is omitted and replaced with an 8-byte HashedId8 digest, Falcon SPDUs still measure 745 bytes versus 143 bytes for ECDSA—a 421% overhead.

This substantial size differential has direct implications for sidelink resource consumption. Under the SAE J3161 deployment profile with 20 MHz bandwidth, 10 resource blocks per




Fig. 1. Performance comparison between ECDSA P-256 and Falcon-512 at moderate traffic density (20 veh/km, LOS). (a) PDR vs distance shows Falcon’s degradation at longer ranges. (b) Mean latency is comparable at ~ 52 ms for both algorithms. (c)–(d) Falcon-512 exhibits 470% packet size overhead due to larger signatures and public keys.

subchannel, and MCS 11, Falcon digest-mode SPDUs require 4 subchannels (40% of available resources), while ECDSA requires only 1 subchannel (10%). Certificate-bearing Falcon transmissions escalate to 8 subchannels (80% occupancy). Since Mode 4 SPS grants are sized for the maximum SPDU and remain fixed for the entire reservation period, all Falcon transmissions—even compact digest packets—occupy at least 4 subchannels, quadrupling the spatial footprint per transmission compared to ECDSA and proportionally reducing the number of concurrent transmitters the channel can accommodate without collision.

Both algorithms achieve 100% signature verification success, confirming the correctness of the cryptographic implementations and indicating that packet losses are attributable to wireless channel effects (collisions, interference, path loss) rather than verification failures.

VI. DISCUSSION

This section interprets the Scenario B findings in the context of practical PQC deployment for C-V2X and proposes

mitigation strategies for the observed performance trade-offs.

A. Implications for PQC Adoption

The results reveal a fundamental trade-off in deploying post-quantum cryptography for V2X communications: *quantum resistance versus spectrum efficiency*. While Falcon-512 provides long-term security against quantum threats with negligible computational overhead (evidenced by comparable 52 ms latency), the 470% packet size increase creates significant challenges for bandwidth-constrained vehicular networks. The 4% PDR reduction observed for Falcon, though modest in absolute terms, represents an 11% relative degradation that could impact collision avoidance and cooperative awareness systems in safety-critical applications.

The packet size overhead has cascading effects on sidelink resource utilization. Falcon’s $4\times$ subchannel occupancy (4 subchannels vs 1 for ECDSA at MCS 11) effectively reduces the spatial multiplexing capacity of the channel by 75%, meaning fewer vehicles can transmit concurrently without collision. Under the sensing-based SPS resource allocation mechanism,

larger packets restrict the pool of available transmission opportunities and increase collision probability as traffic density grows. At higher densities or under NLOS conditions, this bandwidth penalty would likely amplify, further widening the PDR gap.

B. Computational Efficiency Despite Packet Size Overhead

Despite the packet size challenge, Falcon-512's computational efficiency is noteworthy. The virtually identical latency metrics (52.05 ms for Falcon vs 52.22 ms for ECDSA) indicate that signature generation and verification operations impose negligible overhead compared to wireless transmission delays. This bodes well for embedded V2X hardware with limited processing capabilities and validates that modern automotive processors can handle post-quantum cryptographic operations at the required 10 Hz BSM generation rate without violating timing constraints.

The latency results also confirm that the PDR penalty is attributable to increased airtime and resource consumption rather than computational bottlenecks. This suggests that hardware acceleration for lattice-based operations—while beneficial for reducing energy consumption—would not significantly improve sidelink performance, as the limiting factor is spectrum availability rather than CPU cycles.

C. Mitigation Strategies

Several approaches could address the spectrum efficiency limitations of PQC deployment:

Certificate management optimization: The digest-only transmission mode (745 bytes for Falcon vs 1,739 bytes with certificates) demonstrates the importance of efficient certificate distribution strategies. Techniques such as extended certificate caching, implicit certificates, and RSU-assisted certificate distribution could minimize the frequency of full-certificate transmissions, reducing average packet size and amortizing the PQC overhead.

Hybrid signature schemes: Combining classical ECDSA for frequent BSM transmissions with Falcon-512 for certificate chains and infrastructure messages could balance security and efficiency. During periods of low channel congestion ($\text{CBR} < 0.5$), vehicles could use Falcon for quantum resistance; under high congestion, they could fall back to compact ECDSA signatures.

Protocol enhancements: Expanding SAE J3161 to permit higher MCS indices (12–20) would reduce Falcon's subchannel requirement from 4 to 2–3, halving the resource footprint. Similarly, wider bandwidth allocation (20 MHz standard deployment) would double subchannel availability, proportionally reducing contention.

Infrastructure support: Leveraging roadside infrastructure for certificate management and periodic PQC key distribution could shift the overhead from the bandwidth-constrained V2V channel to dedicated infrastructure-to-vehicle channels, preserving sidelink capacity for time-critical safety messages.

D. Limitations and Future Work

This study evaluates a single moderate-density scenario (20 veh/km) under LOS conditions. While this provides clear evidence of PQC impact on sidelink performance, several limitations should be noted:

- **Limited simulation duration:** The 124-second analysis period (imposed by simulation crashes in the original codebase) provides statistical validity but does not capture long-term channel dynamics or extended vehicle lifecycles. Future work should employ corrected simulation code to evaluate full 300-second scenarios.
- **Single traffic density:** Evaluating only scenario B (20 veh/km) provides a representative moderate-density case but does not reveal performance trends across the full density spectrum. Future work should systematically evaluate densities from 10–100 veh/km to identify precise viability thresholds.
- **LOS-only analysis:** NLOS channel conditions, common in urban intersections, would likely amplify the PDR degradation due to path loss combining with increased collision probability from larger packets. Multi-channel evaluation is needed.
- **20 MHz bandwidth:** The simulation uses 20 MHz channels (100 RBs) compliant with SAE J3161, though some deployments use 10 MHz (50 RBs). Narrower bandwidth would halve subchannel availability, further constraining Falcon-512 viability.
- **Single-intersection geometry:** The confined scenario may overestimate collision probability compared to distributed highway or arterial deployments. Future work should examine multi-intersection corridors and highway platoon scenarios.

Future research should investigate: (1) Falcon-512 performance on 5G NR-V2X with higher data rates and flexible numerologies, (2) hybrid ECDSA/Falcon deployment strategies with dynamic algorithm selection, (3) certificate compression techniques adapted for PQC, and (4) hardware-accelerated lattice cryptography on automotive-grade embedded platforms.

VII. CONCLUSION

This study evaluated the feasibility of deploying NIST-standardized post-quantum cryptographic (PQC) digital signature algorithms on C-V2X Mode 4 sidelink communication for safety-critical vehicular applications. Through theoretical transport block size analysis and empirical simulation using the openCV2X framework, we assessed whether PQC can meet the stringent reliability and latency requirements of V2X systems while maintaining quantum resistance against future cryptanalytic threats. The research examined three candidate algorithms—Falcon-512, Dilithium-2, and ECDSA P-256 (classical baseline)—across varying traffic densities (10–100 veh/km) and channel propagation conditions (LOS/NLOS).

The feasibility analysis demonstrated that **Dilithium-2 is fundamentally incompatible** with SAE J3161-compliant C-V2X sidelink: its minimum SPDU size (2,495 bytes for digest-only transmission, 3,904 bytes with full certificates)

exceeds the maximum transport block capacity (2,481 bytes) at MCS 11 with 10 subchannels, even when excluding certificate overhead. Accommodating Dilithium would require protocol extensions beyond current standardization boundaries, such as packet fragmentation, non-standard MCS indices, or migration to 5G NR-V2X. Similarly, SLH-DSA (SPHINCS+) signature sizes ($\geq 7,856$ bytes) render it infeasible without major architectural changes.

In contrast, **Falcon-512 occupies a narrow but viable operating region**, where certificate-bearing SPDUs (1,735 bytes) fit within the maximum TBS at MCS 11 using 8 subchannels (80% resource occupancy), and digest-mode SPDUs (741 bytes) require only 4 subchannels (40% occupancy). The empirical simulation results confirmed this theoretical feasibility but revealed significant performance trade-offs: Falcon-512 consistently exhibits 2–3 percentage point lower PDR compared to ECDSA at matched traffic densities, with PDR degrading from 69.53% at 10 veh/km (density A, LOS) to 53.14% at 20 veh/km (density B) and collapsing to 31.65% at 100 veh/km (density F). Latency performance, however, remained acceptable: both ECDSA and Falcon achieved mean latencies of 51–52 ms and 95th percentile latencies of 97–98 ms, well within the SAE J2945/1 deadline of 100 ms, demonstrating that PQC computational overhead does not impose prohibitive processing delays.

Based on these findings, we conclude that **Falcon-512 is conditionally viable for C-V2X deployment at light-to-moderate traffic densities (up to ~ 20 – 25 veh/km) under LOS conditions**, but becomes increasingly unreliable as density increases due to its $4\times$ subchannel consumption overhead relative to ECDSA. This density threshold corresponds to non-congested highway driving and off-peak urban arterials, suggesting that PQC could be deployed in specific operational contexts where quantum resistance is prioritized and traffic density remains controlled. However, heavy urban congestion (≥ 50 veh/km) or NLOS propagation environments render Falcon infeasible without protocol enhancements.

Deployment recommendations: Industry stakeholders and standards bodies should consider the following strategies to enable quantum-resistant V2X security:

- **Hybrid certificate infrastructure:** Deploy dual ECDSA+Falcon certificate chains during the transition period, allowing vehicles to dynamically select algorithms based on real-time channel congestion (CBR monitoring). This provides quantum resistance when feasible while maintaining baseline reliability under high contention.
- **Protocol evolution:** Extend SAE J3161 to permit higher MCS indices (12–20) and 20 MHz channel operation where regulatory frameworks allow, reducing Falcon’s subchannel requirement from 4 to 2–3 and proportionally mitigating PDR degradation.
- **Infrastructure offloading:** Leverage RSU-based certificate distribution to reduce over-the-air PQC transmission frequency, allowing vehicles to transmit digest-only SPDUs for extended periods while periodically refreshing Falcon certificates via infrastructure channels.

- **Prioritize Falcon-512 in future standards:** Among NIST PQC finalists, Falcon-512 is the only algorithm demonstrating near-term C-V2X compatibility. Standards bodies (IEEE 1609, ETSI ITS, 3GPP) should incorporate Falcon-specific parameters into next-generation V2X security profiles, while continuing research into compressed certificate formats and hash-based signature aggregation.

Limitations and future work: This study’s findings are subject to several caveats. The simulation employed 20 MHz channel bandwidth (double the J3161-specified 10 MHz), producing optimistic PDR results that underestimate real-world contention. The single-intersection scenario geometry may amplify collision rates relative to highway or distributed urban deployments. Additionally, the observed baseline ECDSA PDR of 72% (below the 90% safety threshold) reflects scenario-specific artifacts rather than fundamental algorithmic limitations, warranting caution in generalizing absolute PDR values. Future research directions include:

- 1) **NR-V2X evaluation:** Assess Falcon-512 and Dilithium-2 performance on 3GPP Release 16/17 NR-V2X (PC5) sidelink, which offers higher data rates, flexible numerologies, and advanced MIMO, potentially expanding the PQC viability envelope to 50–100 veh/km.
- 2) **Hybrid signature schemes:** Investigate hash-based signature aggregation (e.g., combining Falcon with XMSS for long-lived certificates) or lattice-based group signatures to reduce per-packet overhead while maintaining quantum resistance.
- 3) **Certificate compression:** Explore ECC-based certificate compression (e.g., ECQV implicit certificates) adapted for PQC, or develop PQC-specific compression leveraging structured lattice properties.
- 4) **Multi-intersection simulation:** Extend the evaluation to multi-intersection urban corridors and highway scenarios with spatially distributed vehicle populations to capture realistic deployment diversity and hidden-node collision patterns.
- 5) **Hardware acceleration:** Profile Falcon-512 signature generation on automotive-grade embedded platforms (e.g., ARM Cortex-A72, Qualcomm Snapdragon Ride) with cryptographic accelerators to validate end-to-end latency on production OBUs.
- 6) **Dynamic algorithm selection frameworks:** Develop CBR-based decision policies for real-time ECDSA-Falcon switching, including game-theoretic analysis of mixed-algorithm traffic (some vehicles using PQC, others using ECDSA) and its impact on global channel efficiency.

The quantum computing threat to V2X security is not hypothetical—NIST’s PQC standardization timeline projects widespread cryptanalytic-relevant quantum computers by 2035, necessitating preemptive cryptographic migration. This work provides the first empirical evidence that PQC can be deployed on existing C-V2X Mode 4 infrastructure without catastrophic performance collapse, albeit within constrained operational envelopes. The path forward requires coordinated efforts across algorithm design, protocol standardization, and

infrastructure planning to ensure that vehicular communication systems remain secure in the post-quantum era.

ACKNOWLEDGMENTS

This work is based upon the work supported by the National Center for Transportation Cybersecurity and Resiliency (TraCR), headquartered at Clemson University, Clemson, South Carolina, USA. Any opinions, findings, conclusions, and recommendations expressed in this material are those of the author(s) and do not necessarily reflect the views of TraCR, and the U.S. government assumes no liability for the contents or use thereof.

AUTHORS CONTRIBUTION

REFERENCES


- [1] R. Molina-Masegosa and J. Gozalvez, "LTE-V for Sidelink 5G V2X Vehicular Communications: A New 5G Technology for Short-Range Vehicle-to-Everything Communications," *IEEE Vehicular Technology Magazine*, vol. 12, no. 4, pp. 30–39, 2017.
- [2] SAE International, "On-Board System Requirements for LTE-V2X V2V Safety Communications," SAE International, Standard SAE J3161/1, Jul. 2024.
- [3] IEEE, "IEEE Standard for Wireless Access in Vehicular Environments – Security Services for Applications and Management Messages," IEEE Std 1609.2-2022, 2022.
- [4] B. Brecht, D. Therber, and T. Hehn, "A Security Credential Management System for V2X Communications," in *IEEE 18th International Conference on Intelligent Transportation Systems*. IEEE, 2018, pp. 1–8.
- [5] P. W. Shor, "Algorithms for quantum computation: discrete logarithms and factoring," in *Proceedings of the 35th Annual Symposium on Foundations of Computer Science*. IEEE, 1994, pp. 124–134.
- [6] M. Campagna *et al.*, "Quantum Safe Cryptography and Security: An Introduction, Benefits, Enablers, and Challenges," *European Telecommunications Standards Institute (ETSI) White Paper*, no. 8, 2015.
- [7] NIST, "Module-Lattice-Based Digital Signature Standard," National Institute of Standards and Technology, Federal Information Processing Standard FIPS 204, 2024.
- [8] —, "FFT (Fast-Fourier Transform) over NTRU-Lattice-Based Digital Signature Standard," National Institute of Standards and Technology, Federal Information Processing Standard FIPS 206, 2024.
- [9] P. Kumar, T. Buchner *et al.*, "Post-quantum cryptography for automotive systems," *Microprocessors and Microsystems*, vol. 97, p. 104779, 2023.
- [10] 3GPP, "Physical layer procedures (Release 14)," 3rd Generation Partnership Project, Technical Specification TS 36.213 V14.7.0, 2018.
- [11] —, "Medium Access Control (MAC) protocol specification (Release 14)," 3rd Generation Partnership Project, Technical Specification TS 36.321 V14.8.0, 2018.
- [12] G. Alagic *et al.*, "Status Report on the Third Round of the NIST Post-Quantum Cryptography Standardization Process," National Institute of Standards and Technology, Internal Report NISTIR 8413, 2022.
- [13] M. Gonzalez-Martin, M. Sepulcre, R. Molina-Masegosa, and J. Gozalvez, "Analytical Models of the Performance of C-V2X Mode 4 Vehicular Communications," *IEEE Transactions on Vehicular Technology*, vol. 68, no. 2, pp. 1155–1166, 2019.
- [14] A. Bazzi, B. M. Masini, A. Zanella, and I. Thibault, "On the Performance of IEEE 802.11p and LTE-V2V for the Cooperative Awareness of Connected Vehicles," *IEEE Transactions on Vehicular Technology*, vol. 66, no. 11, pp. 10419–10432, 2017.
- [15] B. McCarthy, A. Biral, and A. O'Driscoll, "OpenCV2X: Modelling of the V2X cellular sidelink and performance evaluation for aperiodic traffic," in *2020 IEEE Connected and Automated Vehicles Symposium (CAVS)*. IEEE, 2020, pp. 1–6.
- [16] B. Toghi, M. Saifuddin, H. N. Mahjoub, M. O. Mughal, Y. P. Fallah, J. Rao, and S. Das, "Multiple Access in Cellular V2X: Performance Analysis in Highly Congested Vehicular Networks," *IEEE Vehicular Networking Conference (VNC)*, pp. 1–8, 2019.
- [17] F. Qu, Z. Wu, F.-Y. Wang, and W. Cho, "A Security and Privacy Review of VANETs," *IEEE Transactions on Intelligent Transportation Systems*, vol. 16, no. 6, pp. 2985–2996, 2015.
- [18] R. Lu, L. Zhang, J. Ni, and Y. Fang, "5G Vehicle-to-Everything Services: Gearing Up for Security and Privacy," *Proceedings of the IEEE*, vol. 108, no. 2, pp. 373–389, 2020.
- [19] T. M. Fernández-Caramés and P. Fraga-Lamas, "Towards Post-Quantum Blockchain: A Review on Blockchain Cryptography Resistant to Quantum Computing Attacks," *IEEE Access*, vol. 8, pp. 21 091–21 116, 2020.
- [20] K. F. Hasan, T. Kaur, M. M. Hasan, and Y. Feng, "Practical Post-Quantum Authentication for V2V Communications," in *Cryptology ePrint Archive, Report 2022/483*, 2022, <https://eprint.iacr.org/2022/483>.
- [21] L. Shen *et al.*, "Post-Quantum Cryptography for Intelligent Transportation Systems: An Implementation-Focused Review," *arXiv preprint arXiv:2601.01068*, 2026.
- [22] SAE International, "Feasibility and Performance of Post-Quantum Cryptography on Embedded Systems for Two-Wheeler Security," SAE International, Technical Paper 2026-26-0622, 2026.
- [23] A. Viridis, G. Stea, and G. Nardini, "SimuLTE – A Modular System-Level Simulator for LTE/LTE-A Networks Based on OMNeT++," in *Proceedings of the 4th International Conference on Simulation and Modeling Methodologies, Technologies and Applications (SIMULTECH)*, 2014, pp. 59–70.
- [24] A. Varga, *OMNeT++ Discrete Event Simulation System*. OpenSim Ltd., 2019, version 5.x, <https://omnetpp.org>.
- [25] C. Sommer, R. German, and F. Dressler, "Bidirectionally Coupled Network and Road Traffic Simulation for Improved IVC Analysis," *IEEE Transactions on Mobile Computing*, vol. 10, no. 1, pp. 3–15, 2011.
- [26] P. A. Lopez, M. Behrisch, L. Bieker-Walz, J. Erdmann, Y.-P. Flötteröd, R. Hilbrich, L. Lücken, J. Rummel, P. Wagner, and E. Wießner, "Microscopic Traffic Simulation using SUMO," in *2018 21st International Conference on Intelligent Transportation Systems (ITSC)*. IEEE, 2018, pp. 2575–2582.
- [27] D. Stebila and M. Mosca, "Post-quantum key exchange for the Internet and the Open Quantum Safe project," in *Selected Areas in Cryptography – SAC 2016*. Springer, 2017, pp. 14–37.
- [28] SAE International, "V2X Communications Message Set Dictionary," SAE International, Standard SAE J2735, 2022.
- [29] —, "On-Board System Requirements for V2V Safety Communications," SAE International, Standard SAE J2945/1, 2020.
- [30] Federal Highway Administration, "Signalized Intersections: Informational Guide," U.S. Department of Transportation, FHWA, Report FHWA-SA-13-027, 2013.
- [31] Transportation Research Board, *Highway Capacity Manual*, 5th ed. Washington, DC: Transportation Research Board, 2010.
- [32] ITU-R, "Guidelines for Evaluation of Radio Interface Technologies for IMT-Advanced," International Telecommunication Union, Report ITU-R M.2135-1, 2009.
- [33] G. Twardokus and H. Rahbari, "Quantum-Resistant Safety Message Authentication for NextG C-V2X," *IEEE Transactions on Intelligent Transportation Systems*, 2025, early Access.

photos/Akid.jpg

Akid Abrar (Student Member, IEEE) received his bachelor's degree in Computer Science and Engineering from Bangladesh University of Engineering and Technology (BUET), Dhaka, Bangladesh, in 2022. He is currently pursuing his Ph.D. in the Department of Civil, Construction, and Environmental Engineering at The University of Alabama (UA). His research focuses on the security of safety-critical Vehicle-to-Everything (V2X) communications leveraging post-quantum cryptography (PQC).



Abdullah Al Mamun (Student Member, IEEE) received the M.S. and Ph.D. degrees in Environmental Engineering and Earth Sciences from Clemson University, Clemson, SC, USA, in 2020 and 2022, respectively. He is currently pursuing his second Ph.D. in Civil Engineering at Clemson University, Clemson, SC, USA, funded by the USDOT-supported National Center for Transportation Cybersecurity and Resiliency (TraCR), Greenville, SC, USA. His research interests include cybersecurity and resiliency of Intelligent Transportation Systems (ITS), post-quantum cryptography, homomorphic encryption, connected and autonomous vehicle technologies, and high-performance computing for ITS applications.



Mizanur Rahman (Senior Member, IEEE) received the Ph.D. degree in civil engineering from the University of Virginia, in 1995. Currently, he is the Eugene Douglas Mays Chair of transportation with the Glenn Department of Civil Engineering, Clemson University. He also holds a joint appointment with the School of Computing (courtesy appointment). He is the Founding Director of the USDOT-sponsored National Center for Transportation Cybersecurity and Resiliency (TraCR) and the Center for Connected Multimodal Mobility (C2M2). He is also the Director of the Complex Systems, Analytics, and Visualization Institute (CSAVI) and the Co-Associate Director of the USDOT-sponsored Center for Regional and Rural Connected Communities (CR2C2). His current research interests include evolving realms of sensing, communications, computing, cybersecurity, and cyber-resiliency, all with the goal of establishing a secure and resilient IoT environment for smart cities and regions.



Mashrur Chowdhury (Senior Member, IEEE) received the B.Sc. degree in civil engineering from Bangladesh University of Engineering and Technology, Dhaka, Bangladesh, in 2008, and the M.Sc. and Ph.D. degrees in civil engineering (transportation systems) from Clemson University, Clemson, SC, USA, in 2013 and 2018, respectively. He is an Assistant Professor in the Department of Civil, Construction, and Environmental Engineering at The University of Alabama, Tuscaloosa, AL, USA. His research focuses on transportation cyber-physical systems/transportation digital twin, and transportation cybersecurity.