

```

-r --re-interval
-s --no-optimize
-S --sandbox
-t --lint-old
-U --version

```

To report bugs, use the 'gawkbug' program.
 For full instructions, see the node 'Bugs' in 'gawk.info' which is section 'Reporting Problems and Bugs' in the printed version. This same information may be found at https://www.gnu.org/software/gawk/manual/html_node/Bugs.html. PLEASE do NOT try to report bugs by posting in comp.lang.awk, or by using a web forum such as Stack Overflow.

Source code for gawk may be obtained from
<https://ftp.gnu.org/gnu/gawk/gawk-5.3.2.tar.gz>

gawk is a pattern scanning and processing language.
 By default it reads standard input and writes standard output.

Examples:

```

awk '{ sum += $1 }; END { print sum }' file
awk -F: '{ print $1 }' /etc/passwd

```

gentoo /boot # sed

Usage: sed [OPTION]... {script-only-if-no-other-script} [input-file]...

```

-n, --quiet, --silent
    suppress automatic printing of pattern space
--debug
    annotate program execution
-e script, --expression=script
    add the script to the commands to be executed
-f script-file, --file=script-file
    add the contents of script-file to the commands to be executed
--follow-symlinks
    follow symlinks when processing in place
-i[SUFFIX], --in-place[=SUFFIX]
    edit files in place (makes backup if SUFFIX supplied)
-l N, --line-length=N
    specify the desired line-wrap length for the 'l' command
--posix
    disable all GNU extensions.
-E, -r, --regexp-extended
    use extended regular expressions in the script
    (for portability use POSIX -E).
-s, --separate
    consider files as separate rather than as a single,
    continuous long stream.
--sandbox
    operate in sandbox mode (disable e/r/w commands).
-u, --unbuffered
    load minimal amounts of data from the input files and flush
    the output buffers more often
-z, --null-data
    separate lines by NUL characters
--help
    display this help and exit
--version
    output version information and exit

```

If no -e, --expression, -f, or --file option is given, then the first non-option argument is taken as the sed script to interpret. All remaining arguments are names of input files; if no input files are specified, then the standard input is read.

GNU sed home page: <https://www.gnu.org/software/sed/>.

General help using GNU software: <https://www.gnu.org/gethelp/>.

gentoo /boot #

```

gentoo /boot # umask
0022
gentoo /boot # stat
stat: missing operand
Try 'stat --help' for more information.
gentoo /boot # state new.txt
-bash: state: command not found
gentoo /boot # state new
-bash: state: command not found
gentoo /boot # getfacl
Usage: getfacl [-aceEsRLPtpnduh] file ...
Try 'getfacl --help' for more information.
gentoo /boot # getfacl new.txt
# file: new.txt
# owner: root
# group: root
user::rwx
group::r-x
other::r-x

gentoo /boot # setfacl new.txt
Usage: setfacl [-bkndRLP] [-m|-M|-x|-X ...] file ...
Try 'setfacl --help' for more information.
gentoo /boot # lsattr
lsattr: Operation not supported While reading flags on ./EFI
lsattr: Operation not supported While reading flags on ./System Volume Information
lsattr: Operation not supported While reading flags on ./kernel-6.18.29-gentoo-dist
lsattr: Operation not supported While reading flags on ./new.txt
lsattr: Operation not supported While reading flags on ./grub
lsattr: Operation not supported While reading flags on ./new.py
lsattr: Operation not supported While reading flags on ./initramfs-6.18.29-gentoo-dist.img
gentoo /boot # usermod
Usage: usermod [options] LOGIN

Options:
  -a, --append                append the user to the supplemental GROUPS
                              mentioned by the -G option without removing
                              the user from other groups
  -b, --badname               allow bad names
  -c, --comment COMMENT       new value of the GECOS field
  -d, --home HOME_DIR         new home directory for the user account
  -e, --expiredate EXPIRE_DATE set account expiration date to EXPIRE_DATE
  -f, --inactive INACTIVE     set password inactive after expiration
                              to INACTIVE
  -g, --gid GROUP             force use GROUP as new primary group
  -G, --groups GROUPS         new list of supplementary GROUPS
  -h, --help                  display this help message and exit
  -l, --login NEW_LOGIN       new value of the login name
  -L, --lock                  lock the user account
  -m, --move-home             move contents of the home directory to the
                              new location (use only with -d)
  -o, --non-unique            allow using duplicate (non-unique) UID
  -p, --password PASSWORD     use encrypted password for the new password
  -P, --prefix PREFIX_DIR     prefix directory where are located the /etc/* files
  -r, --remove                remove the user from only the supplemental GROUPS
                              mentioned by the -G option without removing
                              the user from other groups
  -R, --root CHROOT_DIR       directory to chroot into
  -s, --shell SHELL           new login shell for the user account
  -u, --uid UID               new UID for the user account
  -U, --unlock                unlock the user account
  -v, --add-subuids FIRST-LAST add range of subordinate uids
  -V, --del-subuids FIRST-LAST remove range of subordinate uids
  -w, --add-subgids FIRST-LAST add range of subordinate gids
  -W, --del-subgids FIRST-LAST remove range of subordinate gids

gentoo /boot #

```

```
gentoo /boot # ifconfig
lo: flags=73<UP,LOOPBACK,RUNNING> mtu 65536
    inet 127.0.0.1 netmask 255.0.0.0
    inet6 ::1 prefixlen 128 scopeid 0x10<host>
    loop txqueuelen 1000 (Local Loopback)
    RX packets 0 bytes 0 (0.0 B)
    RX errors 0 dropped 0 overruns 0 frame 0
    TX packets 0 bytes 0 (0.0 B)
    TX errors 0 dropped 0 overruns 0 carrier 0 collisions 0
```

gentoo /boot # ip

Usage: ip [OPTIONS] OBJECT { COMMAND | help }

ip [-force] -batch filename

where OBJECT := { address | addrlabel | fou | help | ila | ioam | l2tp | link |
macsec | maddress | monitor | mptcp | mroute | mrule |
neighbor | neighbour | netconf | netns | nexthop | ntable |
ntbl | route | rule | sr | stats | tap | tcpmetrics |
token | tunnel | tuntap | vrf | xfrm }

OPTIONS := { -V[ersion] | -s[tatistics] | -d[etails] | -r[esolve] |
-h[uman-readable] | -iec | -j[son] | -p[retty] |
-f[amily] { inet | inet6 | mpls | bridge | link } |
-4 | -6 | -M | -B | -O |
-l[oops] { maximum-addr-flush-attempts } | -echo | -br[ief] |
-o[neline] | -t[imestamp] | -ts[hort] | -b[atch] [filename] |
-rc[ubuf] [size] | -n[etns] name | -N[umeric] | -a[ll] |
-c[olor]}

gentoo /boot # _

gentoo /boot # netstat

Active Internet connections (w/o servers)

Proto Recv-Q Send-Q Local Address

Active UNIX domain sockets (w/o servers)

Proto	RefCnt	Flags	Type	State	I-Mode	Path
unix	2	[]	DGRAM	CONNECTED	7604	
unix	3	[]	STREAM	CONNECTED	2981	
unix	3	[]	DGRAM	CONNECTED	6618	/run/dbus/system_bus_socket
unix	2	[]	DGRAM	CONNECTED	18562	
unix	3	[]	STREAM	CONNECTED	15509	/run/user/0/systemd/notify
unix	3	[]	DGRAM	CONNECTED	6615	/run/systemd/journal/stdout
unix	5	[]	DGRAM	CONNECTED	18565	/run/systemd/notify
unix	6	[]	DGRAM	CONNECTED	10241	
unix	3	[]	DGRAM	CONNECTED	10242	/run/systemd/journal/dev-log
unix	3	[]	DGRAM	CONNECTED	18564	/run/systemd/journal/socket
unix	3	[]	STREAM	CONNECTED	18534	
unix	3	[]	STREAM	CONNECTED	2996	/run/dbus/system_bus_socket
unix	3	[]	STREAM	CONNECTED	6915	/run/systemd/journal/stdout
unix	2	[]	DGRAM	CONNECTED	2576	
unix	2	[]	DGRAM	CONNECTED	11569	
unix	3	[]	DGRAM	CONNECTED	17436	
unix	2	[]	DGRAM	CONNECTED	18540	
unix	3	[]	STREAM	CONNECTED	3013	/run/dbus/system_bus_socket
unix	3	[]	STREAM	CONNECTED	2975	
unix	3	[]	STREAM	CONNECTED	2978	
unix	3	[]	DGRAM	CONNECTED	6616	
unix	2	[]	DGRAM	CONNECTED	2639	
unix	3	[]	DGRAM	CONNECTED	6619	
unix	3	[]	STREAM	CONNECTED	2979	
unix	3	[]	STREAM	CONNECTED	14811	/run/systemd/journal/stdout
unix	3	[]	STREAM	CONNECTED	14730	/run/systemd/journal/stdout
unix	2	[]	DGRAM	CONNECTED	18547	
unix	3	[]	DGRAM	CONNECTED	18563	
unix	3	[]	STREAM	CONNECTED	7555	
unix	3	[]	DGRAM	CONNECTED	6617	
unix	3	[]	DGRAM	CONNECTED	17435	
unix	2	[]	DGRAM	CONNECTED	2977	
unix	2	[]	DGRAM	CONNECTED	17677	
unix	3	[]	DGRAM	CONNECTED	18566	
unix	3	[]	STREAM	CONNECTED	2632	
unix	3	[]	DGRAM	CONNECTED	18567	
unix	3	[]	DGRAM	CONNECTED	18568	
unix	2	[]	DGRAM	CONNECTED	2644	@14451269272783381851
unix	3	[]	STREAM	CONNECTED	18570	@e6a22866a4ade5fd/bus/systemd/bus-system
unix	3	[]	STREAM	CONNECTED	7618	@3e91d79790ee0203/bus/systemd-logind/system
unix	3	[]	STREAM	CONNECTED	17645	@c1129f31ecfec665/bus/systemd/bus-api-system

gentoo /boot #

* 18566

* 2632

* 18567

* 18568

* 18570

* 7618

* 17645

```

unix 3 [ ] DGRAM CONNECTED 18547
unix 3 [ ] STREAM CONNECTED 18563
unix 3 [ ] DGRAM CONNECTED 7555
unix 3 [ ] DGRAM CONNECTED 6617
unix 2 [ ] DGRAM CONNECTED 17435
unix 2 [ ] DGRAM CONNECTED 2977
unix 3 [ ] DGRAM CONNECTED 17677
unix 3 [ ] DGRAM CONNECTED 18566
unix 3 [ ] STREAM CONNECTED 2632
unix 3 [ ] DGRAM CONNECTED 18567
unix 3 [ ] DGRAM CONNECTED 18568
unix 2 [ ] DGRAM 2644
unix 3 [ ] STREAM CONNECTED 18570
unix 3 [ ] STREAM CONNECTED 7618
unix 3 [ ] STREAM CONNECTED 17645

```

@14451269272783381851
 @c6a22866a4adc5fd/bus/systemd/bus-system
 @3e91d79790ec0203/bus/systemd-logind/system
 @c1129f31ecfee665/bus/systemd/bus-api-system

```

gentoo /boot # ss
RTNETLINK answers: Invalid argument

```

Netid	State	Recv-Q	Send-Q
u_dgr	ESTAB	0	0
u_str	ESTAB	0	0
u_dgr	ESTAB	0	0
u_str	ESTAB	0	0
u_dgr	ESTAB	0	0
u_dgr	ESTAB	0	0
u_dgr	ESTAB	0	0
u_dgr	ESTAB	0	0
u_str	ESTAB	0	0
u_str	ESTAB	0	0
u_dgr	ESTAB	0	0
u_dgr	ESTAB	0	0
u_dgr	ESTAB	0	0
u_dgr	ESTAB	0	0
u_str	ESTAB	0	0
u_str	ESTAB	0	0
u_str	ESTAB	0	0
u_dgr	ESTAB	0	0
u_dgr	ESTAB	0	0
u_str	ESTAB	0	0
u_dgr	ESTAB	0	0
u_dgr	ESTAB	0	0
u_dgr	ESTAB	0	0
u_dgr	ESTAB	0	0
u_dgr	ESTAB	0	0
u_str	ESTAB	0	0
u_str	ESTAB	0	0
u_str	ESTAB	0	0

```
gentoo /boot #
```

Local Address:Port	Peer Address:Port
* 7604	* 10242
/run/dbus/system_bus_socket 2981	* 17645
* 6618	* 6619
/run/systemd/journal/stdout 15509	* 2632
/run/systemd/notify 6615	* 0
* 18565	* 18566
/run/systemd/journal/dev-log 10241	* 0
/run/systemd/journal/socket 10242	* 0
* 18564	* 18563
* 18534	* 14011
/run/dbus/system_bus_socket 2996	* 7618
/run/systemd/journal/stdout 6915	* 2975
* 2576	* 6615
* 11569	* 10242
* 17436	* 17435
* 18540	* 10241
/run/dbus/system_bus_socket 3013	* 18570
* 2975	* 6915
* 2978	* 2979
* 6616	* 6617
* 2639	* 10242
* 6619	* 6618
* 2979	* 2978
/run/systemd/journal/stdout 14011	* 18534
/run/systemd/journal/stdout 14730	* 7555
* 18547	* 10242
* 18563	* 10564
* 7555	* 14730
* 6617	* 6616
* 17435	* 17436
* 2977	* 10241
* 17677	* 10241
* 18566	* 18565
* 2632	* 15509
* 18567	* 18568
* 18568	* 18567
@c6a22866a4adc5fd/bus/systemd/bus-system 18570	* 3013
@3e91d79790ec0203/bus/systemd-logind/system 7618	* 2996
@c1129f31ecfee665/bus/systemd/bus-api-system 17645	* 2981

144Hz / Adaptive SYNC

ASUS

✓ I am basically a robot



-bash: traceroute: command not found

gentoo /boot # ps

PID	TTY	TIME	CMD
929	tty1	00:00:00	login
1023	tty1	00:00:00	bash
2440	tty1	00:00:00	top
3066	tty1	00:00:00	less
3089	tty1	00:00:00	less
3696	tty1	00:00:00	ps

gentoo /boot # pgrep

pgrep: no matching criteria specified
Try 'pgrep --help' for more information.

gentoo /boot # pgrep tty1

gentoo /boot # pgrep bash

1023

gentoo /boot # pkill less

gentoo /boot # ps

PID	TTY	TIME	CMD
929	tty1	00:00:00	login
1023	tty1	00:00:00	bash
2440	tty1	00:00:00	top
3066	tty1	00:00:00	less
3089	tty1	00:00:00	less
3746	tty1	00:00:00	ps

gentoo /boot # killall

Usage: killall [OPTION]... [--] NAME...

killall -l, --list

killall -V, --version

-e,--exact	require exact match for very long names
-I,--ignore-case	case insensitive process name match
-g,--process-group	kill process group instead of process
-y,--younger-than	kill processes younger than TIME
-o,--older-than	kill processes older than TIME
-i,--interactive	ask for confirmation before killing
-l,--list	list all known signal names
-q,--quiet	don't print complaints
-r,--regex	interpret NAME as an extended regular expression
-s,--signal SIGNAL	send this signal instead of SIGTERM
-u,--user USER	kill only process(es) running as USER
-v,--verbose	report if the signal was successfully sent
-V,--version	display version information
-w,--wait	wait for processes to die
-n,--ns PID	match processes that belong to the same namespaces as PID
-Z,--context REGEXP	kill only process(es) having context (must precede other arguments)

gentoo /boot # bg

[3]+ less new.txt &

gentoo /boot # fg

less new.txt

[3] Exit 15

less new.txt

gentoo /boot # jobs

[1]+ Stopped

top (wd: ~)

gentoo /boot # nice

0

gentoo /boot # renice

renice: not enough arguments

Try 'renice --help' for more information.

gentoo /boot #

144Hz / Adaptive SYNC


```
[ 493.420009] usb 3-4: new high-speed USB device number 12 using xhci_hcd
[ 493.421115] usb 3-4: New USB device found, idVendor=04e8, idProduct=6864, bcdDevice= 5.04
[ 493.422059] usb 3-4: New USB device strings: Mfr=1, Product=2, SerialNumber=3
[ 493.422979] usb 3-4: Product: SAMSUNG_Android
[ 493.423910] usb 3-4: Manufacturer: SAMSUNG
[ 493.431260] usb 3-4: SerialNumber: R2CY11K669T
[ 493.434642] rndis_host 3-4:1.0 usb0: register 'rndis_host' at usb-0000:00:14.0-4, RNDIS device
[ 863.517185] usb 3-4: USB disconnect, device number 12
[ 863.518276] rndis_host 3-4:1.0 enp0s20f0u4: renamed from usb0
[ 864.130409] usb 3-4: new high-speed USB device number 13 using xhci_hcd
[ 864.273391] usb 3-4: New USB device found, idVendor=04e8, idProduct=6864, bcdDevice= 5.04
[ 864.274447] usb 3-4: New USB device strings: Mfr=1, Product=2, SerialNumber=3
[ 864.275358] usb 3-4: Product: SAMSUNG_Android
[ 864.276256] usb 3-4: Manufacturer: SAMSUNG
[ 864.277177] usb 3-4: SerialNumber: R2CY11K669T
[ 864.282741] cdc_acm 3-4:1.1: ttyACM0: USB ACM device
[ 865.082933] usb 3-4: USB disconnect, device number 13
[ 865.607111] usb 3-4: new high-speed USB device number 14 using xhci_hcd
[ 865.739896] usb 3-4: New USB device found, idVendor=04e8, idProduct=6864, bcdDevice= 5.04
[ 865.740936] usb 3-4: New USB device strings: Mfr=1, Product=2, SerialNumber=3
[ 865.741897] usb 3-4: Product: SAMSUNG_Android
[ 865.742827] usb 3-4: Manufacturer: SAMSUNG
[ 865.743769] usb 3-4: SerialNumber: R2CY11K669T
[ 865.750043] rndis_host 3-4:1.0 usb0: register 'rndis_host' at usb-0000:00:14.0-4, RNDIS device, ea:3a:fd:e2:e4:98
[ 865.753442] rndis_host 3-4:1.0 enp0s20f0u4: renamed from usb0
[ 2411.331155] usb 3-4: USB disconnect, device number 14
[ 2411.332551] rndis_host 3-4:1.0 enp0s20f0u4: unregister 'rndis_host' usb-0000:00:14.0-4, RNDIS device
[ 2412.000038] usb 3-4: new high-speed USB device number 15 using xhci_hcd
[ 2412.142886] usb 3-4: New USB device found, idVendor=04e8, idProduct=6864, bcdDevice= 5.04
[ 2412.143896] usb 3-4: New USB device strings: Mfr=1, Product=2, SerialNumber=3
[ 2412.144805] usb 3-4: Product: SAMSUNG_Android
[ 2412.145685] usb 3-4: Manufacturer: SAMSUNG
[ 2412.146564] usb 3-4: SerialNumber: R2CY11K669T
[ 2412.152018] cdc_acm 3-4:1.1: ttyACM0: USB ACM device
[ 2413.135228] usb 3-4: USB disconnect, device number 15
[ 2413.623391] usb 3-4: new high-speed USB device number 16 using xhci_hcd
[ 2413.755852] usb 3-4: New USB device found, idVendor=04e8, idProduct=6864, bcdDevice= 5.04
[ 2413.756829] usb 3-4: New USB device strings: Mfr=1, Product=2, SerialNumber=3
[ 2413.757325] usb 3-4: Product: SAMSUNG_Android
[ 2413.757816] usb 3-4: Manufacturer: SAMSUNG
[ 2413.758305] usb 3-4: SerialNumber: R2CY11K669T
[ 2413.763444] rndis_host 3-4:1.0 usb0: register 'rndis_host' at usb-0000:00:14.0-4, RNDIS device, 26:27:52:e6:55:8b
[ 2413.766865] rndis_host 3-4:1.0 enp0s20f0u4: renamed from usb0
[ 2525.475933] usb 3-4: USB disconnect, device number 16
[ 2525.477012] rndis_host 3-4:1.0 enp0s20f0u4: unregister 'rndis_host' usb-0000:00:14.0-4, RNDIS device
[ 2528.483221] usb 3-4: new high-speed USB device number 17 using xhci_hcd
[ 2528.632548] usb 3-4: New USB device found, idVendor=04e8, idProduct=6864, bcdDevice= 5.04
[ 2528.633499] usb 3-4: New USB device strings: Mfr=1, Product=2, SerialNumber=3
[ 2528.634381] usb 3-4: Product: SAMSUNG_Android
[ 2528.635250] usb 3-4: Manufacturer: SAMSUNG
[ 2528.636115] usb 3-4: SerialNumber: R2CY11K669T
[ 2528.641605] rndis_host 3-4:1.0 usb0: register 'rndis_host' at usb-0000:00:14.0-4, RNDIS device, 26:27:52:e6:55:8b
[ 2528.645073] rndis_host 3-4:1.0 enp0s20f0u4: renamed from usb0
```

gentoo ~ # uname

Linux

gentoo ~ # uptime

16:06:30 up 57 min, 1 user, load average: 0.00, 0.00, 0.00

gentoo ~ # hostname

gentoo

gentoo ~ # free

	total	used	free	shared	buff/cache	available
Mem:	16091032	610532	15580480	1616	192288	15480500
Swap:	4194300	0	4194300			

gentoo ~ #

top - 16:08:20 up 59 min, 1 user, load average: 0.00, 0.00, 0.00
Tasks: 215 total, 1 running, 214 sleep, 0 d-sleep, 0 stopped, 0 zombie
%Cpu(s): 0.0 us, 0.0 sy, 0.0 ni, 100.0 id, 0.0 wa, 0.0 hi, 0.0 si, 0.0 st
Mem Mem : 15713.9 total, 15191.2 free, 590.7 used, 188.2 buff/cache
Mem Swap: 4096.0 total, 4096.0 free, 0.0 used, 15115.2 avail Mem

PID	USER	PR	NI	VRT	RES	SHR	S	%CPU	%MEM	TIME	COMMAND
2440	root	20	0	11272	6680	3860	R	0.7	0.0	0:00.06	top
1	root	20	0	19296	12852	8604	S	0.0	0.1	0:00.04	systemd
2	root	20	0	0	0	0	S	0.0	0.0	0:00.00	kthreadd
3	root	20	0	0	0	0	S	0.0	0.0	0:00.00	pool_workqueue_release
4	root	0	-20	0	0	0	I	0.0	0.0	0:00.00	worker/0-rcu_gp
5	root	0	-20	0	0	0	I	0.0	0.0	0:00.00	worker/0-sync_wq
6	root	0	-20	0	0	0	I	0.0	0.0	0:00.00	worker/0-kvfree_rcu_reclaim
7	root	0	-20	0	0	0	I	0.0	0.0	0:00.00	worker/0-slab_flushwq
8	root	0	-20	0	0	0	I	0.0	0.0	0:00.00	worker/0-netns
10	root	0	-20	0	0	0	I	0.0	0.0	0:00.00	worker/0:0H-events_highpri
12	root	20	0	0	0	0	I	0.0	0.0	0:00.23	worker/u64:0-events_unbound
13	root	0	-20	0	0	0	I	0.0	0.0	0:00.00	worker/0-ma_percpu_wq
14	root	20	0	0	0	0	I	0.0	0.0	0:00.06	worker/u64:1-flush-259:0
15	root	20	0	0	0	0	S	0.0	0.0	0:00.00	ksoftirqd/0
16	root	20	0	0	0	0	I	0.0	0.0	0:00.06	rcu_preempt
17	root	20	0	0	0	0	S	0.0	0.0	0:00.00	rcu_exp_par_gp_kthread_worker/0
18	root	20	0	0	0	0	S	0.0	0.0	0:00.00	rcu_exp_gp_kthread_worker
19	root	rt	0	0	0	0	S	0.0	0.0	0:00.00	migration/0
20	root	-51	0	0	0	0	S	0.0	0.0	0:00.00	idle_inject/0
21	root	20	0	0	0	0	S	0.0	0.0	0:00.00	cpuhp/0
22	root	20	0	0	0	0	S	0.0	0.0	0:00.00	cpuhp/1
23	root	-51	0	0	0	0	S	0.0	0.0	0:00.00	idle_inject/1
24	root	rt	0	0	0	0	S	0.0	0.0	0:00.10	migration/1
25	root	20	0	0	0	0	S	0.0	0.0	0:00.00	ksoftirqd/1
27	root	0	-20	0	0	0	I	0.0	0.0	0:00.00	worker/1:0H-events_highpri
28	root	20	0	0	0	0	S	0.0	0.0	0:00.00	cpuhp/2
29	root	-51	0	0	0	0	S	0.0	0.0	0:00.00	idle_inject/2
30	root	rt	0	0	0	0	S	0.0	0.0	0:00.10	migration/2
31	root	20	0	0	0	0	S	0.0	0.0	0:00.00	ksoftirqd/2
33	root	0	-20	0	0	0	I	0.0	0.0	0:00.00	worker/2:0H-events_highpri
34	root	20	0	0	0	0	S	0.0	0.0	0:00.00	cpuhp/3
35	root	-51	0	0	0	0	S	0.0	0.0	0:00.00	idle_inject/3
36	root	rt	0	0	0	0	S	0.0	0.0	0:00.10	migration/3
37	root	20	0	0	0	0	S	0.0	0.0	0:00.00	ksoftirqd/3
39	root	0	-20	0	0	0	I	0.0	0.0	0:00.00	worker/3:0H-events_highpri
40	root	20	0	0	0	0	S	0.0	0.0	0:00.00	cpuhp/4
41	root	-51	0	0	0	0	S	0.0	0.0	0:00.00	idle_inject/4
42	root	rt	0	0	0	0	S	0.0	0.0	0:00.10	migration/4
43	root	20	0	0	0	0	S	0.0	0.0	0:00.00	ksoftirqd/4
45	root	0	-20	0	0	0	I	0.0	0.0	0:00.00	worker/4:0H-events_highpri
46	root	20	0	0	0	0	S	0.0	0.0	0:00.00	cpuhp/5
47	root	-51	0	0	0	0	S	0.0	0.0	0:00.00	idle_inject/5
48	root	rt	0	0	0	0	S	0.0	0.0	0:00.10	migration/5
49	root	20	0	0	0	0	S	0.0	0.0	0:00.00	ksoftirqd/5
51	root	0	-20	0	0	0	I	0.0	0.0	0:00.00	worker/5:0H-events_highpri
52	root	20	0	0	0	0	S	0.0	0.0	0:00.00	cpuhp/6
53	root	-51	0	0	0	0	S	0.0	0.0	0:00.00	idle_inject/6
54	root	rt	0	0	0	0	S	0.0	0.0	0:00.10	migration/6
55	root	20	0	0	0	0	S	0.0	0.0	0:00.00	ksoftirqd/6
57	root	0	-20	0	0	0	I	0.0	0.0	0:00.00	worker/6:0H-events_highpri
58	root	20	0	0	0	0	S	0.0	0.0	0:00.00	cpuhp/7
59	root	-51	0	0	0	0	S	0.0	0.0	0:00.00	idle_inject/7
60	root	rt	0	0	0	0	S	0.0	0.0	0:00.10	migration/7
61	root	20	0	0	0	0	S	0.0	0.0	0:00.00	ksoftirqd/7
63	root	0	-20	0	0	0	I	0.0	0.0	0:00.00	worker/7:0H-events_highpri
64	root	20	0	0	0	0	S	0.0	0.0	0:00.00	cpuhp/8
65	root	-51	0	0	0	0	S	0.0	0.0	0:00.00	idle_inject/8
66	root	rt	0	0	0	0	S	0.0	0.0	0:00.11	migration/8
67	root	20	0	0	0	0	S	0.0	0.0	0:00.00	ksoftirqd/8
68	root	0	-20	0	0	0	I	0.0	0.0	0:00.00	worker/8:0H-events_highpri

```
gentoo ~ # arch  
x86_64  
gentoo ~ #
```


GNU nano 9.0

[[[Hello all how are You]]]

(((this is the example text file)))

<<Learn...Improve...Enjoy>>>

new.txt

Modified

Help
Exit

Write Out
Read File

Where Is
Replace

Cut
Paste

Execute
Location

Undo
Redo

Set Mark
Copy

To Bracket
Where Was

Previous
Next

Back
Forward

Prev Word
Next Word

Home
End

Scroll Left
Scroll Right

Prev Line
Next Line

```

gentoo /boot # ls
EFI grub initramfs-6.18.29-gentoo-dist.img kernel-6.18.29-gentoo-dist new.txt 'System Volume Information'
gentoo /boot # cd /
gentoo / # ls
bin boot dev etc home lib lib64 lost+found media mnt opt proc root run sbin srv stage3-and64-desktop-sysend-20260510T170106Z.tar.xz sys tmp usr var
gentoo / # cd
gentoo ~ # cd/
-bash: cd/: No such file or directory
gentoo ~ # cd /
gentoo / # cd home
gentoo /home # pwd
/home
gentoo /home # mkdir new
gentoo /home # ls
new new.txt
gentoo /home # rmdir new
gentoo /home # ls
new.txt
gentoo /home # touch new.py
gentoo /home # ls
new.py new.txt
gentoo /home # rm new.txt
gentoo /home # ls
new.py
gentoo /home # cp new.py /
gentoo /home # ls
new.py
gentoo /home # cd /
gentoo / # ls
bin boot dev etc home lib lib64 lost+found media mnt new.py opt proc root run sbin srv stage3-and64-desktop-sysend-20260510T170106Z.tar.xz sys tmp usr var
gentoo / # mv new.py /boot
gentoo / # ls
bin boot dev etc home lib lib64 lost+found media mnt opt proc root run sbin srv stage3-and64-desktop-sysend-20260510T170106Z.tar.xz sys tmp usr var
gentoo / # cd boot
gentoo /boot # ls
EFI grub initramfs-6.18.29-gentoo-dist.img kernel-6.18.29-gentoo-dist new.py new.txt 'System Volume Information'
gentoo /boot # cat new.txt
[[[Hello all how are You]]]

(((this is the example text file)))

<<<Learn...Improve...Enjoy>>>
gentoo /boot #

```


[2] Stopped

less new.txt

gentoo /boot # more new.txt
[[[Hello all how are You]]]

(((this is the example text file)))

<<<Learn...Improve...Enjoy>>>

gentoo /boot # less new.txt
[[[Hello all how are You]]]

(((this is the example text file)))

<<<Learn...Improve...Enjoy>>>

new.txt lines 1-5/5 (END)

144Hz

Adaptive

```
gentoo /boot # tail new.txt  
[[[Hello all how are You]]]
```

```
((this is the example text file))
```

```
<<<Learn...Improve...Enjoy>>>
```

```
gentoo /boot # head new.txt  
[[[Hello all how are You]]]
```

```
((this is the example text file))
```

```
<<<Learn...Improve...Enjoy>>>
```

```
gentoo /boot # _
```

144Hz

Adaptive
SYNC

```

gentoo /boot # gedit
-bash: gedit: command not found
gentoo /boot # awk
Usage: awk [POSIX or GNU style options] -f progfile [--] file ...
Usage: awk [POSIX or GNU style options] [--] 'program' file ...
POSIX options:          GNU long options: (standard)
    -f progfile          --file=progfile
    -F fs                --field-separator=fs
    -v var=val           --assign=var=val
Short options:          GNU long options: (extensions)
    -b                  --characters-as-bytes
    -c                  --traditional
    -C                  --copyright
    -d[file]            --dump-variables[=file]
    -D[file]            --debug[=file]
    -e 'program-text'   --source='program-text'
    -E file             --exec=file
    -g                  --gen-pot
    -h                  --help
    -i includefile      --include=includefile
    -l                  --trace
    -k                  --csv
    -l library          --load=library
    -L[fatal|invalid|no-ext] --lint[=fatal|invalid|no-ext]
    -n                  --bignum
    -N                  --use-lc-numeric
    -n                  --non-decimal-data
    -o[file]            --pretty-print[=file]
    -O                  --optimize
    -p[file]            --profile[=file]
    -P                  --posix
    -r                  --re-interval
    -s                  --no-optimize
    -S                  --sandbox
    -t                  --lint-old
    -U                  --version

```

To report bugs, use the 'gawkbug' program.
 For full instructions, see the node 'Bugs' in 'gawk.info' which is section 'Reporting Problems and Bugs' in the printed version. This same information may be found at https://www.gnu.org/software/gawk/manual/html_node/Bugs.html. PLEASE do NOT try to report bugs by posting in comp.lang.awk, or by using a web forum such as Stack Overflow.

Source code for gawk may be obtained from
<https://ftp.gnu.org/gnu/gawk/gawk-5.3.2.tar.gz>

gawk is a pattern scanning and processing language.
 By default it reads standard input and writes standard output.

Examples:

```

awk '{ sum += $1 }; END { print sum }' file
awk -F: '{ print $1 }' /etc/passwd

```

```

gentoo /boot #

```