

CYRACODE

Universal Address Naming System

Acceptance Criteria Documentation

Version 1.0

June 2024

Executive Summary

CyraCode is a global platform that enables individuals to register a unique, human-readable name mapped to a single postal address. This document provides comprehensive acceptance criteria for the CyraCode web application, including detailed test scenarios across five primary user flows.

Platform Overview

- Global address registration system for seamless logistics and drone deliveries
- Supports 1M+ users at scale with geolocation mapping
- Integration point for major logistics and postal companies
- Two registration modes: Traditional (custom name) and Auto-Generate (pseudo name)
- Globally unique names that cannot be changed (with mobile owner exception)

Screen 1: Landing Page

The landing page serves as the primary entry point for new and returning users. It provides options for user authentication and registration.

AC 1.1	Login with Existing Credentials	User enters valid email and password	User is authenticated and redirected to dashboard/home page	Credentials are validated against secure user database; session token generated; audit log recorded
AC 1.2	Google OAuth Sign-In	User clicks 'Sign up with Google' button	User is redirected to Google OAuth consent screen and authenticated	Google OAuth flow initiated; user profile data (name, email) pre-populated; seamless redirect to next screen
AC 1.3	Manual Email Registration Entry	User enters first name, last name, email, and password in form fields	Form validates all fields and enables 'Next' button	All fields validated per global standards; password strength requirements enforced (min 8 chars, 1 uppercase, 1 number, 1 special)
AC 1.4	Invalid Email Format Rejection	User enters invalid email format (e.g., 'notanemail' or 'test@')	Error message displayed: 'Please enter a valid email address'	Real-time regex validation; error clears on valid input
AC 1.5	Existing Email Detection	User enters email already registered in system	Error message: 'This email is already registered. Please login or	Database lookup performed; case-insensitive check

			use a different email.'	
AC 1.6	Empty Field Submission	User clicks 'Next' with empty required fields	Fields highlighted in red with error: 'This field is required'	Client-side validation; focus moved to first empty field
AC 1.7	Password Field Visibility Toggle	User clicks eye icon on password field	Password becomes visible/hidden on toggle	No security logs for visibility toggle; session maintained
AC 1.8	Remember Me Functionality	User checks 'Remember Me' and logs in	On return visit, user email is pre-populated	Session cookie persisted for 30 days (configurable); device-specific
AC 1.9	Forgot Password Link	User clicks 'Forgot Password' on login section	Redirected to password reset page with email input	Reset link sent to registered email; valid for 24 hours; OTP-based or token-based flow
AC 1.10	Page Load Performance	Landing page loads in typical network conditions	Page fully loads within 2 seconds; all UI elements responsive	DOM loaded within 2s; interactive within 3.5s; supports 1M concurrent users

Edge Cases & Load Scenarios

- Extreme Load (100K concurrent users): Page should load within 3 seconds
- Slow Network (3G): Page should load within 5 seconds
- Mobile Device (small screen <480px): Form should remain fully usable

- International Characters: Email validation should support internationalized domain names (IDN)
- Rapid API Calls: Rate limiting at 10 requests/minute per IP to prevent brute force

Screen 2: Sign Up - Traditional (Custom Name Registration)

Users manually enter a unique custom name and complete comprehensive address details. This screen supports global address variations and validates country-specific postal formats.

Part A: Geolocation & Custom Name

AC 2.1	Google Map Display & Marker Placement	User views interactive Google Map with location marker	Map displays current location or selected address with red pin marker	Google Maps API integrated; marker updates on address change; supports zoom/pan
AC 2.2	Custom Name Entry & Uniqueness Check	User enters custom name (e.g., 'Mohan Babu Mani')	System validates name uniqueness in real-time; green checkmark if available	Real-time global database lookup; response <500ms; supports 1M+ name searches/day
AC 2.3	Name Already Taken Error	User enters name already registered by another user	Error message: 'This name is already taken. Try: [suggestions]'	System suggests 3-5 alternatives; case-insensitive lookup
AC 2.4	Name Validation Rules	User enters special characters or invalid name format	Error: 'Name must contain only letters, numbers, and spaces. Max 50 characters.'	Regex validation: <code>^[a-zA-Z0-9]{3,50}\$</code>
AC 2.5	Auto-Fetch Coordinates from Map	User selects location on map or enters address	System auto-populates Longitude and Latitude fields	Latitude/Longitude read-only; extracted from map selection; 6+ decimal precision
AC 2.6	Coordinate Immutability	User attempts to manually edit Longitude/Latitude fields	Fields are disabled; cannot be edited	Client-side disabled attribute; server-side validation rejects edits
AC 2.7	Generate Code Button	User clicks 'Generate Code' without selecting location	Button remains disabled; tooltip: 'Please select a location on the map first'	Event handler validates geolocation; visual feedback for disabled state

Part B: Address Details (Country-Specific)

AC 2.8	Country Dropdown Selection	User selects country from dropdown (supports 195+ countries)	Selected country populated; address fields update to country-specific format	Dynamic form fields based on country rules; supports all ISO 3166-1 countries
AC 2.9	India Address Fields (Example)	User selects India as country	Form displays: State, District, City, Postal Code, Flat/Plot Number, Building Name, Street Name, Landmark	Cascading dropdowns for State → District; all fields are required
AC 2.10	USA Address Fields (Example)	User selects USA as country	Form displays: State, City, Street Address, Zip Code, Apartment/Suite Number	State lookup validated against USPS database; ZIP code format validation (5 or 5+4)
AC 2.11	UK Address Fields (Example)	User selects UK as country	Form displays: Postcode, City, Street Address, Building Number/Name, Floor/Unit	Postcode validation via Royal Mail API; case-insensitive
AC 2.12	State/Province Dropdown	User selects country and then state/province dropdown	Dropdown populated with valid states for selected country	Data sourced from authoritative postal service database
AC 2.13	Postal Code Validation	User enters postal code for selected country	System validates format per country standards (e.g., 5-digit for USA, PIN for India)	Regex validation per country; real-time feedback
AC 2.14	Landmark Field (Optional)	User enters landmark for easier delivery location identification	Landmark text accepted (max 100 characters)	Optional field; stored for courier reference
AC 2.15	Flat/Plot/Villa Number Parsing	User enters complex flat number (e.g., 'A-302, Tower 5, Plot 45')	System parses and stores in database for structured queries	Stored as-is; supports special characters and multi-part numbers

AC 2.16	Address Field Mandatory Validation	User submits form with missing required address field	Error highlights missing field in red: 'This field is required'	Client-side and server-side validation; prevents form submission
AC 2.17	Longitude/Latitude Consistency	User enters address that conflicts with map coordinates	Warning message: 'Address and map location do not match. Please verify.'	Geo-distance check: if > 1km difference, warning displayed

Part C: Mobile Verification & OTP

AC 2.18	Mobile Number Input	User enters mobile number in international format (e.g., +91 98765 43210)	Mobile number accepted in E.164 format	Validation: <code>^\+?[1-9]\d{1,14}\$</code> (ITU E.164 standard); country code validated
AC 2.19	OTP Generation & Delivery	User clicks 'Send OTP' for mobile verification	6-digit OTP generated and sent via SMS	OTP valid for 5 minutes; stored with hash; SMS delivery within 10 seconds
AC 2.20	OTP Expiry	User enters OTP after 5 minutes of expiry	Error: 'OTP has expired. Please request a new OTP.'	Expired OTP cannot be reused; user can request new OTP
AC 2.21	Invalid OTP Rejection	User enters incorrect OTP	Error after 3 attempts: 'Invalid OTP. You have 2 attempts remaining.' Lock after 5 failed attempts.	Rate limiting: max 5 attempts per OTP; 15-minute lockout after failure
AC 2.22	Resend OTP	User clicks 'Resend OTP' within 30 seconds	Message: 'Please wait before requesting a new OTP'	Cooldown timer: 30 seconds between resend attempts
AC 2.23	OTP Verification Success	User enters correct OTP	Mobile number verified; proceed to next step	Session updated; mobile flagged as verified in database

Edge Cases & Validation Scenarios

- Duplicate Address Detection: Two users cannot register the same exact longitude/latitude + country combination (within 10m radius)

- Ocean/Uninhabited Land: Coordinates mapping to oceans should be rejected with: 'Please select a valid residential address'
- Spam Name Detection: Machine learning filter to detect spam/inappropriate names; flags for review
- International Character Support: Name field should support Unicode; test with Hindi, Arabic, Chinese, Cyrillic characters
- Timezone Handling: All timestamps stored in UTC; OTP validity calculated based on user timezone

Screen 3: Sign Up - Auto Generate (Pseudo Name Registration)

Users register without choosing a custom name; system generates a unique pseudo code (e.g., 'ABX2I2X8LICN'). All other address requirements remain identical to Traditional mode.

AC 3.1	Auto-Generate Code on Location Selection	User selects location on map without entering custom name	System automatically generates unique pseudo code (12-character alphanumeric)	Algorithm: Geohash-based code with uniqueness salt; generated <100ms
AC 3.2	Generated Code Display & Copy	Auto-generated code displayed in read-only field	User can click copy icon to copy code to clipboard	UX: Tooltip confirms 'Copied!'; code stored in session and database
AC 3.3	Code Immutability	User attempts to edit or change generated code	Code field is read-only; cannot be modified	Client-side: disabled input; server-side: rejects any edit attempts
AC 3.4	Generate New Code	User clicks 'Generate New Code' button	New unique pseudo code generated; old code discarded	Only valid during registration; after submission, code is locked
AC 3.5	Code Format Consistency	System generates multiple codes	All codes follow same 12-character format: 3 uppercase + 2 uppercase + 7 lowercase/numbers	Regex pattern: <code>^[A-Z]{3}[A-Z]{2}[a-z0-9]{7}\$</code>
AC 3.6	Address Details (Same as Traditional)	User fills address fields identical to Screen 2 requirements	All address validations and field requirements apply	Country-specific validation, mandatory fields, postal code format checks
AC 3.7	Mobile Verification (Same as Traditional)	User verifies mobile number with OTP	OTP process identical to AC 2.18 - 2.23	No difference in verification flow between Traditional and Auto-Generate modes

AC 3.8	Uniqueness Guarantee	System generates code; check against database for collision	Generated code is always globally unique	Hash-based uniqueness check: probability of collision < 1 in 10 billion
--------	----------------------	---	--	---

Edge Cases

- Code Generation During High Load: System should generate and validate uniqueness <100ms even at 100K concurrent users
- Database Collision Retry: If collision detected (extreme edge case), system retries generation up to 5 times
- Code Regeneration Limit: Users can regenerate code max 10 times per registration session

Screen 4: Sign Up Confirmation

Final confirmation screen displays success message, registered details, QR code, and next steps.

AC 4.1	Congratulations Message Display	User completes registration successfully	Confirmation page displays: 'Congratulations! Welcome to CyraCode'	Smiley icon displayed; uplifting UX messaging
AC 4.2	Registered Name/Code Display	Confirmation page displays user's registered CyraCode name	User's custom name or auto-generated code prominently displayed	Large, readable font; centered on page for emphasis
AC 4.3	Address Summary Display	Confirmation page shows summary of registered address	All address fields displayed in read-only format	Formatted according to country standards; editable only after account activation
AC 4.4	Coordinates Display	Confirmation page shows Longitude and Latitude	Displayed as: 'Coordinates: 3.1145737, 80.2215774'	Read-only; links to map view on click
AC 4.5	QR Code Generation	System generates QR code encoding CyraCode name + coordinates	QR code displayed for download/sharing	Format: PNG/SVG; size 300x300px; scannable with standard QR readers
AC 4.6	QR Code Functionality	User scans QR code with mobile phone	Opens Google Maps to registered location or	Deep linking to app; fallback to web if app not installed

			launches CyraCode app with pre-filled details	
AC 4.7	Download QR Code	User clicks 'Download QR Code' button	QR code downloaded as PNG file	Filename format: 'CyraCode_[CustomName]_[Timestamp].png'
AC 4.8	Share CyraCode Name	User clicks 'Share' button	Options: Email, SMS, WhatsApp, Facebook, Copy Link	Pre-filled message: 'Find me at my CyraCode: [Name]. Use this for deliveries worldwide!'
AC 4.9	Next Steps Guidance	Confirmation page displays 'Next Steps'	Options: 'Complete Profile' (add photo, business info), 'Set Delivery Preferences', 'Share with Courier Partners'	Skip option available; all steps available in dashboard later
AC 4.10	Confirmation Email	System sends confirmation email to registered address	Email includes: CyraCode name, coordinates, QR code attachment, account activation link	Email delivered within 5 minutes; includes opt-in for notifications

Edge Cases

- QR Code Failure: If QR generation fails, display error with retry option
- Email Delivery Delay: Show message 'Confirmation email may take 5-10 minutes to arrive' if not delivered immediately
- Browser Back Button: Prevent navigation back to edit form; if attempted, redirect to dashboard

Screen 5: Search & Navigation (Google Maps Integration)

Primary landing page showing interactive map with search functionality. Users can search for registered CyraCode names and receive navigation directions.

AC 5.1	Map Display on Page Load	User opens search landing page	Full-screen Google Map loads with default location (user location if permission granted)	Map loads within 2 seconds; supports zoom/pan; default zoom level 15
--------	--------------------------	--------------------------------	--	--

AC 5.2	Search CyraCode Name	User enters CyraCode name in search box (e.g., 'Mohan Babu Mani')	System resolves name to coordinates and displays map marker	Database lookup <500ms; case-insensitive search; autocomplete suggestions in real-time
AC 5.3	Search Results Display	CyraCode name found in database	Marker displayed on map; info window shows: Name, Address, Coordinates	Marker color: green for CyraCode addresses; standard red for other locations
AC 5.4	Search Name Not Found	User searches for non-existent CyraCode name	Message: 'CyraCode '[Name]' not found. Did you mean: [suggestions]?'	Fuzzy matching algorithm returns 3-5 suggestions; allows typo tolerance
AC 5.5	Autocomplete Suggestions	User types in search box	Dropdown shows matching CyraCode names (max 5 suggestions)	Real-time filtering; shows: Name, Brief Address, Distance from current location
AC 5.6	Get Directions	User clicks 'Get Directions' button after finding location	Opens Google Maps directions from current location to CyraCode address	Deep link to Google Maps app; fallback to web version
AC 5.7	Start Navigation	User clicks 'Start Navigation' button	Google Maps navigation mode activates with turn-by-turn directions	Voice guidance enabled (if supported); real-time traffic integration
AC 5.8	Share Location	User clicks 'Share' button for found location	Options: Email, SMS, WhatsApp, Facebook, Copy Link	Pre-filled message: 'Meet me at [CyraCode Name]: [Full Address]'
AC 5.9	Location Details Popup	User clicks marker on map	Popup displays: CyraCode Name, Full Address, Coordinates, Distance from user, 'Directions' button	Clickable address opens address details in new section
AC 5.10	Search History	User has previously searched for CyraCode names	Recent searches displayed in search dropdown	Stored in browser localStorage; max 10 entries; clear option available

Edge Cases & Performance

- Offline Mode: If offline, display cached search results from last session
- Geolocation Permission Denied: Map displays default world view; user can manually enter start location
- International Searches: System supports searching from any country; results show distance in local units (km or miles)
- Mobile Optimization: Map and search fully functional on mobile devices; touch-friendly buttons
- Search Performance at Scale: At 1M CyraCode registrations, search should respond <200ms

Cross-Cutting Acceptance Criteria

Security & Privacy

AC 6.1	HTTPS/TLS Encryption	All user data transmitted over network	TLS 1.2+ enforced; HSTS header present	Certificate valid; no mixed content warnings
AC 6.2	Password Hashing	User passwords stored in database	Passwords hashed with bcrypt (min cost factor 12)	Plaintext passwords never logged; salted hash stored
AC 6.3	OTP Security	OTP transmitted to user	OTP is 6-digit numeric; valid 5 minutes; stored as hash	OTP never logged in plaintext; single-use validation
AC 6.4	API Rate Limiting	Prevent brute force attacks	10 requests/minute per IP for auth endpoints; 100 requests/minute for general API	Returns 429 status after limit exceeded; client-side backoff
AC 6.5	GDPR Compliance	User personal data processed	Data collection consent obtained; right to access/delete implemented	Privacy policy link on landing page; data deletion available in settings
AC 6.6	Input Sanitization	User inputs processed (names, addresses, etc.)	All inputs sanitized against XSS and SQL injection	Server-side validation; parameterized queries used; no eval() calls

Performance & Scalability

AC 6.7	Page Load Time (Landing Page)	Normal network conditions	Fully loaded within 2 seconds; interactive within 3.5 seconds	Measured via Lighthouse; supports 1M concurrent users
AC 6.8	Database Query Performance	Search for CyraCode name	Query response <200ms for 1M records	Indexed database fields; read replicas for search queries
AC 6.9	API Response Time	General API calls	<500ms response time at p95 percentile	CDN caching for static assets; database query optimization
AC 6.10	Image/Media Optimization	QR codes and other images delivered	Images optimized; WebP format used where supported; size <100KB per image	Lazy loading implemented for below-fold content
AC 6.11	Database Backup & Recovery	System operational	Automated daily backups; recovery time objective (RTO) <1 hour	Multi-region replication; disaster recovery tested quarterly

Accessibility & Localization

AC 6.12	WCAG 2.1 AA Compliance	Website content and functionality	Keyboard navigation supported; screen reader compatible; color contrast WCAG AA	Tested with NVDA/JAWS; axe accessibility audit passes
AC 6.13	Multi-Language Support	Users from different countries access platform	UI available in 10+ languages (EN, ES, FR, DE, ZH, JA, AR, HI, PT, RU)	Language selection via dropdown; persisted in user preferences
AC 6.14	Right-to-Left (RTL) Language Support	Users select Arabic or Hebrew	UI layout reverses appropriately; text alignment correct	RTL CSS applied; tested with Arabic and Hebrew interfaces
AC 6.15	Date & Time Localization	Dates and times displayed	Formatted per user's locale; timezone handled correctly	OTP expiry time displayed in user's timezone

AC 6.16	Postal Code Format Localization	User selects different countries	Postal code field label and format changes per country (e.g., 'ZIP Code' for USA, 'Postcode' for UK)	Validation rules per country; placeholder text localized
---------	---------------------------------	----------------------------------	--	--

Data Integrity & Validation

AC 6.17	Idempotency Keys	User submits registration form twice rapidly	Second submission rejected; duplicate registration prevented	Idempotency key stored in cache for 24 hours
AC 6.18	Coordinate Validation	Longitude and Latitude from Google Maps	Coordinates must be valid; latitude range [-90, 90], longitude range [-180, 180]	Server-side validation; coordinates reject if mapping to ocean/uninhabited land
AC 6.19	Duplicate Address Prevention	Two users register with same coordinates (within 10m radius)	Second registration blocked: 'An address within 10 meters already registered'	Geospatial check in database; allows multiple users if coordinates differ >10m
AC 6.20	Email Uniqueness	User registers with email already in system	Registration blocked; user prompted to login or use different email	Case-insensitive check; prevents account enumeration
AC 6.21	Mobile Number Validation	User enters mobile in different formats	All formats accepted and normalized to E.164: +[country code][number]	Validation: country code valid; total length 10-15 digits
AC 6.22	Address Field Length Limits	User enters extremely long address text	Fields truncated per country standards (e.g., Street Address max 100 chars)	Validation error if exceeds limit; user notified before save

Integration with Logistics Partners

AC 6.23	CyraCode API Availability	Logistics partner queries CyraCode API	API endpoint returns address data: Name, Coordinates, Full Address, Postal Code	API response time <200ms; 99.99% uptime SLA
AC 6.24	Geocoding Reverse Lookup	Logistics partner provides coordinates; system returns CyraCode name	Nearest registered CyraCode within 50m radius returned (if exists)	Null response if no match; partner can proceed with manual delivery
AC 6.25	Address Format Standardization	Different logistics partners query same address	Address returned in standardized format per country	Format consistent; no variation in response structure
AC 6.26	API Authentication	Logistics partner accesses CyraCode API	API key required; OAuth2 bearer token validation	Rate limiting per partner; audit log of all API access
AC 6.27	Delivery Confirmation	Logistics partner confirms package delivered to CyraCode address	User notified via app/email with: CyraCode name, Delivery time, Proof of delivery (photo optional)	Delivery status updated in real-time; stored for history

Design Recommendations

1. Enhanced Form UX

- Multi-Step Form with Progress Indicator: Show step 1/4, 2/4, etc. to manage user expectations
- Form Field Validation: Real-time feedback for each field; green checkmark when valid
- Save Progress: Allow users to save form draft and resume later

2. Map Interaction

- Address Search on Map: Allow users to search addresses in Google Maps and auto-populate form
- Map Click to Place Marker: Users click on map to place address marker (alternative to search)
- Visual Confirmation: Show address marker on map as user enters address details

3. Mobile-First Design

- Responsive Layout: Test on screens 320px-1200px wide

- Touch-Friendly Buttons: Min 44px height; adequate spacing
- Mobile Native Features: Use device camera for QR code scanning; mobile keyboard for number input

4. Confirmation & Sharing

- Animated Success State: Celebrate user completion with confetti or animated checkmark
- QR Code Shareable Card: Design a sharable card with CyraCode name, address, and QR code
- One-Click Share: Pre-populated social media posts with CyraCode name and shareable link

5. Error Handling & Feedback

- Clear Error Messages: Avoid technical jargon; provide actionable suggestions
- Inline Validation: Display errors next to fields, not in separate modals
- Loading States: Show skeleton loaders or spinners during API calls

6. Branding & Visual Design

- Primary Color Palette: Use brand colors consistently (CyraCode orange for CTAs)
- Icons & Illustrations: Custom location-themed icons; map-related illustrations
- Typography: Sans-serif font for readability; clear hierarchy with H1, H2, H3
- Whitespace: Adequate spacing to reduce cognitive load

Testing Strategy

1. Functional Testing

- Test each AC manually with real data
- Automated test cases for critical flows (Selenium/Cypress)
- Form submission with valid/invalid data combinations

2. Security Testing

- Penetration testing for SQL injection, XSS, CSRF
- API security testing (rate limiting, authentication)
- Data encryption verification (TLS, password hashing)

3. Performance Testing

- Load testing: 100K concurrent users; measure page load, API response
- Stress testing: Identify system breaking point

- Database indexing verification for search performance

4. Usability Testing

- User interviews: Test with 10+ real users from different countries
- Accessibility audit: Screen reader testing; keyboard navigation
- Mobile usability: Test on iOS and Android devices

5. Localization Testing

- Test all 10+ supported languages
- RTL language layout testing (Arabic, Hebrew)
- Country-specific validation rules

Success Metrics & KPIs

Platform Health

- Uptime: 99.99% availability
- API Response Time: <200ms at p95 percentile
- Database Query Performance: <500ms for 1M record searches

User Adoption

- Registration Completion Rate: >80% (users completing all 4 screens)
- Mobile Registration Rate: >60% of all registrations
- Average Registration Time: <10 minutes

Data Quality

- Address Validation Success Rate: >95% of addresses pass country-specific validation
- Duplicate Detection: <0.1% duplicate address registrations (within 10m radius)
- OTP Verification Success: >98% (users successfully verify mobile)

Logistics Integration

- API Usage: Logistics partners make >1M requests/day by Month 6
- Delivery Success Rate: >95% packages delivered to registered CyraCode addresses
- Partner Onboarding: 50+ logistics partners integrated within Year 1

Glossary

Term	Definition		
CyraCode	Unique identifier for a postal address; either custom name or auto-generated pseudo code		
Geohash	Algorithm that converts geographic coordinates into a short string for spatial indexing		
E.164 Format	International standard for phone numbers: +[country code][area code][number]		
OTP	One-Time Password; 6-digit code sent via SMS for mobile verification		
Longitude/Latitude	Geographic coordinates; immutable once registered		
Pseudo Code	Auto-generated unique name (e.g., 'ABX2I2X8LICN'); system-created, non-customizable		
RTO	Recovery Time Objective; maximum acceptable downtime (CyraCode: 1 hour)		
Idempotency	Property ensuring repeated identical		

	requests produce same result		
WCAG 2.1 AA	Web Content Accessibility Guidelines; Level AA compliance required		
Fuzzy Matching	Search algorithm tolerating spelling mistakes; e.g., 'Mohan Babi Mani' matches 'Mohan Babu Mani'		

Appendix: Example Country-Specific Address Formats

India

- Required: Flat/Plot Number, Building Name, Street Name, Landmark, City, State, Postal Code (PIN)
- Postal Code Format: 6 digits (e.g., 560034)
- Example: 'Flat 302, Prestige Towers, MG Road, Koramangala, Bangalore, Karnataka, 560034'

United States

- Required: Street Address, City, State, ZIP Code
- ZIP Code Format: 5 digits or 5+4 (e.g., 12345 or 12345-6789)
- Example: '123 Main St, Apt 4B, New York, NY 10001'

United Kingdom

- Required: Building Name/Number, Street, City, Postcode
- Postcode Format: Alphanumeric (e.g., SW1A 1AA)
- Example: '10 Downing Street, Westminster, London, SW1A 1AA'

Japan

- Required: Postal Code, Prefecture, City, District, Building Name, Room Number
- Postal Code Format: 7 digits, format XXX-XXXX (e.g., 100-0001)
- Example: '100-0001, Tokyo, Chiyoda, Kasumigaseki Building, Room 502'

--- END OF DOCUMENT ---