
Pyzotero Documentation

Release 0.8.2

Stephan Hügel

July 05, 2011

CONTENTS

1	Indices and tables	3
2	Installation	5
2.1	Testing	5
3	Usage	7
3.1	Hello World	7
3.2	General Usage	7
4	Read API Methods	9
4.1	Retrieving Items	9
4.2	Retrieving Collections	11
4.3	Retrieving groups	12
4.4	Retrieving Tags	12
5	Write API Methods	15
5.1	Item Methods	15
5.2	Collection Methods	16
6	Notes	19
7	License	21
	Python Module Index	23
	Index	25

A Python wrapper for the [Zotero API](#). You'll require a user ID and access key, which can be set up [here](#).

INDICES AND TABLES

- *genindex*
- *modindex*
- *search*

INSTALLATION

Using pip: `pip install pyzotero`

From a local clone, if you wish to install Pyzotero from a specific branch:

```
git clone git://github.com/urschrei/pyzotero.git
cd pyzotero
git checkout dev
pip install .
```

Alternatively, download the latest version from <https://github.com/urschrei/pyzotero/downloads>, and point pip at the zip file. Example: `pip install ~/Downloads/urschrei-pyzotero-v0.3-0-g04ff544.zip`

I assume that running `setup.py` will also work using `easy_install`, but I haven't tested it.

The `feedparser` module ($\geq 0.5.1$) is required. It should automatically be installed when installing Pyzotero using pip.

2.1 Testing

Run `tests.py` in the `pyzotero` directory, or, using `Nose`, `nosetests` from this directory. If you wish to see coverage statistics, run `nosetests --with-coverage --cover-package=pyzotero`.

USAGE

3.1 Hello World

```
from pyzotero import zotero
zot = zotero.Zotero(user_id, user_key)
items = zot.items()
for item in items:
    print 'Author: %s | Title: %s' % (item['creators'][0]['lastName'], item['title'])
```

3.2 General Usage

First, create a new Zotero instance:

```
class pyzotero.zotero.Zotero(userID, userKey)
```

Parameters

- **userID** (*str*) – a valid Zotero API user ID
- **userKey** (*str*) – a valid Zotero API user key

Example:

```
zot = zotero.Zotero(123, ABC1234XYZ)
```

Additional parameters may be set on Read API methods using the following method. They are **optional**:

```
Zotero.add_parameters([limit=None, start=None, order=None, sort=None[, content=None[, style=None]]])
```

Parameters

- **limit** (*int*) – 1 – 99 or None
- **start** (*int*) – 1 – total number of items in your library or None
- **order** (*str*) – A valid Zotero field or None
- **sort** (*str*) – asc or desc or None
- **content** (*str*) – ‘html’ or ‘bib’, default: ‘html’. If ‘bib’ is passed, you may also pass:
- **style** (*str*) – Any valid CSL style in the Zotero style repository

Return type list of HTML strings or None

Example:

```
zot.add_parameters(limit=7, start=3)
```

Note: Any parameters you set will be valid **for the next call only**

The special parameters `content` and `style`:

Example:

```
zot.add_parameters(content='bib', format='mla')
```

If these are set, the return value is a **list** of UTF-8 formatted HTML `div` elements, each containing an item:

```
['<div class="csl-entry">(content)</div>', ... ]
```

READ API METHODS

4.1 Retrieving Items

`Zotero.items()`

Returns Zotero library items

Return type list of dicts

`Zotero.top()`

Returns top-level Zotero library items

Return type list of dicts

`Zotero.item(itemID)`

Returns a specific item

Parameters `itemID` (*str*) – a Zotero item ID

Return type list of dicts

`Zotero.children(itemID)`

Returns the child items of a specific item

Parameters `itemID` (*str*) – a Zotero item ID

Return type list of dicts

`Zotero.tag_items(itemID)`

Returns items for a specific tag

Parameters `itemID` (*str*) – a Zotero item ID

Return type list of dicts

`Zotero.group_items(groupID)`

Returns items from a specific group

Parameters `groupID` (*str*) – a Zotero group ID

Return type list of dicts

`Zotero.group_top(groupID)`

Returns top-level items from a specific group

Parameters `groupID` (*str*) – a Zotero group ID

Return type list of dicts

`Zotero.group_item(groupID, itemID)`

Returns a specific item from a specific group

Parameters

- **groupID** (*str*) – a Zotero group ID
- **itemID** (*str*) – a Zotero item ID

Return type list of dicts

`Zotero.group_item_children (groupID, itemID)`

Returns the child items of a specific item from a specific group

Parameters

- **groupID** (*str*) – a Zotero group ID
- **itemID** (*str*) – a Zotero item ID

Return type list of dicts

`Zotero.group_items_tag (groupID, tag)`

Returns a specific group's items for a specific tag

Parameters

- **groupID** (*str*) – a Zotero group ID
- **tag** (*str*) – a tag whose items you wish to return

Return type list of dicts

`Zotero.group_collection_items (groupID, collectionID)`

Returns a specific collection's items from a specific group

Parameters

- **groupID** (*str*) – a Zotero group ID
- **collectionID** (*str*) – a Zotero collection ID

Return type list of dicts

`Zotero.group_collection_item (groupID, collectionID, itemID)`

Returns a specific collection's item from a specific group

Parameters

- **groupID** (*str*) – a Zotero group ID
- **collectionID** (*str*) – a Zotero collection ID
- **itemID** (*str*) – a Zotero item ID

Return type list of dicts

`Zotero.group_collection_top (groupID, collectionID)`

Returns a specific collection's top-level items from a specific group

Parameters

- **groupID** (*str*) – a Zotero group ID
- **collectionID** – a Zotero collection ID

Return type list of dicts

`Zotero.collection_items (collectionID)`

Returns items from the specified collection

Parameters **collectionID** (*str*) – a Zotero collection ID

Return type list of dicts

`Zotero.get_subset(itemIDs)`

Retrieve an arbitrary set of non-adjacent items. Limited to 50 items per call.

Parameters `itemIDs` (*list*) – a list of Zotero Item IDs

Return type list of dicts

Example of returned data:

```
[{'DOI': '',
  'ISSN': '1747-1532',
  'abstractNote': '',
  'accessDate': '',
  'archive': '',
  'archiveLocation': '',
  'callNumber': '',
  'creators': [{'creatorType': 'author',
                  'firstName': 'T. J.',
                  'lastName': 'McIntyre'}],
  'date': '2007',
  'extra': '',
  'issue': '',
  'itemType': 'journalArticle',
  'journalAbbreviation': '',
  'language': '',
  'libraryCatalog': 'Google Scholar',
  'pages': '',
  'publicationTitle': 'Journal of Intellectual Property Law & Practice',
  'rights': '',
  'series': '',
  'seriesText': '',
  'seriesTitle': '',
  'shortTitle': 'Copyright in custom code',
  'tags': [],
  'title': 'Copyright in custom code: Who owns commissioned software?',
  'url': '',
  'volume': ''} ... ]
```

See *‘Hello World’* example, above

4.2 Retrieving Collections

`Zotero.collections()`

Returns a user’s collections

Return type list of dicts

`Zotero.collections_sub(collectionID)`

Returns a sub-collection from a specific collection

Parameters `collectionID` (*str*) – a Zotero library collection ID

Return type list of dicts

`Zotero.group_collections(groupID)`

Returns collections for a specific group

Parameters `groupID` (*str*) – a Zotero group ID

Return type list of dicts

`Zotero.group_collection(groupID, collectionID)`
Returns a specific collection from a specific group

Parameters

- **groupID** (*str*) – a Zotero group ID
- **collectionID** (*str*) – a Zotero collection ID

Return type list of dicts

Example of returned data:

```
[{'key': 'PRMD6BGB', 'name': "A Midsummer Night's Dream"} ... ]
```

4.3 Retrieving groups

`Zotero.groups()`

Retrieve the Zotero group data to which the current user key has access

Return type list of dicts

Example of returned data:

```
[{'description': u'%3Cp%3EBGGerman+Cinema+and+related+literature.%3C%2Fp%3E',  
  'fileEditing': u'none',  
  'group_id': u'153',  
  'hasImage': 1,  
  'libraryEditing': u'admins',  
  'libraryEnabled': 1,  
  'libraryReading': u'all',  
  'members': {u'0': 436,  
              u'1': 6972,  
              u'15': 499956,  
              u'16': 521307,  
              u'17': 619180},  
  'name': u'German Cinema',  
  'owner': 10421,  
  'type': u'PublicOpen',  
  'url': u''} ... ]
```

4.4 Retrieving Tags

`Zotero.tags()`

Returns a user's tags

Return type list of strings

`Zotero.item_tags(itemID)`

Returns tags from a specific item

Parameters **itemID** (*str*) – a valid Zotero library Item ID

Return type list of strings

`Zotero.group_tags(groupID)`

Returns tags from a specific group

Parameters **groupID** (*str*) – a valid Zotero library group ID

Return type list of strings

`Zotero.group_item_tags (groupID, itemID)`

Returns tags from a specific item from a specific group

Parameters

- **groupID** (*str*) – a valid Zotero library group ID
- **itemID** (*str*) – a valid Zotero library Item ID

Return type list of strings

Example of returned data:

```
['Authority in literature', 'Errata', ... ]
```

WRITE API METHODS

5.1 Item Methods

`Zotero.item_types()`

Returns a dict containing all available item types

Return type dict

`Zotero.item_fields()`

Returns a dict of all available item fields

Return type dict

`Zotero.item_creator_types(itemtype)`

Returns a dict of all valid creator types for the specified item type

Parameters `itemtype` (*str*) – a valid Zotero item type. A list of available item types can be obtained by the use of `item_types()`

Return type dict

`Zotero.item_template(itemtype)`

Returns an item creation template for the specified item type

Parameters `itemtype` (*str*) – a valid Zotero item type. A list of available item types can be obtained by the use of `item_types()`

Return type dict

`Zotero.create_item(items)`

Create Zotero library items.

Parameters `items` (*list*) – one or more dicts containing item data.

Return type list of dicts

Returns a copy of the created item(s), if successful. The use of `item_template()` is recommended in order to first obtain a dict with a structure which the API will accept. Example:

```
template = zot.item_template('book')
template['creators'][0]['firstName'] = 'Monty'
template['creators'][0]['lastName'] = 'Cantsin'
template['title'] = 'Maris Kundzins: A Life'
resp = zot.create_item([template])
```

If successful, `resp` will have the same structure as items retrieved with an `items()` call, e.g. a list of one or more dicts (see *Item Data*, above).

`Zotero.update_item(item)`

Update an item in your library.

Parameters `item` (*dict*) – a dict containing item data.

Return type Boolean

Example:

```
i = zot.items()
# see above for example of returned item structure
# modify the latest item which was added to your library
i[0]['title'] = 'The Sheltering Sky'
i[0]['creators'][0]['firstName'] = 'Paul'
i[0]['creators'][0]['lastName'] = 'Bowles'
zot.update_item(i[0])
```

`Zotero.delete_item(item)`

Delete an item from your library.

Parameters `item` (*dict*) – a dict containing item data. As in the previous example, you must first retrieve the item(s) you wish to delete, and pass it/them to the method one by one. Deletion of multiple items is most easily accomplished using e.g. a `for` loop.

Return type Boolean

Example:

```
i = zot.items()
# only delete the last five items we added
to_delete = i[:6]
for d in to_delete:
    zot.delete_item(d)
```

5.2 Collection Methods

`Zotero.create_collection(name)`

Create a new collection in the Zotero library.

Parameters `name` (*dict*) – dict containing the key `name` and the value of the new collection name you wish to create. May optionally contain a `parent` key, the value of which is the ID of an existing collection. If this is set, the collection will be created as a child of that collection.

Return type Boolean

`Zotero.addto_collection(collection, items)`

Add the specified item(s) to the specified collection.

Parameters

- **collection** (*str*) – a collection key
- **items** (*list*) – list of one or more item dicts.

Return type Boolean

Collection keys can be obtained by a call to `collections()` (see details above).

`Zotero.deletefrom_collection(collection, item)`

Remove the specified item from the specified collection.

Parameters

- **collection** (*str*) – a collection key
- **item** (*dict*) – dict containing item data.

Return type Boolean

See the `delete_item()` example for multiple-item removal.

`Zotero.update_collection(collection)`

Update an existing collection name.

Parameters **collection** (*dict*) – a dict containing collection data, previously retrieved using one of the Collections calls (e.g. `collections()`).

Return type Boolean

Example:

```
# get existing collections, which will return a list of dicts
c = zot.collections()
# rename the last collection created in the library
c[0]['name'] = 'Whither Digital Humanities?'
# update collection name on the server
zot.update_collection(c[0])
```

`Zotero.delete_collection(collection)`

Delete a collection from the Zotero library.

Parameters **collection** (*dict*) – a dict containing collection data, previously retrieved using one of the Collections calls (e.g. `collections()`).

Return type Boolean

See the `delete_item()` example for ways to delete multiple collections.

NOTES

All Read API methods return **lists** of **dicts** or, in the case of tag methods, **lists** of **strings**. Most Write API methods return either `True` if successful, or raise an error. See `zotero_errors.py` for a full listing of these.

Warning: URL parameters will supersede API calls which should return e.g. a single item: `https://api.zotero.org/users/436/items/ABC?start=50&limit=10` will return 10 items beginning at position 50, even though ABC does not exist. Be aware of this, and don't pass URL parameters which do not apply to a given API method. This is a limitation/foible of the Zotero API, and there's nothing I can do about it.

LICENSE

Pyzotero is licensed under the [GNU GPL Version 3](#) license, in line with Zotero's own license. Details can be found in the file `license.txt`.

PYTHON MODULE INDEX

p

`pyzotero.zotero`, [1](#)

INDEX

A

add_parameters() (pyzotero.zotero.Zotero method), 7
addto_collection() (pyzotero.zotero.Zotero method), 16

C

children() (pyzotero.zotero.Zotero method), 9
collection_items() (pyzotero.zotero.Zotero method), 10
collections() (pyzotero.zotero.Zotero method), 11
collections_sub() (pyzotero.zotero.Zotero method), 11
create_collection() (pyzotero.zotero.Zotero method), 16
create_item() (pyzotero.zotero.Zotero method), 15

D

delete_collection() (pyzotero.zotero.Zotero method), 17
delete_item() (pyzotero.zotero.Zotero method), 16
deletefrom_collection() (pyzotero.zotero.Zotero method), 16

G

get_subset() (pyzotero.zotero.Zotero method), 11
group_collection() (pyzotero.zotero.Zotero method), 12
group_collection_item() (pyzotero.zotero.Zotero method), 10
group_collection_items() (pyzotero.zotero.Zotero method), 10
group_collection_top() (pyzotero.zotero.Zotero method), 10
group_collections() (pyzotero.zotero.Zotero method), 11
group_item() (pyzotero.zotero.Zotero method), 9
group_item_children() (pyzotero.zotero.Zotero method), 10
group_item_tags() (pyzotero.zotero.Zotero method), 13
group_items() (pyzotero.zotero.Zotero method), 9
group_items_tag() (pyzotero.zotero.Zotero method), 10
group_tags() (pyzotero.zotero.Zotero method), 12
group_top() (pyzotero.zotero.Zotero method), 9
groups() (pyzotero.zotero.Zotero method), 12

I

item() (pyzotero.zotero.Zotero method), 9
item_creator_types() (pyzotero.zotero.Zotero method), 15

item_fields() (pyzotero.zotero.Zotero method), 15
item_tags() (pyzotero.zotero.Zotero method), 12
item_template() (pyzotero.zotero.Zotero method), 15
item_types() (pyzotero.zotero.Zotero method), 15
items() (pyzotero.zotero.Zotero method), 9

P

pyzotero.zotero (module), 1

T

tag_items() (pyzotero.zotero.Zotero method), 9
tags() (pyzotero.zotero.Zotero method), 12
top() (pyzotero.zotero.Zotero method), 9

U

update_collection() (pyzotero.zotero.Zotero method), 17
update_item() (pyzotero.zotero.Zotero method), 15

Z

Zotero (class in pyzotero.zotero), 7