Efficiently Searching



Giovanni Dicanio
AUTHOR, SOFTWARE ENGINEER
https://blogs.msmvps.com/gdicanio



Overview



Linear search

Binary search

Theory (slides) & practice (demos)


«Big-O» notation






64 80 77 25 88 32




























11	22	33	64	77	80	88
0	1	2	3	4	5	6




ELEMENTS 11 22 33 64 77 80 88 0 1 2 3 4 5 6







11	22	33	64	77	80	88
0	1	2	3	4	5	6









\mathcal{L}	80
П '	









































Repeat the process in the right half



























Introducing the «Big O» Notation













Estimate the Runtime Performance






«Big O» for Data Transfer












Internet




Transferring Big (~100 GB) Files



Transferring Big (~100 GB) Files







1-hour drive

Download: 5 Mbps


Size: 100 GB

+50 Hours






Data Transfer Algorithms







«Big-O» of Data Transfer Algorithms






O(1) Constant time
Independent of data size

Linear
Proportional to data size

O(N)




Linear vs. Constant Complexity






Linear vs. Constant Complexity







Linear vs. Constant Complexity




«Big-O» → Trends










































For *sorted* arrays, prefer *binary* search to linear search



Summary



Linear search

Binary search

Runtime asymptotic analysis

O(N) vs. O(log(N))

