

# Threads

# Processes and Threads

- Traditional processes have two characteristics:
  - Resource Ownership
    - ▶ Process includes a virtual address space to hold the process image
      - the OS provides protection to prevent unwanted interference between processes with respect to resources
  - Scheduling/Execution
    - ▶ Follows an execution path that may be interleaved with other processes
      - a process has an execution state (Running, Ready, etc.) and a dispatching priority and is scheduled and dispatched by the OS
      - traditional processes are sequential; i.e. only one execution path


# Processes and Threads

- Multithreading - The ability of an OS to support multiple, concurrent paths of execution within a single process
- The unit of resource ownership is referred to as a process or task
- The unit of dispatching is referred to as a thread or lightweight process


# Threads

- A thread or lightweight process (LWP) is a basic unit of CPU utilization and comprises following:
  - A thread ID
  - A program counter
  - A register set
  - A stack
  
- A thread shares the following with its parent process and siblings:
  - Code section
  - Data section
  - Memory address space/ global memory
  - I/O devices
  - Other OS resources such as open files and signals

# Single and Multithreaded Processes



single-threaded process




multithreaded process

# Examples of Multithreaded Applications

- An application that creates photo thumbnails from a collection of images may use a separate thread to generate a thumbnail from each separate image.
- A web browser might have one thread display images or text while another thread retrieves data from the network.

# Multithreaded Server Architecture



# Benefits

- Takes less time to create and terminate a thread than a process
- Context switching is faster – Switching between two threads takes less time than switching between processes
- Minimized communication overhead – Threads enhance efficiency in communication between programs
- Responsiveness – may allow continued execution if part of process is blocked, especially important for user interfaces
- Resource Sharing – threads share resources of process, easier than shared memory or message passing
- Economy – cheaper than process creation, thread switching lower overhead than context switching
- Scalability – process can take advantage of multicore architectures




# Thread Control Block (TCB)

- Like a PCB, a TCB also contains the information necessary for a thread to execute
- Each thread has its own TCB.
- TCB information is private to each thread.
- The contents are:
  - A pointer that will enable it to be chained into a linked list
  - Value of its stack pointer
  - A stack area that includes local variables
  - Thread number, type, or name
  - Age of the thread, or how long this thread has been active
  - Priority
  - Resources that this thread has been granted

# Thread State Diagram

- A thread may undergo transitions between different states (like a process) during its lifetime.
- The thread state diagram consists of the following states:
  - Ready
  - Running
  - Blocked



# Operations on Threads

- Thread operations associated with a change in thread state are
  - Spawn
  - Block
  - Unblock
  - Finish

# Thread Synchronization


- It is necessary to synchronize the activities of the various threads
  - All threads of a process share the same address space and other resources
  - Any alteration of a resource by one thread affects the other threads in the same process

# Types of Threads

- There are two broad categories of thread implementation:
  - User-Level Thread (ULT) – Thread Libraries
  - Kernel-Level Thread (KLT) – System Calls


# User-Level Threads (ULTs)

- Thread management is done by the application that uses thread library.
- The thread library manages all threads.
- The kernel is not aware of the existence of threads.
- Three primary thread libraries:
  - POSIX Pthreads
  - Windows threads
  - Java threads



# Relationships Between ULT States and Process States

- Example



Colored state  
is current state

# Advantages of ULTs

- Thread switching does not require kernel mode privileges (no mode switches)
- Scheduling can be application specific
- ULTs can run on any OS



# Disadvantages of ULTs


- In a typical OS many system calls are blocking in nature
  - As a result, when a ULT executes a system call, not only is that thread blocked, but all of the threads within the process are blocked
- The kernel can only assign processes to processors.

# Overcoming ULT Disadvantages

- Writing an application as multiple processes rather than multiple threads
- Jacketing
  - Converts a blocking system call into a non-blocking system call

# Kernel-Level Threads (KLTs)

- Thread management is done by the kernel.
- There is no thread library.
- No thread management is done by the application.
- Examples – virtually all general -purpose operating systems, including:
  - Windows
  - Linux
  - Mac OS X
  - iOS
  - Android



# Advantages of KLTs


- The kernel can simultaneously schedule multiple threads from the same process on multiple processors.
- If one thread in a process is blocked, the kernel can schedule another thread of the same process.

# Disadvantage of KLTs

- The transfer of control from one thread to another within the same process requires a mode switch to the kernel.

# Combined Approaches

- Thread creation is done in the user space.
- Bulk of scheduling and synchronization of threads is by the application.
- User-level threads (i.e. threads library) are invisible to the OS.
- Solaris is an example.




# Multithreading Models

- Many-to-One
- One-to-One
- Many-to-Many

# Many-to-One


- Many user-level threads mapped to single kernel thread
- One thread blocking causes all to block
- Multiple threads may not run in parallel on muticore system because only one may be in kernel at a time
- Few systems currently use this model
- Examples:
  - Solaris Green Threads
  - GNU Portable Threads






# One-to-One

- Each user-level thread maps to kernel thread
- Creating a user-level thread creates a kernel thread
- More concurrency than many-to-one
- Number of threads per process sometimes restricted due to overhead
- Examples
  - Windows
  - Linux




# Many-to-Many Model

- Allows many user level threads to be mapped to many kernel threads
- Allows the operating system to create a sufficient number of kernel threads
- Windows with the *ThreadFiber* package
- Otherwise not very common



# Two-level Model

- Similar to M:M, except that it allows a user thread to be **bound** to kernel thread




# Multicore Programming


- Multicore or multiprocessor systems putting pressure on programmers, challenges include:
  - Dividing activities
  - Balance
  - Data splitting
  - Data dependency
  - Testing and debugging
- *Parallelism* implies a system can perform more than one task simultaneously
- *Concurrency* supports more than one task making progress
  - Single processor / core, scheduler providing concurrency

# Concurrency vs. Parallelism

- Concurrent execution on single-core system:




- Parallelism on a multi-core system:



# Multicore Programming

- Types of parallelism
  - Data parallelism – distributes subsets of the same data across multiple cores, same operation on each
  - Task parallelism – distributing threads across cores, each thread performing unique operation

# Data and Task Parallelism



# Amdahl's Law

- Identifies performance gains from adding additional cores to an application that has both serial and parallel components
- $S$  is serial portion
- $N$  processing cores

$$speedup \leq \frac{1}{S + \frac{(1-S)}{N}}$$


- That is, if application is 75% parallel / 25% serial, moving from 1 to 2 cores results in speedup of 1.6 times
- As  $N$  approaches infinity, speedup approaches  $1 / S$

Serial portion of an application has disproportionate effect on performance gained by adding additional cores

- But does the law take into account contemporary multicore systems?



# Amdahl's Law



# Thread Libraries

- Thread library provides programmer with API for creating and managing threads
- Two primary ways of implementing
  - Library entirely in user space
  - Kernel-level library supported by the OS

# Pthreads

- May be provided either as user-level or kernel-level
- A POSIX standard (IEEE 1003.1c) API for thread creation and synchronization
- *Specification, not implementation*
- API specifies behavior of the thread library, implementation is up to development of the library
- Common in UNIX operating systems (Linux & Mac OS X)

# Pthreads Example

```
#include <pthread.h>
#include <stdio.h>

#include <stdlib.h>

int sum; /* this data is shared by the thread(s) */
void *runner(void *param); /* threads call this function */

int main(int argc, char *argv[])
{
    pthread_t tid; /* the thread identifier */
    pthread_attr_t attr; /* set of thread attributes */

    /* set the default attributes of the thread */
    pthread_attr_init(&attr);
    /* create the thread */
    pthread_create(&tid, &attr, runner, argv[1]);
    /* wait for the thread to exit */
    pthread_join(tid, NULL);

    printf("sum = %d\n", sum);
}
```

# Pthreads Example (Cont.)

```
/* The thread will execute in this function */  
void *runner(void *param)  
{  
    int i, upper = atoi(param);  
    sum = 0;  
  
    for (i = 1; i <= upper; i++)  
        sum += i;  
  
    pthread_exit(0);  
}
```

# Pthreads Code for Joining 10 Threads

```
#define NUM_THREADS 10

/* an array of threads to be joined upon */
pthread_t workers[NUM_THREADS];

for (int i = 0; i < NUM_THREADS; i++)
    pthread_join(workers[i], NULL);
```

# Windows Multithreaded C Program

```
#include <windows.h>
#include <stdio.h>
DWORD Sum; /* data is shared by the thread(s) */

/* The thread will execute in this function */
DWORD WINAPI Summation(LPVOID Param)
{
    DWORD Upper = *(DWORD*)Param;
    for (DWORD i = 1; i <= Upper; i++)
        Sum += i;
    return 0;
}
```

# Windows Multithreaded C Program (Cont.)

```
int main(int argc, char *argv[])
{
    DWORD ThreadId;
    HANDLE ThreadHandle;
    int Param;

    Param = atoi(argv[1]);
    /* create the thread */
    ThreadHandle = CreateThread(
        NULL, /* default security attributes */
        0, /* default stack size */
        Summation, /* thread function */
        &Param, /* parameter to thread function */
        0, /* default creation flags */
        &ThreadId); /* returns the thread identifier */

    /* now wait for the thread to finish */
    WaitForSingleObject(ThreadHandle,INFINITE);

    /* close the thread handle */
    CloseHandle(ThreadHandle);

    printf("sum = %d\n",Sum);
}
```



# Java Threads

- Java threads are managed by the JVM
- Typically implemented using the threads model provided by underlying OS
- Java threads may be created by:
  - Extending Thread class
  - Implementing the Runnable interface

```
public interface Runnable
{
    public abstract void run();
}
```

- Standard practice is to implement Runnable interface

# Java Threads

Implementing Runnable interface:

```
class Task implements Runnable
{
    public void run() {
        System.out.println("I am a thread.");
    }
}
```

Creating a thread:

```
Thread worker = new Thread(new Task());
worker.start();
```

Waiting on a thread:

```
try {
    worker.join();
}
catch (InterruptedException ie) { }
```

# Java Executor Framework

- Rather than explicitly creating threads, Java also allows thread creation around the Executor interface:

```
public interface Executor
{
    void execute(Runnable command);
}
```

- The Executor is used as follows:

```
Executor service = new Executor();
service.execute(new Task());
```

# Java Executor Framework

```
import java.util.concurrent.*;

class Summation implements Callable<Integer>
{
    private int upper;
    public Summation(int upper) {
        this.upper = upper;
    }

    /* The thread will execute in this method */
    public Integer call() {
        int sum = 0;
        for (int i = 1; i <= upper; i++)
            sum += i;

        return new Integer(sum);
    }
}
```

# Java Executor Framework (Cont.)

```
public class Driver
{
    public static void main(String[] args) {
        int upper = Integer.parseInt(args[0]);

        ExecutorService pool = Executors.newSingleThreadExecutor();
        Future<Integer> result = pool.submit(new Summation(upper));

        try {
            System.out.println("sum = " + result.get());
        } catch (InterruptedException | ExecutionException ie) { }
    }
}
```

# Implicit Threading

- Growing in popularity as numbers of threads increase, program correctness more difficult with explicit threads
- Creation and management of threads done by compilers and run-time libraries rather than programmers
- Five methods explored
  - Thread Pools
  - Fork-Join
  - OpenMP
  - Grand Central Dispatch
  - Intel Threading Building Blocks

# Thread Pools

- Create a number of threads in a pool where they await work
- Advantages:
  - Usually slightly faster to service a request with an existing thread than create a new thread
  - Allows the number of threads in the application(s) to be bound to the size of the pool
  - Separating task to be performed from mechanics of creating task allows different strategies for running task
    - ▶ i.e., Tasks could be scheduled to run periodically
- Windows API supports thread pools:

```
DWORD WINAPI PoolFunction(AVOID Param) {  
    /*  
     * this function runs as a separate thread.  
     */  
}
```

# Java Thread Pools

- Three factory methods for creating thread pools in Executors class:
  - `static ExecutorService newSingleThreadExecutor()`
  - `static ExecutorService newFixedThreadPool(int size)`
  - `static ExecutorService newCachedThreadPool()`



# Java Thread Pools (Cont.)

```
import java.util.concurrent.*;

public class ThreadPoolExample
{
    public static void main(String[] args) {
        int numTasks = Integer.parseInt(args[0].trim());


        /* Create the thread pool */
        ExecutorService pool = Executors.newCachedThreadPool();

        /* Run each task using a thread in the pool */
        for (int i = 0; i < numTasks; i++)
            pool.execute(new Task());

        /* Shut down the pool once all threads have completed */
        pool.shutdown();
    }
}
```

# Fork-Join Parallelism

- Multiple threads (tasks) are forked, and then joined.



# Fork-Join Parallelism


- General algorithm for fork-join strategy:

```
Task(problem)
  if problem is small enough
    solve the problem directly
  else
    subtask1 = fork(new Task(subset of problem))
    subtask2 = fork(new Task(subset of problem))

    result1 = join(subtask1)
    result2 = join(subtask2)

    return combined results
```

# Fork-Join Parallelism



# Fork-Join Parallelism in Java

```
ForkJoinPool pool = new ForkJoinPool();  
// array contains the integers to be summed  
int[] array = new int[SIZE];  
  
SumTask task = new SumTask(0, SIZE - 1, array);  
int sum = pool.invoke(task);
```

# Fork-Join Parallelism in Java

```
import java.util.concurrent.*;

public class SumTask extends RecursiveTask<Integer>
{
    static final int THRESHOLD = 1000;

    private int begin;
    private int end;
    private int[] array;

    public SumTask(int begin, int end, int[] array) {
        this.begin = begin;
        this.end = end;
        this.array = array;
    }

    protected Integer compute() {
        if (end - begin < THRESHOLD) {
            int sum = 0;
            for (int i = begin; i <= end; i++)
                sum += array[i];

            return sum;
        }
        else {
            int mid = (begin + end) / 2;


            SumTask leftTask = new SumTask(begin, mid, array);
            SumTask rightTask = new SumTask(mid + 1, end, array);

            leftTask.fork();
            rightTask.fork();

            return rightTask.join() + leftTask.join();
        }
    }
}
```

# Fork-Join Parallelism in Java

- The `ForkJoinTask` is an abstract base class
- `RecursiveTask` and `RecursiveAction` classes extend `ForkJoinTask`
- `RecursiveTask` returns a result (via the return value from the `compute()` method)
- `RecursiveAction` does not return a result



# OpenMP

- Set of compiler directives and an API for C, C++, FORTRAN
- Provides support for parallel programming in shared-memory environments
- Identifies parallel regions – blocks of code that can run in parallel

```
#pragma omp parallel
```

Create as many threads as there are cores

```
#include <omp.h>
#include <stdio.h>

int main(int argc, char *argv[])
{
    /* sequential code */

    #pragma omp parallel
    {
        printf("I am a parallel region.");
    }

    /* sequential code */

    return 0;
}
```



# Run the Loop in Parallel

- Run the for loop in parallel

```
#pragma omp parallel for  
for (i = 0; i < N; i++) {  
    c[i] = a[i] + b[i];  
}
```

# Grand Central Dispatch

- Apple technology for macOS and iOS operating systems
- Extensions to C, C++ and Objective-C languages, API, and run-time library
- Allows identification of parallel sections
- Manages most of the details of threading
- Block is in “^{}” :

```
^{ printf("I am a block"); }
```

- Blocks placed in dispatch queue
  - Assigned to available thread in thread pool when removed from queue

# Grand Central Dispatch

- Two types of dispatch queues:
  - serial – blocks removed in FIFO order, queue is per process, called main queue
    - ▶ Programmers can create additional serial queues within program
  - concurrent – removed in FIFO order but several may be removed at a time
    - ▶ Four system wide queues divided by quality of service:
      - `QOS_CLASS_USER_INTERACTIVE`
      - `QOS_CLASS_USER_INITIATED`
      - `QOS_CLASS_USER_UTILITY`
      - `QOS_CLASS_USER_BACKGROUND`

# Grand Central Dispatch

- For the Swift language a task is defined as a closure – similar to a block, minus the caret
- Closures are submitted to the queue using the `dispatch_async()` function:

```
let queue = dispatch_get_global_queue  
    (QOS_CLASS_USER_INITIATED, 0)
```

```
dispatch_async(queue, { print("I am a closure.") })
```

# Intel Threading Building Blocks (TBB)

- Template library for designing parallel C++ programs
- A serial version of a simple for loop

```
for (int i = 0; i < n; i++) {  
    apply(v[i]);  
}
```

- The same for loop written using TBB with `parallel_for` statement:

```
parallel_for (size_t(0), n, [=](size_t i) {apply(v[i]);});
```

# Threading Issues

- Semantics of fork() and exec() system calls
- Signal handling
  - Synchronous and asynchronous
- Thread cancellation of target thread
  - Asynchronous or deferred
- Thread-local storage
- Scheduler Activations

# Semantics of `fork()` and `exec()`

- Does `fork()` duplicate only the calling thread or all threads?
  - Some UNIXes have two versions of `fork`
- `exec()` usually works as normal – replace the running process including all threads

# Signal Handling

- Signals are used in UNIX systems to notify a process that a particular event has occurred.
- A signal handler is used to process signals
  1. Signal is generated by particular event
  2. Signal is delivered to a process
  3. Signal is handled by one of two signal handlers:
    1. default
    2. user-defined
- Every signal has default handler that kernel runs when handling signal
  - User-defined signal handler can override default
  - For single-threaded, signal delivered to process



# Signal Handling (Cont.)

- Where should a signal be delivered for multi-threaded?
  - Deliver the signal to the thread to which the signal applies
  - Deliver the signal to every thread in the process
  - Deliver the signal to certain threads in the process
  - Assign a specific thread to receive all signals for the process

# Thread Cancellation

- Terminating a thread before it has finished
- Thread to be canceled is target thread
- Two general approaches:
  - Asynchronous cancellation terminates the target thread immediately
  - Deferred cancellation allows the target thread to periodically check if it should be cancelled
- Pthread code to create and cancel a thread:

```
pthread_t tid;

/* create the thread */
pthread_create(&tid, 0, worker, NULL);

. . .

/* cancel the thread */
pthread_cancel(tid);

/* wait for the thread to terminate */
pthread_join(tid, NULL);
```

# Thread Cancellation (Cont.)

- Invoking thread cancellation requests cancellation, but actual cancellation depends on thread state

Mode	State	Type
Off	Disabled	–
Deferred	Enabled	Deferred
Asynchronous	Enabled	Asynchronous

- If thread has cancellation disabled, cancellation remains pending until thread enables it
- Default type is deferred
  - Cancellation only occurs when thread reaches cancellation point
    - ▶ i.e., `pthread_testcancel()`
    - ▶ Then cleanup handler is invoked
- On Linux systems, thread cancellation is handled through signals

# Thread Cancellation in Java

- Deferred cancellation uses the `interrupt()` method, which sets the interrupted status of a thread.

```
Thread worker;
```

```
. . .
```

```
/* set the interruption status of the thread */  
worker.interrupt()
```

- A thread can then check to see if it has been interrupted:


```
while (!Thread.currentThread().isInterrupted()) {  
    . . .  
}
```

# Thread-Local Storage

- Thread-local storage (TLS) allows each thread to have its own copy of data
- Useful when you do not have control over the thread creation process (i.e., when using a thread pool)
- Different from local variables
  - Local variables visible only during single function invocation
  - TLS visible across function invocations
- Similar to `static` data
  - TLS is unique to each thread

# Scheduler Activations

- Both M:M and Two-level models require communication to maintain the appropriate number of kernel threads allocated to the application
- Typically use an intermediate data structure between user and kernel threads – lightweight process (LWP)
  - Appears to be a virtual processor on which process can schedule user thread to run
  - Each LWP attached to kernel thread
  - How many LWPs to create?
- Scheduler activations provide upcalls - a communication mechanism from the kernel to the upcall handler in the thread library
- This communication allows an application to maintain the correct number kernel threads



# Operating System Examples

- Windows Threads
- Linux Threads

# Windows Threads


- Windows API – primary API for Windows applications
- Implements the one-to-one mapping, kernel-level
- Each thread contains
  - A thread id
  - Register set representing state of processor
  - Separate user and kernel stacks for when thread runs in user mode or kernel mode
  - Private data storage area used by run-time libraries and dynamic link libraries (DLLs)
- The register set, stacks, and private storage area are known as the context of the thread



# Windows Threads (Cont.)

- The primary data structures of a thread include:
  - ETHREAD (executive thread block) – includes pointer to process to which thread belongs and to KTHREAD, in kernel space
  - KTHREAD (kernel thread block) – scheduling and synchronization info, kernel-mode stack, pointer to TEB, in kernel space
  - TEB (thread environment block) – thread id, user-mode stack, thread-local storage, in user space

# Windows Threads Data Structures



# Linux Threads

- Linux refers to them as *tasks* rather than *threads*
- Thread creation is done through `clone()` system call
- `clone()` allows a child task to share the address space of the parent task (process)
  - Flags control behavior

flag	meaning
<code>CLONE_FS</code>	File-system information is shared.
<code>CLONE_VM</code>	The same memory space is shared.
<code>CLONE_SIGHAND</code>	Signal handlers are shared.
<code>CLONE_FILES</code>	The set of open files is shared.

- `struct task_struct` points to process data structures (shared or unique)

# References

- Operating Systems Concepts by Silberschatz, Galvin, and Gagne
- Operating Systems, by William Stallings