

# Sorting



Data Structures

Ching-Fang Hsu

Department of Computer Science and Information Engineering

National Cheng Kung University



# Sequential Search

- ❖ The efficiency of a searching strategy depends on the arrangement of records in the list.
  - ❑ Very efficient if the records are ordered
- ❖ What is “sequential search”?
  - ❑ The search examines the list of records in left-to-right or right-to-left order.
  - ❑ p. 334, Program 7.1

```
int seqSearch(element a[], int k, int n)
{
    /* search a[1:n]; return the least i such that
       a[i].key = k; return 0, if k is not in the array */
    int i;
    for (i = 1; i <= n && a[i].key != k; i++)
        ;
    if (i > n) return 0;
    return i;
}
```

### Program 7.1 Sequential search

# Sequential Search (contd.)

- ❑ An unsuccessful search requires  $n$  key comparisons.
  - ◆ The worst case time complexity:  $O(n)$
- ❑ The # of comparisons made in a successful search depends on the position in the array.
  - ◆ The average case:  $O(n)$

$$\left( \sum_{1 \leq i \leq n} i \right) / n = (n + 1) / 2$$



# Binary Search

Record必須為排序好的，才能用中位數作排序

- ❖ After a comparison, either the search ends successfully or the size of the unsearched portion of the list is reduced by about one half.
  - After  $j$  key comparisons, the unsearched part is at most  $\lceil n/2^j \rceil$ .
    - ◆  $O(\log n)$  comparisons are required in the worst case.

# Definitions

## ❖ Two important uses of sorting

- ❑ As an aid to searching
- ❑ As a means for matching entries in lists
- ❑ Applications in areas such as optimization, graph theory, and job scheduling as well

## ❖ What is “sorting”?

### ❑ Givens

- ◆ A list of records  $(R_1, R_2, \dots, R_n)$ , in which each record,  $R_i$ , has key value  $K_i$ . 由小排到大

- ❑ Finding a permutation  $\sigma$ , such that  $K_{\sigma(i)} \leq K_{\sigma(i+1)}$ ,  $1 < i \leq n - 1$ . The desired ordering is  $(R_{\sigma(1)}, R_{\sigma(2)}, \dots, R_{\sigma(n)})$ .

# Definitions (contd.)

排列不唯一：不同record，key值相同

- ❑ The permutation **may not be unique** since a list could have several identical key values.
- ❑ A sorting method is **stable** if the generated permutation  $\sigma_s$  is unique and has the following properties
  - ◆  $K_{\sigma_s(i)} \leq K_{\sigma_s(i+1)}$  for  $0 < i \leq n - 1$
  - ◆ If  $i < j$  and  $K_i == K_j$  in the input list, then  $R_i$  precedes  $R_j$  in the sorted list. 就key值相同的record，排序只與輸入先後順序有關（不更動key值一樣的record），不額外花時間在重新排序key值相同的record
- ❑ We characterize sorting methods into two broad categories.
  - ◆ **Internal methods** 所有資料全部存部存放在記憶體內
    - ⇒ Used when the list to be sorted is small enough so that the entire sort can be carried out in main memory
  - ◆ **External methods** 資料量較大
    - ⇒ Used on larger lists



# Definitions (contd.)

- ⇒ An **internal sort** -- the list is small enough to sort entirely in main memory
- ⇒ An **external sort** is used when there is too much information to fit into main memory.
  - ★ The file must be brought into the main memory in pieces until the entire file is sorted.



# Insertion Sort

- ❖ The basic step 每次讀一個新record和原排序好的record作安插
  - ❑ Inserting a new record into a sorted sequence of  $i$  records in such a way that the resulting sequence of size  $i+1$  is also ordered.
  - ❑ p. 338, Program 7.4
- ❖ Begin with the ordered sequence  $a[1]$  and successively insert the records  $a[2], a[3], \dots, a[n]$ .
  - ❑ Complete by making  $n-1$  insertions for a  $n$ -record list
  - ❑ p. 338, Program 7.5

# Insertion Sort (contd.)

## ❖ Analysis 適用於資料數目不多（處理較簡單）

❑ In the worst case,  $insert(e, a, i)$  makes  $i$  comparisons before making the insertion.

◆ The computing time for inserting one record into the ordered list is  $O(i)$ . record間隔，包含頭尾，總共有 $i+1$ 個間隔

❑ The total worst case time is  $O(\sum_{i=1}^{n-1} (i+1)) = O(n^2)$

❑ Left out of order (LOO)

◆  $R_i$  is LOO iff  $R_i < \max_{1 \leq j < i} \{R_j\}$  第 $i$ 個record的key恆小於最大一個record的key

◆ The insertion step is executed only for those records LOO. 需做data movement（一定要往前插入）

❑ Stable

◆ Very desirable when only a very few records are LOO (i.e.,  $k \ll n$ )  $k$ : LOO個數

## 一次insertion

```
void insert(element e, element a[], int i) 從a[i]開始存
/* insert e into the ordered list a[1:i] such that the
   resulting list a[1:i+1] is also ordered, the array a
   must have space allocated for at least i+2 elements */
a[0] = e; 讀入的暫存在a[0]
while (e.key < a[i].key) 從已排好的record往前比
                        (若key比排好的最後一個小 (第i個) ,
                        插在i之前)
{
    a[i+1] = a[i]; i往後退
    i--; i往下遞減
}
a[i+1] = e; 當e.key >= a[i].key跳出while, 插在i之後
}
```

Program 7.4: Insertion into a sorted list

---

```
void insertionSort(element a[], int n)
{/* sort a[1:n] into nondecreasing order */
    int j; 從a [2] 開始
    for (j = 2; j <= n; j++) {
        element temp = a[j];
        insert(temp, a, j-1);
    }
}
```

---

**Program 7.5:** Insertion sort

# Insertion Sort (contd.)

## ❖ Variations

### ❑ Binary Insertion Sort 減少比較次數，用binary取代sequential

- ◆ Reduce the number of comparisons by replacing the sequential searching technique with binary search
- ◆ The number of record moves remains unchanged.

### ❑ Linked Insertion Sort

- ◆ Using linked list representation rather than an array
- ◆ No record moves
- ◆ Retain sequential search




# Quick Sort

使用recursion

- ❖ The best in average behavior among all the sorting methods we shall be studying
- ❖ The pivot key 控制record分邊
  - ❑ The key currently controlling the insertion
- ❖ Step 1: Select a pivot record from among the records to be sorted.
- ❖ Step 2: Reorder the records to be sorted. 和pivot key比較，分邊
- ❖ Step 3: The records to the left of the pivot and those to its right are sorted independently.
  - ❑ Recursion!

# Quick Sort (contd.)



⇒ Recursion!

❖ p. 341, Program 7.6

❑ Ex. p. 340, Example 7.3

❖ Analysis

❑ The time to position a record in a file of size  $n$  is  $O(n)$ .

# Quick Sort (contd.)

- Let  $T(n)$  be the time taken to sort a file of  $n$  records. Also assume that the file splits roughly into two equal parts each time a record is positioned correctly.

$$\begin{aligned} \blacklozenge T(n) &\leq cn + 2T(n/2), \text{ for some constant } c \\ &\leq cn + 2(cn/2 + 2T(n/4)) \\ &\leq 2cn + 4T(n/4) \\ &\vdots \\ &\leq cn \log_2 n + nT(1) = O(n \log_2 n) \end{aligned}$$

- The worst-case behavior is  $O(n^2)$ .



# Quick Sort (contd.)

- ❖ The best of the internal sorting methods as far as average computing time is concerned
- ❖ **Lemma 7.1** (The average computing time for quick sort)

□ Let  $T_{avg}(n)$  be the expected time for quicksort to sort a file with  $n$  records. Then there exists a constant  $k$  such that  $T_{avg}(n) \leq kn \log_e n$  for  $n \geq 2$ .

□ 
$$T_{avg}(n) \leq cn + \frac{1}{n} \sum_{j=0}^{n-1} (T_{avg}(j) + T_{avg}(n-j-1)) = cn + \frac{2}{n} \sum_{j=0}^{n-1} T_{avg}(j), n \geq 2$$

□ By induction on  $n$



# Quick Sort (contd.)

## ❖ Variation

- ❑ Quick sort using a **median-of-three**

- ◆ A better choice for this pivot is the median of the first, middle, and last keys in the current list.



# Merge Sort

❖ How to merge two sorted lists to get a single sorted list?

- ❑ p. 346, Program 7.7
- ❑  $O(n)$  additional space
- ❑ Time complexity:  $O(n)$

❖ **Iterative merge sort**

- ❑  $n$  sorted lists, each of length 1
- ❑ Merge sublists pairwise to obtain  $n/2$  lists of size 2
- ❑ Then merge the  $n/2$  lists pairwise, and so on, until a we are left with only one sublist.

```

void merge(element initList[], element mergedList[],
           int i, int m, int n)
{
    /* the sorted lists initList[i:m] and initList[m+1:n] are
       merged to obtain the sorted list mergedList[i:n] */
    int j, k, t;
    j = m+1;           /* index for the second sublist */
    k = i;              /* index for the merged list */

    while (i <= m && j <= n) {
        if (initList[i].key <= initList[j].key)
            mergedList[k++] = initList[i++];
        else
            mergedList[k++] = initList[j++];
    }
    if (i > m)
        /* mergedList[k:n] = initList[j:n] */
        for (t = j; t <= n; t++)
            mergedList[t] = initList[t];
    else
        /* mergedList[k:n] = initList[i:m] */
        for (t = i; t <= m; t++)
            mergedList[k+t-i] = initList[t];
}

```

# Merge Sort (contd.)

- ❑ Based on a single merge pass

- ◆ Merge adjacent pairs of sorted segments
- ◆ p. 348, Program 7.8

- ❑ p. 348, Program 7.9

- ❑ p. 349, Fig. 7.5

- ❑ Analysis

- ◆ Several passes over the input
- ◆ The  $i$ th pass merges segments of size  $2^{i-1}$
- ◆ The total # of passes:  $\lceil \log_2 n \rceil$ 
  - ⇒ Each pass takes  $O(n)$  time.
  - ⇒ Total computing time:  $O(n \log n)$
- ◆ Stable

# Merge Sort (contd.)

## ❖ Recursive merge sort

- ❑ Associate an integer pointer with each record to eliminate the record copying that takes place when Program 7.7 is used
  - ◆  $link[1:n]$ ;  $link[i]$  gives the record that follows record  $i$  in the sorted sublist
- ❑ p. 350, Program 7.10
  - ◆ Based on *listMerge* (p. 351, Program 7.11)
  - ◆ Return the first position of the resulting chain
- ❑ Analysis
  - ◆ Stable
  - ◆ Time complexity:  $O(n \log n)$



# Merge Sort (contd.)

## ❖ Summary

- ❑  $O(n \log n)$  computing time both in the worst case and the average case
- ❑ Additional storage requirement

## ❖ Variation

- ❑ Natural Merge Sort
  - ◆ Make an initial pass over the data to determine the sequences of records that are in order
  - ◆ Ex. p. 351, Fig. 7.6



# Heap Sort

- ❖ Only a fixed amount of additional storage requirement
- ❖  $O(n \log n)$  computing time both in the worst case and the average case
- ❖ Slightly slower than merge sort
- ❖ Utilize the max heap structure
  - ❑ Step 1: Insert the  $n$  records into an initially empty max heap
  - ❑ Step 2: Extract records from the max heap one at a time



# Heap Sort (contd.)

- ❖ How to adjust a binary tree to establish the heap?
  - ❑ p. 353, Program 7.12
  - ❑ Time complexity:  $O(d)$  if the tree depth is  $d$
- ❖ The swap, decrement heap size, readjust heap process is repeated  $n - 1$  times to sort the entire array.
  - ❑ On each pass, swap the first and last records in the heap
  - ❑ Place the record with the  $i$ th highest key in position  $n - i + 1$

# Heap Sort (contd.)

❖ p. 354, Program 7.13

□ Suppose  $2^{k-1} \leq n < 2^k$  so that the tree has  $k$  levels

□ In the first **for loop**, `adjust` is called once for each node that has a child

◆ The time required for this loop is the sum, over each level, of the # of nodes on a level times the maximum distance the node can move.

$$\sum_{i=1}^k 2^{i-1} (k-i) = \sum_{i=0}^{k-1} 2^{k-i-1} i \leq n \sum_{i=0}^{k-1} \frac{i}{2^i} < 2n = O(n)$$

# Heap Sort (contd.)

❑ In the second **for loop**, `adjust` is called  $n - 1$  times with maximum depth:  $\lceil \log_2(n+1) \rceil$

◆ Time complexity:  $O(n \log n)$

❑ The total computing time:  $O(n \log n)$

❖ Ex. p. 352, Example 7.7

❑ p. 354, Fig. 7.7(a)

❑ p. 354, Fig. 7.7(b) (max heap following the first **for** loop of *heapsort*)

❑ p. 355, Fig. 7.8

# Sorting on Several Keys

## ❖ Sorting records that have several keys

□ Key labeling:  $K^0, K^1, \dots, K^{r-1}$ , with  $K^0$  being the **most significant key** and  $K^{r-1}$  the **least**

□  $K_i^j$  : key  $K^j$  of record  $R_i$  第*i*個record中第*j*個key

□ A list of records,  $R_1, \dots, R_n$ , is lexically sorted with respect to the keys  $K^0, K^1, \dots, K^{r-1}$  iff for every pair of records  $i$  and  $j$ ,  $i < j$  and  $(K_i^1, K_i^2, \dots, K_i^r) \leq (K_j^1, K_j^2, \dots, K_j^r)$

◆  $(x_1, x_2, \dots, x_r) \leq (y_1, y_2, \dots, y_r)$  iff

⇔  $x_i = y_i$ ,  $1 \leq i \leq j$  and  $x_{j+1} < y_{j+1}$  for some  $j < r$ , or

⇔  $x_i = y_i$ ,  $1 \leq i \leq r$  record *i, j* 比大小 :

先從 **most significant key** 開始比，比*r*個

若在第*n*個key比出大小，就不用繼續比下去

# Radix Sort (contd.)

## ❖ Ex. Sorting a deck of poker cards

- ❑ Two keys:  $K^0$  [Suit] and  $K^1$  [Face value]

- ❑ **MSD** (Most Significant Digit) sort vs. **LSD** (Least Significant Digit) sort

不管以LSD或MSD排序，只是看先以哪種key分疊（排序過程不相同），但不影響最終排序結果

  - ◆ Ex. p. 356

  - ◆ MSD or LSD indicate only **the order in which the keys are sorted** instead of how each key is to be sorted.

## ❖ In a radix sort, the sort key is decomposed into digits using **radix** $r$ .

基數排序

radix（在十進位中）  
有10種值：0-9

- ❑  $r$  bins are needed to sort on each digit

# Radix Sort (contd.)

## ❖ Ex. An LSD radix- $r$ sort

- ❑  $n$  records ( $R_1, \dots, R_n$ )
  - ❑ Each key has  $d$  digits in the range 0 through  $r - 1$ .
  - ❑ p. 358, Program 7.14
    - ◆ The bins are implemented as **queues**.
    - ◆  **$front[i]$  and  $rear[i]$ ,  $0 \leq i < r$**
  - ❑ Ex. p. 359, Example 7.8 and Fig. 7.9
1. 先依個位數分群
  2. **index**由小到大輸出
  3. 再拿個位數輸出結果以十位數分群
  4. **index**由小到大輸出
  5. 再拿十位數輸出結果以位百數分群
  6. **index**由小到大輸出

## ❖ Analysis

- ❑  $d$  passes over the data and each pass takes  $O(n + r)$  time.
- ❑ Time complexity:  $O(d(n + r))$
- ❑ The **value of  $d$  depends on the choice of the radix  $r$  and the largest key.**

# Summary of Internal Sorting

- ❖ Insertion sort is the best sorting method for small  $n$ . 適用record數較少
- ❖ Merge sort has the best worst case behavior.
  - ❑ More storage requirement than heap sort
- ❖ Quick sort has the best average behavior.
  - ❑ But its worst case behavior is  $O(n^2)$  分堆不平均
- ❖ P. 370, Fig. 7.15

# External Sorting

- ❖ Assume that the file to be sorted resides on a disk.
- ❖ The applied overheads when reading/writing from/to a disk
  - ❑ **Seek time**: time taken to position the read/write head to the correct cylinder. 移動到正確的磁軌上所花的時間
  - ❑ **Latency time**: time until the right sector of the track is under the read/write head. 移動到正確的磁頭上所花的時間
  - ❑ **Transmission time**: time to transmit the data to/from the disk 移動到正確的磁碟上所花的時間



# External Sorting (contd.)

- ❖ A **block** is the unit of data that is read from or written to the disk at one time. 最小的資料交流量，包含多個record
  - ❑ Will usually contain several records
- ❖ **Runs** -- the segments of the input file sorted using internal sort 已經排序好的一部分內容
- ❖ The most popular method for sorting on external storage devices is **merge sort**.
  - ❑ It requires only the leading records of the two runs being merged to be present in memory at one time, so it is possible to merge large runs together.

# External Sorting (contd.)

- ❑ **Phase 1:** Segments of the input file are sorted using a good internal sort method and then written onto external storage as they are generated.
- ❑ **Phase 2:** The runs generated in phase 1 are merged together following the merge-tree pattern of Fig. 7.4 until only one run is left.

❖ Ex. p. 377

## ❑ Assumptions

- ◆ A block length of 250 records
- ◆ The input file contains 4500 records (i.e., 18 blocks).

# External Sorting (contd.)

- ◆ An internal memory capable of sorting at most 750 records (i.e., 3 blocks)
- ◆ Another available disk as a scratch pad
- Phase 1: Internally sort 3 blocks at a time
  - ◆ Six runs  $R_1 \sim R_6$  are obtained and written out to the scratch disk. (p. 377, Fig. 7.19) 可使用內部排序處理完成，暫存到磁碟
- Phase 2: Two blocks of memory are used as input buffers and the third as an output buffer.
  - ◆ Blocks of runs are merged from the input buffers into the output buffer. (p. 377, Fig. 7.20)
    - ⇒ The output buffer is written out onto disk when getting full.
    - ⇒ The input buffer is refilled with another block from the same run when getting empty.

# External Sorting (contd.)

## ❖ The time required by the external sort

處理一個block所需的時間

□  $t_{IO}$  = time to input or output one block  $= t_s + t_l + t_{rw}$

◆  $t_s$  = maximum seek time

◆  $t_l$  = maximum latency time

◆  $t_{rw}$  = time to read or write one block of 250 records

□  $t_{IS}$  = time to internally sort 750 records

□  $nt_m$  = time to merge  $n$  records from input buffers to the output buffer

# External Sorting (contd.)

operation	time
read 18 blocks of input, $18t_{IO}$ , internally sort, $6t_{IS}$ , write 18 blocks, $18t_{IO}$	$36t_{IO} + 6t_{IS}$
merge runs 1-6 in pairs	$36t_{IO} + 4500t_m$
merge two runs of 1500 records each, 12 blocks	$24t_{IO} + 3000t_m$ 12個blocks read和12個blocks write
merge one run of 3000 records with one run of 1500 records	$36t_{IO} + 4500t_m$
total time	$132t_{IO} + 12000t_m + 6t_{IS}$

# External Sorting -- $k$ -way Merging

- ❖ The # of passes over  $m$  runs can be reduced by using a higher-order merge, i.e.,  $k$ -way merge for  $k \geq 2$ . 多個run merge，降低merge tree的高度
  - ❑ Simultaneously merge  $k$  runs together
  - ❑ The I/O time may be reduced by using a higher-order merge. 改善I/O處理時間（因為merge tree高度降低）
  - ❑ Ex.  $k = 4$  and  $m = 16$  (p. 380, Fig. 7.22)
  - ❑ At most  $\lceil \log_k m \rceil$  passes Time complexity 會隨著k值增加而增加

# External Sorting -- $k$ -way Merging (contd.)

❖ The most direct way to determine the next record to output in  $k$ -merge is making  $k-1$  comparisons.

□ Time complexity:  $O((k-1) \sum_{i=1}^k s_i)$ , where  $s_i$  is the size of the  $i$ -th run,  $1 \leq i \leq k$

□ With  $n$  being the # of records in the file, the total # of key comparisons is

$$n(k-1) \log_k m = n(k-1) \log_2 m / \log_2 k \quad k \text{ 值固定, complexity: } O(n \log n)$$

◆ The factor  $(k-1) / \log_2 k$