Atomic-GDN2: TPU Kernels and Hierarchical Delta Routing for Hybrid Language Models

Akseleu Omirbay
Independent researcher

October 16, 2026

Abstract

This paper describes a TPU-oriented Gated DeltaNet-2 implementation in JAX/Pallas and a language-model experiment combining recurrent token mixing, Multi-head Latent Attention, and hierarchical delta routing. The kernel uses a three-stage forward path and a fused custom backward, with explicit chunk-level residuals and numerical constraints. The 307.13M-parameter hybrid model is compared with a 334.16M-parameter pure GDN-2 baseline in four fresh TPU v5e-8 runs, with two seeds per architecture and a common batch size of 32. At exactly 61,500 optimizer steps, after 4.030B training target tokens per run, hybrid achieves estimated validation BPB of 0.993838 ± 0.000111, compared with 1.005909 ± 0.000227 for the baseline; the difference is -0.012071 BPB. The uncertainty shown is sample standard deviation over two seeds. Hybrid has lower BPB at every shared logged evaluation in both seeds and reaches the evaluated BPB thresholds using 14.3–18.5% fewer tokens and 10.4–13.6% less logged notebook time. These results compare complete architectures: they do not isolate the contribution of delta routing, equalize FLOPs, or establish downstream generalization. Historical kernel microbenchmark ratios are not used to infer model-level speedups. Code, exact run evidence, analysis data and checkpoint export metadata accompany the paper.

1 Introduction

Recurrent linear-attention models provide a useful alternative to a growing attention cache, but an efficient recurrence also needs an implementation suited to the accelerator. Gated DeltaNet-2 separates channel-wise erasing and writing in a matrix-state update [1]. On a TPU, the implementation must organize that update around chunked matrix operations, on-chip working storage and explicit forward/backward interfaces. The mathematical model, the kernel implementation and the surrounding language model are distinct levels of the system; their evidence should be kept distinct as well.

This work studies two connected engineering questions. First, how can a GDN-2 kernel be structured in JAX/Pallas for TPU execution while making numerical assumptions explicit? Second, how does a recurrent/attention hybrid with hierarchical depth routing compare with a pure GDN-2 model under a practical, fixed session budget? The hybrid replaces one recurrent mixer per block with Multi-head Latent Attention (MLA) [2] and adapts the scoring and additive routing equations of Delta Attention Residuals (DAR) [3] to previous-block summaries and earlier within-block deltas.

The contributions are: (i) a documented kernel decomposition with a fused backward and selective recomputation; (ii) an explicit implementation of hierarchical routing in a GDN-2/MLA language model; and (iii) a two-seed, four-run comparison with complete logged learning curves, first-observed threshold crossings and immutable source provenance. The two architectures share the same kernel implementation, so their quality difference is not a comparison of Pallas against a scan backend.

2 Method: hierarchical delta routing

The design separates mixing across tokens from routing across depth. GDN-2 and MLA compute token-dependent updates; DAR selects earlier depth changes to condition the next update while preserving the ordinary residual stream. Previous blocks are represented by their net changes, whereas earlier mixers in the current block remain separate sources.

Notation. We suppress batch and token-position axes in the depth-routing equations. At one token position, $x_{b,i} \in \mathbb{R}^d$ is the residual after sublayer i of block b; $x_{b,0}$ is its input. Mixers have $i = 1, \ldots, 4$, and $i = 5$ denotes the FFN. $\delta_{b,i}$ is a sublayer output (sanitized and stored locally for mixers), s_b a completed block change, $\mathcal{V}_{b,i}$ the available source list, and $r_{b,i}$ the retrieved update. $z_{b,i} \in \mathbb{R}^d$ is a learned query. The index t below denotes sequence time.

2.1 Gated DeltaNet-2 recurrence

Let $S_t \in \mathbb{R}^{d_k \times d_v}$ be the recurrent state. The reference implemented in the accompanying kernel repository uses channel-wise erase and write vectors b_t, w_t, a decay vector α_t, and query/key/value vectors q_t, k_t, v_t:

$$\bar{S}_t = \mathrm{Diag}(\alpha_t) S_{t-1}, \tag{1}$$

$$u_t = b_t \odot k_t, \qquad \widehat{v}_t = w_t \odot v_t - \bar{S}_t^T u_t, \tag{2}$$

$$S_t = \bar{S}_t + k_t \widehat{v}_t^T, \qquad o_t = \gamma S_t^T q_t. \tag{3}$$

Here $\gamma = 1/\sqrt{d_k}$ in the language model. This explicitly distinguishes the erase and write channels; a scalar-gate formula without w_t would not specify this API. The model projects $w_t = W_w x_t$ without a sigmoid, applies $b_t = \sigma(W_b x_t)$, and uses

$$g_t = -\min\left(\mathrm{softplus}(W_g x_t + c_g), \frac{160}{b_{s2}}\right), \qquad \alpha_t = \exp(g_t). \tag{4}$$

For the training configuration $b_{s2} = 32$, $g_t \in [-5, 0]$. This bound belongs to the chosen balanced two-leg (BTL) decay computation, not to every implementation of GDN-2. The deployed chunked computation also includes damping and sanitization, described below; its agreement with an undamped mathematical recurrence must be evaluated under matched settings.

2.2 Routing rule and initialization

Following DAR [3], each source $v_j \in \mathcal{V}_{b,i}$ supplies a normalized key and its original value. At each token position,

$$a_{b,i,j} = \mathrm{softmax}_j\left(z_{b,i}^{\mathsf{T}} \,\mathrm{RMSNorm}_{\mathrm{key},b,i}(v_j)\right), \tag{5}$$

$$r_{b,i} = \sum_j a_{b,i,j} v_j. \tag{6}$$

The query is a learned vector independent of the current residual; the softmax is over depth sources, not sequence positions. For an empty list we define $r_{b,i} = 0$. For each mixer, the implemented update is

$$h_{b,i} = \mathrm{RMSNorm}_{\mathrm{pre},b,i}(x_{b,i-1} + r_{b,i}), \tag{7}$$

$$\delta_{b,i} = \mathcal{C}(F_{b,i}(h_{b,i})), \qquad x_{b,i} = \mathcal{C}(x_{b,i-1} + \delta_{b,i}), \tag{8}$$

where $\mathcal{C}$ clips to $[-10^3, 10^3]$ and replaces NaNs with zero. The mixer output includes its projection and dropout. Thus local sources are sanitized outputs; when residual clipping activates, they need not equal $x_{b,i} - x_{b,i-1}$. The FFN instead uses

$$\delta_{b,5} = F_{b,5}(\mathrm{LayerNorm}(x_{b,4} + r_{b,5})), \qquad x_{b,5} = x_{b,4} + \delta_{b,5}, \tag{9}$$

without the same outer clipping operation. These details specify the deployed model, rather than an idealized unclipped residual network.

Zero query means uniform retrieval. For $m = |\mathcal{V}_{b,i}| > 0$, initialization at $z_{b,i} = 0$ gives

$$a_{b,i,j} = \frac{1}{m}, \qquad r_{b,i} = \frac{1}{m}\sum_{j=1}^{m} v_j, \qquad \|r_{b,i}\| \le \frac{1}{m}\sum_{j=1}^{m} \|v_j\|. \tag{10}$$

This follows directly from equal softmax logits and the triangle inequality. Retrieval is generally nonzero: zero query alone does not switch routing off or guarantee an identity-preserving conversion of a pretrained backbone. The reported models were trained from scratch. A nonzero task gradient confirms participation in computation, while the quality contribution of routing still requires a controlled ablation.

2.3 Backbone and source hierarchy

The model has seven blocks, each with three GDN-2 mixers followed by one causal MLA mixer and one SwiGLU FFN. MLA uses a rank-512 KV representation and separate 64-dimensional non-positional and rotary query/key components per head. The model configuration is given in Table 1. In comparison, each baseline block has four GDN-2 mixers and one FFN. The baseline has 334,156,800 parameters and hybrid has 307,131,392, approximately 8.09% fewer.

Table 1: Current model configuration. A token mixer is counted separately from the one FFN per block. Both models use the same external kernel implementation.

Setting	Baseline	hybrid
Parameters	334,156,800	307,131,392
Token mixers / blocks	28 / 7	28 / 7
GDN-2 / MLA mixers	28 / 0	21 / 7
SwiGLU FFNs	7	7
Hidden / FFN dimension	1024 / 3584	1024 / 3584
Heads / head dimension	8 / 128	8 / 128
MLA KV rank	—	512
MLA non-RoPE / RoPE dimensions	—	64 / 64
DAR query	—	1024-vector per router
Vocabulary / context	50,257 / 2048	50,257 / 2048
Dropout	0.1	0.1
Tied embeddings	Yes	Yes
Model compute / parameters	bf16 / fp32	bf16 / fp32

Before mixer i in block b, the source list is the concatenation

$$\mathcal{V}_{b,i} = [s_1, \ldots, s_{b-1}] \,\|\, [\delta_{b,1}, \ldots, \delta_{b,i-1}]. \tag{11}$$

The FFN receives the same previous-block summaries plus all four earlier mixer deltas. After the FFN, the block appends $s_b = x_{b,5} - x_{b,0}$, the actual change including the FFN. Only earlier sublayers can contribute; no layer reads its own newly computed delta. These are depth sources at the same sequence position, not persistent memory across independent sequences.

Table 2: What is inherited from DAR and what this implementation changes. The original paper already includes both sublayer and block variants; block grouping itself is not a new claim.

Component	DAR formulation [3]	This hierarchical hybrid
Scoring	Learned query, RMS-normalized source keys, depth softmax	Same scoring form; one query per receiving mixer/FFN
Retrieval	Original delta values added to the residual	Same additive placement before sublayer normalization
Sources	Sublayer deltas or grouped block changes	Prior completed-block changes plus earlier local mixer outputs
Block boundaries	Block variant includes an embedding source	No embedding source; empty history gives zero retrieval; FFN-inclusive net block change
Backbone	Transformer attention/MLP sublayers	Three GDN-2 mixers, one MLA mixer and one FFN per block
Numerics	Residual update formulation	Two mixer clipping sites; FFN update follows Eq. 9

Algorithm 1 fixes the order: retrieve from earlier sources, compute the next output, then expose it to later receivers. After the block, local outputs are represented in later blocks by the net summary s_b. This hierarchy trades individual access to completed-block sublayers for a shorter source list; it does not preserve every past sublayer as a distinct candidate. Figure 1 shows the same path.

Input: $x_{b,0}$, history $H = [s_1, \ldots, s_{b-1}]$; set $x \leftarrow x_{b,0}$, $D \leftarrow [\,]$.
For $i = 1, \ldots, 4$ **do** ($F_{b,1:3}$: GDN-2; $F_{b,4}$: MLA):
  $\mathcal{V}_{b,i} \leftarrow H \parallel D$.
  $r_{b,i} \leftarrow \mathrm{Retrieve}(z_{b,i}, \mathcal{V}_{b,i})$ using Eq. 6; zero if empty.
  $h \leftarrow \mathrm{RMSNorm}_{\mathrm{pre},b,i}(x + r_{b,i})$.
  $\delta_{b,i} \leftarrow \mathcal{C}(F_{b,i}(h))$; append $\delta_{b,i}$ to D.
  $x \leftarrow \mathcal{C}(x + \delta_{b,i})$.
End for.
$\mathcal{V}_{b,5} \leftarrow H \parallel D$.
$r_{b,5} \leftarrow \mathrm{Retrieve}(z_{b,5}, \mathcal{V}_{b,5})$.
$x \leftarrow x + F_{b,5}(\mathrm{LayerNorm}(x + r_{b,5}))$.
$s_b \leftarrow x - x_{b,0}$; append s_b to H.
Return $x_{b,5} = x$ and H.

Algorithm 1: One hierarchical hybrid block, matching the released forward path.




Figure 1: The current hybrid computation, with a diagram layout inspired by the stacked residual presentation of Vaswani et al. [5]. (a) Seven blocks, each containing three GDN-2 mixers, one MLA mixer and one FFN. (b) Sequential sublayers with an ordinary residual bypass and an additive DAR input before normalization. Mixer inputs use RMSNorm; the FFN uses LayerNorm. The depth-source box means summaries and deltas available before the indicated stage; it is not a simultaneous all-layer attention operation. Mixer sanitization follows Eq. 8; the FFN follows Eq. 9. Block input/output correspond to $x_{b,0}$ and $x_{b,5}$; the summary is s_b.

3 TPU implementation

3.1 Execution structure and memory

The `atomic-ops` distribution contains two distinct kernel generations: the older `atomic_ops` port and the TPU-oriented `atomic_gdn2` implementation used here. The current model imports the latter through a small cached binding. Its forward pass has three Pallas stages: decay-aware score construction, a leaf-batched WY solve, and fused WY-factor reconstruction plus an inter-chunk scan. With chunk length 128, a length-2048 segment has 16 recurrence iterations over chunks.

The custom VJP passes saved chunk-level quantities to a reverse scan in `backward_mega`. A single Pallas call per segment combines the stages labelled B2, B1, B3, B4 and B5 in the code, returning gradients for q, k, v, w, b, g and the initial state. Long sequences are segmented; the default maximum is 32 chunks per segment, and recurrent state is passed across segment boundaries. Thus "one fused backward" means one call per segment, not one launch for every possible sequence length or for all of forward/backward.

Memory is reduced through structured residual reuse and selective recomputation. The forward retains, among other quantities, score/solve matrices, chunk-start states and updated values. The backward reconstructs local factors such as w_p, k_g, q_g. These saved arrays scale with the number of chunks. Neither constant-memory training nor the absence of all HBM intermediates is claimed. The recurrent carry is maintained inside the chunk loop, but that should not be confused with keeping the entire training computation in on-chip storage.

3.2 Precision, damping and numerical envelope

The current configuration uses different matmul modes for different stages. Score and CD operations use `highest`; the ladder solve and B1/B2/B3 operations use `bf16x3`; B4 explicitly selects `highest`. FP32 tensor storage and a matmul precision mode are different properties. The bf16x3 helper splits each operand into high and low components and forms three products:

$$AB \approx A_{hi}B_{hi} + A_{hi}B_{lo} + A_{lo}B_{hi}. \tag{12}$$

It does not split each operand into three stored bf16 components.

The WY solve implemented by the shipped code is

$$A = (I + (1 - \varepsilon)A_{kk})^{-1}, \qquad \varepsilon = 10^{-3}. \tag{13}$$

This rescales the triangular coupling; it is not diagonal loading by εI. The BTL score factorization balances two exponential legs. The configuration ties the maximum per-token log decay to the inner block size so the bound $g_{max}b_{s2}/2 = 80$ stays below the nominal exponential limit 88. Kernel-level clipping uses 10^4; the hybrid has separate mixer/residual sanitization at 10^3. The frequency and quality effect of these safeguards were not measured.

3.3 Evidence boundary

Both language-model architectures use the same pinned kernel implementation. Historical kernel microbenchmarks use different shapes and a supplied scan wrapper whose initial-state, scaling, final-state and composition conventions require an equivalence audit. They are not used to claim a speedup of hybrid over the baseline. Detailed source evidence and a corrected, as-yet-untimed reproduction harness are provided in the model repository's kernel evidence notes; kernel code remains at the pinned `atomic-ops` revision.

4 Experiments

4.1 Data, optimization and run protocol

All four runs were trained from scratch on the uint16 GPT-2-tokenized `windmaple/openwebtext-gpt2` corpus. The available files contain 9,035,582,489 training tokens and 4,434,606 validation tokens. The loader forms nonoverlapping windows of 2049 tokens, uses 2048 labels per window, and drops incomplete batches. Final evaluation covers 67 full batches, or 4,390,912 target tokens. The configured intermediate limit of 100 batches

exceeds the available 67, so intermediate and final evaluations use the same available windows. There is no independent held-out test result.

Reported BPB is an estimate from the average token cross-entropy ℓ:

$$\mathrm{BPB}_{\mathrm{est}} = \frac{\ell}{\ln(2)\, 4.2}. \tag{14}$$

The constant 4.2 bytes per GPT-2 token is not measured on each evaluated sequence; therefore the metric is labelled estimated BPB rather than exact byte-level BPB.

Both architectures use batch 32, context 2048 and gradient accumulation 1. Initialization seeds are 1 and 2; the paired data seeds are 43 and 44, and dropout seeds are 124 and 125. The optimizer uses Muon [6] for eligible two-dimensional matrices excluding embeddings, and AdamW for the remaining parameters. Peak learning rate is 3×10^{-4}, weight decay 0.1 and global gradient clipping 1.0. Muon uses momentum 0.95 and five Newton–Schulz iterations; AdamW uses $(\beta_1, \beta_2) = (0.9, 0.95)$.

Each isolated notebook has a 32,040-second (8h54m) limit including setup and compilation, with a 600-second finalization reserve inside the limit. Learning rate follows an elapsed-time warmup/cosine rule with a first-100-update warmup bound and a 0.1 floor ratio. Equal optimizer steps therefore do not imply identical learning-rate trajectories. Each run uses a fresh optimizer and a shuffled single pass over the available train data, ending when its time budget expires. None completed the entire data pass. Validation is logged every 1500 steps; checkpoints are saved every 5000 steps and at finalization.

Table 3: Actual completed runs, before analytical curve truncation. Logged notebook time is the last console timestamp and includes setup/finalization; it is not a billing measurement.

Model	Seed	Final step	Train tokens (B)	Notebook h	Status
Baseline	1	65,000	4.259840	8.768	Complete
Baseline	2	65,000	4.259840	8.743	Complete
hybrid	1	62,673	4.107338	8.808	Complete
hybrid	2	62,683	4.107993	8.801	Complete

4.2 Validation learning curves and matched-step comparison

Figure 2A shows the mean and sample standard deviation over the two seeds. Hybrid is lower at every one of the 41 shared logged evaluations, from step 1500 to 61,500, in both seeds. Selected values appear in Table 4; the complete per-seed table is in the accompanying CSV and machine-readable attestation.

At exactly 61,500 steps, both models have processed 4,030,464,000 training target tokens. Baseline reaches 1.005909 ± 0.000227 estimated BPB and hybrid reaches 0.993838 ± 0.000111. With Δ = hybrid − Baseline, the difference is -0.012071 BPB. The same kernel implementation is used by both architectures. This result does not separate MLA, routing, normalization or parameter-count effects.

For a near-step endpoint presentation, baseline is truncated at 63,000 and hybrid uses its observed final steps 62,673 and 62,683. Their respective means are 1.004928 and 0.993311; $\Delta = -0.011617$. This analytical cutoff was selected after the runs and is not an exactly token-matched endpoint. The original baseline evaluations through 65,000 remain in the released logs; Table 3 reports actual completion rather than the cutoff.




Figure 2: Validation learning curves and token requirements. (A) Means and sample SD over two seeds; the endpoint annotation uses Baseline 63,000 and hybrid 62,673/62,683 and is not an exact token match. (B) Training target tokens at the first logged evaluation meeting each threshold, aggregated over seeds. No crossing interpolation is used. Estimated BPB divides token CE by $\ln(2) \times 4.2$.

Table 4: Selected shared-step estimated BPB results, mean ± sample SD across two seeds. The final row is a separately labelled near-step comparison, not exact token matching.

Step	Tokens (B)	Baseline	hybrid	Δ
1,500	0.098	1.497840 ± 0.001396	1.440855 ± 0.000309	-0.056985
15,000	0.983	1.123090 ± 0.000266	1.104386 ± 0.000481	-0.018704
22,500	1.475	1.087951 ± 0.000609	1.071201 ± 0.000241	-0.016750
24,000	1.573	1.082673 ± 0.000202	1.066318 ± 0.000001	-0.016355
30,000	1.966	1.064235 ± 0.000363	1.048363 ± 0.000689	-0.015872
45,000	2.949	1.028161 ± 0.000065	1.013422 ± 0.000016	-0.014738
60,000	3.932	1.007089 ± 0.000269	0.994866 ± 0.000159	-0.012224
61,500	4.030	1.005909 ± 0.000227	0.993838 ± 0.000111	-0.012071
Near-step*	—	1.004928 ± 0.000254	0.993311 ± 0.000176	−0.011617

*Baseline 63,000; hybrid 62,673/62,683.

The advantage is largest at the earliest recorded evaluation: at step 1500 the mean difference is −0.056985 BPB. It narrows to −0.012071 at the last common step. Figure 3 displays the paired differences directly. This observed trend does not establish a shared asymptotic loss floor, an early-warmup mechanism, or the outcome of continuing training. A descriptive log-step slope is supplied with the plot, but adjacent evaluations are correlated and it is not a significance test.




Figure 3: Paired estimated BPB differences at identical logged steps. Negative values favor hybrid. Error bars show sample SD of the two seed-paired differences, not a confidence interval. The curve stops at the last common observation, 61,500 steps.

4.3 Token and time to target

For each seed separately, the threshold crossing is the first recorded validation at or below the target. We then average those step/token/time values across seeds; this is not a crossing computed from the mean BPB curve. Table 5 gives the four evaluated thresholds. Token savings are 14.29–18.52%. A zero SD in observed crossing steps means both seeds crossed on the same 1500-step grid point; it does not locate the true crossing exactly.

Token efficiency and elapsed-time efficiency are different measurements. The latter includes installation, compilation, validation and checkpoint overhead up to the crossing. Periodic saves sometimes waited roughly 200–243 seconds in the logs. Consequently, the wall-time result reflects the observed execution protocol rather

Table 5: First-observed target crossings. Steps are mean ± sample SD, $n = 2$. Notebook time is measured from the beginning of the notebook console, excluding the TPU queue.

Target BPB	Baseline steps	hybrid steps	Fewer tokens	Less time
≤ 1.10	20250 ± 1061	16500 ± 0	18.52%	13.48%
≤ 1.08	25500 ± 0	21000 ± 0	17.65%	13.55%
≤ 1.06	31500 ± 0	27000 ± 0	14.29%	10.38%
≤ 1.02	50250 ± 1061	42000 ± 0	16.42%	12.51%

than a pure kernel or steady-state throughput benchmark. The wall-time bars and exact per-seed crossing records are included in the appendix and machine-readable tables.

4.4 Run integrity, source provenance and checkpoint export

All four notebooks report completion and contain a nonempty SUCCESS record. Recorded updates have finite loss/gradient norms and zero skipped steps; each runtime preflight reports eight TPU devices and finite forward/backward execution. Hybrid's routing branch has a nonzero preflight task gradient. These checks establish observed execution health, not numerical equivalence to a reference at every training step.

The baseline and hybrid training source commits are respectively `bf80e315` and `697a10d3`; the common kernel commit is `0dbc59cf`. Each run retains its source-file hashes, resolved configuration, dataset file sizes and edge hashes, runtime preflight, metrics and console log. A publication snapshot is not misrepresented as the original training commit. Model parameter exports retain the original Flax tensor paths and orientations in safetensors; optimizer state is not part of inference weights. Export manifests record counts, shapes, finite checks and hashes. The documented loader is required; these files are not advertised as drop-in Transformers models.

5 Related work

Gated DeltaNet-2 supplies the channel-wise erase/write recurrence and its chunkwise formulation [1]; MLA supplies the compressed key/value attention component [2]. The delta-routing scoring and additive equations follow DAR [3], while the source grouping here combines previous block changes and local earlier deltas in a GDN-2/MLA backbone. We do not claim to have introduced those underlying mechanisms. The block composition and engineering integration are the object of this experiment.

Pallas exposes accelerator-specific kernel programming within JAX [4]. The kernel repository distinguishes its older Triton-derived port from the current TPU-oriented implementation. Comparisons with an associative-scan wrapper are useful for implementation analysis, but do not rank this work against all optimized linear attention or state-space kernels. The diagram adopts the clear stacked-residual visual language of Transformer diagrams [5], not their encoder–decoder topology or post-normalization ordering. Muon is used as an optimizer component rather than introduced or independently benchmarked here [6].

6 Discussion and limitations

Observed pattern and open mechanism. The hybrid advantage appears early and narrows over the observed interval, with the same sign in both seed pairs. This is consistent with improved learning efficiency for the combined architecture under this protocol. It does not identify which component causes the gain or predict a different asymptotic loss. A fixed-token LR schedule and matched MLA/routing ablations would make that distinction more informative.

Replication and evaluation scope. Two seeds expose the observed run-to-run variation but give a weak estimate of its distribution. Sample SD is not a confidence interval. The study uses one corpus, one tokenizer and context length 2048, with repeated validation on the available split. There is no independent final test, downstream benchmark or systematic generation study. The consistent sign in both seeds does not establish a universal advantage.

Attribution and resource matching. The architectures differ in MLA, routing and normalization details, parameter counts and FLOPs. No component ablation isolates DAR. Equal target tokens and batch size do not imply equal compute. Both use the same kernel; a historical Pallas/scan ratio cannot explain the architecture comparison as a backend change. Longer-context behavior and comparisons with tuned external implementations remain unmeasured.

Schedule and stopping. Learning rates depend on elapsed time, so models at the same step can have different learning-rate histories. The time-limited runs did not finish the available data pass. The selected near-step cutoff is post hoc and differs slightly between architectures and hybrid seeds; the exact common-step comparison and complete raw logs are therefore reported alongside it.

Metric and crossing resolution. BPB uses a fixed bytes-per-token conversion. Validation drops the final incomplete batch. Threshold estimates are limited by the evaluation grid, and observed time includes overhead. Neither standard deviations from two seeds nor the descriptive trend fit justify a formal significance or asymptotic convergence claim.

Numerics, artifacts and reproducibility. The implementation uses clipping, damping and NaN replacement. Their activation rates and effect on quality are not separately characterized. Historical kernel attestations use older source/content identifiers and incomplete raw provenance. No new equivalent-workload kernel speedup is established in this study. Finite training and successful checkpoint publication do not prove backward equivalence or independent reproduction. The release distinguishes lossless weight serialization checks from a full rerun of evaluation.

7 Conclusion

Atomic-GDN2 combines a documented TPU kernel implementation with an explicit hierarchical delta-routing hybrid and a four-run training comparison. At exactly 4.030B training target tokens, hybrid improves estimated validation BPB by 0.012071 over the pure GDN-2 baseline, with lower BPB at all shared evaluations in both seeds and approximately 8.09% fewer parameters. The observed savings to the evaluated quality thresholds are 14.3–18.5% in tokens and 10.4–13.6% in logged notebook time. These are bounded architectural results, not an isolated explanation of DAR's effect. The next informative experiments are additional seeds, component ablations, a fixed-token learning-rate schedule and independent task evaluation.

Code and artifact availability. The publication repository is `https://github.com/Akseleu-J/atomic-gdn2`. Kernel implementation and detailed historical evidence are at `https://github.com/Akseleu-J/atomic-ops`; checkpoint exports and model card are at `https://huggingface.co/Akseleu/Atomic-GDN2`. The model repository contains the source of this paper, vector figures, exact tables and a ZIP of all four run records. Immutable training commits and per-file manifests identify the code that produced the measurements; the publication repository contains the revised documentation and analysis.

References

[1] A. Hatamizadeh, Y. Choi and J. Kautz. *Gated DeltaNet-2: Decoupling Erase and Write in Linear Attention*. arXiv:2605.22791, 2026. `https://arxiv.org/abs/2605.22791`.

[2] DeepSeek-AI. *DeepSeek-V2: A Strong, Economical, and Efficient Mixture-of-Experts Language Model*. arXiv:2405.04434, 2024. `https://arxiv.org/abs/2405.04434`.

[3] C. Luo, Z. Cai and J. Hu. *Delta Attention Residuals*. arXiv:2605.18855, 2026. `https://arxiv.org/abs/2605.18855`.

[4] JAX authors. *Pallas: a JAX kernel language*. `https://docs.jax.dev/en/latest/pallas/`.

[5] A. Vaswani et al. *Attention Is All You Need*. Advances in Neural Information Processing Systems, 2017. arXiv:1706.03762. `https://arxiv.org/abs/1706.03762`.

[6] K. Jordan. *Muon: An optimizer for hidden layers in neural networks*, 2024. `https://github.com/KellerJordan/Muon`.

A Per-seed and wall-time views




Figure 4: The two seed pairs shown separately, with the same axes and analytical cutoffs. Hybrid has lower estimated BPB at every common recorded step in each pair.




Figure 5: Notebook time at the first logged target crossing, including setup/compilation and earlier validation/checkpoint overhead, excluding queue time. Bars are means and error bars are sample SD over two seeds.

B Reproduction records

The repository attestation contains source hashes, learning curves, per-seed crossings and the exact/near-step distinction. Its artifact ZIP retains metrics, console and training logs, resolved configs and runtime checks for all four runs; see the reproduction guide. Dataset edge hashes are not a full-corpus checksum. Each safetensors manifest records its source step, seed, shapes, count and digest; default aliases refer to seed 2. Inference exports exclude the optimizer state retained in the original Orbax checkpoints. The model card documents research use and absence of instruction tuning.