JAYPEE INSTITUTE OF INFORMATION TECHNOLOGY

COMPUTER NETWORKS & INTERNET of THINGS (18B11CS311)

BTECH 6TH SEM

TRANSPORT LAYER

Q1. Answer true or false to the following questions and briefly justify your answer.

a) With the SR protocol, it is possible for the sender to receive an ACK for a packet that falls outside of its currentwindow.

b) With GBN, it is possible for the sender to receive an ACK for a packet that falls outside of its current window.

Q2. In a reliable transfer protocol, can a sender tell the difference between a lost data packet and a lost ACK?

Q3. How many sequence numbers are needed in a pipelined reliable transfer protocol to avoid ambiguity when the window size is *w*?

Q4. Explain whyfor SR, $receive\ window \leq \frac{sequence\ num\ range}{2}$

Q5. Consider a 5-bit sequence number. If the sequence number starts with 0, what is the sequence number of the 100th packet?

Q6. Using a 5-bit sequence number, what is the maximum size of the send and receive windows for each of the following protocols:

a. top-and-Wait b.Go-Back-N c. Selective-Repeat

Q7. What value is sent for the checksum in one of the following hypothetical situations?

a) The sender decides not to include thechecksum.

b) The sender decides to include the checksum, but the value of the sum is all1s.

c) The sender decides to include the checksum, but the value of the sum is all0s.

Q8. Calculate checksum for a UDP datagram if the message sent is “ITSUDP”. Consider source IP: 172.16.68.11, port 1054 and destination IP 101.25.63.42, port 80.

Q9. In a TCP connection, the initial sequence number at the client site is 2,171. The client opens the connection, sends only one segment carrying 1,000 bytes of data, and closes the connection. What is the value of the sequence number in each of the following segments sent by the client?

a. The SYNsegment?

b. The datasegment?

c. The FINsegment?

Q10. In a connection, the value of cwnd is 3000 and the value of rwnd is 5000. The host has sent 2,000 bytes, which have not been acknowledged. How many more bytes can be sent?

Q11. Suppose that a sender and a receiver are to perform reliable data delivery.

a) Ina Go-Back-N protocol, the window size is 6. Frames with sequence numbers 1, 2, 3, 4 and 5 have been sent. The sender just received an ACK for frame 1. Frames 6, 7, 8, 9 and 10 are waiting to be sent. Draw the time diagram showing thisscenario.

b) Which frame(s) can the sender send before it must wait for the next ACK from the receiver?Explain

c) Sometime later, the sender transmitted frames 20, 21, 22, 23, 24, and 26; however, frame 22 got lost. If Go-Back-N is used, what frame(s) would the sender have to

retransmit? Explain.

d) Suppose the same situation as above but sender and receiver use Selective- Repeat. What frame(s) would the sender need to retransmit? Explain.
e) Can Selective-Repeat use cumulative ACKs? Explain

Q12. Host A is sending a 10,000-byte file to Host B using a sliding window protocol. Packets are limited to 1000 bytes each, packets are numbered by packet number starting at 1, and the window size is 5 packets. Packet 3 is lost.

a) Which packets are retransmitted if Host A and Host B are using the Go-Back-Nprotocol?
b) Which packets are retransmitted if Host A and Host B are using the Selective Repeatprotocol?

Q13. Assume we need to design a Go-Back-N sliding window protocol for a network in which the bandwidth is 100 Mbps and the average distance between the sender and receiver is 10,000 km. Assume the average packet size is 100,000 bits and the propagation speed is $2x10^8 m/s$. Find

a) the maximum size of the send and receive windows
b) the number of bits in the sequence number field
c) an appropriate timeout value for the timer (that determines packet loss at the sender)

Q14. (a.) Consider the sliding window protocol in Figure (4a) to the right. Does this figure indicate that Go-Back-N is being used, Selective Repeat is being used, or there is not enough information to tell? Explain your answerbriefly.





(b.) Consider the sliding window protocol Figure (4b) to the right. Does this figure indicate that Go-Back-N is being used, Selective Repeat is being used, or there is not enough information to tell? Explain your answerbriefly.

(c.) Consider Figure (4b) again. Suppose the sender and receiver windows are of size N = 4 and suppose the sequence number space goes from 0 to 15. Show the position of the sender and receiver windows over this sequence number space at time *t* (the horizontal dashed line).

(d.) Give a list of all possible future events at the sender resulting from the ACKs currently propagating from receiver to sender at time *t*. Foreach of theseevents,indicate the action take at the sender(only).