Name: Akshad Chakor

PRN No: 202501090160

ME2/M22

4.1.1. Pandas - series creation and manipulation

03:12

Write a Python program that takes a list of numbers from the user, creates a Pandas series from it, and then calculates the mean of even and odd numbers separately using the groupby and mean() operations.

Hint: You can group the Series based on whether each number is even or odd.

Input Format:

- The user should enter a list of numbers separated by space when prompted.

Output Format:

- The program should display the mean of even and odd numbers separately.
- Each mean value should be displayed with a label indicating whether it corresponds to even or odd numbers.

Refer to the sample test cases for better understanding regarding input and output format.

```
# import pandas as pd


# # Take inputs from the user to create a list of numbers

# numbers = list(map(int, input().split()))


# grouped =


# # Display the mean of even and odd numbers with labels

# grouped.index = ['Even' if is_even else 'Odd' for is_even in grouped.index]
```

```
# print("Mean of even and odd numbers:")
# print(grouped)
import pandas as pd

# Take inputs from the user to create a list of numbers
numbers = list(map(int, input().split()))

# Create a Pandas series from the list of numbers
s = pd.Series(numbers)

# Grouping by even and odd numbers and calculating the mean
grouped = s.groupby(s % 2 == 0).mean()

# Display the mean of even and odd numbers with labels grouped.index =
['Even' if is_even else 'Odd' for is_even in grouped.index]

print("Mean of even and odd numbers:")
print(grouped)
```



Test case 2 13 ms Debug

Expected output	Actual output
4 4 4 6 6 2 2 2 10 12 14 16	4 4 4 6 6 2 2 2 10 12 14 16
Mean of even and odd numbers:	Mean of even and odd numbers:
Even ... 6.833333	Even ... 6.833333
dtype: float64	dtype: float64

Test case 3 13 ms Debug

Expected output	Actual output
1 5 7 9 11 13 15 17 111 21 25	1 5 7 9 11 13 15 17 111 21 25
Mean of even and odd numbers:	Mean of even and odd numbers:
Odd ... 21.363636	Odd ... 21.363636
dtype: float64	dtype: float64

4.1.2. Dictionary to dataframe

07:26

A dictionary of lists has been provided to you in the editor. Create a DataFrame from the dictionary of lists and perform the listed operations, then display the DataFrame before and after each manipulation.

Create the DataFrame:

- Convert the dictionary to a Pandas DataFrame.

Add a new row:

- Take inputs from the user for the new row data (name, age).
- Add the new row to the DataFrame.
- Display the DataFrame after adding the new row.

Modify a row:

- Modify a specific row by changing the age. Take the row index and new age

value from the user.

- Display the DataFrame after modifying the row.

Delete a row:

- Take the row index to be deleted from the user.
- Remove the specified row.
- Display the DataFrame after deleting the row.

Add a new column:

- Add a column Gender with values taken from the user.
- Display the DataFrame after adding the new column.

Modify a column:

- Convert names to uppercase.
- Display the DataFrame after modifying the column.

Delete a column:

- Remove the Age column.
- Display the DataFrame after deleting the column. import pandas as pd

```
# Provided dictionary of lists
data = {
    'Name': ['Alice', 'Bob', 'Charlie'],
    'Age': [25, 30, 35],
}

# Convert the dictionary to a DataFrame
df = pd.DataFrame(data)

# Display the original DataFrame
```

```
print("Original DataFrame:")
print(df)

# Adding a new row new_name =
input("New name: ") new_age =
int(input("New age: ")) df.loc[len(df)] =
[new_name, new_age]


# Display the DataFrame after adding a new row
print("After adding a row:\n",df)

# Modifying a row row_to_modify = int(input("Index
of row to modify: ")) new_age_value =
int(input("New age: ")) df.at[row_to_modify, "Age"] =
new_age_value

# Display the DataFrame after modifying a row
print("After modifying a row:") print(df)

# Deleting a row row_to_delete = int(input("Index of row to
delete: ")) df =
df.drop(index=row_to_delete).reset_index(drop=True)

# Display the DataFrame after deleting a row
print("After deleting a row:") print(df)

# Adding a new column genders_input = input("Enter
genders separated by space: ") genders =
genders_input.split()

# Ensure correct length if
len(genders) == len(df):
```

```
df["Gender"] = genders
else:
    print("Error: Number of genders must match rows!")
df["Gender"] = ["Unknown"] * len(df)


# Display the DataFrame after adding a new column
print("After adding a new column:")
print(df)

# Modifying a column df["Name"] =
df["Name"].str.upper()


# Display the DataFrame after modifying a column
print("After modifying a column:") print(df)

# Deleting a column df =
df.drop(columns=["Age"])

# Display the DataFrame after deleting a column
print("After deleting a column:")
print(df)
```

Explorer

Average time	Maximum time
0.043 s	0.049 s
43.00 ms	49.00 ms

1 out of 1 shown test case(s) passed

1 out of 1 hidden test case(s) passed

```
After modifying a row:
      Name  Age
0    Alice   27
1      Bob   30
2  Charlie   35
3    Susan   29
Index of row to delete: 3
After deleting a row:
      Name  Age
0    Alice   27
1      Bob   30
2  Charlie   35
Enter genders separated by space: F M M
After adding a new column:
      Name  Age Gender
0    Alice   27      F
1      Bob   30      M
2  Charlie   35      M
After modifying a column:
      Name  Age Gender
0    ALICE   27      F
1      BOB   30      M
2  CHARLIE   35      M
After deleting a column:
      Name Gender
0    ALICE      F
1      BOB      M
2  CHARLIE      M
```


```
After modifying a row:
      Name  Age
0    Alice   27
1      Bob   30
2  Charlie   35
3    Susan   29
Index of row to delete: 3
After deleting a row:
      Name  Age
0    Alice   27
1      Bob   30
2  Charlie   35
Enter genders separated by space: F M M
After adding a new column:
      Name  Age Gender
0    Alice   27      F
1      Bob   30      M
2  Charlie   35      M
After modifying a column:
      Name  Age Gender
0    ALICE   27      F
1      BOB   30      M
2  CHARLIE   35      M
After deleting a column:
      Name Gender
0    ALICE      F
1      BOB      M
2  CHARLIE      M
```


Debugger

Terminal | Test cases

4.1.3. Student Information

01:49

Write a program to read a text file containing student information (name, age, and grade) using Pandas. Perform the following tasks:

- Display the first five rows of the data frame.
- Calculate the average age of the students (limit the average age up to 2 decimal places).
- Filter out the students who have a grade above a certain threshold (consider the threshold grade is 'B').

Note:

Refer to the displayed test cases for better understanding.

```
import pandas as pd

# Read the text file into a DataFrame file = input() data = pd.read_csv(file,

sep="\s+", header=None, names=["Name", "Age", "Grade"])

# Display the first five rows

print("First five rows:")

print(data.head())


# Calculate the average age (2 decimal places)

avg_age = round(data["Age"].mean(), 2)

print("Average age:", avg_age)


# Filter students with grade up to 'B' (A and B)

filtered = data[data["Grade"].isin(['A', 'B'])]


print("Students with a grade up to B")

print(filtered)
```



4.1.3. Student Information

01:49

Write a program to read a text file containing student information (name, age, and grade) using Pandas. Perform the following tasks:

- Display the first five rows of the data frame.
- Calculate the average age of the students (limit the average age up to 2 decimal places).
- Filter out the students who have a grade above a certain threshold (consider the threshold grade is 'B').

Note:

Refer to the displayed test cases for better understanding.

```
import pandas as pd

# Prompt the user for the file name
file_name = input()

# Load the data df =
pd.read_csv(file_name) # Prepare
data for calculation df['Date'] =
pd.to_datetime(df['Date']) df['Month'] =
df['Date'].dt.to_period('M') df['Sales'] =
df['Quantity'] * df['Price']

# Find the month with the highest total sales best_month
= df.groupby('Month')['Sales'].sum().idxmax()
highest_sales = df.groupby('Month')['Sales'].sum().max()
print(f"Best month: {best_month}")
print(f"Total sales: ${highest_sales:.2f}")
```

4.2.2. Best Selling Product 02:08 and

performs the following operations:

Write a Python program that takes the file name of a CSV file as input, reads the data,

- The CSV file contains the columns: Date, Product, Quantity, Price, and City.
- Find the product that sold the most in terms of quantity sold.
- Display the product that sold the most and the total quantity sold for that product.

Sample Data:

Date,Product,Quantity,Price,City

2025-01-01,Product A,5,20,New York

2025-01-01,Product B,3,15,Los Angeles

2025-01-02,Product A,7,20,New York

2025-01-02,Product C,4,30,Chicago

2025-01-03,Product B,2,15,Chicago

2025-01-03,Product A,8,20,Los Angeles

2025-01-04,Product C,6,30,New York

2025-01-04,Product B,5,15,Los Angeles

2025-01-05,Product A,3,20,Chicago

2025-01-05,Product C,10,30,Los Angeles

Note:

The data cannot be displayed in the file. You can refer to the sample data provided for insights.

```
import pandas as pd


# Prompt the user for the file name

file_name = input()


# Load the data df =

pd.read_csv(file_name)
```

Find the product with the highest total quantity sold

best_product = df.groupby('Product')['Quantity'].sum().idxmax()

highest_quantity = df.groupby('Product')['Quantity'].sum().max()

Display the result print(f"Best selling

product: {best_product}") print(f"Total quantity

sold: {highest_quantity}")

4.2.3. City that Sold the Most Products

01:45 and performs the following

operations:

- The CSV file contains the columns: Date, Product, Quantity, Price, and City.
- Group the data by City and calculate the total quantity of products sold for each city.
- Find the city that sold the most products (based on the total quantity sold).

Sample Data:

Date,Product,Quantity,Price,City

2025-01-01,Product A,5,20,New York

2025-01-01,Product B,3,15,Los Angeles

2025-01-02,Product A,7,20,New York

Write a Python program that takes the file name of a CSV file as input, reads the data,

2025-01-02,Product C,4,30,Chicago

2025-01-03,Product B,2,15,Chicago

2025-01-03,Product A,8,20,Los Angeles

2025-01-04,Product C,6,30,New York

2025-01-04,Product B,5,15,Los Angeles

2025-01-05,Product A,3,20,Chicago 2025-01-

05,Product C,10,30,Los Angeles

Note:

The data cannot be displayed in the file. You can refer to the sample data provided for insights.

```
import pandas as pd


# Prompt the user for the file name
file_name = input()


# Load the data df = pd.read_csv(file_name) #
Group by City and calculate total quantity
city_sales = df.groupby('City')['Quantity'].sum()


# Find the city with the highest total quantity sold
best_city = city_sales.idxmax()



# Display the result print(f"City sold the most
products: {best_city}")
```



4.2.4. Most Frequently Sold Product Pairs

01:25

and performs the following operations:

- The CSV file contains the following columns: Date, Product, Quantity, Price, and City.
- For each date, find all pairs of products that were sold together (i.e., two products sold on the same date).
- Output the product pair/s that was sold most frequently.

Sample Data:

Date,Product,Quantity,Price,City

2025-01-01,Product A,5,20,New York

2025-01-01,Product B,3,15,Los Angeles

2025-01-02,Product A,7,20,New York

2025-01-02,Product C,4,30,Chicago

2025-01-03,Product B,2,15,Chicago

2025-01-03,Product A,8,20,Los Angeles

2025-01-04,Product C,6,30,New York

2025-01-04,Product B,5,15,Los Angeles

Write a Python program that takes the file name of a CSV file as input, reads the data,

2025-01-05,Product A,3,20,Chicago 2025-01-

05,Product C,10,30,Los Angeles

Explanation:

Transactions:

- 2025-01-01: Product A, Product B
- 2025-01-02: Product A, Product C
- 2025-01-03: Product B, Product A
- 2025-01-04: Product C, Product B 2025-01-05: Product A, Product C

Now, let's count how often the pairs of products appear together:

- Product A and Product B : Appear in transactions on 2025-01-01 and 2025-0103.
- Product A and Product C : Appear in transactions on 2025-01-02 and 2025-0105.
- Product B and Product C : Appears in transactions on 2025-01-04.

Most Frequent Product Combinations:

- Product A and Product B (2 times)
- Product A and Product C (2 times)

Note:

The data cannot be displayed in the file. You can refer to the sample data provided for insights.

```
import pandas as pd

from itertools import combinations

from collections import Counter


# Prompt user to input the file name

file_name = input()


# Read data from the specified CSV file

df = pd.read_csv(file_name) # write the
```

code pair_counter = Counter()

Group by Date and generate product pairs

for _, group in df.groupby('Date'):

products = group['Product'].tolist() pairs =

combinations(sorted(products), 2)

pair_counter.update(pairs)

Find maximum frequency max_count

= max(pair_counter.values())

Output the most frequent product pairs

for pair, count in pair_counter.items():

if count == max_count:

    print(f"{pair[0]} and {pair[1]}: {count} times")



4.2.5. Titanic Dataset Analysis and Data Cleaning

01:36

You are provided with the Titanic dataset containing information about passengers on the Titanic. Your task is to write Python code to answer the following questions based on the dataset. For each question, perform necessary data cleaning, transformations, and calculations as required.

1. Display the first 5 rows of the dataset.
2. Display the last 5 rows of the dataset.
3. Get the shape of the dataset (number of rows and columns).
4. Get a summary of the dataset (using .info()).
5. Get basic statistics (mean, standard deviation, etc.) of the dataset using .describe().
6. Check for missing values and display the count of missing values for each column.
7. Fill missing values in the ‘Age’ column with the median age.
8. Fill missing values in the ‘Embarked’ column with the most frequent value (mode()).
9. Drop the ‘Cabin’ column due to many missing values.
10. Create a new column, 'FamilySize' by adding the 'SibSp' and 'Parch' columns.

The Titanic dataset contains columns as shown below,

PassengerId	Survived	Pclass	Name	Sex	Age	SibSp	Parch	Ticket	Fare	Cabin	Embark

Sample Data:

PassengerId,Survived,Pclass,Name,Sex,Age,SibSp,Parch,Ticket,Fare,Cabin,Embarked
1,0,3,"Braund, Mr. Owen Harris",male,22,1,0,A/5 21171,7.25,,S

2,1,1,"Cumings, Mrs. John Bradley (Florence Briggs Thayer)",female,38,1,0,PC 17599,71.2833,C85,C

3,1,3,"Heikkinen, Miss. Laina",female,26,0,0,STON/O2. 3101282,7.925,,S

4,1,1,"Futrelle, Mrs. Jacques Heath (Lily May Peel)",female,35,1,0,113803,53.1,C123,S

5,0,3,"Allen, Mr. William Henry",male,35,0,0,373450,8.05,,S

6,0,3,"Moran, Mr. James",male,,0,0,330877,8.4583,,Q

7,0,1,"McCarthy, Mr. Timothy J",male,54,0,0,17463,51.8625,E46,S

8,0,3,"Palsson, Master. Gosta Leonard",male,2,3,1,349909,21.075,,S

9,1,3,"Johnson, Mrs. Oscar W (Elisabeth Vilhelmina Berg)",female,27,0,2,347742,11.1333,,S

10,1,2,"Nasser, Mrs. Nicholas (Adele Achem)",female,14,1,0,237736,30.0708,,C

Note: Refer to the visible test case for better reference.

```
import pandas as pd

import numpy as np

# Load the Titanic dataset data =

pd.read_csv('Titanic-Dataset.csv') # 1.

Display the first 5 rows of the dataset

print(data.head())

# 2. Display the last 5 rows of the dataset

print(data.tail())

# 3. Get the shape of the dataset

print(data.shape)

# 4. Get a summary of the dataset (info)

print(data.info())
```

5. Get basic statistics of the dataset

print(data.describe())

6. Check for missing values

print(data.isnull().sum())

7. Fill missing values in the ‘Age’ column with the median age

data['Age'] = data['Age'].fillna(data['Age'].median())

8. Fill missing values in the ‘Embarked’ column with the mode

data['Embarked'] = data['Embarked'].fillna(data['Embarked'].mode()[0])

9. Drop the ‘Cabin’ column due to many missing values

data = data.drop(columns=['Cabin'])

10. Create a new column 'FamilySize’ by adding ‘SibSp' and ‘Parch'

data['FamilySize'] = data['SibSp'] + data['Parch']



Explorer

Average time
0.166 s
166.00 ms

Maximum time
0.166 s
166.00 ms

1 out of 1 shown test case(s) passed

```
[5 rows x 12 columns]
(891, 12)
<class 'pandas.core.frame.DataFrame'>
RangeIndex: 891 entries, 0 to 890
Data columns (total 12 columns):
 #   Column       Non-Null Count  Dtype
---  ------       --------------  -----
 0   PassengerId  891 non-null    int64
 1   Survived     891 non-null    int64
 2   Pclass       891 non-null    int64
 3   Name         891 non-null    object
 4   Sex          891 non-null    object
 5   Age          714 non-null    float64
 6   SibSp        891 non-null    int64
 7   Parch        891 non-null    int64
 8   Ticket       891 non-null    object
 9   Fare         891 non-null    float64
 10  Cabin        204 non-null    object
 11  Embarked     889 non-null    object
dtypes: float64(2), int64(5), object(5)
memory usage: 66.2+ KB
None
       PassengerId    Survived      Pclass  ...       SibSp       Parch        Fare
count   891.000000  891.000000  891.000000  ...  891.000000  891.000000  891.000000
mean    446.000000    0.383838    2.308642  ...    0.523008    0.381594   32.204208
std     257.353842    0.486592    0.836071  ...    1.102743    0.806057   49.693429
```


```
[5 rows x 12 columns]
(891, 12)
<class 'pandas.core.frame.DataFrame'>
RangeIndex: 891 entries, 0 to 890
Data columns (total 12 columns):
 #   Column       Non-Null Count  Dtype
---  ------       --------------  -----
 0   PassengerId  891 non-null    int64
 1   Survived     891 non-null    int64
 2   Pclass       891 non-null    int64
 3   Name         891 non-null    object
 4   Sex          891 non-null    object
 5   Age          714 non-null    float64
 6   SibSp        891 non-null    int64
 7   Parch        891 non-null    int64
 8   Ticket       891 non-null    object
 9   Fare         891 non-null    float64
 10  Cabin        204 non-null    object
 11  Embarked     889 non-null    object
dtypes: float64(2), int64(5), object(5)
memory usage: 66.2+ KB
None
       PassengerId    Survived      Pclass  ...       SibSp       Parch        Fare
count   891.000000  891.000000  891.000000  ...  891.000000  891.000000  891.000000
mean    446.000000    0.383838    2.308642  ...    0.523008    0.381594   32.204208
std     257.353842    0.486592    0.836071  ...    1.102743    0.806057   49.693429
```


Debugger

Terminal | Test cases

Explorer

Average time
0.166 s
166.00 ms

Maximum time
0.166 s
166.00 ms

1 out of 1 shown test case(s) passed

Debugger

```
count  891.000000  891.000000  891.000000  ...  891.000000  891.00
0000  891.000000
mean   446.000000    0.383838    2.308642  ...    0.523008    0.38
1594   32.204208
std    257.353842    0.486592    0.836071  ...    1.102743    0.80
6057   49.693429
min      1.000000    0.000000    1.000000  ...    0.000000    0.00
0000    0.000000
25%    223.500000    0.000000    2.000000  ...    0.000000    0.00
0000    7.910400
50%    446.000000    0.000000    3.000000  ...    0.000000    0.00
0000   14.454200
75%    668.500000    1.000000    3.000000  ...    1.000000    0.00
0000   31.000000
max    891.000000    1.000000    3.000000  ...    8.000000    6.00
0000  512.329200
```

```
[8 rows x 7 columns]
PassengerId      0
Survived         0
Pclass           0
Name             0
Sex              0
Age            177
SibSp            0
Parch            0
Ticket           0
Fare             0
Cabin          687
Embarked         2
dtype: int64
```


```
count  891.000000  891.000000  891.000000  ...  891.000000  891.00
0000  891.000000
mean   446.000000    0.383838    2.308642  ...    0.523008    0.38
1594   32.204208
std    257.353842    0.486592    0.836071  ...    1.102743    0.80
6057   49.693429
min      1.000000    0.000000    1.000000  ...    0.000000    0.00
0000    0.000000
25%    223.500000    0.000000    2.000000  ...    0.000000    0.00
0000    7.910400
50%    446.000000    0.000000    3.000000  ...    0.000000    0.00
0000   14.454200
75%    668.500000    1.000000    3.000000  ...    1.000000    0.00
0000   31.000000
max    891.000000    1.000000    3.000000  ...    8.000000    6.00
0000  512.329200
```

```
[8 rows x 7 columns]
PassengerId      0
Survived         0
Pclass           0
Name             0
Sex              0
Age            177
SibSp            0
Parch            0
Ticket           0
Fare             0
Cabin          687
Embarked         2
dtype: int64
```


Terminal | Test cases

‹ Prev | Reset | Submit | Next ›

9:37 PM
4/24/2026

4.2.6. Titanic Dataset Analysis and Data Cleaning - 2

02:18

You are provided with the Titanic dataset containing information about passengers on the Titanic. Your task is to write Python code to answer the following questions based on the dataset.

1. Create a new column ‘IsAlone’ which is 1 if the passenger is alone (FamilySize = 0), otherwise 0.
2. Convert the ‘Sex' column to numeric values (male: 0, female: 1).
3. One-hot encode the ‘Embarked’ column, dropping the first category.
4. Get the mean age of passengers.
5. Get the median fare of passengers.
6. Get the number of passengers by class.
7. Get the number of passengers by gender.
8. Get the number of passengers by survival status.
9. Calculate the survival rate of passengers.
10. Calculate the survival rate by gender.

The Titanic dataset contains columns as shown below,

PassengerId	Survived	Pclass	Name	Sex	Age	SibSp	Parch	Ticket	Fare	Cabin	Embark

Sample Data:

PassengerId,Survived,Pclass,Name,Sex,Age,SibSp,Parch,Ticket,Fare,Cabin,Embarked

1,0,3,"Braund, Mr. Owen Harris",male,22,1,0,A/5 21171,7.25,,S

2,1,1,"Cumings, Mrs. John Bradley (Florence Briggs Thayer)",female,38,1,0,PC 17599,71.2833,C85,C

3,1,3,"Heikkinen, Miss. Laina",female,26,0,0,STON/O2. 3101282,7.925,,S
4,1,1,"Futrelle, Mrs. Jacques Heath (Lily May Peel)",female,35,1,0,113803,53.1,C123,S

5,0,3,"Allen, Mr. William Henry",male,35,0,0,373450,8.05,,S

6,0,3,"Moran, Mr. James",male,,0,0,330877,8.4583,,Q

7,0,1,"McCarthy, Mr. Timothy J",male,54,0,0,17463,51.8625,E46,S

8,0,3,"Palsson, Master. Gosta Leonard",male,2,3,1,349909,21.075,,S

9,1,3,"Johnson, Mrs. Oscar W (Elisabeth Vilhelmina
Berg)",female,27,0,2,347742,11.1333,,S

10,1,2,"Nasser, Mrs. Nicholas (Adele Achem)",female,14,1,0,237736,30.0708,,C

Note: Refer to the visible test case for better reference.

```
import pandas as pd

import numpy as np


# Load the Titanic dataset data = pd.read_csv('Titanic-

Dataset.csv') data['FamilySize'] = data['SibSp'] +

data['Parch'] # 1. Create a new column ‘IsAlone' (1 if

alone, 0 otherwise) data['IsAlone'] =

np.where(data['FamilySize'] == 0, 1, 0)


# 2. Convert ‘Sex' to numeric (male: 0, female: 1)

data['Sex'] = data['Sex'].map({'male': 0, 'female': 1})


# 3. One-hot encode the ‘Embarked' column data =

pd.get_dummies(data, columns=['Embarked'], drop_first=True)


# 4. Get the mean age of passengers

print(data['Age'].mean())


# 5. Get the median fare of passengers

print(data['Fare'].median())
```

```
# 6. Get the number of passengers by class
print(data['Pclass'].value_counts())

# 7. Get the number of passengers by gender
print(data['Sex'].value_counts())

# 8. Get the number of passengers by survival status
print(data['Survived'].value_counts())

# 9. Calculate the survival rate
print(data['Survived'].mean())

# 10. Calculate the survival rate by gender
print(data.groupby('Sex')['Survived'].mean())
```



4.2.7. Titanic Dataset Analysis and Data Cleaning - 3

03:10

You are provided with the Titanic dataset containing information about passengers on the Titanic. Your task is to write Python code to answer the following questions based on the dataset.

1. Calculate the survival rate by class.
2. Calculate the survival rate by embarkation location (Embarked_S).
3. Calculate the survival rate by family size (FamilySize).
4. Calculate the survival rate by being alone (IsAlone).
5. Get the average fare by passenger class (Pclass).
6. Get the average age by passenger class (Pclass).
7. Get the average age by survival status (Survived).
8. Get the average fare by survival status (Survived).
9. Get the number of survivors by class (Pclass).
10. Get the number of non-survivors by class (Pclass).

The Titanic dataset contains columns as shown below,

Sample Data:

PassengerId,Survived,Pclass,Name,Sex,Age,SibSp,Parch,Ticket,Fare,Cabin,Embarked

1,0,3,"Braund, Mr. Owen Harris",male,22,1,0,A/5 21171,7.25,,S

2,1,1,"Cumings, Mrs. John Bradley (Florence Briggs Thayer)",female,38,1,0,PC 17599,71.2833,C85,C

3,1,3,"Heikkinen, Miss. Laina",female,26,0,0,STON/O2. 3101282,7.925,,S

4,1,1,"Futrelle, Mrs. Jacques Heath (Lily May Peel)",female,35,1,0,113803,53.1,C123,S

PassengerId	Survived	Pclass	Name	Sex	Age	SibSp	Parch	Ticket	Fare	Cabin	Embark

5,0,3,"Allen, Mr. William Henry",male,35,0,0,373450,8.05,,S

6,0,3,"Moran, Mr. James",male,,0,0,330877,8.4583,,Q

7,0,1,"McCarthy, Mr. Timothy J",male,54,0,0,17463,51.8625,E46,S

8,0,3,"Palsson, Master. Gosta Leonard",male,2,3,1,349909,21.075,,S

9,1,3,"Johnson, Mrs. Oscar W (Elisabeth Vilhelmina

Berg)",female,27,0,2,347742,11.1333,,S

10,1,2,"Nasser, Mrs. Nicholas (Adele Achem)",female,14,1,0,237736,30.0708,,C

Note: Refer to the visible test case for better reference.

```
import pandas as pd
import numpy as np

# Load the Titanic dataset data = pd.read_csv('Titanic-Dataset.csv')
data['FamilySize'] = data['SibSp'] + data['Parch'] data['IsAlone'] =
np.where(data['FamilySize'] > 0, 0, 1) data = pd.get_dummies(data,
columns=['Embarked'], drop_first=True)

# 1. Calculate the survival rate by class
print(data.groupby('Pclass')['Survived'].mean())

# 2. Calculate the survival rate by embarked location
print(data.groupby('Embarked_S')['Survived'].mean())

# 3. Calculate the survival rate by family size
print(data.groupby('FamilySize')['Survived'].mean())

# 4. Calculate the survival rate by being alone
print(data.groupby('IsAlone')['Survived'].mean())

# 5. Get the average fare by class
print(data.groupby('Pclass')['Fare'].mean())

# 6. Get the average age by class
print(data.groupby('Pclass')['Age'].mean())

# 7. Get the average age by survival status
print(data.groupby('Survived')['Age'].mean()) # 8. Get the average fare by survival
```

status print(data.groupby('Survived')['Fare'].mean())

9. Get the number of survivors by class

print(data[data['Survived'] == 1]['Pclass'].value_counts())

10. Get the number of non-survivors by class

print(data[data['Survived'] == 0]['Pclass'].value_counts())

Explorer

Average time
0.103 s
103.00 ms

Maximum time
0.103 s
103.00 ms

1 out of 1 shown test case(s) passed

Debugger

Test case 1 103 ms Debug

Expected output	Actual output
Pclass	Pclass
1 0.629630	1 0.629630
2 0.472826	2 0.472826
3 0.242363	3 0.242363
Name: Survived, dtype: float64	Name: Survived, dtype: float64
Embarked_S	Embarked_S
0 0.506073	0 0.506073
1 0.336957	1 0.336957
Name: Survived, dtype: float64	Name: Survived, dtype: float64
FamilySize	FamilySize
0 0.303538	0 0.303538
1 0.552795	1 0.552795
2 0.578431	2 0.578431
3 0.724138	3 0.724138
4 0.200000	4 0.200000
5 0.136364	5 0.136364
6 0.333333	6 0.333333
7 0.000000	7 0.000000
10 0.000000	10 0.000000
Name: Survived, dtype: float64	Name: Survived, dtype: float64
IsAlone	IsAlone
0 0.505650	0 0.505650
1 0.303538	1 0.303538
Name: Survived, dtype: float64	Name: Survived, dtype: float64
Pclass	Pclass
1 84.154687	1 84.154687
2 20.662183	2 20.662183
3 13.675550	3 13.675550
Name: Fare, dtype: float64	Name: Fare, dtype: float64
Pclass	Pclass
1 38.233441	1 38.233441
2 29.877630	2 29.877630

Explorer

Average time
0.103 s
103.00 ms

Maximum time
0.103 s
103.00 ms

1 out of 1 shown test case(s) passed

Debugger

```
5    0.136364
6    0.333333
7    0.000000
10   0.000000
Name: Survived, dtype: float64
IsAlone
0    0.505650
1    0.303538
Name: Survived, dtype: float64
Pclass
1    84.154687
2    20.662183
3    13.675550
Name: Fare, dtype: float64
Pclass
1    38.233441
2    29.877630
3    25.140620
Name: Age, dtype: float64
Survived
0    30.626179
1    28.343690
Name: Age, dtype: float64
Survived
0    22.117887
1    48.395408
Name: Fare, dtype: float64
1    136
3    119
2    87
Name: Pclass, dtype: int64
3    372
2    97
1    80
```


```
5    0.136364
6    0.333333
7    0.000000
10   0.000000
Name: Survived, dtype: float64
IsAlone
0    0.505650
1    0.303538
Name: Survived, dtype: float64
Pclass
1    84.154687
2    20.662183
3    13.675550
Name: Fare, dtype: float64
Pclass
1    38.233441
2    29.877630
3    25.140620
Name: Age, dtype: float64
Survived
0    30.626179
1    28.343690
Name: Age, dtype: float64
Survived
0    22.117887
1    48.395408
Name: Fare, dtype: float64
1    136
3    119
2    87
Name: Pclass, dtype: int64
3    372
2    97
1    80
```


‹ Prev Reset Submit Next ›