

CAPRICORN ELEVATORS PVT LTD

11th Floor, Jomer Symphony, Ponnurnni-East Vyttila,
Ernakulam, Kerala - 682028

info@capricornelevators.com

+91- 894-3777-000 +91-759-3000-222

GSTIN: 32AAMCC4492R1ZY CIN:U82990KL2025PTC092138



Redefining Vertical Mobility

Project Timeline and Material specifications

SL No.	Description	Duration	Total Price
1	Technical Inspection of site	7 days	To be Done within 7 Days of order Confirmation
2	GAD Submission	15 days	To be submitted within 8 days after technical inspection.
3	Material Delivery	60 days	Within 45 days of approval GAD
4	Installation & Commissioning	90 days	Within 30 days of delivery

• Controller	Microprocessor based full collective selective, Duel Door Control Technology, High Performance for control AC Drive with latest version of integrated controller make of MONARCH
• Power Supply	415 Volts 3 Phase 50 Cycles A C
• Gearless Machine	Make of MONADRIIVE/TORINDRIIVE / MONTANARI make as per IS specification suitable for 6 Passengers for 3 stops with a speed of .06 mps of VVVF model , (3 gr ½) main pulley, 12" brake (110 VDC) with motor capacity of 3.6 HP and RPM of 120 3 phase , 415 Volts electric motor with stand
• Over Speed Governor	Make of MONADRIIVE/TORINDRIIVE / MONTANARI specially designed to bring the lift to safety if speed exceeds the limit
• Main Guide Rail	9 mm main guide rail of MONTIFERRO as per standard specification as per lift act for 6 passengers lift
• Counter wt Guide	6 mm counter wt guide rail of MONTIFERRO.
• Cabin Enclosure	Classic STAINLESS-STEEL HAIRLINE FINISHED CABIN (GRADE 304) of 1.2 mm thickness of makes Jindal with Stainless Steel false ceiling and Blower for fresh air

CAPRICORN ELEVATORS PVT LTD

11th Floor, Jomer Symphony, Ponnurnni-East Vyttila,
Ernakulam, Kerala - 682028

info@capricornelevators.com

+91- 894-3777-000 +91-759-3000-222

GSTIN: 32AAMCC4492R1ZY CIN:U82990KL2025PTC092138



Redefining Vertical Mobility

Cabin Ceiling	Cabin Ceiling shall be of Designer ceiling with Stainless Steel with 6 LED Lights and one fresh air blower for STAINLESS-STEEL HAIRLINE FINISHED CABIN
Car Door and Entrance	Protected by Centre / Telescopic opening of Stainless Steel Hair Finished Door (Grade 304) & Genesis Mechanism
Landing Door and Entrance	Protected by Centre / Telescopic opening of Stainless Steel Hair Finished Door (Grade 304) & Genesis Mechanism
Main Rope	Make USHA MARTIN Rope of 8 mm Rope as per IS 2365/1977
Buffer Spring	Heavy -duty type spring
Main Drive	Make of HPMONT
Floor Sensing Sensors	Floor sensing sensors are of WECO. Door safety sensors make of Multi Beam Sensor (WECO) with 160 Beams
Landing and Car Operating Buttons	The car button and landing button shall be stainless steel (Grade 304) for landing and car display with indicators of DOT MATRIX display or LCD display with Floor display position, RFID & PASSWORD, with safety instructions and Emergency Light.
Cable	Make of Macrotherm of 12 cores 0.50 sqmm for travelling cable with high class insulation and shaft wiring is of FRPVC cable of HPL makes.
Automatic Rescue Device (ARD)	Make of MONARCH(ARD)
Door Drive	MONARCH
Door Mechanism	GENESIS
Emergency Light	Make of Philips
Overload Sensor	Make of WECO

CAPRICORN ELEVATORS PVT LTD

11th Floor, Jomer Symphony, Ponnurnni-East Vyttila,
Ernakulam, Kerala - 682028

info@capricornelevators.com

+91- 894-3777-000 +91-759-3000-222

GSTIN: 32AAMCC4492R1ZY CIN:U82990KL2025PTC092138



Redefining Vertical Mobility

• Audio Annunciation	Floor announcement English with music
• Emergency Hooter	Emergency hooter shall be provided in the lift cabin
• Cabin Barricade	Standard Mild Steel Powder Coated
• Pit Ladder	Standard
• Hand Rails	Standard (Stainless Steel)

