

Query: "What is an LLM?"
Generated: 2026-08-17 15:03:18

OVERALL VERDICT	
PARTIALLY_SUPPORTED	
Hallucination Score: 0.823 / 1.000	
Risk Level: LOW	

CLAIM BREAKDOWN	
Total Claims Analyzed: 11	
Supported:	7 (63.6%)
Contradicted:	0 (0.0%)
Unverifiable:	0 (0.0%)
Insufficient Evidence:	4 (36.4%)

No likely hallucinations detected.

VERIFIED CLAIMS (7 confirmed)	
-------------------------------	--

#1:
Large Language Models (LLMs) are based on transformer-based neural networks developed by OpenAI in 2017.
Confidence: 90.0%
Sources: Large language model, Reasoning model

#2:
LLMs are primarily used for machine translation, text summarization, conversational interfaces like ChatGPT, and question answering systems such as DeepSeek-R1 \citep{radford2019language}.
Confidence: 90.0%
Sources: Large language model, DeepSeek

#3:
LLMs are trained on vast datasets including web texts, books, and documents.
Confidence: 90.0%
Sources: Large language model, List of large language models

#4:
LLMs have revolutionized natural language processing tasks by leveraging self-attention mechanisms.
Confidence: 70.0%
Sources: List of large language models, Large language model

#5:
The foundation of an LLM involves tokenization, where input text is divided into smaller units called tokens.
Confidence: 70.0%
Sources: List of large language models, Large language model

#6:

A key feature of LLMs is their ability to perform multiple reasoning steps.

Confidence: 70.0%

Sources: Reasoning model, Large language model

#7:

Processing inputs within an LLM involves advanced algorithms that weigh the importance of different parts of the input data through attention mechanisms.

Confidence: 70.0%

Sources: Large language model, List of large language models

+-----+				
	ANNOTATED ANSWER			
	= Supported	= Contradicted	= Mixed	= Unverified
+-----+				

Large Language Models (LLMs) are based on transformer-based neural networks developed by OpenAI in 2017, introduced. These models have revolutionized natural language processing tasks by leveraging self-attention mechanisms to weigh the importance of different parts of the input. LLMs are primarily used for a wide range of applications, including machine translation, text summarization, conversational AI, and more. The foundation of an LLM involves tokenization, where input text is divided into smaller units called tokens. These tokens are often subwords that allow the model to understand context more granularly. For example, "breakfast" might be split into "break" and "fast", enabling better semantic representation \citep{vaswani2017}. LLMs are trained on vast datasets, including web texts, books, and documents, which enable them to recognize patterns and generate human-like text. A key feature of LLMs is their ability to perform multiple reasoning steps. They analyze and synthesize information through a series of computations that consider the relationships between different parts of the input. This allows them to generate coherent outputs based on specific tasks they have been trained for, such as answering questions, summarizing text, and more. The architecture of LLMs is designed to handle sequential dependencies in text by maintaining a context-aware understanding of the input. The processing of inputs within an LLM involves advanced algorithms that weigh the importance of different parts of the input data through attention mechanisms. This is achieved through attention mechanisms, which allow the model to focus on relevant aspects of the text when generating output. For instance, in translation tasks, the model must attend to specific words or phrases that carry meaning, ensuring accurate and contextually appropriate translations.

+-----+	
	EVIDENCE SOURCES
+-----+	

DeepSeek
Large language model
List of large language models
Reasoning model