

Name :- Anshu Kumar  
 Stud. id :- 20712077, MCA-3B

1. Ques :-  
 <html>  
 <head>  
 <title> AngularJS Directives </title>  
 </head>  
 <body>  
 <h1> Sample </h1>

<div ng-app = "" ng-init = "countries  
 = [{ locale: 'en-India', name:  
 'India' }, { locale: 'en-GB',  
 name: 'United Kingdom' },  
 { locale: 'en-FR', name: 'France' }]  
 ">

<p> Enter Your Name: <input type=  
 "text" ng-model = "name">

</p>

<p> Hello <span ng-bind = "name">  
 </span> </p>

<p> List of Countries with  
 locale: </p>

<ol>


<li ng-repeat = "country in  
 countries">

{{ 'Country' + country.name + ',  
 '}}



Locale : ' + country.locale &&  
</li>  
</ol>  
</div>

<script src = "http://ajax.googleapis.com/ajax/libs/angularjs/1.3.14/angular.min.js">  
</script>  
</body>  
</html>



## Sample

Enter your Name:

Hello !

List of Countries with locale:

1. Country: India, Locale: en-India
2. Country: United Kingdom, Locale: en-GB
3. Country: France, Locale: en-FR





Name  $\rightarrow$  Ajushi Kanwar  
Stu. id  $\rightarrow$  20712077, MCA-3B

```
2)  $\rightarrow$  const http = require("http");  
const server = http.createServer  
  (req, res)  $\Rightarrow$  {  
  if (req.url == "/" )  
    res.end("You are at home  
    page");  
  else if (req.url == "/contact")  
    res.end("You are at contact");  
  else  
    res.writeHead(404)  
    res.end();  
  }  
server.listen(4002, "127.0.0.1",  
  ()  $\Rightarrow$  {  
  console.log("Listening to the  
  graphic era server...");  
  }  
}
```

The image shows a Visual Studio Code window with the following components:

- EXPLORER:** A folder named "PRACTICAL" containing two files: "ques1.html" and "ques2.js".
- EDITOR:** The file "ques2.js" is open, showing the following JavaScript code:

```
1 const http = require("http")
2 const server = http.createServer((req,res) =>{
3   if(req.url=="/")
4     res.end("You are at home page")
5   else if(req.url=="/contact")
6     res.end("You are at contacts")
7   else
8     res.writeHead(404)
9     res.end()
10  })
11  server.listen(4002,"127.0.0.1",()=>{
12    console.log("Listening to the graphic era server....")
13  })
```
- TERMINAL:** The terminal is open at the bottom, showing the command `node ques2.js` being executed. The output is "Listening to the graphic era server....".