Ans 1 –

```html
<html>
  <head>
    <title>Angular js directive</title>
  </head>

  <body>
    <h1>full Stack Question 1 </h1>

    <div ng-app = "" ng-init = "countries = [{
    local:'en-India', name:'India'},
    {locale: 'en-GrB', name: 'United Kingdom'},
    {locale:'en-FR', name: 'France'}]">

    <p>Hello <span ng-bind="name"></span>!</p>
    <p>List of Countries with locale:</p>
    <ol>

    <li ng-repeat ="country in countries">
      {{ 'Country: " + country.name + ', Locale: " +
      country.locale }}
    </li>

    </ol>
    </div>

    <script src = "https://ajax.googleapis.com/ajax/libs/angularjs/
       1.3.14/angular.min.js">
    </script>
```

Full Stack Question 1

Hello !

List of Countries with locale:

1. Country: India, Locale: en-India
2. Country: United Kingdom, Locale: en-GB
3. Country: France, Locale: en-FR

Any 2 –

```
const http = require("http")
const server = http.createServer((req, res) => {
    if(req.url == "/ ")
    res.end("You are at home page")
    else if (req.url == "/contact")
    res.end(" You are at contacts")
    else
    res.writeHead(404)
    res.end()
})

server.listen(4002,"127.0.0.1",() => {
console.log("Listening to the graphic era server....")
})
```

```
Last login: Mon Jan 31 10:24:10 on ttys000
[→  ~ nano node.js
[→  ~ node node.js
Listening to the graphic era server....
```

You are at home page