Name - Saurav Bhandari

Student Id - 20711088

Paper - Full stack Development Practical

Course - MCA (3B)

SEM - 3rd.

Q.1. Ans :-

```html
<html>
    <head>
        <title> Angular Js Directives </title>
    </head>
    <body>
        <h1> Sample </h1>
        <div ng-app ="" ng-init = "Countries = [{ locale:
        'en-India', name : 'India'}, {locale:' en-GB',
        name : 'United Kingdom'},
        {locale:'en-FR', name : 'France'}]"  >
        <P> Enter your Name :<input type ="text"
        ng-model =" name" ><span></P>
        <P> Hello <span ng-bind ="" name "> </span>!
            </P>

        <P> List of countries with locale: </P>
        <ol>
        <li ng-repeat = "Country in Countries'  >
```

```
{{ 'Country:' + Country.name + ', Locale:' + Country.
locale }}
    </li>
    </ol>
    </div>

    <script src="https://ajax.googleapis.com/ajax/

libs/angularjs/1.3.14/angular.min.js">

    </script>
    </body>
    </html>
```

Sample

Enter your Name: saurav bhandari

Hello saurav bhandari!

List of Countries with locale:

1. Country: India, Locale: en-India
2. Country: United Kingdom, Locale: en-GB
3. Country: France, Locale: en-FR

```
Ans 2 = const http = require ("http")
         const server = http.createServer ((req, res) => {
            if (req.url == "/")
            res.end ("you are at home page")
            else if (req.url == "/contact")
            res.end ("you are at contacts").
            else
            res.writeHead (404)
            res.end ()
         })
         server.listen (4002, "127.0.0.1", () => {
```

```
PROBLEMS    OUTPUT    DEBUG CONSOLE    TERMINAL


Try the new cross-platform PowerShell https://aka.ms/pscore6

PS C:\Users\FrostBite\Desktop\practical> node ques2.js
Listening to the graphic era server....
```