

IT308: Operating Systems

Exam 1

MCQ 1

For the following two questions, assume that there are 3 page frames, initially empty. Consider the reference string

2 1 4 3 1 2 4 3 2 1

Using the FIFO page replacement algorithm, what is the total number of page faults including compulsory faults, for the given reference string?

- A. 4
- B. 6
- C. 8
- D. 10

Solution

Access order: 2 1 4 3 1 2 4 3 2 1

| Access | Hit/Miss? | Evict | Cache state |
|--------|-----------|-------|--------------------|
| 2 | Miss | | First-in → 2 |
| 1 | Miss | | First-in → 2, 1 |
| 4 | Miss | | First-in → 2, 1, 4 |
| 3 | Miss | 2 | First-in → 1, 4, 3 |
| 1 | Hit | | First-in → 1, 4, 3 |
| 2 | Miss | 1 | First-in → 4, 3, 2 |
| 4 | Hit | | First-in → 4, 3, 2 |
| 3 | Hit | | First-in → 4, 3, 2 |
| 2 | Hit | | First-in → 4, 3, 2 |
| 1 | Miss | 4 | First-in → 3, 2, 1 |

A total of 6 misses

MCQ 2

For the following two questions, assume that there are 3 page frames, initially empty. Consider the reference string

2 1 4 3 1 2 4 3 2 1

Using the LRU page replacement algorithm, what is the total number of page faults including compulsory faults, for the given reference string?

- A. 4
- B. 6
- C. 8
- D. 10

Solution

Access order: 2 1 4 3 1 2 4 3 2 1

| Access | Hit/Miss? | Evict | Cache state |
|--------|-----------|-------|---------------------------|
| 2 | Miss | | LRU \rightarrow 2 |
| 1 | Miss | | LRU \rightarrow 2, 1 |
| 4 | Miss | | LRU \rightarrow 2, 1, 4 |
| 3 | Miss | 2 | LRU \rightarrow 1, 4, 3 |
| 1 | Hit | | LRU \rightarrow 4, 3, 1 |
| 2 | Miss | 4 | LRU \rightarrow 3, 1, 2 |
| 4 | Miss | 3 | LRU \rightarrow 1, 2, 4 |
| 3 | Miss | 1 | LRU \rightarrow 2, 4, 3 |
| 2 | Hit | | LRU \rightarrow 4, 3, 2 |
| 1 | Miss | 4 | LRU \rightarrow 3, 2, 1 |

A total of 8 misses

MCQ 3

| Segment | Base | Bounds |
|---------|------|--------|
| 0 | 200 | 500 |
| 1 | 2000 | 50 |
| 2 | 100 | 90 |
| 3 | 1000 | 900 |

Assuming that the leading digit in a virtual address represents the segment, which one of the following virtual addresses is illegal? All numbers are given in hexadecimal.

- A. 0400
- B. 3100
- C. 3900 $\text{Base} + \text{Offset} \not< \text{Base} + \text{Bounds}$
- D. 2089

MCQ 4

Assume, for the following jobs, a FIFO scheduler. Each job has a required runtime, which means the job needs that many time units on the CPU to complete.

Job A arrives at time = 0, required runtime = X time units

Job B arrives at time = 5, required runtime = Y time units

Job C arrives at time = 10, required runtime = Z time units

Assuming an average turnaround time between 10 and 20 time units (inclusive), which of the following run times for A, B, and C is possible?

A. $A = 20, B = 20, C = 20$

B. $A = 30, B = 1, C = 1$

C. $A = 20, B = 30, C = 40$

D. $A = 22, B = 1, C = 1$

Solution

We want run times for which average turnaround time is between 10 and 20 time units (inclusive).

A. $A = 20, B = 20, C = 20$ (not possible)

$$((20 - 0) + (40 - 5) + (60 - 10))/3 = 35$$

Solution

We want run times for which average turnaround time is between 10 and 20 time units (inclusive).

A. $A = 20, B = 20, C = 20$ (not possible)

$$((20 - 0) + (40 - 5) + (60 - 10))/3 = 35$$

B. $A = 30, B = 1, C = 1$ (not possible)

$$((30 - 0) + (31 - 5) + (32 - 10))/3 = 26$$

Solution

We want run times for which average turnaround time is between 10 and 20 time units (inclusive).

A. $A = 20, B = 20, C = 20$ (not possible)

$$((20 - 0) + (40 - 5) + (60 - 10))/3 = 35$$

B. $A = 30, B = 1, C = 1$ (not possible)

$$((30 - 0) + (31 - 5) + (32 - 10))/3 = 26$$

C. $A = 20, B = 30, C = 40$ (not possible)

$$((20 - 0) + (50 - 5) + (90 - 10))/3 = 48.33$$

Solution

We want run times for which average turnaround time is between 10 and 20 time units (inclusive).

A. $A = 20, B = 20, C = 20$ (not possible)

$$((20 - 0) + (40 - 5) + (60 - 10))/3 = 35$$

B. $A = 30, B = 1, C = 1$ (not possible)

$$((30 - 0) + (31 - 5) + (32 - 10))/3 = 26$$


C. $A = 20, B = 30, C = 40$ (not possible)

$$((20 - 0) + (50 - 5) + (90 - 10))/3 = 48.33$$

D. $A = 22, B = 1, C = 1$ (possible)


$$((22 - 0) + (23 - 5) + (24 - 10))/3 = 18$$

Problem 2



(a) Transition 3: Ready \rightarrow Blocked


Problem 2



(a) Transition 3: Ready \rightarrow Blocked


Not legal. A process cannot execute any statements when still in the ready queue.

Problem 2



(b) Transition 1: Blocked \rightarrow Running

Problem 2



(b) Transition 1: Blocked \rightarrow Running

Not legal. A blocked process must first be placed in the ready queue before it can be selected to run.

Problem 3: (a)

A page fault must be preceded by a TLB miss, but a TLB miss does not necessarily mean a page fault will occur.

Problem 3: (a)

A page fault must be preceded by a TLB miss, but a TLB miss does not necessarily mean a page fault will occur.

True

Problem 3: (b)

With MLFQ scheduling, starvation is possible.

Problem 3: (b)

With MLFQ scheduling, starvation is possible.

False

Problem 3: (c)

The Not Frequently Used (NFU) page replacement algorithm keeps a precise count of the number of times that a page has been referenced.

Problem 3: (c)

The Not Frequently Used (NFU) page replacement algorithm keeps a precise count of the number of times that a page has been referenced.

False

Problem 3: (d)

Given a constant number of bits in a virtual address, the size of a page table decreases with larger pages.

Problem 3: (d)

Given a constant number of bits in a virtual address, the size of a page table decreases with larger pages.

True

Problem 3: (e)

In a virtual memory system, a virtual page and a physical page frame must be the same size.

Problem 3: (e)

In a virtual memory system, a virtual page and a physical page frame must be the same size.

True

Problem 3: (f)

Within a given virtual memory system, pages of varying sizes are used to avoid wasting space within partially-filled pages.

Problem 3: (f)

Within a given virtual memory system, pages of varying sizes are used to avoid wasting space within partially-filled pages.

False

Problem 4

- (a) Under what conditions does FIFO scheduling result in the shortest possible average response time?

Problem 4

- (a) Under what conditions does FIFO scheduling result in the shortest possible average response time?
- if the jobs happen to arrive in the ready queue with the shortest completion times first (or, as a special case, if all jobs have the same completion time).



Problem 4

- (b) Under what conditions does round robin scheduling behave identically to FIFO in terms of turnaround time?

Problem 4

- (b) Under what conditions does round robin scheduling behave identically to FIFO in terms of turnaround time?
if the job lengths are no longer than the length of the time slice.

Problem 5



(a) How many queues do you think there are in this MLFQ scheduler?

(a) How many queues do you think there are in this MLFQ scheduler?

Three queues. You will see three distinct time slices being used: 10 ms, 20 ms, 30 ms

Solution

(a) How many queues do you think there are in this MLFQ scheduler?

Three queues. You will see three distinct time slices being used: 10 ms, 20 ms, 30 ms

(b) How long is the time slice at the top-most (high priority) queue?

Solution

- (a) How many queues do you think there are in this MLFQ scheduler?
Three queues. You will see three distinct time slices being used: 10 ms, 20 ms, 30 ms
- (b) How long is the time slice at the top-most (high priority) queue?
10 ms. (it's the first time slice shown.)

Solution

- (a) How many queues do you think there are in this MLFQ scheduler?
Three queues. You will see three distinct time slices being used: 10 ms, 20 ms, 30 ms
- (b) How long is the time slice at the top-most (high priority) queue?
10 ms. (it's the first time slice shown.)
- (c) How long is the time slice at the bottom-most (low priority) queue?

Solution

- (a) How many queues do you think there are in this MLFQ scheduler?
Three queues. You will see three distinct time slices being used: 10 ms, 20 ms, 30 ms
- (b) How long is the time slice at the top-most (high priority) queue?
10 ms. (it's the first time slice shown.)
- (c) How long is the time slice at the bottom-most (low priority) queue?
30 ms. (it's the longest time slice shown.)