Reading Submission Metadata from Unpublished Manuscripts with Layout Rules

Aarav Sharma
dept. of Computer Science
IIT Delhi
New Delhi, India
aarav.sharma@cse.iitd.ac.in

Meera Iyer
School of Informatics
University of Edinburgh
Edinburgh, UK
m.iyer@ed.ac.uk

Daniel Okafor
Microsoft Research
Microsoft
Redmond, USA
dokafor@microsoft.com

Abstract·This paper presents a system that extracts the title, authors, affiliations and declarations from unpublished manuscripts so that authors do not have to retype them into submission forms.

Index Terms·metadata extraction, document layout, research papers.

I. INTRODUCTION

Large language models are now used to read scientific documents, yet most submission systems still ask authors to type the same metadata by hand. Prior work by Smith et al. [3] studied header parsing with conditional random fields, while Lee and Wong [5] relied on font statistics. We compare layout rules with learned models on manuscripts from many templates and report where each one fails.

Large language models are now used to read scientific documents, yet most submission systems still ask authors to type the same metadata by hand. Prior work by Smith et al. [3] studied header parsing with conditional random fields, while Lee and Wong [5] relied on font statistics. We compare layout rules with learned models on manuscripts from many templates and report where each one fails.

Large language models are now used to read scientific documents, yet most submission systems still ask authors to type the same metadata by hand. Prior work by Smith et al. [3] studied header parsing with conditional random fields, while Lee and Wong [5] relied on font statistics. We compare layout rules with learned models on manuscripts from many templates and report where each one fails.

Large language models are now used to read scientific documents, yet most submission systems still ask authors to type the same metadata by hand. Prior work by Smith et al. [3] studied header parsing with conditional random fields, while Lee and Wong [5] relied on font statistics. We compare layout rules with learned models on manuscripts from many templates and report where each one fails.

Large language models are now used to read scientific documents, yet most submission systems still ask authors to type the same metadata by hand. Prior work by Smith et al. [3] studied header parsing with conditional random fields, while Lee and Wong [5] relied on font statistics. We compare layout rules with learned models on manuscripts from many templates and report where each one fails.

II. METHOD

Large language models are now used to read scientific documents, yet most submission systems still ask authors to type the same metadata by hand. Prior work by Smith et al. [3] studied header parsing with conditional random fields, while Lee and Wong [5] relied on font statistics. We compare layout rules with learned models on manuscripts from many templates and report where each one fails.

Large language models are now used to read scientific documents, yet most submission systems still ask authors to type the same metadata by hand. Prior work by Smith et al. [3] studied header parsing with conditional random fields, while Lee and Wong [5] relied on font statistics. We compare layout rules with learned models on manuscripts from many templates and report where each one fails.

Large language models are now used to read scientific documents, yet most submission systems still ask authors to type the same metadata by hand. Prior work by Smith et al. [3] studied header parsing with conditional random fields, while Lee and Wong [5] relied on font statistics. We compare layout rules with learned models on manuscripts from many templates and report where each one fails.

Large language models are now used to read scientific documents, yet most submission systems still ask authors to type the same metadata by hand. Prior work by Smith et al. [3] studied header parsing with conditional random fields, while Lee and Wong [5] relied on font statistics. We compare layout rules with learned models on manuscripts from many templates and report where each one fails.

Large language models are now used to read scientific documents, yet most submission systems still ask authors to type the same metadata by hand. Prior work by Smith et al. [3] studied header parsing with conditional random fields, while Lee and Wong [5] relied on font statistics. We compare layout rules with learned models on manuscripts from many templates and report where each one fails.

Fig. 1. Pipeline overview.

TABLE I
Results on the test set

ACKNOWLEDGMENT

This work was supported by the Science and Engineering Research Board under Grant No. CRG/2021/004567. We thank Priya Raman for comments.

REFERENCES

[1] J. Smith, K. Lee, and R. Patel, ·On parsing headers,· in Proc. ACL, 2011, pp. 1-10.
[2] J. Smith, K. Lee, and R. Patel, ·On parsing headers,· in Proc. ACL, 2012, pp. 2-11.
[3] J. Smith, K. Lee, and R. Patel, ·On parsing headers,· in Proc. ACL, 2013, pp. 3-12.
[4] J. Smith, K. Lee, and R. Patel, ·On parsing headers,· in Proc. ACL, 2014, pp. 4-13.
[5] J. Smith, K. Lee, and R. Patel, ·On parsing headers,· in Proc. ACL, 2015, pp. 5-14.
[6] J. Smith, K. Lee, and R. Patel, ·On parsing headers,· in Proc. ACL, 2016, pp. 6-15.
[7] J. Smith, K. Lee, and R. Patel, ·On parsing headers,· in Proc. ACL, 2017, pp. 7-16.
[8] J. Smith, K. Lee, and R. Patel, ·On parsing headers,· in Proc. ACL, 2018, pp. 8-17.
[9] J. Smith, K. Lee, and R. Patel, ·On parsing headers,· in Proc. ACL, 2019, pp. 9-18.
[10] J. Smith, K. Lee, and R. Patel, ·On parsing headers,· in Proc. ACL, 2020, pp. 10-19.
[11] J. Smith, K. Lee, and R. Patel, ·On parsing headers,· in Proc. ACL, 2021, pp. 11-20.
[12] J. Smith, K. Lee, and R. Patel, ·On parsing headers,· in Proc. ACL, 2022, pp. 12-21.