



EVALUATED COURSE PROJECT REPORT • FLIPPED COURSE

VoltFleet OS

Autonomous Electric Vehicle Fleet Energy, Range Safety, and Grid Load Balancing Engine

CONTINUOUS ASSESSMENT COMPONENT • FALL SEMESTER 2026 TO 2027

STUDENT NAME

Akshat Sharma

REGISTRATION NUMBER

24BEC10124

COURSE TITLE

Programming in Java

COURSE FACULTY / EVALUATOR

Dr. Vipin Jain

COURSE CODE

CSE2006

PUBLIC REPOSITORY

github.com/AkshatIsWired/voltfleet-os

Submitted in partial fulfillment of the academic requirements for the continuous evaluation of the course CSE2006:
Programming in Java.

DOCUMENT INDEX & TABLE OF CONTENTS

Section	Title and Subsections	Page
1.0	Project Title and Student Metadata Cover Page	1
2.0	Document Index and Table of Contents	2
3.0	Introduction & Project Background	3
4.0	Problem Statement & Engineering Motivation	3
5.0	Functional Requirements Specification 5.1 Module 1: Fleet Modeling and Route Feasibility Engine 5.2 Module 2: Substation Grid Load Balancer 5.3 Module 3: Multithreaded Telematics and Audit Persistence	3
6.0	Non-Functional Requirements Specification	4
7.0	System Architecture & Component Design Figure 7.1: Four-Tier Decoupled Layered Architecture Figure 7.2: Telematics Sensor Ingestion and Hardware Block Diagram	4
8.0	Design, UML Diagrams & System Flowcharts Figure 8.1: Operational Use Case Diagram Figure 8.2: Route Dispatch Validation Flowchart Figure 8.3: Charging Bay Allocation Sequence Diagram Figure 8.4: Vehicle Inheritance and Interface Hierarchy Figure 8.5: Operational State Transition Diagram Figure 8.6: 2D Substation Power Schedule Matrix Figure 8.7: CSV File Serialization Schema	6
9.0	Design Decisions & Technical Rationale	8
10.0	Implementation Details, Formulas & Core Code Listings 10.1 Mathematical Energy Formulations and Interlock Rules 10.2 Worked Numerical Calculation Scenarios 10.3 Concrete Java Source Listings (10.1 to 10.5)	8
11.0	Execution Results & Realistic Terminal Output Logs 11.1 Automated Evaluation Demo Trace 11.2 Interactive Terminal Menu Interface Log	11
12.0	Testing Approach, Verification Matrix & Boundary Analysis 12.1 Unit Test Verification Matrix (TC-01 to TC-06) 12.2 Boundary Value Analysis Table	13
13.0	Practical Engineering Challenges & Technical Solutions	14
14.0	Core Learnings & Academic Takeaways (Syllabus Units 1 to 5)	14
15.0	Future Enhancements & Engineering Roadmap	15
16.0	References & Academic Citations	15

3. INTRODUCTION & PROJECT BACKGROUND

Commercial logistics and municipal transit providers are adding battery electric vehicles to their fleets to lower operational fuel expenses and tailpipe emissions. While electric powertrains operate efficiently, managing commercial electric fleets introduces practical software and operational constraints.

Battery energy consumption is non-linear and sensitive to operating conditions. Unlike fossil fuel vehicles that can be refueled in minutes, electric vehicles require careful energy budgeting. A delivery van or heavy truck energy consumption varies with payload mass, aerodynamic resistance at highway speeds, regenerative braking efficiency during stop-and-go city driving, and auxiliary power drawn by heating and air conditioning systems. An inaccurate range calculation can strand a loaded commercial vehicle on a highway.

Depot facilities also face physical electrical limits. When multiple delivery vans, cargo trucks, and transit shuttles return to a central depot at the end of a shift, concurrent use of fast DC charging terminals (ranging from 50 kW to 150 kW each) creates sharp spikes in electrical demand. If the combined power demand exceeds the depot transformer limit, circuit breakers trip and the utility imposes peak demand penalties.

VoltFleet OS is a Java console application that models electric fleet operations, evaluates pre-dispatch energy requirements, schedules depot charging within fixed electrical transformer limits, and logs telemetry streams. By applying object-oriented design, custom exception hierarchies, multithreaded simulation, and file streams, the application coordinates vehicle assignments and depot power distribution.

4. PROBLEM STATEMENT & MOTIVATION

Operating commercial electric vehicle fleets introduces three practical operational problems:

1. Dispatchers often assign delivery routes assuming constant energy consumption per kilometer. Commercial electric vehicles experience variable battery drain from cargo weight, auxiliary climate control, aerodynamic drag, and regenerative braking recapture. Without dynamic modeling, vehicles risk mid-route stranding.
2. Charging commercial electric vehicles draws substantial electrical power. When multiple vehicles connect to fast chargers concurrently, total power demand can exceed depot substation transformer thresholds. Uncoordinated charging leads to breaker trips, costly demand surcharges, and localized brownouts.
3. Fleet operators require continuous visibility into battery health, vehicle position, and operating temperatures. Manual record-keeping cannot track live telemetry from moving assets. Furthermore, regulatory compliance requires verifiable records calculating carbon dioxide displaced compared to diesel baselines.

The primary objective is to build a modular Java application that calculates category-specific energy consumption for different vehicle types, blocks dispatches that violate safety battery reserves, allocates charging bay power under a 250 kW transformer ceiling, and records operational telemetry.

5. FUNCTIONAL REQUIREMENTS

The system is organized into three core modules:

5.1 Module 1: Fleet modeling and route dispatch

- The engine models delivery vans, heavy cargo trucks, and passenger shuttles, with each class implementing its own energy consumption equations.
- Trip energy calculations occur before route assignment, verifying that battery reserves remain above a 15% state-of-charge threshold. If the projected level drops below 15%, the engine throws a `BatteryDepletionException` and stops dispatch.

- The system tracks operational state transitions across Available, En Route, Queued Charging, Charging, and Maintenance states.

5.2 Module 2: Substation grid load balancer

- The balancer coordinates three hardware charging tiers: standard AC slow (7.4 kW), fast DC (50.0 kW), and ultra-rapid DC (150.0 kW).
- Active charger power draws are tracked continuously. The engine blocks new bay activations if total power would exceed the 250.0 kW transformer rating, throwing a `GridOverloadException`.
- Returning depleted vehicles are enqueued into a `PriorityQueue` ordered by lowest state of charge to prioritize charging access.

5.3 Module 3: Multithreaded telematics and audit persistence

- Background worker threads implementing `Runnable` generate simulated sensor telemetry containing GPS coordinates, speed, temperature, and battery charge.
- Fleet inventory and audit records persist to CSV files using Java `BufferedReader` and `BufferedWriter` streams.
- The reporting layer calculates kilograms of carbon dioxide avoided by comparing electric kilowatt-hours consumed against equivalent diesel fuel baselines.

6. NON-FUNCTIONAL REQUIREMENTS

Quality Attribute	Specification and Architectural Strategy
Performance	Evaluates safety checks and route feasibility in sub-millisecond execution time using <code>LinkedHashMap</code> lookups ($O(1)$).
Input validation	Validates VIN strings using a compiled regular expression (<code>^[A-Z0-9]{8,17}\$</code>) and enforces non-negative inputs for distance and payload.
Reliability and concurrency	Synchronizes charging bay bookings and shared audit records to prevent race conditions during concurrent execution.
Error handling strategy	Uses a checked exception hierarchy containing contextual diagnostic telemetry.
Portability	Runs on standard Java SE with zero third-party JAR dependencies; compiles across platforms using standard <code>javac</code> .
Audit reproducibility	Persists telemetry logs and inventory records to disk in standard CSV formatting for external auditing and verification.

7. SYSTEM ARCHITECTURE

VoltFleet OS follows a four-tier decoupled architecture separating presentation, business services, domain models, and file storage:




Figure 7.1: Four-Tier Layered Architecture of VoltFleet OS

7.1 Telematics and Hardware Integration Architecture

The diagram below illustrates how vehicle sensors communicate operational data to the telematics ingestion service, passing through thread-safe queues to the depot dispatch database and electrical grid controller:






Figure 7.2: System Component and Hardware Telematics Ingestion Block Diagram

8. DESIGN & UML DIAGRAMS


8.1 Use Case Diagram




8.2 System Workflow Diagram (Dispatch and Charging Logic)




8.3 Sequence Diagram: Charging Bay Allocation and Grid Safeguard



8.4 Detailed Class and Inheritance Diagram



8.5 Vehicle Lifecycle State Transition Diagram



8.6 Substation 2D Charging Grid Matrix and Power Distribution Schema

BAY TERMINAL	HARDWARE TIER	RATED DRAW	ACTIVE VEHICLE	POWER DRAW
BAY-AC-01	STANDARD_AC	7.4 kW	IDLE (FREE)	0.0 kW
BAY-DC-01	FAST_DC	50.0 kW	1V1EVSABSTMIE501	50.0 kW
BAY-DC-02	FAST_DC	50.0 kW		50.0 kW
BAY-UR-01	ULTRA_RAPID_DC	150.0 kW	1H1EVFREIGHT901	150.0 kW

Figure 8.6: Multi-Bay Power Matrix and Active Substation Draw (Total: 250.0 kW / 250.0 kW Limit)

8.7 Data Storage Schema (CSV and In-Memory Layout)

FILE PERSISTENCE SCHEMA: data/fleet_inventory.csv					
VIN	Category	Model	Capacity(kWh)	Current(kWh)	Status
1V1EVLASTMIE01	DeliveryVan	Transit-Volt 350	75.0	68.85	AVAILABLE

Figure 8.7: CSV File Serialization Schema and Field Formatting

9. DESIGN DECISIONS & TECHNICAL RATIONALE

- Subclasses (DeliveryVan, HeavyCargoTruck, PassengerShuttle) override calculateRequiredEnergy to apply category-specific aerodynamic and payload equations. Using dynamic method dispatch avoids nested conditional branching on vehicle type strings and allows introducing new vehicle categories without altering existing dispatch routines.
- Physical fleet depots operate under a single shared vehicle inventory and a common transformer connection. A thread-safe Singleton pattern ensures that dispatch operations and charging allocations reference one consistent state across all worker threads.
- The design uses checked exceptions for operational conditions that callers must handle, such as battery reserve violations (BatteryDepletionException) and transformer capacity limits (GridOverloadException). Unchecked exceptions, such as InvalidVINException, handle syntactic validation failures.
- Data structure selection reflects operational access patterns. LinkedHashMap preserves insertion order during audits while providing O(1) lookups by VIN. PriorityQueue sorts waiting vehicles by state of charge so the most depleted vehicles receive priority access to charging bays. Stack preserves recent dispatch actions for operational rollbacks.
- Method-level and block-level monitor synchronization prevents race conditions during concurrent charging bay allocations and telemetry logging.

10. IMPLEMENTATION DETAILS & CORE ALGORITHMS

This section details the mathematical formulations, safety threshold rules, and concrete Java code implementations that govern fleet routing and electrical grid balancing.

10.1 Mathematical Energy Consumption Formulations

EQUATION 10.1: VEHICLE ROUTE ENERGY CONSUMPTION FORMULA

$$\text{Energy}_{\text{Required}} \text{ (kWh)} = \text{Distance} \times [\text{BaseRate} + (\text{Payload} \times C_p)] \times K_{\text{env}}$$

Variable definitions:

- Distance is the total route length in kilometers (km).
- BaseRate is category rolling resistance: 0.21 for delivery vans, 0.85 for semi-trucks, and 0.32 kWh/km for shuttles.
- Payload represents cargo or passenger payload mass in kilograms (kg).
- C_p is the payload consumption penalty coefficient: 0.00008 for vans, 0.00005 for semi-trucks, and 0.00006 kWh/km/kg for shuttles.
- K_{env} is the operational environment factor: 0.88 for urban regenerative braking recapture, 1.15 for highway aerodynamic drag, and 1.08 for passenger HVAC climate draw.

EQUATION 10.2: DISPATCH SAFETY BATTERY RESERVE THRESHOLD

$$\text{Energy}_{\text{Usable}} \text{ (kWh)} = \text{CurrentEnergy} - (0.15 \times \text{BatteryCapacity})$$

If $\text{Energy}_{\text{Required}} > \text{Energy}_{\text{Usable}}$, route dispatch is blocked and a BatteryDepletionException is thrown.

EQUATION 10.3: SUBSTATION TRANSFORMER LOAD BALANCE CONSTRAINT

$$\text{TotalDepotLoad} = \sum \text{PowerDraw}_i \text{ (for all active charging bays } i) \leq 250.0 \text{ kW}$$

If $\text{TotalDepotLoad} + \text{RequestedBayPower} > 250.0 \text{ kW}$, bay allocation is rejected with a `GridOverloadException`.

10.2 Worked Numerical Calculation Examples

Vehicle & Scenario	Input Parameters	Intermediate Step	Calculated Energy	Dispatch Decision
DeliveryVan (Urban Route)	Distance: 45 km, Payload: 350 kg, Current Energy: 68.85 kWh (75 kWh total)	$[0.21 + (350 \times 0.00008)] \times 0.88 = 0.238 \times 0.88 = 0.2094 \text{ kWh/km}$	$45 \times 0.2094 = \mathbf{9.42 \text{ kWh}}$	APPROVED (Usable: 57.6 kWh > 9.42 kWh)
HeavyCargoTruck (Freight)	Distance: 120 km, Payload: 15,000 kg, Current Energy: 265.8 kWh (300 kWh total)	$[0.85 + (15000 \times 0.00005)] \times 1.15 = 1.60 \times 1.15 = 1.84 \text{ kWh/km}$	$120 \times 1.84 = \mathbf{220.80 \text{ kWh}}$	APPROVED (Usable: 220.8 kWh ≥ 220.8 kWh)
DeliveryVan (Depleted SoC)	Distance: 120 km, Payload: 400 kg, Current Energy: 16.35 kWh (75 kWh total, SoC: 21.8%)	$[0.21 + (400 \times 0.00008)] \times 0.88 = 0.242 \times 0.88 = 0.213 \text{ kWh/km}$	$120 \times 0.213 = \mathbf{25.56 \text{ kWh}}$	REJECTED (Usable: 5.1 kWh < 25.56 kWh, throws <code>BatteryDepletionException</code>)

10.3 Concrete Java Source Code Implementations

Below are selected source code implementations illustrating core OOP principles, custom exceptions, multithreading, and stream file I/O:

```
// Listing 10.1: Polymorphic Consumption in DeliveryVan.java
package com.voltfleet.model;

public class DeliveryVan extends Vehicle {
    private static final double BASE_RATE = 0.21;
    private static final double PAYLOAD_PENALTY = 0.00008;
    private static final double REGEN_FACTOR = 0.88; // Urban stop-and-go regenerative recapture

    public DeliveryVan(String vin, String modelName, double batteryCapacityKWh, double currentChargeKWh) {
        super(vin, modelName, batteryCapacityKWh, currentChargeKWh);
    }

    @Override
    public double calculateRequiredEnergy(double distanceKm, double payloadKg) {
        double consumptionPerKm = (BASE_RATE + (payloadKg * PAYLOAD_PENALTY)) * REGEN_FACTOR;
        return distanceKm * consumptionPerKm;
    }
}
```

Listing 10.1: Dynamic method dispatch in `DeliveryVan.java`

```
// Listing 10.2: Dispatch Safety Interlock & Custom Exception in Vehicle.java
package com.voltfleet.model;
import com.voltfleet.exception.BatteryDepletionException;

public abstract class Vehicle {
    protected double batteryCapacityKWh;
    protected double currentChargeKWh;

    public void validateDispatchSafety(double requiredEnergy)
        throws BatteryDepletionException {
        double minReserveThreshold = this.batteryCapacityKWh * 0.15; // Mandatory 15% safety buffer
        double usableEnergy = this.currentChargeKWh - minReserveThreshold;

        if (requiredEnergy > usableEnergy) {
            throw new BatteryDepletionException(
                this.vin,
                this.getStateOfCharge(),
                requiredEnergy,
                usableEnergy
            );
        }
    }
}
```

Listing 10.2: Safety verification logic throwing checked BatteryDepletionException

```
// Listing 10.3: Synchronized Power Allocation in GridLoadBalancer.java
package com.voltfleet.service;
import com.voltfleet.exception.GridOverloadException;
import com.voltfleet.model.ChargingBay;
import com.voltfleet.model.Vehicle;

public class GridLoadBalancer {
    private final double maxGridCapacityKW = 250.0;
    private double currentGridLoadKW = 0.0;

    public synchronized void allocateChargingBay(
        ChargingBay bay, Vehicle vehicle) throws GridOverloadException {
        double bayPower = bay.getChargingTier().getPowerKW();
        if (this.currentGridLoadKW + bayPower > this.maxGridCapacityKW) {
            throw new GridOverloadException(
                bay.getBayId(), bayPower, this.currentGridLoadKW, this.maxGridCapacityKW);
        }
        bay.connectVehicle(vehicle);
        this.currentGridLoadKW += bayPower;
    }
}
```

Listing 10.3: Synchronized monitor enforcement of 250 kW transformer ceiling

```
// Listing 10.4: Multithreaded Sensor Streaming in TelematicsSimulator.java
package com.voltfleet.service;
import com.voltfleet.model.TelematicsRecord;

public class TelematicsSimulator implements Runnable {
    private final String vin;
    private final int pingCount;
    private volatile boolean running = true;

    @Override
    public void run() {
        for (int i = 0; i < pingCount && running; i++) {
            double speed = 40.0 + (Math.random() * 30.0);
            double temp = 28.0 + (Math.random() * 4.0);
            TelematicsRecord record = new TelematicsRecord(vin, speed, temp, 23.078, 76.851);
            DepotManager.getInstance().logTelematics(record);
            try {
                Thread.sleep(60);
            } catch (InterruptedException e) {
                Thread.currentThread().interrupt();
                break;
            }
        }
    }
}
```

Listing 10.4: Multithreaded sensor packet generation implementing Runnable

```
// Listing 10.5: Stream File I/O Persistence in FilePersistenceManager.java
package com.voltfleet.storage;
import java.io.*;
import java.util.*;
import com.voltfleet.model.Vehicle;

public class FilePersistenceManager {
    public static void exportFleetToCsv(Collection<Vehicle> fleet, String filePath) throws IOException {
        File file = new File(filePath);
        if (file.getParentFile() != null) file.getParentFile().mkdirs();

        try (BufferedWriter writer = new BufferedWriter(new FileWriter(file))) {
            writer.write("VIN,Category,Model,Capacity_kWh,Current_kWh,Status");
            writer.newLine();
            for (Vehicle v : fleet) {
                writer.write(String.format("%s,%s,%s,%.2f,%.2f,%s",
                    v.getVin(), v.getClass().getSimpleName(), v.getModelName(),
                    v.getBatteryCapacityKWh(), v.getCurrentChargeKWh(), v.getStatus()));
                writer.newLine();
            }
        }
    }
}
```

Listing 10.5: Safe CSV stream persistence using try-with-resources

11. EXECUTION RESULTS & TERMINAL LOGS

Below are the verified command-line execution traces captured from running the automated evaluation suite and interactive terminal console:

11.1 Automated Demo Suite Output Trace

```
PS C:/Users/Apple/Documents/.../repo> java -cp bin com.voltfleet.cli.VoltFleetApp --demo

===== FLEET AUDIT SUMMARY =====
VIN: 1V1EVLASTMILE01 | Category: Last-Mile Van | Model: Transit-Volt 350 | SoC: 91.8% | Odo: 0.0 km |
Carbon Offset: 0.0 kg CO2 | Status: AVAILABLE
VIN: 1V1EVLASTMILE02 | Category: Last-Mile Van | Model: Transit-Volt 350 | SoC: 21.8% | Odo: 0.0 km |
Carbon Offset: 0.0 kg CO2 | Status: AVAILABLE
VIN: 1H1EVFREIGHT901 | Category: Heavy Cargo Semi | Model: VoltHauler Semi | SoC: 88.6% | Odo: 0.0 km |
Carbon Offset: 0.0 kg CO2 | Status: AVAILABLE
VIN: 1P1EVSHUTTLE501 | Category: Transit Shuttle | Model: MetroE-Shuttle 20 | SoC: 86.4% | Odo: 0.0 km |
Carbon Offset: 0.0 kg CO2 | Status: AVAILABLE
-----
Total Fleet Vehicles : 4
Depot Fleet Energy : 501.50 / 630.00 kWh (Avg SoC: 79.6%)
Total Clean CO2 Saved: 0.00 kg CO2
=====

--- [TEST 2] ROUTE DISPATCH (NORMAL BOUNDARY CHECK) ---
Dispatching [1V1EVLASTMILE01] on Route RT-URBAN-12 (Distance: 45 km, Payload: 350 kg)...
Result: DISPATCH APPROVED. Vehicle status changed to EN_ROUTE.

--- [TEST 3] DISPATCH INTERVENTION: BATTERY DEPLETION EXCEPTION ---
Attempting to dispatch Low-Battery Vehicle [1V1EVLASTMILE02] on 120 km High-Payload Route...
SUCCESS: BatteryDepletionException caught and handled gracefully!
-> Diagnostic: Battery Depletion Hazard for VIN [1V1EVLASTMILE02]: Required 25.03 kWh, but only 5.75 kWh
available (Current SoC: 21.8%). Cannot safely dispatch.
-> Enqueueing depleted vehicle into smart charging queue...

--- [TEST 4] GRID POWER ALLOCATION & OVERLOAD CEILING ---
===== DEPOT CHARGING TERMINALS =====
Bay [BAY-AC-01] | STANDARD_AC | 7.4 kW | Status: FREE
Bay [BAY-AC-02] | STANDARD_AC | 7.4 kW | Status: FREE
Bay [BAY-DC-01] | FAST_DC | 50.0 kW | Status: FREE
Bay [BAY-DC-02] | FAST_DC | 50.0 kW | Status: FREE
Bay [BAY-UR-01] | ULTRA_RAPID_DC | 150.0 kW | Status: FREE
-----
Depot Electrical Grid Load: 0.0 kW / 250.0 kW (Utilization: 0.0%)
=====
Allocated BAY-UR-01 (150 kW) -> Load: 150.0 kW
Allocated BAY-DC-01 (50 kW) -> Load: 200.0 kW
Allocated BAY-DC-02 (50 kW) -> Total Load: 250.0 kW (Capacity reached: 100%)

--- [TEST 5] MULTITHREADED TELEMATICS LIVE SENSOR INGESTION ---
[SENSOR STREAM] [2026-09-17 14:19:15] VIN: 1V1EVLASTMILE01 | Speed: 67.8 km/h | SoC: 91.8% | Temp: 29.7°C |
Pos: (23.0787, 76.8507)
[SENSOR STREAM] [2026-09-17 14:19:15] VIN: 1V1EVLASTMILE01 | Speed: 57.9 km/h | SoC: 91.8% | Temp: 29.1°C |
Pos: (23.0786, 76.8530)
[SENSOR STREAM] [2026-09-17 14:19:15] VIN: 1V1EVLASTMILE01 | Speed: 47.7 km/h | SoC: 91.8% | Temp: 30.5°C |
Pos: (23.0764, 76.8527)

--- [TEST 6] PERSISTENCE ENGINE: CSV EXPORT & AUDIT JOURNAL ---
SUCCESS: Fleet inventory exported to data/fleet_inventory.csv (4 records written).
Checking data directory: data/fleet_inventory.csv (Exists: true)
```

11.2 Interactive Terminal Menu Interface

```
PS C:/Users/Apple/Documents/.../repo> java -cp bin com.voltfleet.cli.VoltFleetApp

=====
                VOLT FLEET OS - MAIN MENU
=====
[1] View Complete Fleet Status & Carbon Audit Report
[2] Dispatch Vehicle on Delivery Route (Battery Check)
[3] Return Vehicle & Log Route Completion
[4] Inspect Depot Charging Bays & Active Grid Load
[5] Connect Vehicle to Charging Bay (Grid Overload Protection)
[6] Run Background Multithreaded Telematics Sensor Simulator
[7] Export Fleet Inventory to CSV & View Persistence Log
[8] Run Comprehensive Automated End-to-End System Demo
[9] Exit System
=====
Select an option (1-9): 1

[FLEET INVENTORY RETRIEVED VIA LINKEDHASHMAP - 4 REGISTERED ASSETS]
VIN: 1V1EVLASTMILE01 (Van)   | SoC: 91.8% | Usable: 57.60 kWh | Status: AVAILABLE
VIN: 1V1EVLASTMILE02 (Van)   | SoC: 21.8% | Usable:  5.10 kWh | Status: QUEUED_CHARGING
VIN: 1H1EVFREIGHT901 (Semi)  | SoC: 88.6% | Usable: 220.8 kWh | Status: AVAILABLE
VIN: 1P1EVSHUTTLE501 (Shuttle)| SoC: 86.4% | Usable: 57.12 kWh | Status: AVAILABLE
```

12. TESTING APPROACH & VERIFICATION MATRIX

Testing was carried out using a native test suite (VoltFleetTestSuite.java) executing Java assertions (-ea). This verified operational safety interlocks, dynamic dispatch calculations, grid overload protection, and stream persistence without requiring external testing frameworks.

Test ID	Module / Function Under Test	Test Vector and Precondition	Expected Outcome	Actual Outcome	Status
TC-01	VIN Regex Validator	Invalid string: "1V1EVINVALID#@"	Throws InvalidVINException	Exception intercepted with diagnostics	PASSED
TC-02	Polymorphic Energy Rate	100 km, 500 kg payload (Van vs. Truck)	Heavy Semi consumption > Delivery Van	Semi: 97.75 kWh > Van: 21.12 kWh	PASSED
TC-03	Range Depletion Interlock	16% SoC vehicle dispatched on 150 km route	Throws BatteryDepletionException	Dispatch halted; vehicle enqueued to charger	PASSED
TC-04	Grid Overload Interlock	Depot load at 250 kW; attempt new 50 kW bay	Throws GridOverloadException	Bay allocation blocked; transformer protected	PASSED
TC-05	Telematics Threading	Spawn worker for 4 sensor pings @ 60ms	Worker executes concurrently; joins cleanly	4 telemetry records committed to log	PASSED
TC-06	CSV Persistence Stream	Export 4 vehicles to CSV and parse back	Data fields and VINs match exactly	100% record field fidelity verified	PASSED

12.1 Boundary Value Analysis Table

Boundary Parameter	Minimum / Edge Value	Nominal Value	Maximum / Breach Value	Observed System Behavior
Route Distance	0.0 km	45.0 km	1,200.0 km	0 km calculates 0 kWh; 1,200 km correctly triggers battery depletion interlock
Cargo Payload	0.0 kg	350.0 kg	25,000.0 kg	Zero payload applies BaseRate unladen; 25,000 kg applies maximum mass penalty
State of Charge (SoC)	15.0% (Exact Reserve)	75.0%	100.0%	Vehicles at or below 15.0% cannot be dispatched; prioritized in charging queue
Depot Transformer Load	0.0 kW	150.0 kW	250.0 kW (Ceiling)	New allocations blocked when cumulative active bay draw reaches 250.0 kW

13. PRACTICAL CHALLENGES FACED & SOLUTIONS

During implementation, four technical hurdles required structured resolution. First, when simulated vehicles completed routes simultaneously, concurrent worker threads attempted to claim the same DC charging bay; adding synchronized monitor locks on ChargingBay instances and making allocation checks atomic within GridLoadBalancer.allocateChargingBay() resolved the race condition. Second, the initial VIN regular expression followed the strict ISO 3779 standard, forbidding letters I, O, and Q; broadening the pattern to `^[A-Z0-9]{8,17}$` accommodated unit test identifiers while maintaining alphanumeric validation.

Third, standard JUnit testing requires build tool wrappers such as Maven or Gradle, which introduces environment dependency risks during automated assessment; writing a standalone test suite in VoltFleetTestSuite.java using native Java assertions (-ea) kept the build portable across JDK installations. Fourth, writing persistent fleet CSV files and telemetry logs concurrently risked handle leakage during abnormal exits, which was resolved by wrapping all FileOutputStream and BufferedWriter operations in try-with-resources blocks.

14. CORE LEARNINGS & ACADEMIC TAKEAWAYS

The development of VoltFleet OS reinforced core syllabus topics across Units 1 through 5 of the Programming in Java curriculum:

- Unit 1 covers control flow and primitive data handling through interactive menu navigation loops, double-precision energy calculations, and formatted console diagnostics.
- Unit 2 principles appear in the vehicle class hierarchy, parameterized constructors invoking super, access encapsulation, and runtime dynamic method dispatch.
- Unit 3 concepts are realized through abstract methods in Vehicle.java and decoupled interface contracts (Dispatchable, EnergyChargeable, Auditable).
- Unit 4 techniques govern error recovery through a checked exception hierarchy rooted in VoltFleetException, alongside asynchronous sensor telemetry managed via the Runnable interface.
- Unit 5 collection and I/O structures manage depot state, including 2D arrays for shift schedules, LinkedHashMap for O(1) VIN indexing, a PriorityQueue for battery recharging priority, and BufferedReader and BufferedWriter streams for audit persistence.

15. FUTURE ENHANCEMENTS

- Adding rate-aware scheduling could defer vehicle charging until off-peak nighttime tariffs take effect.
- Tracking internal resistance and capacity fade over cumulative charge cycles would improve multi-year maintenance forecasts.
- Connecting the simulated pipeline to physical microcontrollers (such as ESP32 boards) would enable streaming real-world CAN-bus telemetry over cellular connections.

16. REFERENCES & ACADEMIC CITATIONS

1. Bloch, J. (2018). *Effective Java (3rd Edition)*. Addison-Wesley Professional.
2. Schildt, H. (2021). *Java: The Complete Reference (12th Edition)*. McGraw-Hill Education.
3. IEEE Standards Association. (2022). *IEEE 2030.1.1-2022: Standard for Technical Specifications of Electric Vehicle Fast Chargers*. IEEE.
4. Pelletier, S., Jabali, O., & Laporte, G. (2016). 50 Years of Vehicle Routing: Goods Transport by Electric Commercial Vehicles. *Transportation Research Part B: Methodological*, 88, 1-15.
5. Oracle Corporation. (2024). *Java Platform, Standard Edition Documentation (Java SE 17 & 21)*. Oracle Technology Network.