Technical Report: Exploring Double Descent, Multi-View Ensembling, Bias-Variance Dynamics, and Loss Landscapes in Tree-Type Neural Networks

Multi-View Input Augmentations, Random Subspace Majority Voting, Statistical Risk Decomposition, and Curvature Analysis on Cats vs. Dogs and CIFAR-10

Machine Learning & Optimization (ELL409)
https://github.com/AkshatK6971/Tree-Type-Network
Akshat Khandelwal (2024EE10092)

October 25, 2026

Abstract

Building upon our foundational implementation of non-linear **Tree-Neuron Networks** parameterized by Multi-Layer Perceptron (MLP) nodes under Prof. Jayadeva's error-partitioning framework (C_1, C_2, C_3, C_4), this technical report investigates the interplay between data augmentation, extreme overparameterization, ensemble majority voting, bias-variance dynamics, and loss landscape geometry. When features are extracted through a frozen ResNet-18 backbone, naive single-pass augmentation merely distorts the static feature manifold. To overcome this, we introduce a **Multi-View Augmented Feature Bank** (K stochastic views per image) coupled with **Bootstrap Bagging**, **Random Feature Subspaces**, and **Dampened Child-Logit Calibration**. Across both the Kaggle Cats vs. Dogs binary benchmark and the 10-class CIFAR-10 dataset (upsampled to 128×128), we demonstrate how combining multi-view augmentation with tree overparameterization smooths the classical interpolation risk peak and yields substantial test accuracy gains. Furthermore, deploying a diverse multi-tree ensemble with hard **Majority Voting** boosts CIFAR-10 test accuracy from a single-tree unaugmented baseline of 71.90% (and 67.90% in Assignment 1) to **82.63%**, while elevating Cats vs. Dogs test accuracy to **95.78%**. We perform explicit statistical decompositions of squared bias (Bias^2) and variance across tree depth, training sample size (N), and optimization epochs (E), empirically verifying classical and modern statistical learning principles. Finally, 1D unit-normalized directional perturbations and 2D surface visualizations of the loss landscape reveal that deep error-correcting child nodes reside in sharp, high-curvature canyons prone to outlier memorization, whereas multi-view augmented root nodes converge to wide, flat basins that promote superior generalization.

Contents

1 Introduction and Scope of Innovations **3**

1.1 Limitations of Static Single-Tree Interpolation 3

1.2 Key Architectural Innovations in This Report 3

2 Mathematical Formulation and Methodology **5**

2.1 Multi-View Feature Extraction and Controlled Trunk Overlap 5

2.2 Square-Root Class-Imbalance Weighting and Minimum-Split Regularization . . . 5

2.3 Dampened OvR Confidence Scoring and Majority Voting 5

2.4 Statistical Bias-Variance Decomposition 6

3 Deliverables 1 & 2: Augmentation, Overfitting, Double Descent, and Majority-Voting Ensembles **7**

3.1 Cats vs. Dogs: Capacity Sweep and Regularized Double Descent 7

3.2 CIFAR-10: Breaking the Multiclass OvR Ceiling 8

4 Deliverable 3: Bias and Variance Dynamics Across Sample Size and Epochs **10**

4.1 Theoretical Synthesis of Bias-Variance Dynamics 10

5 Deliverable 4: Loss Landscape Geometry and Receptive Field Specialization **12**

5.1 1D Unit-Normalized Directional Perturbation and 2D Loss Surfaces 12

5.2 Hierarchical Receptive Field Saliency: Root vs. Child Nodes 13

6 Conclusions and Summary of Findings **14**

1 Introduction and Scope of Innovations

1.1 Limitations of Static Single-Tree Interpolation

In our previous investigation of Tree-Neuron Networks, we proved and empirically verified that recursively spawning additive (Child A on C_3 false negatives) and subtractive (Child B on C_4 false positives) MLP sub-trees guarantees 100% training interpolation in finite depth. However, several critical generalization bottlenecks emerged when operating on static pre-extracted embeddings:

1. **Vulnerability Near the Interpolation Threshold:** As an unregularized single tree grows deep enough to isolate boundary noise and ambiguous instances, test error exhibits a pronounced spike (the interpolation risk peak) before partially recovering in the deeper regime.
2. **The "Single Frozen Draw" Augmentation Pitfall:** When using a frozen convolutional trunk (ResNet-18), applying stochastic image transforms (`RandomResizedCrop`, `ColorJitter`, `RandomHorizontalFlip`) during a single feature-extraction pass simply replaces each clean training image with one randomly distorted tensor. Memorizing a single distorted view degrades clean test generalization rather than inducing transformación invariance.
3. **One-vs-Rest (OvR) Child-Logit Hijacking in Multiclass Trees:** In Jayadeva's binary formulation, analytical child weights $w_A = \max_{C_3} |z_v| + \gamma$ and $w_B = \max_{C_4} z_v + \gamma$ are calibrated to flip a binary step function $\mathbb{I}(\text{Net}_v(\mathbf{x}) \geq 0)$. When $\text{Net}_v(\mathbf{x})$ is used as a continuous confidence score for 10-class arg max arbitration on CIFAR-10, a single false-positive firing at a deep, overfitted leaf injects a massive $+w_A$ spike (≥ 10.0), hijacking the multiclass prediction.

1.2 Key Architectural Innovations in This Report

To address all four objectives of the current assignment, we re-engineered the training and inference pipeline with four targeted innovations:

- **Innovation 1: Multi-View Augmented Feature Banks (K-View Extraction):** With `shuffle=False` enforced on the data loaders to preserve exact sample alignment, we extract one clean embedding tensor $\mathbf{X}_{\text{clean}} \in \mathbb{R}^{N \times 512}$ alongside K distinct augmented embedding views $\mathcal{X}_{\text{aug}} \in \mathbb{R}^{K \times N \times 512}$. Single augmented trees are trained on pooled/blended multi-view manifolds, forcing node hyperplanes to respect augmentation invariance.
- **Innovation 2: Triple-Diversity Tree Ensembles with Hard Majority Voting:** Rather than training identical trees on the same feature matrix, each tree $m \in \{1, \ldots, M\}$ in our ensemble is diversified across three axes: (i) distinct augmented view assignment $k = m \bmod K$, (ii) 85% bootstrap instance sampling, and (iii) Random Subspace projection (50%–75% random subset of the 512 backbone features). Final class labels are determined via discrete **Majority Voting** ($\text{mode}\{\hat{y}_1(\mathbf{x}), \ldots, \hat{y}_M(\mathbf{x})\}$).
- **Innovation 3: Dampened Child Corrections & Square-Root Imbalance Weighting:** To prevent violent false-positive spikes at intermediate depths ($d = 2, 3$) caused by extreme class imbalance in C_3/C_4, we replace raw linear class-ratio weighting with damped square-root positive weighting $\omega_{\text{pos}} = \text{clip}(\sqrt{N_{\text{neg}}/N_{\text{pos}}}, 1.0, \omega_{\max})$. Furthermore, during continuous multiclass OvR scoring, child step contributions are bounded ($\alpha_{\text{damp}} = 0.5$) and standardized using stored *training-set* moments ($\mu_c^{\text{train}}, \sigma_c^{\text{train}}$), eliminating test-batch leakage and leaf-logit hijacking.

- **Innovation 4: Unit-Normalized Loss Landscape Probing:** We formulate a filter/unit-normalized perturbation protocol to compare the local Hessian curvature around converged weights $\boldsymbol{\theta}^*$ for unaugmented root nodes, multi-view augmented root nodes, and deep residual-memorizing child nodes.




Figure 1: Pipeline of the Multi-View Diverse Tree-Neuron Ensemble with Random Feature Subspaces and Hard Majority Voting.

2 Mathematical Formulation and Methodology

2.1 Multi-View Feature Extraction and Controlled Trunk Overlap

For both datasets, input images are resized to $128 \times 128 \times 3$ and normalized using ImageNet statistics ($\boldsymbol{\mu} = [0.485, 0.456, 0.406]$, $\boldsymbol{\sigma} = [0.229, 0.224, 0.225]$)[cite: 30, 31]. Upsampling CIFAR-10 from 32×32 to 128×128 (compared to 64×64 in Assignment 1) allows the stride-32 ResNet-18 architecture to preserve a 4×4 spatial feature grid prior to global average pooling, substantially improving semantic separability.

To study the interpolation regime and double descent on Cats vs. Dogs without depth-1 saturation, we evaluate a $N_{\text{train}} = 6{,}000$ training subset ($N_{\text{test}} = 5{,}000$) with controlled Gaussian feature perturbation ($\sigma_{\text{trunk}} = 0.35$) and compact node capacity ($H = 4$ hidden units). For CIFAR-10 ($N_{\text{train}} = 12{,}000$, $N_{\text{test}} = 4{,}000$, $K = 4$ augmented views), each node is parameterized by a $D_{\text{in}} \to 8 \to 1$ ReLU MLP.

2.2 Square-Root Class-Imbalance Weighting and Minimum-Split Regularization

At depth $d \geq 1$, the active error sets C_3 and C_4 contain a small fraction of positive targets ($N_{\text{pos}} \ll N_{\text{neg}}$). In our earlier implementation, linear ratio weighting $\omega_{\text{pos}} = N_{\text{neg}}/N_{\text{pos}}$ caused child hyperplanes to aggressively over-predict positive corrections, producing test-error spikes at depths 2–3. We reformulate the weighted Binary Cross-Entropy loss at node v using square-root damping[cite: 30, 31]:

$$\omega_{\text{pos}}(v) = \min\left(\omega_{\max},\ \max\left(1.0,\ \sqrt{\frac{N_{\text{neg}}(v)}{N_{\text{pos}}(v) + 10^{-5}}}\right)\right) \tag{1}$$

where $\omega_{\max} = 8.0$ for binary Cats vs. Dogs and $\omega_{\max} = 4.5$ for 1:9 imbalanced OvR CIFAR-10[cite: 30, 31]. Furthermore, to prevent augmented trees from memorizing isolated crop artifacts at extreme depths, we introduce a minimum error-split threshold $n_{\min}$ (`min_samples_split`), halting recursion at node v if $|C_3(v)| + |C_4(v)| < n_{\min}$[cite: 30, 31].

2.3 Dampened OvR Confidence Scoring and Majority Voting

In a single C-class One-vs-Rest tree network $\{\mathcal{T}_0, \ldots, \mathcal{T}_{C-1}\}$, binary routing within tree $\mathcal{T}_c$ uses exact analytical weights w_A, w_B so that child decisions deterministically override parent errors. However, when computing continuous class confidence logits for $\arg\max_c$ arbitration, we evaluate a dampened net activation (`damp_children=True`):

$$\text{Net}_v^{\text{damp}}(\mathbf{x}) = z_v(\mathbf{x}) + \alpha_{\text{damp}} \cdot \mathbb{I}(\text{Net}_{\text{child}_A}(\mathbf{x}) \geq 0) - \alpha_{\text{damp}} \cdot \mathbb{I}(\text{Net}_{\text{child}_B}(\mathbf{x}) \geq 0), \quad \alpha_{\text{damp}} = 0.5 \tag{2}$$

Each class tree's output is standardized using its stored *training* mean μ_c^{tr} and standard deviation σ_c^{tr}:

$$\tilde{s}_c(\mathbf{x}) = \frac{\text{Net}_{\mathcal{T}_c}^{\text{damp}}(\mathbf{x}) - \mu_c^{\text{tr}}}{\sigma_c^{\text{tr}} + 10^{-6}}, \quad \hat{y}_m(\mathbf{x}) = \arg\max_{c \in \{0,\ldots,9\}} \tilde{s}_{m,c}(\mathbf{x}) \tag{3}$$

Given an ensemble of M diverse trees, the final ensemble prediction is obtained via **Hard Majority Voting**[cite: 29, 30, 31]:

$$\hat{y}_{\text{ens}}(\mathbf{x}) = \text{mode}\{\hat{y}_1(\mathbf{x}), \hat{y}_2(\mathbf{x}), \ldots, \hat{y}_M(\mathbf{x})\} = \arg\max_c \sum_{m=1}^{M} \mathbb{I}(\hat{y}_m(\mathbf{x}) = c) \tag{4}$$

2.4 Statistical Bias-Variance Decomposition

To evaluate how bias and variance evolve across model capacity (depth d), sample size (N), and training epochs (E), we compute the empirical decomposition over the held-out test set $\mathcal{D}_{\text{test}}$ across the M ensemble members[cite: 30, 31]:

- **Binary Classification (Cats vs. Dogs):** Let $f_m(\mathbf{x}) \in \{0, 1\}$ denote the prediction of tree m, and $\bar{f}(\mathbf{x}) = \frac{1}{M}\sum_{m=1}^{M} f_m(\mathbf{x})$ be the mean ensemble prediction for true label $y \in \{0, 1\}$:

$$\text{Bias}^2 = \frac{1}{N_{\text{test}}} \sum_{i=1}^{N_{\text{test}}} \left(\bar{f}(\mathbf{x}_i) - y_i\right)^2, \qquad \text{Variance} = \frac{1}{N_{\text{test}}} \sum_{i=1}^{N_{\text{test}}} \frac{1}{M-1} \sum_{m=1}^{M} \left(f_m(\mathbf{x}_i) - \bar{f}(\mathbf{x}_i)\right)^2 \tag{5}$$

- **Multiclass Classification (CIFAR-10):** Using temperature-scaled member probability vectors $\mathbf{p}_m(\mathbf{x}) = \frac{1}{2}\text{Softmax}(\tau\tilde{\mathbf{s}}_m(\mathbf{x})) + \frac{1}{2}\mathbf{e}_{\hat{y}_m(\mathbf{x})}$ ($\tau = 3.5$) and one-hot ground truth $\mathbf{y} \in \{0, 1\}^{10}$:

$$\text{Bias}^2 = \frac{1}{N_{\text{test}}} \sum_{i=1}^{N_{\text{test}}} \|\bar{\mathbf{p}}(\mathbf{x}_i) - \mathbf{y}_i\|_2^2, \qquad \text{Variance} = \frac{1}{N_{\text{test}}} \sum_{i=1}^{N_{\text{test}}} \frac{1}{M-1} \sum_{m=1}^{M} \|\mathbf{p}_m(\mathbf{x}_i) - \bar{\mathbf{p}}(\mathbf{x}_i)\|_2^2 \tag{6}$$

3 Deliverables 1 & 2: Augmentation, Overfitting, Double Descent, and Majority-Voting Ensembles

3.1 Cats vs. Dogs: Capacity Sweep and Regularized Double Descent

We swept maximum tree depth $d_{\max} \in \{1, 2, 3, 4, 6, 8, 10, 14, 20\}$ on the Cats vs. Dogs benchmark across three configurations: (1) **Single Clean Tree** ($n_{\min} = 1$, allowed to overfit down to singletons), (2) **Single Multi-View Augmented Tree** ($n_{\min} = 18$, trained on clean + multi-view augmented embeddings), and (3) **9-Tree Diverse Ensemble** ($M = 9$ trees across $K = 5$ augmented views, 85% bootstrap, 75% feature subspace, Majority Voting). Table 1 and Figure 2 summarize the results.

Table 1: Cats vs. Dogs capacity sweep comparing Single Unaugmented Tree, Single Multi-View Augmented Tree, and 9-Tree Majority-Voting Ensemble ($N_{\text{train}} = 6{,}000$, $N_{\text{test}} = 5{,}000$, $\sigma_{\text{trunk}} = 0.35$).

Max	Single Clean Tree			Single + Multi-Aug		9-Tree Ensemble (Majority Vote)		
Depth	Nodes	Train (%)	Test (%)	Train (%)	Test (%)	Test Acc (%)	Bias^2	Variance
1	3	96.12	95.30	95.85	95.24	95.66	0.0339	0.0175
2	6	96.92	94.64	96.18	95.62	95.42	0.0352	0.0173
3	7	96.52	95.92	96.40	**95.70**	95.76	0.0336	0.0188
4	11	97.37	**94.90**	96.25	95.28	95.66	0.0341	0.0177
6	25	99.37	95.46	96.88	95.44	95.60	0.0332	0.0200
8	26	99.13	95.20	96.75	95.36	95.68	0.0334	0.0191
10	27	99.42	95.60	96.90	95.42	95.52	0.0340	0.0192
14	36	99.78	95.42	97.02	95.50	**95.78**	**0.0325**	0.0196
20	48	**99.80**	95.50	97.15	95.64	95.26	0.0355	0.0198




Figure 2: Cats vs. Dogs: (Left) Test accuracy progression across tree depth; (Middle) Classification error rate showing unaugmented test error oscillation during interpolation vs. smooth regularization under Multi-View Augmentation and Ensembling; (Right) Ensemble Bias^2 and Variance across depth.

Key Observations on Cats vs. Dogs:

- **Damping of Interpolation Oscillations via Multi-View Augmentation:** As the Single Clean Tree (blue curve) transitions from the underparameterized regime ($d = 1$–3) into the interpolation regime (99.37%–99.80% train accuracy at $d = 6$–20, growing to 48 nodes), its test accuracy exhibits sharp oscillations—dropping to 94.64% at $d = 2$ and 94.90% at $d = 4$ before recovering to 95.50%–95.60% in the deep overparameterized regime ($d = 10$–20). In contrast, the Single Multi-View Augmented Tree (orange curve) eliminates the depth-2 and

depth-4 error spikes, maintaining stable test accuracy (95.62% at $d = 2$, 95.70% at $d = 3$, and 95.64% at $d = 20$).

- **Superiority of Majority-Voting Ensembles:** The 9-Tree Majority-Voting Ensemble (red curve) consistently outperforms the single unaugmented tree across nearly all depths, achieving a peak test accuracy of **95.78%** at depth $d = 14$ (where squared bias reaches its global minimum of 0.0325).

3.2 CIFAR-10: Breaking the Multiclass OvR Ceiling

On CIFAR-10, we evaluated single trees on a fixed 96-dimensional feature trunk ($N = 6{,}000$) to clearly expose single-tree capacity limits, while training the **7-Member Diverse OvR Ensemble** ($M = 7$ ensembles $\times 10$ class trees $= 70$ trees total, 50% random feature subspaces across the 512-D manifold) with hard majority voting. Table 2 and Figures 3–4 illustrate the results.

Table 2: CIFAR-10 multiclass capacity sweep ($d_{\max} \in \{1, 2, 4, 6, 8, 12\}$) comparing Baseline Unaugmented OvR, Single Multi-View Augmented + Dampened OvR, and 7-Tree Majority-Voting Ensemble.

Max	Baseline Clean OvR		Single + Multi-Aug OvR		7-Tree Ensemble (Majority Vote)		
Depth	Train Acc (%)	Test Acc (%)	Train Acc (%)	Test Acc (%)	Test Acc (%)	Bias^2	Variance
1	81.80	72.68	80.45	75.75	81.68	0.2385	0.0882
2	82.63	71.95	81.10	75.38	82.05	0.2341	0.0914
4	86.80	72.08	83.25	**76.35**	82.03	0.2338	0.0910
6	87.93	**71.23**	82.90	75.15	82.25	0.2319	0.0918
8	87.67	72.00	83.40	76.23	**82.63**	**0.2312**	0.0915
12	**88.62**	71.90	83.65	75.73	82.28	0.2325	0.0919




Figure 3: CIFAR-10 Global Multiclass Performance: (Left) Test accuracy showing a +3.5%–4.3% gain from Multi-View Augmentation + Dampening and a +10.6% leap from the 7-Tree Majority-Voting Ensemble; (Middle) Multiclass error rate; (Right) Ensemble Bias^2 and Variance vs. depth.

Logical Arguments and Evidence on CIFAR-10:

1. **Why Baseline OvR Degrades with Depth (72.68% → 71.23%):** As the unaugmented Baseline OvR tree deepens from $d = 1$ to $d = 6$, its training accuracy climbs from 81.80% to 87.93%, but its test accuracy drops to a minimum of 71.23% (an error peak of 28.77%) before recovering slightly to 72.00% at $d = 8$. Without child-logit damping, false-positive activations at deep leaves inject large $+w_A$ offsets that corrupt cross-class arg max comparisons.




Figure 4: CIFAR-10 Per-Class Binary Error Curves across tree depth ($d \in \{1, 2, 4, 6, 8, 12\}$). Note the smooth monotonic training error descent and the interpolation peak followed by second descent in test error across multiple classes (e.g., Class 0: Airplane, Class 1: Automobile, Class 6: Frog, Class 7: Horse).

2. **Impact of Multi-View Augmentation + Child Damping (+3.5% to +4.3% Gain):** Training a single OvR network on pooled multi-view augmented features with dampened child scoring ($\alpha_{\text{damp}} = 0.5$) lifts test accuracy from 72.08% to **76.35%** at $d = 4$ and 76.23% at $d = 8$.

3. **Synergy of Random Subspace Ensembling + Majority Voting (+10.6% Gain):** When 7 OvR tree networks are trained on diverse augmented views and 50% random feature subspaces, uncorrelated leaf errors cancel out under majority voting. Test accuracy reaches **82.63%** at depth $d = 8$—representing a **+10.63% improvement** over the single-tree baseline (72.00%) and a **+14.73% improvement** over our Assignment 1 result (67.90%).

4 Deliverable 3: Bias and Variance Dynamics Across Sample Size and Epochs

To rigorously answer Objective 3 (*"How does bias and variance change with the number of samples and across epochs?"*), we performed controlled sweeps over training sample size N and per-node optimization epochs E on both datasets[cite: 30, 31].

Table 3: Empirical Bias^2, Variance, and Total Test Error across Training Sample Size (N) and Optimization Epochs (E) on Cats vs. Dogs and CIFAR-10[cite: 30, 31].

Cats vs. Dogs ($M = 7$ **Trees**, $d = 8$)				**CIFAR-10** ($M = 5$ **Ensembles**, $d = 6$)			
Sweep Variable	**Bias^2**	**Variance**	**Test Err**	**Sweep Variable**	**Bias^2**	**Variance**	**Test Err**
$N = 250$	0.0437	0.0369	0.0584	$N = 500$	0.2899	0.1306	0.2335
$N = 500$	0.0389	0.0331	0.0522	$N = 1{,}500$	0.2494	0.1072	0.1945
$N = 1{,}000$	0.0381	0.0249	0.0494	$N = 3{,}000$	0.2367	0.0979	0.1812
$N = 2{,}500$	**0.0362**	0.0222	0.0470	$N = 6{,}000$	0.2300	0.0913	0.1797
$N = 5{,}000$	0.0363	**0.0192**	**0.0454**	$N = 12{,}000$	**0.2236**	**0.0870**	**0.1713**
$E = 5$	0.0502	0.0650	0.0608	$E = 5$	0.2827	0.1458	0.2248
$E = 15$	0.0438	**0.0190**	0.0546	$E = 15$	0.2403	0.0981	0.1852
$E = 30$	0.0384	0.0192	0.0488	$E = 30$	0.2367	**0.0942**	**0.1825**
$E = 60$	0.0358	0.0210	**0.0456**	$E = 60$	0.2381	0.0980	0.1847
$E = 100$	0.0355	0.0228	0.0478	$E = 100$	0.2389	0.1008	0.1875
$E = 150$	**0.0338**	0.0260	0.0458	$E = 140$	0.2392	0.1027	0.1862




Figure 5: Cats vs. Dogs: Squared Bias, Variance, and Total Test Error as a function of (Left) Number of Training Samples $N \in [250, 5000]$ and (Right) Training Epochs per Node $E \in [5, 150]$.

4.1 Theoretical Synthesis of Bias-Variance Dynamics

The empirical curves in Figures 5 and 6 and Table 3 reveal three fundamental phenomena:

1. **Monotonic Variance and Bias Decay with Sample Size (N):** As training sample size increases from $N = 250 \to 5{,}000$ on Cats vs. Dogs, ensemble variance drops by **48.0%** ($0.0369 \to 0.0192$) and Bias^2 declines from $0.0437 \to 0.0363$, driving total test error down from $5.84\% \to 4.54\%$. Similarly, on CIFAR-10 ($N = 500 \to 12{,}000$), variance drops by **33.4%** ($0.1306 \to 0.0870$) and Bias^2 falls from $0.2899 \to 0.2236$, reducing test error from $23.35\% \to 17.13\%$. Larger N densely populates the 512-D ResNet manifold, stabilizing bootstrap hyperplane orientations ($\downarrow$ Variance) and enabling finer boundary estimation ($\downarrow$ Bias^2).




Figure 6: CIFAR-10: Squared Bias, Variance, and Multiclass Test Error as a function of (Left) Number of Training Samples $N \in [500, 12000]$ and (Right) Training Epochs per Node $E \in [5, 140]$.

2. **The Epoch-Wise Variance U-Turn (Early Under-Convergence vs. Late Overfitting):** Across training epochs E, Bias^2 decreases monotonically on Cats vs. Dogs (0.0502 at $E = 5 \rightarrow 0.0338$ at $E = 150$). However, **Variance follows a striking non-monotonic U-shaped trajectory**:

   - *Phase 1 — Random Initialization Instability ($E = 5 \rightarrow 15$):* At $E = 5$, each node MLP has barely moved from its random Kaiming initialization, causing different trees to make erratic, unaligned cuts. Consequently, variance is initially high (0.0650 on Cats vs. Dogs; 0.1458 on CIFAR-10) before plummeting to a minimum at $E = 15$–30 (0.0190 on Cats vs. Dogs; 0.0942 on CIFAR-10) as all root nodes align with the dominant semantic principal components[cite: 30, 31].
   - *Phase 2 — Gradient Over-Specialization ($E = 30 \rightarrow 150$):* Beyond $E = 30$, continued Adam optimization pushes node weights to tightly wrap around specific bootstrap boundary outliers. As a result, inter-tree disagreement resurges: variance climbs steadily from $0.0190 \rightarrow 0.0260$ (+36.8%) on Cats vs. Dogs and from $0.0942 \rightarrow 0.1027$ on CIFAR-10, causing total test error to bottom out around $E = 30$–60[cite: 30, 31].

3. **Depth-Wise Bias-Variance Trade-Off:** Across tree depth d (Figures 2 and 3, right panels), adding error-correcting child layers progressively reduces systematic underfitting (Bias^2 drops from 0.2385 at $d = 1 \rightarrow 0.2312$ at $d = 8$ on CIFAR-10) while slightly increasing model sensitivity (Variance rises from $0.0882 \rightarrow 0.0919$). Because Majority Voting divides effective prediction variance by $\mathcal{O}(M)$, the ensemble reaps the bias reduction of deep trees without suffering their variance penalty.

5 Deliverable 4: Loss Landscape Geometry and Receptive Field Specialization

5.1 1D Unit-Normalized Directional Perturbation and 2D Loss Surfaces

To comment on the loss landscape (Objective 4), we analyzed how the test Binary Cross-Entropy loss $\mathcal{L}(\boldsymbol{\theta})$ behaves in the neighborhood of the converged parameters $\boldsymbol{\theta}^*$ for three distinct neural nodes:

1. **Unaugmented Root Node ($\boldsymbol{\theta}^{\text{clean}}_{\text{root}}$):** Trained on clean embeddings without weight decay.
2. **Multi-View Augmented Root Node ($\boldsymbol{\theta}^{\text{aug}}_{\text{root}}$):** Trained across all K augmented views with ℓ_2 regularization.
3. **Deep Error-Correcting Child Node ($\boldsymbol{\theta}^{\text{leaf}}_{\text{child}}$):** Trained to isolate sparse residual C_3 errors from C_1 true negatives.

To ensure a scale-invariant comparison across models with different weight magnitudes, we sample random Gaussian directions $\mathbf{d}_1, \mathbf{d}_2$ normalized to unit Euclidean norm per parameter tensor ($\hat{\mathbf{d}} = \gamma \mathbf{d}/(\|\mathbf{d}\|_2 + 10^{-8})$) and measure the relative loss increase $\Delta\mathcal{L}(\alpha) = \max(0, \mathcal{L}(\boldsymbol{\theta}^* + \alpha\hat{\mathbf{d}}) - \mathcal{L}(\boldsymbol{\theta}^*))$ for $\alpha \in [-1.0, 1.0]$[cite: 30, 31].




Figure 7: Cats vs. Dogs Loss Landscape: (Left) 1D loss perturbation profiles comparing Root (Unaugmented), Root (Multi-View Augmented), and Child Node (Residual Error Specialist); (Right) 3D surface visualization of the smooth, convex-like basin around the Augmented Root Neuron.

Insights on Loss Landscape Curvature and Generalization:

- **Multi-View Augmentation Flattens the Loss Basin:** As seen vividly in Figure 8 (left) and Figure 7 (left), the Multi-View Augmented Root Node (solid green curve) exhibits the widest, flattest minimum: at perturbation step $|\alpha| = 1.0$, its loss increase on CIFAR-10 is only $\Delta\mathcal{L} \approx 0.18$, whereas the Unaugmented Root Node (dashed blue curve) rises to $\Delta\mathcal{L} \approx 0.25$ (and up to $\Delta\mathcal{L} > 8.0$ on Cats vs. Dogs)[cite: 30, 31]. Training across K augmented views averages out high-frequency instance noise, guiding gradient descent into a flat basin with small Hessian eigenvalues ($\lambda_{\max}(\nabla^2\mathcal{L})$). Under Perturbation Theory, flatter minima are robust to distribution shifts between training and test manifolds.




Figure 8: CIFAR-10 Loss Landscape (Class 0: Airplane vs. Rest): (Left) Symmetric expected loss increase $\Delta\mathcal{L}(\boldsymbol{\theta}^* \pm \alpha\mathbf{d})$ averaged over 5 random unit directions, demonstrating the strict curvature hierarchy $\kappa(\text{Child Leaf}) > \kappa(\text{Clean Root}) > \kappa(\text{Augmented Root})$; (Right) 2D loss surface.

- **Sharpness of Deep Error-Correcting Child Nodes:** Conversely, the Deep Child Node (dotted red curve) exhibits the steepest curvature ($\Delta\mathcal{L} \approx 0.72$ at $|\alpha| = 1.0$ on CIFAR-10). Because child nodes are trained on tiny, highly imbalanced boundary residuals (C_3), their weights must form razor-thin separating wedges in feature space. Perturbing $\boldsymbol{\theta}^*_{\text{child}}$ even slightly causes the wedge to sweep across the dense bulk of C_1 negatives, triggering a rapid loss explosion. This geometric sharpness explains why undampened deep child nodes degrade multiclass test accuracy unless regularized by step-gating, child-weight damping (α_{damp}), or ensemble majority voting!

5.2 Hierarchical Receptive Field Saliency: Root vs. Child Nodes

By backpropagating gradients from internal node logits $z_v(\phi(I))$ through the ResNet-18 trunk to the input image pixels $I \in \mathbb{R}^{128\times128\times3}$, we compute the normalized receptive field saliency map $\mathcal{S}_v(u,w) = \max_{c\in\{R,G,B\}} |\partial z_v/\partial I(u,w,c)|$[cite: 30, 31].




Figure 9: CIFAR-10 Receptive Field Saliency Comparison (128×128 Horse input): (Left) Original test image; (Middle) Augmented Root Node attends to the broad global silhouette and torso-background contrast; (Right) Deep Child Node concentrates on localized high-frequency morphological edges (head/neck contour and legs) to resolve residual classification ambiguity.

As shown in Figure 9, the tree hierarchy naturally induces spatial division of labor: the **Root**

Node captures coarse, low-frequency global object structure, whereas **Child Nodes** act as localized high-frequency feature detectors that inspect specific anatomical regions to rescue false negatives (C_3) or suppress false alarms (C_4).

6 Conclusions and Summary of Findings

Table 4 synthesizes our experimental findings across all four assignment objectives.

Table 4: Executive summary of innovations, empirical evidence, and theoretical conclusions.

Assignment Objective	**Key Innovation Implemented**	**Empirical Evidence**	**Logical / Theoretical Conclusion**
1. Augmentation + Overfitting & Double Descent	Multi-View Augmented Feature Bank (K = 4–5 views, `shuffle=False`) + $\sqrt{N_{\text{neg}}/N_{\text{pos}}}$ weighting + $n_{\min}$ split control.	Single + Aug lifts CIFAR-10 test acc from 72.08% $\rightarrow$ 76.35% and eliminates Cats vs. Dogs depth-2/4 interpolation error spikes.	Seeing multiple stochastic views per image prevents memorizing static crop artifacts and smooths the classical interpolation risk peak.
2. Multi-Tree Ensemble & Majority Voting	Triple-diversity ensemble (M = 7–9 trees): Multi-View + 85% Bootstrap + Random Feature Subspaces + Hard Majority Vote (mode).	CIFAR-10 test accuracy jumps to **82.63%** (+10.63% over single baseline; +14.73% over Assn 1). Cats vs. Dogs reaches **95.78%**.	Random subspaces decorrelate deep child-node errors; discrete majority voting cancels isolated leaf false positives.
3. Bias & Variance vs. Samples (N) & Epochs (E)	Explicit out-of-bootstrap statistical decomposition of Bias^2 and Var across d, N, and E.	As $N \uparrow$: both Bias^2 $\downarrow$ and Var $\downarrow$ monotonically. Across epochs E: Bias^2 $\downarrow$ monotonically, but Var follows a U-curve (min at E = 15–30, rising at E = 150).	Larger N stabilizes hyperplane geometry. Across epochs, early training aligns random weights ($\downarrow$ Var), while excessive epochs overfit boundary noise ($\uparrow$ Var).
4. Loss Landscape Analysis	1D symmetric unit-normalized directional perturbation $\Delta\mathcal{L}(\boldsymbol{\theta}^* \pm \alpha\mathbf{d})$ and 2D surface plotting.	Curvature hierarchy: κ(Child Leaf) > κ(Clean Root) > κ(Augmented Root) on both benchmarks.	Deep child nodes carve narrow, high-curvature wedges around sparse C_3/C_4 errors; multi-view augmentation finds wide, flat minima that generalize robustly.