Inside the Trap: A Renewal Law for Prefix-Cache Collapse in LLM Agent Serving

Akshat Valse* Ali Jannesari
Department of Computer Science, Iowa State University, Ames, IA, USA
avalse@iastate.edu jannesar@iastate.edu

Abstract

Prefix caching lets an LLM agent's follow-up turns reuse cached KV, but a burst can tip a serving engine into a trap in which every turn misses and the backlog does not drain, at a load it served before. Lu et al., who posted first, reported this metastable collapse, its feedback loop and a fluid model of its window. In registered paired tests on two engines, two GPUs and two models, a 200-session burst left the engine at zero hits in all 30 runs, while every matched no-burst run stayed good. We analyse an idealized model of the trapped state exactly: for a fluid FIFO server on which every turn misses, we prove that along FIFO orbits its cycles obey a linear renewal recursion. As is classical, the trap drains if and only if arrivals are below the all-miss capacity; above it, a Perron root fixes the dynamics: every trapped state converges to a known self-similar regime in which the gap between turns grows linearly, the backlog grows at 0.6 to 0.8 of the excess load here, and the turns served are young and short. For our workload, sessions then complete faster than the all-miss capacity, a youth premium with turn-count and cost-growth factors, so in the model a trap's measured throughput overstates the recovery threshold. Retrospectively, with nothing fitted to trap data, the theory matches 57 stuck runs: the turn mix within 3% in 50 runs, the pooled gap growth (median ratio 1.01) and completions above the all-miss capacity in every run. Blind in outcome, 3 runs in one cell trapped by a tool slowdown alone met pre-set tolerances; [pending: CUT]. Of two exits, refusing arrivals sheds sessions, while a session cap restores reuse: in registered tests it rescued 9 of 9 established zero-hit traps at the same load without shedding, and the engine stayed good after release. The model is an idealization; we do not prove that the engine converges to it.

1 Introduction

An LLM agent that calls tools sends its serving engine sessions of many turns: each prompt is the previous context plus the output of the tool just run. Prefix caching keeps the key–value (KV) state of the previous turn, so a follow-up turn whose prefix is still cached prefills only its new tokens [122]. In our workload a hit prefills 551 tokens and a miss about 11,100, and a session's prefill work with every turn missing is about 16 times that with every follow-up hitting. The cached KV belongs to sessions that sit idle in tool calls, and admitting waiting work evicts it. A burst of new sessions can therefore tip the engine into a state in which every turn misses, the queue grows, the gap between a session's turns grows with it, and idle KV is evicted before its owner returns. Fig. 1 shows this on SGLang: at loads that the engine carried from empty, a burst of 200 sessions left it at zero hits for the remaining 7500 s.

What is not ours. The phenomenon, its sustaining loop and a fluid model of its window are not new. Concurrently with and independently of this work, Lu et al. showed on prefill–decode disaggregated SGLang with real agent traces that a finite surge leaves the engine persistently degraded at a base load it previously sustained, identified the population–cache feedback that sustains the failure, and modelled the vulnerable window with a fluid population balance and an empirical hit-rate curve [76]. Their paper appeared first. The registered experiments of §6 up to SHED and TOOLSLOW were designed, registered and run before it appeared (Appendix N); the theory of §2 and the blind tests of §3 (TOOLSLOW-W, TOOLSLOW-D15 and CUT, registered on 2026-11-05) came afterwards, and the trap-state predictions were made with Lu et al.'s paper in hand. The collapse is Denning's thrashing [30], a bad state that a feedback loop sustains after its trigger is a metastable failure [11, 52], and metastability from a unimodal throughput curve, with bounded admission as the cure, is classical [15, 66, 84].

The question. This paper asks what the trapped state *is*. Quasi-static models treat it as the falling branch of a throughput curve, $\dot{n} = \lambda - \mu(n)$; read literally in congestion, sessions then complete at the curve's low end and accumulate at the excess over it. On our engines, where every trapped turn misses, both statements are wrong. Trapped runs complete sessions faster than the all-miss capacity measured with caching disabled (λ_{ref}, the unit of every rate below), by up to 2.4 times (one from-empty run at 6.5 λ_{ref}), while their backlog grows at about two thirds of the quasi-static rate. The gap matters to an operator: in model F below, a cut to just below the throughput measured in an all-miss trap does not clear it.

*Corresponding author.




Figure 1: The trap on SGLang: the registered paired test E2 at nominal rates of 1.35 λ_{ref} (left) and 1.65 λ_{ref} (right), $\lambda_{\text{ref}} = 0.0715$ sessions/s, the all-miss session rate measured with the radix cache disabled; one A100, a 300k-token KV pool. Top: hit fraction (turns with more than half of the prompt cached) in 100 s windows. Bottom: sessions in the system (log scale), including those in tool calls. One thin line per seed and arm. Dashed: a burst of 200 sessions at 1200 s. Shaded: the registered evaluation window. Without the burst (NOBURST) and with a client-side session cap (CAPPED) the engine stays good; after it (BURST), every turn misses to the end of the run.

Contributions.

(1) **A renewal law for an idealized trap** (§2). We idealize the trapped engine as a fluid FIFO server on which every turn misses and every turn rejoins the tail of the queue (model F), analyse it exactly, and prove that along FIFO orbits its cycles obey a linear renewal recursion (Theorem 1). Below λ_{miss} the trap drains, as is classical; above it, the recursion's Perron root z gives the convergence of every trapped state to a self-similar regime in which the gap between a session's turns grows at $z - 1$, the backlog at $\lambda(1 - E[z^{-T}])$ and completions at $D = \lambda E[z^{-T}]$, with the turn mix tilted to $G_k z^{-k}$. We decompose D/λ_{miss} into a turn-count factor and a cost-growth factor, a youth premium above 1 for our workload (Theorem 2), and conclude that in model F the throughput measured in a trap overstates the recovery threshold: only $\lambda' < \lambda_{\text{miss}}$ drains it, after a busy period that diverges at the threshold (Corollary 3). The self-similar regime itself is known [63], the recursion is a discrete renewal equation of Lotka–Leslie type [42], the critical case is the fluid counterpart of heavy-traffic state-space collapse [26, 94], and the premium has a processor-sharing analogue [56]. What we add, as far as a targeted search found, is the derivation of that recursion along FIFO orbits, which carries every trapped state into the regime with an exact virtual origin, and the turn-count and cost-growth factors of the premium. Corollary 3 is the operational reading of Theorem 2 with the classical drain condition; what is new about it is its test on the engine.

(2) **A test of the theory across engines** (§3). With no parameter fitted to any trap measurement, model F matches, across 57 stuck runs on SGLang and vLLM, two GPUs and two models (36 of them from registered protocols, on 30 distinct arrival plans), the trapped turn mix (within 3% in 50 of them), the pooled linear growth of the gap (median ratio of measured to predicted slope 1.01; per run 0.04–1.81) and completions above the all-miss capacity (in every run). It also explains, post hoc, why our registered trap rule was fragile at the lower rate. These checks are retrospective. Three blind tests followed, with predictions frozen before the runs existed; they are blind in outcome, and the tolerances of the trap-state scores were set on the earlier runs. A pre-registered 30 s tool slowdown lasting 1800 s with no burst, designed after a 900 s one had trapped 1 of 3, trapped the engine in 3 of 3 runs while their paired no-burst runs stayed good, and on these runs, in one cell whose outcome every frozen model predicted, the theory met all four pooled scores. A sec-

ond slowdown, at 1.65 λ_{ref}, on which the frozen models disagree: [pending: TOOLSLOW-D15 outcome]. After a burst, a cut in arrivals to below the trapped throughput of the same seeds' uncut runs, but above the all-miss capacity, left all three CUT-A runs trapped. The registered rule rejects only the constant-throughput readings it was built against (a flat-backlog reading fits as well over $[3000, 8700)$ s); the late-window slopes, scored post hoc against frozen values, single out model F; [pending: CUT-B outcome].

(3) **A first-principles account of entry** (§4). We derive the closed-population throughput curve $\mu(n)$ from the pool, the workload and a cost model fitted to server-log timing only. Its all-miss onset is the sessions in tool calls plus one pool of running sessions, which a faster GPU moves out, and we report its out-of-sample record, misses included. Against a post-hoc reading of Lu et al.'s concurrent model on our colocated cells, with one hit curve fitted on one cell (they built the model for disaggregated serving and do not use the curve to predict hits), the measured cliff moved out on the H200, by 6.7 and 10.9 sessions at the two pools against 5.8 and 6.6 from the tool-call term, and on the five cells frozen before their runs were read our crossings err by 1.5 sessions on average, against 4.1.

(4) **Control as two exits** (§5). In model F, starving the trap needs $\lambda' < \lambda_{\text{miss}}$; refusing arrivals (SHED) sheds sessions: in a registered test a 3600 s stop drained the trap and refused 355–378 sessions. Restoring reuse with a session cap, which leaves model F, does not: in registered tests the cap rescued 9 of 9 established zero-hit traps at the same offered load without shedding a session, at a price of 386–569 s of waiting at the client per paused session and 45–97% of the goodput of the hour after the burst, and the engine stayed good after the cap was removed.

(5) **A registered evidence base** (§6): paired tests with matched no-burst and capped arms on common random numbers on two engines, two GPUs and two models, a seed-replicated bracket of the basin in burst size, and registered negatives.

Model F is an idealization, and we do not prove that the engine converges to it. Sessions are synthetic (exponential 5 s tool times, no shared prefixes) and the models are dense and 7–8B in size. Section 7 positions the work in detail.

2 The trapped state: a renewal law

Quasi-static models describe the collapsed state as the falling branch of a throughput curve, $\dot{N} = \lambda - \mu(N)$, whose low end is Lu et al.'s low-reuse departure rate D_{low} [76] and, in our earlier model, the all-miss capacity λ_{miss} (which we used only for the window, §4). Read literally in congestion, such an equation makes a trapped engine complete sessions at that low end and accumulate them at the excess over it. With every turn missing, our engines do neither: every stuck run of the retrospective check completes sessions at 1.10–2.40 λ_{ref}, and the backlog grows at about 0.63 of $\lambda - \lambda_{\text{ref}}$ (§3). Here we characterize the trap exactly, within an explicit idealization of the trapped engine.

Model F. Let a session have T turns, $G_k = P(T \geq k)$ for $k = 1, \ldots, K$ with $G_K > 0$, and let turn k cost $c_k > 0$ GPU seconds when it misses. The costs come from the iteration-cost model of §4, fitted only to server-log timings: the miss prefill of turn k plus the all-miss per-turn decode share. Write

$$\lambda_{\text{miss}} = \Big(\sum_k c_k G_k \Big)^{-1}, \qquad \rho = \lambda / \lambda_{\text{miss}},$$

the all-miss capacity at the stationary turn mix and the load. Rates in this paper are multiples of λ_{ref}, the all-miss session rate measured with the radix cache disabled (E0a, 32 sessions; 0.0715 sessions/s for SGLang on the A100); λ_{miss} is model F's value from the cost model, and $\lambda_{\text{miss}}/\lambda_{\text{ref}} = 0.96$–$1.035$ across our cells. Model F is a fluid single-server queue in which

(F1) every turn misses, so turn k costs c_k;
(F2) the server works at unit rate while anything is pending;
(F3) requests complete in the order in which they joined (request-level FCFS);
(F4) a completed turn $k < T$ rejoins the tail of the queue at once as turn $k + 1$;
(F5) new sessions join as turn 1 at rate $\lambda > 0$;
(F6) the state at time 0 is any finite pending mass with positive work.

(F3)–(F4) make model F a round robin over sessions with visit-dependent quanta c_k: a single-station re-entrant line [67] in overload. A request that joins at time u completes at $f(u) = u + V(u)$, where $V(u)$ is the pending work; so V is also the gap between two consecutive turns of a session. Call u_0, $u_{n+1} = f(u_n)$ a *FIFO orbit* and $\Delta_n = u_{n+1} - u_n$ its cycles. Let $N(t)$ count the sessions present and $V_{\text{tot}}(t)$ be their total remaining all-miss work, future turns included, and let $\bar{k}_c = \sum_k k c_k G_k / \sum_k c_k G_k$ be the cost-weighted mean turn index.

Theorem 1 (the trap obeys a renewal equation)**.** *In model F, along every FIFO orbit the cycles solve the linear renewal recursion*

$$\Delta_n = \sum_{k=1}^{\min(n,K)} \lambda c_k G_k \, \Delta_{n-k} + h_n, \tag{1}$$

where $h_n = \sum_{k=n+1}^{K} c_k G_k \pi_{k-n}(u_0)/G_{k-n}$, *with* $\pi_j(u_0)$ *the turn-j mass pending at* u_0, *is the work that the requests pending at* u_0, *and their later turns, bring in generation n; so* $h_n \geq 0$, $h_n = 0$ *for* $n \geq K$ *and* $\sum_n h_n = V_{\text{tot}}(u_0)$. *Consequently:*

(a) if $\rho < 1$, *the queue empties at* $V_{\text{tot}}(0)/(1-\rho)$;
(b) if $\rho = 1$, $V(t) \to V_{\text{tot}}(0)/\bar{k}_c$ *and* $N(t) \to \lambda E[T] V_{\text{tot}}(0)/\bar{k}_c$;
(c) if $\rho > 1$, *let* $z > 1$ *be the Perron root,* $\lambda \sum_k c_k G_k z^{-k} = 1$. *As* $t \to \infty$: *the gap grows linearly,* $V(t)/t \to \gamma = z - 1$; *the backlog grows as* $N(t)/t \to \alpha = \lambda(1 - E[z^{-T}])$; *sessions complete at rate* $D = \lambda E[z^{-T}]$; *and the pending requests, and the requests served in each cycle, have the tilted turn mix* $\nu_k^z = G_k z^{-k} / \sum_j G_j z^{-j}$;

(d) *(virtual origin and self-similarity) if* $\rho > 1$, *let* $u^* = V_{\mathrm{tot}}(0)/(\rho - 1)$ *and let* r *be the largest modulus of the other roots of* $x^K = \sum_k \lambda c_k G_k x^{K-k}$. *Every FIFO orbit satisfies* $u_n + u^* = Bz^n + O((r+\epsilon)^n)$ *for every* $\epsilon > 0$, *with a constant* B; *hence the gap is affine in time with virtual origin* $-u^*$, $V(u_n) = \gamma(u_n + u^*) + O((r+\epsilon)^n)$, *and proportional to the remaining work,* $V(u_n) = \frac{\gamma}{\rho-1} V_{\mathrm{tot}}(u_n) + O((r+\epsilon)^n)$; *when* $r < 1$ *these errors vanish absolutely. A session that arrives at* u *with* $T = m$ *turns completes at* $f^m(u)$, *and* $f^m(u) + u^* = z^m(u + u^*)(1 + o(1))$;

(e) *as* $\rho \downarrow 1$, $\gamma = (\rho - 1)/\bar{k}_c + O((\rho-1)^2)$ *and* $\alpha/(\lambda - \lambda_{\mathrm{miss}}) \to E[T]/\bar{k}_c$.

Theorem 2 (youth premium)**.** *In Theorem 1(c),* $D/\lambda_{\mathrm{miss}} = H(z)\,\Gamma(z)$, *where*

$$H(z) = \frac{E[T]\,E[z^{-T}]}{\sum_k G_k z^{-k}}, \qquad \Gamma(z) = \frac{E_\nu[c]}{E_{\nu^z}[c]},$$

with $\nu_k \propto G_k$ *the stationary and* $\nu^z_k \propto G_k z^{-k}$ *the trapped turn mix.* H *depends only on the law of* T: $H = 1$ *for a geometric* T *on* $\{1, 2, \dots\}$ *(*$K = \infty$*; the formulas extend for* $z > 1$*), and* $H \in (1 - q^K, 1)$, *non-increasing in* z, *for* $T = \min(\mathrm{Geometric}(1-q), K)$ *with* $K \geq 2$. *If* c *is non-decreasing,* $\Gamma \geq 1$, *with equality only for constant* c, *and* Γ *is non-decreasing in* z. *For that* T *and a non-decreasing, non-constant* c *with* $E_\nu[c]/c_1 > 1/(1 - q^K)$, *let* z_1 *solve* $\Gamma(z_1) = 1/(1-q^K)$; *then* $D > \lambda_{\mathrm{miss}}$ *for every* $z \geq z_1$. *Near the threshold,* $D/\lambda_{\mathrm{miss}} - 1 = (\rho-1)(1 - E[T]/\bar{k}_c) + O((\rho-1)^2)$.

In model F the trapped server thus completes sessions faster than its all-miss capacity while its backlog diverges, because it serves a young backlog of short, cheap turns. The premium is not automatic: truncation lowers H, and with $T = \min(\mathrm{Geometric}(1/15), 60)$ and slowly growing costs $c_k = 1 + 10^{-3}(k-1)$ it is negative at every load checked. For our workload ($T = \min(\mathrm{Geometric}(1/15), 60)$, $c_{60}/c_1 = 17$–23), $E[T]/\bar{k}_c = 0.60$–0.62 in all eight cells, and the premium is positive at every load we checked: proved by Theorem 2's monotonicity for $\rho \geq 1.04$, shown by a monotone bracket (H falling, Γ rising; evaluated in floating point, not interval arithmetic) on $z \in [1 + 10^{-12}, z_1]$, and only to first order below that (Appendix A).

Corollary 3 (trapped throughput overstates the drain threshold)**.** *In model F at load* $\lambda > \lambda_{\mathrm{miss}}$, *let the arrival rate change to* λ' *at a time* t_0 *when the queue is busy. The queue then empties if and only if* $\lambda' < \lambda_{\mathrm{miss}}$, *after the busy period* $V_{\mathrm{tot}}(t_0)/(1 - \lambda'/\lambda_{\mathrm{miss}})$. *If* $\lambda' > \lambda_{\mathrm{miss}}$ *the backlog grows as* $\alpha(\lambda')t$; *at* $\lambda' = \lambda_{\mathrm{miss}}$ *the fluid backlog settles at a positive level. In particular, whenever* $D(\lambda) > \lambda_{\mathrm{miss}}$ *(Theorem 2; for our workload at every load we checked), a cut to any rate in* $[\lambda_{\mathrm{miss}}, D(\lambda))$, *below the asymptotic trapped throughput, does not empty model F's queue.*

Corollary 4 (invariance)**.** z *solves* $\rho \sum_k \omega_k z^{-k} = 1$ *with the cost-weighted turn mix* $\omega_k = c_k G_k / \sum_j c_j G_j$. *So* z, γ, *the trapped composition,* $\alpha/\lambda_{\mathrm{miss}}$ *and* $D/\lambda_{\mathrm{miss}}$ *depend on a cell only through* ρ, ω *and the law of* T; *they are unchanged by a uniform GPU speed-up at equal* ρ, *and the gap slope* γ *(seconds of wait per second of trap age) is then the same on both GPUs. This needs proportional cost vectors; our H200 cell model is a uniform speed-up of the A100's, and the corollary is not a general hardware claim.*

Proof idea. FIFO and work conservation give $f(u) = V(0) + W(u)$, where $W(u)$ is the work that has joined since time 0. FIFO maps the requests that join during one cycle onto the requests that complete during the next, so a session whose first turn joined in $(u_{n-k}, u_{n-k+1}]$ rejoins as turn k in $(u_{n-1}, u_n]$, and the turn-k mass joining there is $\lambda G_k \Delta_{n-k}$. Summing its work, $\Delta_n = W(u_n) - W(u_{n-1})$, turns the nonlinear fluid into Eq. (1), whose coefficients are nonnegative and sum to ρ. Tilting by z^{-n} and a finite-memory renewal lemma give (b)–(c); (a) is a busy-period argument; and the fixed lag structure gives the exact identity $u_{n+1} = V_{\mathrm{tot}}(0) + \sum_k \lambda c_k G_k u_{n+1-k}$, for $n \geq K - 1$, behind (d). Appendix A gives complete proofs, the stochastic counterpart and a sketch of the processor-sharing variant; `tests/test_theory_icml.py` checks each statement numerically; independent AI-agent checks are recorded in `notes/THEORY_ICML_2026-11.md`, §10.

What is classical and what is new. Part (a) is classical in substance: at a single work-conserving station the remaining work obeys $\dot{V}_{\mathrm{tot}} = \rho - 1$ whatever the service order, which gives the fluid busy period, and its stochastic counterpart is Kendall's branching description of the busy period [62]; part (e) is an elementary expansion of the Perron equation. Eq. (1) is a discrete renewal equation [42] of Lotka–Leslie type: the arrivals $\lambda\Delta_n$ play the role of births, G_k of survival and $\lambda c_k G_k$ of net maternity, and the tilted mix $G_k z^{-k}$ is Lotka's stable age distribution. Viewed as a steady solution (constant flows from the empty state), the self-similar regime of parts (c)–(d) is not new either: it is the single-station case of the steady solutions of fluid FIFO re-entrant lines of Khanin et al. [63], in which an overloaded station's queue grows linearly. Their overloaded-station flows give the Perron equation, the gap slope $z - 1$, the z^{-k}-tilted mix and the departure flow; they treat deterministic stages, a closing remark extends their framework to a fixed fraction of the flow leaving at each node (our random T), their normalization gives Corollary 4, and they leave open the uniqueness of non-steady trajectories. FIFO queues with feedback are classical in the stable regime [103, 105], overloaded multiclass FIFO queues have been analysed without re-entry [57], and the processor-sharing version of model F, which our earlier round-robin layer integrated numerically, has the Crump–Mode–Jagers structure of overloaded processor sharing, whose fluid shape converges to an invariant one [47, 56, 90]. What we add, as far as a targeted search found (§7), is the derivation of that recursion along FIFO orbits, which carries every solution from *any* trapped state to the self-similar regime, geometrically in the generation index and with an exact virtual origin (parts (c) and (d)), whereas a burst leaves the engine far from a steady solution.

Part (b) is the fluid counterpart of the state-space collapse of a critically loaded multiclass FIFO feedback queue [26, 94]. Theorem 2 is the visit-indexed analogue of a property of overloaded processor sharing, whose departures $\lambda E[e^{-\alpha_{\mathrm{PS}} S}]$, with α_{PS} its growth exponent, can exceed $1/E[S]$ [56]; new are its turn-count and cost-growth factors. Corollary 3 is not new as mathematics: it is the operational reading of Theorem 2 with the classical busy-period condition, its processor-sharing counterpart follows from [56] in the same way, and Lu et al. state that arrivals below their low-reuse departure rate drain the population [76]. What is new about it is its test on the engine (§3).

Model F is an idealization. On the engine, (F1) is the measured zero hit fraction of the trap and (F2) its saturated GPU. (F3) is request-level FCFS admission, up to the M/E_S requests that run concurrently (M the pool in tokens, E_S the service-weighted KV of a running turn; about 28 at 300k); Proposition 6 bounds the closed system at the stationary mix, and the open trap exceeds λ_{miss} only through its tilted mix. (F4) neglects the 5 s tool time against cycles of 166–516 s; adding it changes the fluid's backlog slope, completion rate and mean served prompt over the window by less than 0.02% and shortens the mean cycle by 5 s (Appendix A). Model F leaves out concurrency, preemption (vLLM preempts), and the transitions into and out of the trap, where hits return. We do not prove that the engine converges to model F; its test is empirical (§3).

Why the trap does not heal. Theorem 1(c) makes the gap between a session's turns grow linearly, while the trapped engine rewrites its pool at the all-miss token rate, every $R_M = M/\mathrm{churn} \approx 26$–$78$ s in our cells (churn, the rate at which new KV is written: uncached prompt plus completion tokens per second). Once the gap is several times R_M, as it is in every BURST run of the first three registered tests ($\mathrm{gap}/R_M = 4.1$–9.7, Table 7), an idle session's KV is overwritten long before it returns, so (F1) is self-consistent, and becomes more so as the trap ages. The pool need not be full: in the trapped SGLang runs with 300k and 600k pools, admitted requests held 55–83% of it on average (the engine's gauge, which also counts locked prefixes), 85–94% with the native pool and on vLLM, and still no follow-up turn hit. This is a heuristic consistency argument, not part of the theorem: R_M is a turnover scale, not a pathwise eviction bound. In a stochastic version (Poisson arrivals), Kendall's branching argument gives the probability that the all-miss queue ever empties from the fluid state 3000 s after the registered burst: 0.35 at $\rho = 1.01$, 4×10^{-3} at 1.05, 4×10^{-23} at 1.35 (Appendix A). Hits return before the queue empties, so these are orders of magnitude for a spontaneous exit, not bounds; they say it matters only within a few percent of λ_{miss}.

Table 1: Theorem 1 against the stuck runs of the registered E2-protocol cells (follow-up hit fraction below 0.2 over $[5700, 8700)$ s; 36 of the 57 stuck runs, the others in Appendix B), ranges over seeds (vLLM: registered and exploratory runs, which share plans). $\rho = \lambda/\lambda_{\mathrm{miss}}$ with the model's λ_{miss}. $\bar{L}$: mean prompt of the turns served, measured, against the tilted-mix prediction (stationary mean about 10,500 tokens). Gap slope: trend of the median gap between a session's turns against the turn's completion time, against $1 - 1/z$. D: session completion rate in units of λ_{ref}. Backlog: slope as a fraction of $\lambda - \lambda_{\mathrm{ref}}$, against $\alpha/(\lambda - \lambda_{\mathrm{miss}})$. Retrospective; no parameter fitted to any trap measurement; vLLM, the H200 and Llama take one speed factor fitted to their all-miss token rate.

cell, rate	ρ	$\bar{L}$ meas. / pred.	gap slope / $1 - 1/z$	D/λ_{ref} / pred.	backlog / pred.
300k 1.35	1.34	9125–9556 / 9324	.004–.020 / .013	1.13–1.28 / 1.13	.14–.89 / .63
300k 1.65	1.64	8417–8830 / 8606	.015–.027 / .022	1.25–1.35 / 1.23	.59–.78 / .65
native 2.5	2.44	7264–7484 / 7374	.044–.051 / .043	1.44–1.56 / 1.49	.74–.79 / .69
native 4.0	3.90	6127–6213 / 6115	.066–.076 / .075	1.87–2.03 / 1.81	.68–.76 / .74
vLLM 1.35	1.32	9097–9547 / 9393	.000–.016 / .012	1.18–1.28 / 1.14	.00–.74 / .63
vLLM 1.65	1.62	8104–8778 / 8676	.013–.028 / .022	1.30–1.42 / 1.24	.41–.80 / .65
H200 1.5	1.45	9015–9177 / 9062	.015–.022 / .016	1.20–1.27 / 1.20	.49–.78 / .64
H200 2.0	1.93	8058–8230 / 8082	.023–.031 / .031	1.40–1.45 / 1.36	.51–.66 / .66
Llama 1.35	1.33	9075–9512 / 9356	.003–.016 / .012	1.22–1.33 / 1.14	.00–.75 / .64
Llama 1.65	1.63	8459–8757 / 8631	.013–.021 / .022	1.34–1.49 / 1.23	.29–.63 / .66

3 The renewal law on the engine

Terms. E2 is our registered paired test (§6): a BURST arm (200 sessions within 60 s at 1200 s on top of Poisson arrivals), a NOBURST arm (the same arrivals without the burst) and a CAPPED arm (BURST behind a client session cap), each 8700 s long and judged over $[5700, 8700)$ s. BASIN, SHED and TOOLSLOW are registered variants of the BURST arm with other burst sizes, an arrival stop, and a tool slowdown instead of a burst; E0b runs start from an empty engine at a constant rate for 3000 s; LPM is SGLang's longest-prefix-match ordering, which reverts to FCFS when more than 128 requests wait.

We test model F on every trapped run we have, in eight cells: SGLang with the 300k pool (FCFS with and without its waiting-prefix refresh, the BASIN, SHED and TOOLSLOW runs, and stock LPM past its 128-request fallback), SGLang's native pool, vLLM, the H200 at 300k and 600k, Llama-3.1-8B, and the 150k and 600k pools. Each cell's costs c_k come from the cost model fitted to server-log iteration timings; vLLM, the H200 and Llama take one speed factor fitted to their own all-miss token rate. No parameter is fitted to any trap measurement.

Retrospective check. The theory was derived after these runs had been read, so this check is retrospective, not blind. Over the 57 stuck runs of the E2 protocol (20 cell and rate groups; 36 runs of registered protocols, on 30 distinct arrival plans; Table 1, Fig. 2):

- *Composition.* The mean prompt of the turns served matches the tilted mix ν^z to within −6.6% and +7.7%, and to within 3% in 50 of the 57 runs. The trapped engine serves turns




Figure 2: Theorem 1 against every stuck run, as a function of the load $\rho = \lambda/\lambda_{\text{miss}}$. Points: the 57 stuck runs of the E2 protocol (orange) and the 13 from-empty runs that were stuck over $[1500, 3000)$ s (E0b, hollow). Lines: model F for each of the eight cells; they nearly coincide because the cells' cost-weighted turn mixes are close ($E[T]/\bar{k}_c = 0.60$–0.62). No parameter is fitted to any trap measurement. (a) Mean prompt of the turns served, over the stationary mean: the tilted turn mix. (b) Session completion rate over λ_{miss}: the youth premium, above 1. (c) Backlog growth over λ_{miss}. (d) Growth rate of the gap between a session's turns, regressed on the turn's completion time, against model F's $\gamma/z = 1 - 1/z$. Dashed: the quasi-static fluid read literally in congestion (stationary composition, completion at λ_{miss}, growth at $\rho - 1$). Retrospective: the theory was derived after these runs were read.

10–42% shorter than the stationary mix, and the Perron root says by how much.

- *Gap growth.* The gap between a session's turns grows linearly in time. We regress it on the turn's completion time; a turn that completes at t joined at about t/z, so model F's slope is $\gamma/z = 1 - 1/z$. Measured over predicted, the ratio has median 1.01 (mean 0.96). Per run it ranges from 0.04 to 1.81; the low values are the seed-1 runs at 1.35 λ_{ref}, whose plans deliver fewer arrivals than nominal (below).
- *Youth premium.* Every stuck run completes sessions above λ_{ref}, at 1.10–2.03 λ_{ref} (up to 2.40 in the from-empty runs), and on average 1.055 times D (0.90–1.21). Part of the excess over D is a congested engine computing prompt tokens faster than the 32-session reference behind λ_{ref}, most on the H200 and the native pool (Appendix B); on vLLM and Llama the completion excess is not explained.
- *Backlog.* The backlog grows at 0.63 of $\lambda - \lambda_{\text{ref}}$ on average, where model F gives $\alpha/(\lambda - \lambda_{\text{miss}})$ of 0.63–0.74 at these loads, not the 1.0 of the quasi-static equation.

These are statements about the runs taken together; per run the gap and backlog statistics scatter widely, mostly with the plan's arrivals over the window. The same composition and gap laws hold for the 13 from-empty runs that were stuck over $[1500, 3000)$ s, at $\rho = 1.4$ to 6.3 (composition within −5.7% and +6.6%; gap-slope ratio 0.63–1.37, mean 1.03), on the pool sweep and on the H200, but their backlog slopes run above the prediction, by about 20–35% in most of them, and their completions by up to 15%; in model F the two add up to the arrival rate, which may reflect window arrival rates above nominal in these single seed-0 runs (not checked; Appendix B). Self-similarity (Theorem 1(d)) is visible only where samples are large and censoring is small: the sojourn of sessions of similar length grows with their arrival time at 0.86–1.19 of the predicted slope on the H200 at 600k and at 0.85–0.96 for short sessions on the native pool, but at 0.2–1.6 in the noisier cells and 0.1–0.8 for long sessions, which right-censoring biases (descriptive; Appendix B). The earlier heuristic round-robin layer of our model already reproduced the backlog slope at 300k numerically (0.63–0.64); Theorem 1 gives the law exactly, in closed form, for every cell.

The registered slope rule, explained post hoc. Our registered trap rule calls a BURST run trapped only if its backlog slope exceeds $0.5(\lambda - \lambda_{\text{ref}})$ (§6). At 1.35 λ_{ref} Theorem 1(c) puts the true slope at about $0.63(\lambda - \lambda_{\text{miss}})$, only about 25% above that line. The client plans are common random numbers, and seed 1's plan delivers 5.8–8.9% fewer arrivals than nominal over the window at 1.35 λ_{ref} in every cell; 8 of the 9 below-threshold runs are seed 1. The plug-in $\lambda_{\text{window}}(\text{plan}) - D$, computable from the plan before any run, falls on the measured side of the threshold for 27 of the 30 distinct plans of the registered protocols, against 23 for always predicting "trapped" (plans of different cells share seeds, so these are not independent trials). Two of the three exceptions lie within 10^{-4} /s of the threshold; the third is Llama at 1.35 λ_{ref}, seed 0, the registered failure. This account is post hoc and changes no registered verdict, but it suggests that the indeterminate seed-1 runs are traps whose growth the plan's arrival dip suppressed.

Persistence and the trigger. Among the runs before the blind tests below, no FCFS run trapped by a burst or by a tool slowdown left the trap on its own. Over 50 such runs (49 after a burst, one after the 900 s tool slowdown), about 100 trapped hours (99–103 h, depending on where the trap is taken to start), no 300 s window after the trap formed reached

a follow-up hit fraction of 0.5; the highest was 0.16. Treating the runs as independent, which shared seeds weaken, a one-sided 95% bound on a run's probability of escaping within its observed span (at least 6100 s) is 5.8%. Stock LPM, which leaves request-level FCFS while its queue is short, escaped in 4 of its 9 trapped runs, and 1 of the 16 from-empty collapses (FCFS, 150k pool, 1.30 λ_{ref}, seed 0) recovered within its 3000 s run. In 16 stuck runs (the 600k H200 paired test, BASIN bursts of 50–100 sessions, SHED's 600 s stop and the trapped TOOLSLOW run) every trigger session had left the system 558–6246 s before the end, and the 727–15,453 turns completed after that had no hit in 15 runs (4 hits among 5,937 turns in the TOOLSLOW run): the trap outlives its trigger, as Lu et al. also observed on hardware [76]. In the 24 registered 200-session runs on the A100 we cannot say so: 3–30 burst sessions were still present at the end (at most 4.1% of the sessions present). These counts are post hoc and exclude the blind tests' runs; an independent recomputation confirmed them, with the corrections included here (Appendix C).

Blind tests. The predictions of Theorem 1 for runs that did not yet exist were frozen under tag `icml-trap-pred` (commit `6b47a6c`, pushed at 00:24:47 CST on 2026-11-05 by GitHub's activity log), with scoring rules S1–S5 declared beforehand: per-run composition within ±8% (pooled ±5%); pooled gap slope within $[0.6, 1.4]\gamma$; completion above λ_{ref} in every trapped run at realized load $\geq 1.1\lambda_{\text{ref}}$ (pooled within ±15% of D); pooled backlog slope within ±35% of α or of the E2 fluid slope; and, per seed, the plug-in's side of the registered threshold and $|\text{slope}-\text{plug-in}| \leq 0.01$ /s. Theorem 1's application to a cell and load is refuted if the pooled S1 or S2 fails in a group of at least two trapped runs (`notes/PREDICTIONS_icml_trap.md`). The tolerances were set after seeing the committed runs; the runs they score did not exist at the push. S2 compares with γ, not with the completion-time slope γ/z; at 1.35 λ_{ref} the two differ by 1.3%, well inside the tolerance.

- *TOOLSLOW-W* (pre-registered: tag `r15-reg`, commit `e05a262`, pushed at 03:18:36 CST, before the first job was submitted at 03:21:38; designed after the 30 s TOOLSLOW arm, whose slowdown ended at 2100 s, trapped 1 of 3, and after reading simulator outputs, so it is blind in outcome only): no burst; every tool call that starts in [1200, 3000) s takes 30 s longer, at 1.35 λ_{ref}, seeds 0–2, paired with the committed NOBURST runs. The registered rule calls the cell TRAPS if at least 2 of the 3 runs are stuck, NO-TRAP if at least 2 are good, and MIXED otherwise; its trapped runs, if any, are scored by S1–S5. Outcome: TRAPS. All three runs were stuck (hit 0.000 over [5700, 8700) s; backlog slopes 0.0192, 0.0184 and 0.0232 /s against a threshold of 0.0125 /s), while their paired NOBURST runs stayed good (hit 0.930–0.934); on the same plans, the slowdown that ended at 2100 s had trapped 1 of 3. All three runs are eligible for S1–S5, and the pooled scores pass: composition +1.9% (limit ±5%), gap slope 1.075γ (1.089 against the unregistered γ/z), completions +1.9% of D with every run above λ_{ref}, and backlog slope +29% of α (limit ±35%); Theorem 1's application to this cell is not refuted. Per run, composition is within ±8% in all three (seed 1 at +7.9%), and S5's plug-in lies on the measured side of the threshold in 2 of 3 runs and within 0.01 /s in 3 of 3. Every model we froze (the calibrated simulator in both modes and the first-principles model) predicted this outcome, so the cell tests the trap-state law on a trap entered with no burst, not the models against each other. Like TOOLSLOW's, its outcome shows that a temporary increase in tool latency, with no burst, can trigger the trap; it does not separate the longer gap from the capacity loss and the larger population that come with it. Of the frozen exploratory measures, the first 150 s window below a follow-up hit of 0.5 fell at 1950, 1950 and 2100 s, inside its predicted band, and the sessions alive at 2100 and 3000 s met their reference accuracy; the outstanding requests at 3300 s missed it by 8 and 6 in seeds 0 and 2, and pred2's queue-free plan walk undercounted the sessions alive at 3000 s by 7–18.
- *TOOLSLOW-D15* (pre-registered with TOOLSLOW-W under tag `r15-reg`; jobs 17256873–75 submitted at 03:57:14 CST; designed, like TOOLSLOW-W, after the 900 s arm and after reading simulator outputs): no burst; every tool call that starts in [1200, 2100) s takes 15 s longer, at 1.65 λ_{ref}, seeds 0–2, paired with the committed NOBURST runs, under the same three-way rule; its stuck runs, if any, are scored by S1–S5. Here the frozen models disagree: the calibrated simulator predicted stuck, good and good (NO-TRAP) in both modes, the first-principles model's fluid verdict TRAPS, and its per-seed layer the simulator's modal calls with $P(\text{TRAPS}) = 0.58$; seeds 1 and 2 discriminate between the simulator and the fluid verdict. [pending: TOOLSLOW-D15 outcome and the S1–S5 scores of its stuck runs (lead's PAPER_INPUT part 2b).]
- *CUT* (a blind test of model F's trajectory under an arrival cut, the setting of Corollary 3): the 1.65 λ_{ref} BURST protocol, then from 2400 s arrivals cut to 1.15 λ_{ref} (CUT-A, $\rho' = 1.145$, inside $(\lambda_{\text{miss}}, D(\lambda))$) or to 0.85 λ_{ref} (CUT-B, $\rho' = 0.846$), seeds 0–2. Model F's predictions, driven by each seed's exact client plan, were frozen under tag `icml-cut-pred` (commit `2f90267`, pushed at 02:25:43 CST on 2026-11-05; `notes/PREDICTIONS_icml_cut.md`). Model F predicts that all six runs stay stuck over [5700, 8700) s; that CUT-A, although its rate is below the trapped throughput of the same seed's uncut run, does not clear, its backlog dipping by less than 15% on 300 s bins and growing again in seeds 0 and 2 (predicted slopes S of the backlog over [3000, 8700) s of +0.0039 and +0.0028 /s; seed 1's plan has few post-cut arrivals, and its predicted slope is −0.0026 /s); and that CUT-B drains slowly (predicted slopes −0.0095 to −0.0131 /s) and would empty only at about 27,100 s, the busy period of Theorem 1(a), far beyond the run.
  The decision rule was registered after the predictions were pushed and before any CUT job (commit `11b0e4e`, tag `r15-cut-reg`, pushed at 03:54:49 CST; jobs 17256867–72 submitted at 03:57). Per seed, the measured slope S over [3000, 8700) s is compared with model F's frozen slope and

with two comparators: a naive one, $\lambda'_{\text{plan}} - D_{\text{trap}}$, where D_{trap} is the trapped throughput of the same seed's uncut 1.65 λ_{ref} control over $[3000, 8700)$ s, fixed beforehand at 0.0956, 0.1005 and 0.0946 sessions/s (1.34, 1.41 and 1.32 λ_{ref}), the reading in which a cut below the measured throughput drains the trap; and, for CUT-A, the quasi-static $\lambda'_{\text{plan}} - \lambda_{\text{ref}}$, in which the trap completes sessions at the all-miss capacity. From the frozen plans the naive comparator is about −0.009 to −0.020 /s for CUT-A and −0.033 to −0.043 /s for CUT-B, and the quasi-static one +0.009 to +0.015 /s for CUT-A, so model F's values lie well between them. A seed is theory-favoured if model F's slope is strictly the closest to S, and a run that leaves the trap counts against the theory. CUT-A passes if at least 2 of 3 seeds are theory-favoured and the slope over $[5700, 8700)$ s is positive in at least 2 of 3 (model F predicts that clause from seeds 0 and 2); CUT-B passes if at least 2 of 3 seeds are theory-favoured and $S < 0$ in at least 2 of 3. Either arm fails if a comparator is favoured, or the run leaves the trap, in at least 2 of 3 seeds; otherwise it is mixed. The rule was fixed after the per-seed predictions had been read, and it differs from the draft rule simulated in the prediction note in five ways: it adds the quasi-static comparator (stricter); where the note counted a run that leaves the trap as not theory-favoured, the rule also counts it toward a fail (stricter); it takes D_{trap} from the frozen controls instead of each run's own completion rate over $[1800, 2400)$ s (stricter for seeds 0 and 1, looser for seed 2); it adds $S < 0$ in at least 2 of 3 to CUT-B (stricter); and it moves CUT-A's sign clause from $[3000, 8700)$ to $[5700, 8700)$ s, as the note recommended (looser: in the note's simulation this raised CUT-A's probability of passing from 0.82 to 0.99). The test has limits: the cut comes 1200 s after the burst, so it probes the young trap's transient and the start of its regrowth, not the asymptotic rate, and CUT-B cannot show recovery within the run.

CUT-A outcome: pass. With arrivals cut to a nominal 1.15 λ_{ref} (realized 1.12–1.20 λ_{ref} over $[3000, 8700)$ s; the plans are thinned Poisson streams), below the trapped throughput of the same seeds' uncut runs (1.32–1.41 λ_{ref}), all three runs stayed stuck to the end of the run, at zero hits over $[5700, 8700)$ s. Over $[3000, 8700)$ s the backlog's slope was +0.0040, −0.0022 and +0.0029 /s, against model F's frozen +0.0039, −0.0026 and +0.0028, the naive comparator's −0.0094, −0.0204 and −0.0099 and the quasi-static one's +0.0146, +0.0086 and +0.0132, so all three seeds were theory-favoured; over $[5700, 8700)$ s it was positive in seeds 0 and 2 and negative in seed 1, as model F predicted for that plan. The draft rule gives the same verdict. The secondary predictions frozen with model F (tolerances declared in the prediction note, not part of the registered rule) held as well: completions over $[5700, 8700)$ s within 0.001 /s of model F's per-seed values, the served prompt within 0.9%, a dip below the $[2100, 2400)$ s level of at most 11.0% on 300 s bins (frozen bound 15%; on 10 s bins, against the backlog at the cut, up to 19.1%), and more than 150 sessions present over the last 300 s. Model F's backlog levels ran 5–10 sessions high (186 against 176 over $[2100, 2400)$ s in seed 0).

The pass is narrower than Corollary 3. Both comparators assume a constant throughput, so the registered rule rejects only the constant-throughput readings, those in which the trap drains at the throughput it showed or completes sessions at the all-miss capacity: over $[3000, 8700)$ s, completions equal to the nominal cut rate fit as well as model F, and both match the measured slopes to within the engine's run-to-run jitter (0.0001–0.0005 /s, from the identical pre-cut parts of runs with the same plan). One result singles out model F: in the late window, scored post hoc against slopes frozen with the predictions, the backlog's slope was +0.0071, −0.0027 and +0.0131 /s against model F's +0.0069, −0.0036 and +0.0129, while constant completions at D_{trap}, at λ_{ref}, at their midpoint or at the nominal cut rate each missed by about 0.004 /s or more (the smallest, 0.0040, at the nominal cut rate in seed 0). The completion rate there supports it, also post hoc: it varied with the plan as model F said (1.05, 1.18 and 1.10 λ_{ref} against 1.04, 1.20 and 1.09), and no single constant rate comes within 0.004 /s of all three seeds, although the best one (0.080 /s) stays within the frozen tolerance of 0.006 /s. All three traps also persisted to 8700 s, which each constant reading above also predicts: the naive one still leaves about 50–130 sessions at the end, far above the onset $n_b = 32.7$. Persistence rules out only a drain at the completion rate seen just before the cut, 1.70, 1.65 and 1.21 λ_{ref} over $[1800, 2400)$ s, which would have reached the onset near 6300 s in seeds 0 and 1; that is the operator-facing content of Corollary 3, and on the engine it held within the run. CUT-A's three runs shared one node, and "did not clear" means within 8700 s.

CUT-B outcome. [pending: CUT-B outcome and its registered verdict (lead's PAPER_INPUT part 2b); draft texts are in the source comments below.]

The arrival stop, retrodicted. In the registered SHED test (§5) arrivals stopped at 1800 s, 600 s after a burst at 1.35 λ_{ref}. In model F the fluid backlog then falls to the onset $n_b = 32.7$ after 2,020 s and the queue empties after 3,180 s, the remaining work $V_{\text{tot}}(1800)$: with no arrivals the queue empties after exactly V_{tot} (Appendix A, proof of Theorem 1(a)). On the engine, a 600 s stop left both runs stuck, and in both 3600 s runs hits returned 2300–2600 s into the stop (the first 300 s window with follow-up hit fraction of at least 0.5 began at 4100 s; post hoc). The quasi-static model's frozen minimum stop was 1,795 s, early by about a quarter, and model F's time to the onset is early too, by about 15%. Model F's numbers are a retrodiction, computed after the SHED runs had ended, and the test does not discriminate: any drain time between 600 and 3600 s fits its two stop lengths.

4 How the trap is entered: a first-principles throughput curve

Model F describes the trap once it exists. Whether a load can be trapped at all is set by the closed-population throughput




Figure 3: Predicted thrashing curves $\mu(n)$ against the engine. Lines: the first-principles model (solid, fluid; dashed, with the demand-fluctuation layer H1, labelled F1 in the legend), from the pool, the workload and a cost model fitted to server-log timing only; vLLM and the H200 also get one speed factor fitted to their all-miss token rate. Points: measured $\mu(n)$, sessions/s (filled) and turns-based (open). Dotted: the predicted all-miss onset n_b (Proposition 2); dash-dotted: the measured λ_{ref}. No measured $\mu(n)$ point enters any prediction. The first three panels are in sample (the agents that derived the model knew every point). The H200 panel is out of sample: predicted under tag `r13-theory-pred` before those agents read it; the runs at $n = 36$, 44 and 52 (ringed) are blind in time, those at $n \le 32$ (shaded) had been seen by the cell's operating agent and the first author, the others are blind by access only; no blind simulator prediction was made for this cell (Appendix S).

curve $\mu(n)$ (Fig. 3), the session completion rate with n sessions present: Denning's thrashing curve [30]. It rises with batching, peaks at μ^*, and collapses to the all-miss level once admitting waiting turns evicts the idle KV of sessions in tool calls. With open arrivals the classical quasi-static approximation $\dot{n} = \lambda - \mu(n)$ [25, 66] makes the good state metastable at every load in the window $\mathcal{W} = (\lambda_{\text{miss}}, \min(\mu^*, \lambda_{\text{e}}))$, where λ_{e} is the measured from-empty edge (§E.3); Lu et al. write the same population balance with an empirical hit curve [76]. We use it for the window and the cap condition only, never for the trap.

The curve from first principles. We predict $\mu(n)$ from the pool size M, the workload, the tool-time law and an iteration-cost model fitted only to SGLang's per-batch timing lines, with no parameter fitted to any $\mu(n)$, hit or trap measurement (§H). Two couplings produce the cliff. Under prefill priority, misses starve decode, so running requests stay longer and reserve more of the pool, $K_{\text{run}}(\nu, h)$; and idle KV, evicted least recently used first at a characteristic idle age R (Che's approximation [17]), gives hits $h = F_Z(R)$ only if it survives the tool time Z. The pool balance

$$M = K_{\text{run}}(\nu, h) + \frac{\nu}{E[T]}\,\mathcal{D}(R), \qquad h = F_Z(R),$$

with ν the turn rate, $\mathcal{D}(R)$ the idle KV per unit session throughput, Little's law for n and a no-slack fluid closure, reduces to the characteristic-time equation of Yao et al. [114] when nothing runs or queues. With the couplings it gives a curve with a rise, a peak, a cliff and an all-miss branch, on which the queue, not the tool, sets the reuse gap.

The all-miss onset. Let ν_b be the turn rate at which running reservations fill the pool with every turn missing, $\mu_b = \nu_b / E[T]$ (the model's λ_{miss}), $\bar{z}'$ the tool time per turn and E_S the service-weighted KV of a running turn. Proposition 2 shows that the all-miss branch exists exactly for

$$n \ge n_b = \nu_b \bar{z}' + M/E_S,$$

the sessions in tool calls at the all-miss rate plus one pool's worth of running sessions, and that if every GPU cost is divided by s, then $n_b(s) = n_b(1) + (s-1)\nu_b(1)\bar{z}'$: a faster GPU moves the onset out.

The pool part M/E_S is a capacity ratio, the form of MISA-T's session cap [51], of AgentKV's collapse predictor [3] and of Lu et al.'s empirical cliff $N_c \approx 1.9\,C/\bar{c}$ [76]. The tool-call term, which grows with GPU speed, is the difference. In colocated serving the cache and the running reservations share one pool, so the onset of the all-miss branch is exactly where running reservations fill it; the cache-first versus decode-first distinction of PD-disaggregated serving collapses into one condition. A second result, Proposition 3, shows that GPU speed and tool time enter the peak ratio $\mu^*/\lambda_{\text{miss}}$ only through their product, which it lowers: memory and tools do not speed up with the GPU, so a faster GPU lowers the peak ratio, the window's upper end when the from-empty edge does not bind. On an H200 the all-miss capacity rose 2.71-fold and the peak only 1.63-fold, and the window shrank from $(1, 2.0)$ to $(1, 1.3)\,\lambda_{\text{ref}}$ (§G.5).

Out-of-sample record. The model's predictions were frozen under pushed tags before the agents that derived it read the results (Appendix S, Table 8, misses included). They

Table 2: The 0.5-hit crossing (sessions): measured; Lu et al.'s hit curve $h(W/C)$, read post hoc with $C = M$, $\bar{c} = \bar{E} = 10{,}569$ tokens and h fixed by the measured A100 300k crossing ($W/C = 1.133$), so that it predicts $1.133\,M/\bar{E}$ on every engine and GPU; our frozen crossing $n_{1/2}$ (fluid; nothing fitted to any curve point; the H200 and vLLM cells use one speed factor fitted to their all-miss token rate); and the capacity ratio M/E_S. Status of our prediction: b, blind in time; a, blind by access only (*the crossing lies between $n = 36$, blind in time, and 40; the cell's operating agent and the first author had seen $n \le 32$); i, in sample. Lu et al.'s own constant $N_c \approx 1.9\,C/\bar{c}$, measured on a disaggregated H100 deployment, would put every crossing 1.4–1.9 times further out, so we fix h on one of our cells; they place their cliff where the hit rate falls to about 0.3, and we compare 0.5-hit crossings. With its constant fitted to all eight crossings instead ($W/C = 1.098$, in sample), the $h(W/C)$ reading errs by 3.7 sessions on average, against 1.4 for $n_{1/2}$.

cell	status	meas.	$h(W/C)$	$n_{1/2}$	M/E_S
A100, 150k	b	16.5	16.1	16.9	13.6
A100, 300k	i	32.2	(32.2)	31.5	27.8
A100, 600k	b	60.1	64.3	60.0	56.1
A100, native	i	93.4	102.5	93.7	89.8
H200, 300k	a*	38.9	32.2	37.3	27.8
H200, 600k	b	71.0	64.3	66.6	56.1
vLLM, 300k	i	29.1	32.2	31.8	28.2
Llama, 300k	a	29.65	32.2	30.9	27.8
mean error, b and a (5)			4.1	1.5	7.0
mean error, all but 300k (7)			4.7	1.5	5.6

held for the rescue verdicts, the arrival stop, both basin tests' rules (BASIN-1's blind by access only), a doubled A100 pool, the 600k H200 registration and the H200's from-empty edge in nominal multiples. They missed the H200's softer tail past the peak (at 600k also the 0.5-hit crossing, 4.4 sessions late), a halved pool's peak height and edge, 4 of the 9 rescue release times, one seed's basin probabilities, the trapped token rates of two paired tests, Llama-3.1-8B's from-empty edge (one grid step high, a near miss) and a 30 s tool slowdown that it said would trap every seed (it trapped 1 of 3; lengthened from 900 to 1800 s in a pre-registered test designed after that miss, it trapped 3 of 3, as predicted); on TOOLSLOW-D15 its fluid verdict was TRAPS and its per-seed layer gave $P(\text{TRAPS}) = 0.58$ ([pending: TOOLSLOW-D15 outcome]). The 0.5-hit crossings of the five cells predicted before their runs were read lie within 0.1–4.4 sessions of the measured ones (Table 2).

Against Lu et al.'s empirical model. Lu et al.'s fluid model takes its hit rate $h(W/C)$, a function of the working set $W = N\bar{c}$ over the prefix-cache capacity C, from measurements of the deployed disaggregated system, and uses it to classify deployments and explain mitigations rather than to predict the hit rate [76]. Read post hoc on our colocated cells, with $C = M$, $\bar{c} = \bar{E}$ and one h fixed by the A100 300k crossing, it puts the 0.5-hit crossing in proportion to the pool and, with that curve carried across GPUs, at the same population on the H200. On the five cells whose crossings we predicted before their runs were read (three blind in time, two blind by access only), it errs by 4.1 sessions on average, against 1.5 for our frozen crossings (Table 2). The measured crossing moved out on the H200, by 6.7 sessions at 300k and 10.9 at 600k, against 5.8 and 6.6 from the tool-call term; refitting h on the H200's own 300k cell still puts its 600k crossing 6.7 sessions out. Their vulnerability condition and drain estimate are stated for separate prefill and decode instances and for resident-first ordering with healthy reuse, so we do not treat them as predictions of theirs; Appendix C applies them post hoc.

5 Two exits from the trap

Corollary 3 leaves two ways out of a trap. One is to *starve* it: bring the arrival rate below λ_{miss} until the busy period ends. The other is to leave model F: make turns hit again, which requires the sessions that compete for the pool to fall below the onset n_b, without lowering the offered load. A client-side session cap does this.

Starving the trap: refusing arrivals sheds sessions, and is slow. The corollary says how far and how long: below λ_{miss}, not below the trapped throughput $D(\lambda)$, and for $V_{\text{tot}}/(1 - \lambda'/\lambda_{\text{miss}})$, which diverges as $\lambda' \uparrow \lambda_{\text{miss}}$. In the all-miss fluid at 1.65 λ_{ref} (300k), a cut to $1.18\lambda_{\text{miss}}$, below $D = 1.22\lambda_{\text{miss}}$, makes the backlog dip by 0.3% and grow again, and a cut to $0.9\lambda_{\text{miss}}$ drains it only after about 15 hours (Appendix A). The registered SHED test at 1.35 λ_{ref} on the 300k pool stopped arrivals entirely from 1800 s, 600 s after a burst. A 600 s stop refused 56–59 sessions and left both runs stuck; a 3600 s stop refused 355–378 and left both good (§3). Lu et al. show in simulation that lowering post-surge arrivals reverses the outcome, and observe that the throughput measured in the collapsed state sets the scale of the cut [76]. Corollary 3, proved in model F, our idealization of an FCFS engine on which every turn misses, sharpens this: there the cut must go below λ_{miss}, which lies below the trapped throughput $D(\lambda)$. Their GPU-only simulations point the same way: the trap persisted at a cut to 0.2 of their reference rate (12 sessions/min) while the trapped departures they measured were 0.20–0.31 of it. Their systems keep some reuse in the trap, though, and with a host tier one seed in three recovered at cuts above the trapped departures they measured, so the corollary does not describe them. The CUT test probes the corollary's setting on our engine (§3): a cut to below the trapped throughput of the same seeds' uncut runs, and below the completion rate seen just before it, but above λ_{miss}, left all three CUT-A traps in place to the end of the run. The registered rule rejects only the constant-throughput readings; the late-window slopes, scored post hoc against frozen values, single out model F ([pending: CUT-B outcome]).




Figure 4: Trap, rescue, release and persistence: the registered rescue tests R1 and R4, seed 0 of each cell. Each rescue run (green) replays the arrival plan of a paired test's BURST run until a client-side session cap is engaged at t_{on} (dash-dotted; 1800 s for R1 on the 300k pool, cap 20; 2100 s for R4 with the native pool, cap 64); the cap is removed at t_{rel} (dotted) once both client queues have been empty for 300 s. The same-seed BURST (vermillion) and NOBURST (blue) runs share its arrivals. Dashed: the burst of 200 sessions at 1200 s. Top: follow-up hit fraction in 60 s bins. Bottom: outstanding work, requests in the engine plus sessions held at the client (log scale); dashed green: sessions held at the client. Seeds 1 and 2 behave alike (Table 3).

Restoring reuse with a session cap. A FIFO gate that admits at most n_{cap} sessions, each holding its slot until its last turn ends, makes the admitted sessions a closed system of $\min(n, n_{cap})$ sessions (Proposition 1). In the quasi-static model the gate then empties if and only if $n_1 < n_{cap} < n_2$, the stable and unstable fixed points of $\dot{n} = \lambda - \mu(n)$, and once it is empty and removed the population stays in the good state's basin (Corollary 5). In model-F terms the cap keeps the admitted sessions below the onset, so their turns hit again, and the excess waits at the client instead of in the engine's queue, where every turn would miss. The registered rescue tests R1 (300k pool, cap 20, engaged at 1800 s, 600 s after the burst, at 1.35 and 1.65 λ_{ref}) and R4 (native pool, cap 64, at 2100 s, at 4.0 λ_{ref}) engaged the registered CAPPED caps inside established traps: follow-up hit fraction 0.000–0.002 over the preceding 300 s, with 139–324 requests or sessions outstanding. All 9 runs were rescued without shedding a session (Table 3, Fig. 4). Hits returned within three minutes, the backlog drained, and the cap was released at 3980–6140 s, once the client queues had been empty for 300 s. With the cap removed, every run stayed good at the same arrival process for the remaining 2560–4720 s, matching its NOBURST control in follow-up hit fraction, outstanding work and turn latency, while the same-seed uncapped BURST run stayed at zero hits. The price is waiting at the client: 386–569 s per paused session on average, 38–78 (300k) and 222–230 (native) session-hours per run. In Lu et al.'s SLO goodput (slowdown at most 4; we cannot apply their per-token latency condition), the burst cost the uncapped runs 99.2–100% of the goodput of base sessions arriving in the following hour, against the same-seed NOBURST run, in all 30 registered BURST runs (in 26 of them no such session met the slowdown target, so there the loss is 100% under either definition); the rescue cost 45–97% in that hour, depending on the reference latency, but restored the evaluation window's goodput to within 1% of NOBURST (Appendix C).

What the rescue does and does not show. Persistence here means that the drained state sustains itself once the cap no longer binds: the release rule waits until the gate is empty, so the tests do not cover a release while the cap still binds, and the cap is engaged at a fixed time, not on an online signal. The frozen first-principles model predicted the rescue in every cell, but 4 of its 9 release times fell outside its ±15% tolerance (R4 released 19–22% late; Appendix S). Lu et al. restore service on hardware by terminating the burst sessions at the end of the burst, when the trap is incipient, prevent it with their controller active before the surge, rescue an established trap in simulation by activating their controller late (and leaving it on), and report one hardware run in which CONCUR's hit

Table 3: The registered rescue tests R1 and R4 (seeds 0, 1, 2); ranges over seeds. After release: follow-up hit fraction and mean outstanding work over $[t_{rel} + 300, 8700)$ s for the rescue run and, over the same interval, its same-seed controls. Delay: session-hours of pauses and admission waits at the client. Rows below the release time are descriptive, computed after the registered verdict.

	R1, 300k $1.35\,\lambda_{ref}$	R1, 300k $1.65\,\lambda_{ref}$	R4, native $4.0\,\lambda_{ref}$
cap; engaged at	20; 1800 s	20; 1800 s	64; 2100 s
rescued (relapses)	3/3 (0)	3/3 (0)	3/3 (0)
release t_{rel} (s)	3980–4550	4430–4920	5980–6140
after release: follow-up hit fraction			
rescue	0.999–1.000	0.994–1.000	1.000
NOBURST	0.999–1.000	0.991–1.000	1.000
BURST	0.000	0.000	0.000
after release: mean outstanding work			
rescue	1.9–2.2	2.5–2.8	8.8–11.8
NOBURST	1.9–2.2	2.5–3.1	8.8–11.8
BURST	195–219	272–317	1133–1178
sessions paused	121–130	138–143	220–251
delay (session-h)	38–65	50–78	222–230

rate fell to 0.33 before its concurrency window contracted and recovered slowly, with the controller left on and no release test [76]. What our tests add is a registered, replicated rescue of an *established* zero-hit trap at the same offered load, without shedding, with release of the control and persistence of the good state after it.

6 The registered evidence base

The theory of §2 explains and quantifies a phenomenon that we tested, independently of Lu et al., under registered rules (Table 4); every test above TOOLSLOW-W was registered and run before Lu et al. appeared. Each registered test fixed its rates, cap and decision rule by formula from earlier measurements of the same cell (the closed curve $\mu(n)$, the all-miss rate with caching disabled and the from-empty edge), and each arm ran in its own job on a fresh server, with the arms of a seed sharing arrival times, turn counts and tool times. Over the five paired tests the burst left the engine at zero hits to the end of every one of its 30 BURST runs, 7500 s after the burst, at rates that the engine carried in the good state for the full 8700 s of every NOBURST run; the registered slope rule called 23 of them trapped. Post hoc, the plug-in of §3 puts four of the other seven below the rule's threshold and two within 10^{-4} /s of it. On an H200 at the 300k pool, the all-miss capacity rose 2.71-fold and the peak of $\mu(n)$ only 1.63-fold, so the window narrowed to $(1, 1.3)\,\lambda_{ref}$, too narrow for the registration rule to place a test; doubling the pool reopened it to $(1, 2.5)\,\lambda_{ref}$ (§G.5).

What the record does not show. The registered tests use synthetic sessions (random tokens, exponential 5 s tool times, geometric turn counts, no shared prefixes) and dense 7–8B models on one GPU per engine; all but two use Qwen2.5-7B on the A100. The vLLM registration reached GitHub only after two of its jobs had started, so we call that test registered, not pre-registered. The 300k H200 cell is a measurement, not a registered test, and its closed-curve values for $n \le 32$ were seen by the cell's operating agent and the first author before the model's freeze; no blind simulator prediction was made for this cell. Some predictions are blind by access only, and the timeline of every registration and prediction, with its slips, is in Appendix N. No registration is in a third-party registry.

7 Related work

Concurrent work. Lu et al. [76] study the same phenomenon on SGLang with prefill–decode disaggregation and a host KV tier, serving a hybrid mixture-of-experts model (Qwen3.6-35B-A3B) on Terminal-Bench and SWE-bench Pro trajectories. On hardware, in single runs, as their run accounting implies, a ten-minute surge cut goodput by about 88% over the following hour, terminating the burst sessions at the end of the burst restored service, and in a run that let them finish the base population kept growing after the last burst session left. Their fluid model, $\dot{N} = \lambda - X(N)/K$ with an empirical hit curve $h(W/C)$ of the working set over the cache, gives the stable and unstable equilibria, the vulnerable window between the low-reuse departure rate D_{low} and the peak, the statement that arrivals below D_{low} let the population drain, a resource condition for cache-first vulnerability, and a drain-time estimate. In simulation they map vulnerability, show that changing post-surge arrivals alone reverses recovery, and report cache hysteresis (a lower hit rate after collapse at a comparable working set). Their controller, Basin[1], combines fixed session priority, admission by predicted peak context, decode-memory lending and shedding; on H200 hardware an arrival-time prototype of it achieves 1.20–1.70 times Continuum's goodput, and the predictor-driven design is evaluated in simulation. Against this, we add an exactly analysed idealization of the trapped state with its tests (§2–3), the reading that the throughput measured in a trap exceeds the drain threshold (Corollary 3, proved in model F, our idealization of an FCFS engine on which every turn misses; CUT-A is consistent with it; their systems keep some reuse), a first-principles entry model with an out-of-sample record (§4), the registered and replicated rescue of an established zero-hit trap at the same offered load without shedding, with release and persistence (§5), and registered matched-arm evidence on colocated engines, including a second engine (§6). They have real traces, disaggregated serving, a larger model, SLO goodput and a full mitigation system, which we do not.

Thrashing and metastability. The thrashing collapse and the working-set remedy are Denning's [30, 31]; metastability from a unimodal throughput curve and bistability under finite sources were analysed for random-access channels and

[1] Their Basin controller is unrelated to our BASIN-1 and BASIN-2 tests, which probe the basin of attraction of the good state.

Table 4: Registered tests (Appendices G, I and M). BURST: 200 sessions within 60 s at 1200 s; NOBURST: the same Poisson stream without them; CAPPED: BURST behind a client FIFO session cap from the start. A rate passes if, in at least two of three seeds, BURST is trapped (zero-hit token rate within ±15% of the all-miss rate and backlog slope above $0.5(\lambda - \lambda_{\text{ref}})$ over $[5700, 8700)$ s), NOBURST good and CAPPED recovered. Pre-registered: the filled registration was committed and pushed to GitHub before the jobs were submitted (the push log of our private development repository, exported in `provenance/`); registered: committed before submission, pushed later. Seeds 0–2 are shared across tests (common random numbers), so counts across tests are descriptive. Rates are nominal multiples of each cell's λ_{ref}.

Test	Cell and design	Status	Outcome
E2	SGLang 0.5.22, Qwen2.5-7B, A100, 300k pool; 1.35 and 1.65; cap 20	pre-registered	Pass at both rates: BURST at zero hits 6/6 (trapped 5/6), NOBURST good 6/6, CAPPED recovered 6/6
native E2	SGLang's own pool (955,757 tokens); 2.5 and 4.0; cap 64	pre-registered	Pass at both rates: 6/6 trapped, 6/6 good, 6/6 recovered
vLLM E2	vLLM 0.32.0, 300k pool; 1.35 and 1.65; cap 20	registered	Pass at both rates (zero hits 6/6, trapped 4/6); BURST arm repeats earlier exploratory seeds; frozen mechanism-check rule not met (detector alarmed in 2 CAPPED runs)
H200 E2	H200 NVL, 600k pool; 1.5 and 2.0; cap 48	pre-registered	Pass at both rates: zero hits 6/6 (trapped 5/6)
Llama E2	Llama-3.1-8B, A100, 300k; 1.35 and 1.65; cap 20	pre-registered	Pass at 1.65, fail at 1.35 (slope rule met by 1 of 3); all six BURST runs at zero hits
R1, R4 (rescue)	cap 20 at 1800 s (300k; 1.35, 1.65) and 64 at 2100 s (native; 4.0), inside an established trap	pre-registered	Rescued 9/9, no relapse, no session shed; stayed good after release, matching NOBURST
BASIN-1, BASIN-2	300k, 1.65; bursts of 25 and 100, then 40, 50, 60	pre-registered	25 and 40 good 3/3; 60 and 100 stuck 3/3; 50 stuck in 1 of 3; boundary between 40 and 60 in every seed
SHED	300k, 1.35; arrivals stopped from 1800 s for 600 or 3600 s	pre-registered	Pass: 600 s stuck 2/2 (56–59 sessions refused); 3600 s good 2/2 (355–378 refused)
TOOLSLOW	300k, 1.35, no burst; tool calls 10 or 30 s longer for 900 s	pre-registered	Rule not met: +10 s good 3/3; +30 s trapped 1/3
Registered on 2026-11-05, after Lu et al. appeared:			
TOOLSLOW-W	300k, 1.35, no burst; tool calls 30 s longer for 1800 s; traps iff stuck in ≥ 2 of 3	pre-registered	Traps: stuck 3/3 at zero hits; paired NOBURST good 3/3; the trap-state law's pooled scores pass (§3)
TOOLSLOW-D15	300k, 1.65, no burst; tool calls 15 s longer for 900 s; traps iff stuck in ≥ 2 of 3	pre-registered	[pending: outcome]
CUT	300k, burst at 1.65; from 2400 s arrivals at 1.15 or 0.85; rule in §3	pre-registered	CUT-A pass: theory-favoured 3/3, late-slope sign 2/3 as predicted, stuck 3/3 (the rule rejects only constant-throughput readings); CUT-B [pending: outcome]

multiprogrammed systems [15, 25, 66, 84]. Metastable failures were named by Bronson et al. [11], studied in production incidents and modelled by Huang et al. [52], whose trigger-and-control design our paired test follows, and analysed with queueing models and Markov chains [2, 48, 54]; Dong poses metastability in queues as an open problem [36]. These works characterize the bad regime as a state or an absorbing region; as far as we found, none gives its growth law or the composition of its population. Service systems whose service slows in congestion show related bistability [16, 37].

Overloaded and re-entrant queues. Overloaded processor sharing has a Crump–Mode–Jagers branching structure [47], linear growth [56] and a fluid limit whose shape converges to an invariant one [90]; overloaded multiclass FIFO queues with abandonment and no re-entry have fluid limits [57], and overloaded networks have bottleneck fluid approximations [18]. Re-entrant lines [67] and their fluid models [10, 27] are studied mostly for stability, and for convergence to equilibria at load at most one. Closest to model F, Khanin et al. study steady, constant-flow solutions of fluid FIFO re-entrant lines, in which an overloaded station's queue grows linearly [63]; at a single station their fixed point is our Perron root, and a closing remark covers fractional exits, which is our random turn count. FIFO queues with Bernoulli or deterministic feedback are classical in the stable regime [103, 105]. Round robin with feedback to the tail of the queue, which model F is at the level of sessions, was analysed in equilibrium for time-shared systems [24, 65], and overloaded polling systems have a random fluid limit with a branching structure [95]. In heavy traffic, multiclass FIFO feedback queues show state-space collapse [26, 94], of which Theorem 1(b) is the fluid counterpart. Theorem 1 adds the renewal recursion along FIFO orbits, a discrete renewal equation of Lotka–Leslie type [42], and, with it, convergence from an arbitrary initial state with an exact virtual origin. Theorem 2 is the visit-indexed analogue of the overloaded processor-sharing growth law, whose departures can exceed the capacity [56]; its turn-count and cost-growth factors have no counterpart we found. Corollary 3 is the operational reading of Theorem 2 with the classical drain condition, and its processor-sharing counterpart follows from [56] in the same way.

Queueing models of LLM serving. Ao et al. give fluid-guided scheduling with memory constraints [4] and show that, in a decode-only model without prefix reuse, the eviction-free

fixed point can be unstable [5]; Dai et al. prove throughput optimality of work-conserving policies without cache state [28]; Nie et al. give stability conditions under KV constraints for one-shot requests [85]; Dexter et al. analyse FCFS and longest-prefix-match scheduling under prefix reuse [34]; and Yao et al. derive a mean-field LRU hit ratio for multi-turn sessions with exogenous gaps between turns [114], which our entry model extends with hit-dependent running reservations (§4).

KV management for agents. Agent-serving systems keep, offload or evict the KV that sessions leave idle in tool calls, order requests to preserve reuse, and bound the number of active agents: PEEK [112], Continuum [69], Sutradhara [9], CONCUR [19], ThunderAgent [60] and its Dynamo port [35], EfficientAgent [98], AgentKV [3], MISA-T [51], MARS [108], VAMP [64] and KAIROS [119], among others (Appendix R). Several report hit-rate collapse as concurrency grows [19, 51, 64, 120], describe the loop between eviction, cold prefill and queueing for closed or bounded populations, or assert that a short overload can leave an instance persistently inefficient [119]. We claim none of these mechanisms; a session cap is classical load control [21, 33].

8 Limitations

The theory. Model F is an idealization: it assumes that every turn misses, that requests complete in FIFO order and that a finished turn rejoins at once. The engine runs about 28 requests concurrently, vLLM preempts, and hits return as the backlog falls toward the onset, so model F describes the trap, not the transitions into and out of it. We do not prove that the engine converges to model F, and the theorem's limits are reached only geometrically: in the registered window about 33–37 generations after the burst, a transient of order 10% remains, so we compare with the exact fluid as well as with the limits. The premium is proved positive for our workload at $\rho \geq 1.04$; below that it rests on a floating-point bracket and a first-order expansion.

The validation. The check on the 57 stuck runs is retrospective: the theory was derived after they were read, and its scoring tolerances were set on them. Only the runs submitted after tag `icml-trap-pred` test it blind, and only in outcome (§3): three TOOLSLOW-W runs, three TOOLSLOW-D15 runs ([pending: TOOLSLOW-D15 outcome]) and the six CUT runs, all on the A100 with the 300k pool. In CUT-A the registered rule rejects only the constant-throughput readings; the late-window slopes, scored post hoc against frozen values, single out model F. The from-empty runs are single runs per rate, and at 300k the seed-0 bracket did not replicate on fresh seeds (2.5 λ_{ref} was stable in 3 of 3; in realized rates the edge lies between 2.665 and 2.726 λ_{ref}). In an exploratory replication on two plans chosen because their outcomes were known, three runs each reproduced both originals, one collapse and one stable run, which suggests that the spread across seeds at the edge comes from the plans rather than from service noise (six runs, on two GPUs of one node). The trapped windows are at most 7500 s long, and "does not escape" means within that horizon.

The experiments. Sessions are synthetic (random tokens, exponential 5 s tool times, geometric turn counts, fixed tool outputs and output lengths, no shared prefixes), clients never retry or abandon, and real agent traces have tool times far shorter and more dispersed. Engines are colocated, with one GPU each, dense 7–8B models and pools of 150k to 956k tokens; disaggregated serving, offloading, larger models and parallelism are untested. Seeds are shared across tests. The rescue engages a fixed cap at a fixed time, the arrival stop ran at one rate, and the tool slowdowns at two. Appendix K gives the full list.

9 Conclusion

A burst can tip a prefix-cached agent server into a trap in which its cache stops paying; Lu et al., who posted first, and we observed this independently (in their disaggregated system the hit rate falls to about 0.3, in ours every turn misses). Idealized, the trap has an exact law: as a fluid FIFO server on which every turn misses, the trapped engine obeys a linear renewal recursion along FIFO orbits, so from any trapped state it converges to the known self-similar regime [63], fixed by a Perron root: the gap between turns grows linearly, the backlog grows at a fraction of the excess load (0.6 to 0.8 at our loads), and the turns it serves are young and short; for our workload it completes sessions faster than its all-miss capacity. Checked retrospectively on 57 stuck runs on two engines, two GPUs and two models, with no parameter fitted to any trap measurement, these laws hold for the runs taken together, and, with predictions frozen before the runs, on three runs in one cell trapped by a tool slowdown alone. The practical reading is Corollary 3: in model F, a cut to just below the throughput measured in an all-miss trap does not clear it, and a cut below the all-miss capacity drains the trap only slowly and by turning sessions away. On the engine, a cut to below the completion rate seen just before it, and below the trapped throughput of the same seeds' uncut runs, but above the all-miss capacity, left all three traps in place to the end of the run; the registered rule rejects only the constant-throughput readings, and the late-window slopes, scored post hoc against frozen values, single out model F ([pending: CUT-B outcome]). The other exit, a session cap that restores reuse, rescued all 9 established traps of our registered tests at the same load without shedding, and the engine stayed good after the cap was removed.

Code and data availability

The code (simulator, load generator, analysis, the first-principles model and model F, the Slurm job scripts), the experiment configurations, every registration file, the frozen predictions with their tags, all real-engine data with

the job logs, the research log, the scripts behind every figure and derived table, and the source of every number in the paper (`paper/NUMBERS.md`) are in our repository, [pending: repository URL]. Its history is a redacted copy of the authors' development repository, whose commit hashes this paper cites; `provenance/` maps them and holds the timing evidence behind our registration claims (Appendix O).

Use of AI tools

Claude and OpenAI Codex assisted with experiments, code, analysis, theoretical development, and writing. The authors directed the work and take full responsibility for its content.

Acknowledgments

The experiments ran on the Nova cluster at Iowa State University. The research reported in this paper is partially supported by the HPC@ISU equipment at Iowa State University, some of which has been purchased through funding provided by NSF under MRI grants number 1726447 and MRI2018594.

References

[1] Reyna Abhyankar, Zijian He, Vikranth Srivatsa, Hao Zhang, and Yiying Zhang. InferCept: Efficient intercept support for augmented large language model inference. In *Proceedings of the 41st International Conference on Machine Learning*, volume 235 of *Proceedings of Machine Learning Research*, pages 81–95, 2024.

[2] Peter Alvaro, Rebecca Isaacs, Rupak Majumdar, Kiran-Kumar Muniswamy-Reddy, Mahmoud Salamati, and Sadegh Soudjani. Formal analysis of metastable failures in software systems. arXiv:2510.03551, 2025.

[3] Anonymous. AgentKV: Predictive admission prevents KV-cache collapse in agentic LLM serving. ICLR 2027 submission, `https://openreview.net/forum?id=zLtopd1ATE`, 2026.

[4] Ruicheng Ao, Gan Luo, David Simchi-Levi, and Xinshang Wang. Optimizing LLM inference: Fluid-guided online scheduling with memory constraints. arXiv:2504.11320 (v4, 13 June 2026), 2025.

[5] Ruicheng Ao, Jing Dong, Gan Luo, and David Simchi-Levi. Service-induced congestion in memory-constrained LLM serving. arXiv:2606.15555 (v3, 20 October 2026), 2026.

[6] Mayank Arya, Agrim Bari, Anjaly Parayil, Yogesh Simmhan, Renee St. Amant, Victor Rühle, and Saravan Rajmohan. Understanding KV residency in production-scale agentic LLM workloads. arXiv:2610.22863 (v1, 16 October 2026), 2026.

[7] L. A. Belady. A study of replacement algorithms for a virtual-storage computer. *IBM Systems Journal*, 5(2): 78–101, 1966.

[8] Zhuohang Bian, Feiyang Wu, Zhuoran Li, Teng Ma, and Youwei Zhuo. TokenCake: A KV-cache-centric serving framework for LLM-based multi-agent applications. arXiv:2510.18586; to appear at EuroSys '27, 2025.

[9] Anish Biswas, Kanishk Goel, Srivarshinee S, Jayashree Mohan, Alind Khare, Anjaly Parayil, Ramachandran Ramjee, and Chetan Bansal. Sutradhara: An intelligent orchestrator-engine co-design for tool-based agentic inference. arXiv:2601.12967 (v3, 22 April 2026), 2026.

[10] Maury Bramson. Convergence to equilibria for fluid models of FIFO queueing networks. *Queueing Systems*, 22(1–2):5–45, 1996. doi: 10.1007/BF01159391.

[11] Nathan Bronson, Abutalib Aghayev, Aleksey Charapko, and Timothy Zhu. Metastable failures in distributed systems. In *Proceedings of the Workshop on Hot Topics in Operating Systems (HotOS '21)*, Ann Arbor, MI, 2021. doi: 10.1145/3458336.3465286.

[12] Marc Brooker, Mike Danilov, Chris Greenwood, and Phil Piwonka. On-demand container loading in AWS Lambda. In *2023 USENIX Annual Technical Conference (USENIX ATC 23)*, pages 315–328, 2023. arXiv:2305.13162 (v2).

[13] Shelby L. Brumelle. On the relation between customer and time averages in queues. *Journal of Applied Probability*, 8(3):508–520, 1971. doi: 10.2307/3212174.

[14] Shiyi Cao, Yichuan Wang, Ziming Mao, Pin-Lun Hsu, Liangsheng Yin, Tian Xia, Dacheng Li, Shu Liu, Yineng Zhang, Yang Zhou, Ying Sheng, Joseph Gonzalez, and Ion Stoica. Locality-aware fair scheduling in LLM serving. arXiv:2501.14312, 2025.

[15] A. Carleial and M. Hellman. Bistable behavior of ALOHA-type systems. *IEEE Transactions on Communications*, 23(4):401–410, 1975. doi: 10.1109/TCOM.1975.1092823.

[16] Carri W. Chan, Galit Yom-Tov, and Gabriel Escobar. When to use speedup: An examination of service systems with returns. *Operations Research*, 62(2): 462–482, 2014. doi: 10.1287/opre.2014.1258.

[17] Hao Che, Ye Tung, and Zhijun Wang. Hierarchical Web caching systems: Modeling, design and

experimental results. *IEEE Journal on Selected Areas in Communications*, 20(7):1305–1314, 2002. doi: 10.1109/JSAC.2002.801752.

[18] Hong Chen and Avi Mandelbaum. Discrete flow networks: bottleneck analysis and fluid approximations. *Mathematics of Operations Research*, 16(2):408–446, 1991. doi: 10.1287/moor.16.2.408.

[19] Qiaoling Chen, Zhisheng Ye, Tian Tang, Peng Sun, Boyu Tian, Guoteng Wang, Shenggui Li, Yonggang Wen, Zhenhua Han, and Tianwei Zhang. CONCUR: High-throughput agentic batch inference of LLM via congestion-based concurrency control. In *Proceedings of the 43rd International Conference on Machine Learning*, volume 306 of *Proceedings of Machine Learning Research*, pages 17881–17891, 2026. arXiv:2601.22705.

[20] Huang Cheng. CacheRoute: Planned prefix-affinity routing for large-scale LLM serving. arXiv:2608.19677 (v1, 20 August 2026), 2026.

[21] L. Cherkasova and P. Phaal. Session-based admission control: A mechanism for peak load management of commercial web sites. *IEEE Transactions on Computers*, 51(6):669–685, 2002. doi: 10.1109/TC.2002.1009151.

[22] Hong-Tai Chou and David J. DeWitt. An evaluation of buffer management strategies for relational database systems. In *Proceedings of the 11th International Conference on Very Large Data Bases (VLDB '85)*, pages 127–141, Stockholm, 1985.

[23] Neil Chowdhury, James Aung, Jun Shern Chan, Oliver Jaffe, Dane Sherburn, Giulio Starace, Evan Mays, Rachel Dias, Marwan Aljubeh, Mia Glaese, Carlos E. Jimenez, John Yang, Leyton Ho, Tejal Patwardhan, Kevin Liu, and Aleksander Madry. Introducing SWE-bench Verified. OpenAI blog post, 13 August 2024 (updated 24 February 2025); `https://openai.com/index/introducing-swe-bench-verified/`, 2024.

[24] Edward G. Coffman and Leonard Kleinrock. Feedback queueing models for time-shared systems. *Journal of the ACM*, 15(4):549–576, 1968. doi: 10.1145/321479.321483.

[25] P. J. Courtois. Decomposability, instabilities, and saturation in multiprogramming systems. *Communications of the ACM*, 18(7):371–377, 1975. doi: 10.1145/360881.360887.

[26] J. G. Dai and Thomas G. Kurtz. A multiclass station with Markovian feedback in heavy traffic. *Mathematics of Operations Research*, 20(3):721–742, 1995. doi: 10.1287/moor.20.3.721.

[27] J. G. Dai and G. Weiss. Stability and instability of fluid models for reentrant lines. *Mathematics of Operations Research*, 21(1):115–134, 1996. doi: 10.1287/moor.21.1.115.

[28] J. G. Dai, Tianze Deng, Yueying Li, and Tianyi Peng. Throughput-optimal scheduling algorithms for LLM inference and AI agents. arXiv:2504.07347 (v3, 18 May 2026), 2025.

[29] Asit Dan, Daniel M. Dias, and Philip S. Yu. The effect of skewed data access on buffer hits and data contention in a data sharing environment. In *Proceedings of the 16th International Conference on Very Large Data Bases (VLDB '90)*, pages 419–431, Brisbane, Australia, 1990.

[30] Peter J. Denning. Thrashing: Its causes and prevention. In *Proceedings of the AFIPS Fall Joint Computer Conference*, pages 915–922, 1968. doi: 10.1145/1476589.1476705.

[31] Peter J. Denning. The working set model for program behavior. *Communications of the ACM*, 11(5): 323–333, 1968. doi: 10.1145/363095.363141.

[32] Peter J. Denning. The locality principle. *Communications of the ACM*, 48(7):19–24, 2005. doi: 10.1145/1070838.1070856.

[33] Peter J. Denning, Kevin C. Kahn, Jacques Leroudier, Dominique Potier, and Rajan Suri. Optimal multiprogramming. *Acta Informatica*, 7(2):197–216, 1976. doi: 10.1007/BF00265771.

[34] Gregory Dexter, Shao Tang, Ata Fatahi Baarzi, Qingquan Song, Tejas Dharamsi, and Aman Gupta. LLM query scheduling with prefix reuse and latency constraints. arXiv:2502.04677 (v3; v1 7 February 2025), 2025.

[35] Ishan Dhanani, Jamie Li, and Karen Chung. Session-aware agentic inference with NVIDIA Dynamo. PyTorch Blog, 8 October 2026; `https://pytorch.org/blog/session-aware-agentic-inference-with-nvidia-dynamo/`, 2026.

[36] Jing Dong. Metastability in queues. *Queueing Systems*, 100(3–4):413–415, 2022. doi: 10.1007/s11134-022-09795-2.

[37] Jing Dong, Pnina Feldman, and Galit B. Yom-Tov. Service systems with slowdowns: Potential failures and proposed solutions. *Operations Research*, 63(2): 305–324, 2015. doi: 10.1287/opre.2015.1346.

[38] Ronald Fagin. Asymptotic miss ratios over independent references. *Journal of Computer and System Sciences*, 14(2):222–250, 1977. doi: 10.1016/S0022-0000(77)80014-7.

[39] Ali Farahbakhsh, Andreas Haeberlen, Qingjie Lu, Lorenzo Alvisi, Robbert van Renesse, and Shir Cohen. Modeling metastability. In *Proceedings of the 24th ACM Workshop on Hot Topics in Networks (HotNets '25)*, pages 19–24, College Park, MD, USA, 2025. ACM. doi: 10.1145/3772356.3772426.

[40] Ali Farahbakhsh, Qingjie Lu, Lorenzo Alvisi, Andreas Haeberlen, and Robbert van Renesse. Characterizing metastable faults and failures. arXiv:2606.00942 (v2, 2 June 2026), 2026.

[41] Guy Fayolle, Erol Gelenbe, and Jacques Labetoulle. Stability and optimal control of the packet switching broadcast channel. *Journal of the ACM*, 24(3): 375–386, 1977. doi: 10.1145/322017.322019.

[42] William Feller. *An Introduction to Probability Theory and Its Applications, Volume I*. Wiley, 3 edition, 1968.

[43] Christine Fricker, Philippe Robert, and James Roberts. A versatile and accurate approximation for LRU cache performance. 24th International Teletraffic Congress (ITC 24); arXiv:1202.3974 (v1, 17 February 2012), 2012.

[44] Bin Gao, Zhuomin He, Puru Sharma, Qingxuan Kang, Djordje Jevdjic, Junbo Deng, Xingkun Yang, Zhou Yu, and Pengfei Zuo. Cost-efficient large language model serving for multi-turn conversations with CachedAttention. In *2024 USENIX Annual Technical Conference (USENIX ATC 24)*, pages 111–126, Santa Clara, CA, 2024. USENIX Association. arXiv:2403.19708.

[45] Nicolas Gast and Benny Van Houdt. Transient and steady-state regime of a family of list-based cache replacement algorithms. In *Proceedings of the 2015 ACM SIGMETRICS International Conference on Measurement and Modeling of Computer Systems*, pages 123–136, 2015. doi: 10.1145/2745844.2745850.

[46] Aaron Grattafiori, Abhimanyu Dubey, Abhinav Jauhri, et al. The Llama 3 herd of models. arXiv:2407.21783, 2024.

[47] Sergei Grishechkin. On a relationship between processor-sharing queues and Crump–Mode–Jagers branching processes. *Advances in Applied Probability*, 24(3):653–698, 1992. doi: 10.2307/1427484.

[48] Farzad Habibi, Tania Lorido-Botran, Ahmad Showail, Daniel C. Sturman, and Faisal Nawab. MSF-Model: Queuing-based analysis and prediction of metastable failures in replicated storage systems. In *Proceedings of the 43rd International Symposium on Reliable Distributed Systems (SRDS)*, pages 12–22, Charlotte, NC, USA, 2024. IEEE. doi: 10.1109/SRDS64841.2024.00013.

[49] Hans-Ulrich Heiss and Roger Wagner. Adaptive load control in transaction processing systems. In *Proceedings of the 17th International Conference on Very Large Data Bases (VLDB '91)*, pages 47–54, Barcelona, 1991. Morgan Kaufmann.

[50] Daniel P. Heyman and Shaler Stidham, Jr. The relation between customer and time averages in queues. *Operations Research*, 28(4):983–994, 1980. doi: 10.1287/opre.28.4.983.

[51] Zetao Hong, Song Yuan, Yuanhao Ding, Yibo Zhu, Daxin Jiang, Zhibin Wang, and Chen Tian. Scheduling mixed RL rollouts beyond prefix locality. arXiv:2608.11152 (v1, 11 August 2026), 2026.

[52] Lexiang Huang, Matthew Magnusson, Abishek Bangalore Muralikrishna, Salman Estyak, Rebecca Isaacs, Abutalib Aghayev, Timothy Zhu, and Aleksey Charapko. Metastable failures in the wild. In *16th USENIX Symposium on Operating Systems Design and Implementation (OSDI 22)*, pages 73–90, 2022.

[53] Armann Ingolfsson, Eman Almehdawe, Ali Pedram, and Monica Tran. Comparison of fluid approximations for service systems with state-dependent service rates and return probabilities. *European Journal of Operational Research*, 283(2): 562–575, 2020. doi: 10.1016/j.ejor.2019.11.041.

[54] Rebecca Isaacs, Peter Alvaro, Rupak Majumdar, Kiran-Kumar Muniswamy-Reddy, Mahmoud Salamati, and Sadegh Soudjani. Analyzing metastable failures. In *Proceedings of the Workshop on Hot Topics in Operating Systems (HotOS '25)*, pages 172–178, Banff, AB, Canada, 2025. ACM. doi: 10.1145/3713082.3730380.

[55] Van Jacobson. Congestion avoidance and control. In *Symposium Proceedings on Communications Architectures and Protocols (ACM SIGCOMM '88)*, pages 314–329, 1988. doi: 10.1145/52324.52356.

[56] Alain Jean-Marie and Philippe Robert. On the transient behavior of the processor sharing queue. *Queueing Systems*, 17(1–2):129–136, 1994. doi: 10.1007/BF01158692.

[57] Otis B. Jennings and Amber L. Puha. Fluid limits for overloaded multiclass FIFO single-server queues with general abandonment. *Stochastic Systems*, 3(1): 262–321, 2013. doi: 10.1214/12-SSY085.

[58] Youhe Jiang, Fangcheng Fu, Binhang Yuan, Krishna Malladi, Ehsan K. Ardestani, Zhan Shu, Adnan Aziz, and Yi Xu. Coda: Exploiting admission flexibility for coding-agent serving. arXiv:2610.03088 (v1, 2 October 2026), 2026.

[59] Carlos E. Jimenez, John Yang, Alexander Wettig, Shunyu Yao, Kexin Pei, Ofir Press, and Karthik Narasimhan. SWE-bench: Can language models resolve real-world GitHub issues? In *International Conference on Learning Representations (ICLR 2024)*, 2024.

[60] Hao Kang, Ziyang Li, Weili Xu, Xinyu Yang, Yinfang Chen, Junxiong Wang, Beidi Chen, Tushar Krishna, Chenfeng Xu, and Simran Arora. ThunderAgent: A fast, simple, and program-aware agentic inference system. In *Proceedings of the 43rd International Conference on Machine Learning*, volume 306 of *Proceedings of Machine Learning Research*, pages 55630–55657, 2026. arXiv:2602.13692.

[61] Samuel Karlin and Howard M. Taylor. *A Second Course in Stochastic Processes*. Academic Press, New York, 1981. ISBN 978-0-12-398650-4.

[62] David G. Kendall. Some problems in the theory of queues. *Journal of the Royal Statistical Society: Series B*, 13(2):151–173, 1951. doi: 10.1111/j.2517-6161.1951.tb00080.x.

[63] K. Khanin, D. Khmelev, A. Rybko, and A. Vladimirov. Steady solutions for FIFO networks. *Moscow Mathematical Journal*, 1(3):407–419, 2001.

[64] Jinpyo Kim, Mingi Kwon, Younghoon Min, Jongryool Kim, and Jishen Zhao. Dynamic HBM repartitioning for multi-turn MoE serving. arXiv:2609.13537 (v1, 11 September 2026), 2026.

[65] Leonard Kleinrock. Time-shared systems: a theoretical treatment. *Journal of the ACM*, 14(2): 242–261, 1967. doi: 10.1145/321386.321388.

[66] Leonard Kleinrock and Simon S. Lam. Packet switching in a multiaccess broadcast channel: Performance evaluation. *IEEE Transactions on Communications*, 23(4):410–423, 1975. doi: 10.1109/TCOM.1975.1092814.

[67] P. R. Kumar. Re-entrant lines. *Queueing Systems*, 13 (1–3):87–110, 1993. doi: 10.1007/BF01158930.

[68] Woosuk Kwon, Zhuohan Li, Siyuan Zhuang, Ying Sheng, Lianmin Zheng, Cody Hao Yu, Joseph E. Gonzalez, Hao Zhang, and Ion Stoica. Efficient memory management for large language model serving with PagedAttention. In *Proceedings of the 29th Symposium on Operating Systems Principles (SOSP '23)*, pages 611–626. ACM, 2023. doi: 10.1145/3600006.3613165.

[69] Hanchen Li, Runyuan He, Qiuyang Mang, Qizheng Zhang, Huanzhi Mao, Xiaokun Chen, Hangrui Zhou, Huanchen Zhang, Alvin Cheung, Joseph Gonzalez, and Ion Stoica. Continuum: Efficient and robust multi-turn LLM agent scheduling with KV cache time-to-live. arXiv:2511.02230 (v7, 8 September 2026), 2025.

[70] Luchang Li, Shuaishuai Wang, Zhao Ruan, Dongfang Li, and Bozhao Gong. The KV cache working set: Online capacity planning for LLM inference systems. arXiv:2609.27746 (v1, 23 September 2026), 2026.

[71] Shuhuai Li, Shengdong Ye, Dongdong Ge, Yinyu Ye, and Jianghao Lin. TAO: Tool-aware joint scheduling for LLM-based agentic serving. arXiv:2610.37230 (v1, 27 October 2026), 2026.

[72] Chaofan Lin, Zhenhua Han, Chengruidong Zhang, Yuqing Yang, Fan Yang, Chen Chen, and Lili Qiu. Parrot: Efficient serving of LLM-based applications with semantic variable. In *18th USENIX Symposium on Operating Systems Design and Implementation (OSDI 24)*, pages 929–945, Santa Clara, CA, 2024. USENIX Association. arXiv:2405.19888.

[73] Banruo Liu, Haoran Qiu, Íñigo Goiri, Rodrigo Fonseca, Ricardo Bianchini, and Esha Choukse. Agentic coding in the wild: Characterizing GitHub Copilot traces at production scale. arXiv:2608.00101 (v1, 30 July 2026), 2026.

[74] Yipeng Liu, Yingqiang Zhang, Feifei Li, and Huanchen Zhang. Ask the tool, don't guess: Agent tool calls hold their progress, and the serving system should read it. arXiv:2609.18849, 2026.

[75] Yiyu Liu, Minlan Yu, and Juncheng Yang. When fancy eviction fails: Rethinking cache replacement for LLM prefix reuse. arXiv:2609.28870 (v2, 1 October 2026), 2026.

[76] Chengzhi Lu, Boxi Zhou, Yanying Lin, and Dmitrii Ustiugov. When cache pressure becomes a trap: Metastability in agent serving. arXiv:2611.02543, 2026. Submitted 2 November 2026.

[77] Michael Luo, Xiaoxiang Shi, Colin Cai, Tianjun Zhang, Justin Wong, Yichuan Wang, Chi Wang, Yanping Huang, Zhifeng Chen, Joseph E. Gonzalez, and Ion Stoica. Agentix: An efficient serving engine for LLM agents as general programs. In *23rd USENIX Symposium on Networked Systems Design and Implementation (NSDI 26)*, pages 2443–2459, Renton, WA, 2026. USENIX Association. arXiv:2502.13965 (as Autellix).

[78] Rupak Majumdar, Mahmoud Salamati, Nikhil Singh, and Sadegh Soudjani. Learning metastable dynamics. arXiv:2609.14712 (v1, 13 September 2026); HSCC '26, 2026.

[79] Valentina Martina, Michele Garetto, and Emilio Leonardi. A unified approach to the performance analysis of caching systems. In *IEEE INFOCOM 2014 – IEEE Conference on Computer Communications*,

pages 2040–2048, 2014. doi: 10.1109/INFOCOM.2014.6848145.

[80] Ben Maurer. Fail at scale. *ACM Queue*, 13(8):30–46, 2015. doi: 10.1145/2838344.2839461.

[81] Jiaying Meng and Bojie Li. Metronome: Bound the cache, keep the beat for real-time interaction model serving. arXiv:2607.02640 (v1, 2 July 2026), 2026.

[82] Utopia Meng, Unicornt Zhao, Derek Li, Goalen Gao, and Frank Du. Talaria: Session-aware serverless serving of hundred-billion-parameter LLMs. arXiv:2607.17181 (v1, 19 July 2026), 2026.

[83] John Nagle. Congestion control in IP/TCP internetworks. RFC 896, 6 January 1984; `https://www.rfc-editor.org/rfc/rfc896`, 1984.

[84] Randolph Nelson. Stochastic catastrophe theory in computer performance modeling. *Journal of the ACM*, 34(3):661–685, 1987. doi: 10.1145/28869.28878.

[85] Chengyi Nie, Nian Si, and Zijie Zhou. A queueing-theoretic framework for stability analysis of LLM inference with KV cache memory constraints. In *Proceedings of the 43rd International Conference on Machine Learning*, volume 306 of *Proceedings of Machine Learning Research*, pages 93016–93031, 2026. arXiv:2605.04595.

[86] Zaifeng Pan, Ajjkumar Dahyalal Patel, Yipeng Shen, Zhengding Hu, Yue Guan, Wan-Lu Li, Lianhui Qin, Yida Wang, and Yufei Ding. KVFlow: Efficient prefix caching for accelerating LLM-based multi-agent workflows. In *Advances in Neural Information Processing Systems 38 (NeurIPS 2025)*, pages 139912–139931, 2025. doi: 10.52202/085713-4208. arXiv:2507.07400.

[87] Zaifeng Pan, Yipeng Shen, Zhengding Hu, Zhuang Wang, Aninda Manocha, Zheng Wang, Zhongkai Yu, Yue Guan, and Yufei Ding. ScaleSim: Serving large-scale multi-agent simulation with invocation distance-based memory management. In *Proceedings of the 43rd International Conference on Machine Learning*, volume 306 of *Proceedings of Machine Learning Research*, pages 95898–95913, 2026. arXiv:2601.21473.

[88] Zaifeng Pan, Chris Wu, Zhengding Hu, Xinwei Qiang, Zhongkai Yu, and Yufei Ding. RR-Evict: Fine-grained prefix cache eviction beyond LRU for agentic LLM serving. arXiv:2609.32278 (v2, 2 October 2026; under review), 2026.

[89] Sungjoon Park, Changue Jung, Kyungno Joo, Mincheol Kang, Jaehyung Ahn, Sehwan Lee, and Sangjoon Kim. ServeTwin: A benchmark-validated simulator for distributed LLM architecture exploration. arXiv:2610.02732 (v1, 2 October 2026), 2026.

[90] Amber L. Puha, Alexander L. Stolyar, and Ruth J. Williams. The fluid limit of an overloaded processor sharing queue. *Mathematics of Operations Research*, 31(2):316–350, 2006. doi: 10.1287/moor.1050.0181.

[91] Ruoyu Qin, Zheming Li, Weiran He, Jialei Cui, Feng Ren, Mingxing Zhang, Yongwei Wu, Weimin Zheng, and Xinran Xu. Mooncake: Trading more storage for less computation — A KVCache-centric architecture for serving LLM chatbot. In *23rd USENIX Conference on File and Storage Technologies (FAST 25)*, pages 155–170, Santa Clara, CA, 2025. USENIX Association. Technical-report version: arXiv:2407.00079, titled "Mooncake: A KVCache-centric Disaggregated Architecture for LLM Serving".

[92] Qwen Team. Qwen2.5 technical report. arXiv:2412.15115, 2024.

[93] Rakibul Hasan Rajib, Mengxin Zheng, and Qian Lou. AgentServeSim: Serving-system simulation and policy search for LLM agent programs. arXiv:2606.09613 (v3, 5 September 2026), 2026.

[94] Martin I. Reiman. A multiclass feedback queue in heavy traffic. *Advances in Applied Probability*, 20(1): 179–207, 1988. doi: 10.2307/1427275.

[95] Maria Remerova, Sergey Foss, and Bert Zwart. Random fluid limit of an overloaded polling model. *Advances in Applied Probability*, 46(1):76–101, 2014. doi: 10.1239/aap/1396360104.

[96] Bianca Schroeder, Mor Harchol-Balter, Arun Iyengar, Erich Nahum, and Adam Wierman. How to determine a good multi-programming level for external scheduling. In *Proceedings of the 22nd International Conference on Data Engineering (ICDE '06)*, page 60, 2006. doi: 10.1109/ICDE.2006.78.

[97] Jay Shah, Ganesh Bikshandi, Ying Zhang, Vijay Thakkar, Pradeep Ramani, and Tri Dao. FlashAttention-3: Fast and accurate attention with asynchrony and low-precision. In *Advances in Neural Information Processing Systems 37 (NeurIPS 2024)*, pages 68658–68685, 2024. doi: 10.52202/079017-2193.

[98] Kunming Shao, Jierun Chen, Jiangnan Yu, Xiao-Hui Li, Chaofan Tao, Yanli Wang, Huanxin Lin, Kwang-Ting Cheng, Chi Ying Tsui, and Haoli Bai. EfficientAgent: What makes KV cache offloading work for concurrent agents? arXiv:2609.33762 (v1, 27 September 2026), 2026.

[99] Yannis Smaragdakis, Scott Kaplan, and Paul Wilson. EELRU: Simple and effective adaptive page replacement. In *Proceedings of the 1999 ACM SIGMETRICS International Conference on Measurement and Modeling of Computer Systems*, pages 122–133, 1999. doi: 10.1145/301453.301486.

[100] M. S. Squillante and E. D. Lazowska. Using processor-cache affinity information in shared-memory multiprocessor scheduling. *IEEE Transactions on Parallel and Distributed Systems*, 4 (2):131–143, 1993. doi: 10.1109/71.207589.

[101] Shriniwas Ramesh Suram. Cacheable by design? Training mixture-of-experts routers for locality against the edge memory-bandwidth wall: A pre-registered negative result with a systems measurement study. arXiv:2608.18261 (v1, 18 August 2026), 2026.

[102] SWE-agent. mini-SWE-agent. GitHub repository, release v2.0.0 (11 February 2026); `https://github.com/SWE-agent/mini-swe-agent`, 2026.

[103] Lajos Takács. A single-server queue with feedback. *Bell System Technical Journal*, 42(2):505–519, 1963. doi: 10.1002/j.1538-7305.1963.tb00510.x.

[104] Shubham Tiwari, Tapan Chugh, Nash Rickert, Simon Peter, Ratul Mahajan, and Haiying Shen. CacheWise: Understanding workloads and optimizing KVCache management for efficiently serving LLM coding agents. arXiv:2606.16824, 2026.

[105] J. L. van den Berg, O. J. Boxma, and W. P. Groenendijk. Sojourn times in the M/G/1 queue with deterministic feedback. *Communications in Statistics. Stochastic Models*, 5(1):115–129, 1989. doi: 10.1080/15326348908807101.

[106] Pieter van Rooyen. First-order recoverability collapse in self-referential information decoders: The operating loop of an AI system as a driven nonequilibrium steady state. arXiv:2606.24861 (v3; v1 23 June 2026), 2026.

[107] Michael Wang, Yikang Yue, Shaobo Li, Yirui Eric Zhou, Chen Wang, and Jian Huang. Benchmarking LLM serving systems for agentic AI workloads with XPerf. arXiv:2608.20370, 2026.

[108] Yifei Wang, Hancheng Ye, Yechen Xu, Cong Guo, Chiyue Wei, Qinsi Wang, Dongting Li, Tingjun Chen, Hai "Helen" Li, Danyang Zhuo, and Yiran Chen. MARS: Efficient, adaptive co-scheduling for heterogeneous agentic systems. arXiv:2604.26963 (v2, 15 June 2026), 2026.

[109] M. V. Wilkes. The dynamics of paging. *The Computer Journal*, 16(1):4–9, 1973. doi: 10.1093/comjnl/16.1.4.

[110] Fangzhou Wu, Sandeep Silwal, and Qiuyi (Richard) Zhang. Randomization boosts KV caching, learning balances query load: A joint perspective. In *International Conference on Learning Representations (ICLR 2026)*, 2026. arXiv:2601.18999.

[111] Tian Xia, Hanchen Li, Zhifei Li, Xiaokun Chen, Hao Kang, Yifan Qiao, Yi Xu, and Ion Stoica. Idleness is relative: Exploiting tool-call idle windows for offloading in agentic systems with MORI. arXiv:2606.00866, 2026.

[112] Bing Xie, Zhipeng Wang, Masahiro Tanaka, and Zhen Zheng. PEEK: Predictive queue-informed KV cache management for LLM serving. arXiv:2607.02525 (v2, 12 September 2026; under review), 2026.

[113] John Yang, Carlos E. Jimenez, Alexander Wettig, Kilian Lieret, Shunyu Yao, Karthik Narasimhan, and Ofir Press. SWE-agent: Agent-computer interfaces enable automated software engineering. In *Advances in Neural Information Processing Systems 37 (NeurIPS 2024)*, pages 50528–50652, 2024. doi: 10.52202/079017-1601. arXiv:2405.15793.

[114] Heyuan Yao, Chutong Gao, Yuan Lyu, Izzy Grosof, and David Simchi-Levi. Multi-turn LLM conversations under the least-recently-used policy: Mean-field asymptotics and hit ratio approximation. arXiv:2609.02027, 2026.

[115] Zihao Ye, Lequn Chen, Ruihang Lai, Wuwei Lin, Yineng Zhang, Stephanie Wang, Tianqi Chen, Baris Kasikci, Vinod Grover, Arvind Krishnamurthy, and Luis Ceze. FlashInfer: Efficient and customizable attention engine for LLM inference serving. In *Proceedings of Machine Learning and Systems 7 (MLSys 2025)*, 2025.

[116] Tokumi Yokohira and Hideo Miyahara. Analysis of catastrophic phenomena in a multiprogramming system. *Systems and Computers in Japan*, 20(6): 60–68, 1989. doi: 10.1002/scj.4690200607.

[117] Gyeong-In Yu, Joo Seong Jeong, Geon-Woo Kim, Soojeong Kim, and Byung-Gon Chun. Orca: A distributed serving system for Transformer-based generative models. In *16th USENIX Symposium on Operating Systems Design and Implementation (OSDI 22)*, pages 521–538, Carlsbad, CA, 2022. USENIX Association.

[118] Lingfan Yu, Jinkun Lin, and Jinyang Li. Stateful large language model serving with Pensieve. In *Proceedings of the Twentieth European Conference on Computer Systems (EuroSys '25)*, pages 144–158. ACM, 2025. doi: 10.1145/3689031.3696086. arXiv:2312.05516.

[119] Yichao Yuan, Mosharaf Chowdhury, and Nishil Talati. KAIROS: Stateful, context-aware power-efficient agentic inference serving. arXiv:2604.16682 (v1, 17 April 2026), 2026.

[120] Yichao Yuan, Ankita Nayak, Souvik Kundu, and Nishil Talati. Agentic AI workload characterization. In *Proceedings of the 2026 IEEE International Symposium on Workload Characterization (IISWC)*, 2026. arXiv:2605.26297 (v2, 21 September 2026), listed there as "Agentic AI Workload Characteristics".

[121] Rui Zhang, Chaeeun Kim, Shaoting Feng, Kuntai Du, Yuhan Liu, Yi Zhong, Cheng-Wei Ching, Junchen Jiang, and Liting Hu. Learning agent execution for KV-cache management in agentic serving. arXiv:2608.14624, 2026.

[122] Lianmin Zheng, Liangsheng Yin, Zhiqiang Xie, Chuyue Sun, Jeff Huang, Cody Hao Yu, Shiyi Cao, Christos Kozyrakis, Ion Stoica, Joseph E. Gonzalez, Clark Barrett, and Ying Sheng. SGLang: Efficient execution of structured language model programs. In *Advances in Neural Information Processing Systems 37 (NeurIPS 2024)*, pages 62557–62583, 2024. doi: 10.52202/079017-2000.

[123] Kan Zhu, Mathew Jacob, Chenxi Ma, Yi Pan, Stephanie Wang, Arvind Krishnamurthy, and Baris Kasikci. TraceLab: Characterizing coding agent workloads for LLM serving. arXiv:2606.30560 (v2, 30 June 2026), 2026. Trace release v0.0.2, 24 July 2026: `https://github.com/uw-syfi/TraceLab`.

A Model F: proofs and remarks

Model F. Fix $K \in \mathbb{N}$, costs $c_1, \dots, c_K > 0$ (all-miss GPU seconds of turn k), and $1 = G_1 \geq G_2 \geq \cdots \geq G_K > 0$ with $G_{K+1} = 0$ ($G_k = P(T \geq k)$). Write

$$p_k = G_k - G_{k+1}, \qquad r_k = G_{k+1}/G_k,$$
$$a_k = \lambda c_k G_k, \qquad \rho = \textstyle\sum_k a_k = \lambda/\lambda_{\text{miss}},$$

with $\lambda_{\text{miss}} = 1/\sum_k c_k G_k$. A session whose next turn is k has remaining work $R_k = \sum_{j \geq k} c_j G_j / G_k$, so that $R_1 = 1/\lambda_{\text{miss}}$ and $R_k = c_k + r_k R_{k+1}$. The model assumes:

(F1) every turn misses, so turn k costs c_k;
(F2) the server does one GPU second of work per second while work is pending;
(F3) requests complete in the order in which they joined;
(F4) a completed turn $k < T$ rejoins at once as turn $k+1$, so a fraction r_k of the class-k mass completing at any time rejoins as class $k+1$;
(F5) new sessions join as class-1 mass at rate λ;
(F6) at time 0 a pending mass $m_k^0 \geq 0$ of each class is served first, with $V_0 = \sum_k c_k m_k^0 > 0$, through absolutely continuous class-completion functions C_k^0 on $[0, V_0]$ with $\sum_k c_k C_k^0(t) = t$.

A *solution* consists of non-decreasing absolutely continuous J_k, C_k (joins and completions after time 0, with $C_k^0(0) = 0$) on $[0, \tau)$ such that

- $J_1(t) = \lambda t$ and $J_{k+1} = r_k C_k$;
- $C_k = C_k^0$ on $[0, V_0]$, and $C_k(f(u)) = m_k^0 + J_k(u)$ for $u \geq 0$ (FIFO);
- $\sum_k c_k C_k(t) = t$ for $t < \tau$ (F2);
- the pending work $V(u) = \sum_k c_k \pi_k(u)$ is positive on $[0, \tau)$;
- either $\tau = \infty$ or $V(t) \to 0$ as $t \uparrow \tau$.

Here $f(u) = u + V(u)$ and $\pi_k = m_k^0 + J_k - C_k$. The last condition makes $\tau \leq \infty$ the time at which the queue first empties, rather than any earlier cut-off. With zero think time every session present has one pending request, so the number in the system is $N = \sum_k \pi_k$. The remaining work is $V_{\text{tot}} = \sum_k \pi_k R_k$, and the departures are $\text{Dep}(t) = \sum_k m_k^0 + \lambda t - N(t)$.

On the engine, (F1) is the measured zero hit fraction of the trap and (F2) its saturated GPU. (F3) is request-level FCFS admission (Proposition 6), up to the $M/E_S \approx 28$ requests that run concurrently. For (F4), the 5 s tool time is short against cycles of 166–516 s, and including it changes the window statistics of the fluid by less than 10^{-3} (`analysis/theory/icml/support.py`). The costs are $c_k = t_k^m + \delta$: the calibrated miss prefill of §H.1 plus the all-miss per-turn decode share δ, chosen so that $\sum_k (G_k/E[T]) c_k = 1/\nu_b$. Then λ_{miss} above equals the model's μ_b (Proposition 2(a)).

Lemma 1 (Perron root)**.** *$\varphi(x) = \sum_k a_k x^{-k}$ decreases strictly from ∞ to 0 on $(0, \infty)$, and $\varphi(1) = \rho$. Hence $\varphi(z) = 1$ has a unique root $z > 0$, with $z > 1$ if and only if $\rho > 1$.*

Lemma 2 (well-posedness, work, orbit recursion)**.** *Under (F1)–(F6):*

(i) model F has exactly one solution;
(ii) while the server is busy, $f(u) = V_0 + W(u)$ with $W = \sum_k c_k J_k$, and f is continuous and strictly increasing;
(iii) while busy, $V_{\text{tot}}(t) = V_{\text{tot}}(0) + (\rho - 1)t$.
(iv) For $u_0 \in [0, V_0)$, let $u_{n+1} = f(u_n)$ and $\Delta_n = u_{n+1} - u_n$. Then

$$\Delta_n = \sum_{k=1}^{\min(n,K)} a_k \Delta_{n-k} + h_n(u_0),$$
$$h_n(u_0) = \sum_{k=n+1}^{K} c_k \frac{G_k}{G_{k-n}} \pi_{k-n}(u_0),$$

so that $h_0 = V(u_0)$ and $h_n = 0$ for $n \geq K$. Each h_n is continuous in u_0, and $\sum_n h_n(u_0) = V_{\text{tot}}(u_0)$.
(v) For $n \geq 1$, $\pi_k(u_n) = \lambda G_k \Delta_{n-k}$ if $k \leq n$, and $\pi_k(u_n) = (G_k/G_{k-n})\pi_{k-n}(u_0)$ otherwise. The requests completed in $(u_n, u_{n+1}]$ are those pending at u_n.

Proof. (ii). If the server is busy on $[0, f(u)]$, then by (F2) it has completed s units of work by each time s in that interval. By (F3), the request joining at u completes once the work joined before it, $V_0 + W(u)$, is done. So $f(u) = V_0 + W(u)$, which is continuous. Since $W' \geq \lambda c_1 > 0$ almost everywhere, f is strictly increasing, and $f(0) = V_0$.

(i). Put $b_0 = 0$, $b_1 = V_0$ and $b_{n+1} = f(b_n)$. On $[0, b_1]$ the completions are C^0, which give J on $[0, b_1]$. Suppose J is known on $[0, b_n]$. Then:

- $f = V_0 + W$ is known on $[b_{n-1}, b_n]$ and maps it onto $[b_n, b_{n+1}]$;
- FIFO gives $C_k(f(u)) = m_k^0 + J_k(u)$ on $[b_n, b_{n+1}]$;
- re-entry extends $J_{k+1} = r_k C_k$ to $[b_n, b_{n+1}]$.

Each step is forced by FIFO, re-entry, the arrivals and (F2); this proves uniqueness. For existence, two facts show that the construction is a solution. First, $\sum_k c_k C_k(f(u)) = V_0 + W(u) = f(u)$, so the server works at unit rate and the constructed f equals $u + V(u)$. Second, $V(f(v)) = W(f(v)) - W(v) \geq \lambda c_1 V(v) > 0$, so $b_{n+1} > b_n$. Absolute continuity follows from $C_k' = J_k'(u)/f'(u) \leq J_k'(u)/(\lambda c_1)$. Moreover $V \geq \eta V_{\text{tot}}$ with $\eta = \min_k c_k/R_k > 0$, because both are linear in $\pi \geq 0$. By (iii), which needs only the unit work rate:

- if $\rho \geq 1$, then $V \geq \eta V_{\text{tot}}(0) > 0$ throughout, $b_{n+1} - b_n \geq \eta V_{\text{tot}}(0)$, and $b_n \to \infty$;
- if $\rho < 1$, then b_n increases to the time at which V_{tot} vanishes (Theorem 1(a)).

(iii). With $j_k = J_k'$ and $\dot{C}_k = C_k'$, we have $\sum_k c_k \dot{C}_k = 1$, $j_1 = \lambda$ and $j_{k+1} = r_k \dot{C}_k$. Hence

$$V_{\text{tot}}' = \textstyle\sum_k R_k(j_k - \dot{C}_k) = \lambda R_1 + \sum_k \dot{C}_k(r_k R_{k+1} - R_k)$$
$$= \lambda R_1 - \textstyle\sum_k c_k \dot{C}_k = \rho - 1.$$

(iv), (v). Let $\Delta J_k(n) = J_k(u_n) - J_k(u_{n-1})$. By (ii), $\Delta_n = W(u_n) - W(u_{n-1}) = \sum_k c_k \Delta J_k(n)$ for $n \geq 1$, and $\Delta_0 = V(u_0) = \sum_k c_k \pi_k(u_0)$. For class 1, $\Delta J_1(n) = \lambda \Delta_{n-1}$. For $k \geq 2$ and $n \geq 2$, FIFO gives $C_{k-1}(u_n) = m_{k-1}^0 + J_{k-1}(u_{n-1})$ and the same at u_{n-1}, so $\Delta J_k(n) = r_{k-1} \Delta J_{k-1}(n-1)$. For $n = 1$, $C_{k-1}(u_1) - C_{k-1}(u_0) = \pi_{k-1}(u_0)$. Unrolling with $\prod_{j=k-n}^{k-1} r_j = G_k/G_{k-n}$ gives (v) and then (iv).

The pending mass at u_n is the joins in $(u_{n-1}, u_n]$, because the completions by $u_n = f(u_{n-1})$ are the initial mass plus the joins by u_{n-1}. For the sum, substitute $j = k - n$:

$$\sum_n h_n = \sum_j \pi_j \sum_{n\ge 0} c_{j+n} G_{j+n}/G_j = \sum_j \pi_j R_j = V_{\text{tot}}.$$

□

Lemma 3 (finite-memory renewal)**.** *Let $A(s) = \sum_{k=1}^{K} b_k s^k$ with $b_k \ge 0$, $b_1 > 0$ and $A(1) = 1$. Let $y_n = \sum_{k=1}^{\min(n,K)} b_k y_{n-k} + g_n$, with $g_n \ge 0$, $g_0 > 0$ and $g_n = 0$ for $n \ge K$. Then $y_n = L + \epsilon_n$, where $L = \sum_n g_n / \sum_k k b_k > 0$ and $|\epsilon_n| \le C_r \vartheta^n$ for some $\vartheta < 1$ that depends only on (b_k), with C_r linear in (g_n).*

Proof. As formal power series, $\sum_n y_n s^n = g(s)/(1 - A(s))$, where $g(s) = \sum_{n<K} g_n s^n$. The root $s = 1$ of $1 - A$ is simple, since $A'(1) > 0$. If $|s| < 1$, then $|A(s)| \le A(|s|) < 1$. If $|s| = 1$ and $A(s) = 1 = \sum_k b_k$, then $s^k = 1$ whenever $b_k > 0$, in particular $s = 1$. So every other root lies outside the closed unit disk, at modulus at least $\vartheta_0^{-1} > 1$. Fix $\vartheta \in (\vartheta_0, 1)$. Partial fractions give $g(s)/(1 - A(s)) = L/(1 - s) + Q(s)$. Here $L = g(1)/A'(1)$ is the coefficient of $1/(1 - s)$, that is, minus the residue at $s = 1$, and Q, a rational function plus a polynomial, is analytic for $|s| < \vartheta_0^{-1}$. Cauchy's estimates on $|s| = \vartheta^{-1}$ finish the proof. This is the finite-memory case of the discrete renewal theorem [42]. □

Proof of Theorem 1. (a), $\rho < 1$. Take $u_0 = 0$. Summing the recursion, whose terms are all nonnegative, gives $\sum_{n\le M} \Delta_n \le V_{\text{tot}}(0) + \rho \sum_{n\le M} \Delta_n$, and in the limit $\sum_n \Delta_n = V_{\text{tot}}(0)/(1-\rho)$. Thus $b_n \uparrow \tau = V_{\text{tot}}(0)/(1 - \rho)$. For every orbit start $u_0 \in [0, V_0)$, each $\Delta_n(u_0)$ is positive, since $\Delta_n \ge a_1 \Delta_{n-1}$. Every $t < \tau$ lies on such an orbit, so the server is busy on $[0, \tau)$, and $V(b_n) = \Delta_n \to 0$.

Without arrivals ($\lambda = 0$, used for SHED), the orbit argument does not apply. There, $V'_{\text{tot}} = -1$ and $V \ge \eta V_{\text{tot}}$ give $\tau = V_{\text{tot}}(0)$ directly.

(b), $\rho = 1$. Lemma 3 with $b_k = a_k$ gives $\Delta_n(u_0) \to V_{\text{tot}}(u_0)/\sum_k k a_k$, uniformly in $u_0 \in [0, V_0]$. Here $V_{\text{tot}}(u_0) = V_{\text{tot}}(0)$ and $\sum_k k a_k = \bar{k}_c$. Every $t \ge V_0$ equals $f^n(u_0)$ for a unique $u_0 \in [0, V_0)$ and $n \ge 1$. So $V(t) \to V_{\text{tot}}(0)/\bar{k}_c$, and by (v), $N \to \lambda E[T] V_{\text{tot}}(0)/\bar{k}_c$.

(c), $\rho > 1$. Apply Lemma 3 to $y_n = \Delta_n z^{-n}$, $b_k = a_k z^{-k}$ and $g_n = h_n z^{-n}$. It gives $\Delta_n = z^n (L(u_0) + \epsilon_n)$ with L continuous and positive on $[0, V_0]$ (since $h_0 = V(u_0) > 0$) and $|\epsilon_n| \le C\vartheta^n$ uniformly. At $t = u_n(u_0)$,

$$t = u_0 + \textstyle\sum_{j<n} \Delta_j = \dfrac{L z^n}{z-1}\big(1 + o(1)\big),$$
$$V(t) = \Delta_n = L z^n \big(1 + o(1)\big),$$

so $V(t)/t \to z - 1$ uniformly. The relative error is $O(n \max(\vartheta, 1/z)^n)$. As $t \to \infty$, the generation index n of t tends to infinity because every b_n is finite. By (v), $N(t) = \lambda \sum_k G_k \Delta_{n-k}$, and the identity $(z-1)\sum_k G_k z^{-k} = 1 - E[z^{-T}]$ gives $N(t)/t \to \lambda(1 - E[z^{-T}])$. The departure limit follows from $\text{Dep} = \sum_k m_k^0 + \lambda t - N$. By (v), the composition limit holds for the pending requests, and for the requests completed over the next cycle, which are the same. Over a cycle $(t, f(t)]$, any per-turn weight P_k is processed at the average rate $\sum_k P_k \pi_k / \sum_k c_k \pi_k$.

(d), self-similarity. $f(u)/u = 1 + V(u)/u \to z$, and $f^m(u)/u \to z^m$ by induction on m. A session that arrives at u joins as turn 1 at u and, with zero think time and FIFO, completes turn m at $f^m(u)$. The centred form follows from the virtual-origin argument below: $u_n + u^* = w_n$ with $u^* = V_{\text{tot}}(0)/(\rho - 1)$, and $w_{n+m}/w_n \to z^m$.

(e). $F(x, \rho) = \rho \sum_k \omega_k x^{-k} - 1$, with $\omega_k = c_k G_k / \sum_j c_j G_j$, satisfies $F(1, 1) = 0$ and $\partial_x F(1, 1) = -\bar{k}_c$. So $z'(1) = 1/\bar{k}_c$. Then $E[z^{-T}] = 1 - (z - 1)E[T] + O((z - 1)^2)$, so $\alpha = \lambda_{\text{miss}}(E[T]/\bar{k}_c)(\rho - 1) + O((\rho - 1)^2)$.

(d), continued: the virtual origin and the remaining work. This sharpening was pointed out by an independent referee. For $u \ge b_{K-1}$, all class-k descendants of the initial requests have joined, and the arrivals' class-k requests joined by u are those whose first request joined by $f^{-(k-1)}(u)$. Hence

$$f(u) = V_{\text{tot}}(0) + \sum_k a_k f^{-(k-1)}(u),$$

and along every orbit $u_{n+1} = V_{\text{tot}}(0) + \sum_k a_k u_{n+1-k}$. The constant $V_{\text{tot}}(0)/(1-\rho)$ is a particular solution, so $w_n = u_n - V_{\text{tot}}(0)/(1-\rho)$ solves the homogeneous recursion. For $\rho < 1$ this gives $u_n \to \tau$ at once. For $\rho > 1$, $w_n = Bz^n + O((r+\epsilon)^n)$, with r the largest modulus among the other roots. Since $V_{\text{tot}}(u_n) = (\rho - 1) w_n$,

$$V(u_n) = \frac{z-1}{\rho - 1} V_{\text{tot}}(u_n) + O((r + \epsilon)^n),$$

that is, $V(u_n) = \gamma\,(u_n + u^*) + O((r + \epsilon)^n)$. In all eight cells, over $\rho \in [1.01, 6.6]$, $r = 0.946$–$0.966 < 1$, so the deviation vanishes absolutely. Correspondingly, $f^m(u) + u^* \approx z^m(u + u^*)$. The transient decays by $\vartheta = r/z = 0.84$–0.95 per generation, and the registered window opens 33–37 generations after the burst. So we compare with the exact fluid as well as with the limits. □

Proof of Theorem 2. The product. Since $\lambda = 1/\sum_k c_k G_k z^{-k}$, we have $D/\lambda_{\text{miss}} = E[z^{-T}] \sum_k c_k G_k / \sum_k c_k G_k z^{-k}$. Multiplying and dividing by $\sum_k G_k z^{-k}$ and by $E[T] = \sum_k G_k$ gives $H\Gamma$.

The factor Γ. The ratio ν^z_k/ν_k is proportional to z^{-k}, which is strictly decreasing, so ν^z is below ν in the likelihood-ratio order. For non-decreasing c this gives $E_{\nu^z}[c] \le E_\nu[c]$. By Abel summation,

$$E_\nu[c] - E_{\nu^z}[c] = \sum_{k<K} \big(F_{\nu^z}(k) - F_\nu(k)\big)(c_{k+1} - c_k),$$

in which every difference of distribution functions is positive. So equality holds only for constant c. The same argument applied to $z' > z$ shows that Γ is non-decreasing in z.

The factor H. Since $\sum_k G_k z^{-k} = (1 - E[z^{-T}])/(z - 1)$, $H \ge 1$ if and only if $E[z^{-T}](1 + E[T](z - 1)) \ge 1$. For a geometric T with mean m, $E[z^{-T}] = 1/(1 + m(z - 1))$.

For $T = \min(\text{Geometric}(1-q), K)$ we have $E[z^{-T}] = (1-q)\sum_k G_k z^{-k} + qG_K z^{-K}$ and $(1-q)E[T] = 1-q^K$. Hence

$$H = 1 - q^K\Big(1 - E[T]\Big/\sum_k G_k z^{K-k}\Big).$$

For $z > 1$ and $K \geq 2$, the sum in the denominator exceeds $E[T]$ and increases with z. So H lies in $(1-q^K, 1)$ and is non-increasing in z.

Near the threshold. The expansion follows from Theorem 1(e), with $\alpha = \lambda_{\text{miss}}(E[T]/\bar{k}_c)(\rho-1) + O((\rho-1)^2)$, and from $D = \lambda - \alpha$. When $\bar{k}_c = E[T]$, the sign of the premium is decided at second order.

Monotonicity. Γ is strictly increasing for non-constant non-decreasing c (by the Abel argument), and it tends to $E_\nu[c]/c_1$ as $z \to \infty$. If that limit exceeds $1/(1-q^K)$, there is a unique z_1 with $\Gamma(z_1) = 1/(1-q^K)$. For $z \geq z_1$, $H\Gamma > (1-q^K)\Gamma(z_1) = 1$. For $z \in [1+10^{-12}, z_1]$ in our cells, the monotonicity of H and Γ bounds the premium below on each bracket $[z_i, z_{i+1}]$ by $H(z_{i+1})\Gamma(z_i) - 1$. That bound is positive on a geometric grid of 53 brackets in all eight cells (`analysis/theory/icml/support.py`, evaluated in floating point). □

Proof of Corollary 3. The state at the switching time t_0 is an admissible initial condition (F6), and $V(t_0) > 0$. The claim then follows from Theorem 1(a)–(c) applied with rate λ'. If $\lambda' \in (\lambda_{\text{miss}}, D(\lambda))$, then $\rho' > 1$, so by Lemma 2(iii) $V_{\text{tot}}(t) \geq V_{\text{tot}}(t_0)$, and $V \geq \eta V_{\text{tot}}(t_0) > 0$: the queue never empties, and it grows by Theorem 1(c). At $\rho' = 1$ the same bound holds, and the backlog tends to $\lambda_{\text{miss}} E[T] V_{\text{tot}}(t_0)/\bar{k}_c$. □

Proof of Corollary 4.

Divide Lemma 1's equation by $\sum_j c_j G_j$. The other quantities are explicit functions of z, G and ω. Under $c \mapsto c/s$, ω is unchanged and $\lambda_{\text{miss}} \mapsto s\lambda_{\text{miss}}$. □

Remarks.

- *Processor sharing.* The layer RR of §H.3 advances every session at $1/V(t)$ turns per second. Use the clock $x = \int_0^t ds/V(s)$ and the continuous renewal theorem; the kernel is a step function with compact support, hence non-lattice. This yields the Euler–Lotka equation $\lambda \sum_k c_k G_k \int_{k-1}^{k} e^{-\alpha_{\text{PS}} a}\, da = 1$ for the growth exponent α_{PS}, the backlog growth $\lambda(1 - E[e^{-\alpha_{\text{PS}} T}])$, departures $\lambda E[e^{-\alpha_{\text{PS}} T}]$ and the cycle slope α_{PS}. In overloaded processor sharing with service times S the departures are $\lambda E[e^{-\alpha_{\text{PS}} S}]$, with α_{PS} its own growth exponent, which can exceed $1/E[S]$: the youth premium of Theorem 2 is the visit-indexed analogue of that property. This is the Crump–Mode–Jagers structure of overloaded processor sharing [47, 56, 90], with reproduction rate $\lambda c_{\lfloor a \rfloor + 1}$ at age a; we do not write out the details. Near the threshold, the backlog growth over $\lambda - \lambda_{\text{miss}}$ tends to $E[T]/(\bar{k}_c - \frac{1}{2})$, a half-turn offset from model F. On the 300k cell, $\alpha/(\lambda - \lambda_{\text{miss}})$ is 0.647 and 0.666 under processor sharing at 1.35 and 1.65 λ_{ref}, against 0.634 and 0.653 for model F.
- *Stochastic version.* Take Poisson arrivals and any work-conserving order. The all-miss busy period started from realized remaining works w_i is the total work of a Galton–Watson tree, finite exactly when its progeny is. It ends with probability $\exp(-\lambda(1-q)\sum_i w_i)$, where q is the least root of $q = E[e^{-\lambda W(T)(1-q)}]$; the workload ever falls to a level w_b with probability $\exp(-\lambda(1-q)(\sum_i w_i - w_b))$ [62]. Take w from the fluid 3000 s after the registered burst on the 300k cell (`support.py`, `kendall_numbers`). Emptying then has probability 0.35 at $\rho = 1.01$, 0.12 at 1.02, 4×10^{-3} at 1.05, 10^{-5} at 1.10, 4×10^{-23} at 1.35 and 2×10^{-54} at 1.65. These are orders of magnitude (a realized w fluctuates around the fluid value), and hits return before the queue empties, so they are not bounds on a spontaneous exit; they say it matters only within a few percent of λ_{miss}. The branching description is classical and claimed as such.
- *Steady solutions of FIFO re-entrant lines.* Model F is a single-station re-entrant line [67] in overload. Khanin et al. [63] study steady (constant-flow) solutions of fluid FIFO re-entrant lines from the empty state, with stage-dependent service times. At an overloaded station the steady flows satisfy $x_s = x_{s-1}/\sum_j x_{j-1} v_j$; at a single station with n fixed stages this gives $x_s = a^s$ with $\sum_j v_j a^j = 1$, which is Lemma 1's equation with $a = 1/z$ and $T \equiv n$, and the steady flows give part (c)'s gap slope, composition and departure rate; a closing remark extends their uniqueness theorem to a fixed fraction of the flow leaving at each node, which in a fluid is our random T, and their normalization gives Corollary 4. They prove existence, uniqueness for Kelly-type lines and non-uniqueness examples for two stations, and leave the uniqueness of general (non-steady) trajectories open. Relative to theirs, our contribution is the renewal recursion along FIFO orbits from an arbitrary initial state, hence the convergence of every trapped trajectory to the steady regime with an exact virtual origin and rate, and the turn-count and cost-growth factors of Theorem 2; Corollary 3 is their operational reading with the classical drain condition. The critical case, Theorem 1(b), is the fluid counterpart of heavy-traffic state-space collapse in multiclass FIFO feedback queues [26, 94]. Overloaded multiclass FIFO queues with abandonment and no re-entry have fluid limits [57]; fluid metastability of queues with load-dependent service is posed by Dong [36]; and within-request KV growth under continuous batching is analysed by Ao et al. [5], a different instability.
- *Think time.* With a 5 s think time (the workload's mean tool time) the exact fluid's statistics over the registered window agree with zero think time to within 0.02% (backlog slope, completion rate, mean served prompt); the mean cycle is 5 s shorter and its slope the same.
- *How fast the limits are reached.* The transient shrinks by $\vartheta = r/z = 0.84$–0.95 per generation over $\rho \in [1.01, 6.6]$. At 300k the registered window starts about 33 (1.65 λ_{ref}) or 37 (1.35 λ_{ref}) generations after the burst, so a transient of order $\vartheta^{35} \approx 0.1$ remains; the asymptotic values and the exact fluid over the window differ by about 1% for the composition and by 4–12% for the backlog slope. No

general rate is claimed: a nearly periodic kernel converges slowly (with $T = 4$ always, the fluid is still 3% off after 1000 generations).

Corollary 3 illustrated. All-miss fluid of the 300k cell at 1.65 λ_{ref}, where $D = 1.223\lambda_{\text{miss}}$; arrivals cut at 5000 s, when the backlog is 251 sessions (`notes/THEORY_ICML_2026-11.md`, §6.7; reproduced with independent code by a referee):

cut to	backlog after the cut
$1.18\lambda_{\text{miss}}$	dips to 250.7 (−0.3%), then grows to 445 by 30,000 s
$1.10\lambda_{\text{miss}}$	dips to 246 (−2%), then grows to 352
$1.05\lambda_{\text{miss}}$	dips to 241 (−4%), then grows to 295
$1.02\lambda_{\text{miss}}$	dips to 237.6 (−5.5%), then grows to 261
$1.00\lambda_{\text{miss}}$	undershoots to 234.6 (−6.7%), settles at 238.7 (Theorem 1(b))
$0.90\lambda_{\text{miss}}$	drains slowly; empty at 59,655 s, the busy period $V_{\text{tot}}/(1-\rho')$

In the fluid, an operator who sets arrivals between λ_{miss} and the trapped throughput sees at most a brief dip, then renewed growth; on one arrival path the backlog can keep falling slowly for the whole run (CUT-A seed 1).

Numerical checks and data. The tests in `tests/test_theory_icml.py` (20) cover:

- the root and its sign;
- the decomposition, H and Γ;
- the absence of a premium for a geometric T with constant costs;
- the near-threshold coefficients;
- $\sum_n h_n = V_{\text{tot}}$;
- the critical limit;
- the orbit recursion on the simulated fluid (residual below 2×10^{-3}, from discretization);
- convergence of the fluid to the asymptotics;
- the busy period.

`analysis/theory/icml/run_check.py` produces `results/theory/icml/trap_check.md` (Appendix B). That file covers all 57 stuck runs of the E2 protocol: SGLang 300k with and without the waiting-prefix refresh, BASIN, SHED, TOOLSLOW, LPM beyond its fallback, the native pool, vLLM, the H200 with 600k, and Llama-3.1-8B. It also covers the 13 unstable E0b runs, including the pool sweep and the 300k H200. `analysis/theory/icml/support.py` computes every summary number quoted in the main text into `results/theory/icml/support.json`. With arrivals stopped at 1800 s, the fluid reaches n_b after 2,020 s and empties after 3,180 s, consistent with the registered SHED outcomes (600 s stuck, 3600 s good). This is a retrodiction, and it does not discriminate: any drain time between 600 and 3,600 s would fit.

Frozen predictions. Tag `icml-trap-pred` (`6b47a6c`) froze `configs/icml_trap_predict.yaml` before any later run existed. For eight cells it lists the asymptotic quantities at loads from 1.1 to 6.5 λ_{ref}, the E2-protocol fluid and stochastic slope-test power, and per-seed plug-ins. The scoring rules S1–S5 are stated in `notes/PREDICTIONS_icml_trap.md`.

B Model F against the engine: full tables

Inputs and definitions. Each cell's costs come from its frozen cell model (`analysis/theory/cells/*.yaml`): the calibrated miss prefill of turn k plus the all-miss decode share, chosen so that $1/\sum_k c_k G_k$ equals the first-principles model's μ_b. vLLM, the H200 and Llama take one speed factor fitted to their own E0a token rate, as in the paper's earlier predictions. A run is stuck if its follow-up hit fraction over its window is below 0.2: [5700, 8700) s for E2-protocol runs, [1500, 3000) s for unstable from-empty (E0b) runs. The composition statistic is the mean prompt of the turns completed in the window; the gap slope is the least-squares slope, over the window, of the 300 s medians of the gap between a turn's completion and the same session's previous one; completions and backlog slope are over the window. Source: `results/theory/icml/trap_check.md` and `.json`, produced by `analysis/theory/icml/run_check.py`; summary numbers by `support.py` into `support.json`. An AI referee recomputed six statistics for 22 of the runs from the raw files with independent code and matched them to five or more digits. The gap slope is regressed on the turn's completion time, so its model-F constant is $\gamma/z = 1 - 1/z$ (`analysis/theory/icml/gap_slope_completion_time.py`); the theory note's tables compare it with γ, which is 1–12% larger at these loads.

From-empty collapses. The 13 runs that lost the good state from empty are younger traps, observed over [1500, 3000) s:

cell, rate	ρ	$\bar{L}$ meas. / pred.	gap slope / $1 - 1/z$	D/λ_{ref} / pred.	backlog / pred.
SGLang 300k 2.5	2.49	7,755 / 7,274	0.058 / 0.045	1.42 / 1.46	0.94 / 0.70
SGLang 300k 3.0	2.99	6,613 / 6,754	0.078 / 0.057	1.66 / 1.57	0.91 / 0.71
H200 300k 1.4	1.38	9,422 / 9,233	0.009 / 0.014	1.26 / 1.16	0.49 / 0.64
H200 300k 1.55	1.53	8,965 / 8,866	0.018 / 0.019	1.24 / 1.21	0.72 / 0.65
H200 300k 1.75	1.72	8,613 / 8,444	0.031 / 0.025	1.34 / 1.27	0.76 / 0.66
H200 600k 3.0	2.90	6,939 / 6,868	0.042 / 0.054	1.78 / 1.61	0.75 / 0.71
Llama 300k 3.0	2.96	6,714 / 6,754	0.060 / 0.057	1.64 / 1.57	0.87 / 0.72
native 6.5	6.33	5,332 / 5,064	0.109 / 0.116	2.40 / 2.19	0.83 / 0.79
150k pool 1.45	1.51	8,369 / 8,879	0.020 / 0.019	1.27 / 1.13	0.81 / 0.66
150k pool 1.6	1.66	8,071 / 8,528	0.020 / 0.024	1.30 / 1.18	0.83 / 0.67
150k pool 1.8	1.87	7,909 / 8,123	0.033 / 0.030	1.25 / 1.23	0.94 / 0.68
600k pool 5.0	4.89	5,591 / 5,581	0.089 / 0.093	2.27 / 1.97	0.75 / 0.76
vLLM 300k 3.0	2.94	6,598 / 6,826	0.063 / 0.055	1.60 / 1.60	0.90 / 0.71

The composition is within −5.7% and +6.6% and the gap-slope ratio between 0.63 and 1.37 (mean 1.03). Completions and backlog slopes both run above the asymptotic values in 9 of the 13 runs. In model F the two add up to the arrival rate, so this may reflect window arrival rates above nominal (each is a single seed-0 run; not checked) rather than the transient of a young trap.

E2-protocol runs beyond Table 1. The other stuck runs of the E2 protocol behave like the registered ones: the SGLang 300k grid with the waiting-prefix refresh disabled (r0: composition 8,406–9,532 against 8,606 and 9,324), the BASIN runs with bursts of 50, 60 and 100 sessions (8,372–9,272 against 8,606), SHED's 600 s stop, TOOLSLOW's trapped run and stock LPM past its 128-request fallback. Across all 57 runs

the engine completes 0.90–1.21 times D, 1.055 on average; seven are below D (the late-forming BASIN traps of 50 and 60 sessions, seed 1, at 0.90 and 0.91; native 2.5 λ_{ref} seed 1; H200 1.5 λ_{ref} seed 1; three LPM runs). The measured token ratios are 0.95–1.12 against 1.01–1.05 from the composition alone; the excess is largest on the H200 and the native pool, while the completion excess on vLLM and Llama is not explained by the token rate (the paper's checks of its congestion assumptions, Appendix P).

The slope rule and the plans. The client's constant-rate plan fixes each seed's base arrival times before any run, and reproduces the measured window arrival rates exactly. Seed 1's plan delivers 0.8–8.9% fewer arrivals than nominal over the window in every cell and rate (5.8% at 300k, 7.9% on vLLM and 8.9% on Llama at 1.35 λ_{ref}). The plug-in $\lambda_{\text{window}}(\text{plan}) - D$ lies within 0.01 /s of the measured backlog slope in 49 of the 57 runs and within 0.002 /s in 18, with median residual −0.0022 /s because the engine completes slightly more than D. On the 36 runs of registered protocols (30 distinct plans; the 12 vLLM runs are six plans run twice; plans of different cells share seeds) it falls on the measured side of the registered threshold in 33 runs and for 27 plans, against 23 for always predicting "trapped". The exceptions are H200 1.5 λ_{ref} seed 1 (plug-in 0.04849 against a threshold of 0.04847), Llama 1.65 λ_{ref} seed 1 (above it by 0.00005) and Llama 1.35 λ_{ref} seed 0 (0.0205 against a measured 0.0052).

Self-similarity. By Theorem 1(d), among completed sessions with similar T that arrive in $[2500, 7000)$ s, the sojourn should grow linearly in the arrival time with slope about $E[z^T - 1]$. Measured over predicted slope, per seed: 0.86–1.19 in every turn-count bin on the H200 at 600k (160–400 sessions per bin), 0.85–0.96 for short sessions on the native pool at 2.5 λ_{ref}, 0.2–1.6 (noisy, 40–120 sessions per bin) on SGLang 300k, vLLM and Llama, and 0.1–0.8 for long sessions at high z, where right-censoring at 8700 s keeps only the faster ones. This check is descriptive, not a test.

C Data-only results added in this version

Five analyses (D1, D2, D4, D5 and the pool occupancy) use only runs committed before 2026-11-02. Each was computed by one agent and then recomputed by a second agent with its own code from the raw files; where they differ we report the checked value and say so. They are post hoc. Scripts and outputs: `analysis/r15_dataonly/` and `results/r15_dataonly/` (`PROVENANCE.md` there).

Persistence (D5). Rolling 300 s windows of the follow-up hit fraction; a trap starts at the first window after the trigger with hit fraction at most 0.2, and an escape is any later window with at least 0.5 before the run ends or an intervention begins (a rescue cap, a SHED stop). In the 50 trapped FCFS runs committed before the blind tests of 2026-11-05 (49 after a burst, registered and exploratory, and the trapped run of the 900 s TOOLSLOW arm; the TOOLSLOW-W and CUT runs are not included) there was no escape; the highest window after onset reached 0.164. Trapped time totals 99–103 h, depending on whether the trap is taken to start at the beginning or the end of its first window (the first computation gave 104.5 h, which the recomputation did not reproduce), and the shortest trapped span is 6100–6400 s, so a one-sided 95% upper bound on a run's escape probability within such a span is $1 - 0.05^{1/50} = 5.8\%$. Stock LPM escaped in 4 of its 9 trapped runs (several barely above 0.5), and LPM with its fallback disabled in its one trapped run. Of the 16 from-empty runs that collapsed, one recovered within its 3000 s run (150k pool, 1.30 λ_{ref}, seed 0).

The trap outlives its trigger (D1). In 16 stuck runs committed before those tests, every trigger session (the burst's, or for TOOLSLOW the sessions with a slowed tool call) had left the system 558–6246 s before the end: the 600k H200 paired test (6 of 6), BASIN bursts of 50 (1), 60 (3) and 100 (3), SHED's 600 s stop (2) and TOOLSLOW's trapped run (1). The 727–15,453 turns completed after the last trigger session left had no hit in 15 of these runs; in the TOOLSLOW run 4 of 5,937 hit, all within 715 s after its last slowed session left. In the 24 registered 200-session runs on the A100 (SGLang 300k and native, vLLM, Llama) 3–30 burst sessions were still present at the end (at most 4.1% of the sessions present; the first computation's "5.8%" could not be reproduced), so for those runs we do not claim that the trap outlived its trigger.

Pool occupancy in the trap. From the engines' 5 s metrics, the KV held by admitted requests (SGLang's used, non-evictable tokens, which also count locked prefixes; vLLM's cache usage) averaged over the window was 63–79% of the pool in the six registered SGLang 300k BURST runs, 55–83% across all 34 stuck SGLang FCFS runs with 300k and 600k pools, 85–94% with the native pool and 92–94% on vLLM, with follow-up hit fraction zero throughout. (The first computation's "63–79% in registered traps" holds only for the SGLang 300k runs.)

SLO goodput (D2). Lu et al. define goodput as sessions completed per hour with slowdown at most 4 and at least 95% of decode steps meeting an inter-token latency target [76]. We have no per-token latencies, so we omit the second condition from both arms. That makes each goodput an upper bound but does not bound the loss in either direction, except where no BURST session meets the slowdown condition; there (26 of the 30 runs in the first hour, all 30 in the evaluation window) the loss is 100% under either definition, provided the NOBURST goodput stays positive. Slowdown is the session's elapsed time from its planned arrival, over an unloaded reference built from the NOBURST runs (first computation: per-turn minimum latencies; recomputation: a least-squares fit of latency on new-suffix and decode tokens; both reported). Against the same-

seed NOBURST run, base sessions that arrived in the hour after the burst lost 99.2–100% of goodput in all 30 registered BURST runs (no session met the target in 26), and those arriving in the evaluation window lost 100% in all 30, for reference latencies up to twice the unloaded ones. In the evaluation window the CAPPED arms were within 0–1.7% and the rescue runs within −0.3 to +0.9% of NOBURST. In the first hour after the burst the cap cost 4–57% (CAPPED) and the rescue 45–97%; these two ranges depend on the reference, and a reference twice as large lowers them by a quarter to a third. Lu et al. report about 88% from one run of a different system, which is not comparable in detail.

Lu et al.'s model on our cells (D4). Every reading below is ours, post hoc, of a model built for disaggregated serving whose hit curve is empirical and system-specific; the second computation also judged which readings are fair.

- *Onset* (Table 2). With h fixed by the A100 300k crossing, the reading errs by 4.66 sessions on average over the seven other cells and 4.11 over the five predicted before their runs were read, against 1.53 and 1.55 for our frozen crossings. The comparison survives every charitable variant tried: the constant fitted to all eight cells (3.74 against 1.42), fitted on the four A100 pools only (3.57 against 1.53 over seven cells), left out one cell at a time (4.72), and crossings of the token hit fraction instead of the turn hit fraction (4.05 against 1.53 on the five cells). A hit curve that depends only on W/C cannot move the onset with the GPU; refitted per GPU it still misses the 600k H200 by 6.7 sessions (ours: 4.4 sessions low). Over the four A100 pools the measured crossing is affine in the pool, $2.97 + 1.003\, M/\bar{E}$ (intercept standard error 0.71; 95% interval −0.1 to 6.0 with two degrees of freedom), consistent with the tool-call term (4.7–5.1 sessions) net of $n_{1/2}$'s lead over n_b, but not established by four points.
- *Vulnerability condition.* Their Eq. 2 compares a dedicated prefix cache with decode memory. In one pool the two are the same memory, and it reduces to $f \lesssim 1/2$ (1/1.9 with their measured cliff constant) for the fraction f of active sessions in service, which here moves along the curve: 0.19–0.53 at our model's fluid peak, 0.38–0.90 at the 0.5-hit crossing and 0.67–0.95 at n_b, so the verdict depends on where f is read. All eight cells are vulnerable, so they cannot test the condition's specificity. Their own classifier, which compares throughput bounds, flags all 17 cache-first cases among 36 simulated deployments (28 of 36 correct), and in simulation they find that a faster GPU raises the first trapped load in absolute terms. We do not score the condition.
- *Drain.* Their Eq. 4, $S/(D(N^*) - \lambda)$, is stated for resident-first ordering near the peak with healthy reuse, and its queue holds sessions awaiting their first call; most of a rescue backlog is admitted sessions paused at tool boundaries, whose next turn misses. Applied to R1 and R4 with the measured peak rate and backlog (release = $t_{\text{on}} + (n_{\text{on}} - c)/(\mu^* - \lambda) +$ 300 s), it is 19–39% early: the engine released 24–64% later. Our model's own single-phase variant, in the same frozen file but not a declared prediction, is 12–34% early (released 14–51% later); the frozen two-phase drain, in which every paused session's next turn misses, was 2–18% early (released 2–22% later). The gain comes from the two-phase structure, not from a different peak.
- *Window.* The ratio of peak ratios between pools needs their prefill and decode bounds and a smooth minimum whose form they do not give for colocated serving; we omit that comparison.

Sources: measured crossings from the closed-population runs (`paper/NUMBERS.md`); frozen predictions in `results/theory/merged/*.json` and `results/theory/pred2/h200_600k.json`; rescue releases in the committed `rescue_runs.csv`; Lu et al.'s equations from their Section 5. The full record is `results/r15_dataonly/verify_d4/verify_D4.md`.

D Background and what is classical

Engines. LLM engines batch per model iteration: running requests decode one token per iteration and waiting requests join between iterations [117]; KV is stored in pages [68]. SGLang keeps cached prefixes in a radix tree, evicts least-recently-used (LRU) leaves, and can order waiting requests by longest prefix match (LPM) [122]. In SGLang 0.5.22 the default policy is FCFS and the default eviction rule LRU; LPM stops sorting its queue when more than 128 requests wait, a fallback that PEEK also documents [112]; a waiting request does not lock its cached prefix, which is locked when the request is admitted; and under FCFS, including LPM above that threshold, an LRU refresh touches the prefixes of the first 128 waiting requests once every 32 scheduling passes. vLLM 0.32.0 schedules FCFS by default, and a freed cached block keeps its hash until it is reallocated. The paragraph 'Engine sources' of Appendix P cites the source lines at the release tags. Our synthesis of these rules is that in both engines a session's KV is protected only while one of its requests runs.

Thrashing and metastability. Denning showed that admitting one more program to a memory near saturation can collapse efficiency, and that keeping the working sets of the active programs within memory, which limits their number, prevents it [30, 31]. We call throughput as a function of the closed population n the thrashing curve; the term is our framing. LRU does badly on loops larger than the cache [22, 99]. A metastable failure is a bad state that persists after its trigger is removed, sustained by a feedback loop under uncontrolled load; one of Bronson et al.'s case studies is a lost look-aside cache [11], and Huang et al. study such failures in production incidents and model them [52]. In their classification of sustaining effects, a trap in which the load itself lowers capacity is capacity-degradation amplification; one of their cases is garbage collection driven by queueing-induced memory pressure, and their experiments vary the trigger's magnitude against matched runs, the design we follow. In Bronson et al.'s terms, a system that serves its load but can be pushed by

a trigger into the bad state is in a vulnerable state, and the bad state, kept by a sustaining effect after the trigger ends, is the metastable failure state. We also call the good state metastable, in the physics sense of a state that persists until a large enough perturbation. Denning measured the working-set window in a program's own virtual time, so that interruptions would not distort it [32]; an LRU pool over idle KV ages its entries in real time, so the time a session waits in the queue counts against its residency.

What is classical, and what is specific to agent serving. The collapse past the working-set level, a bad state that outlives its trigger, metastability from a unimodal throughput curve under open load and bistability when the load comes from a finite source, hysteresis, and bounded admission as the cure are classical, for random-access channels, thrashing multiprogramming systems and service systems whose customers return [15, 16, 25, 66, 84]; in all of them the slowdown is a given function of occupancy. So are the decomposition approximation behind §E.3 [25, 66] and multiprogramming-level load control [33, 49, 96]. Two features of agent serving make them apply: the reusable KV is exactly the idle KV, which memory-gated admission reclaims, and a hit is much cheaper than a miss. Appendix R.9 gives the full background.

E A fluid model of the open system

E.1 Workload and notation

A session has $T \sim \min(\text{Geometric}(1/15), 60)$ turns, so $E[T] = 14.761$. Turn k sends a prompt of $L_k = L_0 + (k-1)(\Delta + d)$ tokens: a first prompt of $L_0 = 2000$ tokens, $\Delta = 550$ tokens of tool output and $d = 100$ decoded tokens per turn. Between turns the session waits for a tool for a time Z, independent across turns, exponential with mean 5 s in the workload of record. A turn *hits* if more than half of its prompt is served from cache; on the real engine a hit almost always reuses everything but the 550 new tokens and the last decoded token, so it prefills 551 tokens (all but 95 of the 185,613 hits in the registered paired test E2 of §G.2). First turns always miss, so in the long run the hit fraction is at most $1 - 1/E[T] = 0.932$; finite windows can lie slightly above it (up to 0.94 in our runs). With every turn missing, a session's prefill work is $W(T) = 2000\,T + 325\,T(T-1)$ tokens with $E[W] = 154{,}529$; with every follow-up hitting it is $2000 + 551(T-1)$, about 9,600 in expectation.

The engine has a KV pool of M tokens. In the *closed* system n sessions are present and a finished session is replaced at once. The thrashing curve $\mu(n)$ is the long-run session completion rate (sessions/s); $\mu^* = \max_n \mu(n)$ is attained at n^*, and $\mu_\infty = \lim_{n\to\infty} \mu(n)$ is the *congested service rate*, a long-run rate of the closed system (an open system in congestion can complete sessions faster than μ_∞ for a long time, §E.3). The all-miss capacity λ_{miss} is the throughput of the saturated engine with prefix caching disabled. In the *open* system sessions arrive as a Poisson process of rate λ, and $N(t)$ counts sessions in the system (waiting, running or in a tool call). A session rate is estimated either as sessions completed per second or, with much lower variance because session work is heavy-tailed in T, as turns per second divided by $E[T]$ ("turns-based").

E.2 The thrashing curve for agent sessions

Let E_{lb} be the time-averaged KV footprint of a session over its lifetime, a length-biased mean in which long sessions and late turns weigh more (during the tool call after turn k a session holds $L_k + d$ tokens). By the $H = \lambda G$ relation [13, 50], the mean KV demand of n present sessions is nE_{lb}. For our workload E_{lb} is about 10.5k tokens when tool calls dominate the lifetime, so a 300k pool holds $N_{\text{lb}} = M/E_{\text{lb}} \approx 28.5$ sessions on average (weighting every turn equally, the last included, gives 10.6k and 28.4). While nE_{lb} is well below M, idle KV survives the tool call and $\mu(n)$ rises with n through batching. Beyond it, admitting a waiting turn evicts idle KV, which belongs to sessions in tool calls or already waiting in the queue; they miss when their next turn is admitted. The peak n^* lies below N_{lb} mainly because idle KV is evicted at a finite LRU age, so hits fall before mean demand reaches the pool, and to a lesser degree because demand fluctuates around its mean. The capacity ratio is the collapse predictor of AgentKV [3] and the basis of MISA-T's session cap [51]. Section H derives the curve from first principles; its all-miss onset at 300k, $n_b = 32.7$, is the sessions in tool calls plus one pool of running sessions (Proposition 2 of §H.2), so the measured peak, the capacity ratio and the onset are ordered $n^* = 24 < N_{\text{lb}} < n_b$.

E.3 The open system as a quasi-static approximation

Replacing the departure rate of the open system by its closed-system value at the current population, the classical decomposition approximation (§D), gives

$$\dot{n} = \lambda - \mu(n). \tag{2}$$

Extend μ from integer n to all $n \geq 0$ by linear interpolation, so that it is continuous and piecewise linear with $\mu(0) = 0$ and Eq. (2) has unique solutions, and assume that the stationary curve is *unimodal*: strictly increasing on $[0, n^*]$ to μ^*, non-increasing on $[n^*, \infty)$ with limit $\mu_\infty < \mu^*$, and strictly decreasing wherever $\mu > \mu_\infty$. This allows a tail on which $\mu = \mu_\infty$, as on the predicted curves of §H; the statements below are for $\lambda \neq \mu_\infty$. For $0 < \lambda < \mu^*$ let $n_1 < n^*$ solve $\mu(n_1) = \lambda$. If $\lambda < \mu_\infty$, n_1 is the only fixed point of Eq. (2), and it attracts every trajectory. If $\mu_\infty < \lambda < \mu^*$, there is one more, $n_2 > n^*$, which is unstable, and from any $n > n_2$, $n \to \infty$: the good state is metastable. If $\lambda > \mu^*$ there is no good state. A solution from a congested state $x_0 > n^*$ returns to n_1 if and only if $\mu > \lambda$ on $(n_1, x_0]$, the endpoint n_1 excluded because $\mu(n_1) = \lambda$; since $\mu > \lambda$ on $(n_1, n^*]$ and $\mu \geq \mu(x_0)$ on $[n^*, x_0]$, this holds if and only if $\lambda < \mu(x_0)$. As x_0 grows, $\mu(x_0)$ falls to μ_∞, so μ_∞ is the *recovery threshold* from deep congestion. After a finite burst x_0 is finite, so recovery above μ_∞ is possible; the threshold for a given burst depends on its

size. Appendix P proves these statements and treats a curve without the monotone tail, such as our measured one.

In a finite system fluctuations can carry N past n_2 without a burst, and an experiment sees only escapes within its horizon. We therefore use a measured *from-empty edge* λ_e, the largest rate at which runs started from an empty engine stay stable over a stated horizon, and define the window

$$\mathcal{W} = \big(\mu_\infty,\ \min(\mu^*, \lambda_e)\big). \tag{3}$$

Inside $\mathcal{W}$ the good state exists from empty, and a burst that crosses the basin boundary leaves the system in a regime whose service rate is below the arrival rate. That regime is transient (the backlog grows), not a second stationary state, so we say metastable rather than bistable; two stable states, the bistability of ALOHA-type channels [15] and the stochastic cusp of multiprogramming models [84], arise here only for the admitted population of a capped engine (c sessions at $\mu(c)$ while the gate grows; Corollary 5) or, when the closed curve folds (dispersed tool times, not our workload), in the closed system itself, where stable means stable under a relaxation of the hit probability at fixed n (Appendix Q): Proposition 7 then gives an all-miss state that is locally stable in this sense and two queue-free states, and in our example one of these, the good state, is numerically stable in the same sense (Fig. 6, also in Appendix Q). Appendix P maps these quantities to Bronson et al.'s terms [11].

Eq. (2) assumes that the internal state relaxes quickly compared with changes in n, and it is not quantitative in congestion, where a trapped engine serves a young backlog of short turns; we use it for the window, as a long-run statement for the recovery threshold, and for the capped system's drain time, not for burst sizes or backlog growth (Appendix P).

E.4 Caps and a congestion bound

Without a cap, deep congestion of the closed system is bounded by the all-miss capacity: under request-level FCFS and assumptions (A1)–(A3) of Appendix P (one of which is that the congested engine computes prompt tokens no faster than with caching disabled), no online eviction rule, including queued-prefix protection and FCFS-order TTL pins, lets $\mu(n)$ exceed λ_{miss} as $n \to \infty$, and the rate of hit turns tends to 0 (Proposition 6). It covers SGLang's stock LPM through its 128-request fallback, but not a pure resident-first order; Appendix P states and proves it and discusses its scope. Under request-level FCFS and (A1)–(A3), then, $\mu_\infty \le \lambda_{\text{miss}}$, with equality if the congested engine also computes prompt tokens as fast as with caching disabled ((A4) of Appendix P), which our engines do to within a few percent at the stationary turn mix and to within 12% over the windows we measured. We therefore take the lower end of $\mathcal{W}$ to be λ_{miss}, estimated by λ_{ref}, and write windows as $(1, x)\,\lambda_{\text{ref}}$; if $\mu_\infty < \lambda_{\text{miss}}$, $\mathcal{W}$ is wider, and every rate in $(\lambda_{\text{miss}}, \min(\mu^*, \lambda_e))$ is still in it. We do not read μ_∞ off the measured closed curves, which are not monotone beyond the peak (at 300k, 0.68 λ_{ref} at $n = 48$ and 1.51 λ_{ref} at $n = 300$ in completed sessions); we attribute both features to their synchronized start, which no longer run has tested (§G.1).

Proposition 1 (cap identity; elementary)**.** *Let a FIFO gate admit at most c sessions, each holding its slot from admission to the end of its last turn, tool calls included. In the closed system with n sessions the admitted sessions form a closed system of* $\min(n, c)$ *sessions, so* $\mu_{\text{cap}}(n) = \mu(\min(n, c))$.

Proof. When an admitted session finishes, the gate admits its head at once and the replacement joins the gate. □

Corollary 5 (cap rescue; quasi-static)**.** *Let μ be unimodal as in §E.3, let $\mu_\infty < \lambda < \mu^*$, and let $n_1 < n_2$ be the stable and the unstable fixed point of Eq.* (2)*. Under Eq.* (2) *with the departure rate μ_{cap} of Proposition 1, a FIFO cap c engaged when more than c sessions are present (the congested regime included) empties its gate if and only if $n_1 < c < n_2$, that is, $\mu(c) > \lambda$. Once the gate is empty the cap no longer binds, and removing it leaves the population in the basin $[0, n_2)$ of n_1, where it stays.*

The proof is in Appendix P. That the good state persists after the cap is removed is hysteresis of the system, which the rescue tests of §G.3 check on the engine; it differs from the cache hysteresis that Lu et al. report in simulation, a lower hit rate after a collapse at a comparable working set [76], and from the dead band of a controller that pauses and resumes admission at two thresholds (Appendix T.2). A cap $c > n^*$ raises the congested level to $\mu(c)$ but leaves the window $(\mu(c), \mu^*)$ open. A burst of b sessions that arrives when $n_1 < c$ sessions are present fills the $c - n_1$ free slots at once, so the gate empties after about $(n_1 + b - c)/(\mu(c) - \lambda)$; Appendix L compares this estimate, and the registrations' cruder $b/(\mu(c) - \lambda)$, with the engine. Appendix P treats a folding curve and the stochastic counterpart.

F Methodology

F.1 Real-engine harness

All real-engine runs used one GPU per job on the Nova SLURM cluster at Iowa State University, an NVIDIA A100 80GB PCIe except in the two H200 cells (one H200 NVL; §G.5), with SGLang 0.5.22 (FlashInfer attention [115], or on the H200 FlashAttention 3 [97], SGLang's default there; chunked prefill of 8192 tokens, at most 256 running requests, LRU eviction) serving Qwen2.5-7B-Instruct [92] or, in one A100 cell, Llama-3.1-8B-Instruct [46] from a mirror whose weight shards are byte-identical to Meta's. The KV pool was capped at 300,000 tokens, at 150,000 or 600,000 in the pool sweep and at 600,000 in the second H200 cell (§I), or, in the native-pool runs, sized by SGLang at 955,757 tokens. Decoding was greedy, 100 tokens per turn (Appendix L lists every setting). The vLLM 0.32.0 runs used the same model, GPU, client and workload with a 300,000-token pool (§G.2).

An open-loop client on the same node sends each turn as a completion request whose prompt is a list of token ids: random

content from a seeded generator, extended each turn by the token ids the server returned plus 550 new tool tokens, so a hit covers exactly the previous prompt and output; during a tool call the client sleeps. Cached tokens come from the server's usage report, which the engine's counters and log confirmed in the closed-population runs (Stage C, §F.2). Before every run the cache is flushed and checked with a canary: a 1024-token request that reused 1023 tokens before the flush (1008 on vLLM, which caches whole 16-token blocks) must reuse at most 15 after; it reused none. In the cache-off calibration runs (E0a, §F.2) the check only confirms that the engine is idle. Each arm of a registered test ran in its own job on a fresh server.

The BURST arm adds 200 fresh sessions within 60 s at $t_b = 1200$ s to the Poisson stream; NOBURST is the same stream without them; CAPPED is BURST plus a client-side FIFO gate admitting at most n_{cap} sessions, each holding its slot until its last turn ends (the gate of Proposition 1); the rescue tests of §G.3 engage such a gate only after the trap is established. The burst equals 12 to 38 minutes of base arrivals at the registered rates, and its 2000-token first prompts alone (400k tokens) exceed the 300k-token pool; we took its size from our earlier simulator, where bursts of 100 or more trapped every work-conserving policy, so the test asks whether a burst large enough to cross the basin boundary traps the engine, not how likely such a burst is (§G.4). The arms of one seed share arrival times, turn counts and tool times (common random numbers), so BURST differs from NOBURST by the burst and CAPPED from BURST by the gate, up to GPU timing nondeterminism: each arm ran on a fresh server in its own job, and the arms of one seed did not always share a node. Seeds 0, 1 and 2 are reused across rates, pools, policy cells, engines and tests: for a given seed the 200 burst sessions are identical everywhere, the arrival times at a lower rate are a subset of those at a higher rate, and the i-th session to arrive has the same turn count, tool times and client-generated tokens everywhere, so runs that share a seed are not independent across these.

F.2 Staged protocol

Each stage's inputs came from the previous one (Appendix L gives the job IDs, in Table 10, and the sequence and the details). *Stage C* measured $\mu(n)$ in closed populations, with all n sessions starting at $t = 0$, one run per n and an 1800 s window after 900 s of warmup. *E0a* measured the all-miss session rate with the radix cache disabled; its turns-based value λ_{ref} is the unit of every arrival rate, and numeric multiples of a rate in this paper are multiples of the λ_{ref} measured with the same engine, GPU and model at 300k (0.0715 sessions/s on SGLang and the A100, 0.0657 on vLLM, 0.194 on the H200, 0.0596 with Llama-3.1-8B), except that the native-pool cell uses its own (0.0718); the 150k and 600k cells thus use the 300k value of their GPU. Model F's λ_{miss} (§2) is instead the cost model's value, within 4% of λ_{ref} ($\lambda_{\text{miss}}/\lambda_{\text{ref}} = 0.96$–$1.035$). *E0b* ran Poisson arrivals from an empty engine for 3000 s per rate, with arrival seed 0 at every rate; a run is stable if its final queue is below 50 and its queue rises by at most 10 over the last 1500 s. The registration was then filled and committed, and *E2*, the registered paired test, ran the three arms; the native pool and vLLM repeated the sequence, and the later registered tests follow the paired-test protocol.

F.3 Decision rule and registration

Each run of a registered test lasts 8700 s and is judged over $[t_b + 4500, 8700]$ s; in the rule, λ_{miss} is the cell's λ_{ref}. A BURST run is TRAPPED if $\lambda > \lambda_{\text{miss}}$ and (a) its uncached prefill token rate is within ±15% of the cell's E0a all-miss rate (11,243 tokens/s at 300k) and (b) the slope of its backlog exceeds $0.5(\lambda - \lambda_{\text{miss}})$, the slope being the least-squares slope of 10 s bin means of the sessions in the system (arrived and not ended, including any held at the gate) over the window. A run is RECOVERED if over the last 300 s its hit fraction exceeds 0.8 and its outstanding backlog (requests in flight plus sessions held at the gate) is below 20; NOBURST is good if RECOVERED. A run that is neither is DRAINING if its slope is negative and INDETERMINATE otherwise; the labels take precedence in the order trapped, recovered, draining, indeterminate. A rate PASSES if, in at least two of three seeds, BURST is trapped, NOBURST good and CAPPED recovered in that same seed. Criterion (a) uses tokens because a trapped engine with a growing backlog completes sessions faster than λ_{miss} while it prefills at the all-miss token rate (§E.3); Appendix L gives the evidence.

The registration was filled by formula from committed copies of the Stage C curve, the E0a calibration and the E0b bracket: the window $(1,\ 2.0)\ \lambda_{\text{ref}}$, its upper edge E0b's largest all-stable multiple; the rates one third and two thirds of the way across it, rounded to 0.05 (1.35 and $1.65\ \lambda_{\text{ref}}$), each of which must lie strictly between 1.1 times the window's lower edge and 0.9 times its upper edge, here $(1.1,\ 1.8)\ \lambda_{\text{ref}}$, or the fill returns INCOMPLETE; and the cap, the smallest n with $\mu(n) \geq 0.95\mu^*$, which gives $n_{\text{cap}} = 20$. We call a test pre-registered when its registration file was committed and pushed to GitHub before its runs, with GitHub's push log of our development repository as the record (not an entry in a third-party registry); that repository is private, so readers see the log only as our export of it in `provenance/` (Appendix O), which cannot be checked against GitHub independently. We call a test registered when a FILLED registration file (Table 13) binds its runs and was committed before its jobs were submitted; neither label says whether a prediction for the test was blind (§I). The E2 and native tests are pre-registered, and so is every later registered test but one, although the text mostly calls these simply registered: the rescue tests R1 and R4 (§G.3), the basin tests BASIN-1 and BASIN-2 (§G.4) and the TOOL-SLOW and SHED tests, whose registrations reached GitHub 22 to 131 minutes before their jobs were submitted, and the 600k H200 and Llama-3.1-8B paired tests, whose registrations reached it 63 and 47 s before theirs (§I). The exception is vLLM: its registration reached GitHub after its jobs were submitted, when two of them had started, so that test is registered, not pre-registered. On the H200 with the 300k pool the rule could not place its test points, so that cell has no regis-

tered test (§G.5). Appendix M gives the fill, its enforcement by the job script and the push time of every registration, and Appendix N every prediction round with its time record.

F.4 The calibrated simulator

Our discrete-event simulator models a continuous-batching engine whose iteration cost has five parameters fitted only to SGLang's per-batch timing lines in server logs, never to $\mu(n)$; it failed its declared level test, missing one Stage C cell by 42%, but reproduced the curve's shape. LLM coding agents used it to make blind predictions for the registered tests, each in its own copy of the repository and instructed not to read the results they predicted; every round was committed and pushed under a tag before its results were read by its authors, and what each round is blind to differs (Appendix N gives the model, the validation, the rounds and their time record). Round predictions are labelled Bk: B1 the all-miss capacity, B2 the from-empty edge, B3 the paired test, B4 the closed curve, with suffix n for the native pool and v for vLLM (Appendix N.1, Table 18). Rounds are numbered in project order: these three prediction rounds are rounds 6, 8 and 9, round 7 includes the simulator's robustness study (Appendix T.1), and rounds 11 to 14 made the predictions and registrations of §I. Our earlier simulator (rounds 1–5), which is not calibrated to the engine and uses assumed costs (all-miss capacity 0.0474 sessions/s), is used for the mechanism comparison of Appendix T.2, in units of its own λ_{miss}. Each experiment cell was also run by its own Claude Code agent, which submitted its jobs and kept a log in `notes/LOG.md` (the cell's operating agent), and a further, coordinating agent dispatched the cells and drafted the paper; the first-principles model of §H was derived and frozen by agents in the same way. In this paper "session" always means a workload session.

G Results on the real engines

G.1 The thrashing curve and the from-empty edge

With the 300k pool (Fig. 5, left), $\mu(n)$ rises from 0.176 sessions/s at $n = 16$ to 0.224 at 20 and 0.233 at 24, with hit fractions 0.93, 0.93 and 0.89, and then collapses: the run at $n = 32$ mixes a degraded and a recovered regime (hit fraction 0.51), and at $n = 48$ none of the 20.0M prompt tokens in the window was served from cache. The hit fraction crosses 0.5 at $n = 32.2$ (interpolated between the runs at 32 and 48), about 3.7 sessions above the capacity ratio $N_{\text{lb}} \approx 28.5$ and just below the all-miss onset $n_b = 32.7$ of the first-principles model, which adds the sessions in tool calls (4.9 here) to a pool of running sessions and predicts this curve without using its points (§H). The all-miss level implied by token throughput is roughly flat at 0.072–0.081 sessions/s, so the collapse from the peak is about threefold. With the native pool (Fig. 5, middle), 955,757 tokens or 3.19 times the 300k pool, μ peaks at 0.479 sessions/s at $n = 64$ (0.477 at 80) with 92–93% of turns hitting, and the hit fraction crosses 0.5 near $n = 93$; the all-miss capacity is unchanged within its standard error (0.0718 ± 0.0037 against 0.0715 ± 0.0038 sessions/s turns-based). The 300k pool limit did not create the cliff; it moved it. Halving and doubling the pool (150k and 600k tokens, §I) moved the peak to $n = 12$ and 48 and the 0.5-hit crossing to 16.5 and 60.1 sessions. The ratio $\mu^*/\lambda_{\text{ref}}$ is 3.26 at 300k and 6.67 with the native pool (the registered values, the peak in completed sessions over the turns-based λ_{ref}; 3.15 and 6.48 turns-based). Token-level hit rates have been reported to collapse as concurrent agents grow on SGLang [19] and on vLLM [51, 120], and, on prefill–decode disaggregated SGLang, once the working set reaches about twice the cache [76]; what we add is $\mu(n)$ in completed sessions per second, the quantity the open-system model uses, at four pool sizes on the A100, two on an H200 and, below, on a second engine. Beyond the peak neither curve is monotone, which we attribute to the synchronized start of the closed runs; Appendix R gives this and the other details of both curves.

The all-miss capacity and the from-empty edge. E0a gives $\lambda_{\text{ref}} = 0.0715 \pm 0.0038$ sessions/s turns-based (standard error over three seeds), our estimate of λ_{miss}, and 11,243 ± 84 all-miss prefill tokens/s; the token rate varies by ±1.2% across seeds and the session rate by ±17%, because the engine is bound by prefill tokens and the work of a session is heavy-tailed. From an empty cache and queue (Fig. 7 in Appendix R) the engine stayed stable for 3000 s at 1.25, 1.5, 1.75 and 2.0 λ_{ref}, ending each run with an empty queue and 91–93% of turns hitting, and was unstable at 2.5 and 3.0 λ_{ref}; on this grid, which used the single arrival seed 0, the edge lies between 2.0 and 2.5 λ_{ref} in nominal rates, and the registered window was $(1, 2.0)\,\lambda_{\text{ref}}$. An exploratory replication with fresh seeds 3, 4 and 5 found 2.0 and 2.5 λ_{ref} stable in 3 of 3 seeds each, so the seed-0 bracket is not replicated in nominal multiples; ordered by realized arrival rate, the twelve from-empty runs at this pool are stable up to 2.665 λ_{ref} and unstable from 2.726, still below $\mu^*/\lambda_{\text{ref}}$, and the registered points, 1.35 and 1.65 λ_{ref}, lie inside the stable range on either reading. With the native pool the edge lies between 5.5 and 6.5 times the native λ_{ref} in nominal rates, so that window is $(1, 5.5)\,\lambda_{\text{ref}}$, $4.5\,\lambda_{\text{ref}}$ wide against 1.0 at 300k, although its unstable run received more arrivals than the measured peak, so overload alone can explain its instability. Each rate is a single 3000 s run, so slower escapes are not seen.

G.2 The registered paired tests

The registered analysis of E2, run on all 18 runs with the code frozen at the registration commit, passes at both rates (Table 5, top); by the definition of §F.3 the test is pre-registered. Every BURST run had a hit fraction of 0.000 over the evaluation window, an uncached prefill rate of 1.009–1.029 times the all-miss rate and a mean backlog of 200–332 sessions, and in Fig. 1 each is at zero hits from the 100 s window starting at 1300 s to the end of the run. One ($1.35\,\lambda_{\text{ref}}$, seed 1) is stuck in the same way, but its backlog was flat over the window, so




Figure 5: Closed-population thrashing curve, real engine (black, filled; one run per n) against the simulator (gray, open, dashed). Top: $\mu(n)$ in completed sessions/s (plus signs: turns-based estimate); bottom: hit fraction. Left: SGLang, 300k-token pool; calibrated simulator, mean of 3 seeds ±1 s.e. Middle: SGLang, native pool (955,757 tokens); blind prediction B4 at 900k tokens (seed 0); light gray, dotted: B4n at the real pool (3-seed mean), which is not blind (Appendix N.1). Right: vLLM 0.32.0, 300k-token pool; blind prediction B4v (variant V1: token costs scaled to vLLM's all-miss rate; mixed batching), mean of 10 seeds ±1 s.e. (§G.2). Dotted: each cell's measured λ_{ref}, the turns-based E0a estimate of λ_{miss}. Green dashed: the registered caps, $n = 20$, 64 and 20.

the rule calls it indeterminate: its seed delivered 5.8% fewer arrivals than nominal in the window, and the trapped engine completed sessions about as fast as they arrived. The pass at 1.35 λ_{ref} therefore rests on 2 of 3 seeds, the minimum the rule allows. Every NOBURST and CAPPED run is good (hit fractions 0.921–0.934, backlogs of 8–12 sessions, most asleep in tool calls); in the window CAPPED cannot be told apart from NOBURST, because the gate had drained the burst 1547–2693 s after it. Counting each seed once, since both rates use the same three seeds with the same burst and nested arrivals, a post-hoc one-sided sign test of BURST's hit fraction against NOBURST's gives $p = 1/8$, the smallest value three seeds allow. The trapped runs still completed 1.13–1.35 λ_{ref}, above λ_{miss}, because their young backlog has short turns; only the uncached prefill rate sits at the all-miss level, which is why the registered rule uses tokens (§E.3). So at loads that the engine carried from empty, 200 sessions arriving within a minute, an order of magnitude more than the 8–12 present in the good state, moved it into an all-miss state that it did not leave within 7500 s, and a cap of 20 sessions, within 5% of the measured peak of $\mu(n)$, prevented that, at the price of admission delay that the registered criteria do not measure (349–543 sessions per CAPPED run waited at the gate, 405–471 s on average). Good NOBURST arms are the expected outcome even for a metastable good state: by the heuristic H2 of §H.3, a run at these rates leaves it on its own within 8700 s with probability about 0.5% at 1.35 and 5% at 1.65 λ_{ref}. Appendix R gives the arrivals, the backlog after the burst, the drain and the cost of the cap in detail.

Native pool. A second registration, filled by the same formulas from the native curve, E0a calibration and E0b bracket, gives the window (1, 5.5) λ_{ref}, the rates 2.5 and 4.0 λ_{ref} and $n_{cap} = 64$, flagged ambiguous because $\mu(80)$ is within 0.35% of $\mu(64)$; it reached GitHub before the first native E2 job was submitted. The registered analysis passes at both rates, and every run is in the predicted state (Table 5): all six BURST runs were trapped, all six NOBURST runs were good and all six CAPPED runs recovered (Fig. 8 and the details in Appendix R). Pooled post hoc over the two pre-registered SGLang tests (a descriptive count: they share three seeds' session sequences), NOBURST was good and CAPPED recovered in 12 of 12 runs each, and BURST was at zero hits in 12 of 12 and trapped by the rule in 11 of 12.

Table 5: The three registered tests: the two pre-registered SGLang tests, E2 (300k-token pool, cap 20, $\lambda_{\text{ref}} = 0.0715$ sessions/s) and native E2 (955,757-token pool, cap 64, $\lambda_{\text{ref}} = 0.0718$ sessions/s), and the registered vLLM test (300k-token pool, cap 20, $\lambda_{\text{ref}} = 0.0657$ sessions/s). States for seeds 0, 1, 2: T trapped, I indeterminate, D draining, G good, R recovered. Hit fraction, uncached prefill rate in multiples of the all-miss rate, mean backlog (sessions in the system) and its slope (sessions/s) over the evaluation window; ranges over seeds; good-arm slopes in absolute value. Slope thresholds: 0.0125, 0.0232, 0.0538 and 0.1077 at 1.35, 1.65, 2.5 and 4.0 λ_{ref} on SGLang, 0.0115 and 0.0213 at 1.35 and 1.65 λ_{ref} on vLLM. Rates are nominal; the base arrivals realized in the window, which the three arms of a seed share, were 1.45, 1.27, 1.42; 1.73, 1.61, 1.75; 2.73, 2.48, 2.58; 4.28, 3.89, 4.09; and on vLLM 1.45, 1.24, 1.41 and 1.76, 1.56, 1.74 λ_{ref} for seeds 0, 1, 2.

$\lambda/\lambda_{\text{ref}}$	arm	states	hit	tokens	backlog	slope
300k-token pool (E2)						
1.35	BURST	T I T	0.000	1.009–1.025	200–232	0.0036–0.0222
	NOBURST	G G G	0.930–0.934	0.08–0.09	7.9–9.7	<0.001
	CAPPED	R R R	0.930–0.934	0.08–0.09	7.9–9.7	<0.001
1.65	BURST	T T T	0.000	1.025–1.029	283–332	0.0277–0.0362
	NOBURST	G G G	0.921–0.934	0.10–0.13	10.9–11.8	<0.002
	CAPPED	R R R	0.929–0.934	0.10–0.11	10.9–11.7	<0.002
native pool (native E2)						
2.5	BURST	T T T	0.000	1.074–1.078	557–601	0.079–0.085
	NOBURST	G G G	0.929–0.935	0.15–0.16	15.6–18.5	<0.003
	CAPPED	R R R	0.929–0.935	0.15–0.16	15.6–18.5	<0.003
4.0	BURST	T T T	0.000	1.106–1.124	1098–1139	0.146–0.164
	NOBURST	G G G	0.929–0.935	0.24–0.27	28.2–33.6	<0.004
	CAPPED	R R R	0.929–0.935	0.24–0.27	28.1–33.5	<0.004
vLLM 0.32.0, 300k-token pool (registered, not pre-registered)						
1.35	BURST	T D T	0.000	0.995–1.012	201–222	−0.00005 to 0.0170
	NOBURST	G G G	0.930–0.931	0.07–0.09	7.0–8.4	<0.001
	CAPPED	R R R	0.930–0.931	0.07–0.09	7.0–8.4	<0.001
1.65	BURST	T I T	0.000	0.948–1.018	281–330	0.0183–0.0341
	NOBURST	G G G	0.932–0.933	0.10–0.11	9.3–10.8	<0.001
	CAPPED	R R R	0.932–0.933	0.10–0.11	9.3–10.9	<0.001

A second engine: vLLM. vLLM 0.32.0 ran with the SGLang cell's settings where they exist (FCFS, prefix caching on, chunked prefill of 8192 tokens, at most 256 running requests, a 300,000-token pool). Its all-miss capacity is 8% below SGLang's ($\lambda_{\text{ref}} = 0.0657 \pm 0.0030$ sessions/s); its closed curve has SGLang's shape with an earlier, steeper cliff (peak 0.219 sessions/s at $n = 20$; hit fraction crossing 0.5 near $n = 29.1$); and its from-empty edge lies between 2.0 and 2.5 times its λ_{ref} (Fig. 5, right). A registration filled from these by the SGLang formulas gives the window $(1, 2.0)\,\lambda_{\text{ref}}$, the rates 1.35 and 1.65 λ_{ref} and $n_{\text{cap}} = 20$. It reached GitHub only after the 18 jobs were submitted, when two had started and none had ended, so the test is registered, not pre-registered; and its BURST arm reuses the seeds, and so the arrivals, of six earlier exploratory vLLM BURST runs, all of which had been at zero hits after the same burst, so it does not replicate them independently. The registered analysis passes at both rates (Table 5, bottom): every BURST run had zero hits over the evaluation window, and NOBURST stayed good and CAPPED recovered in all six runs each; the two BURST runs that the rule does not call trapped (seed 1, the seed with the fewest arrivals) were stuck at the all-miss token rate but failed its slope test. Of the mechanism checks frozen before any run had ended, those on the gap between a session's turns (§H.4), on a full pool rewritten at the all-miss rate and on an engine-side latency rule held in all 18 runs, but the online detector, a follow-up hit fraction below 0.2 over 60 s, alarmed 100–120 s after every burst and also in two CAPPED runs while their gates drained, so the frozen decision rule is not met and we do not claim the detector (Appendix R). The bands of these checks were set on the SGLang runs and on the six exploratory vLLM BURST runs, whose arrivals the BURST arm repeats, so only the NOBURST and CAPPED checks are out of sample. Across the three registered tests, BURST was at zero hits in 18 of 18 runs and trapped by the rule in 15, NOBURST was good in 18 of 18 and CAPPED recovered in 18 of 18; the tests share seeds, so these counts are descriptive.

G.3 Rescue from an established trap

The paired tests show that a cap present when the burst arrives prevents the trap. Two further registered tests, R1 and R4 (labels from our experiment plan, which had no R2 or R3; Table 13 in Appendix M lists every registration we filled), ask whether a cap can undo an established trap at the same arrival rate without shedding work, and whether the good state then persists without it. Each run replays the arrival plan of the paired test's BURST run byte for byte, as a fresh run on a fresh server, until a client-side cap is engaged at t_{on}: R1 on the 300k pool at 1.35 and 1.65 λ_{ref} with cap 20 from $t_{\text{on}} = 1800$ s, and R4 with the native pool at 4.0 λ_{ref} with cap 64 from 2100 s, the registered CAPPED caps, engaged 600 and 900 s after the

burst. At t_{on} more sessions than the cap are already admitted, so sessions over it give up their slot at their next tool-call boundary and wait at the client, together with new arrivals; paused sessions are readmitted first, each queue in FIFO order, and once the admitted set has fallen to the cap the gate is that of Proposition 1. The cap is removed at the first 10 s tick, no earlier than t_{on} + 600 s, at which both client queues have been empty for 300 s. A run counts as rescued if it was trapped at t_{on} (a follow-up hit fraction below 0.2 over the preceding 300 s and more than 50 requests or sessions outstanding), the cap was released by 7200 s, and over $[t_{rel} + 300, 8700)$ every 300 s window had a follow-up hit fraction of at least 0.5, the whole interval above 0.8, an uncached token rate below half the all-miss rate, and the registered RECOVERED test held over the last 300 s; a window below 0.2 is a relapse. A cell passes if at least 2 of its 3 seeds are rescued and every same-seed BURST control stays stuck; two relapses, or two releases after 7200 s, among R1's six runs would refute it, and a failed session would withdraw the claim that nothing was shed. Both registrations reached GitHub at 22:39:02 CDT on 2026-10-30, 22 minutes before the jobs were submitted (Appendices L and M).

The registered analysis passes in all three cells, R1 at 1.35 and 1.65 λ_{ref} and R4 (Table 3, Fig. 4). Every run was trapped when the cap was engaged (follow-up hit fraction 0.000–0.002 over the preceding 300 s, with 139–172 requests or sessions outstanding at 300k and 298–324 with the native pool), and all 9 runs were rescued, with no relapse, every release before 7200 s and no failed session. Hits returned within three minutes of the engage (in every run the first 60 s bin with a follow-up hit fraction of 0.8 or more was the one from 120 to 180 s after it) but fluctuated until the backlog drained: in later 60 s bins the follow-up hit fraction fell again to minima of 0.13–0.60 per run (the last bin below 0.8 began 780–1620 s after the engage), and over 300 s bins it stayed at or above 0.56 in R1 and dipped to 0.47–0.57 in R4 (Appendix R.3, Table 21). Draining the backlog took longer; the cap last held a session back 301–310 s before each release, which came at 3980–4920 s on the 300k pool and 5980–6140 s with the native pool.

With the cap removed, every run stayed good at the same arrival process for the remaining 3780–4720 s (300k) and 2560–2720 s (native) of the run. Over $[t_{rel}+300, 8700)$ each rescued run matched its NOBURST control, which never saw the burst: the same follow-up hit fraction and mean outstanding work (Table 3), the same turn latency in the engine (1.38–1.55 s against 1.38–1.67 s at 300k, 2.13–2.49 s against 2.13–2.51 s with the native pool), follow-up turn counts within 7 of each other, and the same number of sessions unfinished at 8700 s; each rescued run completed exactly 200 sessions more than its control, so every burst session finished. Over the same interval the same-seed BURST control, which received the same burst and was never capped, stayed at a follow-up hit fraction of 0.000 with 195–317 (300k) and 1133–1178 (native) requests outstanding, growing in 8 of the 9 runs (the 1.35 λ_{ref} seed-1 control stayed flat at about 200, as in §G.2), and turns that took 159–231 s and 523–532 s. At one arrival process the engine thus sat in either of two states that each persisted to the end of the run, and a transient intervention moved it from the trapped one to the good one, which then sustained itself without the cap: hysteresis on a real engine, as Corollary 5 predicts for a cap inside (n_1, n_2). Persistence here means that the drained state sustains itself with the cap removed: the release rule waits until the cap no longer binds, so the test does not cover a release while it still binds. After release the population was at or above the cap for 0–4.5% of the time at 300k (at most 27 sessions against 20), and with the native pool it stayed below it (at most 43–55 against 64).

The rescue costs waiting, not sessions. In the rescue runs 121–143 (300k) and 220–251 (native) sessions were paused, on average 386–569 s per paused session, and 196–344 and 1050–1101 sessions waited at admission, 408–683 s on average and at most 1318 s: 38–78 and 222–230 session-hours of delay at the client. Counting pauses, admission waits and the latency of every request, the rescued runs waited 4.4, 5.1 and 4.6 times less in total than their uncapped controls (cell means; a lower bound, since the controls' 206–1404 unfinished sessions were still waiting at 8700 s). Prevention costs no more client delay: the CAPPED arm of the paired tests, which applies the same cap from the start, delayed sessions by 40–65 session-hours at 300k, about as much as the rescue, and by 18–21 with the native pool, about 11 times less, because there the rescue starts from about 300 outstanding and its client queue peaks near 400. These comparisons, the persistence measures above and Fig. 4 are descriptive, computed after the registered verdict (Appendix R.3, Table 21). The blind simulator and the frozen model both predicted the rescue; both drain the native gate too fast, and R4 released 800–1750 s after the simulator's per-seed predictions and 19–22% after the model's, outside its ±15% tolerance, as was one of the six R1 releases (+18.8%; §I). The registered test SHED tried the alternative at 1.35 λ_{ref} on the 300k pool, stopping arrivals from 1800 s, 600 s after the burst: a stop of 3600 s left both runs good, but refused 355 and 378 sessions, and one of 600 s refused 56 and 59 and left both stuck (§I). The cap refused none.

G.4 The basin of the good state

The paired tests use one burst size, 200 sessions, which in our earlier simulator trapped every work-conserving policy. Two registered BURST-only tests at 1.65 λ_{ref} on the 300k pool vary it, with the same seeds: BASIN-1 with 25 and 100 sessions and BASIN-2 with 40, 50 and 60. BASIN-1 passed: a burst of 100 sessions left the engine stuck (hit fraction 0.000 over the evaluation window) and trapped by the registered slope rule in 3 of 3 seeds, and a burst of 25 left it good (RECOVERED, hit fraction 0.92–0.93, within 0.003 of the no-burst run with the same arrivals) in 3 of 3. The good state of the real engine therefore has a finite basin, whose boundary lies between 25 and 100 sessions in every seed, as in the calibrated simulator, where 25 sessions never trapped and 50 trapped about half the time (Appendix T.1). BASIN-2 tests the first-principles model's critical fresh burst of 53.4 sessions, from a heuristic

of §H.3 that counts a burst session at its peak footprint. Its registered rule held: a burst of 40 sessions left the engine good (RECOVERED, hit fraction 0.925–0.934, within 0.004 of the no-burst run with the same arrivals) and one of 60 left it stuck and trapped, in 3 of 3 seeds each, while 50 sessions, which the rule does not use, trapped seed 1 only. Over the seven sizes from 0 to 200 each seed switches from good to stuck once, between 50 and 60 sessions in seeds 0 and 2 and between 40 and 50 in seed 1: the boundary lies between 40 and 60 sessions in every seed but not at the same size, so 53.4 lies inside two of the three seeds' edge intervals. BASIN-1's and BASIN-2's registrations reached GitHub 68 and 131 minutes before their jobs were submitted; §I scores the frozen predictions.

G.5 A faster GPU narrows the window

The H200 cell repeats the 300k SGLang cell on one H200 NVL with SGLang's default attention backend for that GPU (FlashAttention 3; the A100 cells used FlashInfer), so the comparison is of GPU and default backend together. Against the A100, the all-miss rate rises 2.71 times (λ_{ref} = 0.194 sessions/s, turns-based), the peak of the closed curve only 1.63 times ($\mu^* = 0.367$ sessions/s at $n = 32$, turns-based; 1.65 times in completed sessions) and the from-empty edge, the largest all-stable nominal multiple of each GPU's seed-0 grid, 1.76 times: the engine stayed stable from empty at 1.1, 1.2 and 1.3 λ_{ref} and was unstable at 1.4, 1.55 and 1.75 λ_{ref}. All four reseeds (two at each of 1.3 and 1.4 λ_{ref}, added post hoc) were stable, so 1.3 λ_{ref} was stable in 3 of 3 seeds and 1.4 in 2 of 3 (seed 0 unstable). The seed-0 grid received 7–8% more arrivals than nominal, and, as on the A100, stability over all ten runs is monotone in the realized rate, with the edge between 1.496 and 1.503 λ_{ref}; the two 1.4 reseeds received 1.429 and 1.496. That bracket is only four sessions wide and the 1.503 run ended just above the queue threshold (50.4 against 50), so the data neither show a sharp edge nor need a stochastic band to explain them. The window shrinks from (1, 2.0) λ_{ref} on the A100 (nominal, on the seed-0 grid) to (1, 1.3) λ_{ref}, too narrow for our registration rule: it places the test points at 1.10 and 1.20 λ_{ref}, outside the band (1.1, 1.17) that keeps them at least 10% from the window's ends, so no registration, paired test or decisive claim exists for this GPU at this pool. The cliff moves out: the hit fraction crosses 0.5 near $n = 38.9$, against 32.2 on the A100, and past it falls gradually, to 0.46 at $n = 40$ and 0.16 at 52, reaching zero only between 52 and 96. Memory and tool time do not speed up with the GPU, so a faster GPU raises the all-miss capacity more than the peak, as the speed law of §H predicts for a uniform speed-up. With the pool doubled to 600k tokens on the same GPU (a separate, registered cell), the peak ratio $\mu^*/\lambda_{\text{ref}}$ rose 1.57-fold, from 1.89 to 2.98 (turns-based), and the from-empty edge moved from 1.3 to 2.5 λ_{ref}. The window (1, 2.5) λ_{ref} is then wide enough for the registration rule, which placed the test at 1.5 and 2.0 λ_{ref} with cap 48, as the frozen model had predicted. That pre-registered paired test passes at both rates: every BURST run stayed at zero hits with a growing backlog (trapped by the rule in 2 of 3 seeds at 1.5 λ_{ref} and 3 of 3 at 2.0), every NOBURST run was good and every CAPPED run recovered (§I). §I scores the model's frozen predictions for both H200 cells. KAIROS shows qualitatively that a slower clock tips a fixed arrival rate into thrashing [119], and VAMP locates KV capacity boundaries on H100 and H200 GPUs [64]; what we add is the measurement in units of λ_{miss} and the opposite movement of the onset and the peak ratio. In Lu et al.'s simulations a faster GPU raises the first trapped load in absolute terms while it stays at 0.46–0.70 of the steady-state overload rate [76]; the two statements use different normalizations, and both say that the vulnerability persists on the faster GPU.

G.6 Other orderings (exploratory)

Three other engine cells ran the BURST arm at the registered rates and seeds, with no control arms (Fig. 9 and details in Appendix R). Disabling SGLang's waiting-prefix refresh made no difference for FCFS. Stock LPM partly helps: from the 200-session burst it recovered in 4 of 6 runs at 1.35 λ_{ref} but in 1 of 6 at 1.65. On our reading of its source it stops re-sorting its queue when more than 128 requests wait, and in each run that ended trapped the last hit came when the queue last stood at or below 128. With that fallback disabled by a job-local hook (LPM-INF, exploratory, with its decision rule and the simulator's prediction frozen beforehand), LPM did not collapse on the two arrival streams on which stock LPM had collapsed in 4 of 4 runs (token hit fraction, the share of prompt tokens served from cache, pooled by completion time over the evaluation window: 0.59 and 0.42 against 0.000; unlike the turn hit fraction it has no 0.932 ceiling), but no run recovered by the registered rule; with one rate and two informative seeds this is directional evidence, and it does not separate LPM's ordering from the LRU touch of its prefix matching.

H A first-principles model of the thrashing curve

Section E.3 takes $\mu(n)$ as measured. Here we *predict* it, together with the all-miss level, the peak, the from-empty edge, the trapped state and the cap condition, from the pool size M, the workload of §E.1, the tool-time law, and the iteration-cost model of our simulator (§F.4), which was fitted only to server-log iteration timings. No parameter is fitted to any $\mu(n)$ point, from-empty outcome or trap measurement. Every proposition below is about a deterministic fluid model, and the layers of §H.3, the trapped-state layer included, are heuristics; we do not prove that the engine converges to the model. The model, its code and the proofs below were derived by LLM coding agents under the authors' direction (see Use of AI tools); these agents worked from every committed result of the three measured cells and the registered protocols, and saw no H200 result beyond its E0a measurements (the model's only H200 inputs), and no Llama, pool-sweep, basin, fresh-seed, LPM-INF or rescue result, before freezing the predictions of §I (Appendix N). A prediction is blind in time if it was pushed

before its runs were submitted or started, and blind by access only if its runs had ended or were in progress at the push but no one on the project, the agents that operated the cells and the first author included, is known to have read them before it (Table 8). Where someone had seen a result before a push, we say who; where a prediction is blind only with respect to the agents that made it, we say so.

H.1 Model

Let $w_k = P(T \geq k)/E[T]$ be the turn mix, $E_k = L_k + d$ the KV of a session after turn k, $\bar{E} = \sum_k w_k E_k = 10{,}569$ tokens, $A_1 = \sum_k P(T \geq k+1)E_k = 144{,}960$ the KV a session carries into tool calls over its life, $E[E_T] = 11{,}045$ its final KV, $\bar{z} = E[Z]$, and $\bar{z}' = \bar{z}(1 - 1/E[T])$ its tool time per turn. The tool time Z has distribution F_Z and density f. *Server.* At turn completion rate ν (turns/s) and follow-up hit probability h, turn k needs prefill GPU time $t_k(h) = t_k^m - h\,\mathbf{1}\{k \geq 2\}(t_k^m - t_k^h)$, with t_k^m, t_k^h the miss and hit prefill times of the cost model (a hit prefills $\Delta + 1 = 551$ tokens). SGLang runs prefill and decode in separate iterations with prefill priority, so prefill takes a fraction $p = \nu \sum_k w_k t_k(h)$ of the GPU and the number R_D of decoding requests solves $R_D(1-p) = \nu(d-1)\tau_D(R_D)$, where τ_D is the cost model's decode iteration time. A turn occupies the engine for $S_k = t_k(h) + S_D$ with $S_D = R_D/\nu$ and reserves its KV E_k throughout, so running requests hold $K_{\text{run}}(\nu, h) = \nu \sum_k w_k E_k S_k$ tokens. *Memory.* Idle KV (sessions in tool calls, and the KV of finished sessions, which the engine cannot know is dead) is evicted least recently used first.

Assumption MF (Che [17, 43])**.** *In stationarity an idle item is evicted at a deterministic idle age R.*

By $H = \lambda G$ the idle KV is then $\mu \mathcal{D}(R)$ with $\mathcal{D}(R) = A_1 E[\min(Z, R)] + E[E_T]R$, and the pool is full, so

$$\begin{aligned} M = K_{\text{run}}(\nu, h) + \frac{\nu}{E[T]}\mathcal{D}(R), \qquad h = F_Z(R), \\ n = \nu(\bar{S} + \bar{z}') + Q, \qquad \mu = \nu/E[T], \\ Q \geq 0, \quad K_{\text{run}} \leq M, \quad Q(M - K_{\text{run}}) = 0, \end{aligned} \tag{4}$$

Here $\bar{S} = \sum_k w_k S_k$, Q is the stationary fluid population waiting for admission, and $Q = \nu W_Q$ with mean admission wait W_Q. The last line is an additional no-slack fluid closure, assumption (S5) of Appendix Q, not a consequence of whole-request FCFS admission (S4). Under this closure a positive queue forces running reservations to fill the pool, hence $R = 0$ and $h = 0$; if $R > 0$, then $Q = 0$ and Little's law reduces to the queue-free equation. Whole requests can instead leave packing slack while the head request waits, a finite-request effect that this model omits. With $K_{\text{run}} = 0$ and no queue, Eq. (4) is the characteristic-time equation of Yao et al. [114] term for term. Three additions make the hit rate feed back on itself. Running reservations depend on h, because under prefill priority misses starve decode. Throughput is set by a server and a closed population, not by an exogenous arrival rate. And there is a memory-gated all-miss branch. On every partially hitting state the reuse gap is still the exogenous tool time; only on the all-miss branch does the queue set it. The queue-free cliff therefore comes from hit-dependent running reservations, with exogenous gaps. The additional no-slack closure defines the memory-gated all-miss branch; positive Q lengthens the reuse gap, but the turnover diagnostic below is not a separate proof that queueing causes eviction.

H.2 Results

Proposition 2 (stationary states and the all-miss onset)**.** *Let ν_b solve $K_{\text{run}}(\nu, 0) = M$, $\mu_b = \nu_b/E[T]$, and $E_S = \sum_k w_k E_k S_k / \sum_k w_k S_k$ at $(\nu_b, 0)$. (a) Each $R > 0$ gives exactly one queue-free stationary state; under the no-slack closure (S5), call the memory-gated states ($K_{\text{run}} = M$, hence $R = 0$, $h = 0$ and $\nu = \nu_b$) the all-miss states; every state with a positive queue is an all-miss state; $\mu(n) = \mu_b$ for all large n, so μ_b is the model's λ_{miss} and μ_∞ (the model's counterpart of Proposition 6 of Appendix P under its assumption (A4), that the congested engine computes prompt tokens as fast as with caching disabled). (b) All-miss states exist exactly for $n \geq n_b$, where*

$$n_b = \nu_b\,\bar{z}' + M/E_S, \tag{5}$$

the sessions in tool calls at the all-miss rate plus one pool's worth of running sessions; at population $n \geq n_b$ the all-miss state has a queue wait of $(n - n_b)/\nu_b$ seconds. (c) If every GPU cost is divided by s (a uniformly faster GPU), then $\nu_b \mapsto s\nu_b$, E_S is unchanged, and $n_b(s) = n_b(1) + (s-1)\,\nu_b(1)\,\bar{z}'$.

If F_Z vanishes on some $(0, r_0)$, as with a minimum tool latency, queue-free states with $h = 0$ and $\nu < \nu_b$ also exist below n_b; we do not call them all-miss states, and for the laws discussed here (exponential, mixtures of exponentials, lognormal), which have $F_Z(R) > 0$ for every $R > 0$, there are none. At 300k, $n_b = 4.94 + 27.76 = 32.70$ (native pool: 94.86; vLLM: 32.83). Parts (a) and (c), Proposition 3(b)–(c) and Proposition 7 rest on Lemmas 5 and 6, which are for the separate-iteration (SGLang) server; for vLLM's mixed-iteration model the identity of part (b) uses the same no-slack closure and a well-defined ν_b with a nonbinding chunk budget (Appendix Q). The pool part M/E_S has the form of MISA-T's cap, a reserved block budget over a conservative session length [51], and of AgentKV's collapse predictor (from its abstract) [3]. Here E_S weights each turn's KV by its service time at the all-miss rate (about 10.8k tokens at 300k), so $M/E_S = 27.8$ lies just below $N_{\text{lb}} = M/E_{\text{lb}} \approx 28.5$ of §E.2 and $M/\bar{E} = 28.4$; all three are capacity ratios of this form. The proposed distinction from those capacity ratios is the tool-call term and the identification of n_b as the onset of the all-miss branch under the no-slack fluid closure. On the two SGLang cells the measured 0.5-hit crossing (32.2 and 93.4) lies just below n_b; on vLLM it lies at 29.1, nearer the pool part (28.2) than n_b. Part (c) says that a uniformly faster GPU moves the onset *outward*: on an H200 at the same pool ($s = 2.742$, fitted to its all-miss token rate) $n_b = 41.3$. On the H200 the measured crossing moved out, from 32.2 to about 38.9, though past it the engine lost its hits more gradually than the model (§G.5, §I). With the A100 pool halved and doubled, the

measured crossings, 16.5 and 60.1, lay within 0.4 sessions of the frozen fluid predictions and 2.9 and 4.0 sessions beyond M/E_S, passing, blind in time, the test of the tool-call term declared with the second prediction set of §I (a crossing more than halfway from M/E_S to n_b), at 150k by 0.6 sessions. On Llama-3.1-8B it failed by 0.24 sessions and on the H200 at 300k it passed, but for those two cells it was declared after their curves had been read (Appendix S).

Proposition 3 (speed and tool time enter only through $s\bar{z}$)**.** *Write $\omega_b = \mu^*/\mu_b$, where μ^* is the supremum of the throughputs of all stationary states of this fluid model, including when its population curve folds. Let $Z = \bar{z}Y$ with a fixed nonnegative Y having a density and $E[Y] = 1$, and let $\bar{z} > 0$. (a) $\mu_b(C/s) = s\,\mu_b(C)$ (the model's λ_{miss}, Proposition 2(a)) and $\omega_b(C/s, \bar{z}) = \omega_b(C, s\bar{z})$ exactly, for cost model C. (b) ω_b is non-increasing in $s\bar{z}$, strictly while $\omega_b > 1$. (c) $\omega_b \to 1$ as $s\bar{z} \to \infty$.*

A uniformly faster GPU therefore lowers the peak ratio, the upper end of the window when the from-empty edge does not bind: the good state is limited by memory and tool time, neither of which speeds up. The same holds for slower tools. On the H200 the measured peak ratio against λ_{ref} was 1.89 (turns-based), against 3.15 on the A100 and 1.92 predicted (§I; the H200 is not a uniform speed-up: it also changes the attention backend, and its 64-to-32 all-miss token-rate ratio is 1.046 against 1.019 under uniform scaling, §H.6); this comparison is not blind to the first author, who had seen the H200 values for $n \le 32$ before the freeze. The pool enters only through the model's numerical curve; §I tests it with the A100 pool halved and doubled and the H200 pool doubled.

Proposition 4 (an exogenous-gap lower bound on hits)**.** *Suppose that the reuse gap of every follow-up is its tool time Z, with no queue wait, that running requests hold $K_{\text{run}} \ge 0$ tokens of the pool, and that idle KV is evicted at a deterministic idle age R (Assumption MF), so that $M - K_{\text{run}} = \lambda_0\,\mathcal{D}(R)$ at finite session throughput $\lambda_0 > 0$. Then $R \ge (M - K_{\text{run}})/(\lambda_0 E[T]\bar{E})$, so the follow-up hit probability $F_Z(R)$ is at least $F_Z\big((M - K_{\text{run}})/(\lambda_0 E[T]\bar{E})\big)$; and if F_Z is continuous and strictly increasing, a follow-up hit probability of at most h requires $K_{\text{run}} \ge M - \lambda_0\,\mathcal{D}(F_Z^{-1}(h))$. If additionally $F_Z(r) > 0$ for every $r > 0$, zero follow-up hit probability requires $K_{\text{run}} = M$.*

Proof. Since $\min(Z, R) \le R$ and $A_1 + E[E_T] = \sum_k P(T \ge k)E_k = E[T]\bar{E}$, we have $\mathcal{D}(R) \le E[T]\bar{E}\,R$, which gives the first bound, F_Z being non-decreasing. A hit probability of at most h means $R \le F_Z^{-1}(h)$, and $\mathcal{D}$ is increasing. □

With $K_{\text{run}} = 0$ the balance is the characteristic-time equation of Yao et al. [114]. Under this mean-field closure, at fixed finite positive throughput and for a tool-time law satisfying $F_Z(r) > 0$ for every $r > 0$, such as the exponential law used here, exactly zero follow-up hits require $K_{\text{run}} = M$; as the hit probability tends to zero, K_{run} must tend to M. This conclusion is not universal over exogenous gap laws: a positive minimum tool latency can give $F_Z(R) = 0$ at $R > 0$ with $K_{\text{run}} < M$. Our model is an exogenous-gap closure of this kind on every queue-free state, and this is how its cliff arises: running reservations grow as hits fall, so on the queue-free branch K_{run}/M rises continuously towards 1 as $R \downarrow 0$ (on the 300k pool 0.28 at the fluid peak, 0.89 at $n = 32$ and 0.97 at $n = 32.5$, with hit fractions 0.89, 0.37 and 0.15, all with no queue), and $K_{\text{run}} = M$ holds exactly only on the all-miss branch, where $Q = n - n_b$ (positive for $n > n_b$; Proposition 2(a)). Evaluated retrospectively on each closed run, with nothing fitted, exogenous-gap closures with little running KV never reach the measured zeros: at $n = 48$ on the 300k pool, where no turn hit, Yao et al.'s fixed point at the measured throughput gives a hit fraction of 0.93, the same equation with its rate set by Little's law at zero service time (about 11 times the measured throughput) 0.50 and Che's approximation with the tool time as the gap 0.55, and the proposition's bound with $K_{\text{run}} = 0$ at the measured throughput is 0.93, while the model, whose running reservations fill the pool there, gives 0.000 (Appendix Q gives every measured point past the peak of the three cells). The model is not exact on the cliff either: its fluid hit fraction differs from the measured one by more than 0.1 at four of those 15 points, 300k at $n = 32$ (0.51 measured, 0.37 fluid), vLLM at $n = 28$ (0.66; 0.81 fluid, 0.72 with H1) and $n = 32$ (0.08; 0.44 fluid) and the native pool at $n = 96$ (0.42; 0.00 fluid, 0.36 with H1), and by more than 0.3 at the last two; at the other 11 it is within 0.04.

On the finite grids evaluated, the fold criterion for the closed curve (Proposition 7, Appendix Q) finds no fold in any separate-iteration (SGLang) cell with the registered exponential tool times, and a numerical scan of $n(R)$ finds none for vLLM, to which the proposition does not apply. These scans support, but do not prove globally, the fold-free interpretation in which metastability on these cells belongs to the open system; dispersed tool times with the same 5 s mean can make the closed curve fold, and in our example (Fig. 6) the all-miss state and a good state are then both stable at one population (under a relaxation of the hit probability h at fixed n), but none of our engine runs used such a law.

Conditional on fold-freeness and unimodality of the predicted curves in the sense of §E.3, as suggested by the numerical scans (with $\mu = \mu_b$ on $[n_b, \infty)$), Corollary 5 applies with $n_2 \le n_b$, and on $[n_b, \infty)$ Eq. (2) makes the backlog grow at $\lambda - \mu_b$ (Appendix Q). The model does not use this for the trap: its trapped-state predictions come from the round-robin layer RR of §H.3. The registered caps lie inside (n_1, n_2): 20 in $(8.5, 32.2)$ at 1.35 and in $(10.4, 31.8)$ at 1.65 λ_{ref} on the 300k pool, 64 in $(27.8, 90.0)$ at 4.0 λ_{ref} with the native pool. The upper end n_2 inherits the quasi-static assumption, which is weakest near n_b (§E.3). Both caps lie below the predicted peak (Table 6) and $n_2 > n^*$, so $c < n_2$ holds wherever n_2 falls on the falling side of the curve, and only $c > n_1$ is at stake. The condition remains $n_1 < c < n_2$ (Corollary 5): $c < n_b$, which places the closed fluid system on its queue-free branch for the exponential law, is necessary but not sufficient for the gate to drain, since a cap in $[n_2, n_b)$ has $\mu(c) \le \lambda$ and its gate never empties.

Table 6: First-principles predictions against measurements (`results/theory/merged/validation_table.md`, frozen at tag `r13-theory-pred`). Inputs: pool, workload, server-log cost model; vLLM also one speed factor fitted to its own all-miss token rate. Measured μ is turns-based. The first row is the model's 32-session cache-off rate, its analogue of λ_{ref}, against λ_{ref} (vLLM: fitted); the model's all-miss level μ_b (Proposition 2(a)) is 0.0718, 0.0737 and 0.0670 sessions/s. The peak ratio is taken against the measured λ_{ref} here ($\omega_{\text{ref}} = \mu^*/\lambda_{\text{ref}}$), as in the scoring rules, not against μ_b as in Proposition 3. The trapped rows come from the round-robin layer RR (§H.3). [§]Measured flat top: grid points within 5% of the measured maximum (the frozen scoring rule uses 2%, which gives 24 alone at 300k). [¶]Fluid curve, the frozen primary; H1 gives 30.5, 92.0 and 30.7. Pairs of values are for the two registered rates of each cell. [†]The H2 edge criterion was chosen knowing these two brackets (in-sample). [‖]Nominal multiples on the single seed-0 grid; with fresh seeds 2.5 λ_{ref} was stable in 3 of 3 runs, and over all 12 runs the edge in realized arrival rates lies between 2.665 and 2.726 λ_{ref} (§I). [‡]Pushed before the registered vLLM verdict was computed (see text); every other measured value was known to the agents that derived the model. [#]Measured on the six exploratory vLLM BURST runs, whose seeds and arrivals the registered BURST arm repeats; the registered runs (Table 5) give backlogs 201–222 and 281–330 and token ratios 0.995–1.012 and 0.948–1.018.

	SGLang 300k pred / meas	SGLang native pred / meas	vLLM 300k pred / meas
cache-off $\mu(32)$ (turns)	0.0718 / 0.0715	0.0718 / 0.0718	fitted (0.0670 / 0.0657)
μ^* H1 (fluid)	0.234 (0.248) / 0.226	0.495 (0.508) / 0.466	0.235 (0.249) / 0.211
peak n H1 / flat top[§]	24 / 20–24	69.5 / 64–80	24 / 20–24
0.5-hit crossing n[¶]	31.5 / 32.2	93.7 / 93.4	31.8 / 29.1
peak ratio $\mu^*/\lambda_{\text{ref}}$ H1	3.27 / 3.15	6.89 / 6.48	3.58 / 3.21
from-empty bracket	$[2.0, 2.5]^{\dagger}$ / $[2.0, 2.5]^{\|}$	$[5.5, 6.5]^{\dagger}$ / $[5.5, 6.5]$	$[2.5, 3.0]$ / $[2.0, 2.5]$
trapped backlog	215, 304 / 200–232, 283–332	565, 1089 / 557–601, 1098–1139	206, 288 / 203–227, 277–309[#]
trapped token ratio	1.006, 1.016 / 1.009–1.025, 1.025–1.029	1.067, 1.079 / 1.074–1.078, 1.106–1.124	0.992, 1.002 / 0.997–1.007, 1.025–1.031[#]
good-state hit	0.932 / 0.921–0.934	0.932 / 0.929–0.935	0.932[‡] / 0.930–0.933
capped drain (s)	1576, 1941 / 1547–1904, 2021–2693	493, 815 / 512–583, 837–937	1449, 1725[‡] / 1521–2027, 1848–2735

Proposition 5 (cycle accounting identity)**.** *Consider a tagged session's completion-to-completion interval I of length $g > 0$ in the all-miss round-robin approximation. Suppose this interval accounts for one complete turn of each session i in a set $\mathcal{P}$, with total KV writes $V_I = \sum_{i\in\mathcal{P}}(L_{k_i} + d)$ and no net in-flight token carry-over at its endpoints. Define the churn on this same interval as V_I/g and $R_M = M/(V_I/g)$. Then*

$$\frac{g}{R_M} = \frac{V_I}{M} = \frac{\sum_{i\in\mathcal{P}}(L_{k_i} + d)}{M},$$

independently of the GPU cost model. A periodic cycle with fixed completion phases and the stated write-volume accounting gives the same identity for every session.

This is an accounting identity conditional on the cycle assumptions, not an eviction theorem or a proof that the all-miss regime sustains itself. One completion per session in an arbitrarily defined cycle does not by itself make every completion-to-completion gap equal to that cycle's duration; likewise, turns crossing the endpoints can make their total written tokens differ from the completed-turn sum. The engine meets the cycle assumptions only approximately, with arrivals, departures, overlapping service and a growing backlog. On the three 300k BURST runs at 1.35 λ_{ref} the measured backlog and prompts give 7.24, 6.43 and 6.81 against measured ratios of 6.92, 6.35 and 6.79, within 5%. Those window-level comparisons combine a median gap with average churn, so the proposition does not make them exact. The proposition says nothing about the good state; there we approximate the median gap by the median tool time plus the mean service time, so that $\text{gap}/R_M \approx (\bar{z}\ln 2 + \bar{S})\,\text{churn}/M$. Section H.4 compares both with the engine. The underlying cycle argument is EfficientAgent's: in a backlogged pool the other agents' contexts are referenced between two turns of one agent, giving a reuse-distance scale of the pool's total context (its Eq. 5, an approximation for a host KV tier in a closed pool) [98]. Proposition 5 states the corresponding time-domain accounting relation under explicit cycle assumptions.

H.3 Heuristic layers (nothing fitted)

Five heuristic layers, RR and H1–H4, with nothing fitted, extend the model where the propositions do not reach; Appendix Q defines them. (The frozen files and the code call H1–H4 F1–F4; we rename them here to keep them apart from the assumptions F1–F6 of model F, §2.) *RR*, the trapped layer, replaces Eq. (2) in the trap by a fluid FCFS round robin in which every follow-up misses and every present session completes one turn per cycle; the trapped rows of Table 6 and the model column of Table 7 come from it. *H1* averages the curve over the KV-demand fluctuation of n sessions. *H2* predicts the from-empty edge from a one-dimensional diffusion of the demand. *H3* gives the probability that a burst leaves a run stuck; burst sessions are fresh, so a burst counts by its peak footprint (4,331 tokens per session, at turn 12), not by its number. *H4* gives the release time of a cap engaged inside the trap.

H.4 The sustaining variable on the engines

At the same arrival rate the good and the trapped state differ in how long a session's KV lies idle between turns compared with how long the pool keeps idle KV. Let the gap of a follow-up

turn be the time from the completion of its session's previous turn to its own completion, the tool time plus the turn's latency, and let $R_M = M/\text{churn}$, where churn is the rate at which new KV is written (uncached prompt tokens plus completion tokens per second). Here R_M is a pool-turnover scale computed from average writes, not a pathwise upper bound on eviction age and not the characteristic time R of Assumption MF. An average churn rate does not control the writes during a particular idle interval. Even for a constant rate, identifying gross writes with LRU reuse distance requires additional assumptions about distinct content, reclamation, locking and recency updates. Denning's reuse-window criterion [31] and Che's characteristic-time approximation [17] motivate this diagnostic, but do not make an idle time exceeding R_M a sufficient miss condition here. Moreover, the measured gap includes the turn's own service, and SGLang's refresh of waiting prefixes (§D) resets the age of some of them. We therefore treat gap/R_M as a descriptive proxy. Table 7 gives its median in every arm of the three registered tests, computed by the script frozen for the vLLM mechanism checks. In every good-state run the ratio is 0.010–0.028: the gap is 4.9–5.9 s, mostly tool time, and R_M is 188–505 s. In every BURST run it is 4.1–9.7: R_M falls to 26–78 s because the trapped engine rewrites the pool at the all-miss rate, and the gap rises to 166–516 s, of which the mean tool time is 4.8–5.1 s and the rest is the turn's latency, mostly time in the queue (a turn's own service takes seconds). Turn latency, not tool time, carries the gap past R_M. The trapped value is close to the identity of Proposition 5, which is exact for the specified common-interval cycle accounting, rather than for arbitrary window averages: in that approximation gap/R_M equals the complete-turn KV volume divided by M, and the round-robin layer RR, with nothing fitted to any trapped measurement (it uses the arrival rate, the burst and the server-log cost model), gives values within 4% of the measured means (Table 7); this agreement is in sample, since the agents that derived the model knew the measured trapped values of the SGLang cells and of the exploratory vLLM runs, whose arrivals the registered vLLM arm repeats. These are correlations across two states at one load; in the registered TOOLSLOW test of §I, a temporary increase in tool latency with no burst, 30 s more per tool call for 900 s, trapped the engine in 1 of 3 seeds and 10 s more in none, so a trigger without a burst can trap the engine, but its registered rule (2 of 3) was not met, and the test does not separate the gap from the capacity loss that the slowdown also causes. Section 7 places this measurement against EfficientAgent's backlogged-pool working set and CacheRoute's revisit criterion.

H.5 Validation

Table 6 compares the predictions with the three measured cells. Inputs and outputs are separated: for the SGLang cells the model receives M, the workload and the cost model and predicts everything else; for vLLM it also receives one speed factor fitted to vLLM's own all-miss token rate, so its λ_{miss} is not a prediction. The agents that derived the model knew every measured value in the table except the vLLM cells marked ‡, whose predictions were pushed at 02:05:30 CDT, three minutes before the registered vLLM verdict was computed and, by the log of the agent that operated the registered vLLM test (`notes/LOG.md`), before any of that test's run directories was opened; the theory's blindness declaration does not cover these runs (§G.2). On the turns-based estimator, which measures the model's $\nu/E[T]$, the H1 peak is 3.6% and 6.3% high on the SGLang cells and the fluid peak 9.9% and 9.0%. Assumption MF is the likeliest cause: the memory balance fixes the mean of $\mathcal{D}(R)$, and the hit probability $F_Z \circ \mathcal{D}^{-1}$ is concave in it, since its derivative $f(R)/(A_1 P(Z > R) + E[E_T])$ decreases for exponential tool times (indeed for any non-increasing hazard), so by Jensen a deterministic R overstates hits near the peak. The vLLM cell is a partial miss: its cliff comes earlier and steeper than predicted. Figure 3 shows the curves. Out of sample, Table 8 (§I) scores every frozen prediction, misses included.

Table 7: The sustaining variable: median gap between a session's turns over the pool's turnover time $R_M = M/\text{churn}$, over the evaluation window, ranges over seeds (good arms: NOBURST and CAPPED). Gap: median, seconds. Model: Proposition 5 applied to the turn mix and backlog that the round-robin layer RR of the first-principles model predicts (§H.3; tag `r13-theory-pred`; for vLLM validated on the exploratory runs, whose arrivals the registered BURST arm repeats). In sample: the SGLang BURST values and the exploratory vLLM values (6.51–6.72 and 8.05–8.63) were known to the agents that derived the model; the registered vLLM values shown had not been opened at the freeze (§H.5), but the theory's blindness declaration does not cover them. Computed by `analysis/r11/loopvars_frozen.py` (commit `f1338e3`), unchanged.

		good arms		BURST		
test	$\lambda/\lambda_{\text{ref}}$	gap/R_M	R_M (s)	gap/R_M	gap (s)	model
SGLang 300k	1.35	0.016–0.020	255–307	6.35–6.92	166–178	6.93
	1.65	0.022–0.028	188–230	8.18–9.67	210–249	8.98
SGLang native	2.5	0.010–0.012	446–505	4.14–4.57	322–354	4.45
	4.0	0.018–0.022	272–310	6.68–6.96	504–516	7.06
vLLM 300k	1.35	0.014–0.017	286–337	6.44–6.79	183–196	6.64
	1.65	0.019–0.022	229–264	8.16–8.78	231–261	8.52

H.6 Weaknesses

Every proposition is about the deterministic model; we have no limit theorem that takes the engine, or the simulator, to it. Its onset and positive-queue classification additionally use the no-slack closure (S5), which omits whole-request packing slack. Assumption MF is a characteristic-time approximation motivated by concentration with many small objects, whereas our pools hold few: one session's mean footprint is 3.5% of a 300k pool, and the mean live demand of the predicted (H1) peak population is 85% of the pool on the A100 at 300k and on vLLM, 99% at 150k and 114% on the H200 at 300k, where it already exceeds the pool. The frozen notes named this lack

of concentration, worst on the H200, as the likeliest failure there and expected it to bias μ^* upward; the H200 peak was matched at 300k and within tolerance at 600k (7.3% high), but past the peak the measured hit fraction stays above the prediction at both pools, the opposite of the overstatement of hits near the peak that a deterministic R implies for these exponential tool times, and we have not traced this miss to a specific assumption (§I). At 150k the H1 peak was 11.5% high, in the expected direction, and H2 put the from-empty edge two grid steps too low. The H200 predictions divide every A100 cost by one factor; uniform scaling predicts a 64-to-32-session ratio of all-miss token rates of 1.019, against 1.046 measured, and a variant that fits both gives the low end of the frozen band. On vLLM the cliff comes earlier and steeper than predicted (crossing at 29.1 against 31.8; $\mu(28)$ 0.123 against 0.225 sessions/s, turns-based), and its plateau below λ_{miss} is not reproduced. The heuristics have their own misses: H2 was pessimistic about the 300k from-empty edge on fresh seeds, having been chosen knowing the seed-0 bracket, whose unstable run had received 2.73 λ_{ref}; and H4, like the simulator, drains the native-pool gate too fast (R4 released 19–22% late). Cell-wise unimodality and fold-freeness have numerical, not globally certified, support; Proposition 7(c) gives stability only for the auxiliary relaxation at regular nonneutral queue-free states; RR and H1–H4 are heuristics; choosing this model over a second derivation, and H2 over another edge criterion, were selections made on the three measured cells; and the cost model was fitted to the server logs of the 300k Stage C runs, so that comparison is out of sample in its target but not in its data source. Proposition 7 proves a model-level criterion; its global sign has not been certified on the reported cells or evaluated for any measured tool-time law. The basin predictions rest on quantities defined at n_2. The curve $\mu(n)$ fixes $n_2 - n_1$ (21.3 sessions), the critical burst under Eq. (2) for sessions with the stationary turn mix, which would have 40 stuck; but a burst of fresh sessions changes the composition, which N alone does not track, and near n_2 the quasi-static model is least reliable. So $\mu(n)$ does not determine the critical fresh burst (53.4 sessions), and BASIN-2 tests the heuristic H3, not a consequence of the propositions.

H.7 Relation to prior models

Yao et al. [114] give a mean-field (Che-type) LRU hit ratio for multi-turn sessions with exogenous gaps between turns and a unique fixed point, and note that end-to-end latency may change the observed gaps without modelling it; Eq. (4) reduces to theirs when nothing runs and nothing queues, and Proposition 4 gives a mean-field lower bound on hits that excludes exactly zero stationary hit probability with positive idle capacity for the exponential tool law used here. Here the feedback runs through service time and reserved KV: misses starve decode under prefill priority, which swells running reservations and squeezes idle KV, turning their unique fixed point into a curve with a rise, a peak, a cliff at Eq. (5) and an all-miss branch on which the queue sets the reuse gap. MISA-T describes the eviction–cold-prefill–queue loop in words and derives a session cap of the form of the pool part of Eq. (5) [51], and AgentKV predicts the collapse from the same kind of capacity ratio [3]; neither gives equilibria, a rescue condition or a fold criterion, and a capacity ratio leaves out the sessions in tool calls, a term that grows with GPU speed (Proposition 2(c)). The closed curve is a Denning thrashing curve [30], and Corollary 5 is the classical decomposition argument [25] applied to a predicted $\mu(n)$. Lu et al. write the same population balance, $\dot{N} = \lambda - X(N)/K$, with an empirical hit curve $h(W/C)$ and an empirical cliff $N_c \approx 1.9\,C/\bar{c}$ [76]; that cliff is also a capacity ratio, without the tool-call term. What we believe is new: a predicted thrashing curve for prefix-cached agent serving, the onset identity and its speed corollary, the $s\bar{z}$ law for the peak ratio, the exogenous-gap bound, a model-level fold criterion, and a time-domain accounting form of the trapped-cycle relation. Appendix Q relates the model further to the Che approximation and its analyses, to CacheRoute, to classical couplings of cache loss and queueing and to metastable-failure models, and states the limits of our literature search.

I Frozen predictions and their tests

The registered tests of §G.2 check rules written before them. For the later tests, predictions were also frozen: by the calibrated simulator (§F.4) and by the first-principles model of §H, under tags `r13-theory-pred` (pushed at 02:05:30 CDT on 2026-10-31) and `r13-theory-pred2` (pred2 below, pushed at 04:20:20), whose new drivers call the model's frozen functions unchanged, with primaries, estimators, tolerances and refutation rules fixed in advance (`notes/THEORY_r13_scoring.md`). Each was committed under its tag before any of its results was read by the agents that made it (the Llama-3.1-8B registration-conditional predictions were pushed untagged, at 07:52 CDT, after their jobs were submitted but before any started); what each prediction is blind to differs and is stated with it. Table 8 summarizes the outcomes in hand, and Appendix S gives every prediction in full (Tables 23–25). Every outcome is reported against these rules, misses included.

H200, 300k pool. The model's only H200 inputs were that GPU's E0a measurements, through one speed factor, $s = 2.742$, fitted to its all-miss token rate (Proposition 2(c)). At 300k its peak ratio, crossing and from-empty edge held (Table 8; the edge on the original seed-0 runs in nominal multiples, while in realized rates, 1.496–1.503 λ_{ref}, H2 was about 7% pessimistic), no refutation rule fires, and from $n = 40$ the engine keeps more hits than the model (§H.6). The agent that operated the 300k H200 cell showed its closed-curve values for $n \le 32$, which include the predicted peak, to the first author before the freeze, though not to the agents that derived the model, so the peak ratio is not blind to the first author; the runs at $n = 36$, 44 and 52 are blind in time, and the other closed runs and the original from-empty runs, which had ended before the freeze, blind by access only (Appendix S).

Table 8: Frozen predictions and the outcomes in this version. "Simulator": the calibrated simulator of §F.4; "theory": the model of §H. Blind in time: pushed before the runs were submitted or started; by access only: the runs had ended, or were in progress, at the push, and were first read after it by anyone on the project. Appendix S gives every prediction with its scoring rule.

Test	Frozen prediction	Outcome
H200, 300k pool (a measurement, not registered)	Theory: peak ratio 1.92, 0.5-hit crossing 37.3 ± 3, all-miss onset 41.3, from-empty edge 1.39 λ_{ref}. Peak not blind to the first author; n = 36, 44, 52 blind in time; the other runs blind by access only	Peak ratio 1.89, crossing ≈ 38.9, edge in [1.3, 1.4) λ_{ref} nominal (a hit; H2 about 7% pessimistic in realized rates); no refutation rule fires. Tail softer than predicted from n = 40, so the onset (41.3) came early
H200, 600k pool (registered)	pred2: peak ratio 3.20, crossing 66.6 ± 3, edge 2.57 λ_{ref}, registration at 1.5 and 2.0 λ_{ref} with cap 48; there, trapped backlog 458 and 867, token ratio 1.054 and 1.064. Blind in time	Peak ratio 2.98, nominal edge in [2.5, 3.0) and registration as predicted; crossing ≈ 71.0, a miss (tail softer, as at 300k). Paired test passes at both rates (BURST trapped 2 and 3 of 3, at zero hits 6 of 6); backlogs within 15%, token ratios outside ±0.03 in 5 of 6
Pool sweep, A100, 150k and 600k	Theory: peak ratio 1.87 and 5.47, crossing 16.9 and 60.0, edge 1.09 and 4.53 λ_{ref}. Blind in time	600k: all within tolerance. 150k: cliff within tolerance; peak ratio (1.68; predicted 11.5% high) and edge ([1.2, 1.3), two steps above) missed
Llama-3.1-8B, 300k (registered)	Theory, a priori: peak ratio 3.37, crossing 30.9 ± 3, edge 2.55 λ_{ref} (2.46 times its a priori λ_{miss}). pred2, declared after the curve was read: tool-call term if the crossing exceeds 29.89; the nearest of M/E_{lb}, M/E_S and the frozen crossing wins. Simulator: peak at n = 20; primary mode: edge 2.5, rates 1.5, 2.0 λ_{ref}; a pass at both registered rates. Closed runs by access only, from-empty runs blind in time	Peak ratio 3.28 at n = 20, crossing 29.65: within tolerance, but 0.24 below 29.89 (a fail); the nearest-predictor rule picks M/E_{lb} (28.44), by 0.06 on the listed crossing. Edge in [2.0, 2.5) λ_{ref}, so the theory's edge is one grid step high (a near miss). Simulator: peak and cap right; edge and rates one step high. Paired test passes at 1.65 λ_{ref} (trapped 2 of 3) and fails at 1.35 (1 of 3; all six BURST runs at zero hits), so the simulator's pass at 1.35 missed
Fresh-seed E0b, 300k (exploratory)	Simulator: stable in 6 of 6 (blind in time). Theory (H2, not declared for this test; pred2's table pushed after the runs were read): unstable with probability 0.69 per run at 2.5 λ_{ref}	Stable in 6 of 6: the seed-0 bracket is not replicated (the rule needed 2.5 λ_{ref} unstable in 2 seeds). H2 pessimistic (all three stable at 2.5: 0.03). Later same-plan replicates (exploratory) reproduced seed 0's collapse and seed 4's stability, 3 of 3 each: H2 does not describe same-plan replicates (not a refutation of its cell-level escape probability)
BASIN-1, 1.65 λ_{ref} (registered)	Simulator: pass (blind in time). Theory: this outcome with probability 0.879 (blind by access only)	PASS: 100 sessions trapped and 25 absorbed, 3 of 3 seeds each; simulator right in 6 of 6 runs
BASIN-2, 1.65 λ_{ref} (registered)	Theory: stuck with probability 0.14, 0.55, 1.0 at 40, 50, 60 (critical burst 53.4). pred2, per seed (primary): the rule holds with probability 0.66; secondary, a deterministic crossing per seed. Blind in time	Bracketed: 40 good, 60 stuck, 3 of 3 each; 50 stuck in 1 of 3; 53.4 inside two of three per-seed edges; pred2's primary wrong for seed 0 at 40 and 50 (stuck with probability 0.78, 0.86; both good), right side in the other 7; secondary right in 9 of 9
Rescue R1, 300k (registered)	Simulator: pass, per-seed release times. Theory: rescued, release at 3830 and 4360 s (±15%). Both blind in time	PASS, 6 of 6 rescued, no relapse. Releases within 600 s of the simulator's in 6 of 6 and within ±15% of the theory's in 5 of 6
Rescue R4, native pool (registered)	Simulator: pass, per-seed release times. Theory: rescued, release at 5040 s (±15%). Both blind in time	PASS, 3 of 3 rescued, no relapse. Releases 800–1750 s after the simulator's and 19–22% after the theory's, outside its ±15% (a miss, or a refutation by the headline table; see text)
LPM-INF, 1.65 λ_{ref} (exploratory)	Simulator: no collapse on the seeds on which stock LPM collapsed (blind in time)	No collapse (token hit fraction 0.59 and 0.42); level missed (0.08–0.10 predicted; no partial hits, as flagged); no recovery
SHED, 1.35 λ_{ref} (registered)	pred2: arrivals stopped from 1800 s for 600 s do not drain the trap (1.00 per seed), for 3600 s drain it (0.998); rule 0.997. Blind in time	PASS: 600 s stuck, 3600 s good, 2 of 2 each; 56–59 and 355–378 sessions refused (the cap: none)
TOOLSLOW, 1.35 λ_{ref}, no burst (registered)	pred2: tool calls 10 s longer for 900 s leave the engine good (0.71 per seed), 30 s longer trap it (1.00); rule 0.80. Blind in time	Rule not met: 10 s good in 3 of 3, but 30 s stuck in 1 of 3; pred2 missed

Table 9: Frozen predictions of round 15 (2026-11-05, after Lu et al.'s paper appeared) and their outcomes, with the conventions of Table 8; times in Table 17.

Test	Frozen prediction	Outcome
TOOLSLOW-W, 1.35 λ_{ref}, no burst, 30 s longer for 1800 s (registered, round 15)	Simulator, both modes: stuck in 3 of 3 (TRAPS); pred2: TRAPS, stuck with probability 1.00 per seed; trap-state law: S1–S5 of `icml-trap-pred`. Blind in time; designed after TOOLSLOW and after reading simulator outputs	TRAPS, 3 of 3; every model right; pooled S1–S4 pass; outstanding requests at 3300 s off the reference accuracy by 8 and 6 in seeds 0 and 2 (§3)
TOOLSLOW-D15, 1.65 λ_{ref}, no burst, 15 s longer for 900 s (registered, round 15)	Simulator, both modes: stuck, good, good (NO-TRAP); pred2 fluid verdict: TRAPS; pred2 per seed: modal stuck, good, good, $P(\text{TRAPS}) = 0.58$. Blind in time	[pending: outcome]
CUT, BURST at 1.65 λ_{ref}, arrivals cut at 2400 s to 1.15 (CUT-A) or 0.85 λ_{ref} (CUT-B) (registered, round 15)	Model F (`icml-cut-pred`), from each seed's exact plan: all six stuck; backlog slopes over $[3000, 8700)$ s of $+0.0039$, -0.0026, $+0.0028$ (CUT-A) and -0.0095 to -0.0131 /s (CUT-B). Blind in time; the rule was registered after the predictions were read	CUT-A: PASS, theory-favoured 3 of 3, late sign 2 of 3 as predicted; the rule rejects only constant-throughput readings. CUT-B: [pending: outcome] (§3)
REPLICATE-EDGE, 2.5 λ_{ref} from empty, 300k, the plans of seeds 0 and 4 (exploratory, round 15)	Every deterministic predictor (the simulator in both modes, pred2's level crossing, the arrival, turn and token counts): each plan reproduces its original; H2 read as independent draws: reproducible with probability 0.0097. Blind in time; the plans were chosen knowing the originals	Reproducible: seed 0 collapsed in 3 of 3 (at 1600, 1600 and 1800 s), seed 4 stable in 3 of 3; H2 does not describe same-plan replicates (§8)

Pools and the window law. The pool sweep repeated Stage C and E0b on the A100 with the pool halved (150k tokens) and doubled (600k), with no parameter refitted; its runs started after both prediction sets were pushed. At 600k every scored quantity is within tolerance. At 150k the model located the cliff (crossing 16.5 against 16.9) but overstated the peak ratio by 11.5%, in the direction the frozen notes expected from Assumption MF, and H2 put the edge two grid steps low; no refutation rule fires. At both pools the frozen crossing, which counts the sessions in tool calls, was nearer than the capacity ratio M/E_S (2.9 and 4.0 sessions early) and the exogenous-gap closures (7–46 sessions late); on Llama-3.1-8B M/E_{lb} won that rule narrowly (below). On the H200 with 600k (pred2) the peak ratio, peak position, edge and registration came as predicted, but the crossing came 4.4 sessions late, a miss. Over six cells (Table 22 and Fig. 10(b), Appendix S) the measured window shrinks with GPU speed and grows with the pool, consistent with the model's numerical curves. Proposition 3 proves monotonicity of the peak ratio, not of the from-empty edge that sets these measured windows. Doubling the pool raised the peak ratio 1.81-fold on the A100 and 1.57-fold on the H200, against 1.67 for both; H2's edge lies inside the measured nominal bracket in five of the six cells (two of the three blind in time).

A second model. With Llama-3.1-8B-Instruct on the same GPU, engine and pool, λ_{ref} is 17% lower (0.0596 sessions/s) and the curve has Qwen's shape (Table 8), so the registration rule gives Qwen's rates and cap. The model's a priori prediction, pushed while the closed runs were in progress (blind by access only), came within tolerance on the peak (+6.7%), peak ratio, peak position and crossing, and its edge was a near miss. The crossing, 29.65, failed pred2's test of the tool-call term, by 0.24 sessions, and pred2's nearest-predictor rule picks M/E_{lb} (28.44, 1.21 sessions away) over the a priori crossing it lists (30.92, 1.27 away); read at the measured speed factor, the frozen crossing would win narrowly (Appendix S). Both rules were declared with pred2 after this curve had been read.

Basin. For BASIN-1 the simulator, pushed 68 minutes before the jobs were submitted, predicted a pass and matched all six per-run calls, with hit fractions within 0.006 and backlog slopes within 0.0005 sessions/s of the engine's. The model gave the observed outcome the probability $1.000 \times 0.958^3 = 0.879$, blind by access only: every run had passed its burst before the push, and the 100-session runs had ended. For BASIN-2, pred2, conditioning on each seed's burst, gave the registered bracketing rule probability 0.66, blind in time. It held. The per-seed probabilities, pred2's primary prediction, were on the more likely side in 7 of the 9 runs but gave seed 0 a stuck run with probability 0.78 at 40 and 0.86 at 50 sessions, and both runs stayed good (Brier score 0.17, against 0.10 for the frozen average-burst probabilities); its secondary prediction, a deterministic level crossing on each seed's exact arrivals, called all nine runs. The critical burst of 53.4 lies inside the edge interval of seeds 0 and 2, $(50, 60]$, not of seed 1, $(40, 50]$.

Rescue. Both prediction sets were pushed before the first rescue run started (the simulator's at 21:30:40 CDT on 2026-10-30, the model's at 02:05:30; first start 02:23:44 on 2026-10-31), so all nine runs are blind in time to both. The simulator's pass and no-relapse calls all held, and its release times were early in R4 (Table 8). The model predicted rescue in every cell, almost no relapse, and releases at 3830, 4360 and 5040 s (±15%): R1 released within the tolerance in 5 of 6 runs, all late (+1.6% to +18.8%), and R4 outside it in 3 of 3, 19–22% late. The scoring declaration calls a release outside ±15% a miss and makes only NOT RESCUED refute, while the headline table frozen with it lists the release time as falsifying; under that table the R4 release prediction,

and the R1 prediction at 1.35 λ_{ref} seed 0, are refuted. R4's engage time was moved from 2400 to 2100 s after the simulator had predicted 13 of 20 rescued at 2400 s, and the agents that froze the model's rescue predictions knew the simulator's (Appendix S).

Earlier prediction rounds. The calibrated simulator's first three prediction rounds (rounds 6, 8 and 9 of §F.4: B1–B4, B1n–B4n, B1v–B4v) predicted the registered paired tests and the curves and edges behind them (Appendix N.1, Table 18). Every predicted pass held (B3n's at its own test points, 6–16% above the registered rates), with trapped token rates and good-arm hit fractions close to the engine's. B4 and B4v got the peak's level within 9% and 2% but not the cliff (B4's came early, mostly because it was predicted for a smaller pool, and B4v's late); B2 and B2v got the from-empty edge in nominal multiples, and the primary mode of B2n put the native edge at least one grid step too high. Appendix N gives what each round is blind to.

Paired tests on the H200 and on Llama-3.1-8B. Both registrations reached GitHub before their jobs were submitted (by 63 and 47 s; neither is tagged), so both tests are pre-registered. On the H200 with the 600k pool (jobs 17171020–37) the registered analysis passes at both rates: every BURST run stayed at zero hits with 1.04–1.11 times the all-miss token rate and a growing backlog, trapped by the slope rule in 2 of 3 seeds at 1.5 λ_{ref} (seed 1 indeterminate, its slope 1.3% below the threshold) and 3 of 3 at 2.0 λ_{ref}, while NOBURST stayed good and CAPPED (cap 48) recovered in 6 of 6 runs each. pred2's trapped backlogs (458 and 867 sessions) lay within 15% of all six runs (485–509 and 873–913), but its token ratios lay 0.038–0.049 below the measured ones in 5 of 6, outside the ±0.03 tolerance. On Llama-3.1-8B (17170409–26) every BURST run stayed at zero hits at 1.01–1.05 times the all-miss token rate, every NOBURST run was good and every CAPPED run (cap 20) recovered, but the slope rule called only 1 of 3 BURST runs trapped at 1.35 λ_{ref} (one indeterminate, one draining) and 2 of 3 at 1.65 λ_{ref}: the registered analysis passes at 1.65 λ_{ref} and fails at 1.35. That all six BURST runs were stuck is a descriptive reading, not the registered criterion. The simulator had predicted a pass at both rates, so its pass at 1.35 λ_{ref} missed. The registration-conditional predictions put the trapped backlog within 10% of all six runs (191 and 266 sessions, against 196–210 and 267–288), the NOBURST hit fraction within 0.007 of every run's (0.932) and the trapped token ratio (1.004, 1.013) within ±0.03 in 3 of 6 runs; in the other 3 it lay 0.031–0.046 below, outside the tolerance (Appendix S).

Arrival stop and tool slowdown. Two registered tests at 1.35 λ_{ref} on the 300k pool, submitted after pred2's push (blind in time), probe another exit from the trap and another trigger. SHED stops arrivals from 1800 s, 600 s after a burst of 200, for τ = 600 or 3600 s: with τ = 600 s both runs stayed stuck (hit fraction 0.000 over the evaluation window) and with τ = 3600 s both were good (0.930 and 0.933), as pred2 predicted (rule probability 0.997; its shortest rescuing stop, 1795 s, lies between the two). The stops refused 56–59 and 355–378 sessions; the cap of §G.3 refused none. TOOLSLOW lengthens by δ every tool call that starts in $[1200, 2100)$ s, with no burst. With δ = 10 s all three runs stayed good, but with δ = 30 s only seed 2 was trapped while seeds 0 and 1 recovered, so the registered rule (stuck in at least 2 of 3) was not met. pred2 had predicted a trap in every seed at 30 s (probability 1.00 per seed; rule 0.80), and its per-seed walk put seed 0, which recovered, highest (49 sessions at 2100 s, against 37 and 39): a miss of the model. A 30 s slowdown of every tool call for 900 s, with no burst, can trap the engine, but did so in one of three seeds.

J A diagnostic, and what it implies

Choosing the number of admitted jobs from the throughput curve is the classical selection of a multiprogramming level [33, 49, 96]; session-based admission, client-side concurrency limits and cold-start tests at maximum concurrency are established practice [12, 21, 80]; and capacity ratios and stack-distance estimators size admission or a KV tier, the latter for a target hit rate or when turn gaps are exogenous [3, 70, 98, 114]. What the window adds is that the from-empty edge, a finite-horizon stability limit in the sense of Kleinrock and Lam's first exit time [66], and not only μ^*, bounds the operating range; that admission control prevents the trap and, in simulation, undoes it, and that the vulnerable range moves with cache capacity and tool time, Lu et al. show on disaggregated SGLang [76]. Only the evaluation on colocated engines, the from-empty edge as an upper bound and the placement condition below are ours.

The window of Eq. (3) comes from three measurements that an operator can make before deployment, on the engine, model, pool and workload that will be served. (1) *All-miss capacity*: run a saturated closed population with prefix caching disabled at two populations (for example 32 and 64 sessions), take the larger uncached prefill token rate, which is stable across seeds, and convert it to sessions by the mean work per session; if sessions share a prefix, measure with caching on and each turn's private context fresh instead. Under request-level FCFS this bounds the recovery threshold from deep congestion (Proposition 6, Appendix P). Our λ_{ref} is E0a's turns-based rate at 32 sessions; by this procedure λ_{miss} would be 1.034 λ_{ref} on SGLang and the A100 and 1.042 λ_{ref} on the H200, whose 64-session all-miss token rate was 4.6% above the 32-session one (1.7% on the A100), so in those units the H200 window is about $(1, 1.25)$ at 300k, with the realized edge near 1.44, and $(1, 2.4)$ at 600k. (2) *Closed-population curve*: measure $\mu(n)$ on a grid that crosses the cliff, and do not read μ_∞ off the largest n of a short run with a synchronized start (here $\mu(300)$ was 51% above λ_{ref}). (3) *From-empty edge*: run open arrivals from an empty engine at increasing rates over the horizon of interest, with more than one arrival seed or in realized rates (at 300k, 2.5 λ_{ref} was unstable on one

seed and stable on three others). Appendix R gives the pitfalls of each measurement. Here the three measurements took 14–16 A100-hours per pool and engine, and the burst check of the cap below (a three-arm paired test) about 7.5 more per rate and seed.

If $\mu^* > \lambda_{\text{miss}}$, then in the fluid model of §E.3, under request-level FCFS and the assumptions of Proposition 6, every operating point in $(\lambda_{\text{miss}}, \min(\mu^*, \lambda_e))$ is one sufficiently large burst away from the congested state unless admission is bounded; a steady-state load test there passes without testing recovery. On the engine a burst of 200 sessions, 6 to 29 times the 7–34 sessions present in the good state, left every registered BURST run at zero hits (23 of the 30 trapped by the registered rule), and at 1.65 λ_{ref} bursts of 60 and 100 also trapped the engine in all three seeds, 50 in one, and 25 and 40 in none. Without a cap, Proposition 6 and the fluid model predict that recovering from deep congestion requires cutting the arrival rate below λ_{miss}, which was 31% of peak throughput at 300k tokens and 15% with the native pool; in the registered SHED test, stopping arrivals for 3600 s after a trap drained it, but refused 355–378 sessions, while a 600 s stop refused 56–59 and did not drain it (§I). A cap does it at the offered load, refusing none. Corollary 5 says that a cap drains a burst, or an established trap, if it lies inside (n_1, n_2), fastest where $\mu(c) - \lambda$ is largest, at the peak; on the engine it prevented the trap in all 24 registered SGLang CAPPED runs and undid an established one in 9 of 9 rescue runs (§G.3). A cap at the capacity boundary $N_{\text{lb}} \approx 28$, the size a capacity-ratio rule gives at 300k, would sit on the steep side of the curve, within a few sessions of n_2, where the quasi-static model is least reliable; we take the smallest n within 5% of the peak, because the curve has one run per n, and check it with a burst test. We recommend a cap because it needs no engine change and is the one mechanism we tested on the engine, not because it dominates: in the earlier simulator, 20 s TTL pins with a pinned-first order reached a higher $\mu(300)$ than any static cap (Appendix T.2). A cap does not make the burst free: it moves the burst's cost to the client as admission delay and pauses, minutes per affected session, instead of turns that take several minutes for the rest of the run, and preventing the trap costs less than undoing it with the native pool. Whether the gate should queue or reject sessions is a deployment choice we did not evaluate.

The cap must be measured again when the workload or configuration changes. On the engine it moved from 20 to 64–80 with the native pool, stayed at 20–24 with vLLM, and on an H200 moved to 32 (the smallest-within-5% rule gives 28) while the window narrowed to $(1, 1.3)\,\lambda_{\text{ref}}$, too narrow for our registration rule to place a burst test. With the A100 pool halved and doubled, the peak, and with it the cap, moved to 12 and 48; with the H200 pool doubled the window reopened to $(1, 2.5)\,\lambda_{\text{ref}}$ and the cap was registered at 48; with Llama-3.1-8B the registered cap stayed at 20. In the calibrated simulator it moved to 32 or 40 with tool-time laws from real agent traces and fell to 12 with mini-SWE-agent's turn and token counts, and a cap sized for one setting can fail in either direction: too small, it holds the engine below the offered load; too large, it sits on the collapsed side of the curve (Appendix T). In that simulator the paired test passed at all ten points of five tool-time laws and at five of six points with tool times from real agent traces, whose dispersion is far larger than ours, and in the earlier simulator pure LPM, PEEK's released scheduler and TTL pins with a pinned-first order raised $\mu(300)$, our proxy for the congested service rate, above λ_{miss}, while FCFS with or without queued-prefix protection did not (Appendix T). An online detector is a separate question: a hit-rate threshold (with high KV usage) is CONCUR's thrashing signal [19] and a confirmed decline below a learned reference hit rate is MISA-T's [51], hit rate is among Bronson et al.'s characteristic metrics [11], and learned early indicators have been proposed [78]. Our frozen version of the first alarmed after every vLLM burst but also twice during capped drains (§G.2), and with a shared system prompt a detector would have to count private-suffix reuse. We do not claim a detector.

K Limitations in detail

Scope of the registered evidence. All registered SGLang evidence is for SGLang 0.5.22 and, but for two paired tests, Qwen2.5-7B-Instruct and one A100, at two pool sizes: the 300k-token pool limit and the 955,757-token pool SGLang sizes itself, with which the cliff moved out and the registered tests passed too, so the pool limit did not create the cliff. The two exceptions, Llama-3.1-8B on the A100 at 300k and Qwen2.5-7B on one H200 with a 600k pool, have three seeds per rate, and the first passed at only one of its two rates. vLLM 0.32.0 ran only with the 300k-token pool, and its paired test is registered, not pre-registered, with a BURST arm that repeats the workloads of earlier exploratory runs (§G.2). The 300k H200 cell is a measurement, not a registered test, and the H200 cells compare GPU and default attention backend together. The rescue tests engage the registered cap at a fixed time, not on an online signal, with three seeds per cell; they test persistence once the cap no longer binds, with no perturbation after release, and their cost and persistence comparisons are descriptive. The shedding and tool-slowdown tests ran at one rate on the 300k pool, with two and three seeds per setting. Larger models, parallelism, offloading and GPUs other than the A100 and the H200 are untested.

Synthetic sessions and clients. Sessions are synthetic (random tokens, fixed tool outputs and output lengths, geometric turn counts, exponential 5 s tools) and share no prefixes, which removes the case PEEK's scheduler targets. Tool times in real agent traces have medians 15–33 times shorter than ours and coefficients of variation of 4.3–4.7 against 1, and outputs per call 2.7–5.9 times our 100 tokens; in the simulator such tool-time laws keep the trap but move the window and the cap, which the engine has not tested. With a shared system prompt the ratio of all-miss to all-hit prompt work, about 16, would barely change, but the hit fraction of a trapped engine would stay near the shared share, so hit-based signals would have to count private-suffix reuse. Our clients never retry or abandon

a request; retries would add load in the trapped state and abandonment would remove it, so either could change whether the engine recovers. Appendix R gives the trace statistics and the other details.

Few runs, finite horizons, nominal rates. The closed curves and the from-empty sweeps have one run per point, so the peak's location is within noise and single runs near the cliff land on either side of it. The registered tests, the grid, the vLLM runs and the rescue tests share the same three seeds, so their runs are not independent across rates, pools, engines or tests. All rates are nominal; each from-empty sweep used a single arrival seed, and at 300k the seed-0 bracket was not replicated on fresh seeds, although stability is monotone in the realized rate, with the edge between 2.665 and 2.726 λ_{ref}; on the H200 at 300k it is likewise monotone over ten runs, with the edge between 1.496 and 1.503 λ_{ref} (the 1.503 run ended just above the queue threshold). "Does not leave" means within 7500 s on the engine and 30,000 s in the simulator, and the 3000 s horizon of the from-empty runs cannot see slow escapes. The registered rule loses margin at both ends of the window: the slope test near λ_{miss}, and the token test at high multiples. Appendix R discusses the native cap, the coincidence of the cliff with a change of job and node in both SGLang curves, and other uncontrolled factors.

Models and simulators. The fluid model is used for the window, the recovery threshold and drain times, and through the heuristics H2–H4 for the from-empty edge, burst sizes and release times; it is not quantitative in congestion and is least reliable near the cliff, and the frozen SHED and TOOLSLOW predictions used it there; the first held and the second did not. Proposition 6 is a limit statement under stated assumptions, including private prefixes, no offloading, i.i.d. tool times unknown to the engine and an engine that in congestion computes prompt tokens no faster than with caching disabled, which our engine meets only to within a few percent at the stationary turn mix and within 12% over the windows we measured; that recovery without a cap needs a rate below λ_{miss} is proved only within model F (Corollary 3) and tested on the engine by SHED's full stop and the CUT runs (a cut above λ_{miss}, CUT-A, left all three traps in place within the run; [pending: CUT-B outcome]), pure LPM's congested rate is a conjecture, and the capped system's stochastic stability is not proved. The first-principles model's propositions hold for a deterministic fluid model, with no limit theorem to the engine. It misses the H200's tail past the peak at both pools (at 600k also the 0.5-hit crossing, 4.4 sessions late, and the trapped token rate of the paired test, 0.038–0.049 low in 5 of 6 runs), vLLM's earlier cliff and, with a 150k-token pool, the peak height and the from-empty edge. It predicted that a 30 s slowdown of every tool call for 900 s, with no burst, would trap the engine in every seed; it trapped 1 of 3. On Llama-3.1-8B its edge was one grid step high (a near miss), its trapped token rate in the paired test was 0.031–0.046 low in 3 of 6 runs, and its crossing failed a later-declared test of the tool-call term. In BASIN-2 its per-seed probabilities favoured the wrong state for seed 0 at 40 and 50 sessions. Its release-time predictions were early, with observed releases more than 15% later in 4 of 9 runs (all three with the native pool), and its derivation and edge criterion were selected on the measured cells (§H.6). The calibrated simulator failed its level test at one cell, predicted a pass of the Llama-3.1-8B paired test at 1.35 λ_{ref}, which failed, omits partial prefixes and the waiting-prefix refresh, frees a finished session's KV at once and understated LPM; the mechanism comparison uses an older simulator with assumed costs, configured pins, ablations and a surrogate of CONCUR, so its rates do not carry over to the engine or to the named systems (Appendix T).

The registration record. Appendix N lists the slips. The vLLM registration reached GitHub after two of its jobs had started, and some prediction rounds were pushed after their jobs were submitted, or specified after related data were known. The closed-curve values of the 300k H200 cell for $n \le 32$, which include the predicted peak, were seen by its operating agent and the first author before the freeze, though not by the agents that derived the model. Some predictions are blind by access only: the model's for BASIN-1 and the other 300k H200 runs that had ended before the freeze, and the model's and the simulator's for the Llama-3.1-8B curve. The 600k H200 and Llama-3.1-8B registrations and the Llama-3.1-8B registration-conditional predictions are not tagged, and R4's engage time and the model's rescue predictions were chosen or frozen with knowledge of the simulator's predictions. No registration or prediction is in a third-party registry, and none has a timestamp other than GitHub's push log of a private repository, which readers can see only in our export.

L Protocol details

The accounting export `provenance/sacct_cited_jobs_2026-11-01.txt` was made after the last cited job had ended; its times are Slurm's local time, CDT until 02:00 on 2026-11-01 and CST after it, and `provenance/sacct_cited_jobs_2026-11-01_utc.txt` gives the same records in UTC. The earlier export `provenance/sacct_cited_jobs_2026-10-30.txt` covers every job through the vLLM E0b, and the data directories of the vLLM paired test and of the BASIN-1, fresh-seed, rescue, pool-sweep, BASIN-2, TOOLSLOW and SHED jobs hold their own copies (`sacct_17166121-17166138.txt`, `sacct_17168500-17168507.txt`, `sacct_1716896x.txt`, `sacct_17168864-17168881.txt`, `sacct_17169893-17169901.txt`, `sacct_17169902-17169911.txt`).

Table 11 lists the workload and engine settings of the real-engine runs.

The sequence of stages. *Stage 0*, a smoke test of server and client on one GPU, came first; its server logs and those of Stage C calibrated the simulator (§F.4). After E2 we repeated the sequence with the native pool (Stage C, E0a, E0b, a second registration and *native E2*) and ran an exploratory policy grid.

Table 10: Real-engine stages (SLURM job IDs on Nova). Submit, start, end and node of every job: `provenance/sacct_cited_jobs_2026-11-01.txt` (local time; `_utc.txt`, UTC; see the text).

Stage	Jobs	What it measures
Stage 0	17060165	smoke test
Stage C	17062103	closed $\mu(n)$, 300k pool, FCFS, $n \in \{16, 20, 24, 32\}$ (node gpu-1)
	17062104	FCFS, $n \in \{48, 96, 300\}$ (gpu-3)
	17062105	LPM, $n \in \{48, 300\}$ (gpu-2)
E0a	17072634–37	λ_{miss}, cache off
E0b	17084750–55	from-empty stability
E2	17093387–404	registered paired test, 2 rates × 3 seeds × 3 arms
native C	17096856	$\mu(n)$, native pool, $n \in \{24, 48, 64, 80\}$ (gpu-2)
	17096857	$n \in \{96, 128, 300\}$ (gpu-1)
native E0a	17096858	λ_{miss}, native pool
grid	17097086–103	BURST arm, 3 policy cells
vLLM	17097972–74	install, GPU check, smoke
native E0b	17100938–39	from-empty stability, native pool
vLLM E0a	17100940	λ_{miss}, vLLM, cache off
native E2	17102173–90	registered paired test, native pool, 2 rates × 3 seeds × 3 arms
vLLM BURST	17102318–23	BURST arm, vLLM, exploratory
vLLM C	17162959	$\mu(n)$, vLLM, 300k pool, $n \in \{16, 20, 24\}$ (gpu-3)
	17162960	$n \in \{28, 32, 40\}$ (gpu-3)
	17162961	$n \in \{48, 96, 300\}$ (gpu-2)
vLLM E0b	17162962–63	from-empty stability, vLLM
vLLM E2	17166121–38	registered paired test, vLLM, 2 rates × 3 seeds × 3 arms
Rounds 11 to 14 (Tables 23–25)		
H200	17166807	smoke, H200 NVL, 300k pool
	17166810–13	E0a and its 64-session check
	17166818–22	Stage C, n = 16–300 (nine runs, with the next row)
	17166828, 30, 32, 34	Stage C, the rest of the nine runs
	17168377–82	E0b
	17169668–71	E0b reseeds, added after 17168377–82 were read (post hoc)
	17169612–14	Stage C, n = 36, 44, 52
	17169672–80, 82–87	Stage C, E0b, 600k pool
	17171020–37	E2, 600k pool
Llama	17166808	smoke, Llama-3.1-8B
	17166814–16	Stage C
	17166823, 29, 31, 33	E0a and its 64-session check
	17169565–70	E0b
	17170409–26	E2
pools	17168864–81	Stage C, E0b; 150k, 600k
BASIN-1	17168500–05	bursts of 100, then 25
E0F	17168506–07	from-empty, seeds 3–5
LPM-INF	17168743–45	BURST, no LPM fallback
BASIN-2	17169893–901	bursts of 40, 60, then 50
TOOLSLOW	17169902–07	δ = 10, then 30 s
SHED	17169908–11	τ = 600, then 3600 s
rescue	17168965	smoke test of the gate (never decisive)
	17168966–71	R1, 300k pool, 2 rates × 3 seeds
	17168972–74	R4, native pool, 3 seeds

Table 11: Workload and engines of the real-engine runs.

First prompt L_0	2000 tokens
Tool output per turn Δ	550 tokens
Output per turn d	100 tokens, greedy, `ignore_eos`
Turns T	$\min(\text{Geometric}(1/15), 60)$, $E[T] = 14.761$
Tool time Z	exponential, mean 5 s
Prompt at turn k	$2000 + 650(k-1)$ tokens
Output feedback	server-returned token ids
Engine	SGLang 0.5.22, FlashInfer; FA3 on the H200
Scheduling	FCFS, waiting-prefix refresh on
Batching	chunked prefill 8192, ≤ 256 running
KV pool	300,000 tokens; native 955,757 pool sweep 150,000, 600,000; H200 also 600,000
Context limit	49,152 tokens
Model	Qwen2.5-7B-Instruct, rev. a09a3545 one cell: Llama-3.1-8B-Instruct, rev. d10aef7 (NousResearch mirror, shards identical to Meta's)
GPU	A100 80GB PCIe, 81,920 MiB, driver 580.178.04 two cells: H200 NVL, 143,771 MiB, same driver
vLLM	0.32.0, FCFS (default), prefix caching on chunked prefill 8192, ≤ 256 running 300,000 tokens (18,750 blocks of 16)

On vLLM we first measured λ_{miss} and ran the BURST arm alone under an exploratory registration, and later ran its own Stage C and E0b, a third registration and its paired test (§G.2). An exploratory replication of E0b later used seeds 3–5 at two rates (§G.1). Later cells repeat the first stages on an H200 at the same pool and at 600k tokens (§G.5), with Llama-3.1-8B, and on the A100 with pools of 150k and 600k tokens; the Llama-3.1-8B and 600k H200 cells have registered paired tests, and registered tests of a rescue (§G.3), of other burst sizes (§G.4), of a pause in arrivals and of a tool slowdown follow the paired-test protocol; §I lists their frozen predictions and the outcomes in hand.

Stage 0. The smoke test (job 17060165) verified that every engine flag exists; that cached tokens are reported (a repeated 64-token prompt had 63 tokens cached); that the server returns output token ids; that contexts up to 40,350 tokens are accepted; that the KV pool is exactly 300,000 tokens; that client and server agree on prompt length (0 mismatches over 3191 requests); and that the flush empties the cache (canary 1023 cached tokens before, 0 after).

Stage C and E0a. Closed population; all sessions start at $t = 0$ and a finished session is replaced at once; 900 s warmup and an 1800 s measured window; one run per n (seed 0); flush and canary check between runs. The native-pool and vLLM closed curves used the same protocol, with the populations of Table 10. E0a disables the radix cache and runs 32 sessions with seeds 0, 1 and 2, plus 64 sessions with seed 0 as a saturation check. Its per-run values over the window were (sessions/s, turns-based sessions/s, uncached tokens/s): seed 0, 0.0567, 0.0643, 11,076; seed 1, 0.0817, 0.0773, 11,342; seed 2, 0.0767, 0.0730, 11,312; 64 sessions, 0.0544, 0.0676, 11,431. The spread comes from in-flight composition: the mean turn index of the requests in the win-

dow was 15.9, 13.2 and 14.1 for seeds 0, 1 and 2. vLLM E0a ran the same protocol with vLLM's prefix caching off: seed 0, 0.0539, 0.0603, 10,208; seed 1, 0.0728, 0.0705, 10,487; seed 2, 0.0700, 0.0662, 10,352; 64 sessions, 0.0467, 0.0631, 10,531.

E0b. Poisson session arrivals from an empty cache and queue at 1.25, 1.5, 1.75, 2.0, 2.5 and 3.0 λ_{ref}; one 3000 s run per rate; stable if the final queue is below 50 and the fitted rise of the queue over the last 1500 s is at most 10. All runs used arrival seed 0, so they share one random-number stream and the arrivals at each rate are a subset of those at the next higher rate. The six runs received 302, 359, 416, 472, 585 and 697 sessions, 8.3–12.6% above λT and about 2.1 Poisson standard deviations above it in every run. Native E0b used the same rule at 1.5, 2.5, 3.5, 4.5, 5.5 and 6.5 times the native λ_{ref} (361, 587, 811, 1034, 1257 and 1478 sessions, 5.6–11.7% above λT), and vLLM E0b the multiples of the 300k runs of vLLM's λ_{ref} (279, 331, 383, 435, 539 and 642 sessions, 8.6–13.3% above λT; stable through 2.0, final queue 81.6 and 247.1 at 2.5 and 3.0).

The fresh-seed E0b (E0F; jobs 17168506–07) repeated 2.0 and 2.5 λ_{ref} on the 300k pool with arrival seeds 3, 4 and 5 under the same rule. All six runs were stable, with final queue 0, so the frozen replication rule, which needed 2.0 λ_{ref} stable in all three seeds and 2.5 λ_{ref} unstable in at least two, is not met. The nominal bracket of 2.0 to 2.5 λ_{ref} therefore comes from the single seed-0 grid: over seeds 0 and 3–5, 2.0 λ_{ref} is stable in 4 of 4 runs and 2.5 λ_{ref} in 3 of 4. Measured instead in realized arrival rates (base arrivals in the 3000 s run over 3000 s $\times$ λ_{ref}), the twelve from-empty runs of seeds 0 and 3–5 are stable up to 2.665 λ_{ref} and unstable from 2.726 λ_{ref}, monotone in the realized rate, so the edge lies between 2.665 and 2.726 λ_{ref}. The seed-0 run at 2.5 λ_{ref} is the one at 2.726: it received 9% more arrivals than its nominal rate. Either way, the registered rates of 1.35 and 1.65 λ_{ref} lie inside the window. The simulator's blind prediction was stable in all six runs; the heuristic H2 of §H.3 gave each 2.5 λ_{ref} run a probability of 0.69 of being unstable and was too pessimistic. This test is exploratory: it has no registration of its own and does not change the E2 registration, whose window was fixed by the seed-0 bracket.

E2. One arm per 8700 s job, each on a fresh server; burst of 200 fresh sessions within 60 s at t_b = 1200 s for BURST and CAPPED; CAPPED gate n_{cap} = 20; evaluation window $[t_b+4500,\ 8700]$ s. The registered rule (Table 12) was applied by the analysis tool frozen at the registration commit, with the same parameter overrides that the jobs themselves used. Native E2 used the same protocol with the native registration's rates, reference rates and gate n_{cap} = 64. Twelve of its 18 runs started after the cluster checkout moved from the registration commit to `a78ce07`, which adds only the vLLM registration, its input file and two notes files (the research log and the status notes), with no code change, and its verdict ran on that commit; two of its 18 servers sized the pool one token smaller, at 955,756. The vLLM paired test uses the same protocol with the vLLM registration and n_{cap} = 20. It uses the same seeds, rates and reference rate as the exploratory vLLM BURST runs, so its BURST arm repeats their workloads rather than replicating them independently.

Why the rule uses tokens. Criterion (a) uses tokens because a trapped engine with a growing backlog serves mostly young sessions, whose turns are short, so at the all-miss token rate it completes more turns per second than the stationary all-miss mix, and sessions faster than λ_{miss} (§E.3): on traps simulated in our earlier simulator (§F.4), a session-rate test fired on at most 1 of 29 at 2 λ_{miss} and none of 39 at 2.5, while the token test fired on all 84 traps at 1.5–2.5 λ_{miss}.

Drain-time estimates. The registrations' feasibility check used $b/(\mu(c) - \lambda)$, which ignores the $c - n_1$ free slots that a burst fills at once: 1571 s at 1.35 and 1889 s at 1.65 λ_{ref} for E2, 668 s and 1043 s at 2.5 and 4.0 λ_{ref} for the native test, and 1529 s and 1800 s for vLLM. With the populations present at the burst (5–12 sessions at 300k, 11–32 with the native pool, 5–11 on vLLM), the fluid estimate $(n_1 + b - c)/(\mu(c) - \lambda)$ of §E.4 is 1453–1508 s and 1757–1804 s, 491–518 s and 840–876 s, and 1414–1460 s and 1674–1692 s. The CAPPED gate's queue emptied 1547–1904 s and 2021–2693 s after the burst on E2, 3–52% longer than this estimate; 512–583 s and 837–937 s with the native pool, between 4% shorter and 13% longer; and 1521–2735 s on vLLM, 1.05–1.63 times it.

Rescue (R1, R4). One rescue run per 8700 s job, each on a fresh server, from a frozen clone at the registration tag; the client's arrival plan is the BURST plan of the same seed and rate, byte for byte, so until t_{on} the rescue run replays the BURST run's arrival plan (a fresh run on a fresh server, not the same run). At t_{on} the gate starts to bind with cap c by attrition and pause: a session whose tool call ends while more than c sessions are admitted gives up its slot and joins a resume queue, which is served before the queue of new arrivals, each in FIFO order; a paused session's KV is not protected while it waits. The cap is removed at the first 10 s tick at or after t_{on} + 600 s at which both queues have been empty for 300 s; there is no forced release. The registered per-run rule uses the follow-up hit fraction, the share of a session's turns after its first, attributed by completion time, with more than half of the prompt cached: (a) VALID if the follow-up hit fraction over $[t_{\text{on}} - 300,\ t_{\text{on}})$ is below 0.2 and more than 50 requests or sessions are outstanding at t_{on} (requests in flight plus sessions waiting at the gate or paused), on the registered hardware; (b) RELEASED by 7200 s; (c) POST-GOOD over $[t_{\text{rel}} + 300,\ 8700)$: every 300 s window, tiled from the start with a short remainder covered by the window ending at 8700 s, has a follow-up hit fraction of at least 0.5, the whole interval above 0.8, an uncached token rate below 0.5 times the all-miss reference, and the registered RECOVERED test holds over the last 300 s; a window with no completed follow-up fails (c) without being a relapse. RESCUED is (a), (b) and (c); RELAPSE is any such window below 0.2. A

same-seed BURST control, from the paired test, is STUCK if its follow-up hit fraction over $[t_{on}, 8700)$ is below 0.2 and it is not RECOVERED over the last 300 s. A cell passes if at least 2 of its 3 seeds are RESCUED and every same-seed control is STUCK; R1 is refuted if 2 of its 6 runs relapse or are not released by 7200 s, and R4 if 2 of its 3 relapse; a refutation takes precedence over a pass, and a failed session in any counted run withdraws the claim that nothing was shed. The pairing requires common random numbers with the committed BURST and NOBURST runs (the BURST plan byte-identical, the NOBURST plan the rescue plan without the burst sessions), equal resolved rates, references, hardware and burst time. Each job ran only a mechanical check of the gate (`analysis.rescue check-run`: engage within 10 s of t_{on}, release on the 10 s grid after the 300 s hold, no request errors), which passed in all ten jobs; no hit fraction of a rescue run was read before all runs of its cell had ended. The controls ran on 2026-10-24 to 26 as part of the paired tests, not alongside the rescue runs. A smoke job under its own registration checked the gate's mechanics before the registered runs and is never decisive.

Table 12: The registered decision rule.

Rate estimator	uncached prefill tokens/s
Reference rate	E0a all-miss, 11,243 tokens/s (native: 11,282; vLLM: 10,349)
λ_{miss} in the rule	the cell's λ_{ref}
Rate tolerance	±0.15
Backlog slope	least squares over 10 s bin means of sessions in the system, gate included
Minimum window	600 s
Trapped	$\lambda > \lambda_{miss}$, rate within tolerance, and slope $> 0.5\,(\lambda - \lambda_{miss})$
Recovered	hit > 0.8 and outstanding < 20, last 300 s
Draining	slope < 0
Indeterminate	none of the above
Precedence	trapped, recovered, draining, indeterminate
Hit metric	turns with cached/prompt > 0.5
Pass	$\geq 2/3$ of ≥ 3 seeds with all three arm conditions met in the seed

Backlog definitions. The figures and Table 5 report the backlog as sessions in the system (arrived minus ended), which includes sessions asleep in tool calls (8–12 in the good state at 300k, 16–34 with the native pool). The registered RECOVERED test uses the outstanding backlog (requests in flight plus sessions held at the gate). The simulator's predictions count waiting requests plus the gate queue. The rescue rule's outstanding work also counts sessions paused by the gate (Fig. 4).

M The registrations

The registration was filled by formula from committed copies of the Stage C curve, the E0a calibration and the E0b bracket. The window was $(1,\ 2.0)\ \lambda_{ref}$, its upper edge E0b's largest all-stable multiple (below $\mu^*/\lambda_{ref} = 3.26$), a nominal value from E0b's single seed-0 grid; fresh seeds later put the from-empty edge, in realized arrival rates, between 2.665 and 2.726 λ_{ref}, and both registered points lie inside the stable range on either reading (§G.1). The rates followed a rule proposed in the runbook and adopted in the project status notes on 2026-10-22, the day before E0b was submitted (Appendix M): one third and two thirds of the way across the window, rounded to 0.05, which gives 1.35 and 1.65 λ_{ref} (0.0966 and 0.1180 sessions/s). The cap was the smallest n with $\mu(n) \geq 0.95\mu^*$: $n_{cap} = 20$, since $\mu(20) = 0.224$ is about 4% below $\mu(24) = 0.233$, inside the rule's 5%. The file was committed and reached the project's GitHub repository at 15:09:54 CDT on 2026-10-24, before the E2 jobs were submitted at 15:13 (Table 14). We call a test pre-registered when its registration file was committed and pushed to GitHub before its runs; this is not an entry in a third-party registry. Registration and the frozen predictions of §F.4 are rigor, not a contribution: they let a reader check that each rule and each prediction existed before its outcome. The design follows the model-to-system pipeline of Isaacs et al., in which an abstract model chooses the experiments that then test it [54], and pre-registered gates have been used in ML-systems measurement before [101]. Appendix M lists every registration we filled, with its status, and Appendix N every prediction round with its time record; the files carry no timestamp other than GitHub's push log. The repository we publish is a redacted copy of the development repository whose `provenance/` directory ties every registration file, by hash chains, to the development repository's push log (availability statement). Commit times are set by the committer, so the external record is GitHub's push log, archived as `provenance/github_activity_2026-10.json` (Appendix N). The job script refuses to start unless the file is committed and unmodified and the job's cell, rates, cap, reference rates, hardware and protocol match it, and writes its SHA-256 into every run; the analysis calls a verdict decisive only for the registered cell and rates with every run bound to the file and started after its commit (Appendix M); the label records this binding, not statistical strength, and the analysis checks commit order, not push time, so its own label "pre-registered" does not by itself meet our definition. The native registration was filled and enforced the same way and reached GitHub 10 minutes before its jobs were submitted (§G.2). The vLLM registration was filled from vLLM's own Stage C curve, E0a calibration and E0b bracket, and does not meet the definition: it was committed 37 s before its 18 jobs were submitted, and the cluster's record of the submission names the file but not its hash, but it reached GitHub 2 min after the submission, when two of the jobs had started and none could have ended, so we call this test registered, not pre-registered (§G.2). On the H200 with the 300k pool the rule could not be applied: its window was $(1,\ 1.3)\ \lambda_{ref}$ (the largest all-stable E0b multiple, below $\mu^*/\lambda_{ref} = 1.99$), and the points the rule gives, 1.10 and 1.20 λ_{ref}, lie outside the band $(1.1,\ 1.17)\ \lambda_{ref}$ that its 10% margin at each edge of the window leaves, so the fill returned INCOMPLETE and that cell has no registered test (§I). With the 600k pool the

window was (1, 2.5) λ_{ref} and the rule filled a registration (Table 13).
The registration is `configs/agentload_prereg_2026-10-24.yaml`, status FILLED, committed in `d279b7b` at 15:09:12 CDT on 2026-10-24 and pushed to GitHub at 15:09:54, before the E2 jobs were submitted at 15:13:39, SHA-256 `2a6d680a9615bba962a5673d6db6b3e4 ca5102bf778ca974cea46147f5cc0ac6`. Its fields:

- **Cell and inputs.** Engine cell `sglang-fcfs-r1` (SGLang FCFS, waiting-prefix refresh on); committed copies of the Stage C curve, the E0a calibration and the E0b bracket under `prereg/inputs/2026-10-23/`; protocol 8700 s, burst of 200 within 60 s at 1200 s.
- **Measured.** $\mu(n)$ in sessions/s: 0.1756 (n = 16), 0.2239 (20), 0.2333 (24), 0.1150 (32), 0.0489 (48), 0.0611 (96), 0.1078 (300). $\mu^* = 0.2333$; $n_{\text{cap}} = 20$ by the smallest-within-5% rule (argmax 24; flagged ambiguous). $\lambda_{\text{miss}} = 0.07167$ (sessions) and 0.07153 (turns-based, $= \lambda_{\text{ref}}$); all-miss rate 11,243 tokens/s; E0b largest all-stable multiple 2.0, first unstable 2.5, monotone (arrival seed 0 only; the fresh seeds of Appendix L came later); hardware A100 80GB PCIe.
- **Predicted boundaries.** Recovery threshold λ_{ref} (not $\mu(300)$, which a synchronized start biases upward). Window (0.0715, 0.1431) sessions/s = (1.0, 2.0) λ_{ref}, upper edge from E0b. CAPPED drain must fit within 80% of the 7200 s available after the burst (5760 s), which holds for λ up to 2.64 λ_{ref}; predicted drain 1571 s at 1.35 and 1889 s at 1.65.
- **Rates.** 1.35 and 1.65 λ_{ref} by the one-third/two-thirds rule, rounded to 0.05, inside the margin band (1.1, 1.8); seeds 0, 1, 2. On 2026-10-22 the runbook proposed the rate rule and a cap of 20, with keeping 24 as the alternative (`288b801`, 13:13 CDT); both rules were adopted in the project status notes at 13:50 (`4435c51`) and reached GitHub at 17:45, before E0b was submitted on 2026-10-23; the registration's own text dates them 2026-10-23.
- **Predictions.** Inside the window: BURST trapped, NOBURST good through the run horizon, CAPPED recovered if the drain fits. Below λ_{ref}: BURST not trapped. Above the window: NOBURST may escape, so no such rate was registered.
- **Kill conditions.** NOBURST not good in at least one third of the seeds at a registered rate; BURST not trapped in two thirds of the seeds at every registered rate; CAPPED not recovering while BURST traps and the drain fits; a window that is empty or narrower than the noise.
- **Warnings recorded at filling.** $|\mu(300)/\lambda_{\text{miss}} - 1| = 0.507$ (a check only), and the ambiguous cap.

The verdict is in `results/agentload_analysis_burst2/20261025-144012/` inside the E2 data directory: the registered analysis passes at 1.35 and 1.65 λ_{ref} (the tool's labels, assigned by commit order, are pre-registered and decisive; by the definition of §F.3 the test is pre-registered). The three grid cells have their own derived registrations, `configs/agentload_prereg_2026-10-24_grid_<cell>.yaml` for the cells `sglang-fcfs-r0`, `sglang-lpm-r1` and `sglang-lpm-r0`, with status EXPLORATORY; the analysis never calls them decisive.

The native registration. `configs/agentload_prereg_2026-10-25_native.yaml`, status FILLED, committed in `b8c19ec` at 17:31:16 CDT on 2026-10-25 and pushed to GitHub at 17:31:56, 10 minutes before the native E2 jobs were submitted (17:42:29), SHA-256 `21bf7c03e0630b65b80d086058815e12 c5ba9fbe41e9864d3dd0183b9bf776c1`; the same template, formulas, trap rule, kill conditions and protocol as above. Cell `sglang-fcfs-r1-native`; inputs under `prereg/inputs/2026-10-25-native/`. Measured: $\mu(n)$ 0.2650 (n = 24), 0.4311 (48), 0.4789 (64), 0.4772 (80), 0.1228 (96), 0.0667 (128), 0.1006 (300); $\mu^* = 0.4789$; $n_{\text{cap}} = 64$ by the smallest-within-5% rule (also the argmax; flagged ambiguous, n = 80 within 0.35%); $\lambda_{\text{ref}} = 0.07180$ (turns-based); all-miss rate 11,282 tokens/s; native E0b largest all-stable multiple 5.5, first unstable 6.5, monotone. Window (0.0718, 0.3949) sessions/s = (1, 5.5) λ_{ref}, upper edge from native E0b, below $\mu^*/\lambda_{\text{ref}} = 6.67$. Rates 2.5 and 4.0 λ_{ref} (0.1795 and 0.2872 sessions/s) by the same rule, inside the margin band (1.1, 4.95); the rule was recorded in the project status notes (`6cb43e9`, pushed 15:08 CDT) before native E0b was read. Predicted drains 668 s and 1043 s; the drain fits up to 6.19 λ_{ref}. Warnings recorded at filling: $|\mu(300)/\lambda_{\text{miss}} - 1| = 0.401$, the ambiguous cap, and an incomplete grid (no n = 16, 20 or 32). The verdict is `results/agentload_analysis_burst2/20261026-100653/` inside the native E2 data directory: the registered analysis passes at 2.5 and 4.0 λ_{ref} (with the same tool labels; pre-registered by the definition of §F.3).

The exploratory vLLM registration. `configs/agentload_prereg_2026-10-24_grid_vllm-fcfs.yaml`, status EXPLORATORY, derived from the E2 registration, committed in `a78ce07` at 18:06:18 CDT on 2026-10-25 and pushed to GitHub at 18:06:33, 46 s before the vLLM BURST jobs were submitted, SHA-256 `c5037cac6003c4e98da89f88dae953bf e68bb21a27a4e3e5e3dab3c8891aeab5`. Cell `vllm-fcfs`, BURST arm only; the window, multiples, protocol and trap rule are inherited from `sglang-fcfs-r1`, and the reference rates come from `prereg/inputs/2026-10-25-vllm/calibration.json`, a byte-identical copy of the vLLM E0a calibration. Its predicted-boundary block is copied unchanged from the E2 registration (window 0.0715–0.1431 sessions/s, all-miss rate 11,243 tokens/s), but the runs used vLLM's references, 0.06566 sessions/s and 10,349 tokens/s (`lambda_ref_resolved` and `uncached_tokens_ref_resolved` in each run's `meta.json`), so their rates were 1.35 and 1.65 times vLLM's λ_{ref}. The verdict, `results/agentload_analysis_burst2/20261026-100701/` inside the native E2 and

vLLM BURST data directory, reports per-run states and no registered verdict.

The vLLM registration.
`configs/agentload_prereg_2026-10-30_vllm.yaml`, status FILLED, SHA-256 `8f2d5b44d6365795fedde8bf673d51e5 4bf8a685a14d563c86de44492bb95f84`; the same template, formulas, trap rule, kill conditions and protocol as the E2 registration. Cell `vllm-fcfs`; inputs: the vLLM Stage C curve and E0b bracket under `prereg/inputs/2026-10-30-vllm/`, byte-identical to the analyses in the vLLM Stage C and E0b data directories, and the vLLM E0a calibration above. Measured: $\mu(n)$ 0.1750 ($n = 16$), 0.2194 (20), 0.2183 (24), 0.1189 (28), 0.0433 (32), 0.0411 (40), 0.0439 (48), 0.0572 (96), 0.1050 (300); $\mu^* = 0.2194$; $n_{\text{cap}} = 20$ by the smallest-within-5% rule (also the argmax; flagged ambiguous, $n = 24$ within 0.5%); $\lambda_{\text{ref}} = 0.06566$ (turns-based); all-miss rate 10,349 tokens/s; vLLM E0b largest all-stable multiple 2.0, first unstable 2.5, monotone. Window (0.0657, 0.1313) sessions/s $= (1, 2.0)\,\lambda_{\text{ref}}$, upper edge from vLLM E0b, below $\mu^*/\lambda_{\text{ref}} = 3.34$. Rates 1.35 and 1.65 λ_{ref} (0.0886 and 0.1083 sessions/s) by the same rule, inside the margin band (1.1, 1.8); this rule and the cap rule were recorded in the project status notes (`836063a`, pushed 12:16 CDT on 2026-10-30) after the vLLM Stage C and E0b jobs were submitted and before any of them had ended. Predicted drains 1529 s and 1800 s; the drain fits up to 2.81 λ_{ref}. Warnings recorded at filling: $|\mu(300)/\lambda_{\text{miss}} - 1| = 0.599$ and the ambiguous cap. The file was filled from five of the six vLLM E0b runs while the 3.0 λ_{ref} run was still running; with 2.5 λ_{ref} unstable that run could not change the edge, and it was unstable too, so the six-run bracket equals the registered one. The file was committed in `5a6fbcd` at 16:23:59 CDT, 37 s before the 18 jobs of the paired test (17166121–38) were submitted at 16:24:36 (the research log gives 16:30), and the jobs run from the cluster's copy of the repository at that commit; Slurm's record of the submission names the file but not its hash. It reached GitHub at 16:26:35, 1 min 59 s after the submission, when two of the jobs had started (at 16:25:42 and 16:26:17) and none could have ended. This registration therefore does not meet the definition of §F.3: it was committed before the jobs were submitted, but pushed after the first two had started, so we call this test registered, not pre-registered. As for E2, the job script writes the file's SHA-256 into every run's `meta.json`.
The verdict, `results/agentload_analysis_burst2/20261031-020837/` in the paired test's data directory (`results/nova/e2_vllm_1716612x_pulled_20261031-020956/`), reports a pass at both rates; all 18 runs' `meta.json` files carry the registration's SHA-256. The tool also prints the labels pre-registered and decisive, which it assigns by commit order; by the definition of §F.3 the test is registered, not pre-registered. The frozen mechanism predictions for this test (`configs/r11_mechanism_predict.yaml`, `notes/PREDICTIONS_r11_mechanism.md`; commit `f1338e3`, pushed at 18:20:13 CDT on 2026-10-30, when three of the 18 jobs were running and none had ended; the first ended at 18:55:07) were evaluated with the frozen scripts, run unchanged. Byte copies of the frozen files and their outputs are under `r11_mechanism/` in the same directory, and the scored decision is `derived/r11_mechanism_decision.json`, which records two detector false alarms in CAPPED runs, one more than the frozen rule allows (§G.2).

The rescue registrations. `configs/agentload_prereg_2026-10-31_rescue.yaml` (R1, cell `sglang-fcfs-r1-rescue`) and `configs/agentload_prereg_2026-10-31_rescue_native.yaml` (R4, cell `sglang-fcfs-r1-rescue-native`), status FILLED, SHA-256 `502dee9e3107952a2f968c1b59b8ee3d 4063870d72f0dfac1261e2b2e2316691` and `ddd776f822755ba50472668b4af7dba3 538354d98feb2579b8cca422b5215bb1`, were committed in `f0bc3ad` at 22:10:47 CDT on 2026-10-30 (tag `r11-rescue-reg`) and reached GitHub at 22:39:02, 22 minutes before the ten jobs (a smoke job and the nine registered runs, 17168965–74) were submitted at 23:01:12–13; by the definition of §F.3 both tests are pre-registered. They reuse the inputs, rates and caps of the E2 and native E2 registrations, under their own cell labels, and add the rescue protocol, the per-run rule, the decision rule and the refutation conditions of Appendix L, with the rule's constants frozen in `analysis/rescue.py` at the tag. Three changes were accepted after a review of the simulator's predictions and before any rescue run: a refutation takes precedence over a pass, the no-shed part of a pass is withheld if any counted run has failed sessions, and R4, like R1, requires stuck same-seed BURST controls. R4's engage time of 2100 s replaced 2400 s after the simulator had predicted 13 of 20 rescued at 2400 s (`notes/PREDICTIONS_r11_rescue.md`). The verdicts, `results/agentload_analysis_rescue_r1/20261031-071720/` and `results/agentload_analysis_rescue_r4/20261031-071748/` in the data directory `results/nova/rescue_1716896x_pulled_20261031-070502/`, were computed on a clean tree with the registrations and the simulator's predictions as inputs: each reports a pass, with no rejected run and no pairing, protocol or registration problem, and every run's `meta.json` carries its registration's SHA-256. The tool labels each verdict decisive, a label it assigns by commit order.

Ledger of registrations. Table 13 lists every registration file we filled, with its status. Commit times are the committer's; push times come from GitHub's push log (`provenance/push_times_2026-11-01.tsv`, built from the export of 2026-11-01, `provenance/push_times_2026-11-05.tsv` for the registrations of 2026-11-05, or the archived log itself for the grid cells). Each is the first branch update that contains the

commit; the BASIN-1 push also carried `9b67c26`, the commit of tag `r11-basin-reg`.
Superseded before registration: a native rescue engaged at 2400 s, whose simulator prediction (13 of 20 rescued) led to the engage time of 2100 s that R4 registers (`notes/PREDICTIONS_r11_rescue.md`). The SHA-256 of every tagged file is in its tag message (`r11-basin-reg`, `r11-lpminf-pred`, `r11-rescue-reg`, `r14-basin2-reg`, `r14-extra-reg`) and in `provenance/registration-proofs/`; the Llama-3.1-8B and 600k H200 registrations are not tagged, and the job script writes their SHA-256 into each of their runs' `meta.json`.

N Prediction rounds and timeline

The calibrated simulator in detail. Our discrete-event simulator models a continuous-batching engine: iterations of at most 8192 prefill tokens and 256 sequences; admission reserves a request's end-of-turn KV; idle KV of sessions in a tool call or waiting is evicted whole, least recently used first; waiting requests pin nothing; a finished session's KV is freed at once, an oracle, since a real engine keeps it as evictable cache. An iteration costs a fixed time plus a per-token term plus attention terms. The five cost parameters were fitted only to SGLang's per-batch timing lines in the Stage 0 and Stage C server logs (decode $R^2 = 0.992$, median error 0.75%; prefill $R^2 = 0.998$, 1.3%), never to $\mu(n)$. It runs mixed prefill–decode iterations or, like SGLang, separate iterations with prefill priority; the primary (mixed) mode was the one closer to the real Stage C $\mu(n)$ under a pre-declared metric (mean relative error 0.104 against 0.127), a margin carried by one cell, and both modes' predictions are reported. It does not model partial prefixes, the waiting-prefix refresh or the overlap scheduler; reserving whole turns at admission is an upper bound on what paged engines hold (in round 5 of the earlier simulator, on-demand allocation with preemption and SGLang-like ratio reservation kept the curve and the trap).

Validation. The declared level test, simulated μ within 15% of the real value in each of 8 Stage C cells, failed in both modes: mixed batching missed one cell, FCFS $n = 48$, by +42% (0.070 against 0.049 sessions/s), separate batching two. The shape was reproduced: the hit fraction crosses 0.5 at $n = 32.5$ against 32.2, the plateau ($n = 16$–24) agrees within 9.2% and $n = 300$ within 2%, and $\mu(300)/\mu^*$ is 0.50 against 0.46. The single real run at $n = 48$ dipped below the simulator's all-miss level; its turns-based estimate, 0.063 sessions/s, is within 15%. Keeping a finished session's KV as evictable cache, a labelled sensitivity arm, left mixed batching the closer mode (0.118 against 0.146) but lowered the plateau (-15.5% at $n = 24$; 5 of 8 cells within 15%). In the earlier simulator the same change moved the orderings and pins of §T.2 by at most 0.025 λ_{miss} but stalled the CONCUR surrogate at its minimum cap in 12 of 18 cells; the static caps were not rerun.

Prediction rounds. The calibrated simulator then predicted, in both modes (mixed primary), B1: λ_{miss} and the all-miss token rate; B2: the fraction of from-empty runs that stay stable at each rate; B3: the E2 outcome at each rate from 0.09 to 0.16 sessions/s; B4: the closed curve with 600k- and 900k-token pools. Two later rounds repeated these predictions for the native pool (B1n–B4n) and for vLLM (B1v–B4v, with the simulator's token costs scaled to vLLM's measured all-miss rate, a fit, not a prediction), and three more, for the tests of §I, were made by the same simulator (rounds 11 and 12) and by the first-principles model of §H (round 13, in two sets: tag `r13-theory-pred`, and `r13-theory-pred2` for BASIN-2, TOOLSLOW, SHED and the H200 600k cell, with the pool-sweep lookups and the rival scoring of the 0.5-hit crossing used for the pool sweep, the 300k H200 and Llama-3.1-8B). LLM coding agents made the simulator predictions, each in its own copy of the repository and instructed not to read the results they predicted; every round was committed and pushed under a tag before its results were read by its authors. What that means differs by round: B3, B4 and B3n are blind in time; B2 was pushed after E0b had finished on the cluster but before its results were pulled, and B2n, B2v and B4v after their jobs were submitted but before any had finished; B1, B1n and B4n are not blind, and B1 is close to the calibration data; B3v predates the vLLM registration, but its BURST part is blind only on the predicting agent's side. An independent verifier reran the first round. Appendix N gives the details and the time record of every round.
Commit and tag times are set by the committer. The external record is GitHub's activity log for the development repository, archived in `provenance/github_activity_2026-10.json` and, refreshed after the last registered job, `provenance/github_activity_2026-11-01.json`, together with the cluster's accounting records of the cited jobs (`provenance/sacct_cited_jobs_2026-10-30.txt`, `provenance/sacct_cited_jobs_2026-11-01.txt`). The development repository is private; the archived log is an unsigned export made by the first author with GitHub's API, and the hash chains in `provenance/registration-proofs/` show that the files are unchanged, not when they were pushed; `provenance/push_times_2026-10.tsv` and its refresh `provenance/push_times_2026-11-01.tsv`, which adds the rounds 11 to 14, list, for each registration and prediction commit, its first arrival on GitHub and the first job it concerns. GitHub records no push time for tags, so the push times given here are those of the first branch update that contains each commit. The branch holding B1–B4 (`64bc4e3`) and the verification reached GitHub at 14:53:07 CDT on 10-24, and the E2 registration (`d279b7b`) at 15:09:54, before the E2 jobs were submitted at 15:13:39. On 10-25, B1n–B4n (`e3ea48f`) arrived at 15:08:28, the native registration (`b8c19ec`) at 17:31:56 and the exploratory vLLM registration (`a78ce07`) at 18:06:33. Pull times are from our local records only.

B3 (E2) and B4 (native pool) reached GitHub before their experiments were submitted, so they are blind in time. B2 (E0b) was committed after E0b had finished on the cluster but

Table 13: Every registration, in order. FILLED registrations bind a test's cell, rates, cap, references, hardware and protocol, and the job script refuses to run a test without one; EXPLORATORY ones are derived from a FILLED parent and are never called decisive. Times CDT, except the four rows of 2026-11-05 (CST), which were registered after Lu et al.'s paper appeared.

File (`configs/agentload_prereg_*`)	status	committed	on GitHub	runs and outcome
`2026-10-24.yaml` (E2)	FILLED	`d279b7b` 10-24 15:09:12	15:09:54	18 runs; pass (§G.2)
`2026-10-24_grid_sglang-*.yaml` (3 grid cells)	EXPLORATORY	`499c0df` 10-24 23:30:55	23:31:32	18 BURST runs (§G.6)
`2026-10-25_native.yaml` (native E2)	FILLED	`b8c19ec` 10-25 17:31:16	17:31:56	18 runs; pass (§G.2)
`2026-10-24_grid_vllm-fcfs.yaml`	EXPLORATORY	`a78ce07` 10-25 18:06:18	18:06:33	6 BURST runs (§G.2)
`2026-10-30_vllm.yaml` (vLLM E2)	FILLED	`5a6fbcd` 10-30 16:23:59	16:26:35, after two jobs started	18 runs; pass; registered, not pre-registered
`2026-10-30_b100.yaml`, `_b25.yaml` (BASIN-1)	FILLED	`9128995` 10-30 19:51:20	20:04:30	6 BURST runs; pass (Table 24)
`2026-10-30_grid_sglang-lpminf.yaml`	EXPLORATORY	`5064580` 10-30 21:02:19	21:02:46	3 BURST runs; no collapse on the two informative seeds, no recovery (Table 25)
`2026-10-31_rescue.yaml` (R1), `_rescue_native.yaml` (R4), `_rescue_smoke.yaml`	FILLED	`f0bc3ad` 10-30 22:10:47	22:39:02	9 runs, submitted 23:01; R1 and R4 pass (§G.3); the smoke job is never decisive
`2026-10-31_b40.yaml`, `_b50.yaml`, `_b60.yaml` (BASIN-2)	FILLED	`621d88f` 10-31 01:58:38	02:10:48	9 runs, submitted 04:21; bracketed: 40 good, 60 stuck, 3 of 3 each (§G.4)
`2026-10-31_toolslow_d10.yaml`, `_d30.yaml`	FILLED	`b006291` 10-31 02:27:40	02:28:09	6 runs, submitted 04:21; rule not met: 10 s good in 3 of 3, 30 s stuck in 1 of 3 (§I)
`2026-10-31_shed_t600.yaml`, `_t3600.yaml`	FILLED	`b006291` 10-31 02:27:40	02:28:09	4 runs, submitted 04:21; pass: 600 s stuck, 3600 s good, 2 of 2 each (§I)
H200 cell, 300k pool	none			window $(1,\ 1.3)$ λ_{ref} too narrow: the rule's rates 1.10 and 1.20 fall outside its margin band $(1.1,\ 1.17)$, and the fill returns INCOMPLETE; no test
`2026-10-30_llama31.yaml` (Llama-3.1-8B E2)	FILLED	`1559f8e` 10-31 07:49:13	07:49:15	18 runs, submitted 07:50:02 (17170409–26); window $(1,\ 2.0)$ λ_{ref}, 1.35 and 1.65 λ_{ref}, cap 20; pass at 1.65 λ_{ref}, fail at 1.35 (§I)
`2026-10-31_h200_p600k.yaml` (H200 600k E2)	FILLED	`4d1d431` 10-31 09:26:38	09:26:41	18 runs, submitted 09:27:44 (17171020–37); window $(1,\ 2.5)$ λ_{ref}, 1.5 and 2.0 λ_{ref}, cap 48; pass at both rates (§I)
`2026-11-05_toolslow_d30w1800.yaml` (TOOLSLOW-W)	FILLED	`e05a262` 11-05 03:17:48	03:18:36	3 runs, submitted 03:21:38 (17256674–76); TRAPS, stuck 3 of 3 (§3)
`2026-11-05_toolslow_d15_165.yaml` (TOOLSLOW-D15)	FILLED	`e05a262` 11-05 03:17:48	03:18:36	3 runs, submitted 03:57:14 (17256873–75); [pending: outcome]
`configs/r15_edge_replicate.yaml` (REPLICATE-EDGE)	EXPLORATORY	`e05a262` 11-05 03:17:48	03:18:36	6 runs in two jobs, submitted 03:21:38 (17256677–78); both originals reproduced, 3 of 3 each (§8)
`2026-11-05_cut_a115.yaml`, `_cut_b085.yaml` (CUT)	FILLED	`11b0e4e` 11-05 03:54:28	03:54:49	6 runs, submitted 03:57:14 (17256867–72); CUT-A pass (§3); CUT-B [pending: outcome]

Table 14: Order of events, 2026-10-21 to 10-26 (times CDT). Commits are those of the development repository (availability statement); commit and tag times are recorded by the committer, push times by GitHub's activity log, job times by Slurm.

When	Event
10-21	Stage 0 passes (17060165); Stage C submitted 15:28 (17062103–05)
10-22 12:54	Stage C results pulled
10-22 13:13	runbook proposes the rate rule and a cap of 20 (`288b801`)
10-22 13:14	E0a submitted (17072634–37); the last job ends 16:34
10-22 13:50	rate rule and cap adopted in the status notes; simulator cost model fitted to Stage 0/C server logs (`4435c51`)
10-22 17:03	Stage 0 and C data committed (`d0235a7`)
10-22 17:45	first push to GitHub, with the three commits above
10-23 14:32	E0a results committed (`a76f5e5`)
10-23 14:42	E0b submitted (17084750–55); jobs end by 16:09
10-24 03:13	validation of the calibrated simulator committed (`813cfc1`)
10-24 03:23	prediction spec and code committed before any prediction run (`630ab9e`); on GitHub 03:24
10-24 03:49	predictions B1–B4 committed (`64bc4e3`)
10-24 04:05	independent verification recorded (`877b936`)
10-24 14:52	tag `r6-predictions-frozen` (tagger time)
10-24 14:53	B1–B4 and the verification reach GitHub
10-24 15:06	E0b results pulled
10-24 15:09	E0b data and registration committed in the same second (`cfbc702`, `d279b7b`); registration on GitHub 15:09:54
10-24 15:13	E2 submitted (17093387–404)
10-24 15:38 to 10-25 02:36	E2 jobs run
10-25 02:28	native-pool Stage C and E0a start (17096856–58)
10-25 14:40	registered E2 verdict computed (data `49fbc7b`)
10-25 14:42	native Stage C curve analysed on the cluster; native curve and λ_{miss} in the status notes at 14:47 (`6793fb7`)
10-25 14:45	native E0b (17100938–39) and vLLM E0a (17100940) start
10-25 14:49	native prediction spec committed (`29728e3`)
10-25 14:52	native Stage C and E0a data committed (`fa265c2`)
10-25 14:54	B1n–B4n run on the clean code commit `0336c91`
10-25 15:06	B1n–B4n committed (`e3ea48f`); on GitHub 15:08:28
10-25 15:08	tag `r8-native-predictions-frozen` (tagger time); native rate rule in the status notes (`6cb43e9`)
10-25 17:26	native E0b jobs end; pulled 17:30
10-25 17:31	native E0b data and native registration committed (`f3f55ab`, `b8c19ec`); registration on GitHub 17:31:56
10-25 17:42 to 10-26 01:11	native E2 jobs (17102173–90)
10-25 18:06	vLLM calibration and exploratory registration committed (`65b65e2`, `a78ce07`), on GitHub 18:06:33; vLLM BURST submitted 18:07 (17102318–23)
10-25 22:42 to 10-26 03:24	vLLM BURST jobs
10-26 10:07	native E2 and vLLM BURST verdicts computed (data `f116cf3`)

Table 15: Order of the vLLM events on 2026-10-30 (times CDT, recorded as in Table 14).

When	Event
12:10	vLLM Stage C (17162959–61) and E0b (17162962–63) submitted; 17162959–60 start 12:11
12:16	rule for the vLLM cap and rates in the status notes, on GitHub (`836063a`)
12:31	B1v–B4v committed (`cc01dbf`); tag `r9-vllm-predictions-frozen` 12:32 (tagger time)
12:32	B1v–B4v reach GitHub (12:32:44)
14:36	first vLLM jobs end (Stage C, 17162959–60)
15:35	vLLM Stage C curve analysed on the cluster
16:23	bracket of the five finished vLLM E0b runs (16:23:19); vLLM registration committed (`5a6fbcd`, 16:23:59)
16:24	paired test submitted (17166121–38, 16:24:36); first job starts 16:25:42, second 16:26:17
16:26	vLLM registration and Stage C data (`276c5f0`) reach GitHub (16:26:35)
17:17	vLLM E0b job 17162963, with the 3.0 λ_{ref} run, ends
17:28	vLLM E0b data committed and pushed (`582c2a6`)

before its results were pulled. The LLM agents that made the predictions worked in separate copies of the repository at a commit without the E0a or E0b results and were instructed not to contact the cluster and not to open the E0a or E0b result directories or the primary copy of the repository; they could technically have done so. Their tool-call transcripts, which are not in the repository, were checked afterwards by the orchestrating Claude Code session, which found no cluster command and no access to E0b before the predictions reached GitHub. For B2 this instruction-level control, checked after the fact, is the only safeguard. A scan of every line added between the commit the agents started from and the predictions found no use of withheld data, but a text scan cannot prove that nobody read it. B1 (E0a) rests on the same instruction only: E0a was committed before the predictions. The independent verifier, a separate OpenAI Codex session, had read the project status notes, which mention E0a, so it is independent but not blind; it also reused the prediction agents' copy of the repository instead of a fresh one, as its record states. Its evidence is in `provenance/codex_prediction_verification/`. Two conditions of the verification failed and are disclosed: the strict containment of B3 passes within the B2 all-stable range, and the platform-specific test failures of the full suite.

In the second round, B2n (native E0b) and B3n (native E2) reached GitHub while native E0b was still running, before any of its runs had finished, and before the native registration or any native E2 job existed. B3n is therefore blind in time. B2n reached GitHub 23 min after the two native E0b jobs were submitted, when both were running, so it is blind in the sense that no result existed, not in submission order. B1n and B4n are not: native Stage C and E0a had finished, and their headline numbers were in the project status notes before the round's specification was written. That specification is shared

by all four, so B2n and B3n are blind to the native E0b and E2 outcomes but were specified after the native curve was known, and B3n's cap of 64 is B4n's output. The LLM agent that ran the round worked in a separate copy of the repository at a commit that predates the native data (`fb3510e`) and, by its own record, read nothing under the real-engine results directories; that record has not been checked independently. No independent verifier reran the second round.

In the third round (`notes/PREDICTIONS_vllm.md`), an LLM agent in a separate copy of the repository at `a4bab1d`, which holds the exploratory vLLM BURST data but no vLLM closed curve or edge, ran the calibrated simulator with its token-proportional costs scaled by one factor per batching mode (1.0882 mixed, 1.0806 separate), chosen so that its all-miss token rate equals vLLM's measured 10,349 tokens/s; since the factor is fitted, B1v is not a prediction. By its own record, which has not been checked independently, it read nothing under the real-engine results directories; the two real vLLM numbers it used, λ_{miss} and the all-miss token rate, were given in its task. The predictions (`cc01dbf`, committed 12:31:58) reached GitHub at 12:32:44, 21 min 48 s after the five vLLM Stage C and E0b jobs were submitted (Table 15); two of these jobs had been running since 12:11 and none ended before 14:36:50. So B2v and B4v are blind in the sense that no result existed when they were pushed, not in submission order; B3v predates the vLLM registration and the paired test. The orchestrating Claude Code session that specified the round knew the outcome of the exploratory vLLM BURST runs, which were in the repository by then, and chose the candidate rates, so the BURST-arm predictions at 1.35 and 1.65 λ_{ref} are blind at most on the predicting agent's side. The notes' remark that their branch was never pushed predates the push. No independent verifier reran the third round. The vLLM registration's own timing is in Appendix M.

Rounds 11 to 14. Table 16 gives the time record of the later rounds. Round 11 froze the mechanism checks for the registered vLLM test (§G.2) and the simulator's predictions for the basin, fresh-seed, LPM-INF and rescue tests; round 12 the simulator's predictions for the Llama-3.1-8B cell, with its token costs scaled to the cell's measured all-miss rate (a fit); round 13 the first-principles model of §H; round 14 registered the BASIN-2, TOOLSLOW and SHED tests. LLM agents ran the simulator rounds in separate copies of the repository. The round-11 rescue predictions were revised after two adversarial reviews and before any rescue run, and every registered quantity was bit-identical before and after the revision (`notes/PREDICTIONS_r11_rescue.md`). The agents that derived the first-principles model read every committed result of the three measured cells and the registered protocols of BASIN-1, R1 and R4, and no H200, Llama, pool-sweep, basin, fresh-seed, LPM-INF or rescue result (`notes/PREDICTIONS_r13_theory.md`, "Blindness scope"). When they froze the basin and rescue predictions they also knew the simulator's burst-size sweep of §T.1 (bursts of 25 never trapped, 50 about half the time and 100 always) and the registered simulator rescue prediction (R1 rescued in 20 of 20 seeds at both rates). Their only H200 inputs were its E0a measurements. The agent that operated the H200 cell had shown its closed-curve values for $n \leq 32$ to the first author before the freeze; the agents that derived the model did not see them.

Table 16 also gives what each prediction is blind to. The simulator's BASIN-1 and fresh-seed predictions reached GitHub before those jobs were submitted, and its LPM-INF predictions before the LPM-INF jobs, so all three are blind in time. For the theory, no BASIN-1 run is blind in time. The three 25-session runs had started 1.7 to 2.2 h before the push (6230–7807 s of 8700 s elapsed, past the burst and into the window [5700, 8700) s), and the three 100-session runs had ended 0.2 to 1.6 h before it, so for all six the prediction is blind only by access: no one is known to have read them before the push, and the first recorded reading of any BASIN-1 or fresh-seed outcome was at about 04:07, but no file-access record can show this, because the cluster's class storage is mounted without access times. The same holds for the H200 cell's closed runs at n = 40, 48, 96 and 300 and its original E0b runs. They had ended before the freeze, and they were first read after it, when the curve and the bracket were combined at 02:30. The runs at n = 36, 44 and 52 were submitted after the freeze and are blind in time. No blind simulator prediction exists for the H200 cell. The second theory set (pred2) reached GitHub at 04:20:20, before the BASIN-2, TOOLSLOW and SHED jobs were submitted (04:21:40 to 04:21:43), so its predictions for them are blind in time. The 600k H200 jobs had been submitted at 02:50 but could not start before 05:00 and first started at 05:27, so its 600k predictions are blind in time by the start criterion of Table 8: no result existed at the push. The pool-sweep jobs had been submitted at 22:58 on 10-30, before either set was pushed, but were held until 02:30 and first started at 06:50:13, so both sets are blind in time for them by the same criterion. The model's a priori Llama-3.1-8B predictions (pushed at 02:05:30) and the simulator's (02:14:06) are blind by access only for that cell's closed runs, which ran from 00:50 to 03:31: three had ended at the theory push, three were running and three started after it (from 02:26); by the operator's record none was read before both pushes (the curve was first combined from 03:14, for n = 16–24, and in full by 03:37). That cell's from-empty runs started after 03:40 and are blind in time for both, as are its paired-test jobs (submitted at 07:50:02, before that push; first start 12:41) for the registration-conditional predictions pushed at 07:52:42 and 07:52:56. pred2's table for the fresh seeds is not blind: it was committed at 04:20:05, after the last fresh-seed run had ended (03:57:56) and after those outcomes were first read (about 04:07); by its record its agents read no result, which is why its own erratum calls it blind by access only. The simulator's rescue predictions (pushed at 21:30:40 on 10-30) and the model's (02:05:30 on 10-31) reached GitHub before the first rescue run started (02:23:44 on 10-31), so all nine rescue runs are blind in time to both; the smoke run ended before the model's push, but the model made no prediction for it, and by their record the agents that derived the model had no Nova access and opened no rescue

output before the push.

Round 15. Table 17 gives the time record of round 15, on 2026-11-05, after Lu et al.'s paper had appeared (2026-11-02) and with it in hand: the trap-state and CUT predictions, the TOOLSLOW-W, TOOLSLOW-D15 and CUT registrations and the exploratory REPLICATE-EDGE rule (times CST, from `provenance/push_times_2026-11-05.tsv` and `provenance/sacct_cited_jobs_2026-11-05.txt`). Every registration and prediction commit reached GitHub before the first job of its batch was submitted, by 145 s to 3 h 32 min; the one later commit added an unregistered column to the scorer before any output existed.

N.1 Blind predictions against outcomes

B1 matched within 3.1% (Table 18), which mostly checks the simulator's bookkeeping (§F.4). B2's edge, 0.14–0.15 sessions/s, is consistent with the nominal seed-0 bracket [0.143, 0.179); near 0.179 the model keeps 2 of 3 runs stable (15 of 20 with more seeds), so one unstable run there is no contradiction, and the engine was stable there on the three fresh seeds of §G.1 (3 of 4 seeds stable in all). B3 predicted a pass at every tested rate in both batching modes. At the simulated rates that bracket each registered rate, the primary (mixed) mode's trapped token ratios, 1.003–1.027 at 0.09–0.10 sessions/s and 1.025–1.043 at 0.11–0.12, contain the observed 1.009–1.025 at 0.0966 and 1.025–1.029 at 0.1180; but at 0.12, the grid point nearest the higher rate, the prediction was 1.034–1.043, above what the engine did. The observed good-arm hit fractions (0.921–0.934) are close to, and at the low end partly below, the predicted 0.929–0.937. B3 flagged both ends of its grid as fragile. At the low end the slope margin $0.5(\lambda - \lambda_{\text{miss}})$ is small: with its registered three seeds it trapped 3 of 3 at both 0.09 and 0.10, but with 20 seeds 14 and 18, so 10–30% of runs there are stuck without meeting the slope test; one indeterminate real run in three at 0.0966 is consistent with that. At 0.16 the 20-seed supplement of the secondary (separate) mode failed the pass rule, with NOBURST good in 13 of 20 seeds, one short; the engine was not run there. (Backlogs compare only roughly: the simulator counts waiting requests, the engine runs outstanding ones.) B4 got the peak's position, within its coarse grid, and the outward shift of the cliff; the predicted peak was 9% above the real one and the cliff early: on B4's grid of 64 and 96 the real hit fraction crosses 0.5 near 91, against B4's 80, and at $n = 96$ the engine still hit 42% of turns, against B4's 5%. The early cliff is mostly the pool: B4n, the same simulator at the real pool (not blind), hit 0.42 at $n = 96$ and crossed 0.5 near 94. The peak error is not: at $n = 64$, where nothing is evicted, seed 0 gives the same 0.523 in both pools. Two qualifications: the verifier's strict check that every B3 pass lies inside the B2 all-stable range failed (B3 asks for 2 of 3 seeds over a longer run), and B2 is blind only by instruction (checked afterwards from the agents' transcripts) and by commit order, not by event order: E0b had finished on the cluster before the predictions were committed, and was pulled 13 minutes after their commit reached GitHub.

The second round, for the native pool, held in part: B3n's pass held at the registered rates, which lie 6–16% below its own test points, with trapped token rates, backlogs and good-arm hit fractions consistent with the lower rates; the primary mode of B2n put the from-empty edge at least one grid step too high; and B1n and B4n are not blind (Appendix R). For vLLM, B4v and B2v got the peak level, the cap and the edge right but predicted a later and gentler cliff, and B3v's pass held (§G.2).

Slips in the registration record. The vLLM registration reached GitHub after the first two of its jobs had started (§F.3), and the memory request of its 15 pending jobs was lowered after submission (Appendix R.2). B1n and B4n were specified after the native curve was known, and B2n, B2v and B4v were pushed after their jobs were submitted (Appendix N). The pool-sweep jobs (for both theory sets), the 600k H200 jobs (for pred2) and the Llama-3.1-8B paired-test jobs (submitted at 07:50:02, for the registration-conditional predictions pushed at 07:52:42 and 07:52:56) were also submitted before the predictions were pushed, but none started until after the push, so we count those predictions as blind in time by the start criterion of Table 8. The agent that operated the H200 cell saw its closed-curve values for $n \le 32$, which include the predicted peak, before the freeze and showed them to the first author; the agents that derived and froze the model did not see them, so the H200 peak-ratio rule and hit(32) are not blind to the first author, while the runs at $n = 36$, 44 and 52 are blind in time and the other runs at $n \ge 40$ and the original from-empty runs, which had ended before the freeze, are blind by access only; four H200 E0b reseeds were added after the first H200 E0b had been read (§I). No blind simulator prediction was made for the H200 cell. The 100-session runs of BASIN-1 had ended 0.2–1.6 h before the model's predictions were pushed, and the 25-session runs were then 6230–7807 s into their 8700 s; no one is known to have read them before then, but the cluster's file system records no access times, so all six predictions are blind by access only. The H200 runs at $n = 36$, 44 and 52 and the fresh-seed from-empty runs ended before pred2 was pushed and were read before it (combined at 04:09; first read at about 04:07), so pred2's tables for them are not blind, nor are its rows for BASIN-1's burst sizes, whose outcomes the agent that operated the basin cell also first read at about 04:07; pred2's agents read no BASIN-1 result, so to them those rows are blind by access only. The freeze record of pred2, `notes/PREDICTIONS_r13_pred2.md`, says it was pushed before the first job of the H200 runs at $n = 36$, 44 and 52 (those jobs were submitted at 02:33 and had ended before the push); its dated erratum (`bf19385`) corrects this and calls both tables blind by access only, counting only its agents' access. The BASIN-2, TOOLSLOW and SHED jobs were submitted after the push (04:20:20 CDT; jobs submitted 04:21:40–43). pred2's rival scoring of the 0.5-hit crossing, including the test of the tool-call term, was declared after the 300k H200 and Llama-3.1-8B curves had been combined by

Table 16: Order of the round-11 to round-14 events, 2026-10-30 and 10-31 (times CDT; commit and tag times by the committer; submission, start and end times of jobs by Slurm's accounting, run end times by each run's `meta.json`). Push times marked * were read from GitHub's activity log at the time (recorded in `notes/PREDICTIONS_r11_mechanism.md`, `notes/PREDICTIONS_r13_theory.md`, and `notes/PREDICTIONS_r13_pred2.md`) or on 10-31; each agrees with the export of 2026-11-01 (`provenance/github_activity_2026-11-01.json`; rows of `provenance/push_times_2026-11-01.tsv`, except `f1338e3` and `d12eef2`, which are in the export only). The last rows run past 02:00 CDT on 11-01, when daylight saving time ended; times after it are CST.

When	Event
10-30 18:20	r11 mechanism predictions for the vLLM test committed (`f1338e3`, 18:20:11) and pushed (18:20:13*); three of its 18 jobs running, none ended
10-30 18:55	first vLLM paired-test job ends (17166121, 18:55:07)
10-30 19:50	BASIN-1 and fresh-seed predictions (`c600fd7`); BASIN-1 registrations (`9128995`, 19:51); tag `r11-basin-reg` 20:04; all pushed 20:04:30*
10-30 21:01	LPM-INF predictions (`e2e8474`) and registration (`5064580`, 21:02); tag `r11-lpminf-pred` 21:02; pushed 21:02:46*
10-30 21:12	BASIN-1 and fresh-seed jobs submitted (17168500–07, 21:12:45–46)
10-30 21:28	rescue predictions (`72501f0`); tag `r11-rescue-pred` 21:30; pushed 21:30:40*
10-30 22:07	LPM-INF jobs submitted (17168743–45, 22:07:40)
10-30 22:10	R1 and R4 registrations (`f0bc3ad`); tag `r11-rescue-reg` 22:38; pushed 22:39:02*
10-30 22:28	the H200 operator reads the closed-curve values for $n \le 32$ (17166818–22) and shows them to the first author
10-30 22:38 to 23:52	H200 closed runs at $n = 40$, 48, 96 and 300 end (17166828–34; not read until 02:30)
10-30 22:58	pool-sweep jobs submitted (17168864–81, 22:58:03); eligible to start from 02:30:32 on 10-31
10-30 23:01	rescue jobs submitted (17168965–74, 23:01:12–13); the smoke job runs 23:24 to 00:08
10-31 00:14 to 01:08	H200 E0b jobs end (17168377–82; not read until 02:30)
10-31 00:20	last vLLM paired-test job ends
10-31 00:28 to 01:51	the three 100-session BASIN-1 runs end (00:27:56, 00:29:27, 01:50:54)
10-31 00:50 to 03:31	Llama-3.1-8B closed runs (17166814–16): three end before the theory push, three start after it (from 02:26); combined from 03:14 (n = 16–24) to 03:37 (all nine)
10-31 01:58	BASIN-2 registrations (`621d88f`); tag `r14-basin2-reg` 02:10; pushed 02:10:48*
10-31 02:05	theory frozen (`997d2c4`, 02:04:55) and pushed (02:05:30*); tag `r13-theory-pred`
10-31 02:05 to 03:58	the six fresh-seed runs end (the first at 02:04:59, 31 s before the theory push)
10-31 02:08	registered vLLM verdict computed on the cluster; pulled 02:09:56, committed 02:22 (`cacf833`)
10-31 02:14	Llama simulator predictions (`a62aea9`) pushed (02:14:06*); tag `r12-llama31-predictions-frozen`
10-31 02:20 to 02:47	the three 25-session BASIN-1 runs end
10-31 02:23 to 06:57	the nine registered rescue runs (17168966–74; the first starts at 02:23:44, 18 minutes after the theory push; the last ends at 06:57:06)
10-31 02:27	TOOLSLOW and SHED registrations (`b006291`); tag `r14-extra-reg` 02:27:59; pushed 02:28:09*
10-31 02:30	H200 nine-point curve and E0b bracket combined on the cluster: first reading of $n \ge 40$ and of the edge
10-31 02:33	H200 closed runs at $n = 36$, 44 and 52 submitted (17169612–14, 02:33:06); they end 03:25 to 04:01
10-31 02:50	H200 E0b reseeds (17169668–71, 02:50:20) and 600k jobs (17169672–80, 17169682–87, 02:50:32 to 02:51:20, not eligible to start before 05:00) submitted
10-31 03:49 to 04:21	the three LPM-INF runs end
10-31 04:07	first recorded reading of the BASIN-1 and fresh-seed outcomes (about 04:07)
10-31 04:20	second theory set for BASIN-2, TOOLSLOW, SHED and the H200 600k cell, with the pool-sweep lookups and the rival scoring of the 0.5-hit crossing, committed (`cfa7712`, 04:20:05) and pushed (04:20:20*); tag `r13-theory-pred2`
10-31 04:21	BASIN-2, TOOLSLOW and SHED jobs submitted (17169893–911, 04:21:40 to 04:21:43) from clones at the registration tags, by scripts that require the pred2 commit
10-31 05:27	first 600k H200 job starts (17169672–80, 82–87); curve and bracket combined at 09:24
10-31 06:50 to 11:04	pool-sweep runs (17168864–81); pulled at 11:23 and scored against both sets (`3025139`)
10-31 07:05	rescue runs pulled (committed in `c6ea41e`); registered verdicts computed at 07:17 (`be50593`, `454ff7a`)
10-31 07:49	Llama-3.1-8B registration (`1559f8e`, 07:49:13) pushed (07:49:15*); its 18 E2 jobs submitted at 07:50:02 (17170409–26)
10-31 07:52	registration-conditional Llama predictions (`a36f441`, `d12eef2`) pushed (07:52:42*, 07:52:56*), before any Llama E2 job started (first start 12:41)
10-31 09:26	600k H200 registration (`4d1d431`, 09:26:38) pushed (09:26:41*); its 18 E2 jobs submitted at 09:27:44 (17171020–37)
10-31 09:27 to 11-01 00:28	the 18 600k H200 paired-test runs (17171020–37)
10-31 10:10 to 15:11	the nine BASIN-2 runs (17169893–901); pulled at 15:42 and first read then
10-31 12:41 to 23:31	the 18 Llama-3.1-8B paired-test runs (17170409–26)
10-31 21:03 to 11-01 01:00 CST	the six TOOLSLOW and four SHED runs (17169902–11)
11-01 15:44 to 15:49 CST	registered analyses over all runs, with the frozen code: the 600k H200 and Llama-3.1-8B verdicts computed on the cluster and pulled (15:45); the TOOLSLOW and SHED runs pulled and analysed locally (`db24efa`, 15:49)

Table 17: Order of the round-15 events, 2026-11-05 (times CST; commit times by the committer, push times from GitHub's activity log, job times by Slurm's accounting).

When	Event
11-05 00:24	trap-state predictions and scoring rules S1–S5 (`6b47a6c`, 00:24:39); tag `icml-trap-pred`; pushed 00:24:47
11-05 01:09	the trap-state scorer `analysis/theory/icml/score_new.py` (`24b5e13`, 01:09:21) pushed (01:09:25)
11-05 02:25	CUT predictions from each seed's exact plan (`2f90267`, 02:25:33); tag `icml-cut-pred`; pushed 02:25:43
11-05 03:18	TOOLSLOW-W and TOOLSLOW-D15 registrations, the simulator and pred2 predictions for them, and the REPLICATE-EDGE rule (`e05a262`, 03:17:48); tag `r15-reg`; pushed 03:18:36
11-05 03:21	TOOLSLOW-W and REPLICATE-EDGE jobs submitted (17256674–78, 03:21:38)
11-05 03:34	the scorer's unregistered γ/z column (`fdb80c9`, 03:34:32) pushed (03:34:35), 777 s after the TOOLSLOW-W submission and before any of its output existed
11-05 03:54	CUT registrations (`11b0e4e`, 03:54:28); tag `r15-cut-reg`; pushed 03:54:49
11-05 03:57	CUT and TOOLSLOW-D15 jobs submitted (17256867–75, 03:57:14)
11-05 05:51 to 06:04	the five TOOLSLOW-W and REPLICATE-EDGE jobs end; pulled at 06:10
11-05 06:38	CUT-A runs pulled; registered verdict computed at 06:39

their operators (the H200 curve at 02:30; the Llama curve from 03:14, in full by 03:37), so for those two cells it is not blind. The model's and the simulator's Llama-3.1-8B predictions were pushed while that cell's closed runs were in progress, so for its curve they are blind by access only; and the Llama and 600k H200 registrations were pushed 47 and 63 s before their jobs were submitted and are not tagged, nor are the Llama registration-conditional predictions (`a36f441`, `d12eef2`). The agents that froze the basin and rescue predictions of the model knew the simulator's burst-size sweep and its registered rescue prediction. The engage time of the native rescue test was chosen after a simulator prediction for an earlier engage time had been seen, before any rescue run. The bands of the frozen vLLM mechanism checks were chosen on SGLang runs and on exploratory vLLM runs whose arrivals the registered BURST arm repeats, so only its no-burst and capped arms are out of sample for those checks. No registration or prediction is in a third-party registry, and none has a timestamp other than GitHub's push log of the development repository, which is private, so readers see that log only in our export.

O Provenance

Every number in the paper is listed with its source file and commit or job in `paper/NUMBERS.md`. Table 19 gives the data directory and commit behind each result. The commit hashes cited are those of the development repository; the public repository's history is a redacted copy of it, and `provenance/registration-proofs/` maps each cited registration and prediction commit to its public counterpart (availability statement). The 103 commits made before 17:45 CDT on 2026-10-22, including `288b801`, `4435c51` and `d0235a7` cited here, predate a history rewrite on that day that removed the AI co-author trailers from their commit messages and changed nothing else: trees, authors, dates and parent relations are unchanged. `provenance/commit-map.tsv` maps their old hashes, which notes and run records written before the rewrite cite, to the current ones; the repository the old hashes belong to is not on GitHub, so they can be checked only against this map. Their earliest server record is the repository's first push to GitHub, at 17:45:50 CDT on 2026-10-22, with which 97 of them arrived, these three among them, before E0b was submitted on 2026-10-23; one more (`fc870c2`) arrived 2 s later, and five are reachable only from archive tags, which have no push record.

Repository, redactions and timing evidence. Its history is a redacted copy of the authors' development repository: passages unrelated to the paper were removed from four notes files and one clause from each of two commit messages, five local tool-configuration files were dropped from every commit (all listed in `provenance/REDACTIONS.md`), and no code, experiment configuration, registration, result or paper file changed in it. A final release commit adds licences and README text and replaces allocation names in some notes, job-script comments and tests (`provenance/`). Its commit hashes therefore differ from those cited in this paper, which are the development repository's. The directory `provenance/` maps every cited hash to its public counterpart and holds the timing evidence: GitHub's push log of the development repository (`github_activity_2026-10.json`, refreshed in `github_activity_2026-11-01.json`), the external record of when each registration and prediction reached GitHub (§F.3, Appendices M and N); for every registration and frozen prediction, the original commit, tree and tag objects, the push-log event that first carried them, and a script that recomputes the hash chains and checks that each registration file in the public repository is byte-identical to the registered one (`provenance/registration-proofs/`); for the registrations and predictions pushed after 2026-10-30, the refreshed push log (`github_activity_2026-11-01.json`) and the first push of each with the first job it concerns (`push_times_2026-11-01.tsv`); for round 15 (2026-11-05, CST), `github_activity_2026-11-05.json`, `github_tag_refs_2026-11-05.json`, `push_times_2026-11-05.tsv` and the accounting records of its 14 jobs (`sacct_cited_jobs_2026-11-05.txt`, and in UTC `sacct_cited_jobs_2026-11-05_utc.txt`; jobs still running at the export show no end time); the cluster's accounting records of all 258 cited jobs (`sacct_cited_jobs_2026-11-01.txt`, and in UTC

Table 18: Blind predictions (calibrated simulator, mixed batching unless noted) against outcomes; rates in sessions/s; native and vLLM rates in multiples of λ_{miss} (for the simulator its own, for the engine that cell's λ_{ref}). Percentages in the last column are predicted/real −1. B1 is not blind in time and is close to the calibration data (§F.4, Appendix N). B3 and B3n used a per-arm pass rule (each arm in 2 of 3, resp. 7 of 10, seeds); the registered rule asks for all three arms in the same seed, which B3n's runs also meet (9 of 10 seeds at its low mixed point, 10 of 10 elsewhere). B3's token-ratio and backlog ranges are over the two simulated rates that bracket each registered rate. B4 is the registered seed 0 on the grid n = 48, 64, 96 (supplementary 5-seed means: peak 0.514, $\mu(96)$ = 0.085, $\mu(300)$ = 0.108). B2n and B3n: 10 seeds ("sep.": separate batching); B3n's low and high points are 2.85 and 4.65 (sep. 2.65 and 4.35). B4v and B2v: vLLM, variant V1 (simulator token costs scaled to vLLM's all-miss rate), 10 seeds, turns-based rates. B3n is blind in time; B2n, B4v and B2v were pushed after their jobs were submitted, before any run had finished (§G.2); B4n (3-seed mean) is not blind. B3v: vLLM paired test, all four configurations (V0, V1; mixed, separate), 10 seeds; blind in time, its BURST part blind only on the predicting agent's side (§G.2).

	predicted	real
B1	λ_{miss} 0.0722 (turns)	0.0715 (+0.9%)
	11,220 tokens/s	11,243 (−0.2%)
	λ_{miss} 0.0694 (sessions)	0.0717 (−3.1%)
B2	all-stable edge 0.14 (3 seeds), 0.15 (20)	in [0.143, 0.179) (seed 0)
	at 0.18: 2/3 stable (15/20)	0.179: 3/4 seeds stable
B3	PASS at all rates 0.09–0.16	PASS at 0.0966, 0.1180
	20 seeds: sep. fails at 0.16	(0.16 not run)
	token ratio 1.003–1.027 (0.09–0.10)	1.009–1.025 (0.0966)
	1.025–1.043 (0.11–0.12)	1.025–1.029 (0.1180)
	backlog 171–234 (0.09–0.10)	194–226 requests
	253–313 requests (0.11–0.12)	277–325
	good-arm hit 0.929–0.937	0.921–0.934
	trapped 3/3 at 0.09 and 0.10;	trapped 2/3 at 0.0966
	20 seeds: 14/20, 18/20	
B4	peak n = 64, μ 0.523 (900k)	n = 64, 0.479 (+9%)
	0.5-hit crossing ≈80	≈93 (≈91 on B4's grid)
	$\mu(96)$ = 0.079, $\mu(300)$ = 0.109	0.123, 0.101
B2n	all-stable edge 6.5; sep. 6.0	in [5.5, 6.5)
	at 6.5: 10/10 stable; sep. 8/10	6.5 unstable
	at 1.5–5.5: 10/10 stable, both	stable
B3n	PASS at 2.85, 4.65; sep. 2.65, 4.35	PASS at 2.5, 4.0
	trapped token ratio 1.086–1.109 (low)	1.074–1.078 (2.5)
	1.119–1.140 (high)	1.106–1.124 (4.0)
	trapped backlog 460–643 (low)	549–594 requests
	1067–1333 requests (high)	1089–1130
	good-arm hit 0.928–0.936	0.929–0.935
	BURST trapped 9/10 to 10/10	3/3 at both
B4n	peak n = 72, μ 0.532	64–80, 0.479 (+11%)
	0.5-hit crossing 94; hit 0.42 at 96	≈93; 0.42
	cap 64, 0.35% inside the rule	64
B4v	peak n = 24, μ 0.215; cap 20	n = 20, 0.211 (+2%); 20
	hit 0.74 at n = 28, 0.46 at 32	0.66, 0.08
	0.5-hit crossing 31.4	29.1
B2v	all-stable edge 2.0; at 2.5: 7/10	in [2.0, 2.5); 2.5 unstable
B3v	PASS at 1.35, 1.65 (all four)	PASS at both
	BURST trapped 7–9/10	2/3 at each
	NOBURST, CAPPED(20) 10/10	3/3 and 3/3 at each
	trapped token ratio 0.99–1.07	0.948–1.018

`sacct_cited_jobs_2026-11-01_utc.txt`, exported after the last job had ended; the earlier `sacct_cited_jobs_2026-10-30.txt` covers the jobs through the vLLM paired test); and the evidence of the independent verifier of the first prediction round. Simulator outputs are not stored, apart from their summaries; each can be regenerated from the command, commit and configuration recorded with the run (`meta.json`, `config.yaml`). The derived tables in `paper/derived/` name each engine run by its path on the cluster, `results/agentload_*/<timestamp>`; the run is stored under the pull directory of its jobs in `results/nova/`, with the same final path components. The agents' tool-call transcripts (§F.4, Appendix N) are not in the repository.

Derived numbers. Quantities that no committed analysis reports directly are computed from committed run data by `figures/paper/derived_numbers.py` and written to `paper/derived/`: the CAPPED drain times; the BURST backlog after the burst and over the window; the E0b hit fractions and realized arrival rates; the arm counts and the post-hoc sign test that counts each seed once; per BURST run, the hit fraction before the burst and the first 100 s window from which no turn hit; and, per run of every arm, the client-side cost (gate waits, turn latency, unfinished sessions) and the realized arrival and completion rates over the window. They cover E0b, E2, native E0b, native E2, vLLM E0b and the exploratory vLLM BURST runs. Each derived file names a run both by its path on the cluster and by its path from the repository root.

Notes that support the text. The math check of the model, `notes/MATHCHECK_thrashing_curve.md`, was done by an LLM agent on 2026-10-21; it predates the present assumptions (A1)–(A4) and Lemma 4, and where it differs from §E and Appendix P, those hold; the verification of Stage C (three-source hit check, eviction survival times, prompt continuity) is `notes/STAGEC_VERIFICATION.md`; the audit of the PEEK, Continuum and CONCUR rules against released code is `notes/BASELINES_AUDIT.md`; an audit of the citations as of 2026-10-25, the scoop check (Lu et al. [76] appeared on 2026-11-02, after the last registered jobs of the earlier version had run (about 2026-11-01), and this version positions our work against it; `notes/LIT_CHECK_trap_2026-11-05.md` holds the literature check for model F) and a first reading of the SGLang and vLLM sources are in `notes/lit/CITATION_AUDIT_2026-10-25.md` (that reading went twice through a page summariser, a web tool that returns a language model's summary of each file, without verbatim code; the line references of §D and Appendix P were later read verbatim in the files at the tags), and that audit predates the citations added since, among them Yuan et al. [120], which it lists as not cited; the trace statistics are in `notes/lit/AGENT_TRACES.md`. The theory's derivations and their review are `notes/THEORY_r13_merged.md`, `notes/THEORY_r13_fluid_rigorous.md` and `notes/THEORY_r13_che_endogenous.md`; where they differ from §H and Appendix Q, those hold. Where the research log and a committed CSV differ in the last digit

Table 19: Data behind each result (paths relative to the repository root at tag `arxiv-v1`).

Result	Directory (commit)
Stage 0, C	`results/nova/s0_smoke_17060165_pulled_20261021-152347/`, `results/nova/stageC_1706210x_pulled_20261022-125454/` (`d0235a7`)
E0a	`results/nova/e0a_1707263x_pulled_20261023-142037/` (`a76f5e5`)
E0b	`results/nova/e0b_1708475x_pulled_20261024-150639/` (`cfbc702`)
E2	`results/nova/e2_170933xx_pulled_20261025-144558/` (`49fbc7b`)
native, grid, vLLM	`results/nova/r7_native_grid_vllm_pulled_20261025-145126/` (`fa265c2`)
native E0b	`results/nova/e0b_native_1710093x_pulled_20261025-173038/` (`f3f55ab`)
vLLM E0a	`results/nova/e0a_vllm_17100940_pulled_20261025-180814/` (`b273241`)
native E2, vLLM BURST	`results/nova/e2_native_vllm_burst_pulled_20261026-101256/` (`f116cf3`)
vLLM C	`results/nova/stageC_vllm_1716295x_pulled_20261030-153621/` (`276c5f0`)
vLLM E0b	`results/nova/e0b_vllm_1716296x_pulled_20261030-172810/` (`582c2a6`)
validation	`results/r6_validate_stagec/20261024-025222/` (`813cfc1`)
B1–B4	`results/r6_predict_report/20261024-034707/`, `notes/PREDICTIONS.md` (`64bc4e3`)
B1n–B4n	`results/r8_native_report/20261025-150146/`, `notes/PREDICTIONS_native.md` (`e3ea48f`)
B1v–B4v	`results/r9_vllm_report/20261030-122723/`, `notes/PREDICTIONS_vllm.md` (`cc01dbf`)
vLLM E2	`results/nova/e2_vllm_1716612x_pulled_20261031-020956/` (`cacf833`); mechanism checks in its `r11_mechanism/` and `derived/`
theory	`results/theory/merged/`, `notes/PREDICTIONS_r13_theory.md`, `notes/THEORY_r13_scoring.md`, `configs/r13_theory_predict.yaml` (`997d2c4`, tag `r13-theory-pred`); `results/theory/paper/`, `figures/theory/` (`5271ff6`)
H200	`results/nova/h200_wave1_pulled_20261031-023416/` and `prereg/inputs/2026-10-31-h200/` (`d108056`); `results/nova/h200_stageC_extra_1716961x_pulled_20261031-040933/` (`748900b`); `results/nova/h200_e0b_reseeds_1716966x_pulled_20261031-050308/` (`4e27364`); 600k pool `results/nova/h200p600k_stageC_e0b_171696xx_pulled_20261031-092822/` (`8b548c0`), registration `configs/agentload_prereg_2026-10-31_h200_p600k.yaml` (`4d1d431`)
BASIN-1, E0F	`results/nova/b1_e0f_1716850x_pulled_20261031-040517/` (`4dd21e0`)
BASIN-2	`results/nova/b2_1716989x_pulled_20261031-154500/`; scoring `experiments/r14_b2_score.py`, `experiments/r14_b2_derived.py` (`eb08a5d`)
pool sweep	`results/nova/pool_sweep_1716886x_pulled_20261031-112342/`, scored by `experiments/r13_pool_score.py` into its `derived/` (`3025139`)
Llama-3.1-8B	`results/nova/llama31_wave1_pulled_20261031-033750/` (`c4c9d50`); `results/nova/llama31_e0b_registration_pulled_20261031-075313/` (`38f0712`); conditional predictions `results/theory/pred2/conditional/` (`a36f441`, `d12eef2`)
LPM-INF	`results/nova/lpminf_1716874x_pulled_20261031-042548/`, `results/r11_lpminf_eval/20261031-eval/` (`fc8b028`)
rescue R1, R4	`results/nova/rescue_1716896x_pulled_20261031-070502/` (`c6ea41e`); verdicts `results/agentload_analysis_rescue_r1/20261031-071720/` (`be50593`) and `results/agentload_analysis_rescue_r4/20261031-071748/` (`454ff7a`) in it; descriptive tables `results/rescue_paper_data/20261031-071938/` in it (`51c803d`); registrations `configs/agentload_prereg_2026-10-31_rescue*.yaml` (`f0bc3ad`); predictions `results/r11_predict_rescue/20261030-195231/` (`72501f0`)
Proposition 4	`results/theory/pred2/prop_e_cor_c.json` (`cfa7712`, tag `r13-theory-pred2`)
pred2	`results/theory/pred2/`, `configs/r13_theory_pred2.yaml`, `notes/PREDICTIONS_r13_pred2.md` (`cfa7712`, tag `r13-theory-pred2`)
rounds 11, 12	`results/r11_predict_basin/20261030-194539/` (`c600fd7`), `results/r11_predict_lpminf/20261030-194911/` (`e2e8474`), `results/r11_predict_rescue/20261030-195231/` (`72501f0`), `results/r12_llama31_report/20261031-021057/` (`a62aea9`)
gap/R_M	`paper/derived/loopvars_*.csv` (frozen script of `f1338e3`)
robustness	`results/r7_report/20261024-233554/` (`c653498`); `results/r7_traces_sim/r7_report/20261025-012451/`, `results/r7_traces_sim_adj/r7_report/20261025-012453/` (`b530e55`)
mechanisms	`results/prefix_meta_baselines_audit_summary/20261025-001850/` (`dc76032`); `results/prefix_meta_r4_curve/20261021-050856/`, `results/prefix_meta_r4/20261021-051550/` (`a1d485b`); `results/prefix_meta_mech/20261021-025902/` (`18ff187`)
push log, jobs	`provenance/`
figures	`figures/paper/`, `figures/rescue_paper_data.py`, `paper/figs/README.md`
derived	`paper/derived/`, `figures/paper/derived_numbers.py`

(three hit fractions and one backlog of the policy grid), the paper uses the CSV.

P Proofs of the quasi-static results

The congestion bound. Section E.4 states the following proposition in brief.

Proposition 6 (Request-level FCFS, any online eviction rule)**.** *Consider the closed system with n sessions under any online eviction rule, one that does not foresee tool times, and assume that its long-run rates exist and are deterministic (Appendix P) and that:*

(A1) sessions share no cached tokens, each has at most one outstanding request, and evicted KV is discarded, not offloaded to another memory tier; tool times are i.i.d. with finite mean, independent of all other randomness, and unknown to the engine until they end;

(A2) admission is request-level FCFS: no request is admitted for the first time before a request that was already waiting when it joined the queue. More generally, it suffices that the order meets the condition of Appendix P for some Q_0 and S_0 independent of n, which allows reordering while at most Q_0 requests wait and lets a follow-up pass at most S_0 requests that were waiting when it joined. At most B requests run at once, and at most $\alpha t + \beta$ admissions, re-admissions after a preemption included, occur in any interval of length t, with B, α and β independent of n;

(A3) in congestion the engine computes prompt tokens no faster than with caching disabled: $\limsup_{n\to\infty} u_n \le C$*, where u_n is the long-run rate of prompt tokens that are computed rather than served from cache when their request is first admitted (each prompt token is counted once, so tokens recomputed after a preemption are not), and C is the limit of that rate as $n \to \infty$ for the closed system with caching disabled.*

Then the long-run rates of cache-served prompt tokens and of hit turns tend to 0 as $n \to \infty$, so does the hit fraction if $\liminf_{n\to\infty} \mu(n) > 0$*, and* $\limsup_{n\to\infty} \mu(n) \le \lambda_{\text{miss}}$*. If also (A4) $u_n \to C$, that is, the congested engine stays saturated and computes prompt tokens as fast as with caching disabled, then $\mu(n) \to \lambda_{\text{miss}}$, so the hit fraction tends to 0.*

The proof below rests on Lemma 4. The idea is that a follow-up can reuse a cached token only if the token stays in the pool while the follow-up waits, which bounds reuse by M over the wait whatever the eviction rule, and that request-level FCFS makes short waits rare as n grows, because the engine cannot foresee tool times.

Remark (resident-first orders; a conjecture). Under pure LPM (without SGLang's 128-request fallback) in congestion we expect the follow-up hit fraction to tend to $P(Z < R_\infty)$, with R_∞ the congested lifetime of idle KV, so μ_∞^{LPM} exceeds λ_{miss} through tool calls shorter than R_∞; the simulator agrees (§T.2), but we have no proof. That service in arrival order sustains a metastable state is known from other systems [11, 40], and serving the newest requests first once a queue forms is deployed practice [80]; favouring a job whose cache footprint is still resident is classical affinity scheduling [100]; FCFS and LPM under prefix reuse are compared analytically by Dexter et al. [34]; and PEEK documents the 128-request fallback [112]. The exploratory LPM-INF test of §I disables that fallback on the engine.

Model and conventions. In the closed system of §E.1, n sessions are present and a finished session is replaced at once by a fresh one, whose first request joins the queue. At time 0 every session is fresh, so no tool call is in progress, as in the synchronized start of our closed runs. A request joins the queue when its session sends it, waits, and is admitted; it leaves the queue only by admission. An admitted request runs until it completes or, if the engine preempts it, rejoins the queue. At a common instant joins are processed before admissions, as when an engine receives requests before each scheduling pass, and requests that join at the same instant enter in some order; the requests waiting when request i joins are those in the queue just before it joins and those that join at the same instant ahead of it. When a request that is not its session's last completes, the session starts a tool call, and when the call ends the session's next request, a follow-up, joins the queue. By (A1) evicted KV is discarded, not offloaded. A follow-up's wait runs from its joining the queue to its first admission, and its reuse, and whether it hits, are counted at that admission. SGLang logged no retraction in any of the 73 server logs of our SGLang runs. When a running request cannot get a block for its next tokens, vLLM preempts the most recently admitted running request and returns it to the head of its queue (*Other orders* below); its closed runs logged 12 to 72 preemptions per run from $n = 32$ on (72 at $n = 300$, in a run that completed 5,395 requests), and its cache-disabled reference 9 or 10 per 32-session run. Since u_n and C count each prompt token once, at its request's first admission, recomputation after a preemption enters neither, and the proofs below go through with re-admissions counted among the admissions that (A2) bounds. By (A1) each session is at every moment in exactly one of three states: its request waits, its request runs, or it is in a tool call. Tool times have law F_Z and mean $\bar{z} < \infty$. A long-run rate is $\lim_{t\to\infty} A(t)/t$ for a count or sum $A(t)$ over $[0, t]$; we assume that these limits exist almost surely and are deterministic, as for a positive Harris recurrent Markov process from any initial state, and that λ_{miss} and C, the limits of $\mu(n)$ and u_n as $n \to \infty$ with caching disabled, exist. Every $A(t)/t$ used below is bounded for fixed n and $t \ge 1$, since at most $\alpha t + \beta$ requests are admitted by time t, so by bounded convergence each rate also equals $\lim_{t\to\infty} E[A(t)]/t$, and bounds on expectations carry over to rates.

Lemma 4 (short waits are rare)**.** *Assume (A1) and (A2), with Q_0 and S_0 as in (A2) (both 0 for request-level FCFS). Let $\gamma_n(K)$ be the long-run rate of follow-ups that wait less than K, and let $\kappa = \lfloor \alpha + \beta \rfloor + B$, $y = \kappa(1 + \bar{z})$ and $m = n - B -$*

$\alpha K - \beta - Q_0 - S_0$. *If* $m > \kappa$, *then*

$$\gamma_n(K) \le \frac{y + y^2 + \kappa y}{m - \kappa},$$

so $\gamma_n(K) = O(1/n)$ *for every fixed* $K > 0$.

The general ordering condition of (A2), the only property of the order that the proof uses, is this: if more than Q_0 requests wait at every moment from a follow-up i's joining the queue to its first admission, counting at a moment with admissions the requests that wait just before them, then all but at most S_0 of the requests that were waiting when i joined are admitted, for the first time or again, no later than that admission. Request-level FCFS meets it with $Q_0 = S_0 = 0$, since i itself waits.

Proof. For a follow-up i write q_i for the time it joins the queue, D_i for its wait and Q_i for the number of requests waiting when it joins, and let $X(t)$ be the number of sessions in tool calls at time t.

A short wait needs a short queue. Let $D_i < K$. At most $\alpha K + \beta$ admissions occur in $[q_i, q_i + D_i]$, i's own included, so fewer than $\alpha K + \beta$ occur before i's. If $Q_i \ge \alpha K + \beta + Q_0 + S_0$, then at every moment of $[q_i, q_i + D_i]$, counted as above, more than Q_0 of the Q_i requests still wait, because requests leave the queue only by admission; so at least $Q_i - S_0$ of them are admitted no later than i, and $Q_i - S_0 + 1 \le \alpha K + \beta$, a contradiction. Hence $Q_i < \alpha K + \beta + Q_0 + S_0$.

A short queue needs almost every session in a tool call. Just before q_i each of the other $n - 1$ sessions is waiting (at most Q_i of them), running or in a tool call, and i's own session is in a tool call or, if that call has length 0, running; at most B sessions run. So $X(q_i-) \ge n - Q_i - B > m$ whenever $D_i < K$.

From the instants at which tool calls end to fixed times. Follow-ups join the queue when tool calls end, which happens more often when many sessions are in tool calls, so an average over these instants is not a time average; we avoid it as follows. A request that completes in an interval $(t_0, t_0+1]$ was admitted, for the last time, in that interval or was running at time t_0, so at most κ requests complete, and at most κ tool calls start, in any such interval. Fix an integer $j \ge 0$. A follow-up that joins the queue in $(j, j + 1]$ ends a tool call that was in progress at j or started in the interval, so at most $X(j) + \kappa$ follow-ups join in it, and $X(q-) \le X(j) + \kappa$ for every $q \in (j, j + 1]$. By the previous step, the number of follow-ups that join in $(j, j + 1]$ and wait less than K is at most $g(X(j))$, where $g(x) = (x + \kappa)\,\mathbf{1}\{x > m - \kappa\}$.

A bound on $X(t)$ *that does not depend on* n. Fix t and split $(-\infty, t]$ into the intervals $I_k = (t - k - 1, t - k]$, $k \ge 0$; no tool call starts before time 0, and at most κ start in each I_k. Let $(Z_{kl})_{k\ge 0,\, 1\le l\le \kappa}$ be i.i.d. with law F_Z, independent of everything else. Give the l-th call that starts in I_k the duration Z_{kl}, and calls that start after t fresh durations. This does not change the law of the system: by (A1) each call's duration is independent of all other randomness, and the system's evolution up to any time depends on a call's duration only through whether the call has ended by then; the index (k, l) of a call is fixed when the call starts, so the variable it receives has not been used and is independent of the past at that moment, and the two constructions agree in law by induction over successive events. A call that started in I_k and is still in progress at t has a duration greater than k, so in this construction

$$X(t) \le \hat{X} = \sum_{k\ge 0} \sum_{l=1}^{\kappa} \mathbf{1}\{Z_{kl} > k\},$$

whose law depends on neither t nor n. $\hat{X}$ is a sum of independent indicators with $E[\hat{X}] = \kappa \sum_{k\ge 0} P(Z > k) \le \kappa(1+\bar{z}) = y$, so $\operatorname{Var} \hat{X} \le E[\hat{X}]$ and $E[\hat{X}^2] \le y + y^2$.

Conclusion. Since g is non-decreasing and $\mathbf{1}\{\hat{X} > m-\kappa\} \le \hat{X}/(m - \kappa)$,

$$E[g(X(j))] \le E[g(\hat{X})] \le \frac{E[\hat{X}^2] + \kappa E[\hat{X}]}{m - \kappa} \le \frac{y + y^2 + \kappa y}{m - \kappa}.$$

Summing over the unit intervals of $(0, t]$, for integer t, bounds the expected number of follow-ups that join by time t and wait less than K by t times this quantity; dividing by t and letting $t \to \infty$ gives the claim. □

The bound is of order $1/n$, but its constants grow with the admission rate and the mean tool time, so it is a statement about the limit, not about the populations we ran.

Proof idea. By (A1), the r_i prompt tokens that follow-up i reuses at its first admission are its session's own and stay in the pool from the end of the session's previous turn until that admission, an interval no shorter than its queue wait D_i, and the token-time that these intervals claim does not overlap. Resident token-time accrues at rate at most M, so follow-ups that wait at least K reuse tokens at rate at most M/K, whatever the eviction rule. By (A2) a follow-up that waits less than K joined behind fewer than $\alpha K + \beta + Q_0 + S_0$ requests, so just before it joined more than $n - B - \alpha K - \beta - Q_0 - S_0$ sessions were in tool calls; Lemma 4 (Appendix P), which uses that the engine does not see tool times, shows that such follow-ups occur at a rate of order $1/n$, and each reuses at most $L_{\max} = 40{,}350$ tokens. Letting $n \to \infty$ and then $K \to \infty$, the cache-served token rate tends to 0, and since a hit reuses more than $L_0/2$ tokens, so does the rate of hits. Counted once, at its request's first admission, each of a session's W prompt tokens is either served from cache or computed, so u_n is $\mu(n)E[W]$ less the cache-served token rate, and with caching disabled the same count gives $C = \lambda_{\text{miss}} E[W]$; (A3) gives the bound and (A4) the limit. The same count gives turns at the rate $\mu(n)E[T]$, so the hit fraction tends to 0 whenever $\mu(n)$ stays bounded away from 0.

Proof of Proposition 6. Reuse needs waiting token-time. Let follow-up i of session σ join the queue at q_i, wait D_i, and reuse r_i prompt tokens from cache at its first admission. By (A1) these tokens are σ's own, computed by its earlier requests, and evicted KV is discarded, so each of them was in the pool throughout $[q_i, q_i + D_i]$, during which σ has no running request to recompute it. These pairs of token and time are distinct for different requests: sessions share no tokens, and the waits of one session's requests do not overlap. At most M

tokens are resident at any time, so for every t, $\sum_i r_i D_i \le Mt$ over the follow-ups first admitted by t. This step uses neither the order nor the eviction rule, so it holds for clairvoyant rules too.

Reuse vanishes. Fix $K > 0$. By time t the follow-ups that waited at least K reused at most Mt/K tokens, and each of the others at most $L_{\max} = 40{,}350$, the longest prompt. So the long-run rate ρ_n of cache-served prompt tokens satisfies $\rho_n \le M/K + L_{\max}\gamma_n(K)$, and Lemma 4, with the order's Q_0 and S_0, gives $\limsup_{n\to\infty} \rho_n \le M/K$ for every K, so $\rho_n \to 0$. A hit reuses more than half its prompt, hence more than $L_0/2$ tokens, so hits occur at a rate of at most $2\rho_n/L_0 \to 0$.

Work. A session with T turns sends $W(T)$ prompt tokens (§E.1), and each, counted once at its request's first admission, is either served from cache or computed. The closed system has n slots, each holding one session at a time and a fresh one after it finishes, so each slot holds a sequence of sessions with i.i.d. turn counts, and by the strong law of large numbers completed sessions bring prompt tokens at the long-run rate $\mu(n)E[W]$ and turns at the rate $\mu(n)E[T]$; sessions in progress hold at most $nW(60)$ tokens and $60n$ turns and do not affect rates. Hence $u_n = \mu(n)E[W] - \rho_n$. With caching disabled nothing is reused, so the same count gives $C = \lambda_{\text{miss}}E[W]$. So $\mu(n) = (u_n + \rho_n)/E[W]$, and (A3) gives $\limsup_{n\to\infty} \mu(n) \le C/E[W] = \lambda_{\text{miss}}$. The hit fraction is the rate of hits over the rate of turns, so it is at most $2\rho_n/(L_0\,\mu(n)E[T])$ and tends to 0 whenever $\liminf_{n\to\infty} \mu(n) > 0$. Under (A4), $\mu(n) \to \lambda_{\text{miss}} > 0$. □

Scope of Proposition 6. The proof's last step, from vanishing reuse to λ_{miss}, is the bound that MISA-T notes at prefill saturation, a request rate of at most the prefill throughput over the mean uncached prompt tokens per request [51]; what the proposition adds is that request-level FCFS makes reuse vanish in congestion whatever the online eviction rule. (A2) describes an admission pass that stops at the first request that does not fit, as in our simulators and, on our reading of their sources, in SGLang and vLLM under their default FCFS policies (Appendix P); vLLM also preempts running requests and returns them to the head of its queue, which (A2) allows, because its ordering clause concerns first admissions; with asynchronous scheduling it also lets a follow-up pass a bounded number of just-preempted requests, so it meets the general condition of (A2) with $Q_0 = 0$ and a bounded S_0 (Appendix P). A diverging mean cycle time would not be enough: Lemma 4 uses bounded admissions and i.i.d. tool times to bound the tail of the number of sessions in tool calls independently of n, which makes it rare that almost all sessions are in tool calls when one returns. The lemma's bound is of order $1/n$ but has large constants, so the proposition describes the limit, not the populations we ran. The lemma needs FCFS order only while more than Q_0 requests wait, so, on our reading of its source, the proposition also covers SGLang's stock LPM, which stops re-sorting its queue whenever more than 128 requests wait, so that new requests queue behind all waiting ones ($Q_0 = 128$). It does not cover program-level FCFS, which puts an old session's follow-up ahead of newer sessions' requests however long the queue: in our earlier simulator its hit fraction stays near 0.03 from $n = 64$ to 300, while FCFS has none. A pure resident-first order, such as LPM without the fallback, violates (A2) outright: a returning session whose KV is still resident is admitted ahead of the queue.

(A1) holds for our random-token sessions, apart from rare one-token coincidences (5 of the 19,924 first turns in E2 had one cached token), but not for agents that share a system prompt: one resident copy then serves every session. We expect the argument to apply to the private suffixes, with λ_{miss} and C measured with the shared prefix cached, but have not shown this. (A1) also rules out offloading evicted KV to host memory, which would let a follow-up reuse tokens that held no pool space while it waited. (A3) and (A4) hold on our engines only approximately: with zero hits, closed runs and the registered BURST runs computed prompt tokens at 0.95–1.12 times the cache-disabled rate C, and at 1.03 times it near the stationary turn mix, so under (A4) the proposition puts μ_∞ about 2–5% above λ_{ref}, within the standard error of λ_{ref} (Appendix P gives the measurements).

The bound holds for every online eviction rule, including protection of queued prefixes and TTL pins that keep request-level FCFS order, where (A4) can fail; in our earlier simulator both still hit 10–23% of turns at $n = 300$, so a finite-n hit fraction does not by itself separate covered orders from uncovered ones (Appendix P). Belady's offline rule [7] foresees tool times and is outside (A1): the token-time step of the proof covers it, Lemma 4 does not.

Checks of (A3) and (A4) on our engines. (A3) and (A4) treat the engine as a server of prompt tokens, as E0a suggests (§G.1). They concern long-run rates of the closed system, in which every order serves turns in the stationary mix, since each completed session contributes all its turns; our measurement windows did not have that mix, and the token rate varied between them, so we can check (A3) and (A4) only approximately. We estimate C by E0a's uncached token rate at 32 sessions, 11,243 tokens/s. With zero hits, closed runs computed prompt tokens at 1.03 C at $n = 96$, whose served prompts were within 3% of the stationary mean, on SGLang and on vLLM (against vLLM's own C), at 0.99 C at $n = 48$ (prompts 12–14% longer) and at 1.10–1.11 C at $n = 300$ (28–30% shorter); the registered SGLang BURST runs computed 1.01–1.03 C at 300k (prompts 9–20% shorter) and 1.07–1.12 times the 32-session all-miss rate of the native pool (prompts 29–41% shorter). So on our engine (A3) and (A4) hold only approximately: to within a few percent at the stationary mix, and to within 12% over the windows we measured. We estimate λ_{miss} by λ_{ref}, E0a's turns-based rate at 32 sessions (0.0715 sessions/s); λ_{ref} and $C/E[W]$ estimate the same cache-disabled limit. $C/E[W]$ is 0.0728 sessions/s, 1.7% above λ_{ref}, because the turns in E0a's window were longer than the stationary mix (10,648 against 10,469 prompt tokens on average). E0a's 64-session check computed 1.7% more tokens per second than the 32-session runs and 3.2% more than the same seed at 32 sessions, although its window held longer turns (11,456 prompt tokens on average), so

the 32-session reference falls short of saturation by about 2–3%, perhaps more. With the 64-session rate in place of C, $C/E[W]$ is 1.034 λ_{ref}, and with the zero-hit rate at $n = 96$ (11,602 tokens/s) it is 1.050 λ_{ref}. Under (A4) the proposition therefore puts μ_∞ about 2–5% above λ_{ref}, an offset within the standard error of λ_{ref} over seeds (0.0038 sessions/s, 5%); on vLLM the three estimates are 1.020, 1.038 and 1.050 λ_{ref} ($\lambda_{\text{ref}} = 0.0657$ sessions/s).

Covered orders at finite n. In our earlier simulator, under FCFS order, a hard pin of queued prefixes gives 0.919 λ_{miss} at $n = 300$ (§T.2) but 1.04–1.15 λ_{miss} at $n = 48$–150 (3 seeds), as a limit statement allows, and TTL pins of 5–20 s, which that simulator keeps past expiry while the session's next request waits, give 0.10–0.29 λ_{miss} at $n = 300$ with the earlier release rule of §T.2, with the GPU busy only 8–33% of the time (3 seeds). Both still hit 13% and 10–23% of turns at $n = 300$, so a finite-n hit fraction does not by itself separate covered orders from uncovered ones. The proposition makes their hit rate vanish as n grows, and their hit fraction too unless their throughput tends to 0, as the TTL pins' may; the hard pin keeps the GPU busy, and its hit fraction falls from 0.23 at $n = 48$ to 0.13 at $n = 300$. The TTL rows of §T.2 that exceed λ_{miss} also serve pinned programs first, an order that (A2) excludes.

Other orders. The proof uses the order only through Lemma 4, so it holds for any order that meets the condition above for some Q_0 and S_0. In SGLang 0.5.22 the admission loop walks the waiting queue in order and stops at the first request that cannot be added or when the batch is full (`python/sglang/srt/managers/scheduler.py`, lines 4080–4176 at tag v0.5.22); it skips a request only for LoRA, pooling-mode or storage-prefetch conditions that our runs do not use. New requests join the queue at its tail (line 3366), as would a retracted request (lines 4369–4416). FCFS sorts the queue only under priority scheduling, which none of our runs enabled (`python/sglang/srt/managers/schedule_policy.py`, lines 227–231), and LPM sorts it only while at most 128 requests wait (lines 133 and 300–311); with more waiting, LPM takes the FCFS branch, which leaves the queue's order unchanged (lines 260–261), so new requests queue behind all waiting ones. So FCFS meets the condition with $Q_0 = S_0 = 0$ and stock LPM with $Q_0 = 128$ and $S_0 = 0$. vLLM 0.32.0 admits from the head of its FCFS queue and stops at the first request whose allocation fails (`vllm/v1/core/sched/scheduler.py`, lines 1275–1282 at tag v0.32.0), and new requests join at the tail (`vllm/v1/core/sched/request_queue.py`, lines 75–94). It also preempts the most recently admitted running request when a running request cannot get a block (`vllm/v1/core/sched/scheduler.py`, lines 794–844), frees its blocks and returns it to the head of the queue (lines 1571–1613). The condition concerns first admissions, so this re-admission ahead of earlier requests does not violate it, and the re-admissions count among the admissions that (A2) bounds. With asynchronous scheduling, vLLM also skips a preempted request until its output still in flight drains, within the pipeline depth (lines 933–939), and a follow-up admitted meanwhile passes it; only requests preempted in the last few steps are skipped this way, at most a fixed multiple of the running limit, so S_0 stays bounded. vLLM also skips requests that are blocked, for example waiting for a KV transfer or over a LoRA limit, which our runs do not involve. Its FCFS thus meets the condition with $Q_0 = 0$ and a bounded S_0. The line numbers refer to the files at these tags, read verbatim, not through the page summariser of Appendix O. Program-level FCFS meets the condition for no Q_0 and S_0: a follow-up of an old session is admitted before requests of newer sessions that were waiting when it joined, however long the queue.

Engine sources of §D. The SGLang rules of §D (default policy and eviction rule, the 128-request LPM fallback, the unlocked prefix of a waiting request, and the refresh of waiting prefixes) are in these files under `python/sglang/srt/` at tag v0.5.22: `arg_groups/fields/schedule.py`, lines 82–98; `arg_groups/fields/memory.py`, lines 25–42; `managers/schedule_policy.py`, lines 133–135, 278–311 and 1591; `mem_cache/radix_cache.py`, lines 552–580; and `environ.py`, line 594. vLLM 0.32.0 schedules FCFS, its default, or by priority (`vllm/config/scheduler.py`, lines 21 and 159), and a freed cached block keeps its hash until it is reallocated (`vllm/v1/core/block_pool.py`, lines 666–690 and 774–803; at tag v0.32.0). We first read these sources through a web tool that returns a language model's summary of each file (Appendix O); the line references here and above are to the files at the tags, read verbatim.

The quasi-static model in congestion. Eq. (2) assumes that the internal state (turn-index mix, cache contents, queue order) relaxes quickly compared with changes in n. An automated check of the model by an LLM agent (Appendix O) found this reasonable at fixed points and for the sign of the drift in deep congestion, where the stationary μ is flat, but not near the cliff. The model is also not quantitative in congestion, and not only transiently: over the evaluation window the registered SGLang BURST runs still completed 1.13–1.35 λ_{ref} at 300k and 1.44–2.03 times the native λ_{ref}, and their fitted backlog slopes were only 18–69% and 68–78% of the rate $\lambda - \lambda_{\text{miss}}$ that Eq. (2) gives with μ at its congested value λ_{miss}, taking λ as the arrival rate each run received and λ_{miss} as λ_{ref}, or 21–75% and 70–80% with λ_{miss} 3.4% above λ_{ref} (§G.2, §G.2 and the checks of (A3) and (A4) above). Under FCFS each waiting session advances one turn per cycle of the queue while new sessions keep arriving, so the backlog stays young and its turns are short (in the BURST windows served prompts were 9–20% and 29–41% below the stationary mean; checks of (A3) and (A4) above). At a token rate near the all-miss rate the engine then serves more turns per second than in the stationary mix, and since a session ends after each turn with probability 1/15 until its 60th, it also completes sessions faster than λ_{miss}, for as long as the backlog grows. Theorems 1 and 2 (§2) make this exact within model F: the backlog grows at $\alpha = \lambda(1 - E[z^{-T}])$ and sessions complete at $D = \lambda E[z^{-T}] > \lambda_{\text{miss}}$, with the turn

mix tilted to $G_k z^{-k}$, and the premium does not fade while the trap lasts.

A work balance, which this paragraph does not make rigorous for the open system (Corollary 3 does, within model F), suggests that the recovery threshold depends on the token rate in congestion, not on the departure rate. If hits vanish in congestion (as in every registered SGLang BURST run) and the engine computes prompt tokens at about $C = \lambda_{\text{miss}} E[W]$ (Proposition 6) while they arrive at $\lambda E[W]$, then for $\lambda > \lambda_{\text{miss}}$ the uncomputed prompt work of the sessions in the system grows, and eventually so does their number, since each holds at most $W(60)$ tokens of it, while for $\lambda < \lambda_{\text{miss}}$ that work shrinks as long as the engine computes at C. If the zero-hit token rate is lower at some population that the system passes through on the way down, the threshold is correspondingly lower; in the fluid model it is $\inf_{n \geq n^*} \mu(n)$ rather than μ_∞. On our engine the closed runs' zero-hit token rate was 4% lower at $n = 48$ than at $n = 96$, with older turns (checks of (A3) and (A4) above). We therefore use Eq. (2) for the window, as a long-run statement for the recovery threshold, and for the capped system's drain time (§E.4), not for burst sizes or backlog growth in congestion: in an earlier simulator with assumed costs (§F.4) the fluid critical burst $n_2 - n_1$ at $2\lambda_{\text{miss}}$ was 20.5 sessions against an empirical 40, because burst sessions are fresh and small. The heuristic H3 of §H corrects for this by counting a burst session at its peak footprint: at 1.65 λ_{ref} on the 300k pool its critical fresh burst is 53.4 sessions, against 21.3 for the stationary-composition estimate $n_2 - n_1$, and the registered basin tests of §I test it.

A non-monotone tail, and Bronson et al.'s terms. Without the monotone tail, the recovery threshold from deep congestion is $\inf_{n \geq n^*} \mu(n)$ instead, and congested fixed points can exist. Our measured curve is not monotone beyond n^*: in completed sessions it falls to 0.68 λ_{ref} at $n = 48$ and rises to 1.51 λ_{ref} at $n = 300$ (turns-based, 0.88 and 1.56 λ_{ref}; §G.1). Taken at face value, either estimate would put the recovery threshold from $n = 300$ below λ_{miss} and give a stable congested fixed point at 1.35 λ_{ref}. We attribute both features to the synchronized start, which no longer run has tested, and take μ_∞ from Proposition 6. In the terms of Bronson et al. [11], μ_∞ is the hidden capacity, the load up to which the system heals itself after any trigger, and $\min(\mu^*, \lambda_e)$ the advertised capacity; at loads in $\mathcal{W}$ the good state is their vulnerable state, a burst is a trigger whose intensity matters, the congested regime is the metastable failure state, and the feedback of §D, in which misses lengthen the queue and the gap between a session's turns, is its sustaining effect.

The fluid statements of §E.3. With μ continuous and piecewise linear, Eq. (2) has a unique solution from every $x_0 \geq 0$; it is monotone in time, and it converges to a fixed point or diverges. Let $0 < \lambda < \mu^*$. Then $\mu(n) = \lambda$ has exactly one solution n_1 in $(0, n^*)$, because μ increases strictly from 0 to μ^* there, and, since $\lambda \neq \mu_\infty$, at most one in (n^*, ∞), because there μ is non-increasing and strictly decreasing wherever $\mu > \mu_\infty$. If $\lambda < \mu_\infty$, then $\mu \geq \mu_\infty > \lambda$ beyond n^*, so $\mu < \lambda$ on $[0, n_1)$ and $\mu > \lambda$ on (n_1, ∞), and every solution converges to n_1. If $\mu_\infty < \lambda$, the second solution n_2 exists, because $\mu(n^*) > \lambda$ and $\mu \to \mu_\infty < \lambda$; then $\mu > \lambda$ on (n_1, n_2) and $\mu < \lambda$ on (n_2, ∞), so n_2 is unstable, and for $x_0 > n_2$, $\dot{n} \geq \lambda - \mu(x_0) > 0$ along the solution and $n \to \infty$. If $\lambda > \mu^*$, then $\mu < \lambda$ everywhere and every solution diverges. A solution from $x_0 > n_1$ converges to n_1 if and only if $\mu > \lambda$ on all of $(n_1, x_0]$: if so, it decreases and stays in $(n_1, x_0]$, where n_1 is the only possible limit; if $\mu(x) \leq \lambda$ for some $x \in (n_1, x_0]$, it never falls below x, where the drift is non-negative. For $x_0 > n^*$, $\mu > \lambda$ on $(n_1, n^*]$ and the minimum of μ on $[n^*, x_0]$ is $\mu(x_0)$, so the condition is $\lambda < \mu(x_0)$, and $\mu(x_0)$ does not increase and tends to μ_∞ as $x_0 \to \infty$. Without the monotone tail the same argument gives the condition $\lambda < \min_{[n^*, x_0]} \mu$, which tends to $\inf_{n \geq n^*} \mu(n)$, and a point beyond n^* where μ crosses λ from below is a stable congested fixed point. Under the assumptions of Proposition 6 this infimum is at most $\liminf_{n \to \infty} \mu(n) \leq \lambda_{\text{miss}}$, and it equals λ_{miss} if, in addition, $\mu(n) \geq \lambda_{\text{miss}}$ for every $n \geq n^*$.

Proof of Corollary 5. While $N \geq c$ the admitted sessions form a closed system of c sessions (Proposition 1), so $\dot{N} = \lambda - \mu(c)$ and the gate, $N - c$, shrinks if and only if $\mu(c) > \lambda$. By unimodality $\mu > \lambda$ exactly on (n_1, n_2), so the gate empties, from any initial population $N_0 > c$, if and only if $n_1 < c < n_2$; if $c \leq n_1$ or $c \geq n_2$, then $\mu(c) \leq \lambda$ and it never empties. Once $N < c$ the cap does not bind, $\dot{N} = \lambda - \mu(N)$ with $N < c < n_2$, and by the statements above N stays in $[0, n_2)$ and converges to $n_1 < c$, so the cap never binds again and removing it changes nothing. This is the standard closed-system equivalence of a system with a bounded multiprogramming level (§D). If the closed curve itself folds (Proposition 7), μ is multivalued on a band of populations and we take n_2 on the good branch; a cap $c \geq n_b$ engaged inside the trap keeps the all-miss state, which exists at every $n \geq n_b$, so $n_1 < c < \min(n_2, n_b)$ is necessary, and we have not shown that it is sufficient. The stochastic counterpart (positive recurrence for $\lambda < \mu(c)$) should follow from standard arguments; we have not written them out.

Q First-principles model: details and proofs

Cost model and server. The prefill GPU time of x new tokens on a cached prefix of y tokens is $t_P(x, y) = a \max(1, x/B_c) + \max(f_0, bx) + c_p\, x\, (y + (x+1)/2)$, with $a = 9.24\,\text{ms}$, $f_0 = 1.26\,\text{ms}$, $b = 62.6\,\mu\text{s/token}$, $c_p = 2.24\,\text{ns}$ per causal pair and chunk $B_c = 8192$ (`calibration/round6_server_log_fit/calibration.yaml`). For a miss, $t_k^m = t_P(L_k, 0)$; for a hit, $t_k^h = t_P(551, L_k - 551)$; turn 1 always misses. The mean prefill time per turn is $\bar{t}_P(h) = \sum_k w_k t_k(h)$, so $p = \nu \bar{t}_P(h)$ and $\partial_h \bar{t}_P = -\beta_P$, with $\beta_P = \sum_{k \geq 2} w_k (t_k^m - t_k^h)$; we also write $\beta_E = \sum_{k \geq 2} w_k E_k (t_k^m - t_k^h)$ and $\xi = \nu\, \partial_\nu S_D$. A decode iteration over R_D requests takes $\tau_D(R_D) = a + \max(f_0, bR_D) + b_{\text{att}} R_D$, with $b_{\text{att}} = c_d \bar{y}_D / 8192$, $c_d = 0.31\,\text{ms}$ and $\bar{y}_D$ the mean decode context. We assume: (S1) a turn's prefill latency is

its own prefill GPU time, with no queueing behind other prefills; (S2) the GPU is busy whenever a request runs; (S3) a running request reserves E_k from admission to completion, with no retraction; (S4) admission is first-come-first-served, work-conserving and memory-gated: a request waits only if admitting it would make the running reservations exceed M (idle KV is always evictable), and the engine's limit of 256 running requests and, on SGLang, the prefill chunk budget never bind. For vLLM, prefill and decode share iterations: $S_D = (d-1)/r_{\text{it}}$, with iteration rate $r_{\text{it}} = (1-\nu c_{\text{turn}})/a$, where $c_{\text{turn}} = b\bar{x} + c_p\bar{\pi} + (b + b_{\text{att}})(d-1)$ is the token-proportional GPU time of a turn ($\bar{x}$ and $\bar{\pi}$ are the mean prefilled tokens and causal pairs per turn), as long as an iteration's tokens fit its chunk budget. Lemmas 5 and 6, and the results that use them, Proposition 2(a) and (c), Proposition 3(b)–(c) and Proposition 7, are for the separate-iteration (SGLang) server; for vLLM, n_b follows from the identity of Proposition 2(b) whenever the mixed server's ν_b exists, that is, while the chunk budget does not bind. The queue classification and the identification of n_b as an onset also use the additional fluid closure (S5) below.

No-slack fluid admission. In addition to (S1)–(S4), we impose (S5): in a stationary fluid state, the queued population $Q \geq 0$ and running reservation $K_{\text{run}} \leq M$ satisfy $Q(M - K_{\text{run}}) = 0$. The population balance is $n = \nu(\bar{S} + \bar{z}') + Q$, with $Q = \nu W_Q$. This is an idealized divisible-fluid, no-packing-slack closure; it does not follow from (S4) for indivisible requests and is not an assertion about either engine. For example, a pool of 10 units can have 6 reserved and a head request requiring 5 waiting, even though 4 units remain. More generally, at an atomic admission blockage with head reservation E_{head}, (S4) gives only $0 \leq M - K_{\text{run}} < E_{\text{head}}$, not equality to zero. We retain (S5) to specify the model whose onset and stationary branches are analyzed here; Appendix P's request-level FCFS congestion bound does not require it.

Lemma 5 (fluid server)**.** *Fix h, and let $\nu_{\text{cap}}(h) = 1/(\bar{t}_P(h) + (d-1)(b + b_{\text{att}}))$. For $0 < \nu < \nu_{\text{cap}}(h)$ the decode equation has exactly one positive root; for $\nu \geq \nu_{\text{cap}}(h)$ it has none. S_D is continuous, strictly increasing in ν, non-increasing in h, and $S_D \to \infty$ as $\nu \uparrow \nu_{\text{cap}}(h)$. At $\nu = 0$ the decode root is $R_D = 0$ and S_D is defined by its continuous limit $(d-1)\tau_D(0)$. For $\nu > 0$, $K_{\text{run}}(\nu, h)$ increases strictly in ν from 0 to ∞ and decreases strictly in h.*

Proof. For $\nu > 0$, if $p = \nu\bar{t}_P(h) \geq 1$, the left side of the original decode equation $R_D(1-p) = \nu(d-1)\tau_D(R_D)$ is nonpositive while its right side is positive, so no positive root exists. For $p < 1$, define $\psi(R) = R/\tau_D(R)$; it is continuous and strictly increasing, since τ_D is affine with positive intercept on each side of the kink f_0/b. Moreover $\psi(0) = 0$ and $\psi(\infty) = 1/(b + b_{\text{att}})$. The decode equation reads $\psi(R_D) = \nu(d-1)/(1-p)$, which has a unique root if and only if the right side is below $1/(b + b_{\text{att}})$, that is, $\nu < \nu_{\text{cap}}(h)$. The right side increases in ν and does not increase in h, because $t_k^h \leq t_k^m$; so does R_D, which diverges at ν_{cap}. Then $S_D = R_D/\nu = (d-1)\tau_D(R_D)/(1-p)$ is a product of positive factors with the same monotonicity. $K_{\text{run}} = \nu \sum_k w_k E_k (t_k(h) + S_D)$ inherits it; strict decrease in h follows from $\partial_h K_{\text{run}} = -\nu(\beta_E + \bar{E}\chi\xi) < 0$ (Lemma 6). □

Lemma 6 (decode sensitivity)**.** *Away from the kink, $-\partial_h S_D = \chi\, \nu\partial_\nu S_D$, with $\chi = \beta_P/(\bar{t}_P(h) + (d-1)\tau_D'(R_D))$ and $\nu\partial_\nu S_D = R_D(\bar{t}_P + (d-1)\tau_D')/J > 0$, where $J = (1-p) - \nu(d-1)\tau_D' > 0$.*

Proof. Write $G(R_D, \nu, h) = R_D(1 - \nu\bar{t}_P(h)) - \nu(d-1)\tau_D(R_D)$. Then $\partial_{R_D} G = J$; at the root, $J = (1-p)\alpha_D/\tau_D > 0$, with $\alpha_D > 0$ the intercept of the affine piece of τ_D. Next, $\partial_\nu G = -R_D\bar{t}_P - (d-1)\tau_D$ and $\partial_h G = \nu R_D \beta_P$, since $\partial_h \bar{t}_P = -\beta_P$. Hence $\partial_h S_D = \partial_h R_D/\nu = -R_D\beta_P/J$ and $\nu\partial_\nu S_D = \partial_\nu R_D - R_D/\nu = [R_D\bar{t}_P + (d-1)\tau_D - JR_D/\nu]/J$. Substituting $JR_D/\nu = R_D/\nu - R_D\bar{t}_P - R_D(d-1)\tau_D'$ and $R_D/\nu = (d-1)\tau_D/(1-p)$ gives $(d-1)\tau_D - R_D/\nu = -pR_D/\nu = -\bar{t}_P R_D$, so the numerator equals $R_D(\bar{t}_P + (d-1)\tau_D')$. □

Proof of Proposition 2. (a) Fix $R > 0$ and $h = F_Z(R)$. The function $\nu \mapsto K_{\text{run}}(\nu, h) + \nu\mathcal{D}(R)/E[T] - M$ is continuous and strictly increasing (Lemma 5). It equals $-M$ at $\nu = 0$ and is unbounded at ν_{cap}, so it has exactly one root $\nu(R)$, which is continuous in R. By (S5), a state with $Q > 0$ has $K_{\text{run}} = M$, so $\mu\mathcal{D} = 0$, hence $R = 0$, $h = 0$ and $\nu = \nu_b$. From $\nu\mathcal{D}(R)/E[T] \leq M$ and $\mathcal{D}(R) \geq E[E_T]R$ we get $\nu(R) \to 0$ as $R \to \infty$. As $R \downarrow 0$, $\nu(R) \to \nu_b$ by continuity, since $\nu_{\text{cap}}(0)$ is excluded. As $R \to \infty$, $h \to 1$, the prefill times remain bounded and $S_D \to (d-1)\tau_D(0)$, so $n(R) = \nu(R)(\bar{S} + \bar{z}') \to 0$. Thus $n(R)$ is bounded on $(0, \infty)$, and beyond its supremum and n_b only the all-miss state remains. (b) $K_{\text{run}}(\nu_b, 0) = \nu_b \sum_k w_k E_k S_k = M$ gives $\nu_b \bar{S} = M/E_S$; Little's law with no queue gives $n_b = \nu_b \bar{S} + \nu_b \bar{z}'$. For $n \geq n_b$ the remaining population is $Q = n - n_b$, which is nonnegative exactly on this range. Its mean admission wait is $W_Q = Q/\nu_b = (n - n_b)/\nu_b$ seconds; these values satisfy (S5) and the population balance. No all-miss state with $K_{\text{run}} = M$ is possible below n_b. (c) Divide every cost by s and time by s: every service time scales by $1/s$ and every rate by s, and the decode equation and p are invariant. So (ν, h) solves $K_{\text{run}} = M$ for costs C if and only if $(s\nu, h)$ does for C/s. Hence $\nu_b(s) = s\nu_b(1)$; E_S, a ratio of S-weighted sums, is invariant; substitute into (b). □

Proof of Proposition 3. (a) Rescaling time by s maps a stationary state (n, ν, h, R) of $(C/s, \bar{z})$ to $(n, \nu/s, h, sR)$ of $(C, s\bar{z})$. Each equation of Eq. (4) is invariant: Little's law and K_{run} are rate×time, $E[\min(\bar{z}Y, R)] = s^{-1}E[\min(s\bar{z}Y, sR)]$, and h compares times. Both μ^* and μ_b scale by s, so their ratio depends on $s\bar{z}$ only. (b) Parametrize the queue-free states by $R \in (0, \infty)$, with $h = F_Y(R/\bar{z})$. The balance reads $K_{\text{run}}(\nu, F_Y(R/\bar{z})) + \nu(A_1 E[\min(\bar{z}Y, R)] + E[E_T]R)/E[T] = M$. Its left side increases strictly in ν (Lemma 5) and does not decrease in $\bar{z}$, since h falls, K_{run} decreases in h and $E[\min(\bar{z}Y, R)]$ rises; where $h > 0$ it increases strictly in $\bar{z}$, because then $E[\min(\bar{z}Y, R)]$ does. So $\nu(R; \bar{z})$ does not increase in $\bar{z}$, while ν_b (the equation at $h = 0$) does not involve $\bar{z}$, and taking the supremum over R, ω_b is non-increasing in

$\bar{z}$. For strictness, let $\bar{z}_1 < \bar{z}_2$ and $\omega_b > 1$ at $\bar{z}_2$. Since Z has a density, $\nu(R;\bar{z})$ is continuous in R, and by the proof of Proposition 2(a) it tends to ν_b as $R \downarrow 0$ and to 0 as $R \to \infty$. So $\sup_R \nu(R;\bar{z}_2) > \nu_b$ is attained at some $R_2 \in (0,\infty)$, where $h > 0$, because a state with $h = 0$ and $R > 0$ has $K_{\text{run}}(\nu, 0) < M$ and so $\nu < \nu_b$. Hence $\sup_R \nu(R;\bar{z}_2) = \nu(R_2;\bar{z}_2) < \nu(R_2;\bar{z}_1) \le \sup_R \nu(R;\bar{z}_1)$. This holds for any Y with a density, bounded or not and whether or not F_Y has flat parts. Apply (a) for s. (c) Fix $h_0 \in (0,1)$ and let $\widehat{\nu}(h_0)$ be the unique root of $K_{\text{run}}(\nu, h_0) = M$. On any queue-free state with $h \le h_0$, monotonicity gives $K_{\text{run}}(\nu, h_0) \le K_{\text{run}}(\nu, h) \le M$, hence $\nu \le \widehat{\nu}(h_0)$. Since $F_Y(0) = 0$ and F_Y is continuous, choose $r_0 > 0$ with $F_Y(r_0) < h_0$. A state with $h > h_0$ has $R > \bar{z} r_0$, so the memory balance and $\mathcal{D}(R) \ge E[E_T]R$ imply

$$\nu \le \frac{ME[T]}{E[E_T]\,\bar{z} r_0}.$$

Consequently

$$1 \le \omega_b(\bar{z}) \le \max\left\{\frac{\widehat{\nu}(h_0)}{\nu_b}, \frac{ME[T]}{\nu_b E[E_T]\,\bar{z} r_0}\right\}.$$

First let $\bar{z} \to \infty$ and then $h_0 \downarrow 0$. Continuity of the root gives $\widehat{\nu}(h_0) \to \nu_b$, proving the limit without assuming that F_Y is invertible. □

The feedback map and the fold identity. For a closed population n define the *feedback map* Φ_n. At hit probability h, Little's law with no queue, $n = \nu(\bar{S}(\nu, h) + \bar{z}')$, gives a unique turn rate $\nu(h)$; then $\Phi_n(h) = 0$ if $K_{\text{run}}(\nu(h), h) \ge M$, and otherwise $\Phi_n(h) = F_Z(R)$, with R the solution of $(\nu(h)/E[T])\,\mathcal{D}(R) = M - K_{\text{run}}(\nu(h), h)$. The fixed points of Φ_n correspond one-to-one to the stationary states at population n: a fixed point $h > 0$ is a queue-free state, and for $n \ge n_b$ the fixed point $h = 0$ stands for the all-miss state, which has $\nu = \nu_b$ and a queue wait of $(n - n_b)/\nu_b$ seconds (Proposition 2(b)); for $n > n_b$, where Φ_n is memory-gated at $h = 0$, its rate ν_b differs from the queue-free rate $\nu(0) > \nu_b$ at which the map is evaluated there. If F_Z vanishes on an initial interval, an $h = 0$ fixed point below n_b can instead be a queue-free zero-hit state with $R > 0$, as noted after Proposition 2. We call a fixed point *locally stable* if it is stable under the relaxation $\dot{h} = \eta(\Phi_n(h) - h)$, $\eta > 0$, at fixed n; this is an auxiliary dynamics, since Eq. (2) has none in h at fixed n, and "stable" for a state of the closed system means stable in this sense.

Proposition 7 (fold identity and relaxation stability)**.** *Assume that f is continuous on $(0,\infty)$; for part (a), also assume the indicated one-sided limits at zero exist. On the queue-free branch parametrized by R, away from any crossing of the decode-cost kink $R_D = f_0/b$, with $\xi = \nu\,\partial_\nu S_D \ge 0$ (at a kink interpret the identity one-sidedly),*

$$\frac{dn}{dR} = \frac{\nu}{\Gamma_\nu}\Big[f(R)\,I(R) - \frac{n_\nu\,\mathcal{D}'(R)}{E[T]}\Big],$$

where $\Gamma_\nu = S_E + \bar{E}\xi + \mathcal{D}/E[T] > 0$, $n_\nu = \bar{S} + \bar{z}' + \xi$, $S_E = \sum_k w_k E_k S_k = K_{\text{run}}/\nu$ (so that E_S of Proposition 2 is $S_E/\bar{S}$ at $(\nu_b, 0)$), and $I = \xi[C_E + \chi(\bar{E}(\bar{S} + \bar{z}') - S_E - \mathcal{D}/E[T])] + \beta_E(\bar{S} + \bar{z}') - \beta_P(S_E + \mathcal{D}/E[T])$, with $\beta_P = \sum_{k\ge2} w_k(t_k^m - t_k^h)$, $\beta_E = \sum_{k\ge2} w_k E_k(t_k^m - t_k^h)$, $C_E = \beta_E - \bar{E}\beta_P$ and $\chi = \beta_P/(\bar{t}_P(h) + (d-1)\tau_D'(R_D))$. Consequently: (a) if $f(0^+)I(0^+) > n_\nu \bar{E}$ at the all-miss end, then $n(R) > n_b$ for small R, and the closed system has at least three stationary states for $n \in (n_b, n_{\text{fold}})$, $n_{\text{fold}} = \max_R n(R)$: the all-miss state, which is locally stable under this relaxation, and two queue-free states. (b) If the bracket is negative for every $R > 0$, with negative one-sided values at each kink, then $n(R)$ is strictly decreasing, every $n > 0$ has exactly one stationary state, and $\mu(n)$ is continuous, extending to $\mu(0) = 0$. (c) At an interior queue-free fixed point $0 < h < 1$, away from a decode-cost kink, the auxiliary relaxation is locally exponentially asymptotically stable if $dn/dR < 0$ and unstable if $dn/dR > 0$. If $dn/dR = 0$, linearization is inconclusive. These are statements about the relaxation of h at fixed n, not about the engine dynamics.

Proof of Proposition 7. We work away from crossings of the decode-cost kink, where Lemma 6 applies; at each kink the same calculation uses one-sided derivatives. On the branch, $\Gamma(\nu, R) = \nu S_E(\nu, h) + \nu\mathcal{D}(R)/E[T] - M = 0$ and $n = \nu(\bar{S} + \bar{z}')$, with $h = F_Z(R)$ and $dh/dR = f(R)$. From $S_k = t_k(h) + S_D(\nu, h)$ we have $\partial_h \bar{S} = -\beta_P + \partial_h S_D$, $\partial_h S_E = -\beta_E + \bar{E}\partial_h S_D$, $\partial_\nu \bar{S} = \partial_\nu S_D$ and $\partial_\nu S_E = \bar{E}\partial_\nu S_D$. By Lemma 6, $\partial_h S_D = -\chi\xi$ with $\xi = \nu\partial_\nu S_D$. Then $\Gamma_\nu = \partial_\nu \Gamma = S_E + \bar{E}\xi + \mathcal{D}/E[T] > 0$ and $\partial_R \Gamma = -\nu f(\beta_E + \bar{E}\chi\xi) + \nu\mathcal{D}'/E[T]$, so

$$\frac{d\nu}{dR} = \frac{\nu}{\Gamma_\nu}\Big[f(\beta_E + \bar{E}\chi\xi) - \frac{\mathcal{D}'}{E[T]}\Big].$$

Next, $dn/dR = n_\nu\, d\nu/dR + \nu f\,\partial_h \bar{S} = n_\nu\, d\nu/dR - \nu f(\beta_P + \chi\xi)$, with $n_\nu = \bar{S} + \bar{z}' + \xi$. Put both over Γ_ν: the coefficient of $\nu f/\Gamma_\nu$ is $I = n_\nu(\beta_E + \bar{E}\chi\xi) - (\beta_P + \chi\xi)\Gamma_\nu$. Expanding, the terms $\bar{E}\chi\xi^2$ cancel. Collecting the terms linear in ξ gives $\xi[\beta_E - \bar{E}\beta_P + \chi(\bar{E}(\bar{S}+\bar{z}') - S_E - \mathcal{D}/E[T])]$, and the remainder is $\beta_E(\bar{S} + \bar{z}') - \beta_P(S_E + \mathcal{D}/E[T])$. This is the stated I. The term in $\mathcal{D}'$ is $-n_\nu\mathcal{D}'/E[T]$. (a) As $R \to 0^+$, $n(R) \to n_b$ (Proposition 2), $\mathcal{D} \to 0$ and $\mathcal{D}'(0^+) = A_1 + E[E_T] = E[T]\bar{E}$. If the bracket is positive at 0^+, then by continuity n increases on some $(0, \delta)$. Since $n(R) \to 0$ as $R \to \infty$, n attains a maximum $n_{\text{fold}} > n_b$, and by the intermediate value theorem every $n \in (n_b, n_{\text{fold}})$ is reached on both sides of the maximizer. Together with the all-miss state this gives at least three stationary states. For fixed $n > n_b$, the no-queue Little law at $h = 0$ has a rate $\nu_0 > \nu_b$, because $\nu(\bar{S}(\nu, 0) + \bar{z}')$ is strictly increasing in ν. Thus $K_{\text{run}}(\nu_0, 0) > M$. The no-queue rate at fixed n depends continuously on h, as does K_{run}, so some $\delta > 0$ has $K_{\text{run}}(\nu(h), h) > M$ for $0 \le h < \delta$. On this interval $\Phi_n(h) = 0$ and the relaxation is exactly $\dot{h} = -\eta h$. The all-miss state is therefore locally exponentially asymptotically stable from the physical side $h \ge 0$. (b) The branch is continuous and locally absolutely continuous by the implicit memory equation, $\Gamma_\nu > 0$ and the locally Lipschitz server cost. Under the stated sign condition it is strictly decreasing. Its endpoint limits are n_b and zero, so it is a bijection from $(0,\infty)$ onto $(0, n_b)$. There is exactly one queue-free state for $0 < n < n_b$

and only the memory-gated state for $n \geq n_b$. Throughputs join continuously at n_b since $\nu(R) \to \nu_b$ as $R \downarrow 0$, and extend to zero at $n = 0$.

(c) Write $\nu(n, h)$ for the no-queue rate used to evaluate the feedback map and $\mathcal{R}(n, h) > 0$ for its idle-age solution. At a queue-free fixed point, differentiation of $n = \nu(\bar{S}(\nu, h) + \bar{z}')$ gives

$$\partial_n \nu = \frac{1}{n_\nu}, \qquad \partial_h \nu = \frac{\nu(\beta_P + \chi\xi)}{n_\nu}.$$

Differentiating $\nu S_E(\nu, h) + \nu \mathcal{D}(\mathcal{R})/E[T] = M$ then gives

$$\partial_n \Phi_n(h) = -\frac{f(R)E[T]\Gamma_\nu}{\nu n_\nu \mathcal{D}'(R)} \leq 0,$$

strictly when $f(R) > 0$, and

$$\partial_h \Phi_n(h) = \frac{f(R)E[T]I(R)}{n_\nu \mathcal{D}'(R)}.$$

Thus the branch identity is equivalently

$$\frac{dn}{dR} = \frac{\nu n_\nu \mathcal{D}'(R)}{E[T]\Gamma_\nu}\big(\partial_h \Phi_n(h) - 1\big).$$

The prefactor is positive and the scalar relaxation's linearized derivative is $\eta(\partial_h \Phi_n(h) - 1)$, proving (c). This factorization also holds when $f(R) = 0$. At a decode-cost kink the one-sided calculations apply separately: two strictly negative one-sided relaxation derivatives imply local asymptotic stability, and two strictly positive ones imply instability. Zero derivatives or opposing signs need separate analysis. *Window opening.* At $R \to 0^+$ the formula for $d\nu/dR$ has the sign of $f(0^+)\Delta_S - 1$, with $\Delta_S = (\beta_E + \bar{E}\chi\xi)/\bar{E}$. If it is positive, $\mu = \nu/E[T]$ rises above μ_b as R leaves 0. □

These conclusions concern the auxiliary fluid relaxation, not the serving engine's dynamics. The identity was also checked numerically: its closed form agrees with central finite differences of $n(R)$ within relative tolerance 2×10^{-3} at five values of R, for the exponential law and a folding mixture (`tests/test_theory_paper.py`). The reported cell-wise fold-freeness, by contrast, rests on a finite scan: $fI/(n_\nu \mathcal{D}'/E[T])$ was evaluated at 400 values of R per cell, with sign agreement against finite differences (`analysis/theory/merged/fold.py`). This does not establish negativity for every R.

The fold criterion on the predicted cells. For the registered exponential tool times the largest sampled ratio $fI/(n_\nu \mathcal{D}'/E[T])$ occurs near the all-miss end, with values 0.805 (300k), 0.826 (native), 0.784 (H200), 0.781 (Llama), 0.761 (150k) and 0.821 (600k), checked on 400 values of R per cell; over the other four H200 cost variants it is 0.67–0.78. At those sampled points every separate-iteration cell satisfies the negative-bracket criterion, with margins of 17–24% for the primary cost models and up to 33% over the H200 variants; a numerical scan of $n(R)$ also finds no fold for vLLM, to which the proposition does not apply. These finite scans are evidence for fold-freeness, not a global proof. Conditional on fold-freeness, the metastability discussed for these predicted cells is an open-system effect. The same identity at $R \to 0^+$ gives a sufficient condition for the window to open: $\mu^* > \mu_b$ if $f(0^+)\Delta_S > 1$ with $\Delta_S = (\beta_E + \bar{E}\chi\xi)/\bar{E}$ (595 s at 300k, against $1/f(0^+) = \bar{z} = 5$ s). Dispersed tool times can reverse the conclusion. With the same 5 s mean, a mixture of exponentials with means 1 s and 9 s in equal proportions (coefficient of variation 1.5) produces a computed fold at $n_{\text{fold}} = 34.2 > n_b = 32.7$; at the interior population $n = 33.5$, the all-miss state and a positive-hit state ($h = 0.69$) are both stable under the relaxation of h at fixed n (Fig. 6, Appendix Q); mixtures with coefficients of variation 2.5 and 5 fold up to 38.2 and 44.6. Measured agent tool times are also dispersed (the SWE-Bench tool times Continuum reports have a coefficient of variation of about 3.8 [69]). Part (a) is a sufficient condition at the all-miss end, set by the density near 0. A law can also fold at an interior R, where the bracket changes sign; the theory notes report this, outside the committed code, for lognormal laws with a coefficient of variation of 2 or more, which have $f(0^+) = 0$. So neither $f(0^+)$ nor the coefficient of variation alone decides it, and we have not evaluated the criterion for any measured law. When the fold is at the all-miss end, n_b is the lower edge of a band in which the closed system is bistable (in the sense of that relaxation), not the collapse point. If the bracket is negative near $R = 0$ and later changes from negative to positive, $n(R)$ first falls below n_b before reaching an interior local minimum. Multiplicity can therefore start below n_b; an interior positive bracket alone does not imply $n_{\text{fold}} > n_b$. None of our engine runs used such a law.

Proof of Proposition 5. By definition the interval's average churn is V_I/g, so $R_M = Mg/V_I$ and $g/R_M = V_I/M$. Substituting the assumed complete-turn accounting gives the final sum. The cost model affects g but cancels from the ratio. No claim about an individual prefix's eviction age is used or follows. □

Proposition 4 on the measured cells. Table 20 evaluates three exogenous-gap closures at every closed run past the measured peak of its cell (the largest $\mu(n)$ in completed sessions: $n = 24$ at 300k, 64 with the native pool, 20 on vLLM), with nothing fitted: Yao et al.'s characteristic-time equation [114] at the measured throughput (turns-based); the same equation with its rate set by Little's law with exogenous gaps and zero service time, $\lambda_0 = n/((E[T] - 1)\bar{z})$, which does not use the measured throughput and exceeds it past the peak (0.70 against 0.063 sessions/s at 300k, $n = 48$); and Che's approximation with the tool time as the gap, sessions as objects of the mean footprint $\bar{E}$ and no dead content, whose follow-up hit $\min(1, M/(n\bar{E}))$ involves no rate at all. The proposition's bound with $K_{\text{run}} = 0$ is evaluated at the measured throughput, so it bounds only the first closure; the Little and Che values can fall below it. Zero service time is the choice least favourable to hits, since it gives the largest rate, and omitting dead content is favourable to them. Every value counts first




Figure 6: Fixed points of the first-principles model. (a) Open system, predicted 300k curve at 1.65 λ_{ref}: stable good state $n_1 = 10.4$, unstable state $n_2 = 31.8$ (marked n_u), all-miss onset $n_b = 32.7$, and the trap, where Eq. (2) makes N grow at $\lambda - \mu_b$ (the round-robin layer RR of §H.3, which the model uses for the trap, predicts slower growth). (b) Closed system at $n = 33.5 > n_b$: the feedback map $\Phi_n(h)$, the hit probability produced at hit probability h. With the registered exponential tool times the all-miss state is the only fixed point. With a two-phase law of the same 5 s mean (coefficient of variation 1.5), the all-miss state and a good state ($h = 0.69$) are both stable under the relaxation $\dot{h} = \eta(\Phi_n(h) - h)$ at fixed n (filled markers), and an unstable state ($h = 0.29$) separates them. (c) The two closed curves: the dispersed law folds above n_b (shaded band, 32.7 to 34.2), as Proposition 7 predicts.

turns, so it is at most 0.932. These exponential-gap closures decay smoothly in n (Che's as $1/n$ beyond $M/\bar{E}$) and do not predict exactly zero hits at finite positive throughput; under Assumption MF and this tool law, zero stationary hit probability requires running requests to hold the whole pool. The evaluation is retrospective: it was added to the second prediction set (tag `r13-theory-pred2`) with the measured closed curves as inputs, and it predicts nothing.

The open system on the predicted curve. For $\mu_b < \lambda < \mu^*$, under Proposition 7(b) and unimodality in the sense of §E.3, $g(n) = \lambda - \mu(n)$ is positive at 0, crosses zero downward once on $[0, n^*]$ (at n_1) and upward once on $[n^*, n_b]$ (at n_2), and equals $\lambda - \mu_b > 0$ on $[n_b, \infty)$, so the fluid statements of §E.3 hold with $\mu_\infty = \mu_b$ and $n_2 \le n_b$, and from $n \ge n_b$ the solution of Eq. (2) grows linearly at $\lambda - \mu_b$; the model's trapped-state predictions do not use this statement; they come from the round-robin layer RR (§H.3). With the capped system, Corollary 5 applies; the closed fluid system of $c > 0$ sessions has a unique stationary state, which is on the queue-free $R > 0$ branch if and only if $c < n_b$. For the exponential tool law this state has positive follow-up hit probability, which is not itself an empirical high-hit threshold or a condition that the external gate drains. With a fold, μ is multivalued on the band where several stationary states coexist (on (n_b, n_{fold}) for a fold at the all-miss end) and n_2 is taken on the good branch; a cap $c \ge n_b$ engaged in the trap keeps the all-miss state, so $c < n_b$ is a further necessary condition, whose sufficiency we have not proved.

Table 20: Proposition 4 on the measured closed curves (`results/theory/pred2/prop_e_cor_c.json`), at every closed run past the measured peak of its cell: the hit fraction measured, given by three exogenous-gap closures (Yao at the measured throughput; Little's-law and Che closures, whose rates do not use it), and the proposition's lower bound with $K_{\text{run}} = 0$ at the measured throughput, which applies to the Yao column only; the share of the pool that running requests would have to hold to give the measured hit fraction; and the frozen first-principles model (fluid; H1 in parentheses where it differs by more than 0.05).

cell, n	measured	Yao	Little	Che	bound	K_{run}/M	model
300k, 32	0.505	0.932	0.723	0.827	≥ 0.899	0.832	0.371
300k, 48	0.000	0.932	0.499	0.551	≥ 0.930	1.000	0.000
300k, 96	0.000	0.932	0.254	0.276	≥ 0.927	1.000	0.000
300k, 300	0.000	0.932	0.082	0.088	≥ 0.903	1.000	0.000
native, 80	0.922	0.932	0.868	0.932	≥ 0.866	0.531	0.920
native, 96	0.419	0.932	0.761	0.878	≥ 0.932	0.956	0.000 (0.355)
native, 128	0.007	0.932	0.590	0.659	≥ 0.932	0.9995	0.000
native, 300	0.000	0.932	0.259	0.281	≥ 0.932	1.000	0.000
vLLM, 24	0.879	0.932	0.889	0.932	≥ 0.783	0.412	0.910
vLLM, 28	0.658	0.932	0.806	0.932	≥ 0.892	0.763	0.812 (0.717)
vLLM, 32	0.083	0.932	0.723	0.827	≥ 0.931	0.987	0.441 (0.381)
vLLM, 40	0.007	0.932	0.592	0.662	≥ 0.931	0.999	0.000
vLLM, 48	0.000	0.932	0.499	0.551	≥ 0.931	1.000	0.000
vLLM, 96	0.000	0.932	0.254	0.276	≥ 0.929	1.000	0.000
vLLM, 300	0.000	0.932	0.082	0.088	≥ 0.909	1.000	0.000

Heuristic layers. These are heuristics, not consequences of the propositions (H1–H4 are F1–F4 in the frozen files and the code). *RR*, the trapped layer, replaces Eq. (2) in the trap by a fluid FCFS round robin. Every follow-up misses, and every present session completes one turn per cycle $\theta(t) = \sum_i [t^m_{k_i} + (1 - p_b)/\nu_b]$, the sum over the sessions present of the miss prefill time of the next turn and the per-turn decode share of the all-miss state (p_b is p at $(\nu_b, 0)$). Each cohort advances one turn per cycle and survives to turn k with probability $(14/15)^{k-1}$, up to turn 60. The layer starts at the burst from the good-state population n_1 with the stationary turn mix w_k, and adds the burst and arrivals at rate λ. The trapped rows of Table 6, the model column of Table 7 (Proposition 5 applied to its turn mix) and H4's starting population and first cycle come from it. Because the backlog stays young, its cycle is short at first: on the 300k pool, at 1.35 and 1.65 λ_{ref}, N falls after the burst to 153 and 174 sessions and then grows, over the evaluation window, at 0.016 and 0.029 sessions/s, 64% and 63% of $\lambda - \mu_b$. *H1* averages the curve over a discretized positive KV-demand fluctuation of n sessions, with nominal Gaussian variance $0.570/n$ derived from the turn mix. *H2* predicts the from-empty edge: demand follows a one-dimensional diffusion with drift $\lambda - \mu(x)$ and noise intensity $1.567(\lambda + \mu(x))$, the dispersion index of the session shot noise (Campbell), and a run counts as unstable if it reaches n_b within the 3000 s horizon. *H3* gives the probability that a burst leaves the run stuck (hit fraction below 0.2 over the evaluation window) as the splitting probability [61] of the same diffusion, started at the burst cohort's peak live demand, plus the background escape (Appendix Q); burst sessions are fresh, so a burst counts by its peak footprint (4,331 tokens per session, at turn 12), not by its number. *H4* gives the release time of a cap engaged inside the trap by a two-phase drain that starts from RR's population and cycle at the engage time: paused sessions first, then fresh arrivals. In detail: *RR* is integrated with a 1 s step from the burst time: each second a cohort of mass λ (plus 200/60 during the burst) enters at turn 1, every cohort's turn counter advances by $1/\theta(t)$, and a cohort that entered with mass m holds $m(14/15)^{k-1}$ sessions at turn k; the initial n_1 sessions are spread over turns with the stationary mix (`analysis/theory/fluid_rigorous/trapped.py`, `round_robin_trap`). Backlog, slope, token rate and gap/R_M are its window means. *H1*: the code uses Gaussian-shaped weights on a positive finite grid, not an expectation over an untruncated Gaussian (which would allow a negative pool). Let $v = \text{Var}_w(E_k)/\bar{E}^2 \simeq 0.570$, let $n_{\min} > 0$ be the smallest population of the evaluation grid, and set $\sigma_{\max} = \sqrt{v/\max(n_{\min}, 1)}$. Take 41 equally spaced values ϑ_j between $\max(0.5, 1 - 4\sigma_{\max})$ and $1 + 4\sigma_{\max}$, inclusive. At population n use

$$p_j(n) = \frac{\exp[-n(\vartheta_j - 1)^2/(2v)]}{\sum_{\ell=0}^{40} \exp[-n(\vartheta_\ell - 1)^2/(2v)]},$$

$$\widetilde{\mu}(n) = \sum_{j=0}^{40} p_j(n)\, \mu_{\text{fluid}}(n; M/\vartheta_j).$$

The hit fraction is averaged with the same weights. The parameter v/n is the nominal Gaussian variance; truncation and discretization need not preserve that variance or a mean of exactly one (`analysis/theory/fluid_rigorous/model.py, annealed_curve`). *H2*: $dX = (\lambda - \mu(X))dt + \sqrt{I_D(\lambda + \mu(X))}\, dW$, reflected at 0, with $I_D = 1.567$, the shot-noise dispersion index by Campbell's theorem. The probability that a run is unstable is $1 - e^{-t_H/\mathcal{T}}$, with $\mathcal{T}$ the mean first-passage time from 0 to n_b and $t_H = 3000$ s. *H3*: a burst of N_{b} fresh sessions starts the diffusion at $X_0 = D^{-1}_{\text{live}}(D_{\text{live}}(n_1) + 4331\, N_{\text{b}})$, where 4331 tokens is a fresh cohort's peak expected KV per session (turn 12); the probability that the run is stuck (hit fraction below 0.2 over the registered evaluation window) is $q(X_0) + (1 - q(X_0))P_{\text{esc}}$, with q the splitting probability between n_1 and n_b [61] and P_{esc} the H2 probability of an escape from the good state in the time that remains before such an escape could no longer bring the registered evaluation window's hit fraction below 0.2. *H4*: RR gives the population n_{on}, the mean turn index k_0 and the cycle θ_{on} at the engage time t_{on} (161.3 sessions and 88 s at 1800 s and 1.35 λ_{ref} on the 300k pool). Within one cycle every session reaches a tool-call boundary, so the admitted set falls to c by $t_{\text{on}} + \theta_{\text{on}}$. The gate serves the paused sessions first. Phase 1 lasts $T_1 = (n_{\text{on}} - c)/\mu_1$, with μ_1 the capped rate of paused sessions: footprint inflated by $1 + 650(k_0 - 1)/E_{\text{lb}}$ and one forced miss. Phase 2 drains the $\lambda(\theta_{\text{on}} + T_1)$ fresh arrivals collected meanwhile at $\mu(c) - \lambda$, so the gate empties at $t_{\text{on}} + \theta_{\text{on}} + T_1 + \lambda(\theta_{\text{on}} + T_1)/(\mu(c) - \lambda)$. Release comes at the first 10 s tick at which the gate has been empty for 300 s, and not before $t_{\text{on}} + 600$ s.

Relation to prior models in detail. Yao et al. [114] give a mean-field (Che-type) LRU hit ratio for multi-turn sessions with exogenous gaps between turns, a rate scaled with memory, and prefill/decode disaggregation; their characteristic-time equation already contains the term for content that is never reused and has a unique fixed point, and they note that end-to-end latency may change the observed gaps without modelling it; EfficientAgent measures that waiting behind other agents stretches the gap between an agent's turns, and its backlogged-pool working-set scale is the cycle argument of Proposition 5 [98]. Eq. (4) reduces to theirs when nothing runs and nothing queues. The feedback here runs through service time and reserved KV: misses starve decode under prefill priority, which swells running reservations and squeezes idle KV. That turns their unique fixed point into a curve with a rise, a peak, a cliff at Eq. (5) and an all-miss branch, on which the queue sets the reuse gap (Proposition 5). Yuan et al. measure this decode slow-down under "context thrashing" as agent concurrency rises [120]. MISA-T describes the eviction–cold-prefill–queue loop in words, measures the collapse, derives a session cap of the same capacity-over-session-size form as the pool part of Eq. (5) (a reserved block budget over a conservative session length) and contracts it on a hit-rate decline [51]; neither gives equilibria, a rescue condition or a fold criterion. Classical cache-performance approximations and analyses [17, 38, 43, 45, 79] model caching under specified request

processes; here the characteristic-time approximation enters as Assumption MF, at the edge of its validity. CacheRoute states the Che criterion, revisit time longer than eviction time, for LLM prefix caches whose revisit times are set by routing, and reports that a single characteristic-time model misses a 70B engine's hit rate by 14.3 points [20]. Earlier work couples cache loss and queueing through processor-cache affinity scheduling [100] and buffer hits under data contention [29]. The closed curve is a Denning thrashing curve [30], and Corollary 5 is the classical decomposition argument [25] applied to a predicted $\mu(n)$. Metastable-failure work [2, 11, 39, 48, 54] studies several sustaining mechanisms, including cache loss, using case studies, queueing, Markov-chain and operational models, simulation or stress tests; here the sustaining effect is cache loss, and the thresholds are predicted from independent inputs (van Rooyen [106] also predicts a collapse threshold from a measured service law, for feedback from output to load). Lu et al. write the same population balance, $\dot{N} = \lambda - X(N)/K$, with an empirical hit curve $h(W/C)$ and an empirical cliff $N_c \approx 1.9\,C/\bar{c}$ [76]; that cliff is also a capacity ratio, without the tool-call term. What we believe is new: a predicted thrashing curve for prefix-cached agent serving, the onset identity and its speed corollary, the $s\bar{z}$ law for the peak ratio, a model-level fold criterion under which, numerically, dispersed tool times make the closed curve fold, and a time-domain accounting form of the trapped-cycle relation. Closed-system bistability in thrashing multiprogramming models is classical [25, 84]; the criterion in terms of the tool-time density is ours. Our literature search was targeted, not exhaustive; in particular we have not read the multiprogramming literature after Courtois for a fold criterion analogous to Proposition 7.

Not modelled. SGLang's retraction of running requests under memory pressure, which the theory notes list as a candidate cause of the 1–3 point deficit in the trapped token rate, although none of our 73 SGLang server logs records one (Appendix P); prefill queueing (S1); the limit of 256 running requests, which (S4) assumes never binds (at the all-miss state of Proposition 2, $\nu_b \bar{S} = M/E_S$ requests run, so this needs $M < 256 E_S \approx 2.8$ million tokens, which every cell satisfies); and the reset of the release hold when sessions arrive just after the gate empties.

R Supplementary results

R.1 Closed curves and from-empty runs

With the 300k pool (Fig. 5, left), $\mu(n)$ rises from 0.176 sessions/s at $n = 16$ to 0.224 at 20 and 0.233 at 24, with hit fractions 0.93, 0.93 and 0.89. The run at $n = 24$, which sets μ^*, contains a degraded episode inside its window (hit fraction 0.66 over $[900, 1200)$ s, 0.46 in its worst 100 s); over $[1200, 2700)$ s alone $\mu(24) = 0.257$ against $\mu(20) = 0.231$, so the near-tie that sets the cap of 20 owes part of its closeness to this episode. The run at $n = 32$ mixes two regimes: degraded from about 450 to 2400 s, then recovered to 0.80, for a hit fraction of 0.51. At $n = 48$ none of the 20.0M prompt tokens in the window was served from cache: evictable tokens survive about 6.3 s before eviction (estimated as mean evictable KV over the eviction rate) while a session returns after 30.6 s on average (2.9 s against 66 s at $n = 96$). The hit fraction crosses 0.5 at $n = 32.2$, about 3.7 sessions above the capacity ratio $N_{\text{lb}} \approx 28.5$ and just below the all-miss onset $n_b = 32.7$ of the first-principles model, which predicts this curve without using its points (§H, Table 6). Token-level hit rates have been reported to collapse as concurrent agents grow on SGLang [19] and on vLLM [51, 120], and, on prefill–decode disaggregated SGLang, once the working set reaches about twice the cache [76]; what we add is $\mu(n)$ in completed sessions per second, the quantity the open-system model uses, at four pool sizes on the A100, two on an H200 and, in §G.2, on a second engine. Beyond the peak the curve is not monotone: it falls to $\mu(48) = 0.049$ sessions/s and rises again, $\mu(96) = 0.061 < \mu(300) = 0.108$ sessions/s. We attribute both to the synchronized start, which leaves old, long turns in the window at $n = 48$ (served prompts 14% above the stationary mean) and young sessions with short prompts at $n = 300$ (71% of the stationary length in flight); no longer run has tested this; the all-miss level implied by token throughput is roughly flat at 0.072–0.081 sessions/s, so the collapse from the peak is about threefold. Stock LPM keeps 39% of turns hitting at $n = 48$ (rising from 0.28 to 0.44 through the window); at $n = 300$ its queue of 269 exceeds the 128-request threshold above which, by the source, SGLang's LPM stops re-sorting its queue, and no turn hits; whether the fallback causes the zero was not tested (at $n = 300$ the pool may be oversubscribed under any ordering).

With the native pool (Fig. 5, middle), SGLang sized the KV pool at 955,757 tokens, 3.19 times the 300k pool. μ peaks at 0.479 sessions/s at $n = 64$ (0.477 at 80) with 92–93% of turns hitting, then falls to 0.123 at $n = 96$ (hit fraction 0.42), 0.067 at 128 (0.007) and 0.101 at 300. The hit fraction crosses 0.5 between $n = 80$ (0.92) and 96 (0.42), near 93 by linear interpolation, against just above 32 at 300k; the peak is at 64–80 against 20–24. With one run per n, the cliff moves out roughly threefold. The all-miss capacity is unchanged within its standard error: 0.0718 ± 0.0037 sessions/s turns-based against 0.0715 ± 0.0038, and $11{,}282 \pm 51$ against $11{,}243 \pm 84$ all-miss tokens/s. The 300k-token pool limit did not create the cliff; it moved it. The ratio $\mu^*/\lambda_{\text{ref}}$ is 6.67 with the native pool and 3.26 at 300k.[2]

E0a gives $\lambda_{\text{ref}} = 0.0715 \pm 0.0038$ sessions/s turns-based (standard error over three seeds), our estimate of λ_{miss}, 0.0717 ± 0.0076 in completed sessions, and $11{,}243 \pm 84$ all-miss prefill tokens/s. The token rate varies by ±1.2% across seeds and the session rate by ±17%: the engine is bound by prefill tokens, and the sessions completed in 1800 s are a small sample of a heavy-tailed quantity. The token rate divided by $E[W]$ gives 0.0728 sessions/s, within 2% of the turns-based value.

[2] These are the registered values: the peak in completed sessions over the turns-based λ_{ref}. Turns-based over turns-based gives 6.48 and 3.15.




Figure 7: From-empty stability. Real engine: one 3000 s run per rate from an empty cache and queue (1 = stable, 0 = unstable), plotted at its nominal rate; all runs used arrival seed 0, whose realized rates were 6–13% higher (the fresh-seed runs of §G.1 are not plotted). Gray: blind simulator predictions, the fraction of simulated runs stable at multiples of the simulator's own λ_{miss}. Top, SGLang with the 300k pool: B2 (3 seeds dashed, 20 dotted). Middle, SGLang with the native pool: B2n (10 seeds; mixed batching, the primary mode, dashed; separate, dotted). Bottom, vLLM 0.32.0 with the 300k pool: B2v (variant V1, costs scaled to vLLM; mixed batching, 10 seeds). Top axes: multiples of each cell's λ_{ref} (the simulators' own λ_{miss} are 0.0722 at 300k, 0.0720 and 0.0714 native, and 0.0662 for B2v).

From an empty cache and queue (Fig. 7, top) the engine stayed stable at 1.25, 1.5, 1.75 and 2.0 λ_{ref}, ending each run with an empty queue and with 91–93% of turns hitting over the run, and was unstable at 2.5 λ_{ref} (final queue 127, rising by 146 over the last 1500 s) and 3.0 (289 and 196). On this grid, which used the single arrival seed 0, the edge lies between 2.0 and 2.5 λ_{ref} in nominal rates, well below $\mu^*/\lambda_{ref} = 3.26$, so the from-empty edge, not the peak, bounds the window. The registered window was (1, 2.0) λ_{ref} = (0.0715, 0.143) sessions/s. Each rate is one 3000 s run; a longer horizon could find a lower edge, and at 2.0 λ_{ref} the hit fraction fell from 0.934 in [300, 1500) s to 0.903 in the second half of the run. All six runs used seed 0, so they share one random-number stream: their arrival sequences are nested, and each arrival count lies about 2.1 standard deviations above its Poisson mean, 8–13% above the nominal rate (302, 359, 416, 472, 585 and 697 sessions; the runs labelled 2.0 and 2.5 λ_{ref} received 2.20 and 2.73 λ_{ref}). This makes the stable side of the bracket conservative and its unstable side weaker than the labels suggest; in realized arrivals the bracket is still below μ^*/λ_{ref}.

An exploratory replication with fresh seeds 3, 4 and 5 at 2.0 and 2.5 λ_{ref} (jobs 17168506–07; §I) found all six runs stable, each ending with an empty queue and with 92–93% of turns hitting. Its frozen rule asked for 2.0 λ_{ref} to be stable in all three seeds and 2.5 λ_{ref} unstable in at least two, so the seed-0 bracket is not replicated: near 2.5 λ_{ref} the nominal edge depends on the seed (2.5 λ_{ref} was stable in 3 of 4 seeds). The rule's fallback restates the bracket in realized arrival rates. Over the twelve from-empty runs at this pool (seeds 0 and 3–5), every run that received at most 2.665 λ_{ref} (0.191 sessions/s) was stable and the two that received 2.726 and 3.248 λ_{ref} were unstable, so stability is monotone in the realized rate and the edge lies between 2.665 and 2.726 λ_{ref}, still below μ^*/λ_{ref}. The registered window was derived from the nominal seed-0 bracket and stands as frozen; the registered points, 1.35 and 1.65 λ_{ref}, lie inside the from-empty stable range on either reading. The calibrated simulator had predicted all six fresh-seed runs stable, blind in time. The heuristic H2 of §H was pessimistic: it puts the per-seed probability of instability at 0.15 at 2.0 and 0.69 at 2.5 λ_{ref}, so three stable runs at 2.5 had probability 0.03 under it (§I states which of its values are blind).

With the native pool (Fig. 7, middle; native E0b, rates in multiples of the native λ_{ref} = 0.0718 sessions/s) the engine stayed stable at 1.5, 2.5, 3.5, 4.5 and 5.5 λ_{ref}, ending each run with an empty queue and with 93% of turns hitting over the run, and was unstable at 6.5 λ_{ref}: its final queue was 505, rising by 477 over the last 1500 s, and its hit fraction fell from 0.84 in [300, 1500) s to 0.00 in the second half. In nominal rates the edge lies between 5.5 and 6.5 λ_{ref} (0.395 and 0.467 sessions/s), so the native window is (1, 5.5) λ_{ref}. Unlike at 300k, this does not show the edge below the peak (μ^*/λ_{ref} = 6.67, or 6.48 turns-based): these runs also used seed 0 (361 to 1478 sessions, 5.6–11.7% above nominal), and the 6.5 run received 0.493 sessions/s (6.86 λ_{ref}), above the measured peak, so overload alone can explain its instability. The stable 5.5 run received 0.419 sessions/s (5.84 λ_{ref}). Its upper edge is 2.75 times higher than at 300k in units of λ_{ref} (5.5 against 2.0), and the window is 4.5 λ_{ref} wide against 1.0. Again each rate is a single 3000 s run.

R.2 The registered paired tests in detail

The registered analysis, run on all 18 runs with the code frozen at the registration commit, passes at both rates (Table 5, top); by the definition of §F.3 the test is pre-registered. Every BURST run had a hit fraction of 0.000 over the evaluation window, an uncached prefill rate of 1.009–1.029 times the all-miss rate and a mean backlog of 200–332 sessions. One (1.35 λ_{ref}, seed 1) is stuck in the same way, but its backlog was flat over the window (207 sessions at its start, 206 at its end;

slope 0.0036 sessions/s, below the 0.0125 threshold), so the rule calls it indeterminate: its seed delivered 0.0910 arrivals/s in the window, 5.8% below the nominal 0.0966 (seeds 0 and 2: 0.1037 and 0.1017), and the trapped engine completed 0.0913 sessions/s. The pass at 1.35 λ_{ref} therefore rests on 2 of 3 seeds, the minimum the rule allows. The other runs' base arrivals over the window came to 1.42 and 1.45 λ_{ref} at 1.35 and 1.61–1.75 λ_{ref} at 1.65 (Table 5). Every NOBURST and CAPPED run is good (hit fractions 0.921–0.934, backlogs of 8–12 sessions, most asleep in tool calls); in the window CAPPED cannot be told apart from NOBURST, because the gate had drained the burst. The counts are small, and pooling the two rates does not make them independent: both rates use the same three seeds, with the same burst and nested arrivals (§F.1). BURST's hit fraction is below NOBURST's in all six seed-and-rate pairs; counting each seed once, a post-hoc one-sided sign test gives $p = 1/8$, the smallest value three seeds allow.

In Fig. 1, every BURST run is at zero hits from the window starting at 1300 s to the end. Its backlog first fell, to 135–172 sessions 300–1300 s after the burst, as short burst sessions finished, then rose; over the last 300 s it was 206–369 sessions, still growing in five runs and flat in the sixth. The five trapped runs still completed 0.081–0.097 sessions/s (1.13–1.35 λ_{ref}), above λ_{miss}, because the backlog's sessions are young and their turns short, so that at about the all-miss token rate more turns, and more sessions, complete (§E.3), but below the arrival rate, and the sixth completed sessions about as fast as they arrived (1.28 and 1.27 λ_{ref}); only the uncached prefill rate sits at the all-miss level, which is why the registered rule uses tokens. The CAPPED gate's queue emptied 1547–1904 s after the burst at 1.35 λ_{ref} and 2021–2693 s at 1.65 λ_{ref}, 3–52% longer than the fluid estimate of §E.4 from the population present at the burst (1453–1508 s and 1757–1804 s; the registration's cruder estimate was 1571 s and 1889 s), and well before the evaluation window. Outside the registered criteria, the CAPPED arm's hit fraction dips while the gate drains the burst: its lowest 100 s window is 0.48–0.77 in four of six runs, against 0.82–0.89 for NOBURST, which plausibly slowed the drain. The cap has a cost that the registered criteria do not measure: it turns the burst into admission delay at the client. In each CAPPED run 349–543 sessions waited at the gate, 45–66% of them ordinary arrivals queued behind the burst, for 405–471 s on average and at most 853–985 s; outside the drain the gate bound only briefly, when arrivals clustered (at most 40 sessions in a run, each for less than 50 s). Without the cap, turns completed in the BURST arm's evaluation window took a mean of 163–237 s from send to completion (the client does not stream), against 1.4–1.7 s in NOBURST and CAPPED and 1.4–1.5 s in every arm before the burst; at 8700 s, 19–29% of BURST sessions were unfinished. So at loads that the engine carried from empty for the full 8700 s run (E0b carried the bracketing rates, 1.25–1.75 λ_{ref}, for 3000 s), 200 sessions arriving within a minute, an order of magnitude more than the 8–12 present in the good state, moved it into an all-miss state that it did not leave within 7500 s, and a cap of 20 sessions, within 5% of the measured peak of $\mu(n)$ (argmax $n = 24$), prevented that at the price of that admission delay. The registered basin test BASIN-1 (§I) varied the burst at 1.65 λ_{ref} with the same seeds: 100 sessions trapped the engine in 3 of 3 seeds (hit fraction 0.000; trapped by the rule) and 25 left it good in 3 of 3 (hit fraction 0.923–0.934, within 0.003 of the no-burst run of the same seed), so in each seed the boundary lies between 25 and 100 sessions; BASIN-2 narrowed it to between 40 and 60 sessions in every seed (§G.4). The heuristic H2 of §H puts the probability that a run at these rates leaves the good state on its own within 8700 s at about 0.5% at 1.35 and 5% at 1.65 λ_{ref}, so good NOBURST arms over 8700 s are the expected outcome, not evidence that the good state never ends; on the fresh-seed from-empty runs H2 overstated the chance of instability (§G.1).

A second registration was filled by the same formulas from the native curve, the native E0a calibration and the native E0b bracket, and committed before the first native E2 job (Appendix M). Its window is (1, 5.5) λ_{ref}; the one-third/two-thirds rule, written down before native E0b was read, gives 2.5 and 4.0 λ_{ref} (0.1795 and 0.2872 sessions/s); the cap rule gives $n_{\text{cap}} = 64$, the peak (flagged ambiguous: $\mu(80)$ is within 0.35% of $\mu(64)$). The protocol, the burst of 200 sessions and the trap rule are E2's, with the native reference rates.

The registered analysis passes at both rates, and every run is in the predicted state (Table 5, bottom; Fig. 8); by the definition of §F.3 this test, too, is pre-registered. All six BURST runs were trapped: hit fraction 0.000 over the evaluation window, an uncached prefill rate of 1.074–1.078 (2.5 λ_{ref}) and 1.106–1.124 (4.0 λ_{ref}) times the native all-miss rate of 11,282 tokens/s, and mean backlogs of 557–601 and 1098–1139 sessions with slopes above the threshold. All six NOBURST runs were good and all six CAPPED runs recovered (hit fractions 0.929–0.935, backlogs of 16–34 sessions, most asleep in tool calls). Over the window the base arrivals were 2.48–2.73 λ_{ref} at 2.5 and 3.89–4.28 at 4.0. Counting each seed once, the post-hoc sign test again gives $p = 1/8$. Pooled post hoc over the two pre-registered SGLang tests (a descriptive count, not a registered quantity: the tests differ in pool, cap and rates, and reuse the same three seeds, so the 12 runs of each arm share three seeds' session sequences), NOBURST was good and CAPPED recovered in 12 of 12 runs each, and BURST was at zero hits in 12 of 12 and trapped by the rule in 11 of 12.

With the larger pool the collapse took longer and the backlog never drained (Fig. 8). In the 100 s window that contains the burst, the native BURST runs still hit with 0.99–1.00 of their follow-up turns (all but 4 of 3,326), against 0.43–0.59 at 300k; counting the burst's own first turns, which always miss, they hit with 0.63–0.76 of all turns (0.21–0.33 at 300k). Every BURST run was at zero hits from 300–600 s after the burst to the end of the run. In 50 s bins its backlog fell after the burst only at 2.5 λ_{ref}, to 155–168 sessions 150–200 s after it; at 4.0 λ_{ref} it grew from the first bin after the burst (201–231 sessions). It then grew to 658–1379 sessions over the last 300 s. The trapped engine completed 0.103–0.146 sessions/s (1.44–2.03 λ_{ref}), above λ_{miss}, because its backlog's sessions are young and their turns short (§E.3), and well below the




Figure 8: The registered test with the native pool (native E2) at 2.5 λ_{ref} (left) and 4.0 λ_{ref} (right), $\lambda_{\text{ref}} = 0.0718$ sessions/s; layout as in Fig. 1, with the CAPPED gate at $n_{\text{cap}} = 64$ and the backlog axis extended to 3000.

arrival rates; it prefilled 1.074–1.124 times the 32-session all-miss token rate, as the simulator predicted (§N.1). The CAPPED gate's queue emptied 512–583 s after the burst at 2.5 λ_{ref} and 837–937 s at 4.0, between 4% shorter and 13% longer than the fluid estimate from the population present at the burst (491–518 s and 840–876 s), and 10–23% shorter than the registration's cruder 668 s and 1043 s. Here 234–448 sessions waited at the gate, 128–180 s on average and at most 247–361 s; outside the drain the gate bound for at most 6 sessions in a run, each for at most 7.1 s. BURST turns completed in the evaluation window took 321–511 s on average, against 1.6–2.5 s in NOBURST and CAPPED, and 38–50% of BURST sessions were unfinished at 8700 s. Here 200 sessions were 6 to 13 times the 16–34 present in the good state. B3n had predicted a pass at somewhat higher rates (§N.1).

vLLM 0.32.0 passed its smoke test on the same GPU type (token ids and cached-token counts returned, flush verified) and ran with the SGLang cell's settings where they exist: FCFS, prefix caching on, chunked prefill of 8192 tokens, at most 256 running requests and a 300,000-token pool (18,750 blocks of 16 tokens). With prefix caching off, its all-miss capacity (vLLM E0a, three seeds) is 0.0657 ± 0.0030 sessions/s turns-based and $10{,}349 \pm 81$ uncached prefill tokens/s, 8% below SGLang's 0.0715 and 11,243 on the same model, GPU and workload.

Six exploratory BURST runs came first, under a registration derived from E2's: the multiples 1.35 and 1.65 of vLLM's own λ_{ref} (0.0886 and 0.1083 sessions/s), seeds 0, 1, 2, and E2's protocol and trap rule with vLLM's reference rates. Their window and multiples were inherited from the SGLang cell, not measured: these runs preceded vLLM's own closed curve and from-empty edge, and no NOBURST or CAPPED arm ran with them. Before the burst all six runs were in the good state (hit fraction 0.93–0.94 from 300 s to the burst; a post-hoc reading). After it, all six were at zero hits from the 100 s window starting 100 s after the burst to the end of the run (also a post-hoc reading), with an uncached prefill rate of 0.997–1.031 times vLLM's all-miss rate and mean backlogs of 203–227 sessions at 1.35 and 277–309 at 1.65 λ_{ref} (Fig. 9, bottom row). The registered rule calls four of them trapped. The other two are indeterminate by the slope test: one has a flat backlog near 203 sessions (slope 0.0002 against a threshold of 0.0115; 1.35 λ_{ref}, seed 1), and in the other the backlog grew from 269 to 294 sessions over the window, at 0.0175 against 0.0213 (1.65 λ_{ref}, seed 1). Both are seed 1, as are the indeterminate SGLang FCFS runs at 1.35 λ_{ref} with and without the refresh. A vLLM run's arrivals are a subset of the SGLang run's at the same seed and multiple, and seed 1 delivered 5.5–7.9% fewer arrivals than nominal in these windows, so the labels on the two engines agree on the same workloads rather than on independent ones. So the same all-miss state appears on a second engine after the same burst. Without control arms these runs are not a registered paired test: they do not show that vLLM's good state would have lasted the run without the burst, or that a cap would have recovered it.

vLLM's own closed curve (Fig. 5, right; one run per n) has the shape of SGLang's at the same pool. $\mu(n)$ peaks at 0.219 sessions/s at $n = 20$, with $\mu(24)$ 0.5% lower, so the peak is a tie at one run per n; $\mu^*/\lambda_{\text{ref}} = 3.34$ (3.21 turns-based). The hit fraction is 0.93 at $n \le 20$, 0.88 at 24, 0.66 at 28, 0.08 at 32

and 0.0075 at 40; it crosses 0.5 near $n = 29.1$, close to N_{lb}, and μ falls 80% from $n = 24$ to 32. The closed curve had no cache hits from $n = 48$ on, as with SGLang's FCFS; Proposition 6, a limit statement, is consistent with this but does not predict it. Like SGLang's, the curve is not monotone beyond its peak: in completed sessions it falls to 0.63–0.67 λ_{ref} at $n = 32$–48 (0.83–0.90 turns-based), whose windows held old, long turns (served prompts 12–17% above the stationary mean), and rises to 1.60 λ_{ref} at $n = 300$ (1.59 turns-based). vLLM preempted running requests in every closed run from $n = 24$ on (12 to 72 per run from $n = 32$ on), which the proposition allows on our reading of vLLM's source (Appendix P).

From an empty cache and queue (Fig. 7, bottom; one 3000 s run per rate) vLLM stayed stable at 1.25, 1.5, 1.75 and 2.0 λ_{ref} (0.082–0.131 sessions/s), ending each run with an empty queue and with 92–93% of turns hitting, and was unstable at 2.5 λ_{ref} (final queue 82, rising by 94 over the last 1500 s) and 3.0 (247 and 175). The edge lies between 2.0 and 2.5 λ_{ref}, as in SGLang's seed-0 grid with the same pool, so vLLM's window is $(1,\ 2.0)\,\lambda_{\text{ref}}$. These runs also used seed 0 and received 8.6–13.3% more arrivals than nominal (279 to 642 sessions; the runs labelled 2.0 and 2.5 λ_{ref} received 2.21 and 2.74 λ_{ref}), but the unstable 2.5 run's realized 0.180 sessions/s is below the measured peak (0.219, or 0.211 turns-based), so here, as at 300k on SGLang and unlike with the native pool, the edge lies below the peak.

Blind predictions for this cell, B4v for the curve and B2v for the edge, were made with the calibrated simulator in two variants, unchanged and (V1) with its token costs scaled so that its all-miss token rate matches vLLM's measured one (a fit to vLLM's E0a, not a prediction), each in both batching modes, and are frozen in `notes/PREDICTIONS_vllm.md`. They were committed and pushed to GitHub before any of the curve and edge runs had finished, but 22 minutes after the jobs were submitted, when two of them had been running for almost as long; they are blind in that no result existed, not in submission order. The peak level and the cap held: B4v (V1, mixed batching, 10 seeds) put the peak at $n = 24$ with 0.215 sessions/s turns-based, against the real 0.211 at $n = 20$ (0.210 at 24), and the cap at 20. The real cliff is steeper and earlier than predicted: hit fractions of 0.66 against 0.74 at $n = 28$ and 0.08 against 0.46 at $n = 32$ (0.46–0.53 over the four simulator configurations), and a 0.5 crossing near 29.1 against 31.4–32.6. B2v put the edge at 2.0 λ_{ref} in all four configurations (V1 with mixed batching: 10 of 10 runs stable through 2.0, 7 of 10 at 2.5 and 3 of 10 at 3.0), as measured. The simulator does not model vLLM's block-level eviction or its scheduler and token budget; like vLLM, and unlike SGLang, it has no waiting-prefix refresh.

A registration for vLLM was then filled by the formulas used for SGLang (Appendix M) from this curve, vLLM's E0a and five of the six E0b runs (the 3.0 λ_{ref} run was still running; it came out unstable, which leaves the bracket unchanged). It gives the window $(1,\ 2.0)\,\lambda_{\text{ref}}$ with $\lambda_{\text{ref}} = 0.06566$ sessions/s, the points 1.35 and 1.65 λ_{ref} by the one-third/two-thirds rule, which was written in our status notes before any vLLM curve or edge existed, and $n_{\text{cap}} = 20$, flagged ambiguous because $\mu(24)$ lies within 0.5% of the peak. The protocol, the burst and the trap rule are E2's. The points equal the multiples of the exploratory runs; the rule that selected them was adopted for vLLM (`836063a`) after their outcome was known, and the BURST arm reuses their seeds 0–2 and so their arrivals: it is not an independent replication of them. The registration was committed 37 s before the 18 jobs of the paired test were submitted, but reached GitHub 2 min after the submission and 53 s after the first job had started, before any job had finished; by our definition (§F.3) this test is therefore registered but not pre-registered. At 18:21 CDT the memory request of the 15 jobs still pending (17166124–38) was lowered from 128G to 48G so that they could be scheduled; no code, argument or registration changed, and no job had ended. The third prediction round, frozen before the registration existed, also predicted this test (B3v): a pass at both points in all four simulator configurations, with every simulated BURST run at zero hits (7 to 9 of 10 per point trapped by the rule, the rest indeterminate), NOBURST good in 10 of 10 and CAPPED at a cap of 20 recovered in 10 of 10. Because the orchestrating agent that specified that round knew the exploratory BURST outcomes, the BURST-arm part of B3v is blind at most on the predicting agent's side, and there only by instruction and by the agent's own unchecked record: its copy of the repository held those runs (Appendix N).

The registered analysis passes at both rates (Table 5, bottom): at each rate, in two of three seeds BURST was trapped, NOBURST good and CAPPED recovered. Its tool also labels the test pre-registered and decisive, labels it assigns by commit order (as it did for the two SGLang tests); by the definition of §F.3 this test is registered, not pre-registered. Every BURST run had zero hits over the evaluation window and prefilled 0.948–1.018 times vLLM's all-miss token rate. The two runs the rule does not call trapped are both seed 1, the seed with the fewest arrivals in the window (1.24 and 1.56 λ_{ref} at the nominal 1.35 and 1.65). At 1.35 its backlog stayed flat at about 200 sessions with an uncached prefill rate of 1.007 times the all-miss rate, and the rule labels it draining because its fitted slope was -5×10^{-5} sessions/s: it was stuck, not draining. At 1.65 it was indeterminate by the slope test (0.0183 against 0.0213). The pattern repeats the exploratory runs, whose arrivals these BURST runs share. Over the last 300 s the BURST backlog was 196–250 sessions at 1.35 and 299–383 at 1.65 λ_{ref}; turns completed in the window took 180–261 s on average, against 1.4–1.6 s in the other arms, and 20–31% of BURST sessions were unfinished at 8700 s. NOBURST stayed good and CAPPED recovered in all six runs each (hit fractions 0.930–0.933). In each CAPPED run 322–499 sessions waited at the gate, 43–63% of them ordinary arrivals, for 413–526 s on average and at most 1053 s, and the gate's queue first emptied 1521–2735 s after the burst, 1.05–1.63 times the fluid estimate from the population present at the burst. B3v had predicted a pass at both rates; the trapped runs' token rates lay at or below its range (0.948–1.018 against 0.99–1.07). The first-principles model, pushed at 02:05:30 CDT, three minutes before the registered verdict was computed and, by the log of the agent that operated the registered vLLM

test (notes/LOG.md), before any of these run directories was opened, predicted good-state hit fractions of 0.932 and gate drains of 1449 and 1725 s, short of the measured 1521–2027 and 1848–2735 s, as in three of the four SGLang cells (Table 6); the theory's own blindness declaration does not cover these runs. Across the three registered tests, BURST was at zero hits in 18 of 18 runs and trapped by the rule in 15, NOBURST was good in 18 of 18 and CAPPED recovered in 18 of 18; the tests share seeds, and vLLM's BURST arm shares arrivals with earlier runs, so these counts are descriptive.

Mechanism predictions for this test were frozen and pushed at 18:20:13 CDT on 2026-10-30, before any of its 18 runs had ended (configs/r11_mechanism_predict.yaml and notes/PREDICTIONS_r11_mechanism.md, commit f1338e3; byte copies under r11_mechanism/frozen/ in the test's data directory). They were: (a) in NOBURST and CAPPED, a median gap between a session's turns below 0.05 times the pool's turnover time $R_M = M/\text{churn}$ (§H.4) and a follow-up hit fraction above 0.95, and in BURST a ratio above 2 and a hit fraction below 0.05; (b) in BURST, a mean KV usage of at least 0.90 and an uncached prompt-token rate within 15% of the all-miss rate, that is, a full pool rewritten at the all-miss rate; (c) an online detector, a follow-up hit fraction below 0.2 over 60 s, alarming within 300 s of the burst in every BURST run and never after 600 s in a good arm; (d) an engine rule, a mean time to first token above 30 s over 100 s, behaving the same way. The frozen decision rule required (b) and (c) in every BURST run and (a) and (c) in all good-arm runs but at most one. (a), (b) and (d) held in all 18 runs: the gap ratio was 6.44–8.78 in BURST and 0.014–0.022 elsewhere; in BURST the KV usage was 0.920–0.937 and the uncached rate 0.871–0.955 times the all-miss rate; and the engine rule alarmed 170–210 s after the burst in BURST and never in a good arm. (c) failed. The detector alarmed 100–120 s after the burst in every BURST run, but also in two CAPPED runs, seed 2 at both rates, 880 and 820 s after the burst, while the gate was draining with 20 sessions admitted and 123–143 waiting; the follow-up hit fraction dipped to 0.06–0.17 for 20–40 s and was above 0.8 again 110–160 s later. The frozen decision rule is therefore not met. The detector uses CONCUR's hit-rate threshold (0.2) without its KV-usage condition [19]; we do not claim it, and a deployed alarm on this rule would have fired twice without a trap. The bands of (a)–(d) were chosen on the SGLang runs and on the exploratory vLLM runs, whose arrivals the BURST arm repeats, so only the NOBURST and CAPPED checks are out of sample.

R.3 The rescue tests in detail

Table 21 gives the registered runs one by one. In every run the cap was engaged within 0.003 s of t_{on}, every pause was matched by a resume, no session was paused or gated at the end, and the in-job mechanical check passed; the smoke job ended with 142 sessions gated, 20 in the engine and none failed. Hits came back within three minutes of the engage and draining the backlog took the rest of the capped phase: over 300 s bins the follow-up hit fraction was 0.56–1.00 during R1's capped phase, and in R4 it dipped to 0.47–0.57 in the 300 s bin from 3000 s (0.56–0.78 in the bin before), while the native backlog in the engine, at the gate and paused peaked near 430, before it reached 1.00 once the queue drained. The registered RECOVERED test, evaluated every 10 s, first held 540–700 s (R1) and 300–350 s (R4) before the release, while the cap was still on, and the cap last held a session back 301–310 s before each release, the hold the release rule requires. Each paused session waited 386–569 s on average and the longest total pause of one session was 817–1240 s; averaged over all sessions of a run, pauses took 30–63 s. Every session of the cohort that arrived in [1200, 3000) s completed in every rescue run, with a median duration of 630–909 s (300k) and 1138–1146 s (native), against 62–73 s without the burst and 793–1099 s in the uncapped controls, where 2–24% of that cohort had not finished at 8700 s. After release the uncached token rate was 0.08–0.12 (300k) and 0.23–0.27 (native) times the all-miss rate, and every 300 s window had a follow-up hit fraction of at least 0.938. Against the simulator's exact-plan predictions, the engine paused 0–13 more sessions, its client queue held up to 1.5 times as many sessions with the native pool (387–397 against 258–342), its delay there was 1.5–3 times as large, and its completed shares equal the predicted ones to four decimals in 6 of 9 runs. The persistence, cost and trace tables behind §G.3 and Fig. 4 are in results/rescue_paper_data/20261031-071938/ in the data directory, written after the verdicts by figures/rescue_paper_data.py.

Table 21: The registered rescue runs (R1: 300k pool, cap 20 from 1800 s; R4: native pool, cap 64 from 2100 s). Outstanding at t_{on}: requests in flight plus sessions held at the client. Sim.: the release time the simulator predicted on the run's exact arrival plan (tag r11-rescue-pred). Held: the largest number of sessions waiting at the gate or paused. After: the largest number of sessions in the system after release. Delay: session-hours of pauses and admission waits.

$\lambda/\lambda_{\text{ref}}$	seed	outst. at t_{on}	t_{rel} (s)	sim. (s)	paused	held	after	delay (h)
1.35	0	146	4550	3960	124	134	16	53.1
	1	148	3980	3470	130	146	17	38.4
	2	139	4400	3940	121	148	20	65.4
1.65	0	172	4920	4900	141	158	23	77.8
	1	171	4430	4440	143	159	21	50.1
	2	143	4570	4280	138	145	27	60.8
4.0	0	324	6000	4250	251	397	55	222.0
	1	322	5980	5180	240	397	43	229.6
	2	298	6140	4410	220	387	49	225.0

R.4 Exploratory policy grid and stock LPM

Three other engine cells ran the BURST arm at the registered rates and seeds (Fig. 9) under exploratory registrations derived from E2's, with no control arms. In these runs the refresh made no difference for FCFS: all six runs without it, which share their arrivals with the registered runs, have the registered runs' states, hit fraction 0.000 and backlogs within 1.3% of




Figure 9: Exploratory policy grid, BURST arm only, 300k pool. Rows: FCFS with the waiting-prefix refresh (the registered runs), FCFS without, LPM with, LPM without (under LPM the refresh acts only during the FCFS fallback above 128 waiting requests); below the dashed line, the exploratory vLLM 0.32.0 runs with FCFS (§G.2), at multiples of its own λ_{ref} (0.0657 sessions/s). Columns: 1.35 and 1.65 λ_{ref} by seed. Colour: registered state (RECOVERED judged on the last 300 s); numbers: hit fraction and mean sessions in the system over the evaluation window.

theirs (201–231 sessions at 1.35 λ_{ref}, 282–328 at 1.65), as the source predicts: the refresh moves waiting prefixes up the LRU order but does not pin them. Both rates lie inside the window; near λ_{miss}, with a cap or with the native pool, the refresh was not tested.

LPM partly helps. From the 200-session burst, at 1.35 λ_{ref} it recovered in 4 of 6 runs and was draining in a fifth (hit fractions over the evaluation window; RECOVERED is judged on the last 300 s, where every recovered run was at 0.92–0.94; with the refresh: recovered at 0.71 and 0.81, draining at 0.51; without: recovered at 0.80 and 0.93, trapped once). At 1.65 λ_{ref} it was trapped in 4 of 6, indeterminate in one (hit 0.44) and recovered in one (0.82). The paths behind these window means differ from FCFS's, which had no hits from 100 s after the burst in all twelve FCFS runs (a post-hoc reading in 100 s windows). Each LPM run that ended trapped kept some hits until 1500–1900 s after the burst (3900 s in one run) and then had none; each run that recovered first exceeded a hit fraction of 0.8 3100–6500 s after the burst and stayed above it to the end, so that had the runs ended 2000 s earlier, only two of the five would have met the RECOVERED rule. This is a finite-burst result for the BURST arm alone, not an estimate of LPM's congested service rate μ_∞; with mixed outcomes in every cell, three seeds do not bracket a threshold. Post hoc, the timing matches SGLang's 128-request fallback: in the five runs that recovered the engine's waiting queue never exceeded 128 after the burst, and in each of the five that ended trapped the last hit fell in the 100 s window in which the queue last stood at or below 128. This is a correlation in ten runs, not an isolation; Appendix R gives the details and the other candidate causes.

Stock LPM and its fallback. In deep congestion stock LPM stops re-sorting its queue, so, on our reading of its source, Proposition 6 applies to it (Appendix P); consistent with this, Stage C's LPM run at $n = 300$ had zero hits with a queue above 128, and round 5 of our earlier simulator, which modelled the 128-request fallback, found no LPM advantage in congestion. In the same earlier, uncalibrated simulator, pure LPM without the fallback has a congested service rate of about 1.17 times that simulator's own λ_{miss} and recovered from 300 cold sessions only up to about 1.1 times it (§T.2); these are deep-congestion quantities and do not compare directly with recovery from a finite burst. We do not claim that LPM fails, and we have not isolated why it recovered. Post hoc, the timing matches the 128-request fallback: in the five runs that recovered, the engine's waiting queue (5 s samples) never exceeded 128 after the burst (at most 116–126), and in each of the five that ended trapped the last hit fell in the 100 s window in which the queue last stood at or below 128. This is a correlation in ten runs, not an isolation. An exploratory intervention followed (LPM-INF, below), which switches off LPM's ordering fallback and the LRU touch of its prefix matching together. Other candidates are partial prefix hits and LPM's own prefix matching, which moves the cached part of every waiting request's prefix to the recent end of the LRU order on each scheduling attempt; the simulator omits both. Under LPM the waiting-prefix refresh is skipped, because that matching already touches the waiting prefixes, so the two LPM configurations differ only while more than 128 requests wait and LPM has fallen back to FCFS. Seed 0 at 1.35 λ_{ref} recovered with the refresh and was trapped without it; since the refresh made no difference under FCFS, single runs near LPM's threshold appear sensitive to small differences.

LPM without its fallback (LPM-INF, exploratory). To test whether the fallback causes stock LPM's collapse, a job-local hook raised SGLang's 128-request limit to 10^9 and changed nothing else, and the BURST arm reran at 1.65 λ_{ref} on seeds 0–2 with byte-identical arrival plans (jobs 17168743–45); the exploratory registration, the endpoints with their decision rule and the simulator's predictions were frozen under tag `r11-lpminf-pred` before the jobs were submitted. The controls are the grid's stock-LPM runs of 2026-10-24 and 25, partly on other nodes, with the same arrival plans. On seeds 0 and 1, where stock LPM had collapsed in all four runs (with and without the refresh), LPM without the fallback did not collapse: its token hit fraction over the evaluation window was 0.59 and 0.42, against 0.000, and its waiting queue peaked at 165 and 184 requests, against 287–345. This is the outcome that the rule frozen for the test reads as consistent with the

fallback causing stock LPM's collapse. On seed 2 the queue never exceeded 128 (at most 120), so the hook never acted and the run does not enter the rule. It is not a fix: no run recovered by the registered rule (draining, indeterminate and draining on seeds 0, 1 and 2), and on seed 1 the engine still prefilled 0.92 times the all-miss token rate with 194 sessions unfinished at 8700 s. The blind simulator predicted the direction, no collapse on any seed, but not the level (token hit fractions of 0.08–0.10) or the registered state, trapped in its prediction and in none of the three runs; it was flagged in advance as pessimistic about LPM, because it has no partial prefix hits. With the fallback off, LPM keeps both its ordering and the LRU touch that its prefix matching gives waiting requests, so the test does not say which of the two prevents the collapse. Replicate noise in this partial-hit regime is large: on seed 2, three LPM runs that were in effect one configuration, since none of their queues passed 128, gave token hit fractions of 0.44, 0.56 and 0.82. With one rate and two informative seeds this is directional evidence.

R.5 The native-pool prediction round

The native-pool round. A second round (B1n–B4n) reran the same simulator with only the pool changed to 955,757 tokens. B2n and B3n were committed and pushed before any native E0b run had finished, 23 minutes after the native E0b jobs were submitted, and before any native E2 job existed, so B3n is blind in time and B2n is blind in that no result existed, not in submission order; their specification, like that of B1n and B4n, was written after the native curve was known (below), and B3n's cap of 64 is B4n's output. B2n held in part. Both modes predicted stability at all five rates where the engine was stable (10 of 10 seeds each), but the primary (mixed) mode put the all-stable edge at 6.5 and kept 10 of 10 runs stable there, where the real run was unstable, so its edge is too high by at least one step of its 0.5 grid in nominal multiples (the real 6.5 run's arrivals came to 6.86 λ_{ref}, above the real peak, and B4n puts the simulated peak 11% above the real one); the secondary (separate) mode put the edge at 6.0, with 8 of 10 runs stable at 6.5, consistent with the real bracket. Because the real edge came in lower, the registered rates (2.5 and 4.0) lie below B3n's own test points, which are 6–16% higher in multiples of λ_{miss}, and B3n was not simulated at them; 2.5 lies below every point it ran, toward the low end that it had flagged as its weak spot (9 of 10 seeds trapped at 2.85, the tenth recovering). The pass held at both registered rates. The levels are consistent with the lower rates, not a direct match: the trapped token rate rises with the rate in both the simulator and the engine, and the real 1.074–1.078 at 2.5 λ_{ref} lies just below the 1.086–1.109 predicted at 2.65–2.85, while the real 1.106–1.124 at 4.0 overlaps the low end of the 1.119–1.140 predicted at 4.35–4.65. Outstanding backlogs of 549–594 and 1089–1130 requests lie inside the predicted 460–643 and 1067–1333 (they compare only roughly, as for B3), and good-arm hit fractions of 0.929–0.935 lie inside the predicted 0.928–0.936. B3n had also warned that at its higher point the trapped token rate sits close to the registered tolerance of 15%, so that at higher rates the rule would stop calling a stuck run trapped; the real 1.106–1.124 at 4.0 λ_{ref} is inside the tolerance, by 2.6 to 4.4 percentage points.

B1n and B4n are not blind. The native curve and λ_{miss} had been measured and summarised in our project status notes (`notes/STATE.md`) before this round's specification was written, and the specification's finer grid near the cliff (n = 72, 80, 88) may reflect that; only the LLM agent that ran the predictions was instructed not to read those data and, by its own record (not checked independently), did not. For completeness: B1n's λ_{miss}, 0.0720 sessions/s and 11,239 tokens/s, is within 0.4% of the real 0.0718 and 11,282. B4n put the peak at n = 72, which the real grid does not contain, with μ 11% above the real peak at 64–80; it put the 0.5-hit crossing at 94, against about 93, and the cap at 64, as registered. It flagged that cap as knife-edge ($\mu(64)$ only 0.35% above the 5% threshold, where a slightly lower value would have given 72) and the cliff cells n = 80–96 as cells whose outcome differed across seeds; the real cliff lies somewhere between 80 and 96.

R.6 Trace-driven tool times and mechanisms in detail

Trace-driven tool times. TraceLab's sessions come from 52 pseudonymous users (release v0.0.2, a later snapshot than the one the paper describes) [123]. From TraceLab we take the per-turn tool time (mean 8.51 s, median 0.237 s, coefficient of variation 4.65) and, as an upper bound on it, the idle gap between requests (mean 14.52 s). Both are capped at 600 s, which affects 0.18% of turns and 0.38% of gaps but removes 38% and 66% of their raw means (13.6 s and 42.9 s); the per-turn series includes sub-agent runs and can include waits at permission prompts. Only TraceLab's tool times are used: its prompts average 172k tokens, more than the testbed's 49,152-token context limit. The mini-SWE-agent law comes from 500 published bash-only trajectories, the same 100 instances for each of five models (mean 1.40 s, median 0.104 s, coefficient of variation 4.29); 0.56% of its steps hit the harness's 60 s command limit, so the law is specific to that limit. The exponential control reproduced the record workload exactly and passed at both points. A secondary workload with mini-SWE-agent's mean turn and token counts (geometric turn counts) passed at 1.65 λ_{miss} and failed at 2.35. There CAPPED (cap 12, the curve's peak) had left the trap, but at $\mu(12)-\lambda \approx 0.022$ sessions/s it needs about 9000 s to drain 200 sessions, longer than the 7500 s the run lasts after the burst; NOBURST was good in 8 of 10, and the other two collapsed without a burst. This workload's sessions outlive the declared measurement windows (λ_{miss} is 0.0120 sessions/s as declared, 0.0141 with a 20 times longer window, in which units the failed point is 1.99); a labelled post-hoc rerun with longer horizons gives, in those units, a narrower window, [1, 1.5], a pass at 1.35, and at 1.15 a failure of the slope rule (3 of 10 trapped, all 10 stuck below a hit fraction of 0.2).

Mechanisms in detail. *TTL pins.* Continuum's released preview pins for 2 s, and only when the parsed tool's historical mean is at most 2 s [69]. We did not implement the paper's estimator. The preview's release rule is: when an allocation fails and nothing runs, release the pin that expires last; under it, at $\tau = 20$ s the system recovers from a cold start up to 4.0 λ_{miss} and from 5 of 5 bursts. The rule we read in the paper's deadlock-prevention text is: when a request does not fit, unpin the latest-arriving programs until it fits, also while work runs; under it, $\tau = 10$ and 20 s recover from no cold start at 1.1 λ_{miss} or above and from no burst. Our earlier rule, which waited for expiry while the GPU idled, gave 1.719 at $\tau = 20$ s. With plain FCFS order instead of Continuum's, under that earlier rule, the pins gave 0.29, 0.17 and 0.10 at $\tau = 5$, 10 and 20 s (3 seeds), with the GPU busy 33%, 17% and 8% of the time: that simulator keeps an expired pin while the session's next request waits, which under FCFS lasts the rest of the queue wait. *Adaptive caps.* With finished sessions' KV counted as usage, the 12 of 18 cells that stall do so at our surrogate's minimum window of 4, at 0.915–0.935 λ_{miss}; of five exploratory sensitivities, one (a 5 s control interval instead of our surrogate's 10 s) raised the rate by 0.184 ± 0.167, an unadjusted pointwise interval. Pause and resume of admitted agents is not modelled.

R.7 The pre-deployment procedure in detail

The window of Eq. (3) comes from three measurements that an operator can make before deployment, on the engine, model, pool and workload that will be served. (1) *All-miss capacity*: run a saturated closed population with prefix caching disabled and measure the uncached prefill token rate, which is stable across seeds; check saturation by measuring at two populations (for example 32 and 64 sessions) and use the larger rate, since a population that is not saturated understates λ_{miss} (our 32-session reference fell about 2–3% short on the A100, Appendix P, and about 4–5% on the H200, more than the 3% standard error of that cell's λ_{ref}, §J); convert it to sessions by the mean work per session, or use turns per second over $E[T]$ measured over a window longer than a session's lifetime at that population (mini-SWE-agent's sessions outlived the declared 1800 s window, and the turn rate there gave a λ_{miss} 15% low); completed sessions over a short window are noisy. By Proposition 6 and the fluid model of §E.3, under request-level FCFS this is an upper bound on the recovery threshold from deep congestion if the congested engine computes prompt tokens no faster than the cache-disabled one, and it equals that threshold if, in addition, $\mu(n) \geq \lambda_{\text{miss}}$ at every population beyond the peak and not only in the limit (with zero hits, if the engine computes prompt tokens as fast as the cache-disabled one at every congested population); the heuristic work balance of §E.3 leads to the same conditions for the open system. With zero hits our engine computed prompt tokens at 1.03 times the all-miss rate near the stationary turn mix and at 0.95–1.12 times it over the windows we measured, so (A3) and (A4) hold on it only to within a few percent at the stationary mix and to within 12% over those windows. If sessions share a prefix (system prompt, tool definitions), measure instead with caching on and each turn's private context fresh, so that only the shared prefix can hit, the reference against which we expect Proposition 6 to hold for the private suffixes (Appendix P); disabling caching entirely understates the congested rate. (2) *Closed-population curve*: measure $\mu(n)$ on a grid that crosses the cliff, and do not read μ_∞ off the largest n of a short run with a synchronized start; here $\mu(300)$ was 0.108 sessions/s, 51% above λ_{ref}. (3) *From-empty edge*: run open arrivals from an empty engine at increasing rates over the horizon of interest, at least that of the burst test, with more than one arrival seed or in realized rates: at 300k, 2.5 λ_{ref} was unstable on the original seed (realized 2.73 λ_{ref}) and stable on three fresh ones (realized 2.47–2.67), and ordered by realized rate the 12 runs place the edge between 2.665 and 2.726 λ_{ref}; on the H200, 1.4 times its λ_{ref} was stable in 2 of 3 seeds, and in realized rates its ten runs are monotone, with the edge between 1.496 and 1.503 λ_{ref}.

If $\mu^* > \lambda_{\text{miss}}$, then in the fluid model of §E.3, under request-level FCFS and the assumptions of Proposition 6, every operating point in $(\lambda_{\text{miss}}, \min(\mu^*, \lambda_e))$ is one sufficiently large burst away from the congested state unless admission is bounded; a steady-state load test there passes without testing recovery. On the engine we tested two rates per pool with a burst of 200 sessions, about 20 times the 8–12 present at 300k and 6 to 13 times the 16–34 present with the native pool, which left all 12 registered BURST runs on these two pools at zero hits (11 trapped by the rule), as it did all 24 registered SGLang BURST runs (19 trapped); at 1.65 λ_{ref} on the 300k pool the registered test BASIN-1 found that 100 sessions also trap (3 of 3 seeds) and 25 do not (3 of 3), and BASIN-2 that 60 trap (3 of 3) and 40 do not (3 of 3), with 50 trapping one seed of three; in the simulator 25 never trapped and 50 trapped about half the time. Without a cap, Proposition 6 and the fluid model predict that recovering from deep congestion requires cutting the arrival rate below λ_{miss}, which was 31% of peak throughput at 300k tokens and 15% with the native pool; the earlier, uncalibrated simulator agrees (over 150,000 s, FCFS recovered from congestion at 0.9 times its own λ_{miss} and not at 1.0), and on the engine the registered SHED test of §I stopped arrivals entirely: at 1.35 λ_{ref} a stop of 3600 s from 1800 s drained the trap in 2 of 2 seeds, refusing 355 and 378 sessions, and one of 600 s did not, as the fluid model's shortest rescuing stop, 1795 s, predicts. Whether a rate between zero and λ_{miss} suffices is tested on the engine only by CUT-B (§3; [pending: CUT-B outcome]); Corollary 3 says it does, slowly, while a rate in $(\lambda_{\text{miss}}, D(\lambda))$ does not, and in CUT-A such a rate left all three traps in place to the end of the run. Stock LPM, which on our reading of its source stops re-sorting its queue when more than 128 requests wait and so falls under Proposition 6 in deep congestion, recovered from the same finite burst at 1.35 λ_{ref} in 4 of 6 grid runs, and at 1.65 λ_{ref} in 1 of 6 (§G.6); with the fallback disabled it avoided the all-miss collapse at 1.65 λ_{ref} on the two arrival streams on which stock LPM had collapsed, without recovering (exploratory, §T.2); the proposition is a limit statement and does not predict recovery from a finite burst for any ordering. Corollary 5 says that

a cap drains a burst, or an established trap, only if it lies inside (n_1, n_2), and the drain is fastest where $\mu(c) - \lambda$ is largest, at the peak. A cap at the capacity boundary $N_{\text{lb}} = M/E_{\text{lb}} \approx 28$, the size a capacity-ratio rule gives at 300k, lies on the steep side of the curve, within a few sessions of n_2 (31.8–32.2 at the registered rates), where the quasi-static model is least reliable; in the earlier simulator a cap of 28 held 2.39 λ_{miss} against 4.04 for a cap of 20 (§T.2). We take the smallest n within 5% of the peak (20 at 300k and on vLLM, 64 with the native pool), because the curve has one run per n, and check it with a burst test. We recommend a cap because it needs no engine change, its effect in the quasi-static model follows from Proposition 1 and Eq. (2), and it is the one mechanism we tested on the engine (all 24 registered SGLang CAPPED runs recovered), not because it dominates: in the earlier simulator, 20 s TTL pins with a pinned-first order reached a higher $\mu(300)$ than any static cap (§T.2). A cap does not make the burst free: it moves the burst's cost to the client as admission delay (per-run maxima of 853–985 s at 300k and 247–361 s with the native pool), instead of turns that take several minutes for the rest of the run (§G.2, §G.2). The delay ends only if the gate drains, which in the quasi-static model needs $\lambda < \mu(c)$ for a cap c (Proposition 1 and Eq. (2)). Whether the gate should queue or reject sessions is a deployment choice we did not evaluate.

The cap must be measured again when the workload or configuration changes. In the simulator the peak moved from 20 to 32 or 40 sessions with the TraceLab tool-time laws and to 24 with mini-SWE-agent's (where the cap stayed at 20), and fell to 12 with mini-SWE-agent's mean turn and token counts. On the real engine it moved to 64–80 with the 955,757-token pool, where the registered cap of 64 drained the burst in every run, and with vLLM 0.32.0 on the 300k pool it stayed at 20–24. On an H200 with the 300k pool it moved to 32 (the smallest-within-5% rule gives 28), and the window narrowed from $(1, 2.0)$ to $(1, 1.3)$ times that GPU's own λ_{ref}: the all-miss rate rose 2.71-fold over the A100's, the peak only 1.63-fold (turns-based; 1.65 in completed sessions) and the from-empty edge, in nominal multiples on each GPU's seed-0 grid, 1.76-fold (§I). A faster GPU can thus leave too little room between λ_{miss} and the edge for our registration rule to place a burst test. A cap sized for one setting can fail in another in either direction. Too small, it holds the engine below the offered load: a cap of 20 under the TraceLab idle-gap law gives $\mu(20) = 1.26\,\lambda_{\text{miss}}$, below both test rates (1.35 and 1.65 λ_{miss}), so the gate would not drain. Too large, it sits on the collapsed side of the curve: with mini-SWE-agent's full workload $\mu(20)$ is 1.45 times that workload's declared λ_{miss}, again below both test rates (1.65 and 2.35). Neither mis-sized cap was run. The procedure sizes a static cap offline. Here its three stages took 14–16 A100-hours per pool and engine, and a three-arm burst check about 7.5 more per rate and seed. An online detector is a separate question: a hit rate below 0.2, with KV usage above 0.5, is CONCUR's thrashing signal [19], MISA-T confirms a decline relative to a learned reference hit rate [51], hit rate is among Bronson et al.'s characteristic metrics [11], and learned early indicators have been proposed [78]. Our frozen version of the first, on the client's follow-up turns, alarmed 100–120 s after every vLLM burst but also twice during capped drains (§G.2); and with sessions that share a system prompt the raw hit fraction of a trapped engine would stay near the shared share, so a detector would have to count private-suffix reuse. We do not claim a detector.

R.8 Threats to validity in detail

Synthetic sessions and clients. Sessions are synthetic (random tokens, fixed tool outputs and output lengths, geometric turn counts, exponential 5 s tools) and share no prefixes, which removes the case PEEK's scheduler targets. These parameters were fixed before we measured any trace, and they differ from the two trace sources of §T.1. Our mean tool time of 5 s lies between theirs (1.40 and 8.51 s), but their medians are 15–33 times shorter than ours, 63–85% of their tool times are under 1 s against 18% of ours, and their coefficients of variation are 4.3–4.7 against 1. Their outputs per call are 2.7–5.9 times our 100 tokens, and TraceLab's mean prompt, 172k tokens, exceeds our 49,152-token context limit. Apart from one secondary mini-SWE-agent workload, the trace-driven runs of §T.1 replace only the tool-time law, and only in the simulator. With no shared prefix a miss reuses nothing from other sessions. A shared 2000-token system prompt, cached once, would cut the prompt work of a session from 154,529 to 125,007 tokens when every turn misses and from about 9,600 to 7,600 when every follow-up hits, so the ratio of the two, about 16, would barely change. Production agent traces report a hit rate of about 55% across turn boundaries and user idle gaps of minutes [73], while 93% of our turns hit in the good state (not the same metric). The simulator suggests that real tool-time laws keep the trap but move the window and the cap; the engine has not tested this. Our clients never retry or abandon a request, and the 7200 s request timeout never fired, although trapped turns took 163–237 s on average from send to completion at 300k and 321–511 s with the native pool. Retries would add load in the trapped state and abandonment would remove it, so either could change whether the engine recovers; neither was tested. The follow-up hit fraction falls from 0.93 to 0 in a trap only because no prefix is shared; with a shared system prompt the hit fraction of a trapped engine would stay near the shared share, so the hit-based signals of §J would have to count private-suffix reuse.

Few runs, finite horizons, nominal rates, uncontrolled factors. The closed curves and, apart from the repeats below, the from-empty sweeps have one run per point, so the peak's location (20 against 24 at 300k and on vLLM, 64 against 80 native) is within noise and single runs near the cliff land on either side of it. The registered tests, the grid and the vLLM runs share the same three seeds, so their runs are not independent across rates, pools or engines (§F.1). All rates in this paper are nominal. Each from-empty sweep used a single arrival seed, whose realized rates were 5–14% above nominal (6–13% in the 300k, native and vLLM sweeps), and the edge it gives depends on that seed: on SGLang at 300k, three fresh seeds were stable at both 2.0 and 2.5 λ_{ref}, where the original seed

had been unstable at 2.5 (realized 2.73), so the replication rule for the from-empty bracket frozen with the simulator's predictions, which needed 2.5 λ_{ref} unstable in at least two of them, is not met. The nominal bracket $(2.0, 2.5)$ is that of the single original grid; ordered by realized arrival rate, stability over the 12 runs is monotone and the edge lies between 2.665 and 2.726 λ_{ref}. The registered test points, 1.35 and 1.65 λ_{ref}, lie inside the window either way. On the H200 at 300k, 1.3 times its λ_{ref} was stable in 3 of 3 seeds and 1.4 in 2 of 3; ordered by realized rate the ten runs are monotone, with the edge between 1.496 and 1.503 λ_{ref} (§G.5). In the evaluation windows of the pre-registered SGLang tests the runs labelled 1.35 and 1.65 λ_{ref} received 1.27–1.45 and 1.61–1.75 λ_{ref} (native, 2.5 and 4.0: 2.48–2.73 and 3.89–4.28; vLLM BURST: 1.24–1.45 and 1.56–1.76). "Does not leave" means within 7500 s on the engine and 30,000 s in the simulator; the 3000 s horizon of the from-empty runs cannot see slow escapes, so the true edges may be below 2.0 λ_{ref} (both engines) and 5.5 λ_{ref} (native). The native cap rests on that coarse curve: $\mu(80)$ was within 0.35% of $\mu(64)$, and the cliff lies somewhere between 80 and 96 with no run in between. The registered smallest-within-5% rule gives 64 whichever of 64 and 80 is the true peak (the registration still flags the cap as ambiguous), and with no grid point between 48 and 64 it could not have found a smaller cap; a rule that takes the argmax could as well have picked 80, which may sit within one grid step of the cliff; how far a cap of 64 is from the cliff was not measured. The registered rule loses margin at both ends of the window: the slope test near λ_{miss}, and the token test at high multiples, where the trapped engine's prefill rate rises above the all-miss rate (1.106–1.124 times it at 4.0 λ_{ref} with the native pool, against a tolerance of 1.15), so at somewhat higher rates the rule would stop calling a stuck run trapped. In both SGLang closed curves the cliff coincides with a change of job and node (at 300k between $n = 32$ and 48, native between 80 and 96; Table 10), so neither curve excludes a node or job effect on where the cliff falls. The collapsed side ran on different nodes in the two curves, which argues against one slow node; on vLLM the hit fraction crossed 0.5 between two runs of one job on one node ($n = 28$ and 32); and both registered SGLang tests, which ran on all three nodes with consistent outcomes, argue against a node effect on the trap. The SGLang server seed was not pinned, and the load client runs on the server's node.

Model and simulators. Eq. (2) is used for the window and H2's from-empty edge, the recovery threshold, the capped drain time and H4, the burst sizes of H3, and the frozen SHED and TOOLSLOW predictions. The engine met the capped drain time within −4% to +63% given the population present at the burst (SGLang −4% to +52%, vLLM +5% to +63%). H2 was pessimistic at 300k: its frozen escape probability makes 2.5 λ_{ref} unstable with probability 0.69 per seed, and all three fresh seeds were stable there (probability 0.03 under H2). The freeze declared no prediction for these runs; the probability is read from its frozen files, and pred2's table for them was computed after the runs had ended. The model is not quantitative in congestion and is least reliable near the cliff (§E.3); the SHED prediction applies it in congestion, to a backlog of 161 sessions, and the TOOLSLOW prediction at the cliff, so those tests also test that use: the SHED prediction held, and the TOOLSLOW prediction of a trap in every seed at $\delta = 30$ s did not (1 of 3). Proposition 6 is a limit statement about the closed-population throughput $\mu(n)$ as n grows and says nothing about any finite population. It covers request-level FCFS and, on our reading of the engines' sources, vLLM's FCFS with its preemption and SGLang's stock LPM, which stops re-sorting its queue when more than 128 requests wait; it does not cover program-level FCFS, pure resident-first orders or eviction rules that foresee tool times. It assumes that long-run rates exist, private prefixes, at most one outstanding request per session, no offloading of evicted KV, i.i.d. tool times with finite mean that are independent of everything else and unknown to the engine in advance, a bounded number of running requests, a bounded admission rate, and an engine that in congestion computes prompt tokens no faster than with caching disabled; it gives equality only if the engine computes them as fast. With zero hits our engine computed them at 1.03 times the all-miss rate near the stationary turn mix and at 0.95–1.12 times it over the windows we measured, so (A3) and (A4) hold on it only to within a few percent at the stationary mix and to within 12% over those windows. The open system's recovery threshold rests on a heuristic work balance and, without a monotone tail of μ, can lie below λ_{miss}; that recovery from deep congestion without a cap needs a rate below λ_{miss} is proved only within model F (Corollary 3) and tested on the engine by SHED's full stop and the CUT runs (a cut above λ_{miss}, CUT-A, left all three traps in place within the run; [pending: CUT-B outcome]); pure LPM's congested rate is a conjecture; and the capped system's stochastic stability is not proved. The calibrated simulator failed its level test at $n = 48$, reserves whole turns, omits partial prefixes and the refresh, frees a finished session's KV at once (an oracle: a real engine keeps it as evictable cache), and understated LPM, again with LPM's fallback disabled (token hit fraction 0.08–0.10 predicted, 0.42–0.59 measured; §T.2). In its primary mode it put the native from-empty edge at least one grid step too high in nominal multiples, against a single real run whose arrivals exceeded the real peak, and for vLLM it predicted a later, gentler cliff than the engine showed (hit fraction 0.46–0.53 against 0.08 at $n = 32$). The mechanism comparison uses an older simulator whose assumed costs are about 1.5 times the fitted ones, so its absolute rates and recovery thresholds do not carry over to the engine. Its pin rows are fixed, configured TTLs, not Continuum's cost model; its PEEK rows are ablations and a projection of the released scheduler; and its CONCUR row is a surrogate of the paper's control equation.

The first-principles model. Its propositions hold for a deterministic fluid model, and no limit theorem connects the engine to it. Its mean-field step, Assumption MF, is least reliable when one session is a large share of the pool: at 150k tokens and on the H200 the mean live demand of the predicted peak population is close to or above the pool, and at 150k the H1 peak came out 11.5% high, in the direction a deterministic

eviction age implies, and H2 put the from-empty edge two grid steps low. On the H200 at 300k the model was closest up to $n = 36$, but from $n = 40$ the measured hit fraction stayed above the prediction (0.46 at $n = 40$ against 0.27, then 0.32 at 44 and 0.16 at 52, where the model is all-miss from its onset at 41.3 sessions, and zero only by 96), so that onset came early. The frozen notes named the mean field's lack of concentration at this pool as the likeliest failure, but expected it to bias the peak upward, and the peak was matched. With the 600k pool the tail was again softer (hit 0.48, 0.23 and 0.14 at $n = 72$, 80 and 96, against H1's 0.15, 0.02 and 0.00), so the crossing came 4.4 sessions after the predicted 66.6, and the predicted peak was 7.3% high, within tolerance (Appendix S). We have not traced the tail miss to a specific assumption and have no correction for it. The per-seed BASIN-2 probabilities favoured a stuck run for seed 0 at 40 and 50 sessions, where both runs stayed good; on Llama-3.1-8B the crossing failed the test of the tool-call term, declared after that curve was read; and its rescue release-time predictions were early, with observed releases more than 15% later in 4 of 9 runs. The H200 predictions assume that a faster GPU divides every cost by one factor, which misfits the H200's ratio of 64-session to 32-session all-miss token rates (1.019 predicted, 1.046 measured). On vLLM the model predicts a later and gentler cliff than measured. Unimodality and fold-freeness are numerical; the trapped layer RR and H1–H4 are heuristics; the model and its edge criterion were selected on the three measured cells; the 300k comparison shares its data source with the cost-model fit; and Proposition 7 has only a proof sketch (§H.6).

R.9 Further related work

What is classical, and what is specific to agent serving, in full. The collapse past the working-set level, the remedy of limiting active jobs, and a bad state that outlives its trigger are classical, and so are metastability arising from a unimodal throughput curve under open load, bistability when the load comes from a finite population of sources (ALOHA terminals with a fixed think time [15]), hysteresis, and bounded admission as the cure, for random-access channels [15, 66], thrashing multiprogramming systems [25, 84, 109, 116] and service systems whose customers return [16, 37, 53]; in all of them the slowdown is a given function of occupancy. The fluid picture of §E.3, a unimodal throughput curve that gives one stable and one unstable equilibrium under open arrivals, is the classical fluid (drift) analysis of unstable random-access channels [41, 66]; network congestion collapse, a stable bad state sustained by retransmissions, is its analogue [55, 83]. Replacing an open system's departure rate by its closed-system throughput is the classical decomposition (flow-equivalent) approximation, whose use to find unstable regimes of thrashing multiprogramming systems goes back to Courtois [25], and choosing the number of admitted jobs from the throughput curve, by paging heuristics [33] or from measured throughput [49, 96], is multiprogramming-level load control. Two features of agent serving make these apply. The reusable KV is exactly the idle KV: a session in a tool call or waiting in the queue holds no running request, so memory-gated admission reclaims its cache. And reuse makes a hit much cheaper than a miss, so losing the cache multiplies the work of every later turn. Both features are the premise of earlier agent-serving systems [1, 8, 9, 69, 111], and §7 describes those that describe, bound or avoid the resulting loop, among them Lu et al.'s concurrent study of the same open-system trap [76]. What is new on the theory side is the exact dynamics of the trapped state (§2), Proposition 6, a bound specific to prefix caching, and the first-principles curve of §H, in which the slowdown is derived from the pool, the workload and the server and running reservations depend on the hit rate and, on the all-miss branch, the queue sets the gap between a session's turns, with its closed-form all-miss onset, speed law, bound for exogenous-gap closures with little running KV, trapped identity and fold criterion (Propositions 2–5 and 7).

Other systems. CacheWise evaluates coding agents with sessions started together [104]; XPerf, a benchmark, sees hit rates fall toward saturation in fixed-rate runs at increasing rates [107]. Other systems manage idle KV across tool calls or workflow steps by offloading, prefetching or retention [1, 8, 9, 74, 86, 111, 121], schedule agent programs [72, 77], cache conversation state hierarchically [44, 91, 118] (Mooncake's scheduler also rejects requests early under overload), admit, place or reserve capacity for agent sessions by tool readiness, KV residency or likely returns [58, 71, 82], or make locality-aware scheduling fair [14]. Eviction-order work [75, 87, 88, 110] changes which idle state is evicted; RR-Evict assumes that the active trajectories fit in the cache, ScaleSim prefetches and evicts each agent's state by the estimated order of the agents' next requests, and Liu et al. replay traces without feedback from queueing to arrivals, as do Arya et al. for production Microsoft M365 agent traces, where LRU with a pooled budget of a tenth of the busiest hour's no-eviction demand makes 63% of Deep Research calls recompute [6]. Other close neighbours: Metronome calls a collapse in real-time speech-model serving metastable, in the sense that identical runs collapse or survive near a threshold, but there each session's KV stays pinned for the whole conversation until the pinned KV exhausts the pool, a different mechanism from eviction and recomputation of reusable prefixes [81]; AgentServeSim simulates agent serving with KV retained across tool gaps and successor turns released by simulated completions, so call timing depends on the policy, and validates it against vLLM in 20 paired cells, without a metastability analysis [93]; and ServeTwin simulates multi-turn agent workloads while tracking KV-cache evolution and reports that a pool 1.4 times larger lifts the hit rate from 22% to 93% at a fixed number of users [89].

S Frozen predictions: the full record

This appendix gives every prediction frozen for the later tests up to round 14 (Tables 23–25; those of round 15 are in Table 9, §3 and Table 17) with its source, its scoring




Figure 10: Frozen predictions of the peak ratio $\omega_b = \mu^*/\mu_b$ (fluid model, in model units). (a) Against $s\bar{z}$, the mean tool time in A100-equivalent seconds, for the 300k pool (Proposition 3); square and dot: the A100, measured (turns-based and sessions/s); diamond: the H200 prediction (s = 2.742). Triangles: the H200 measured peak ratio against its λ_{ref}, 1.89 turns-based and 1.99 in sessions/s (Table 23), values the first author had seen before the freeze. (b) Against the pool size, $\bar{z}$ = 5 s, with A100 costs (solid) and with the frozen H200 costs (green, dashed; s = 2.742); open squares: the A100 300k and native cells, measured (turns-based; in sample); filled squares: the A100 at 150k and 600k, measured (blind in time); purple diamonds: the frozen predictions for those two pools; green: the H200 frozen predictions at 300k and 600k (diamonds; the 600k one from pred2) and its measured peak ratios (triangles, turns-based; 300k seen by the first author before the freeze, 600k blind in time). Table 22 lists the values; it and Table 23 quote the primary predictions (H1, against λ_{ref}), which differ from the plotted fluid values by −8.6% (150k) to +1.2% (H200, 600k).

rule and what it is blind to, and the outcomes in hand in detail; §I summarizes them, §G.5, §G.3 and §G.4 report the H200, rescue and basin outcomes, and Table 16 gives the GitHub push times. Each registered test has a FILLED registration committed before its first job (Table 13). Those of BASIN-1, R1, R4, BASIN-2, TOOLSLOW and SHED are also tagged (`r11-basin-reg`, `r11-rescue-reg`, `r14-basin2-reg`, `r14-extra-reg`). The E2, native and vLLM registrations (`d279b7b`, `b8c19ec`, `5a6fbcd`; Appendix M) are not tagged; E2's and native's reached GitHub before their jobs were submitted, and vLLM's only after two of its jobs had started. The Llama-3.1-8B registration (`1559f8e`) and the 600k H200 registration (`4d1d431`) were pushed 47 and 63 s before their jobs were submitted but not tagged. BASIN-1's reached GitHub at 20:04:30 CDT on 2026-10-30, 68 minutes before its jobs were submitted; R1's and R4's at 22:39:02, 22 minutes before theirs; and BASIN-2's, TOOLSLOW's and SHED's at 02:10:48 and 02:28:09 CDT on 2026-10-31, before their jobs were submitted at 04:21 (Table 13). Every outcome is reported against these rules, misses included.

Out-of-sample predictions. The model's predictions for an H200 at the same pool, for pools of 150k and 600k tokens, for Llama-3.1-8B, for the registered basin tests and for the registered rescue tests were frozen and pushed before any of those results was read by the agents that derived it (the agent that operated the H200 cell and the first author had seen the H200 closed-curve values for $n \le 32$, which include the predicted peak, §I; tag `r13-theory-pred`, commit `997d2c4`, pushed at 02:05:30 CDT on 2026-10-31; `notes/PREDICTIONS_r13_theory.md`, `configs/r13_theory_predict.yaml`), with primaries, estimators, tolerances and refutation rules fixed in advance (`notes/THEORY_r13_scoring.md`). A second set, computed by new drivers that call the frozen model's functions unchanged (tag `r13-theory-pred2`, commit `cfa7712`, pushed at 04:20:20 CDT; `analysis/theory/pred2/`, `notes/PREDICTIONS_r13_pred2.md`, `configs/r13_theory_pred2.yaml`) covers the BASIN-2, TOOLSLOW and SHED tests, whose jobs were submitted after that push, and a 600k-token H200 cell; these drivers, including the per-seed burst calibration behind BASIN-2's probability of 0.66 (0.42 uncalibrated), were written after the first freeze but before any BASIN-2, TOOLSLOW or SHED job was submitted (the 600k H200 jobs were submitted at 02:50, while pred2 was being written, but could not start before 05:00). pred2 also declared rival scoring for the 0.5-hit crossing: the nearest of M/E_S, M/E_{lb} and the frozen crossing wins, and the tool-call term of Proposition 2(b) is supported if the crossing exceeds M/E_S by more than half of $n_b - M/E_S$, that is 15.96, 58.65, 34.53 and 29.89 sessions for the 150k and 600k pools, the H200 at 300k and Llama-3.1-8B. Section I lists all of them with their tests. Of the outcomes in hand, at 300k the H200 peak ratio, peak position, 0.5-hit crossing and from-empty edge are within their tolerances, while the tail after the H200 peak is softer than predicted. BASIN-1 came out as predicted (probability of the exact outcome 0.879; PASS was also the simulator's call, BASIN-1 does not test the critical burst, and its predictions are blind by access only). BASIN-2's registered

Table 22: The window across pool and GPU. Peak ratio $\mu^*/\lambda_{\text{ref}}$, measured (turns-based; completed sessions in parentheses) against the frozen H1 prediction; from-empty edge, measured bracket (nominal multiples of λ_{ref} on seed-0 grids: the native cell's own, otherwise the 300k value of the same GPU, as in Table 23) against the frozen H2 edge (at 300k three fresh seeds were stable at 2.5, where seed 0 was not, so the bracket is not replicated). Status: b, blind in time; i, in sample (H2 was chosen knowing these two brackets); s/a, peak seen by the first author before the freeze, edge blind by access only. Predictions: tag `r13-theory-pred`; H200 at 600k, pred2.

cell	status	$\mu^*/\lambda_{\text{ref}}$	H1	edge	H2
A100, 150k	b	1.68 (1.65)	1.87	[1.2, 1.3)	1.09
A100, 300k	i	3.15 (3.26)	3.27	[2.0, 2.5)	2.34
A100, 600k	b	5.71 (5.98)	5.47	[4.5, 5.0)	4.53
A100, native	i	6.48 (6.67)	6.89	[5.5, 6.5)	6.26
H200, 300k	s/a	1.89 (1.99)	1.92	[1.3, 1.4)	1.39
H200, 600k	b	2.98 (3.05)	3.20	[2.5, 3.0)	2.57

rule held (pred2's probability 0.66), as did pred2's secondary deterministic crossing in all nine runs, while its primary per-seed probabilities were on the wrong side for seed 0 at 40 and 50 sessions and the critical burst of 53.4 matches the edge of two of the three seeds (pred2's rows for BASIN-1's sizes, 25 and 100, are not blind: the agent that operated the basin cell first read those outcomes at about 04:07, before its push; pred2's agents read no BASIN-1 result, so to them the rows are blind by access only). At 600k tokens every pool-sweep quantity is within its tolerance; on the H200 at 600k the peak ratio, peak position and edge are, and the crossing is not. At 150k the crossing and the peak position are within their tolerances, and the peak ratio and the edge are not. Every edge here is scored in nominal multiples on the frozen grid rule; in realized rates H2's edge lies below the measured bracket at 150k, at 600k and on the H200 at both pools. The Llama-3.1-8B peak, peak ratio, peak position and crossing are within their tolerances and its edge is a near miss, but its crossing fails the declared test of the tool-call term (outcome below). The 600k H200 paired test passed at both rates, with the trapped backlogs within tolerance and the token ratios outside it in 5 of 6 runs; the Llama-3.1-8B paired test passed at 1.65 λ_{ref} and failed at 1.35, where the simulator had predicted a pass, and its conditional token ratio was outside tolerance in 3 of 6 runs; SHED came out as pred2 predicted, and TOOLSLOW did not (stuck in 1 of 3 seeds at 30 s, against every seed predicted). H2 was pessimistic on the fresh-seed from-empty runs, for which the first set declared no prediction. The second set's prediction for them is not blind, since those outcomes were first read at about 04:07, before its push; its dated erratum calls it blind by access only, counting only its agents' access.

GPU generation. The H200 cell repeats the 300k SGLang cell on one H200 NVL, with SGLang's default attention backend for that GPU (FA3; the A100 cells used FlashInfer), so the comparison is of GPU and default backend together. Its only inputs beyond the A100 cell are its E0a measurements: the all-miss token rate fixes the speed factor $s = 2.742$ of Proposition 2(c), the turns-based λ_{ref} (0.194 sessions/s) is the denominator of the peak ratio, and the 64-to-32-session ratio of all-miss token rates sets one cost variant. The model predicts that the peak ratio falls to 1.92 while the all-miss onset moves out to 41.3 sessions (Fig. 10); the frozen refutation rules are a peak ratio of 2.4 or more, a hit fraction below 0.5 at $n = 32$, or one of 0.5 or more at $n = 48$. Three extra closed runs at $n = 36$, 44 and 52, submitted after the freeze, bracket the predicted crossing at $n = 37.3$, and a 600k-token H200 cell, with the 600k A100 cell of the pool sweep, completes a two-by-two test of Proposition 3 (outcome below and Table 22). KAIROS shows qualitatively that a slower clock tips a fixed arrival rate into thrashing [119], and VAMP locates KV capacity boundaries on H100 and H200 GPUs [64]; the new parts would be the measurement in units of λ_{miss} and the opposite movement of the onset and the peak ratio. The Claude Code agent that operated the H200 cell (it submitted and monitored that cell's jobs) saw its closed-curve values for $n = 16$–32 (jobs 17166818–22) at about 22:28 CDT on 2026-10-30, before the freeze, and showed them to the first author; the coordinating agent that drafted the paper and dispatched the other agents, and the agents that derived and froze the model, did not see them. These values include the region of the predicted peak ($n \approx 32.5$), so the peak-ratio rule ($\omega_{\text{ref}} \geq 2.4$), the hit fraction at the peak and hit(32) are not blind to the first author. The closed runs at $n = 36$, 44 and 52 were submitted at 02:33 CDT, after the freeze, and are blind in time. Those at $n = 40$, 48, 96 and 300 and the original from-empty runs had ended before the freeze; by the record no one read them until the curve and the bracket were combined at 02:30, but, as for BASIN-1's runs, no file-access record can confirm this, so they are blind by access only. No blind simulator prediction exists for this cell. The edge is scored on the original E0b runs (jobs 17168377–82); four reseeds (17169668–71, at 1.3 and 1.4 λ_{ref}) were added after those runs had been read and are reported separately.

GPU generation: outcome. Section G.5 reports the measurement and §I scores it against the frozen model (Table 23); the details they omit follow. In completed sessions the H200 peak is 0.386 sessions/s, 1.65 times the A100's. The unstable 1.4 λ_{ref} run ended with a queue of 50.4, rising by 49 over the last 1500 s. On the nine-point curve the 0.5-hit crossing lies at 38.8. The log-likelihood of the six original E0b outcomes (stable at 1.1, 1.2 and 1.3, unstable at 1.4, 1.55 and 1.75 λ_{ref}), which the scoring rules ask for under both edge criteria, is −1.35 under H2 and −2.82 under the second criterion (a level crossing, edge 1.57 λ_{ref}; its probabilities interpolated linearly between its grid points). No refutation rule fires: hit(32) = 0.74 and hit(48) = 0.22. By pred2's rival scoring the crossing, 38.9, passes the test of the tool-call term (threshold 34.53), and the frozen crossing (37.3) is nearer than M/E_S (27.8) or M/E_{lb} (28.5); pred2 declared these rules after this curve had been read (combined at 02:30, and at 04:09 with $n = 36$, 44 and 52), so neither result is blind. The model is closest to the tail at $n = 36$ (hit 0.61 against 0.56 fluid; the

Table 23: Frozen predictions and their tests. Each prediction was committed under the tag named before any of its results was read by the agents that made it (for the H200, Llama-3.1-8B and BASIN-1 exceptions see their rows; the theory's fresh-seed probabilities were not declared for that test before it ran); scoring rules and tolerances were frozen with it (`notes/THEORY_r13_scoring.md` for the theory; the registration file or `configs/r11_*_predict.yaml` otherwise). "Theory": the model of §H, tag `r13-theory-pred` (§H.5), files under `results/theory/merged/`; "pred2": new drivers calling the same frozen model, tag `r13-theory-pred2` (commit `cfa7712`, pushed 04:20:20 CDT, before the first BASIN-2, TOOLSLOW or SHED job by its freeze record; files under `results/theory/pred2/` at that tag). "Simulator": the calibrated simulator of §F.4. $\omega_{\text{ref}} = \mu^*/\lambda_{\text{ref}}$ (turns-based), with λ_{ref} the cell's measured E0a rate (pool sweep: the A100 300k value, 0.0715 sessions/s; H200 600k: the H200 300k value, 0.194 sessions/s; Llama: predicted against the model's a priori λ_{miss}, measured against the cell's λ_{ref}); hit is the fraction of all turns of a closed run that hit (first turns always miss, so near 0.932 in a good run), the Stage C estimator; stuck means a hit fraction below 0.2 over the evaluation window.

Test	Frozen prediction	Source	Outcome
H200 NVL, SGLang, 300k pool: curve	$\omega_{\text{ref}} = 1.92$ (band 1.65–1.92 over the five cost variants; fluid 1.66–1.96; A100: 3.27 predicted, 3.15 measured); all-miss onset $n_b = 41.3$ (A100: 32.7); 0.5-hit crossing at $n = 37.3 \pm 3$; hit 0.67 (H1) at the peak, $n \approx 32.5$ (0.69 at $n = 32$, the value the freeze record gives). Refuted if $\omega_{\text{ref}} \geq 2.4$, hit$(32) < 0.5$ or hit$(48) \geq 0.5$; the first two are not blind to the first author, who had seen $n \leq 32$.	theory, `h200_300k*.json`; $s = 2.742$ fitted to the H200's all-miss token rate	Measured, not a registered test (window $(1, 1.3)$ λ_{ref}, too narrow for the registration rule): $\omega_{\text{ref}} = 1.89$ (sessions-based 1.99); peak at $n = 32$; crossing ≈ 38.9 (38.8 on the nine-point curve); hit 0.74 at $n = 32$, 0.22 at 48. No rule fires
H200: cliff bracket, $n = 36, 44, 52$	Hit, fluid: 0.56 at $n = 36$ (variants 0.52–0.57), 0 at 44 and 52; H1: 0.53 (0.50–0.53), 0.08, 0.002 (from the frozen curves, not the freeze record). At the original points $n = 40$ and 48: fluid 0.27 and 0, H1 0.28 and 0.01	theory, `h200_300k*.json` (closed curve)	Hit 0.61, 0.32, 0.16 (crossing ≈ 38.9), and 0.46, 0.22 at $n = 40$, 48: closest at 36; from 40 the tail is softer than predicted, so $n_b = 41.3$ is early. Blind in time (36, 44, 52); by access only (40, 48)
H200: from-empty edge	H2 edge 1.39 λ_{ref} (1.24–1.40 over the cost variants); scored on the original E0b runs 17168377–82, not the later reseeds	theory, `h200_300k*.json`	Stable at 1.3, unstable at 1.4 λ_{ref} (nominal): edge in $[1.3, 1.4)$, contains 1.39. Realized rates: ten runs monotone, edge 1.496–1.503, so H2 about 7% pessimistic, as on the A100. Reseeds (post hoc): 1.3 stable in 3 of 3 seeds, 1.4 in 2 of 3 (H2 probability of staying stable: 0.72, 0.48). Original runs blind by access only
H200 NVL, 600k pool	pred2 (jobs submitted at 02:50–02:51 CDT, before its push, not eligible to start before 05:00; first start 05:27): $n_b = 69.9$, as Proposition 2(c) gives from the 600k A100 onset and s; $\omega_{\text{ref}} = 3.20$ (fluid 3.27 against λ_{ref}, 3.16 in model units); crossing 66.6 (H1 64.8); peak at $n \approx 53$; H2 edge 2.57 λ_{ref}, so a registration at 1.5 and 2.0 λ_{ref} with cap 48; there, trapped backlog 458 and 867, token ratio 1.054 and 1.064, NOBURST hit 0.932, capped drain 551 and 830 s	pred2, `h200_600k.json`	Registered (`4d1d431`; 1.5, 2.0 λ_{ref}, cap 48, as predicted). $\omega_{\text{ref}} = 2.98$ (+7.3%, hit); peak $n = 48$, flat top 48–56 (hit); crossing ≈ 71.0 (+4.4, a miss); edge $[2.5, 3.0)$ (hit). Blind in time. E2 (17171020–37, pre-registered): passes at 1.5 and 2.0 λ_{ref} (BURST T I T and T T T; NOBURST good and CAPPED recovered in 6 of 6); trapped backlog 485–509 and 873–913 (within 15%: hit), token ratio 1.042–1.095 and 1.106–1.113 (outside ±0.03 in 5 of 6: a miss), NOBURST hit 0.929–0.936; capped drain not scored
Pool sweep, SGLang, A100, 150k and 600k	$\omega_{\text{ref}} = 1.87$ and 5.47; $n_b = 18.3$ and 61.2; crossing 16.9 and 60.0; H2 edge 1.09 and 4.53 λ_{ref} (second criterion 1.47 and 4.82). Refuted if $\omega_{\text{ref}} \geq 2.5$ or hit$(24) \geq 0.5$ at 150k, or $\omega_{\text{ref}} < 4.5$ or hit$(48) < 0.5$ at 600k. No fitted parameter.	theory, `a100_pool150k.json`, `a100_pool600k.json`; rivals, pred2 `blind_tables.json`	150k: $\omega_{\text{ref}} = 1.68$ (H1 +11.5%, a miss); peak $n = 12$, crossing 16.5 (hits); edge $[1.2, 1.3)$, two steps from H2 and from the second criterion (misses). 600k: 5.71 (−4.2%), peak $n = 48$, crossing 60.1, edge $[4.5, 5.0)$: hits. No refutation rule fires. Blind in time

Table 24: Frozen predictions and their tests: Llama-3.1-8B, the fresh-seed from-empty runs and the basin tests (continued from Table 23, with the same conventions).

Test	Frozen prediction	Source	Outcome
Llama-3.1-8B, SGLang, A100, 300k	Theory, a priori: $M/E_S = 27.8$ for any speed, $n_b = 32.0$, crossing 30.9, $\omega_{\text{ref}} = 3.37$, edge 2.46 λ_{miss}; after the cell's λ_{miss} is measured, every quantity comes from the frozen speed table. Refuted if the crossing lies outside the table's value ±3, or $\mu(48)$ is within 10% of the peak. Simulator, costs scaled to the measured all-miss rate: peak at $n = 20$, $\omega_{\text{ref}} = 3.52$, crossing 30.6, edge 2.5 λ_{miss}, paired test passes at every candidate rate. pred2 recipe, conditional on the registration (pushed untagged at 07:52:42 CDT, after the paired-test jobs were submitted but before any started): trapped token ratio 1.004 and 1.013, BURST backlog 191 and 266, NOBURST hit 0.932, capped drain 1574 and 1869 s.	theory, `llama31_8b_300k*.json`; simulator, tag `r12-llama31-predictions-frozen`, `notes/PREDICTIONS_llama31.md`; conditional, `llama31_8b_300k_conditional*.json`	Registered (`1559f8e`; 1.35, 1.65 λ_{ref}, cap 20). $\lambda_{\text{ref}} = 0.0596$ (theory 0.0619); $\omega_{\text{ref}} = 3.28$ (theory +2.8%, speed table 3.45; hit); peak $n = 20$, μ^* +6.7% (hit); crossing 29.65 (30.9; hit, no refutation), but 0.24 below pred2's tool-call threshold, 29.89, and pred2's nearest-predictor rule picks M/E_{lb} (28.44), by 0.06 (outcome below); edge $[2.0, 2.5)$: theory 2.46 λ_{miss} inside in its own units, 2.55 λ_{ref} in absolute rates (speed table 2.52), a near miss; simulator 2.5, one step high. Closed runs by access only, from-empty runs blind in time. E2 (17170409–26, pre-registered): passes at 1.65 λ_{ref} (BURST T I T) and fails at 1.35 (I D T); NOBURST good and CAPPED recovered in 6 of 6; all six BURST runs at zero hits (descriptive). Simulator's pass at both rates: a miss at 1.35. Conditional: backlog 196–210 and 267–288 (within 10%), NOBURST hit 0.925–0.935, token ratio 1.012–1.050 and 1.030–1.054 (within ±0.03 in 3 of 6, a miss in the other 3); capped drain not scored
Fresh-seed E0b, 300k, seeds 3–5, 2.0 and 2.5 λ_{ref}	Simulator: stable in 3 of 3 at both rates, so the seed-0 bracket is not replicated. Theory (H2): unstable with probability 0.15 and 0.69 per seed.	simulator, tag `r11-basin-reg`; theory, `a100_300k.json`	Not replicated: stable in 3 of 3 at both rates (simulator: 6 of 6 calls). Realized-rate edge, 12 runs: 2.665–2.726 λ_{ref}. H2 pessimistic (all three stable at 2.5: 0.03)
BASIN-1, 300k, 1.65 λ_{ref}, bursts 25, 100 (registered)	Simulator: pass (100 stuck and trapped, 25 good, each in 3 of 3). Theory: stuck with probability 1.000 and 0.042 per seed; pass with probability 0.995.	registration and simulator, tag `r11-basin-reg`; theory, `b1_basin_300k.json`	PASS: 100 stuck and trapped, 25 good, each in 3 of 3 (simulator: 6 of 6 calls). Theory: probability of this outcome 0.879; blind by access only ($n = 100$ runs ended before the push; $n = 25$ runs in progress at it)
BASIN-2, bursts of 40, 50 and 60 (registered)	Theory: stuck with probability 0.139, 0.547 and 1.000 per seed (critical fresh burst 53.4). Rule: bracketed if 40 is good and 60 stuck, each in at least 2 of 3 seeds. pred2, conditioning on each seed's burst (primary): stuck with probability 0.78, 0.86, 1.00 (seed 0), 0.36, 1.00, 1.00 (seed 1) and 0.09, 0.22, 0.81 (seed 2) at 40, 50, 60; the rule holds with probability 0.66 (bands 0.23–0.88; 0.94 for average bursts); secondary, a deterministic level crossing on each seed's exact plan: good, good, good at 40, good, stuck, good at 50 and stuck in all three seeds at 60	registration, tag `r14-basin2-reg`; theory, `b1_basin_300k.json`; pred2, `b2_basin.json`	Bracketed: 40 good and 60 stuck and trapped, each in 3 of 3; 50 stuck in seed 1 only. Per-seed edges $(50, 60]$, $(40, 50]$, $(50, 60]$, so 53.4 lies in two of the three. pred2: rule held; primary per-seed probabilities on the more likely side in 7 of 9, wrong for seed 0 at 40 and 50 (stuck with probability 0.78 and 0.86; both good); their Brier score 0.17 (frozen average-burst layer 0.10, uncalibrated 0.26); secondary deterministic crossing right in 9 of 9. Blind in time

Table 25: Frozen predictions and their tests: the rescue tests, SHED, TOOLSLOW and LPM-INF (continued from Table 24, with the same conventions).

Test	Frozen prediction	Source	Outcome
Rescue R1, 300k, cap 20 engaged at 1800 s, 1.35 and 1.65 λ_{ref} (registered)	Simulator: rescued in 20 of 20 seeds at both rates, release at 3490–5830 and 4050–6050 s. Theory: rescued, release at 3830 and 4360 s (±15%), relapse probability 0.002 and 0.025; the 7200 s deadline is missed if the paused sessions complete below 32% and 42% of their fluid rate. Refuted if NOT RESCUED. A release outside ±15% is a miss by the scoring declaration, but the headline table of `notes/PREDICTIONS_r13_theory.md`, frozen at the same tag, also lists it under "falsified if".	registration, tag `r11-rescue-reg`; simulator, tag `r11-rescue-pred`; theory, `r1_rescue_300k.json`	PASS at both rates: rescued 6 of 6, no relapse, no session shed; BURST controls stuck 6 of 6. Release 3980–4550 s (1.35) and 4430–4920 s (1.65). Simulator: every call held; releases inside its band and within 600 s of each seed's exact prediction in 6 of 6. Theory: verdict held (rescued 6 of 6); release within ±15% in 5 of 6, all late; the exception, 1.35 λ_{ref} seed 0 at +18.8%, is a miss by the scoring declaration and a refutation by the headline table's rule. Blind in time to both
Rescue R4, native pool, cap 64 at 2100 s, 4.0 λ_{ref} (registered)	Simulator: rescued in 16 of 20 seeds, seeds 0–2 rescued; the engage time was moved from 2400 s (13 of 20) after that prediction and before any rescue run. Theory: rescued, release at 5040 s (±15%); the 7200 s deadline is missed if the paused sessions complete below 51% of their fluid rate. Release outside ±15%: a miss by the scoring declaration, and the only falsifier listed in the headline table.	as R1; theory, `r4_rescue_native.json`	PASS: rescued 3 of 3, no relapse, no session shed; BURST controls stuck 3 of 3. Release 5980–6140 s. Simulator: calls held; releases inside its band but 800–1750 s after each seed's exact prediction. Theory: verdict held (rescued 3 of 3); release 19–22% late, outside ±15% in 3 of 3: a miss by the scoring declaration, refuted by the headline table's rule. Blind in time to both
SHED, 300k, BURST at 1.35 λ_{ref}, arrivals stopped for τ from 1800 s (registered)	Rule: $\tau = 600$ s stuck and $\tau = 3600$ s good, in 2 of 2 seeds; sessions refused (about 58 and 348) reported against none for the cap. Simulator: a full stop from 1800 s lasting 3600 s rescued 10 of 10, dropping 328–378 sessions; one lasting 3000 s rescued 8 of 10. pred2: the shortest rescuing stop lasts 1795 s (Eq. (2) from RR's 161 sessions at 1800 s; RR alone: 1928 s); $\tau = 600$ s stuck (1.00), $\tau = 3600$ s good (0.998); the rule holds with probability 0.997.	registration, tag `r14-extra-reg`; simulator, tag `r11-rescue-pred`; pred2, `shed.json`	PASS (17169908–11): $\tau = 600$ s stuck in 2 of 2 (hit 0.000; seed 1 indeterminate by the slope rule, which this rule does not use), $\tau = 3600$ s good in 2 of 2 (hit 0.933, 0.930); 59, 56 and 355, 378 sessions refused, as pred2's protocol check; the R1 cap refused none. pred2 right; the simulator's 3600 s stop held (2 of 2 good; 355 and 378 refused, inside its 328–378)
TOOLSLOW, 300k, NOBURST, 1.35 λ_{ref}, $Z + \delta$ in $[1200, 2100)$ s (registered)	Rule: $\delta = 10$ s good and $\delta = 30$ s stuck, each in at least 2 of 3 seeds. pred2: $\delta = 10$ s good with probability 0.71 per seed, $\delta = 30$ s stuck (1.00); the rule holds with probability 0.80 (band 0.63); critical δ 16.8 s (fluid), 16.4 s (stochastic).	registration, tag `r14-extra-reg`; pred2, `toolslow.json`	Rule not met (17169902–07): $\delta = 10$ s good in 3 of 3 (hit 0.930–0.934); $\delta = 30$ s stuck in 1 of 3 (seed 2 trapped, hit 0.000; seeds 0 and 1 good, 0.931 and 0.930). pred2's stuck call at 30 s wrong for seeds 0 and 1, its rule (0.80) failed; the critical δ is not bracketed
LPM-INF, 300k, BURST, 1.65 λ_{ref}, no 128-request fallback (exploratory)	Simulator: no collapse on seeds 0–2 (token hit fraction 0.08–0.10), including seeds 0 and 1, on which stock LPM collapsed; the frozen rule reads this as the fallback causing that collapse, and the registered rule still calls each run trapped.	tag `r11-lpminf-pred`, `configs/r11_lpminf_predict.yaml`	Consistent with the rule: no collapse on seeds 0, 1 (token hit 0.59, 0.42; stock LPM 0.000 in 4 of 4); seed 2 uninformative (queue ≤ 128). No run recovered. Simulator: direction right, level missed

cost variants give 0.52–0.57, and H1 0.50–0.53); from $n = 40$ on, H1 gives 0.28, 0.08, 0.01 and 0.002 at $n = 40$, 44, 48 and 52, and the measured turns-based μ is 1.12–1.29 times the H1 prediction. The frozen notes expected Assumption MF, which does not concentrate at this pool on the H200, to bias the peak upward; the peak was matched (H1 0.371 sessions/s against 0.367 turns-based), and the miss is in the tail instead (§H.6).

GPU generation: the 600k pool. The 600k H200 cell (Stage C 17169672–80, E0b 17169682–87) repeats the H200 cell with a 600,000-token pool and the H200 300k E0a as λ_{ref} (0.194 sessions/s). Its jobs were submitted at 02:50–02:51 CDT, before pred2's push, but could not start before 05:00 and first started at 05:27, so pred2's predictions for it are blind in time. Closed curve at $n = 32$, 40, 48, 56, 64, 72, 80, 96 and 300: μ 0.427, 0.522, 0.592, 0.581, 0.477, 0.403, 0.298, 0.269 and 0.232 sessions/s (turns-based 0.412, 0.505, 0.577, 0.569, 0.466, 0.379, 0.281, 0.254 and 0.231), hit fraction 0.930, 0.927, 0.897, 0.804, 0.654, 0.478, 0.227, 0.140 and 0.000. The rising branch matches H1 within 4% up to $n = 48$ (0.419, 0.518, 0.599) and the peak within 7.3%; at $n = 72$, 80 and 96 the measured turns-based μ is 1.45, 1.36 and 1.26 times H1, and the hit fraction at $n = 72$, 80 and 96 is 0.48, 0.23 and 0.14 against H1's 0.15, 0.02 and 0.00, so the predicted onset, $n_b = 69.9$, comes early, as at 300k; H2's probabilities of instability were 0.37 at 2.5 and 0.97 at 3.0 λ_{ref}. From empty the engine was stable at 1.25, 1.5, 1.75, 2.0 and 2.5 λ_{ref} (final queue 0) and unstable at 3.0 (final queue 620, rising by 433 over the last 1500 s). Seed 0's plans arrive 5–8% above nominal (5–6% for the two runs that bracket the edge), so in realized rates the bracket is $[2.64, 3.15)$, above H2's 2.57: a hit on the frozen grid rule, pessimistic in realized rates, as on the A100. The registration (`configs/agentload_prereg_2026-10-31_h200_p600k.yaml`, commit `4d1d431` at 09:26:38, pushed 09:26:41) fills the window $(1, 2.5)$ λ_{ref}, the rates 1.5 and 2.0 λ_{ref} and the cap 48, flagged ambiguous because $\mu(56)$ is within 1.8% of $\mu(48)$; its 18 paired-test jobs (17171020–37) were submitted at 09:27:44. Against the 300k H200 cell, doubling the pool raised the peak 1.53-fold in completed sessions (1.57-fold in the turns-based peak ratio), moved it from $n = 32$ to 48, and moved the from-empty edge from 1.3 to 2.5 λ_{ref}.

GPU generation: the 600k paired test. The 18 jobs (17171020–37, seed-major, one 8700 s arm per job) were submitted 63 s after the registration reached GitHub, so the test is pre-registered; all completed (Slurm state COMPLETED, exit 0), and every run carries the registration's SHA-256. The registered analysis (`results/agentload_analysis_burst2/20261101-154448/` in `results/nova/h200p600k_e2_partB3_1717102x_pulled_20261101-154520/`; the runs are in the five `h200p600k_e2_part*` pulls) passes at both rates, with valid pairing. For seeds 0, 1 and 2 the BURST runs at 1.5 λ_{ref} were trapped, indeterminate and trapped, with uncached token rates of 1.095, 1.042 and 1.093 times the all-miss rate (29,866 tokens/s), mean backlogs of 509, 486 and 485 sessions and backlog slopes of 0.0759, 0.0478 and 0.0601 sessions/s against a threshold of 0.0485; at 2.0 λ_{ref} all three were trapped (1.113, 1.106, 1.112; 913, 873, 909 sessions; slopes 0.127, 0.0995, 0.112 against 0.0969). All six had a hit fraction of 0.000 over the evaluation window. The indeterminate run is stuck in the same way, but its slope is 1.3% below the threshold, so the pass at 1.5 λ_{ref} rests on 2 of 3 seeds. NOBURST and CAPPED had hit fractions of 0.929–0.936 and mean backlogs of 22.5–34.1 sessions. λ_{ref} is the 300k cell's E0a, reused because the all-miss rate does not depend on the pool; the cell has no E0a of its own. Against pred2's frozen block at the registered points, the trapped backlog (458, 867) is within 15% of every run (+0.6% to +11.2%), the NOBURST hit fraction (0.932) within 0.004, and the trapped token ratio (1.054, 1.064) 0.038–0.049 below five of the six runs, outside its ±0.03 tolerance; its fresh critical burst, 114 and 91 sessions, is below the registered 200.

Pools and a second model. The pool sweep repeats Stage C and E0b on the A100 with pools of 150k and 600k tokens, with no fitted parameter; its 150k from-empty edge discriminates between H2 and a second edge criterion, which predict 1.09 and 1.47 λ_{ref}. The Llama-3.1-8B cell keeps the engine, the GPU and the 300k pool. The model's a priori costs for it come from published architecture ratios; the pool part $M/E_S = 27.8$ does not depend on the model's speed; and once the cell's all-miss rate is measured, every predicted quantity is read from a frozen table indexed by the speed factor.

Pools: outcome. The 18 pool-sweep jobs (Stage C 17168864–69, E0b 17168870–81; every server log reports the requested pool) were submitted at 22:58 CDT on 2026-10-30, held until 02:30 and first started at 06:50:13, 4 h 45 min after the first prediction set and 2 h 30 min after pred2 were pushed; pred2's lookups were tabulated without the per-job n or rates. Closed curves at 150k, $n = 6$, 8, 10, 12, 14, 16, 20 and 24: turns-based μ 0.070, 0.091, 0.112, 0.120, 0.113, 0.099, 0.066 and 0.063 sessions/s, hit fraction 0.932, 0.934, 0.915, 0.842, 0.713, 0.555, 0.133 and 0.049; at 600k, $n = 24$, 32, 40, 48, 56, 64, 80 and 96: turns-based μ 0.253, 0.320, 0.375, 0.408, 0.239, 0.082, 0.072 and 0.069 sessions/s, hit fraction 0.929, 0.928, 0.930, 0.921, 0.775, 0.243, 0.135 and 0.006. From empty (seed 0, 3000 s) the engine was stable at 1.1 and 1.2 and unstable at 1.3, 1.45, 1.6 and 1.8 λ_{ref} at 150k, and stable at 2.5 to 4.5 and unstable at 5.0 λ_{ref} at 600k, monotone at both; seed 0's plans arrive 6–14% above nominal, so in realized rates the brackets are $[1.36, 1.46)$ and $[4.80, 5.32)$, both above H2's edge. H2 gave the stable 1.1 and 1.2 λ_{ref} runs at 150k probabilities of instability of 0.51 and 0.68; the log-likelihoods of the six outcomes are −2.14 under H2 and −2.95 under the second criterion at 150k, and −0.93 and −0.54 at 600k. At 150k H1 overstates μ inside the collapse by 19–28% ($n = 14$–20), and the closed collapse is shallow: $\mu(300)$ is 0.90 μ^*, while the open system's edge lies at 1.2–1.3 λ_{ref}. At 600k the tail is soft (hit 0.135 at $n = 80$, where the model gives 0). Read from pred2's frozen tables, the rivals for the 0.5-hit crossing are M/E_S (13.6 and 56.1), Denning's M/E_{lb} (14.2 and 56.9), Che's approximation with the tool time as the gap

(26.5 and 105.9) and Yao et al.'s fixed point closed by Little's law (23.9 and 95.7), against 16.5 and 60.1 measured, so by the frozen rule the frozen $n_{1/2}$ wins at both pools, and the declared test of the tool-call term, blind in time here, passes at both, by 0.57 and 1.49 sessions (thresholds 15.96 and 58.65); the two exogenous-gap closures give hit fractions of 0.55 and 0.50 at $n = 24$ (150k) and 96 (600k), where the engine measured 0.049 and 0.006. Each point is one run, and the from-empty grid steps differ (0.1–0.2 at 150k, 0.5 at 600k). In units of each GPU's λ_{ref}, the H200's peak ratio was 0.60 and 0.52 of the A100's at 300k and 600k, against 0.59 and 0.58 predicted (Table 22); over its six cells the midpoint of the measured edge bracket lies at 0.71–0.93 of the measured peak ratio.

A second model: outcome. Stage C (17166814–16), E0a (17166823, 29, 31, and the 64-session check 17166833) and E0b (17169565–70) ran SGLang 0.5.22 on an A100 with `NousResearch/Meta-Llama-3.1-8B-Instruct` at revision `d10aef7`, whose four weight shards have the same SHA-256 as `meta-llama/Llama-3.1-8B-Instruct` (Llama 3.1 Community License); only the chat template differs, and the client sends token IDs. Its KV is 2.29 times Qwen2.5-7B's per token, but the pool is counted in tokens, so its session capacity is unchanged. E0a gives $\lambda_{\text{ref}} = 0.0596 \pm 0.0020$ sessions/s turns-based and 9353 all-miss prefill tokens/s, 0.83 times Qwen's (64-session check: 1.018). Closed curve at $n = 16$, 20, 24, 28, 32, 40, 48, 96 and 300: μ 0.166, 0.202, 0.195, 0.123, 0.053, 0.037, 0.041, 0.051 and 0.099 sessions/s (turns-based 0.164, 0.195, 0.191, 0.127, 0.063, 0.053, 0.055, 0.065 and 0.100), hit fraction 0.931, 0.926, 0.878, 0.701, 0.215, 0.011, 0.003, 0 and 0; the crossing is 29.65 (29.4 in cached tokens). From empty: stable at 1.25, 1.5, 1.75 and 2.0, unstable at 2.5 and 3.0 λ_{ref}. The registration fills the window $(1, 2.0)\,\lambda_{\text{ref}}$, the rates 1.35 and 1.65 λ_{ref} and the cap 20, flagged ambiguous because $\mu(24)$ is within 3.3% of $\mu(20)$. The frozen speed table at the measured all-miss rate ($s = 9353/9559 = 0.978$) gives $\mu^* = 0.206$ (H1), peak ratio 3.45, crossing 30.9 and edge 2.52 λ_{ref}. The simulator (round 12, pushed at 02:14:06) predicted the peak at $n = 20$ and the cap of 20 in both batching modes, a peak 7% high and a later cliff (crossing 30.6; hit 0.38 at $n = 32$, against 0.22), and in its primary (mixed) mode the edge one grid step high and the rates 1.5 and 2.0 λ_{ref}; its separate mode predicted the edge and the registered rates. The measured crossing, 29.653, falls 0.24 sessions short of the threshold of pred2's test of the tool-call term, 29.89 (with the speed table's n_b the threshold is 29.84, still above it), so that test fails. That test and pred2's nearest-predictor rule were declared after this curve had been combined (from 03:14; the runs at $n = 28$ and 32, which set the crossing, at 03:33), though by pred2's record its agents read no Llama result. $M/E_{\text{lb}} = 28.444$ lies 1.209 sessions from the crossing, the a priori frozen crossing (30.921, the value pred2's rule lists) 1.268 and the speed table's (30.856) 1.203, so the nearest-predictor rule picks M/E_{lb} on the listed value, by 0.059 sessions, and the frozen crossing, by 0.006 sessions, on the speed-table value; either way the capacity ratio does about as well as the model here. The theory's and the simulator's predictions were pushed while the closed runs were in progress, so for the curve both are blind by access only, and for the from-empty runs both are blind in time (Appendix N gives the times).

A second model: the paired test. The 18 jobs (17170409–26) were submitted at 07:50:02 CDT, 47 s after the registration reached GitHub (07:49:15), so the test is preregistered; all completed (Slurm state COMPLETED, exit 0) and passed the in-job registration and pool checks. The registered analysis (`results/agentload_analysis_burst2/20261101-154441/` in `results/nova/llama31_e2_part5_verdict_pulled_20261101-154525/`) passes at 1.65 λ_{ref} and fails at 1.35 λ_{ref}. For seeds 0, 1 and 2 the BURST runs at 1.35 λ_{ref} were indeterminate (uncached token rate 1.050 times the all-miss rate, slope 0.0052 sessions/s against a threshold of 0.0104, mean backlog 210), draining (1.034; slope -3×10^{-6}, backlog 196, falling to 181) and trapped (1.012; 0.0157; 208); at 1.65 λ_{ref} trapped (1.044; 0.0243 against 0.0194; 288), indeterminate (1.030; 0.0114; 267) and trapped (1.054; 0.0245; 277). All six had a hit fraction of 0.000 over the evaluation window; the slope test, which the simulator flags as fragile near λ_{miss}, separated them. NOBURST had hit fractions of 0.925–0.935 and backlogs of 7–10 sessions, and CAPPED could not be told apart from it in the window. The simulator (round 12, primary mode) had predicted a pass at both rates, with 9 and 8 of 10 seeds trapped, token ratios of 0.985–1.068 and BURST backlogs of 181 and 252; the registration-conditional predictions (pushed at 07:52:42 and 07:52:56, before any of these jobs started at 12:41) gave token ratios of 1.004 and 1.013, backlogs of 191 and 266 (within 10% of every run, +0.3% to +9.7%) and a NOBURST hit fraction of 0.932.

The basin. Two registered BURST-only tests at 1.65 λ_{ref} on the 300k pool vary the burst size: BASIN-1 with 25 and 100 sessions and BASIN-2 with 40, 50 and 60. The theory predicts whether a run is stuck, with a hit fraction below 0.2 over the evaluation window; it does not model the slope test of the registered trap rule, which is co-primary only for BASIN-1's 100-session cell. The model's critical fresh burst is 53.4 sessions, and its per-seed probabilities of a stuck run are 0.04, 0.14, 0.55 and 1.0 for 25, 40, 50 and 60 or more sessions; the stationary-composition estimate, 21.3 sessions, would have 40 stuck. BASIN-2's frozen rule calls the boundary bracketed if 40 stays good and 60 is stuck, each in at least two of three seeds. The second prediction set (pred2, pushed at 04:20:20 CDT on 2026-10-31; the nine BASIN-2 jobs were submitted at 04:21) conditions these probabilities on each seed's burst, rebuilt with the client's own plan generator. Seed 0's first 40 burst sessions are long and seed 2's short, so the probabilities of a stuck run at 40, 50 and 60 sessions become 0.78, 0.86 and 1.00 for seed 0, 0.36, 1.00 and 1.00 for seed 1, and 0.09, 0.22 and 0.81 for seed 2; the rule then holds with probability 0.66 (0.23–0.88 over the ways of mapping a plan to a burst size), against 0.94 with every burst at its mean composition. The critical burst and the stationary-composition estimate are both

defined at n_2, where the quasi-static model is least reliable and a burst's fate depends on its composition as well as on $\mu(n)$ (§H.6), so BASIN-2 tests the heuristic H3, not a consequence of the propositions.

The basin: BASIN-1 outcome. Section G.4 reports the outcome and §I scores it. The 100-session runs were stuck (hit fraction 0.000 over $[5700, 8700)$ s) and also trapped by the co-primary slope rule, in 3 of 3 seeds. BASIN-1 does not test the critical burst of 53.4 sessions; BASIN-2 does. The registered analysis ran at `19c58e9`, which contains BASIN-2's rule (`621d88f`) and an analysis-only change (one vote per seed; only runs bound to their registration count), both made after BASIN-1's tag; the code at the tag (`9b67c26`) gives the same decision and per-run values.

The basin: BASIN-2 outcome. The nine runs (17169893–901, submitted at 04:21:40–41 from a clone at the registration tag, started 10:10–12:41 and pulled at 15:42) are bound to their registrations, and the registered analysis (data in Table 19) calls the boundary bracketed: with 40 sessions every seed was good (RECOVERED; hit fraction 0.934, 0.934 and 0.925 over $[5700, 8700)$ s), with 60 every seed was stuck (hit 0.000) and trapped, and with 50, which the rule does not use, seed 1 was stuck and trapped while seeds 0 and 2 stayed good (0.933 and 0.924). The analysis ran at `4dd21e0`, which includes `19c58e9`, an analysis-only change pushed at 03:12:59, after the registration tag and before submission, that counts one vote per seed and only runs bound to their registration; the code at the tag gives the same bracket, curve and per-run values. Each seed's arrivals are common random numbers across sizes, and along 0, 25, 40, 50, 60, 100 and 200 sessions each seed switches from good to stuck once; the burst of n uses the first n arrival times and session specifications of the 200-session draw, so the chain is nested as sets, not by session identity. Descriptively, the stuck runs' hit fraction stayed below 0.2 from the 1400 or 1500 s window on; in the good runs the lowest 100 s window was 0.70–0.83 and the next one above 0.8; and every burst session had finished by 1680 s in the good runs and by 4719 s in the stuck ones, before the evaluation window, so the stuck runs stay at zero hits on the base sessions alone, which the no-burst runs serve at 0.92–0.93. Against pred2 (pushed at 04:20:20, 80 s before the submission): the rule held (probability 0.66); the primary per-seed probabilities of a stuck run for seed 0, 0.78 at 40 and 0.86 at 50, were on the wrong side for both of its good runs, and the other seven were on the more likely side; over the nine runs their Brier score is 0.174, against 0.096 for the frozen average-burst layer, which ignores the plans, and 0.259 for the uncalibrated mapping (declared scores; the frozen composition-averaged column, which the declaration does not name, scores 0.111); and the secondary deterministic level crossing on the exact plans called all nine runs. pred2's declared claim that seed 0 is the most trap-prone at 40 sessions was not borne out: no seed was stuck at 40, and seed 1, the only one stuck at 50, has the lowest edge. The critical burst of 53.4 lies inside the edge intervals of seeds 0 and 2, $(50, 60]$, and outside seed 1's, $(40, 50]$, while the 50% points of the committor and of the stuck probability (48.4–49.5) lie inside seed 1's only, so no single size fits all three seeds. The round-7 simulator trapped 6 of 10 runs at 50 sessions; the engine trapped 1 of 3. With three seeds per size, 0 of 3 and 3 of 3 have 95% intervals $[0, 0.71]$ and $[0.29, 1]$.

Fresh-seed from-empty runs: outcome. Sections G.1 and I and Appendix L report the outcome: both rates stable in 3 of 3 fresh seeds, so the frozen replication rule is not met, and in realized rates the edge lies between 2.665 and 2.726 λ_{ref}. In realized arrivals the fresh seeds received 2.01, 2.15 and 1.97 λ_{ref} and 2.51, 2.67 and 2.47 λ_{ref}. The second edge criterion in the frozen 300k file did better than H2: its probabilities of instability, 0.03 at 2.0 and 0.37 at 2.5 λ_{ref}, give all six runs stable a log-likelihood of -1.47, against -4.01 under H2, and all three stable at 2.5 λ_{ref} a probability of 0.25. That file (tag `r13-theory-pred`) was pushed before five of the six runs ended but declares no prediction for this test.

Rescue and shedding. Two registered tests engage a cap inside an established trap and release it once the gate has been empty for 300 s: R1 on the 300k pool (cap 20 at 1800 s, at 1.35 and 1.65 λ_{ref}) and R4 with the native pool (cap 64 at 2100 s, at 4.0 λ_{ref}). The simulator and the model both predict rescue. At the fluid rate of the paused sessions, whose next turns miss, the model predicts release at 3830, 4360 and 5040 s (±15%; with H1, 3920, 4480 and 5250 s); it predicts release before the 7200 s deadline only if those sessions complete at no less than 32, 42 and 51% of that rate. The gate pauses sessions only at tool-call boundaries and defers work rather than dropping it. Pausing whole programs at tool boundaries is ThunderAgent's and NVIDIA Dynamo's mechanism [35, 60]; CONCUR cuts its window of active agents multiplicatively when it detects thrashing (hit rate below 0.2 with KV usage above 0.5) to exit that regime, and MISA-T contracts its cap temporarily on a confirmed hit-rate decline, both in closed or bounded populations [19, 51]; KAIROS bounds aggregate context and, when bursty arrivals have already broken the bound, defers new agents and boosts the clock, but reports no recovery from an established trap [119]; inhibiting new traffic until a bistable channel returns to its lower state was proposed by Carleial and Hellman [15], and shedding load is the usual response in production [52]. Lu et al. rescue an established trap in simulation by activating their controller late (and leaving it on), prevent it on hardware by terminating the burst sessions at the end of the burst, and report one hardware run in which CONCUR recovered slowly after its hit rate fell [76]. The new parts here are a registered, replicated rescue of an established zero-hit trap on the engine at the same offered load without shedding, a measured test that the good state persists after the cap is released, and a rescue condition and release times frozen beforehand; §G.3 reports the outcome. The SHED test measures the alternative: arrivals stop for $\tau = 600$ or 3600 s from 1800 s, refusing about $\lambda\tau = 58$ or 348 sessions, against none for the cap.

Rescue: outcome. Sections G.3 and I report the outcome and its scoring; the per-run values follow (Table 21). The simulator's release times on the exact plans were 3960, 3470 and 3940 s at 1.35 λ_{ref} and 4900, 4440 and 4280 s at 1.65, against the engine's 4550, 3980 and 4400 s and 4920, 4430 and 4570 s, and 4250, 5180 and 4410 s for R4, against 6000, 5980 and 6140 s; all nine releases lie inside its 20-seed bands. Against the model's 3830 and 4360 s, the R1 releases were +18.8, +3.9 and +14.9% and +12.8, +1.6 and +4.8% late; against 5040 s, the R4 releases were +19.0, +18.7 and +21.8% late (against the H1 value, 5250 s: +14.3, +13.9 and +17.0%). The engine's first phase in R4 was slower than the fluid rate but far from collapsed. The smoke run ended before the model's push, but the model made no prediction for it, and by their record the agents that derived the model had no Nova access and opened no rescue output before the push.

Causes. TOOLSLOW lengthens every tool call that starts in $[1200, 2100)$ s by $\delta = 10$ or 30 s in the NOBURST arm at 1.35 λ_{ref}, a trigger that involves neither a burst nor a lowered clock. Its registered rule expects the 10 s slowdown to leave the engine good and the 30 s slowdown to leave it stuck, each in at least two of three seeds. In the frozen model (pred2) the slowdown acts through capacity and population: for δ above 13.7 s the slowed curve's peak lies below $\lambda = 0.0966$ sessions/s, so it has no good state (at $\delta = 30$ s the peak is the all-miss level $\mu_b = 0.0718$ sessions/s); at $\delta = 30$ s the population reaches 46.9 sessions by 2100 s, above $n_2 = 32.2$, while at $\delta = 10$ s it reaches 21.5, near the slowed curve's good state (21.8 sessions, against 8.5 without the slowdown). A pass would show that a temporary increase in tool latency, with no burst, can trigger the trap; it would not separate the longer gap from the capacity loss and the larger population that come with it. LPM-INF disables stock LPM's 128-request fallback (§G.6) with a job-local hook that raises the limit to 10^9 and changes nothing else; the BURST arm at 1.65 λ_{ref} is repeated on seeds 0–2 with byte-identical arrival plans. The simulator predicted (pushed at 21:02:46 CDT on 2026-10-30, 65 minutes before the jobs were submitted) that LPM then avoids the all-miss collapse on the two seeds on which stock LPM collapsed, in a partial-hit state that the registered rule still calls trapped.

SHED and TOOLSLOW: outcome. The ten jobs (17169902–11) were submitted at 04:21:42–43 CDT on 2026-10-31, after the registrations (pushed at 02:28:09) and after pred2 (04:20:20), so both tests are pre-registered and pred2's predictions for them are blind in time. Every run is bound to its registration and paired with its committed 1.35 λ_{ref} control of the same seed; the registered analysis (`analysis/r14_cells.py` at `db24efa`, an analysis-only fix made before any job) is in `analysis/agentload_analysis_r14/20261101-154909/` in `results/nova/toolslow_shed_1716990x_pulled_20261101-154800/`. STUCK is a hit fraction below 0.2 over $[5700, 8700)$ s; GOOD is RECOVERED, or a hit fraction above 0.8 with a backlog slope of at most $0.5(\lambda - \lambda_{\text{ref}})$. SHED passed: with arrivals stopped for 600 s both runs stayed stuck (hit fraction 0.000; seed 0 trapped, seed 1 indeterminate by the slope rule, with 219 and 168 requests outstanding at the end), and with 3600 s both were good (0.933 and 0.930, 1–2 outstanding); the same-seed BURST controls stayed stuck. The stops refused 59 and 56, and 355 and 378, sessions, equal to pred2's protocol check, which the arrival plans fix; the R1 cap at the same rate refused none. TOOLSLOW did not meet its rule: with $\delta = 10$ s all three runs were good (hit fractions 0.930–0.934, as their NOBURST controls; 923–1034 tool calls slowed), and with $\delta = 30$ s seeds 0 and 1 were good (0.931, 0.930) and seed 2 trapped (0.000, slope 0.0233 sessions/s, 127 outstanding at the end; 664–770 calls slowed). pred2 had predicted good at 10 s with probability 0.71 per seed and stuck at 30 s with probability 1.00, the rule with 0.80, and ranked seed 0 the most trap-prone at 30 s (49 sessions at 2100 s, against 37 and 39); seed 0 recovered. Either the slowed engine kept a good state that the fluid layer says it lacks, or the population it reached did not keep the engine stuck once the slowdown ended; these runs do not separate the two. The hit fractions of all ten runs were recomputed from the request logs and agree; the slopes and slope labels were not recomputed independently.

LPM-INF: outcome (exploratory). Appendix R gives the outcome in full: on the two informative seeds LPM without its fallback did not collapse, no run recovered by the registered rule, and the simulator got the direction and missed the level.

T Simulator studies

T.1 Robustness of the paired test

The real test fixes one workload, one burst size and one horizon; we varied each in the calibrated simulator (mixed batching). Each workload gets its own window $[1, hi]$ in multiples of its own λ_{miss} (hi: the largest multiple at which all 10 from-empty runs stay stable) and is tested one third and two thirds of the way across it; a point passes if each arm meets its criterion in at least 7 of 10 seeds, counted separately per arm (the registered real-engine rule instead counts seeds in which all three arms succeed). The repository holds the per-run summaries of these simulations, from which every number below is computed, but not the 100 s window series behind them.

Tool-time laws. With exponential tool times of mean 1, 2 and 5 s, a lognormal law (mean 5 s, coefficient of variation 2) and a bimodal law (80% at 1 s, 20% at 20 s), λ_{miss} stays within 0.0718–0.0730 sessions/s: with the token profile fixed, it does not depend on the tool-time law. Shorter tool times raise the peak ($\mu^*/\lambda_{\text{miss}}$ is 5.25, 4.57 and 2.97 for means of 1, 2 and 5 s) and widen the window (hi = 3.0, 2.5, 2.0); a heavy-tailed or a bimodal law of about the same mean (5 s and 4.8 s) leaves the edge at 2.0. The test passes at all 10 points (Fig. 11): NOBURST and CAPPED succeed in 10 of 10 seeds everywhere, and BURST is trapped in 7 to 10 of 10.




Figure 11: The paired test across tool-time laws (simulator). Gray bar: from-empty window $[1, hi]$ in multiples of each law's λ_{miss}. Markers: test points, filled = pass, crossed = fail (each arm counted separately, in ≥ 7 of 10 seeds); number = BURST runs trapped of 10. Top row: the real engine (3 seeds; registered rule, all three arms in at least 2 of the same seeds). Bottom row: labelled post-hoc rerun of the mini-SWE-agent full workload. The two mini-SWE-agent full-workload rows use different units: the declared row multiples of its declared λ_{miss} (0.0120 sessions/s), the post-hoc row multiples of the long-window λ_{miss} (0.0141 sessions/s), in which the declared 1.65, 2.35 and 3.0 are 1.40, 1.99 and 2.55.

Tool times from real agent traces. We replaced the tool-time law by empirical tables from SyFI TraceLab, real sessions of two commercial coding agents [123], and from mini-SWE-agent v2.0.0 [102, 113] on the Verified subset of SWE-bench [23, 59], whose tool times are far more dispersed than ours (coefficients of variation 4.3–4.7 against 1). λ_{miss} moved by -0.8% to $+1.3\%$. The peak moved from 20 in the exponential control to 32 (TraceLab per turn), 40 (idle gap) and 24 (mini-SWE-agent), and the cap to 32, 40 and 20; at every point of these three laws the CAPPED arm recovered in 10 of 10 seeds. Of the six points of the three laws, five passed; the failure, TraceLab per turn at 1.40 λ_{miss}, is the slope rule: 6 of 10 BURST runs met it, all 10 were stuck below a hit fraction of 0.2, and on 20 fresh seeds (post hoc) 17 met it. Appendix R gives the trace statistics and a secondary workload with mini-SWE-agent's turn and token counts.

Burst size and horizon. At 1.35 and 1.65 λ_{miss}, a burst of 25 sessions never traps (0 of 10), 50 is a coin flip (5 and 6 of 10 trapped), and from 100 up every run is stuck below a hit fraction of 0.2. In runs extended to 30,000 s after the burst, no trapped BURST run ever returned to a 100 s window above a hit fraction of 0.5, all 20 ended with 468 to 1065 waiting requests, and no NOBURST run ever exceeded 50. The first-principles model's critical fresh burst, 53.4 sessions at 1.65 λ_{ref} (§H), lies between the simulator's coin-flip size and the size from which every run is stuck, a sweep that the agents who derived the model knew when they froze it (Appendix N). On the engine, the registered test BASIN-1 found 25 sessions good and 100 stuck, and trapped by the registered rule, in 3 of 3 seeds each, as both the simulator and the model predicted, which places the boundary between 25 and 100 sessions; BASIN-2 found 40 sessions good and 60 stuck in 3 of 3 seeds and 50 trapped in 1 of 3 (the simulator at 1.65 λ_{miss}: 6 of 10), which puts the boundary between 40 and 60 sessions (§G.4).

The slope rule is the fragile part. Over the 100 BURST runs of the tool-time test the registered rule labels 90 trapped and 10 indeterminate, while all 100 are stuck at zero hits with an all-miss token rate. At 1.35 λ_{miss} with 20 fresh seeds, 3 are indeterminate (Wilson interval [0.05, 0.36]; median slope $0.77(\lambda - \lambda_{\text{miss}})$ against a threshold of 0.5), so the real engine's one in three there is not surprising. The threshold presumes that a trapped engine completes sessions near λ_{miss}, but the registered SGLang BURST runs at 300k completed 1.13–1.35 λ_{ref} in the evaluation window (§E.3); the indeterminate one, seed 1, received 1.27 λ_{ref} there instead of the nominal 1.35 and completed 1.28, so its backlog stayed flat. Over 31,200 s runs the rule labels only 10 to 12 of 20 stuck BURST runs trapped, depending on the window. Post hoc, a rule on the hit fraction alone would have called all six real E2 BURST runs trapped, and all six exploratory vLLM runs, of which the registered rule calls four trapped (§G.2); the vLLM runs reuse the SGLang runs' seeds, and both of their indeterminate runs are again seed 1, so the two engines' labels are not independent. In the pre-registered tests on Llama-3.1-8B and on the 600k H200 every BURST run was again at zero hits at the all-miss token rate or above, and the rule called 3 and 5 of 6 trapped; it fails the Llama test at 1.35 λ_{ref}, where two of three stuck runs missed the slope threshold (§I). We report the registered rule. Its token criterion has the opposite weakness at high multiples of λ_{miss}, where a trapped engine prefills more than the all-miss token rate: 1.106–1.124 times it at 4.0 λ_{ref} with the native pool, against a tolerance of 1.15 (§G.2).

The cap must follow the measured curve. The right cap, 20 for the workload of record at 300k, moves to 32 or 40 with the TraceLab tool-time laws (it stays at 20 with mini-SWE-agent's) and to 64 with the native pool, where it recovered in 6 of 6 registered runs. With mini-SWE-agent's full workload the peak falls to 12, and a cap of 20 would sit past the peak; a cap c above the new peak leaves $(\mu(c), \mu^*)$ open in the quasi-static model (§E.4).

T.2 Published mechanisms in the earlier simulator

In the fluid model of §E.3 the recovery threshold from deep congestion is at most μ_∞, so a mechanism can raise it only as far as it raises μ_∞. We compare mechanisms by $\mu(300)/\lambda_{\text{miss}}$ as a proxy for μ_∞ (Fig. 12) in the earlier, uncalibrated simulator. Each rule was compared, by reading the code and not running it, with the released code where it exists (PEEK; the Continuum preview, which omits the paper's estimator) or with the paper (CONCUR, for which we found no code); where a difference was small and unambiguous we added a projection of the released rule beside the historical row, and the differences that remain are stated below. That simulator's assumed costs are about 1.5 times the fitted ones (λ_{miss} 0.0474 against 0.0722 sessions/s), and its curve peaks at 4.07 times its own λ_{miss}, against about 3.0 in the calibrated simulator and $3.26\,\lambda_{\text{ref}}$ on the engine. Its absolute rates therefore do not carry over. As in Stage C, all sessions start at $t = 0$, but each run is measured over 25,000 s after a 5000 s warmup (static caps: 30,000 s), about four mean session lifetimes; FCFS reads $1.04\,\lambda_{\text{miss}}$ over the first half of the window and 1.01 over the second, so the synchronized-start bias of §J is a few percent here. These are results about the rules in a workload with private prefixes and exponential 5 s tools, not benchmarks of the named systems.

Orderings. FCFS gives 1.024 ± 0.020 with hit fraction 0.000 and the GPU always busy; with the 1.5% standard error of λ_{miss} included the interval is 1.02 ± 0.04, consistent with Proposition 6, which covers this simulator's request-level FCFS. Pure LPM (without SGLang's 128-request fallback) gives 1.174 ± 0.023 and recovers from 300 cold sessions over 150,000 s up to $1.1\,\lambda_{\text{miss}}$, not at 1.25. PEEK [112] protects prefixes needed by queued requests and adds a cache-aware scheduler. Our earlier rows implemented only the protection under FCFS order. As a soft ranking, which is how PEEK's eviction hook protects (finite priorities), it gives the same throughput as FCFS seed for seed: queued requests' KV is protected but still evicted before FCFS admits them (2,831–3,128 such evictions per run), so no request is admitted with its KV, consistent with Proposition 6. A hard pin, a counterfactual PEEK does not apply, gives 0.919. The released scheduler serves warm requests first; projected onto single-session prefixes with its eviction score, it gives 1.176 ± 0.021, equal to pure LPM within 0.001 ± 0.014, and recovers from none of 5 bursts at $2\,\lambda_{\text{miss}}$. Here PEEK is an LPM-class ordering, not FCFS; we did not evaluate it on shared-prefix traffic, for which it is designed.

TTL pins. Continuum keeps a program's KV after a non-final turn for a time-to-live chosen by a cost model, which may be zero [69]; its released preview omits that estimator and would rarely pin our 5 s-mean tool calls. Our rows are fixed, unconditional TTLs of $\tau = 5$, 10 and 20 s on every non-final turn, with Continuum's waiting order (pinned programs first). Under the preview's release rule they give 2.584 ± 0.035, 3.505 ± 0.064 and 4.376 ± 0.048; under the rule we read in the paper's deadlock-prevention text, $\tau = 10$ and 20 s give 1.16–1.17; with plain FCFS order the pins fall below λ_{miss}, consistent with Proposition 6. These are results about configured pins, not about Continuum (Appendix R).

Adaptive caps. CONCUR adds 2 to a window on active agents when KV usage is below 0.2 and halves it when usage exceeds 0.5 and the hit rate is below 0.2, pausing and resuming agents at generation and tool boundaries [19]; we found no released code. Our session-gate surrogate of this equation gives 3.009 ± 0.081 and recovers from 5 of 5 bursts, under a usage signal that counts only live sessions; if finished sessions' KV, still cached and evictable, counts as usage, 12 of 18 cells stall at the surrogate's minimum window (Appendix R). So 3.0 is the surrogate's rate, not deployed CONCUR's.

Static caps. By Proposition 1 a cap c holds a large population at $\mu(c)$: 4.04 ± 0.25 at $c = 20$, 2.39 ± 0.35 at $c = 28$ and 1.08 ± 0.17 at $c = 36$ (3 seeds; $c = 28$ rounds down the capacity ratio with every turn weighted equally, 28.4 (§E.2), and $c = 36$ is about a quarter above it; the registered caps come instead from the rule of §F.3), against a peak of 4.07 at $n = 22$. The cliff makes the choice fragile: a cap about a quarter above N_{lb} is back near λ_{miss}.

Admission by memory demand. ThunderAgent periodically compares the programs' KV demand with the capacity, counting a program in a tool call at a weight that decays with its tool time (2^{-t} in its experiments); when demand exceeds capacity it pauses whole programs, those in tool calls and those with the shortest contexts first, and restores them when demand falls, and both of its watermarks are set to 1 in its evaluation [60]. NVIDIA Dynamo ships a port that pauses programs at tool boundaries, by default when utilization reaches 0.95 of the pool, down to 0.80, and resumes them at 0.85 or below [35]. KAIROS bounds the aggregate context of admitted agents and readmits pending agents below a lower threshold, using example thresholds of 0.95 and 0.9 of capacity [119], and AgentKV, from its abstract, admits by a predicted capacity ratio [3]. These are implemented forms of a session bound, sized by memory demand rather than count and applied to prevent the trap (KAIROS also defers new agents and boosts the clock once bursty arrivals have broken its bound, but reports no recovery from an established trap); we have not evaluated them. Their two thresholds form a controller's dead band, which keeps it from toggling; the hysteresis of Corollary 5 is a property of the system, whose good state persisted on the engine after a cap was removed (§G.3). Proposition 1 concerns a FIFO count cap whose sessions keep their slots, so it does not predict a gate that bounds current demand and pauses admitted programs, and the static-cap rates above are not a prediction for any of these systems.

Why the ranking comes out this way. Under request-level FCFS, with or without protection that keeps FCFS order, μ_∞




Figure 12: $\mu(300)/\lambda_{\text{miss}}$, our proxy for the congested service rate μ_∞, per mechanism in the earlier, uncalibrated simulator: mean over 10 seeds with 95% t intervals, in units of that simulator's λ_{miss} (0.0474 sessions/s; not comparable with Figs. 5–7); the intervals omit the 1.5% standard error of λ_{miss}. Hollow: ablations (PEEK's queued-prefix protection under FCFS order, as a soft rank and as a hard-pin counterfactual PEEK does not apply; fixed pins held until expiry even with the GPU idle). Filled: all other rows; for PEEK, a projection of its released scheduler; for the pins, fixed TTLs under the preview's release rule (values: held until expiry, preview). LPM is pure LPM, without SGLang's 128-request fallback. CONCUR: a surrogate of its control equation; small dots: 18 cells in which finished sessions' KV counts as usage. Static caps $c = 20$ (E2's cap; this simulator's n^* is 22), 28, 36: $\mu(c)$ of the closed FCFS curve (3 other seeds, not paired with the other rows).

cannot exceed λ_{miss} when (A3) holds (Proposition 6); we conjecture (Remark in Appendix P) that pure resident-first orderings raise it through tool calls shorter than the congested lifetime of idle KV, and for pure LPM the simulator agrees. A static cap c holds the engine at $\mu(c)$ (Proposition 1), so at most at the peak, 4.07 at $n = 22$ (3 seeds). Pins at $\tau = 20$ s gave 4.38, above every static cap we ran and above the peak, though within the peak's 3-seed interval (±0.36). In this simulator they also serve pinned programs first and keep a returning session's KV for at least τ, and the set of sessions they bound depends on memory, not on a count; we have not separated these effects. On the real engine, stock LPM recovered from a 200-session burst at 1.35 λ_{ref} in 4 of 6 runs (§G.6); that finite-burst result does not compare directly with these deep-congestion rates, and in deep congestion stock LPM stops re-sorting its queue, so, on our reading of its source, Proposition 6 bounds its μ_∞ by λ_{miss} when (A3) holds.