ML MODEL BUILDING REPORT

Telco Customer Churn Prediction

Prepared by: Data Science Team

Dataset: IBM Telco Customer Churn | Features: 21 | Records: 7,032

Models Evaluated: 7 Algorithms (13 Configurations) | Best Model: XGBoost + Threshold Optimization

Date: April 2026

80%	0.65	0.847	$74.2K
Best Accuracy	Best F1 (Churn)	Best ROC-AUC	Added Business Value

1. Project Overview & Methodology

This report documents the end-to-end machine learning pipeline built to predict customer churn for a telecom provider. Starting from a preprocessed dataset of 7,032 customers, seven classification algorithms were evaluated across 13 configurations using rigorous cross-validation, hyperparameter tuning, and business-oriented threshold optimization.

1.1 Objective

- Primary Goal: Predict which customers will churn (leave the service) before they do.
- Business Goal: Maximize retention campaign ROI by targeting the right customers at the right time.
- Technical Goal: Balance recall (catch as many churners as possible) with precision (avoid wasting retention offers).

1.2 Pipeline Summary

#	Stage	Details
1	Data Loading	7,032 rows × 21 features from output.csv (post-EDA)
2	Feature Engineering	One-hot encoding of categoricals — final shape: (7032, 21)
3	Train/Test Split	80/20 stratified split — Train: 5,625 | Test: 1,407
4	Scaling	StandardScaler on MonthlyCharges, TotalCharges, tenure, Charge_Spike (fit on train only)
5	Modeling	LR → Decision Tree → Random Forest → XGBoost → Voting → AdaBoost → LightGBM
6	Tuning	GridSearchCV + RandomizedSearchCV | CV=3–5 | Scoring: Recall / F1 / Avg Precision
7	Threshold Opt.	Precision-Recall curve analysis; custom thresholds tested from 0.50 to 0.79
8	SHAP Analysis	TreeExplainer for global + local feature importance
9	Deployment	Model serialized with joblib as xgboost_churn_model_production.pkl

1.3 Class Imbalance

The dataset has a significant class imbalance: 73.5% No Churn vs. 26.5% Churn. Several strategies were applied:

- class_weight="balanced" — used in Logistic Regression and Decision Tree.
- scale_pos_weight=2.76 — used in XGBoost and LightGBM (ratio of negatives to positives).
- SMOTE (Synthetic Minority Oversampling) — used inside the Random Forest pipeline via ImbPipeline.
- is_unbalance=True — used in LightGBM base model.



Figure 1: Class Distribution Before and After SMOTE Oversampling

2. Model-by-Model Results

2.1 Logistic Regression

Three configurations of Logistic Regression were evaluated: baseline, hyperparameter-tuned (optimized for Recall), and custom-threshold tuned (optimized for F1).

Configuration	Acc.	Prec.(C)	Rec.(C)	F1(C)	ROC-AUC	Threshold
Baseline (default)	81%	0.68	0.56	0.61	—	0.50
Tuned (Recall scoring)	75%	0.51	0.80	0.62	0.847	0.50
Custom Threshold (F1 opt.)	80%	0.61	0.70	0.65	—	Best F1

- Best Params (Recall-tuned): C=100, penalty=L1, solver=liblinear
- Key Finding: Tuning for Recall dramatically improved churn detection (56% → 80%) at the cost of overall accuracy.
- The custom-threshold variant achieved the best balance: 80% accuracy with 0.65 F1 for churn class.

2.2 Decision Tree

Decision Tree was evaluated in default and hyperparameter-tuned forms. An optional threshold adjustment was also tested.

Configuration	Acc.	Prec.(C)	Rec.(C)	F1(C)	Best Params
Default	74%	0.51	0.53	0.52	—
Tuned (Recall)	76%	0.53	0.76	0.62	balanced, gini, depth=5, leaf=10
Tuned (F1)	74%	0.51	0.78	0.62	balanced, gini, depth=3

- Decision Tree is more interpretable than ensemble methods, but consistently underperforms on the minority class.
- Tree depth of 5 was optimal — preventing overfitting while retaining enough complexity to capture churn patterns.

2.3 Random Forest

Random Forest showed significant improvement over a single Decision Tree, especially after Randomized Search tuning.

Configuration	Acc.	Prec.(C)	Rec.(C)	F1(C)	Notes
Default (100 trees)	77%	0.59	0.47	0.53	Low recall — misses too many churners
Tuned (RandomizedSearch)	78%	0.58	0.69	0.63	n=100, depth=10, class weight {0:1,1:2}

- Best class weight configuration: {0:1, 1:2} — doubling the penalty for missing churners.
- Bootstrap sampling with log2 feature selection per split gave the best generalization.

2.4 XGBoost (Extreme Gradient Boosting)

XGBoost was the primary focus of tuning effort, with multiple configurations including base, grid-searched, and feature-engineered advanced versions.

Configuration	Acc.	Prec.(C)	Rec.(C)	F1(C)	Notes
Base XGBoost	77%	0.55	0.73	0.63	scale_pos_weight=2.76
Grid-Tuned (F1 scoring)	75%	0.52	0.80	0.63	lr=0.01, depth=4, gamma=0.1
Advanced + Threshold 0.62	79%	0.59	0.70	0.64	3 new features added
Advanced + Threshold 0.64	80%	0.61	0.69	0.65	★ **BEST MODEL**

- Advanced Feature Engineering added 3 new predictors: Charge_Tenure_Ratio, Service_Stickiness, and High_Value_At_Risk.
- Threshold 0.64 (balanced Precision–Recall score with 60% precision weight) gave the best F1 and overall accuracy.
- PR-AUC = 0.xx — strong ability to rank churners ahead of non-churners.

2.5 Ensemble Methods

Two ensemble strategies were evaluated: a Voting Classifier combining XGBoost + RF (SMOTE) + LightGBM, and AdaBoost with Decision Tree stumps.

Model	Acc.	Prec.(C)	Rec.(C)	F1(C)	Notes
Voting (soft, thr=0.50)	76%	0.53	0.75	0.62	XGB + RF(SMOTE) + LightGBM
Voting (thr=0.55)	77%	0.56	0.71	0.62	Slight precision improvement
AdaBoost (default)	70%	0.47	0.85	0.60	Very high recall, low precision
AdaBoost (Tuned)	65%	0.43	0.89	0.58	Best recall in dataset; impractical precision

- The Voting Classifier did not outperform the best standalone XGBoost, suggesting diminishing returns from ensemble stacking at this dataset size.
- AdaBoost achieved the highest recall (89%) but at only 43% precision — catching almost all churners but flagging too many loyal customers.

2.6 LightGBM

Configuration	Acc.	Prec.(C)	Rec.(C)	F1(C)	Notes
Base LightGBM	75%	0.53	0.73	0.61	scale_pos_weight=2.76
Tuned (RandomizedSearch)	76%	0.53	0.78	0.63	50 iterations, CV=3
Threshold 0.60	78%	0.57	0.71	0.63	Comparable to RF tuned

- LightGBM delivered competitive results with faster training than XGBoost.
- Further tuning of num_leaves and min_child_samples could potentially close the gap with XGBoost Final.

3. Visual Performance Analysis

3.1 Full Model Comparison

The chart below compares all 13 model configurations across Accuracy, F1 (Churn class), and Recall (Churn class). This provides a comprehensive view of the tradeoffs made throughout the modeling process.



Figure 2: Accuracy, F1, and Recall comparison across all model configurations

3.2 Confusion Matrix Comparison — Key Models

The confusion matrix captures the most business-critical errors: False Negatives (missed churners — the most costly error) and False Positives (loyal customers incorrectly flagged — wasted offer cost).



Figure 3: Confusion matrices for LR Baseline, RF Tuned, and XGBoost Final

Reading the matrices above:

- LR Baseline: 165 False Negatives — misses a large share of churners.
- RF Tuned: 116 False Negatives — solid improvement; 190 False Positives.
- XGBoost Final: 113 False Negatives — best FN score; 165 False Positives — manageable.

3.3 Top 4 Models — Metric Comparison



Figure 4: Side-by-side metric comparison for the four best performing models

4. Threshold Optimization

The default decision threshold of 0.50 is rarely optimal for imbalanced classification problems. By shifting the threshold, we control the trade-off between catching more churners (recall) and making fewer false alarms (precision).

4.1 Threshold Sensitivity



Figure 5: Precision, Recall, F1, and Accuracy as a function of decision threshold (XGBoost Final)

Key observations from the threshold curve:

- F1 score peaks around 0.62–0.65, confirming that the chosen threshold of 0.64 is optimal for balanced performance.
- At 0.50: Recall = 79%, Precision = 52% — too many false alarms for a targeted campaign.
- At 0.79: Precision = 70%, Recall = 39% — high precision but misses too many churners to be useful.
- At 0.64: Precision = 61%, Recall = 69%, Accuracy = 80% — the best business trade-off.

Threshold	Accuracy	Prec. (C)	Rec. (C)	F1 (C)	FN Count	Recommended For
0.50	75%	0.52	0.79	0.63	~79	Max recall use cases
0.57	77%	0.55	0.74	0.63	~99	Balanced recall-biased
0.60	78%	0.57	0.71	0.63	~108	General balanced use
0.64 ★	80%	0.61	0.69	0.65	~116	**★ Production (Best F1)**
0.79	79%	0.70	0.39	0.50	~228	High precision, low recall

5. SHAP Feature Importance

SHAP (SHapley Additive exPlanations) provides a rigorous, game-theory-based framework for explaining model predictions. Both global (dataset-level) and local (individual customer) explanations were generated using the XGBoost Final model.

5.1 Global Feature Importance



Figure 6: SHAP Global Feature Importance — Mean absolute SHAP value per feature

5.2 Feature Interpretation

Feature	SHAP Value	Business Interpretation
Short_Contract	0.62	Strongest predictor. Month-to-month customers can leave anytime — zero commitment penalty.
tenure	0.41	Long-tenured customers are anchored by switching costs and service familiarity.
InternetService_Fiber optic	0.39	Fiber users pay ~$91/month and expect premium quality; unmet expectations drive churn.
MonthlyCharges	0.31	Higher monthly bills increase price sensitivity and likelihood of seeking cheaper alternatives.
Total_Services	0.28	More subscribed services = higher switching cost. Each service is a reason to stay.
High_Value_At_Risk	0.25	Engineered flag: Fiber Optic + Short Contract = the most dangerous combination.
TotalCharges	0.22	Total lifetime spend — a proxy for customer lifetime value and long-term engagement.
Is_Auto_Pay	0.19	Automatic payment removes the monthly re-evaluation cycle, reducing intentional churn.

5.3 Local Explanation — Sample Customer

The SHAP waterfall plot for an individual customer shows how each feature pushes the prediction above or below the average. For a sample customer from the test set:

- InternetService_No = 1 → Strong negative SHAP (−0.66): Reduces churn risk significantly.
- Short_Contract = 1 → Positive SHAP (+0.47): Increases churn risk — this customer is on a month-to-month plan.
- MonthlyCharges (scaled −1.45) → Slight negative (−0.15): Low charges reduce churn probability.
- Final prediction: Low churn probability — the no-internet anchor outweighs the contract risk.

6. Business Impact Analysis

Beyond classification metrics, the model was evaluated in terms of direct financial impact using a cost-benefit framework.

6.1 Business Cost Model

Business Cost Parameter	Value
Cost of Retention Offer (per customer)	**$20**
Estimated Revenue Loss from 1 Churner	**$500**
Default Threshold (0.50) Profit	**$85,580**
Optimal Threshold (0.10) Max Profit	**$159,780**
Added Business Value	**$74,200**



Figure 7: Business Profit Curve — Revenue gained vs. decision threshold

The profit curve above shows that the default 0.50 threshold leaves $74,200 in potential retention profit on the table. The curve peaks at threshold 0.10 in the cost-model simulation, demonstrating that an aggressive early-intervention strategy (flag customers at lower confidence) yields substantially higher returns when the cost of missing a churner ($500) greatly exceeds the cost of a retention offer ($20).

6.2 Production Deployment

The final model was packaged and serialized for production deployment:

- File: xgboost_churn_model_production.pkl (via joblib)
- Contents: {model, optimal_threshold, expected_columns, business_metrics}

- Inference pattern: probabilities = model.predict(new_data) → (probabilities >= threshold).astype(int)
- Expected columns: 24 features (21 original + 3 engineered: Charge_Tenure_Ratio, Service_Stickiness, High_Value_At_Risk)

7. Final Model Summary & Recommendation

7.1 Recommended Model: XGBoost Final (Threshold 0.64)

Attribute	Value
Algorithm	XGBoost (XGBClassifier) — Gradient Boosted Trees
Hyperparameters	lr=0.02, depth=3, min_child_weight=1, gamma=0.1, scale_pos_weight=2.76
Extra Features	Charge_Tenure_Ratio, Service_Stickiness, High_Value_At_Risk
Decision Threshold	**0.64 (balanced F1-optimal)**
Accuracy	**80%**
F1 Score (Churn)	**0.65**
Precision (Churn)	0.61
Recall (Churn)	0.69
ROC-AUC	**~0.85**
False Negatives (test set)	~113 (lowest among all models)

7.2 Why XGBoost Won

- Gradient boosting iteratively corrects previous errors — ideal for complex, non-linear churn patterns.
- scale_pos_weight directly addresses class imbalance without SMOTE oversampling overhead.
- Advanced feature engineering (Charge_Tenure_Ratio, High_Value_At_Risk) gave XGBoost additional signal not available to other models.
- Threshold tuning with PR-AUC optimization yielded the best F1 score (0.65) in the entire experiment.
- SHAP explainability ensures predictions can be justified to business stakeholders.

7.3 Alternative Threshold Recommendations by Use Case

Use Case	Threshold	Recall	Precision	When to Use
Mass Retention Campaign	0.40	~85%	~45%	Large budget, low offer cost
Balanced (Production) ★	0.64	69%	61%	**★ Default production setting**
Premium Segment Only	0.79	39%	70%	Small budget, high LTV focus

End of Report

Telco Churn ML Model Building — April 2026