

```

#include<stdio.h>
#include<conio.h>
int main()
{
    int a[10];
    int size,i,num,del,temp,j;
    printf("enter size of the array");
    scanf("%d",&size);
    printf("enter elements of array");
    for(i=0;i<size;i++)
    {
        scanf("%d",&a[i]);
    }
    printf("array elements-");
    for(i=0;i<size;i++)
    {
        printf("%d ",a[i]);
    }

    printf("enter the number to find its index value \n ");
    scanf("%d",&num);
    for(i=0;i<size;i++)
    {
        if(a[i]==num)
        {
            printf("element found at index %d \n",i);
        }
    }

    for (i = 0; i < size - 1; i++)
    {
        for (j = 0; j < size - i - 1; j++)
        {
            if (a[j] > a[j + 1])
            {
                temp = a[j];
                a[j] = a[j + 1];
                a[j + 1] = temp;
            }
        }
    }

    printf("Sorted array: \n");
    for (i = 0; i < size; i++)
    {
        printf("%d ", a[i]);
    }
    printf("\n");
}

```

```
printf("\n enter the element position to delete ");
scanf("%d",&del);
for(i=del-1;i<size-1;i++)
{
    a[i]=a[i+1];
    size--;
}
printf("\n array after deletion");
for(i=0;i<size;i++)
{
    printf("%d ",a[i]);
}
return 0;
}
```