

Rajalakshmi Engineering College

Name: akshaya d
Email: 241901002@rajalakshmi.edu.in
Roll no: 241901002
Phone: 9363744696
Branch: REC
Department: I CSE (CS) FA
Batch: 2028
Degree: B.E - CSE (CS)

Scan to verify results



NeoColab_REC_CS23231_DATA STRUCTURES

REC_DS using C_Week 4_COD_Question 1

Attempt : 1
Total Mark : 10
Marks Obtained : 10

Section 1 : Coding

1. Problem Statement

Imagine a bustling coffee shop, where customers are placing their orders for their favorite coffee drinks. The cafe owner Sheeren wants to efficiently manage the queue of coffee orders using a digital system. She needs a program to handle this queue of orders.

You are tasked with creating a program that implements a queue for coffee orders. Each character in the queue represents a customer's coffee order, with 'L' indicating a latte, 'E' indicating an espresso, 'M' indicating a macchiato, 'O' indicating an iced coffee, and 'N' indicating a nabob.

Customers can place orders and enjoy their delicious coffee drinks.

Input Format

The input consists of integers corresponding to the operation that needs to be performed:

Choice 1: Enqueue the coffee order into the queue. If the choice is 1, the following input is a space-separated character ('L', 'E', 'M', 'O', 'N').

Choice 2: Dequeue a coffee order from the queue.

Choice 3: Display the orders in the queue.

Choice 4: Exit the program.

Output Format

The output displays messages according to the choice and the status of the queue:

If the choice is 1:

1. Insert the given order into the queue and display "Order for [order] is enqueued." where [order] is the coffee order that is inserted.
2. If the queue is full, print "Queue is full. Cannot enqueue more orders."

If the choice is 2:

1. Dequeue a character from the queue and display "Dequeued Order: " followed by the corresponding order that is dequeued.
2. If the queue is empty without any orders, print "No orders in the queue."

If the choice is 3:

1. The output prints "Orders in the queue are: " followed by the space-separated orders present in the queue.
2. If there are no orders in the queue, print "Queue is empty. No orders available."

If the choice is 4:

1. Exit the program and print "Exiting program"

If any other choice is entered, the output prints "Invalid option."

Refer to the sample output for the exact text and format.

Sample Test Case

Input: 1 L

1 E

1 M

1 O

1 N

1 O

3

2

3

4

Output: Order for L is enqueued.

Order for E is enqueued.

Order for M is enqueued.

Order for O is enqueued.

Order for N is enqueued.

Queue is full. Cannot enqueue more orders.

Orders in the queue are: L E M O N

Dequeued Order: L

Orders in the queue are: E M O N

Exiting program

Answer

```
#include <stdio.h>
```

```
#define MAX_SIZE 5
```

```
char orders[MAX_SIZE];
```

```
int front = -1;
```

```
int rear = -1;
```

```
void initializeQueue() {
```

```
    front = -1;
```

```
    rear = -1;
```

```
}
```

```
int isEmpty() {
```

```
    return front == -1;
```

```
}
```

```
int isFull() {  
    return (rear + 1) % MAX_SIZE == front;  
}
```

```
int enqueue(char order) {  
    if (isFull()) {  
        printf("Queue is full. Cannot enqueue more orders.\n");  
        return 0;  
    }
```

```
    if (isEmpty()) {  
        front = rear = 0;  
    } else {  
        rear = (rear + 1) % MAX_SIZE;  
    }
```

```
    orders[rear] = order;  
    printf("Order for %c is enqueued.\n", order);  
    return 1;  
}
```

```
int dequeue(char* order) {  
    if (isEmpty()) {  
        return 0;  
    }
```

```
    *order = orders[front];  
  
    if (front == rear) {  
        front = rear = -1;  
    } else {  
        front = (front + 1) % MAX_SIZE;  
    }
```

```
    return 1;  
}
```

```
void display() {  
    if (isEmpty()) {  
        printf("Queue is empty. No orders available.\n");
```

```

    } else {
        printf("Orders in the queue are: ");
        int i = front;
        while (i != rear) {
            printf("%c ", orders[i]);
            i = (i + 1) % MAX_SIZE;
        }
        printf("%c\n", orders[rear]);
    }
}

int main() {
    char order;
    int option;
    initializeQueue();
    while (1) {
        if (scanf("%d", &option) != 1) {
            break;
        }
        switch (option) {
            case 1:
                if (scanf(" %c", &order) != 1) {
                    break;
                }
                if (enqueue(order)) {

                }
                break;
            case 2:
                if (dequeue(&order)) {
                    printf("Dequeued Order: %c\n", order);
                } else {
                    printf("No orders in the queue.\n");
                }
                break;
            case 3:
                display();
                break;
            case 4:
                printf("Exiting program");
                return 0;
            default:
                printf("Invalid option.\n");
        }
    }
}

```

```
        break;  
    }  
    }  
    return 0;  
}
```

Status : Correct

Marks : 10/10

Rajalakshmi Engineering College

Name: akshaya d
Email: 241901002@rajalakshmi.edu.in
Roll no: 241901002
Phone: 9363744696
Branch: REC
Department: I CSE (CS) FA
Batch: 2028
Degree: B.E - CSE (CS)

Scan to verify results



NeoColab_REC_CS23231_DATA STRUCTURES

REC_DS using C_Week 4_COD_Question 2

Attempt : 1
Total Mark : 10
Marks Obtained : 10

Section 1 : Coding

1. Problem Statement

In a bustling IT department, staff regularly submit helpdesk tickets to request technical assistance. Managing these tickets efficiently is vital for providing quality support.

Your task is to develop a program that uses an array-based queue to handle and prioritize helpdesk tickets based on their unique IDs.

Implement a program that provides the following functionalities:

Enqueue Helpdesk Ticket: Add a new helpdesk ticket to the end of the queue. Provide a positive integer representing the ticket ID for the new ticket. Dequeue Helpdesk Ticket: Remove and process the next helpdesk ticket from the front of the queue. The program will display the ticket ID of the processed ticket. Display Queue: Display the ticket IDs of all the

helpdesk tickets currently in the queue.

Input Format

The input consists of integers corresponding to the operation that needs to be performed:

Choice 1: Enqueue the ticket ID into the queue. If the choice is 1, the following input is a space-separated integer, representing the ticket ID to be enqueued into the queue.

Choice 2: Dequeue a ticket from the queue.

Choice 3: Display the ticket IDs in the queue.

Choice 4: Exit the program.

Output Format

The output displays messages according to the choice and the status of the queue:

If the choice is 1:

1. Insert the given ticket ID into the queue and display "Helpdesk Ticket ID [id] is enqueued." where [id] is the ticket ID that is inserted.
2. If the queue is full, print "Queue is full. Cannot enqueue."

If the choice is 2:

1. Dequeue a ticket ID from the queue and display "Dequeued Helpdesk Ticket ID: " followed by the corresponding ID that is dequeued.
2. If the queue is empty without any elements, print "Queue is empty."

If the choice is 3:

1. The output prints "Helpdesk Ticket IDs in the queue are: " followed by the space-separated ticket IDs present in the queue.
2. If there are no elements in the queue, print "Queue is empty."

If the choice is 4:

1. Exit the program and print "Exiting the program"

If any other choice is entered, print "Invalid option."

Refer to the sample output for formatting specifications.

Sample Test Case

Input: 1 101

1 202

1 203

1 204

1 205

1 206

3

2

3

4

Output: Helpdesk Ticket ID 101 is enqueued.

Helpdesk Ticket ID 202 is enqueued.

Helpdesk Ticket ID 203 is enqueued.

Helpdesk Ticket ID 204 is enqueued.

Helpdesk Ticket ID 205 is enqueued.

Queue is full. Cannot enqueue.

Helpdesk Ticket IDs in the queue are: 101 202 203 204 205

Dequeued Helpdesk Ticket ID: 101

Helpdesk Ticket IDs in the queue are: 202 203 204 205

Exiting the program

Answer

```
#include <stdio.h>
```

```
#define MAX_SIZE 5
```

```
int ticketIDs[MAX_SIZE];
```

```
int front = -1;
```

```
int rear = -1;
```

```
int lastDequeued;
```

```
void initializeQueue() {
```

```
    front = -1;
```

```
    rear = -1;
```

```
}
```

```
int isEmpty() {  
    return front==-1;  
}
```

```
int isFull() {  
    return (rear+1)%MAX_SIZE==front;  
}
```

```
int enqueue(int ticketID) {  
    if(isFull()){  
        printf("Queue is full.Cannot enqueue.\n");  
        return 0;  
    }  
    if(isEmpty()){  
        front=rear=0;  
    }  
    else{  
        rear=(rear+1)%MAX_SIZE;  
    }  
    ticketIDs[rear]=ticketID;  
    printf("Helpdesk Ticket ID %d is enqueued.\n",ticketID);  
    return 1;  
}
```

```
int dequeue() {  
    if(isEmpty()){  
        return 0;  
    }  
    lastDequeued=ticketIDs[front];  
    if(front==rear){  
        front=rear=-1;  
    }  
    else{  
        front=(front+1)%MAX_SIZE;  
    }  
    return 1;  
}
```

```

void display() {
    if(isEmpty()){
        printf("Queue is empty.\n");
    }
    else{
        printf("Helpdesk Ticket IDs in the queue are: ");
        int i=front;
        while(i!=rear){
            printf("%d ",ticketIDs[i]);
            i=(i+1)%MAX_SIZE;
        }
        printf("%d\n",ticketIDs[rear]);
    }
}

int main() {
    int ticketID;
    int option;
    initializeQueue();
    while (1) {
        if (scanf("%d", &option) == EOF) {
            break;
        }
        switch (option) {
            case 1:
                if (scanf("%d", &ticketID) == EOF) {
                    break;
                }
                enqueue(ticketID);
                break;
            case 2:
                if (dequeue()) {
                    printf("Dequeued Helpdesk Ticket ID: %d\n", lastDequeued);
                } else {
                    printf("Queue is empty.\n");
                }
                break;
            case 3:
                display();
                break;
            case 4:
                printf("Exiting the program\n");

```

```
        return 0;
    default:
        printf("Invalid option.\n");
        break;
    }
}
return 0;
}
```

Status : Correct

Marks : 10/10

Rajalakshmi Engineering College

Name: akshaya d
Email: 241901002@rajalakshmi.edu.in
Roll no: 241901002
Phone: 9363744696
Branch: REC
Department: I CSE (CS) FA
Batch: 2028
Degree: B.E - CSE (CS)

Scan to verify results



NeoColab_REC_CS23231_DATA STRUCTURES

REC_DS using C_Week 4_COD_Question 3

Attempt : 1
Total Mark : 10
Marks Obtained : 10

Section 1 : Coding

1. Problem Statement

Write a program to implement a queue using an array and pointers. The program should provide the following functionalities:

Insert an element into the queue. Delete an element from the queue. Display the elements in the queue.

The queue has a maximum capacity of 5 elements. If the queue is full and an insertion is attempted, a "Queue is full" message should be displayed. If the queue is empty and a deletion is attempted, a "Queue is empty" message should be displayed.

Input Format

Each line contains an integer representing the chosen option from 1 to 3.

Option 1: Insert an element into the queue followed by an integer representing the element to be inserted, separated by a space.

Option 2: Delete an element from the queue.

Option 3: Display the elements in the queue.

Output Format

For option 1 (insertion):-

1. The program outputs: "<data> is inserted in the queue." if the data is successfully inserted.
2. "Queue is full." if the queue is already full and cannot accept more elements.

For option 2 (deletion):-

1. The program outputs: "Deleted number is: <data>" if an element is successfully deleted and returns the value of the deleted element.
2. "Queue is empty." if the queue is empty no elements can be deleted.

For option 3 (display):-

1. The program outputs: "Elements in the queue are: <element1> <element2> ... <elementN>" where <element1>, <element2>, ..., <elementN> represent the elements present in the queue.
2. "Queue is empty." if the queue is empty no elements can be displayed.

For invalid options, the program outputs: "Invalid option."

Refer to the sample output for the formatting specifications.

Sample Test Case

Input: 1 10

3

5

Output: 10 is inserted in the queue.

Elements in the queue are: 10

Invalid option.

Answer

```
#include <stdio.h>
```

```
#include <stdlib.h>
```

```
#define max 5
```

```
int queue[max];
```

```
int front = -1, rear = -1;
```

```
int insertq(int *data)
```

```
{
```

```
    if(rear==max-1)
```

```
        return 0;
```

```
    else{
```

```
        rear++;
```

```
        queue[rear]=*data;
```

```
        return 1;
```

```
    }
```

```
}
```

```
int delq()
```

```
{
```

```
    if(front==rear){
```

```
        printf("Queue is empty.\n");
```

```
        return 0;
```

```
    }
```

```
    else{
```

```
        front++;
```

```
        int data=queue[front];
```

```
        printf("Deleted number is: %d\n",data);
```

```
        if(front>rear){
```

```
            front=rear=-1;
```

```
        }
```

```
        return 1;
```

```
    }
```

```
}
```

```

void display()
{
    if(front==rear){
        printf("Queue is empty.\n");
    }
    else{
        printf("Elements in the queue are: ");
        for(int i=front+1;i<=rear;i++){
            printf("%d ",queue[i]);
        }
        printf("\n");
    }
}

int main()
{
    int data, reply, option;
    while (1)
    {
        if (scanf("%d", &option) != 1)
            break;
        switch (option)
        {
            case 1:
                if (scanf("%d", &data) != 1)
                    break;
                reply = insertq(&data);
                if (reply == 0)
                    printf("Queue is full.\n");
                else
                    printf("%d is inserted in the queue.\n", data);
                break;
            case 2:
                delq(); // Called without arguments
                break;
            case 3:
                display();
                break;
            default:
                printf("Invalid option.\n");
                break;
        }
    }
}

```



```
}  
return 0;  
}
```

Status : Correct

Marks : 10/10

Rajalakshmi Engineering College

Name: akshaya d
Email: 241901002@rajalakshmi.edu.in
Roll no: 241901002
Phone: 9363744696
Branch: REC
Department: I CSE (CS) FA
Batch: 2028
Degree: B.E - CSE (CS)

Scan to verify results



NeoColab_REC_CS23231_DATA STRUCTURES

REC_DS using C_Week 4_COD_Question 4

Attempt : 1
Total Mark : 10
Marks Obtained : 10

Section 1 : Coding

1. Problem Statement

In an office setting, a print job management system is used to efficiently handle and process print jobs. The system is implemented using a queue data structure with an array.

The program provides the following operations:

Enqueue Print Job: Add a print job with a specified number of pages to the end of the queue. Dequeue Print Job: Remove and process the next print job in the queue. Display Queue: Display the print jobs in the queue

The program should ensure that print jobs are processed in the order they are received.

Input Format

The input consists of integers corresponding to the operation that needs to be performed:

Choice 1: Enqueue the print job into the queue. If the choice is 1, the following input is a space-separated integer, representing the pages to be enqueued into the queue.

Choice 2: Dequeue a print job from the queue.

Choice 3: Display the print jobs in the queue.

Choice 4: Exit the program.

Output Format

The output displays messages according to the choice and the status of the queue:

If the choice is 1:

1. Insert the given page into the queue and display "Print job with [page] pages is enqueued." where [page] is the number of pages that are inserted.
2. If the queue is full, print "Queue is full. Cannot enqueue."

If the choice is 2:

1. Dequeue a page from the queue and display "Processing print job: [page] pages" where [page] is the corresponding page that is dequeued.
2. If the queue is empty without any elements, print "Queue is empty."

If the choice is 3:

1. The output prints "Print jobs in the queue: " followed by the space-separated pages present in the queue.
2. If there are no elements in the queue, print "Queue is empty."

If the choice is 4:

1. Exit the program and print "Exiting program"

If any other choice is entered, the output prints "Invalid option."

Refer to the sample output for the formatting specifications.

Sample Test Case

Input: 1

10

1

20

1

30

1

40

1

50

1

60

3

2

3

4

Output: Print job with 10 pages is enqueued.

Print job with 20 pages is enqueued.

Print job with 30 pages is enqueued.

Print job with 40 pages is enqueued.

Print job with 50 pages is enqueued.

Queue is full. Cannot enqueue.

Print jobs in the queue: 10 20 30 40 50

Processing print job: 10 pages

Print jobs in the queue: 20 30 40 50

Exiting program

Answer

```
void enqueue(int pages) {  
    if (rear == MAX_SIZE) {  
        printf("Queue is full. Cannot enqueue.\n");  
        return;  
    }  
    queue[rear++] = pages;
```

```

    printf("Print job with %d pages is enqueued.\n", pages);
}

// Function to dequeue a print job
void dequeue() {
    if (front == rear) {
        printf("Queue is empty.\n");
        return;
    }
    printf("Processing print job: %d pages\n", queue[front++]);

    // Reset queue if it becomes empty
    if (front == rear) {
        front = rear = 0;
    }
}

// Function to display the queue
void display() {
    if (front == rear) {
        printf("Queue is empty.\n");
        return;
    }
    printf("Print jobs in the queue: ");
    for (int i = front; i < rear; i++) {
        printf("%d ", queue[i]);
    }
    printf("\n");
}

```

Status : Correct

Marks : 10/10

Rajalakshmi Engineering College

Name: akshaya d
Email: 241901002@rajalakshmi.edu.in
Roll no: 241901002
Phone: 9363744696
Branch: REC
Department: I CSE (CS) FA
Batch: 2028
Degree: B.E - CSE (CS)

Scan to verify results



NeoColab_REC_CS23231_DATA STRUCTURES

REC_DS using C_Week 4_COD_Question 5

Attempt : 1
Total Mark : 10
Marks Obtained : 10

Section 1 : Coding

1. Problem Statement

You are tasked with implementing basic operations on a queue data structure using a linked list.

You need to write a program that performs the following operations on a queue:

Enqueue Operation: Implement a function that inserts an integer element at the rear end of the queue. Print Front and Rear: Implement a function that prints the front and rear elements of the queue. Dequeue Operation: Implement a function that removes the front element from the queue.

Input Format

The first line of input consists of an integer N, representing the number of elements to be inserted into the queue.

The second line consists of N space-separated integers, representing the queue elements.

Output Format

The first line prints "Front: X, Rear: Y" where X is the front and Y is the rear elements of the queue.

The second line prints the message indicating that the dequeue operation (front element removed) is performed: "Performing Dequeue Operation:".

The last line prints "Front: M, Rear: N" where M is the front and N is the rear elements after the dequeue operation.

Refer to the sample output for the formatting specifications.

Sample Test Case

Input: 5

12 56 87 23 45

Output: Front: 12, Rear: 45

Performing Dequeue Operation:

Front: 56, Rear: 45

Answer

```
#include <stdio.h>
#include <stdlib.h>
```

```
struct Node {
    int data;
    struct Node* next;
};
```

```
struct Node* front = NULL;
struct Node* rear = NULL;
```

```
void enqueue(int d) {
    struct Node* new_n=(struct Node*)malloc(sizeof(struct Node));
    new_n->data=d;
    new_n->next=NULL;
```

```

    if(front==NULL && rear==NULL){
        front=rear=new_n;
    }
    else{
        rear->next=new_n;
        rear=new_n;
    }
}

void printFrontRear() {
    printf("Front:%d, ",front->data);
    printf("Rear:%d\n",rear->data);
}

void dequeue() {
    struct Node* temp;
    temp=front;
    front=front->next;
    free(temp);
}

int main() {
    int n, data;
    scanf("%d", &n);
    for (int i = 0; i < n; i++) {
        scanf("%d", &data);
        enqueue(data);
    }
    printFrontRear();
    printf("Performing Dequeue Operation:\n");
    dequeue();
    printFrontRear();
    return 0;
}

```

Status : Correct

Marks : 10/10

Rajalakshmi Engineering College

Name: akshaya d
Email: 241901002@rajalakshmi.edu.in
Roll no: 241901002
Phone: 9363744696
Branch: REC
Department: I CSE (CS) FA
Batch: 2028
Degree: B.E - CSE (CS)

Scan to verify results



NeoColab_REC_CS23231_DATA STRUCTURES

REC_DS using C_Week 4_PAH

Attempt : 1
Total Mark : 50
Marks Obtained : 50

Section 1 : Coding

1. Problem Statement

Amar is working on a project where he needs to implement a special type of queue that allows selective dequeuing based on a given multiple. He wants to efficiently manage a queue of integers such that only elements not divisible by a given multiple are retained in the queue after a selective dequeue operation.

Implement a program to assist Amar in managing his selective queue.

Example

Input:

5

10 2 30 4 50

5

Output:

Original Queue: 10 2 30 4 50

Queue after selective dequeue: 2 4

Explanation:

After selective dequeue with a multiple of 5, the elements that are multiples of 5 should be removed. Therefore, only 10, 30, and 50 should be removed from the queue. The updated Queue is 2 4.

Input Format

The first line contains an integer n , representing the number of elements initially present in the queue.

The second line contains n space-separated integers, representing the elements of the queue.

The third line contains an integer multiple, representing the divisor for selective dequeue operation.

Output Format

The first line of output prints "Original Queue: " followed by the space-separated elements in the queue before the dequeue operation.

The second line prints "Queue after selective dequeue: " followed by the remaining space-separated elements in the queue, after deleting elements that are the multiples of the specified number.

Refer to the sample output for the formatting specifications.

Sample Test Case

Input: 5

10 2 30 4 50

5

Output: Original Queue: 10 2 30 4 50

Queue after selective dequeue: 2 4

Answer

```
// You are using GCC
#include <stdio.h>
#include <stdlib.h>

// Define the node structure
typedef struct Node {
    int data;
    struct Node* next;
} Node;

// Function to create a new node
Node* createNode(int data) {
    Node* newNode = (Node*)malloc(sizeof(Node));
    newNode->data = data;
    newNode->next = NULL;
    return newNode;
}

void enqueue(Node** front, Node** rear, int data) {
    Node* newNode = createNode(data);
    if (*front == NULL) {
        *front = *rear = newNode;
    } else {
        (*rear)->next = newNode;
        *rear = newNode;
    }
}

int dequeue(Node** front, Node** rear) {
    if (*front == NULL) {
        return -1; // Queue is empty
    }
    int data = (*front)->data;
    Node* temp = *front;
    *front = (*front)->next;
    if (*front == NULL) {
        *rear = NULL;
    }
    free(temp);
    return data;
}

void selectiveDequeue(Node** front, Node** rear, int multiple) {
    Node* current = *front;
```

```

Node* prev = NULL;
while (current != NULL) {
    if (current->data % multiple == 0) {
        if (prev == NULL) {
            *front = current->next;
        } else {
            prev->next = current->next;
        }
        Node* temp = current;
        current = current->next;
        free(temp);
    } else {
        prev = current;
        current = current->next;
    }
}
*rear = prev;
}

int main() {
    Node* front = NULL;
    Node* rear = NULL;
    int n, multiple, input;
    scanf("%d", &n);
    for (int i = 0; i < n; i++) {
        scanf("%d", &input);
        if (input < 1 || input > 100) {
            printf("Invalid input. Please enter a value between 1 and 100.\n");
            return 1;
        }
        enqueue(&front, &rear, input);
    }
    scanf("%d", &multiple);
    if (multiple < 1 || multiple > 10) {
        printf("Invalid input. Please enter a value between 1 and 10.\n");
        return 1;
    }
    printf("Original Queue: ");
    Node* current = front;
    while (current != NULL) {
        printf("%d ", current->data);
        current = current->next;
    }
}

```

```

printf("\n");
selectiveDequeue(&front, &rear, multiple);
printf("Queue after selective dequeue: ");
current = front;
while (current != NULL) {
    printf("%d ", current->data);
    current = current->next;
}
printf("\n");

return 0;
}

```

Status : Correct

Marks : 10/10

2. Problem Statement

You are tasked with developing a simple ticket management system for a customer support department. In this system, customers submit support tickets, which are processed in a First-In-First-Out (FIFO) order. The system needs to handle the following operations:

Ticket Submission (Enqueue Operation): New tickets are submitted by customers. Each ticket is assigned a unique identifier (represented by an integer). When a new ticket arrives, it should be added to the end of the queue.

Ticket Processing (Dequeue Operation): The support team processes tickets in the order they are received. The ticket at the front of the queue is processed first. After processing, the ticket is removed from the queue.

Display Ticket Queue: The system should be able to display the current state of the ticket queue, showing the sequence of ticket identifiers from front to rear.

Input Format

The first input line contains an integer n , the number of tickets submitted by customers.

The second line consists of a single integer, representing the unique identifier of each submitted ticket, separated by a space.

Output Format

The first line displays the "Queue: " followed by the ticket identifiers in the queue after all tickets have been submitted.

The second line displays the "Queue After Dequeue: " followed by the ticket identifiers in the queue after processing (removing) the ticket at the front.

Refer to the sample output for the exact text and format.

Sample Test Case

Input: 6

14 52 63 95 68 49

Output: Queue: 14 52 63 95 68 49

Queue After Dequeue: 52 63 95 68 49

Answer

```
#include <stdio.h>
```

```
#define MAX_QUEUE_SIZE 20
```

```
int queue[MAX_QUEUE_SIZE];  
int front = -1, rear = -1;
```

```
// Function to enqueue a ticket
```

```
int enqueue(int ticket_id) {  
    if (rear == MAX_QUEUE_SIZE - 1) {  
        return 0; // Queue is full  
    }  
    if (front == -1) {  
        front = 0;  
    }  
    rear++;  
    queue[rear] = ticket_id;  
    return 1; // Enqueue successful  
}
```

// Function to dequeue a ticket

```
int dequeue() {  
    if (front == -1 || front > rear) {  
        return -1; // Underflow  
    }  
    int ticket_id = queue[front];  
    if (front == rear) {  
        front = -1;  
        rear = -1;  
    } else {  
        front++;  
    }  
    return ticket_id;  
}
```

// Function to display the current ticket queue

```
void display_queue() {  
    if (front == -1) {  
        printf("Queue is empty.\n");  
        return;  
    }  
    printf("Queue: ");  
    for (int i = front; i <= rear; i++) {  
        printf("%d ", queue[i]);  
    }  
    printf("\n");  
}
```

```
int main() {  
    int n, ticket_id;  
    if (scanf("%d", &n) != 1) {  
        return 1;  
    }  
    if (n < 2 || n > 20) {  
        return 1;  
    }  
    for (int i = 0; i < n; i++) {  
        if (scanf("%d", &ticket_id) != 1) {  
            return 1;  
        }  
        if (ticket_id < 0 || ticket_id > 100) {  
            return 1;  
        }  
    }  
}
```

```

    }
    if (!enqueue(ticket_id)) {
        printf("Queue is full.\n");
        return 1;
    }
}
display_queue();
int first_ticket = dequeue();
if (first_ticket == -1) {
    printf("Underflow\n");
} else {
    printf("Queue After Dequeue: ");
    for (int i = front; i <= rear; i++) {
        printf("%d ", queue[i]);
    }
    printf("\n");
}
return 0;
}

```

Status : Correct

Marks : 10/10

3. Problem Statement

You've been assigned the challenge of developing a queue data structure using a linked list.

The program should allow users to interact with the queue by enqueueing positive integers and subsequently dequeuing and displaying elements.

Input Format

The input consists of a series of integers, one per line. Enter positive integers into the queue.

Enter -1 to terminate input.

Output Format

The output prints the space-separated dequeued elements.

Refer to the sample output for the exact text and format.

Sample Test Case

Input: 1

2

3

4

-1

Output: Dequeued elements: 1 2 3 4

Answer

```
// You are using GCC
```

```
#include <stdio.h>
```

```
#include <stdlib.h>
```

```
// Define the node structure
```

```
typedef struct Node {
```

```
    int data;
```

```
    struct Node* next;
```

```
} Node;
```

```
// Function to create a new node
```

```
Node* createNode(int data) {
```

```
    Node* newNode = (Node*)malloc(sizeof(Node));
```

```
    newNode->data = data;
```

```
    newNode->next = NULL;
```

```
    return newNode;
```

```
}
```

```
// Function to enqueue an element
```

```
void enqueue(Node** front, Node** rear, int data) {
```

```
    Node* newNode = createNode(data);
```

```
    if (*front == NULL) {
```

```
        *front = *rear = newNode;
```

```
    } else {
```

```
        (*rear)->next = newNode;
```

```
        *rear = newNode;
```

```
    }
```

```
}
```

```

// Function to dequeue an element
int dequeue(Node** front, Node** rear) {
    if (*front == NULL) {
        return -1; // Queue is empty
    }
    int data = (*front)->data;
    Node* temp = *front;
    *front = (*front)->next;
    if (*front == NULL) {
        *rear = NULL;
    }
    free(temp);
    return data;
}

```

```

int main() {
    Node* front = NULL;
    Node* rear = NULL;
    int input;

    // Read the input and enqueue the elements
    while (1) {
        scanf("%d", &input);
        if (input == -1) {
            break;
        }
        if (input < -1000 || input > 1000) {
            printf("Invalid input. Values should be between -1000 and 1000.\n");
            return 1;
        }
        enqueue(&front, &rear, input);
    }

    // Dequeue and print the elements
    printf("Dequeued elements: ");
    while (front != NULL) {
        printf("%d ", dequeue(&front, &rear));
    }
    printf("\n");

    return 0;
}

```

Status : Correct

Marks : 10/10

4. Problem Statement

Sharon is developing a queue using an array. She wants to provide the functionality to find the Kth largest element. The queue should support the addition and retrieval of the Kth largest element effectively. The maximum capacity of the queue is 10.

Assist her in the program.

Input Format

The first line of input consists of an integer N, representing the number of elements in the queue.

The second line consists of N space-separated integers.

The third line consists of an integer K.

Output Format

For each enqueued element, print a message: "Enqueued: " followed by the element.

The last line prints "The [K]th largest element: " followed by the Kth largest element.

Refer to the sample output for formatting specifications.

Sample Test Case

Input: 5
23 45 93 87 25
4

Output: Enqueued: 23
Enqueued: 45
Enqueued: 93
Enqueued: 87

Enqueued: 25

The 4th largest element: 25

Answer

```
#include <stdio.h>
```

```
#include <stdlib.h>
```

```
#define MAX_SIZE 10
```

```
// Function to find the Kth largest element in the queue
```

```
int findKthLargest(int queue[], int size, int K) {
```

```
    // Sort the queue in descending order
```

```
    for (int i = 0; i < size - 1; i++) {
```

```
        for (int j = 0; j < size - i - 1; j++) {
```

```
            if (queue[j] < queue[j + 1]) {
```

```
                int temp = queue[j];
```

```
                queue[j] = queue[j + 1];
```

```
                queue[j + 1] = temp;
```

```
            }
```

```
        }
```

```
    }
```

```
    // Return the Kth largest element
```

```
    return queue[K - 1];
```

```
}
```

```
int main() {
```

```
    int queue[MAX_SIZE];
```

```
    int front = -1, rear = -1;
```

```
    int N, K, input;
```

```
    // Read the input
```

```
    scanf("%d", &N);
```

```
    if (N < 1 || N > 10) {
```

```
        printf("Invalid input. N should be between 1 and 10.\n");
```

```
        return 1;
```

```
    }
```

```
    for (int i = 0; i < N; i++) {
```

```
        scanf("%d", &input);
```

```
        if (input < 1 || input > 100) {
```

```
            printf("Invalid input. Values should be between 1 and 100.\n");
```

```

        return 1;
    }
    queue[++rear] = input;
    printf("Enqueued: %d\n", input);
}

scanf("%d", &K);
if (K < 4 || K > 10) {
    printf("Invalid input. K should be between 4 and 10.\n");
    return 1;
}

int kthLargest = findKthLargest(queue, N, K);
printf("The %dth largest element: %d\n", K, kthLargest);

return 0;
}

```

Status : Correct

Marks : 10/10

5. Problem Statement

Guide Harish in developing a simple queue system for a customer service center. The customer service center can handle up to 25 customers at a time. The queue needs to support basic operations such as adding a customer to the queue, serving a customer (removing them from the queue), and displaying the current queue of customers.

Use an array for implementation.

Input Format

The first line of the input consists of an integer N, the number of customers arriving at the service center.

The second line consists of N space-separated integers, representing the customer IDs in the order they arrive.

Output Format

After serving the first customer in the queue, display the remaining customers in the queue.

If a dequeue operation is attempted on an empty queue, display "Underflow".

If the queue is empty, display "Queue is empty".

Refer to the sample output for formatting specifications.

Sample Test Case

Input: 5

101 102 103 104 105

Output: 102 103 104 105

Answer

```
// You are using GCC
```

```
#include <stdio.h>
```

```
#define MAX_QUEUE_SIZE 25
```

```
int queue[MAX_QUEUE_SIZE];
```

```
int front = -1, rear = -1;
```

```
// Function to enqueue a customer
```

```
int enqueue(int customer_id) {
```

```
    if (rear == MAX_QUEUE_SIZE - 1) {  
        return 0; // Queue is full
```

```
    }
```

```
    if (front == -1) {
```

```
        front = 0;
```

```
    }
```

```
    rear++;
```

```
    queue[rear] = customer_id;
```

```
    return 1; // Enqueue successful
```

```
}
```

```
// Function to dequeue a customer
```

```
int dequeue() {
```

```
    if (front == -1 || front > rear) {
```

```
        return -1; // Underflow
```

```
    }
```

```
    int customer_id = queue[front];
```

```
    if (front == rear) {  
        front = -1;  
        rear = -1;  
    } else {  
        front++;  
    }  
    return customer_id;  
}
```

// Function to display the current queue

```
void display_queue() {  
    if (front == -1) {  
        printf("Queue is empty.\n");  
        return;  
    }  
    for (int i = front; i <= rear; i++) {  
        printf("%d ", queue[i]);  
    }  
    printf("\n");  
}
```

```
int main() {  
    int n, customer_id;  
    if (scanf("%d", &n) != 1) {  
        return 1;  
    }  
    if (n == 0) {  
        printf("Underflow\n");  
        printf("Queue is empty\n");  
        return 0;  
    }  
    for (int i = 0; i < n; i++) {  
        if (scanf("%d", &customer_id) != 1) {  
            return 1;  
        }  
        if (!enqueue(customer_id)) {  
            printf("Queue is full.\n");  
            return 1;  
        }  
    }  
    int first_customer = dequeue();  
    if (first_customer == -1) {
```

```
printf("Underflow\n");  
printf("Queue is empty\n");  
} else {  
    display_queue();  
}  
return 0;  
}
```

Status : Correct

Marks : 10/10

Rajalakshmi Engineering College

Name: akshaya d
Email: 241901002@rajalakshmi.edu.in
Roll no: 241901002
Phone: 9363744696
Branch: REC
Department: I CSE (CS) FA
Batch: 2028
Degree: B.E - CSE (CS)

Scan to verify results



NeoColab_REC_CS23231_DATA STRUCTURES

REC_DS using C_Week 4_CY

Attempt : 1
Total Mark : 30
Marks Obtained : 30

Section 1 : Coding

1. Problem Statement

Saran is developing a simulation for a theme park where people wait in a queue for a popular ride.

Each person has a unique ticket number, and he needs to manage the queue using a linked list implementation.

Your task is to write a program for Saran that reads the number of people in the queue and their respective ticket numbers, enqueue them, and then calculate the sum of all ticket numbers to determine the total ticket value present in the queue.

Input Format

The first line of input consists of an integer N, representing the number of people

in the queue.

The second line consists of N space-separated integers, representing the ticket numbers.

Output Format

The output prints an integer representing the sum of all ticket numbers.

Refer to the sample output for formatting specifications.

Sample Test Case

Input: 5

2 4 6 7 5

Output: 24

Answer

```
#include <stdio.h>
```

```
#include <stdlib.h>
```

```
struct Node {  
    int ticketNumber;  
    struct Node* next;  
};
```

```
struct Node* createNode(int ticketNumber) {  
    struct Node* newNode = (struct Node*)malloc(sizeof(struct Node));  
    newNode->ticketNumber = ticketNumber;  
    newNode->next = NULL;  
    return newNode;  
}
```

```
void enqueue(struct Node** head, int ticketNumber) {  
    struct Node* newNode = createNode(ticketNumber);  
    if (*head == NULL) {  
        *head = newNode;  
    } else {  
        struct Node* temp = *head;  
        while (temp->next != NULL) {  
            temp = temp->next;  
        }  
        temp->next = newNode;  
    }
```

```
    }  
    temp->next = newNode;  
    }  
}
```

```
int calculateSum(struct Node* head) {  
    int sum = 0;  
    struct Node* temp = head;  
    while (temp != NULL) {  
        sum += temp->ticketNumber;  
        temp = temp->next;  
    }  
    return sum;  
}
```

```
int main() {  
    int N;  
    struct Node* queue = NULL;  
  
    scanf("%d", &N);  
  
    for (int i = 0; i < N; i++) {  
        int ticketNumber;  
        scanf("%d", &ticketNumber);  
        enqueue(&queue, ticketNumber);  
    }  
    int totalSum = calculateSum(queue);  
    printf("%d\n", totalSum);  
  
    struct Node* temp;  
    while (queue != NULL) {  
        temp = queue;  
        queue = queue->next;  
        free(temp);  
    }  
  
    return 0;  
}
```

Status : Correct

Marks : 10/10

2. Problem Statement

Imagine you are developing a basic task management system for a small team of software developers. Each task is represented by an integer, where positive integers indicate valid tasks and negative integers indicate erroneous tasks that need to be removed from the queue before processing.

Write a program using the queue with a linked list that allows the team to add tasks to the queue, remove all erroneous tasks (negative integers), and then display the valid tasks that remain in the queue.

Input Format

The first line consists of an integer N, representing the number of tasks to be added to the queue.

The second line consists of N space-separated integers, representing the tasks. Tasks can be both positive (valid) and negative (erroneous).

Output Format

The output displays the following format:

For each task enqueued, print a message "Enqueued: " followed by the task value.

The last line displays the "Queue Elements after Dequeue: " followed by removing all erroneous (negative) tasks and printing the valid tasks remaining in the queue in the order they were enqueued.

Refer to the sample output for formatting specifications.

Sample Test Case

Input: 5

12 -54 68 -79 53

Output: Enqueued: 12

Enqueued: -54

Enqueued: 68

Enqueued: -79

Enqueued: 53

Queue Elements after Dequeue: 12 68 53

Answer

```
#include <stdio.h>
```

```
#include <stdlib.h>
```

```
struct Node {  
    int task;  
    struct Node* next;  
};
```

```
struct Node* createNode(int task) {  
    struct Node* newNode = (struct Node*)malloc(sizeof(struct Node));  
    newNode->task = task;  
    newNode->next = NULL;  
    return newNode;  
}
```

```
void enqueue(struct Node** head, int task) {  
    struct Node* newNode = createNode(task);  
    if (*head == NULL) {  
        *head = newNode;  
    } else {  
        struct Node* temp = *head;  
        while (temp->next != NULL) {  
            temp = temp->next;  
        }  
        temp->next = newNode;  
    }  
    printf("Enqueued: %d\n", task);  
}
```

```
void displayQueue(struct Node* head) {  
    struct Node* temp = head;  
    printf("Queue Elements after Dequeue: ");  
    while (temp != NULL) {  
        if (temp->task >= 0) {  
            printf("%d ", temp->task);  
        }  
    }
```

```
    temp = temp->next;
}
printf("\n");
}
```

```
struct Node* removeErroneousTasks(struct Node* head) {
    struct Node* current = head;
    struct Node* previous = NULL;
```

```
    while (current != NULL) {
        if (current->task < 0) {
            if (previous == NULL) {
```

```
                struct Node* temp = current;
                current = current->next;
                free(temp);
                head = current;
            } else {
```

```
                previous->next = current->next;
                free(current);
                current = previous->next;
```

```
            }
        } else {
            previous = current;
            current = current->next;
```

```
    }
}
return head;
}
```

```
int main() {
    int N;
    struct Node* queue = NULL;
```

```
    scanf("%d", &N);
```

```
    for (int i = 0; i < N; i++) {
        int task;
        scanf("%d", &task);
        enqueue(&queue, task);
    }
```

```
queue = removeErroneousTasks(queue);
```

```
displayQueue(queue);
```

```
struct Node* temp;  
while (queue != NULL) {  
    temp = queue;  
    queue = queue->next;  
    free(temp);  
}
```

```
return 0;  
}
```

Status : Correct

Marks : 10/10

3. Problem Statement

Pathirana is a medical lab specialist who is responsible for managing blood count data for a group of patients. The lab uses a queue-based system to track the blood cell count of each patient. The queue structure helps in processing the data in a first-in-first-out (FIFO) manner.

However, Pathirana needs to remove the blood cell count that is positive even numbers from the queue using array implementation of queue, as they are not relevant to the specific analysis he is performing. The remaining data will then be used for further medical evaluations and reporting.

Input Format

The first line consists of an integer n , representing the number of a patient's blood cell count.

The second line consists of n space-separated integers, representing a blood cell count value.

Output Format

The output displays space-separated integers, representing the remaining blood

cell count after removing the positive even numbers.

Refer to the sample output for formatting specifications.

Sample Test Case

Input: 5

1 2 3 4 5

Output: 1 3 5

Answer

```
#include <stdio.h>
```

```
#define MAX_SIZE 15
```

```
int main() {
    int n, bloodCounts[MAX_SIZE], remainingCounts[MAX_SIZE];
    int j = 0;

    scanf("%d", &n);
    for (int i = 0; i < n; i++) {
        scanf("%d", &bloodCounts[i]);
    }

    for (int i = 0; i < n; i++) {
        if (!(bloodCounts[i] > 0 && bloodCounts[i] % 2 == 0)) {
            remainingCounts[j++] = bloodCounts[i];
        }
    }

    for (int i = 0; i < j; i++) {
        printf("%d", remainingCounts[i]);
        if (i < j - 1) {
            printf(" ");
        }
    }
    printf("\n");
    return 0;
}
```


Status : Correct

Marks : 10/10