

Creating a RESTful API using express.js and creating a database and index in MongoDB.

NAME:- AKSHAYA BANDI

EMAIL ID: akshayabandi12@gmail.com


PHONE NO:- 9182078256

ROLL NUMBER: 20ME1A04B4(ECE)

COLLEGE NAME:- RAMACHANDRA COLLEGE OF ENGINEERING, ELURU

source code :


index.js file :



```
1 import path from 'path';
2 import express from 'express';
3 import { config } from 'dotenv';
4 import { connectToDB } from './db/connectToDB.js';
5 config();
6 import userRoute from './routes/user.routes.js';
7
8
9 const __dirname = path.resolve();
10 const app = express();
11
12 app.use(express.json());
13
14 app.use('/api/user', userRoute);
15
16 app.use(express.static(path.join(__dirname, 'client/dist')));
17
18 app.get('*', (req, res) => {
19   res.sendFile(path.join(__dirname, 'client', 'dist', 'index.html'))
20 })
21
22 const PORT = process.env.PORT || 5000
23 app.listen(PORT, () => {
24   connectToDB();
25   console.log('Server is running on PORT : ', PORT)
26 })
```

```
> nodemon api/index.js
[nodemon] 3.1.0
[nodemon] to restart at any time, enter 'rs'
[nodemon] watching path(s): *.*
[nodemon] watching extensions: js,mjs,cjs,json
[nodemon] starting 'node api/index.js'
Server is running on PORT : 5000
DB connected successfully
```

MONGODB CONNECTION :




The screenshot shows the VS Code interface with the Explorer view on the left displaying a project structure. The file `connectToDB.js` is selected under the `db` folder. The main editor shows the code for `connectToDB.js`, which imports `mongoose` and defines a `connectToDB` function. The function attempts to connect to a MongoDB database using `process.env.CONN_STR` and logs the result. The terminal at the bottom shows the command `nodemon api/index.js` being executed, and the output indicates that the database connection was successful.

```
api > db > JS connectToDB.js > connectToDB
1 import mongoose from 'mongoose';
2
3 export function connectToDB(){
4   mongoose.connect(process.env.CONN_STR)
5   .then(()=>{
6     console.log("DB connected successfully")
7   })
8   .catch((err)=>{
9     console.log("Error while connecting to DB : ",err.message);
10  })
11 }
```

```
> nodemon api/index.js
[nodemon] 3.1.0
[nodemon] to restart at any time, enter `rs`
[nodemon] watching path(s): *.*
[nodemon] watching extensions: js,mjs,cjs,json
[nodemon] starting `node api/index.js`
Server is running on PORT : 5000
DB connected successfully
```

MODEL :




The screenshot shows the VS Code interface with the Explorer view on the left displaying a project structure. The file `emp.model.js` is selected under the `model` folder. The main editor shows the code for `emp.model.js`, which imports `mongoose` and defines a `userSchema` for a `User` model. The schema includes fields for `username`, `email`, `role`, and `salary`. The `Emp` model is created using `mongoose.model` and exported. The terminal at the bottom shows the command `nodemon api/index.js` being executed, and the output indicates that the database connection was successful.

```
api > model > JS emp.model.js > @ userSchema > role
1 import mongoose from 'mongoose';
2
3 const userSchema = new mongoose.Schema({
4   username:{
5     type:String,
6     unique:true,
7     required:true
8   },
9   email:{
10    type:String,
11    required:true
12  },
13  email:{
14    type:String,
15    required:true
16  },
17  role:{
18    type:String,
19    required:true
20  },
21  salary:{
22    type: Number,
23    required: true,
24  }
25 },{timestamps:true})
26
27 const Emp = mongoose.model("User",userSchema);
28
29 export default Emp;
```

```
> nodemon api/index.js
[nodemon] 3.1.0
[nodemon] to restart at any time, enter `rs`
[nodemon] watching path(s): *.*
[nodemon] watching extensions: js,mjs,cjs,json
[nodemon] starting `node api/index.js`
Server is running on PORT : 5000
DB connected successfully
```

ROUTES:




The screenshot shows the VS Code editor with the file explorer on the left. The file explorer shows a project structure with folders like api, controllers, db, model, routers, and client. The file user.routes.js is selected in the routers folder. The main editor shows the code for user.routes.js, which imports express and defines routes for create, read, update, and delete operations. The terminal at the bottom shows the command to run the application using nodemon, and the output indicates that the server is running on port 5000 and the database is connected successfully.

```
api > routers > JS user.routes.js > [Enter] router
1 import express from 'express'
2 import { create, readAll, read, remove, update, } from '../controllers/emp.controller.js';
3
4 const router = express.Router();
5
6 router.post('/create',create);
7 router.get('/readall',readAll);
8 router.get('/read/:id',read);
9 router.put('/update/:id',update);
10 router.delete('/remove/:id',remove);
11
12 export default router;
```

```
> nodemon api/index.js
[nodemon] 3.1.0
[nodemon] to restart at any time, enter `rs`
[nodemon] watching path(s): *.*
[nodemon] watching extensions: js,mjs,cjs,json
[nodemon] starting `node api/index.js`
Server is running on PORT : 5000
DB connected successfully
```

CONTROLLERS:


CREATE :



The screenshot shows the VS Code editor with the file explorer on the left. The file explorer shows a project structure with folders like api, controllers, db, model, routers, and client. The file emp.controller.js is selected in the controllers folder. The main editor shows the code for emp.controller.js, which defines a create function that takes a request and a response object, and returns a new employee object. The terminal at the bottom shows the command to run the application using nodemon, and the output indicates that the server is running on port 5000 and the database is connected successfully.


```
api > controllers > JS emp.controller.js > [Enter] remove
1 import Emp from '../model/emp.model.js';
2
3 export async function create(req,res){
4   try {
5     const {username,empname,email,role,salary} = req.body;
6
7     console.log(req.body);
8     const emp = await Emp.findOne({username});
9
10    if(emp) return res.status(400).json({error:"username is already exists"});
11
12    const newEmp = new Emp({
13      username,
14      empname,
15      email,
16      role,
17      salary
18    });
19
20    if(newEmp){
21      await newEmp.save();
22
23      res.status(201).json({
24        _id : newEmp._id,
25        username : newEmp.username,
26        empname : newEmp.empname,
27        email : newEmp.email,
28        role : newEmp.role,
29        salary : newEmp.salary
30      });
31    }else{
32      res.status(400).json({error:"Invalid emp data"});
33    }
34  } catch (error) {
35    console.log("Error in create controller : ",error.message);
36    res.status(500).json({message :error.message})
37  }
38 }
39
40 }
```

READALL:




```
api > controllers > JS emp.controller.js > remove
1  import Emp from "../model/emp.model.js";
2
3  > export async function create(req,res){...
40 }
41
42 > export async function read(req,res){...
58 }
59
60 export async function readAll(req,res){
61   try {
62     const emps = await Emp.find();
63
64     if(!emps || !emps.length ) return res.status(404).json({error:" no emp data found!"});
65
66     res.status(201).json({
67       emps
68     })
69   } catch (error) {
70     console.log("Error in create controller : ",error.message);
71     res.status(500).json({error:"Internal server Error"});
72   }
73 }
74
75 }
76
77 > export async function update(req,res){...
94 }
95
96 > export async function remove(req,res){...
110 }
```

READONE :



```
api > controllers > JS emp.controller.js > remove
1  import Emp from "../model/emp.model.js";
2
3  > export async function create(req,res){...
40 }
41
42 export async function read(req,res){
43   try {
44     const {id} = req.params;
45     const emp = await Emp.findById({_id:id});
46
47     if(!emp) return res.status(404).json({error:"emp not found!"});
48
49     res.status(201).json({
50       emp
51     })
52   } catch (error) {
53     console.log("Error in create controller : ",error.message);
54     res.status(500).json({error:"Internal server Error"});
55   }
56 }
57
58 }
59
60 > export async function readAll(req,res){...
75 }
76
77 > export async function update(req,res){...
94 }
95
96 > export async function remove(req,res){...
110 }
```


UPDATE :



The screenshot shows the VS Code editor with the file explorer on the left and the code editor on the right. The file explorer shows the project structure with folders like api, controllers, db, model, routers, and client. The code editor shows the file `emp.controller.js` with the following code:

```
api > controllers > JS emp.controller.js > remove
1  import Emp from "../model/emp.model.js";
2
3  > export async function create(req,res){ ...
40 }
41
42 > export async function read(req,res){ ...
58 }
59
60 > export async function readAll(req,res){ ...
75 }
76
77 export async function update(req,res){
78   try {
79     const {id} = req.params;
80
81     const emp = await Emp.findById(_id:id);
82
83     if(!emp) return res.status(404).json({error:"emp not found!"});
84
85     const newEmp = await Emp.findByIdAndUpdate(_id:id,{...req.body},{new:true});
86
87     res.status(201).json({
88       newEmp
89     })
90   } catch (error) {
91     console.log("Error in create controller : ",error.message);
92     res.status(500).json({error:"Internal server Error"})
93   }
94 }
95
96 > export async function remove(req,res){ ...
110 }
```

DELETE :



The screenshot shows the VS Code editor with the file explorer on the left and the code editor on the right. The file explorer shows the project structure with folders like api, controllers, db, model, routers, and client. The code editor shows the file `emp.controller.js` with the following code:

```
api > controllers > JS emp.controller.js > remove
1  import Emp from "../model/emp.model.js";
2
3  > export async function create(req,res){ ...
40 }
41
42 > export async function read(req,res){ ...
58 }
59
60 > export async function readAll(req,res){ ...
75 }
76
77 > export async function update(req,res){ ...
94 }
95
96 export async function remove(req,res){
97   try {
98     const {id} = req.params;
99
100    await Emp.findByIdAndDelete(_id:id);
101
102    res.status(201).json({
103      id,
104      message : "deleted successfully..",
105    })
106  } catch (error) {
107    console.log("Error in create controller : ",error.message);
108    res.status(500).json({error:"Internal server Error"})
109  }
110 }
```

HOW TO RUN ON LOCALLY :


- 1 . Create a folder as any name.
- 2 . Open that folder in any code editor (vs code).
- 3 . Open terminal (ctrl + ~) on code editor.
- 4 . Type this code to get code locally.

`git clone https://github.com/4727yesuraju/crud.git`
- 5 . Now move to crud folder (cd crud in terminal)
- 6 . Ignore client folder.
- 7 . Here crud is root folder.
- 8 . In root folder create a .env file and create a PORT and

CONN_STR variables and assign value.

ex : PORT = 3000 (commonly any number between 3000 - 8080).

CONN_STR = your mongodb_connection_string.



--- trouble in above process ? :

simply paste this code in .env file .

PORT = 5000

CONN_STR=mongodb+srv://4727yesuraju:rough@cluster0.wbclvtg.mongodb.net
/?retryWrites=true&w=majority&appName=Cluster0

9 . After in terminal (in crud folder as root folder) type this command to run server.

npm i (installing all dependencies)

npm run dev (to run server)

10 . if you get below message in terminal then your server will running successfully.

```
PS C:\Users\4727y\OneDrive\Desktop\internshala\crud> npm run dev

> crud@1.0.0 dev
> nodemon api/index.js

[nodemon] 3.1.0
[nodemon] to restart at any time, enter `rs`
[nodemon] watching path(s): *.*
[nodemon] watching extensions: js,mjs,cjs,json
[nodemon] starting `node api/index.js`
Server is running on PORT : 5000
DB connected successfully
```

route and its functionality :

For this use any API using tools like Postman or Thunder Client.

i use THUNDER CLIENT.

CREATE ROUTE :

1 . This route is used to create a new employee in database with a below fields.

username, empname, email, role, salary

**2 . in thunder client click on new request and select this options
method as post**

url as http://localhost:5000/api/user/create

pass this json data as a body as your required value.

```
{  
  
  "username": "jack",  
  
  "empname": "jack rider",  
  
  "email": "jack@gmail.com",  
  
  "role": "Front End Developer",  
  
  "salary": 60000  
}
```

**3 . finally press send to insert data in mongodb data base and get a
inserted**

data as a response.

**4 . If user is already in db it will return User is already exist as
response.**

for more details visit below output images...

READONE :

- 1 . This route is used to read specific user info by passing that user id as a param.

method as get

url as

http://localhost:5000/api/user/read/65ed7b3d76e1dcc9a51654ca

- 2 . After sending you will get that specific user details as response.

READALL :

- 1 . Read all route is used to get all the user data existing in the mongodb data base .

method as get

url as http://localhost:5000/api/user/readall

- 2 . After sending you will get that all user details as response.

UPDATE :

- 1 . This route is used to update specific user by passing that user id as a param.

method as put

url as

http://localhost:5000/api/user/update/65ed7b3d76e1dcc9a51654ca

- 2 . After sending you will get updated user details as response.

DELETE :

1 . This route is used to delete specific user by passing that user id as a param.

method as delete


url as

<http://localhost:5000/api/user/delete/65ed7b3d76e1dcc9a51654ca>


2 . After sending you will deleted successfully as response.

OUTPUT :


CREATE A NEW USER :




CREATING USER WITH EXISTING USERNAEM :




READONE :



READ ALL :



UPDATE :



DELETE :

The screenshot displays the Thunder Client interface with a DELETE request configured and executed. The request is sent to the URL `http://localhost:5000/api/user/remove/65ed7b3d76e1dcc9a51654ca`. The response is a 201 Created status with a JSON body containing the user ID and a success message.

Request Details:

- Method: DELETE
- URL: `http://localhost:5000/api/user/remove/65ed7b3d76e1dcc9a51654ca`
- Query Parameters: None

Response Details:

- Status: 201 Created
- Size: 68 Bytes
- Time: 111 ms
- Response Body:

```
{
  "id": "65ed7b3d76e1dcc9a51654ca",
  "message": "deleted successfully.."
}
```

Terminal Output:

```
Node.js v20.11.0
[nodemon] app crashed - waiting for file changes before starting...
[nodemon] restarting due to changes...
[nodemon] starting `node api/index.js`
Server is running on PORT : 5000
DB connected successfully
```