

INTELLIGENT BATTERY MANAGEMENT SYSTEM (AI-PBMS)

Industrial Applications, Field Operational Architecture & Commercial Deployment

Team ANS_4X · PSG Institute of Technology and Applied Research (PSG iTech)

1. INDUSTRIAL PROBLEM STATEMENT & REAL-WORLD MOTIVATION

- **The Limitations of Traditional BMS in the Field:** Conventional commercial BMS units act only as reactive fuses—they disconnect loads only *after* a cell drops below 2.80V or exceeds 55°C. In commercial operations, this results in sudden mid-trip vehicle strandings, unpredicted battery fires in depots, and accelerated degradation without warning.
- **Fleet Operational Blindspots:** Fleet managers lack actionable insight into individual cell health and impending failures. When a single weak cell degrades inside an 8S2P pack, the entire vehicle suffers reduced range, yet depot technicians cannot diagnose the root cause until the pack completely dies.
- **The AI-PBMS Value Proposition:** An edge-integrated, physics-informed AI system that predicts impending battery failures **30 to 90 seconds in advance**, enabling automated graceful power derating, driver early warnings, and zero-downtime maintenance dispatch.

2. TARGET INDUSTRIAL APPLICATIONS & USE CASES

- **Commercial Electric Vehicle Fleets (2W / 3W Logistics & Last-Mile Delivery):**
 - *Preventing Mid-Route Vehicle Strandings:* Identifies high-impedance weak cells that sag under sudden hill-climbing or heavy acceleration, alerting dispatch to reroute before the vehicle stalls.
 - *Intelligent Dynamic Power Derating:* Instead of abruptly cutting traction power on busy roads, the system communicates with motor controllers to restrict peak draw, allowing safe transit to the nearest service hub.
- **Battery Swapping Stations & Automated Health Screening:**
 - *Instant Pre-Charge Quarantine:* Automatically screens returning swapped packs for internal thermal gradients ($\Delta T > 5^{\circ}\text{C}$) or cell imbalance ($\Delta V \geq 80\text{ mV}$), isolating risky packs before fast-charging.
 - *Degradation-Based Pack Allocation:* Allocates healthier packs to high-demand commercial delivery riders while reserving partially degraded packs for low-speed, localized usage.
- **Stationary Energy Storage Systems (BESS) & Solar Microgrids:**
 - *Depot & Solar Storage Protection:* Mitigates catastrophic thermal runaway by flagging anomalous heat generation hours before conventional smoke or bimetallic heat sensors trip.
 - *Active Operational Equalization:* Identifies unevenly aging series blocks to schedule preventive module re-balancing during non-peak solar hours.
- **Circular Economy & Second-Life Battery Repurposing:**
 - *Automated Cell Health Grading:* Uses recorded driving cycle dynamic impedance signatures to classify retired EV battery modules for second-life residential backup without expensive laboratory teardowns.

3. END-TO-END FIELD OPERATIONAL ARCHITECTURE

- **Physical Battery Integration:** Designed for 8S2P Li-ion packs (LG INR21700-M50 NMC cells, 29.04V nominal, 10 Ah, ~290 Wh) equipped with industrial JBD balance wiring harnesses and 4 surface-mounted thermal probes.
- **Rugged Edge Gateway Telematics (Raspberry Pi / On-Board Unit):**
 - *Continuous Bluetooth Telemetry:* Connects wirelessly over BLE to the BMS interface at 1.0–2.0 Hz, reading 8 cell voltages, current, SOC, and temperatures without bulky communication wiring.
 - *Autonomous Offline Edge Resilience:* Operates fully independently of internet access. If a vehicle enters underground parking, tunnels, or rural dead-zones, telemetry logs continuously to local non-volatile storage (`bms_local_telemetry_log.csv`), and local physical acoustic alarms remain active.
- **Dual-Layer Decision Flow:** Real-time edge inference runs locally on the vehicle. Predictive ML models identify early anomalous trajectories, while hard Layer 1 physical safety logic guarantees immediate contactor disconnect if limits are violated.

INTELLIGENT BATTERY MANAGEMENT SYSTEM (AI-PBMS)

Operational Failure Remediation, Automated Dispatch Workflow & Economic Impact

Team ANS_4X · PSG Institute of Technology and Applied Research (PSG iTech)

4. FIELD FAILURE SCENARIOS & PRACTICAL REMEDIATION MATRIX

How the AI-PBMS translates live predictive anomaly detection into actionable operational workflows in real-world fleet environments:

Field Failure Scenario	Real-World Operational Risk	AI-PBMS Early Predictive Action	Field Maintenance & Fleet Response
Weak Cell Under Load (High Impedance)	Vehicle abruptly shuts down during high-load acceleration or steep incline, stranding goods.	Detects asymmetric dynamic sag (>20% vs pack) during acceleration pulses 60s ahead of cutoff.	Signals motor controller for graceful limp-home power limit; automatically tickets module for replacement.
Developing Cell Imbalance	Premature vehicle range loss; early termination of charge cycles; accelerated cell degradation.	Flags progressive divergence rate $d(\Delta V)/dt$ at 80 mV spread during driving transitions.	Schedules automated overnight active balancing cycle at depot; prevents premature pack scrapping.
Charging Thermal Runaway Risk	Localized hot-spot during fast charging triggers fire in parking garage or fleet depot.	Identifies rapid dT/dt rise $>0.1^{\circ}\text{C/s}$ and spatial gradient $\Delta T > 5^{\circ}\text{C}$ 90s before critical thermal trip.	Immediately throttles charger current, sounds local acoustic siren, and dispatches SMS/email to depot safety crew.
Regenerative Braking Overvoltage	Downhill braking at 100% SOC forces lithium plating, internal shorts, and permanent pack death.	Projects dV/dt trajectory near 4.20V/cell; warns that charge acceptance limit is being exceeded.	Dynamically tapers regenerative braking torque; safely dissipates surplus kinetic energy into mechanical brakes.
Impending Deep Overdischarge	Battery completely drained to 0% on delivery route, causing copper dissolution and total pack ruin.	Detects non-linear knee-point voltage collapse 60s prior to hard 2.80V cutoff.	Prompts driver with audible alert to pull over safely; navigates vehicle to nearest charging kiosk.
Harness / Wire Disconnection	Vibration on bumpy roads causes balance tap pin disconnect; conventional BMS falsely trips as dead cell.	Validates step-drop to 0V against current; recognizes non-physical open-circuit discontinuity.	Pinpoints exact disconnected balance wire channel in diagnostics alert, slashing technician troubleshooting to minutes.

5. AUTOMATED FIELD ALERTING & MAINTENANCE DISPATCH WORKFLOW

- **Three-Tiered Alert Escalation:**
 - *Tier 1 (Vehicle Driver / Operator):* Real-time acoustic warning beeps and visual dashboard banner indicating status (NORMAL / WARNING / CRITICAL) and actionable advice (e.g. "Reduce Speed - Limp Home Mode Engaged").
 - *Tier 2 (Depot Service Team):* Direct local SMTP email dispatch (`smtp.gmail.com:465` over SSL) dispatched in <1 second, containing fault classification, live driving mode, and an **attached CSV snapshot of the last 10 telemetry rows**.
 - *Tier 3 (Central Fleet Cloud Operations):* Live dashboard stream over HTTPS displaying fleet-wide pack status, health scores, and historical incident logs.
- **Zero Interruption to Vehicle Telematics:** Multi-threaded non-blocking queue (`queue.Queue`) offloads notification tasks so high-frequency sensor sampling and safety control never stall during network handshakes.

6. COMMERCIAL & ECONOMIC IMPACT (ROI FOR FLEET OPERATORS & OEMS)

- **Elimination of Catastrophic Fire Risk:** 30–90 seconds of advance predictive warning allows active thermal mitigation and safe passenger egress before hazardous thermal runaway can initiate.
- **Up to 40% Reduction in Unscheduled Roadside Downtime:** Shifts maintenance from reactive roadside towing to scheduled off-hours cell replacement at the depot.
- **15–25% Extended Usable Battery Life:** Mitigating micro-overcharging, aggressive deep discharge knees, and extreme thermal gradients preserves cell active material and slows irreversible capacity fade.
- **Transparent Warranty & Insurer Auditing:** The automated 10-row black-box forensic snapshot provides irrefutable evidence of operating conditions during fault events, preventing fraudulent warranty claims and lowering fleet insurance premiums.