EXP NO: 6	Bidirectional Rnn Vs Feedforward Nn For Time-Series Prediction

AIM:

To implement a Bidirectional RNN and a Feedforward Neural Network for time-series prediction on the Airline Passenger dataset and compare their prediction performance.

ALGORITHM:

1. Load the monthly airline passenger data and scale it to the range 0-1 with MinMaxScaler.
2. Create input sequences of length 10 with the next value as the target, and split them 80% training / 20% testing.
3. Convert the data to PyTorch tensors and create a DataLoader with batch size 16.
4. Define the BiRNN model: a bidirectional nn.RNN (hidden size 32) followed by a Linear(64, 1) layer applied to the last time step.
5. Define the Feedforward network: Linear(10, 32), ReLU, Linear(32, 1).
6. Train both models for 50 epochs using the Adam optimizer (learning rate 0.01) and the Mean Squared Error loss.
7. Predict on the test data, convert the values back to passenger counts and calculate the MSE of both models.
8. Plot the predictions against the actual values and compare the training losses.

CODE:

```
# EXPERIMENT 6
# Bidirectional RNN vs Feedforward Neural Network
# Time-Series Prediction using Airline Passenger Dataset

import pandas as pd
import numpy as np
import matplotlib.pyplot as plt
import torch
import torch.nn as nn

from sklearn.preprocessing import MinMaxScaler
from sklearn.metrics import mean_squared_error
from torch.utils.data import TensorDataset, DataLoader

# Device
device = torch.device("cuda" if torch.cuda.is_available() else "cpu")
print("Using device:", device)

# Load Airline Passenger Dataset
url = "https://raw.githubusercontent.com/jbrownlee/Datasets/refs/heads/master/monthly-airline

      -passengers.csv"

df = pd.read_csv(url)

data = df.iloc[:, 1].values.astype("float32").reshape(-1, 1)
# Normalize
scaler = MinMaxScaler()
data_scaled = scaler.fit_transform(data)

# Create sequences
SEQ_LENGTH = 10
```

```
X = []
y = []

for i in range(len(data_scaled) - SEQ_LENGTH):
    X.append(data_scaled[i:i + SEQ_LENGTH])
    y.append(data_scaled[i + SEQ_LENGTH])

X = np.array(X)
y = np.array(y)

# Train-test split
train_size = int(len(X) * 0.8)

X_train = X[:train_size]
X_test = X[train_size:]

y_train = y[:train_size]
y_test = y[train_size:]

# Convert to tensors
X_train_tensor = torch.tensor(X_train, dtype=torch.float32)
y_train_tensor = torch.tensor(y_train, dtype=torch.float32)

X_test_tensor = torch.tensor(X_test, dtype=torch.float32) y_test_tensor
= torch.tensor(y_test, dtype=torch.float32)

# DataLoader
train_loader = DataLoader(
    TensorDataset(X_train_tensor, y_train_tensor),
    batch_size=16,
    shuffle=True
)

# BiRNN Model
class BiRNN(nn.Module):

def __init__(self):
        super().__init__()

        self.rnn = nn.RNN(
            input_size=1,
            hidden_size=32,
            batch_first=True,
            bidirectional=True
        )

        self.fc = nn.Linear(64, 1)

    def forward(self, x):

        out, _ = self.rnn(x)

        return self.fc(out[:, -1, :])

# Feedforward Neural Network
class FeedforwardNN(nn.Module):

    def __init__(self):
        super().__init__()

        self.fc1 = nn.Linear(SEQ_LENGTH, 32)
        self.fc2 = nn.Linear(32, 1)
```

```
    def forward(self, x):

        x = x.view(x.size(0), -1)

        x = torch.relu(self.fc1(x))

        return self.fc2(x)

# Training function
def train_model(model, epochs=50):

    model = model.to(device) criterion

    =   nn.MSELoss()   optimizer   =

    torch.optim.Adam(
        model.parameters(),
        lr=0.01
    )

    losses = []

    for epoch in range(epochs):

        model.train()

        total_loss = 0

        for sequences, targets in train_loader:

            sequences = sequences.to(device)
            targets = targets.to(device)


            optimizer.zero_grad()

            outputs = model(sequences)

            loss = criterion(outputs, targets)

            loss.backward()

            optimizer.step()

            total_loss += loss.item()

        avg_loss = total_loss / len(train_loader)

        losses.append(avg_loss)

        if (epoch + 1) % 10 == 0:
            print(
                f"Epoch {epoch+1}/{epochs} - Loss: {avg_loss:.5f}"
            )

    return model, losses

# Train BiRNN
print("\nTraining BiRNN...")


birnn = BiRNN()

birnn, birnn_losses = train_model(birnn)
```

```
# Train Feedforward NN
print("\nTraining Feedforward Neural Network...")


ffnn = FeedforwardNN()

ffnn, ffnn_losses = train_model(ffnn)

# Prediction

birnn.eval()

ffnn.eval()

with torch.no_grad():
    X_test_device = X_test_tensor.to(device)

    pred_birnn = birnn(X_test_device).cpu().numpy()

    pred_ffnn = ffnn(X_test_device).cpu().numpy()

# Inverse transform
pred_birnn = scaler.inverse_transform(pred_birnn)


pred_ffnn = scaler.inverse_transform(pred_ffnn)

actual = scaler.inverse_transform(y_test)

# Calculate MSE

mse_birnn = mean_squared_error(actual, pred_birnn)

mse_ffnn = mean_squared_error(actual, pred_ffnn)

print("\nResults")
print(f"BiRNN MSE              : {mse_birnn:.2f}")
print(f"Feedforward MSE : {mse_ffnn:.2f}")
print("-----------------------")


# Plot predictions
plt.figure(figsize=(12, 5))


plt.plot(actual, label="Actual")

plt.plot(
    pred_birnn,
    label="BiRNN Prediction"
) plt.plot(


    pred_ffnn,
    label="Feedforward Prediction"

)

plt.title("BiRNN    vs    Feedforward    NN")

plt.xlabel("Time                              Step")

plt.ylabel("Passengers") plt.legend()

plt.grid()

plt.show()
```

```
# Plot training losses
plt.figure(figsize=(10, 5))

plt.plot(
        birnn_losses,
        label="BiRNN"
) plt.plot(


        ffnn_losses,
        label="Feedforward NN"

)

plt.title("Training        Loss        Comparison")

plt.xlabel("Epoch") plt.ylabel("Loss")

plt.legend()


plt.grid()


plt.show()
```

OUTPUT:

```
Using device: cpu
Training BiRNN...
Epoch 10/50 - Loss: 0.00203
Epoch 20/50 - Loss: 0.00256
Epoch 30/50 - Loss: 0.00201
Epoch 40/50 - Loss: 0.00177
Epoch 50/50 - Loss: 0.00238
Training Feedforward Neural Network... Epoch
10/50 - Loss: 0.00480
Epoch 20/50 - Loss: 0.00278
Epoch 30/50 - Loss: 0.00226
Epoch 40/50 - Loss: 0.00205
Epoch 50/50 - Loss: 0.00189
Results
------------------------------

BiRNN MSE              : 1707.09
    Feedforward MSE : 1452.24
```





RESULT:

The Bidirectional RNN and the Feedforward Neural Network were trained on the Airline Passenger data and both followed the trend of the test data. The test MSE was 1707.09 for the BiRNN and 1452.24 for the Feedforward network, so the Feedforward network gave the lower error in this run.