ReconX CLI Report

Target: example.com

Summary

Open Ports: 2 | Vulnerabilities: 16 | Paths: 11 | Subdomains: 7 | Technologies: 1 | Takeovers: 0

Open Ports

80/tcp

443/tcp

Discovered Subdomains

dev.example.com () [ct_sh] status=None title=

emudhra-lab.example.com () [ct_sh] status=None title=

example.com () [ct_sh] status=None title=

m.example.com () [ct_sh] status=None title=

products.example.com () [ct_sh] status=None title=

support.example.com () [ct_sh] status=None title=

www.example.com () [ct_sh] status=None title=

Discovered Paths

OPTIONS admin (405) text/html

OPTIONS api (405) text/html

OPTIONS assets (405) text/html

OPTIONS backup (405) text/html

OPTIONS config (405) text/html

OPTIONS dashboard (405) text/html

OPTIONS login (405) text/html

OPTIONS robots.txt (405) text/html

OPTIONS sitemap.xml (405) text/html

OPTIONS static (405) text/html

OPTIONS uploads (405) text/html

Technology Stack

Cloudflare (cdn) — Cloudflare is a content delivery network and DDoS protection service that sits between visitors and the or

Subdomain Takeovers

None found.

Vulnerabilities

[HIGH] Missing Security Header: Content-Security-Policy — Mitigates XSS and data-injection attacks by restricting resource
[HIGH] Missing Security Header: Strict-Transport-Security — Forces browsers to use HTTPS only (HSTS), preventing downg
[MEDIUM] Missing Security Header: X-Frame-Options — Protects against clickjacking by controlling frame embedding. [Secu
[MEDIUM] Missing Security Header: X-Content-Type-Options — Prevents MIME-type sniffing by browsers. [Security Headers
[LOW] Missing Security Header: Referrer-Policy — Controls how much referrer information is sent with requests. [Security H
[LOW] Missing Security Header: Permissions-Policy — Controls browser features and APIs available to the page. [Security H
[INFO] Missing Security Header: X-XSS-Protection — Legacy XSS filter toggle (modern CSP preferred). [Security Headers]
[LOW] Server Version Disclosure: Server — The server discloses technology version information via the Server header. [Info
[MEDIUM] Clickjacking Protection Missing — Neither X-Frame-Options nor Content-Security-Policy frame-ancestors is set, a
[LOW] MIME Sniffing Not Disabled — X-Content-Type-Options: nosniff is not set, allowing browsers to MIME-sniff responses
[MEDIUM] Dangerous HTTP Method Enabled: PUT — The server allows the PUT HTTP method, which may be abused for u
[MEDIUM] Dangerous HTTP Method Enabled: DELETE — The server allows the DELETE HTTP method, which may be abu
[MEDIUM] Dangerous HTTP Method Enabled: TRACE — The server allows the TRACE HTTP method, which may be abuse
[MEDIUM] Dangerous HTTP Method Enabled: CONNECT — The server allows the CONNECT HTTP method, which may be
[MEDIUM] Dangerous HTTP Method Enabled: PATCH — The server allows the PATCH HTTP method, which may be abuse
[MEDIUM] Dangerous HTTP Method Enabled: PROPFIND — The server allows the PROPFIND HTTP method, which may b

Potential Attack Areas (Not Tested)

SQL Injection (manual/authorized testing only)
OS Command Injection (manual/authorized testing only)
Broken Authentication (requires credential testing)
Brute Force (active attack, not performed)
Advanced XSS payloads (not performed)
CORS Misconfiguration (checked above)
Denial of Service (active attack, not performed)
Man-in-the-Middle (requires network position, not performed)

JWT Token Security (requires token analysis, not performed)