ReconX CLI Report

Target: example.com

Summary

Open Ports: 2 | Vulnerabilities: 16 | Paths: 11 | Subdomains: 7 | Technologies: 1

Open Ports

80/tcp - http

443/tcp - https

Discovered Subdomains

dev.example.com () [ct_sh] status=None title=

emudhra-lab.example.com () [ct_sh] status=None title=

example.com () [ct_sh] status=200 title=Example Domain

m.example.com () [ct_sh] status=None title=

products.example.com () [ct_sh] status=None title=

support.example.com () [ct_sh] status=None title=

www.example.com () [ct_sh] status=200 title=Example Domain

Discovered Paths

OPTIONS admin (405) text/html

POST api (405) text/html

POST assets (405) text/html

OPTIONS backup (405) text/html

POST config (405) text/html

POST dashboard (405) text/html

OPTIONS login (405) text/html

POST robots.txt (405) text/html

OPTIONS sitemap.xml (405) text/html

POST static (405) text/html

OPTIONS uploads (405) text/html

Technology Stack

Cloudflare (cdn) — Cloudflare is a content delivery network and DDoS protection service that sits between visitors and the or

Vulnerabilities

[HIGH] Missing Security Header: Content-Security-Policy — Mitigates XSS and data-injection attacks by restricting resource
[HIGH] Missing Security Header: Strict-Transport-Security — Forces browsers to use HTTPS only (HSTS), preventing downg
[MEDIUM] Missing Security Header: X-Frame-Options — Protects against clickjacking by controlling frame embedding. [Secu
[MEDIUM] Missing Security Header: X-Content-Type-Options — Prevents MIME-type sniffing by browsers. [Security Headers
[LOW] Missing Security Header: Referrer-Policy — Controls how much referrer information is sent with requests. [Security He
[LOW] Missing Security Header: Permissions-Policy — Controls browser features and APIs available to the page. [Security H
[INFO] Missing Security Header: X-XSS-Protection — Legacy XSS filter toggle (modern CSP preferred). [Security Headers]
[LOW] Server Version Disclosure: Server — The server discloses technology version information via the Server header. [Info
[MEDIUM] Clickjacking Protection Missing — Neither X-Frame-Options nor Content-Security-Policy frame-ancestors is set, a
[LOW] MIME Sniffing Not Disabled — X-Content-Type-Options: nosniff is not set, allowing browsers to MIME-sniff responses
[MEDIUM] Dangerous HTTP Method Enabled: PUT — The server allows the PUT HTTP method, which may be abused for u
[MEDIUM] Dangerous HTTP Method Enabled: DELETE — The server allows the DELETE HTTP method, which may be abu
[MEDIUM] Dangerous HTTP Method Enabled: TRACE — The server allows the TRACE HTTP method, which may be abuse
[MEDIUM] Dangerous HTTP Method Enabled: CONNECT — The server allows the CONNECT HTTP method, which may be
[MEDIUM] Dangerous HTTP Method Enabled: PATCH — The server allows the PATCH HTTP method, which may be abuse
[MEDIUM] Dangerous HTTP Method Enabled: PROPFIND — The server allows the PROPFIND HTTP method, which may b

Potential Attack Areas (Not Tested)

None found.