

(To be filed within 30 days after drilling is completed)

OKLAHOMA CORPORATION COMMISSION

OIL AND GAS CONSERVATION DIVISION

380 Jim Thorpe Building — Oklahoma City, Oklahoma 73103


4815

OTC COUNTY
LEASE NO

API NO

640 Acres
N

COUNTY Creek, SEC 16, TWP 16N, RGE 9E

COMPANY OPERATING Bovaard Inc.OFFICE ADDRESS Box 2590 or 823 S. Detroit (74120)TOWN Tulsa STATE OK ZIP 74102FARM NAME Ada Williams WELL NO 1DRILLING STARTED 1923 DRILLING FINISHED 1923DATE OF FIRST PRODUCTION 1923 COMPLETED 1923WELL LOCATED SE 1/4 SW 1/4 SE 1/4 264', North of SouthLine and 3.696' ft East of West Line of Quarter SectionElevation (Relative to sea level) NR DERRICK FLOOR NR GROUND NRCHARACTER OF WELL (Oil, gas or dryhole) Oil SWDLOCATE WELL CORRECTLY
AND OUTLINE LEASE

ORDER NO

OIL OR GAS SANDS OR ZONES

Name	From	To	Name	From	To
1 Dutcher	2960	3006	4		
2			5		
3			6		

Perforating Record If Any

Shot Record

Formation	From	To	No of Shots	Formation	From	To	Size of shot
			None				NR

CASING — PACKER RECORD

CASING SET						CSG PULLED		PACKER	
Size	Wgt	Thrds	Grade	Ft	In	Size	Length	Depth Set	Make
7"	NR	NR	NR	2775'	-				
5 1/2"	NR	NR	NR	2760'	-				
5" liner	NR	NR	NR	206				2754	NR

CEMENT AND MUDDING

Casing Set			Cement				Chemical		Method of Cementing	Casing Test (Rule 206)	
Size	Ft	In	Sacks	Fill-up	Top	Gals	Make			Pressure	Bailing
7"	2775	-	NR	NR	NR	NR	NR	NR	NR	NR	NR
5 1/2"	2760	-	NR	NR	NR	NR	NR	NR	NR	NR	NR

NOTE What method was used to protect sands if outer strings were pulled? NRNOTE Were bottom hole plugs used? NR If so, state kind, depth set and results obtained -

TOOLS USED

Rotary tools were used from none Feet to none Cable tools were used from 0 feet to 3006'Size of hole drilled Rotary none Cable NR

INITIAL PRODUCTION TEST (Rule 2-101)

Date 1923 Duration NR hrs, Pumping ☐ Flowing ☐

Producing Thru Casing ☐ Tubing ☒ Size of Choke NR

Oil Production NR Bbls, A P I Gravity NR

Gas Production NR MCF, Open Flow Potential NR MCF

Water Production NR Bbls, Gas-Oil Ratio NR

Casing Pressure NR P S I A, Tubing Pressure NR P S I A

(RULE 3-205) FORMATION RECORD

Give detailed description and thickness of all formations drilled through, contents of sand, whether dry, water, oil or gas

Formation	Top	Bottom	Formation	Top	Bottom
Red Sand		25'			
Shale	35'	105'			
Sand	105'	140'			
Blue Shale	140'	260'			
Lime	260'	325'			
Fine Sand	325'	360'			
Shale	360'	500'			
Lime	500'	515'			
Shale	515'	600'			
Lime	600'	610'			
Shale	610'	700'			
Lime	700'	710'			
Shale	710'	820'			
Shale	820'	840'			
Shale	840'	870'			
Shale	870'	920'			
Lime	920'	935'			
Shale	935'	1400'			
Shale	1400'	1900'			
Lime Shell	1900'	1915'			
Shale	1915'	2170'			
Lime Shell	2170'	2300'			
Shale	2300'	2610'			
Glenn Sand	2610'	2750'			
Shale	2750'	2775'			
Shale	2775'	2960'			
Sand-Dutcher	2960'	2970'			
Shale	2970'	2989'			
Sand	2989'	3006'			

RECEIVED

OIL & GAS CONSERVATION DIVISION

MAR - 2 1977

OKLAHOMA CORPORATION
COMMISSION

Note: This well has been converted to a SWD well by
permission of the Oklahoma Corporation Commission, cause
PD 3159, Order #128319, February 23, 1977

I, the undersigned, being first duly sworn upon oath, state that this well record is true, correct
and complete according to the records of this office and the best of my knowledge and belief

BOVAIRD, INC.

Wanda H. Harkins
Name and title of representative of company
Vice-President

Subscribed and sworn before me this 1st day of March, 19 77

My Commission expires June 3, 1978

James S. Pitman
Notary Public