



PRESSED-WOOD PALLET DECLARATION

Pressed-wood pallet PW-AU-1165, 1165 x 1165 mm

Ref: SYN/PW/2026/23 | Batch: SYN-PW-260908-23 | Region: Australia

Issue: 2026-09-08 | Valid until: 2027-09-07 | Revision: 01

01 DIMENSIONS AND HANDLING

Property	Declared nominal value	Basis
Footprint (L x W)	1165 x 1165 mm	45.9 x 45.9 in (approx.)
Overall height	145 mm	Selected within 142-152 mm
Empty pallet mass	19.0 kg	Selected within 14-20 kg
Dynamic load	Up to 1,134 kg	Approx. 2,500 lb; uniform payload

02 CONSTITUENTS - AS-SUPPLIED INPUT MASS

Constituent	Input share	Material description
MUF resin	25%	Melamine Urea Formaldehyde
Crushed wood	75%	Wood particles for moulded presswood

Resin solids: **55%** of supplied MUF resin mass. Resin grade designation: E0.

Recipe totals 100% of input mass. Resin solids are a property of the resin input; the resin-solids percentage is not an additional formulation constituent. Finished dry composition is not declared.


03 PROCESSED-WOOD STATUS

Entire pallet, including moulded feet, consists of crushed wood bonded with resin and formed using heat and pressure. No solid-sawn wood parts are included. The manufacturer claims the processed-wood exemption under ISPM 15 section 2.1. An HT treatment certificate and IPPC mark are not issued for this wholly processed-wood article.

04 PACKAGING SUBSTANCE DECLARATION

For the named pallet/component, Pb + Cd + Hg + Cr(VI) sum = 32.4 mg/kg, assessed with CR 13695-1:2000. The supplier declares compliance with the 100 mg/kg SUM limit in Regulation (EU) 2025/40 Article 5(4). This fictional declaration is not an accredited laboratory report.

E0 is a supplier resin-grade description only; no formaldehyde test method or emission result is supplied. Load capacity is a synthetic manufacturer claim without an attached load-test report. Regional footprint names do not establish EUR/EPAL certification.



Avira Nelvon | Head - Quality Assurance

Approved for the stated grade and batch; changes require reissue.

