Performance Limits of Tunable Servers with Finite Buffer Capacity and a Packet-Drop Probability Constraint

Akshit Kumar¹ Parikshit Hegde¹ Rahul Vaze²

¹Department of Electrical Engineering Indian Institute of Technology, Madras

²School of Technology and Computer Science Tata Institute of Fundamental Research, Mumbai

VSRP Talk, 2017

Motivation: Immigration Queue

Motivation: Immigration Queue



Motivation: Immigration Queue





Motivation: Web Hosting


Motivation: Web Hosting


























• $c_t \propto f(\gamma g_t)$, f is a convex function

- $c_t \propto f(\gamma g_t)$, f is a convex function
- $\blacktriangleright \ \mu = \mathbb{E}\left[E_t\right]$

- $c_t \propto f(\gamma g_t)$, f is a convex function
- $\mu = \mathbb{E}\left[E_t\right]$
- ▶ Good choice for servers is $c_t = g_t^2$ [Wierman et. al.]

- $c_t \propto f(\gamma g_t)$, f is a convex function
- $\blacktriangleright \ \mu = \mathbb{E}\left[E_t\right]$
- ▶ Good choice for servers is $c_t = g_t^2$ [Wierman et. al.]

So our objective is to

minimize
$$\lim_{n\to\infty} \mathbb{E}\left[\frac{1}{n}\sum_{t=1}^n c_t\right]$$

- $c_t \propto f(\gamma g_t)$, f is a convex function
- $\mu = \mathbb{E}\left[E_t\right]$
- ▶ Good choice for servers is $c_t = g_t^2$ [Wierman et. al.]

So our objective is to

minimize
$$\lim_{n \to \infty} \mathbb{E}\left[\frac{1}{n} \sum_{t=1}^{n} c_{t}\right]$$
 subject to $P_{dropping} \leq \alpha$ (1)

The probability constraint can be equivalently written as:

The probability constraint can be equivalently written as:

$$\lim_{n \to \infty} \mathbb{E}\left[\sum_{t=1}^{n} g_{t} + B\right] \geq (1 - \alpha) \mathbb{E}\left[\sum_{t=1}^{n} E_{t}\right]$$

$$\lim_{n \to \infty} \mathbb{E}\left[\frac{\sum_{t=1}^{n} g_{t}}{n} + \frac{B}{n}\right] \geq (1 - \alpha) \mathbb{E}\left[\frac{\sum_{t=1}^{n} E_{t}}{n}\right]$$

$$= (1 - \alpha)\mu$$

The probability constraint can be equivalently written as:

$$\lim_{n \to \infty} \mathbb{E} \left[\sum_{t=1}^{n} g_t + B \right] \ge (1 - \alpha) \mathbb{E} \left[\sum_{t=1}^{n} E_t \right]$$

$$\lim_{n \to \infty} \mathbb{E} \left[\frac{\sum_{t=1}^{n} g_t}{n} + \frac{B}{n} \right] \ge (1 - \alpha) \mathbb{E} \left[\frac{\sum_{t=1}^{n} E_t}{n} \right]$$

$$= (1 - \alpha)\mu$$

Now, the performance of an arbitrary policy is given by:

The probability constraint can be equivalently written as:

$$\lim_{n \to \infty} \mathbb{E} \left[\sum_{t=1}^{n} g_t + B \right] \ge (1 - \alpha) \mathbb{E} \left[\sum_{t=1}^{n} E_t \right]$$

$$\lim_{n \to \infty} \mathbb{E} \left[\frac{\sum_{t=1}^{n} g_t}{n} + \frac{\beta}{n} \right] \ge (1 - \alpha) \mathbb{E} \left[\frac{\sum_{t=1}^{n} E_t}{n} \right]$$

$$= (1 - \alpha) \mu$$

Now, the performance of an arbitrary policy is given by:

$$\mathcal{J} = \mathbb{E}\left[\lim_{n \to \infty} \frac{1}{n} \sum_{t=1}^{n} f(g_t)\right]$$

$$\geq f\left(\mathbb{E}\left[\lim_{n \to \infty} \frac{1}{n} \sum_{t=1}^{n} g_t\right]\right)$$
 Using Jensen's Inequality
$$= f((1-\alpha)\mu) = \mathcal{J} *$$

► Perkins & Srikant,1999 : Finding the optimal policy is hard

- ▶ Perkins & Srikant,1999 : Finding the optimal policy is hard
- ► Hence we look for a "near" optimal policy

- ▶ Perkins & Srikant,1999 : Finding the optimal policy is hard
- ► Hence we look for a "near" optimal policy
- ► Fix packet arrival distribution to **Bernoulli Distribution**


- ► Perkins & Srikant,1999 : Finding the optimal policy is hard
- Hence we look for a "near" optimal policy
- ► Fix packet arrival distribution to **Bernoulli Distribution**

$$E_t = \begin{cases} B, & \text{w.p } p \implies \text{Queue gets full} \\ 0, & \text{w.p } 1 - p \end{cases}$$
 (2)

▶ Bernoulli distribution gives the worst performance (*Shaviv et al.*,2016)

If the number of packets in the buffer are b_t at time t, then


Tunable Server



service: $g_t = \lambda b_t$

If the number of packets in the buffer are b_t at time t, then

Tunable Server



service: $g_t = \lambda b_t$

▶ If the number of packets in the buffer are b_t at time t, then service: $g_t = \lambda b_t$

- ▶ If the number of packets in the buffer are b_t at time t, then service: $g_t = \lambda b_t$
- ▶ The Probability of Dropping can be calculated as:

$$P = \frac{\mathbb{E}_{N}\left[B(1-\lambda)^{N}\right]}{B}$$

- ▶ If the number of packets in the buffer are b_t at time t, then service: $g_t = \lambda b_t$
- ▶ The Probability of Dropping can be calculated as:

$$P = \frac{\mathbb{E}_{N}\left[B(1-\lambda)^{N}\right]}{B}$$

• Setting $P = \alpha$ in the above equation we get:

$$\lambda = \frac{p(1-\alpha)}{p(1-\alpha) + \alpha}$$

▶ The performance J_{λ} is given by:


$$J_{\lambda} = \frac{\mathbb{E}\left[\sum_{t=1}^{N} g_t^2\right]}{\mathbb{E} N} = \frac{B^2 p^2 (1-\alpha)^2}{1-(1-p)(1-\alpha)^2}$$

▶ The performance J_{λ} is given by:

$$J_{\lambda} = \frac{\mathbb{E}\left[\sum_{t=1}^{N} g_t^2\right]}{\mathbb{E} N} = \frac{B^2 p^2 (1-\alpha)^2}{1 - (1-p)(1-\alpha)^2}$$

▶ Recollect that the lower bound \mathcal{J}^* is given by:

$$\mathcal{J}^* = B^2 \rho^2 (1 - \alpha)^2 \tag{3}$$



Proposition

For $\alpha<<1$, p<<1, there exists no online policy that has a cost which is lower than $\Theta\left(\frac{B^2p^2}{p+\alpha}\right)$

Proposition

For $\alpha<<1$, p<<1, there exists no online policy that has a cost which is lower than $\Theta\left(\frac{B^2p^2}{p+\alpha}\right)$

$$\mathcal{J}_{\lambda} = \frac{B^{2} \rho^{2} (1 - \alpha)^{2}}{1 - (1 - \rho)(1 - \alpha)^{2}}$$
$$\approx \frac{B^{2} \rho^{2}}{\rho + 2\alpha} \qquad [\alpha << 1, \rho << 1]$$

$$P(N=1)$$

$$P(N=1)[B-g_1]$$

$$P(N=1)[B-g_1] \leq B\alpha$$

$$P(N = 1)[B - g_1] \le B\alpha$$
 $g_1 \ge B\left(1 - \frac{\alpha}{p}\right)$

$$P(N = 1)[B - g_1] \le B\alpha$$
 $g_1 \ge B\left(1 - \frac{\alpha}{p}\right)$
 $\approx B$

Simple Case: $\alpha << p$

Simple Case: $\alpha << p$

$$\mathcal{J} = \frac{\mathbb{E}\left[\sum_{t=1}^{N} g_t^2\right]}{\mathbb{E} N}$$

Simple Case: $\alpha << p$

$$\mathcal{J} = rac{\mathbb{E}\left[\sum_{t=1}^{N} g_t^2
ight]}{\mathbb{E}N}$$

$$\geq rac{g_1^2}{\mathbb{E}N}$$

Simple Case: $\alpha << p$

$$\mathcal{J} = \frac{\mathbb{E}\left[\sum_{t=1}^{N} g_t^2\right]}{\mathbb{E} N}$$
$$\geq \frac{g_1^2}{\mathbb{E} N}$$
$$\approx B^2 p$$

Simple Case:
$$\alpha << p$$

$$g_1 \approx B$$

$$\mathcal{J} = \frac{\mathbb{E}\left[\sum_{t=1}^{N} g_t^2\right]}{\mathbb{E} N}$$
$$\geq \frac{g_1^2}{\mathbb{E} N}$$
$$\approx B^2 p$$


$$\therefore \mathcal{J} \ge \Theta\left(\frac{B^2 p^2}{p+\alpha}\right)$$

 $[\mathsf{For}\ \alpha << \mathit{p}]$

Summary

- ▶ Tune server speed with convex cost function s.t., $P_{\sf drop} \leq \alpha$
- Approximate online-policy for Bernoulli packet arrivals.
- ▶ Lower bounds for any online-policy; our policy is near optimal.
- Future Work:
 - ► Extend the policy to a general arrival distribution
 - lacktriangle Tighten the lower bound for small lpha for a general distribution

Thank You!



Reference: I



James R. Perkins, R. Srikant

The Role of Queue Length Information In Congestion Control and Resource Pricing.

Proceedings of the 38th Conference on Decision and Control,1999.



Adam Wierman, Lachlan L.H. Andrew, Ao Tang Power-aware speed scaling in processor sharing systems: Optimality and robustness Performance Evaluation, 2012.

Simple Case:
$$lpha << p$$

$$P(\textit{N}=1)$$

$$g_1 \geq B\left(1-\frac{lpha}{p}\right)$$

$$\geq B/2$$

Simple Case:
$$\alpha << p$$

$$P(N = 1)[B - g_1]$$
 $g_1 \ge B\left(1 - \frac{\alpha}{p}\right)$ $\ge B/2$

$$P(N = 1)[B - g_1] \le B\alpha$$
 $g_1 \ge B\left(1 - \frac{\alpha}{p}\right)$
 $\ge B/2$

Case: $p \ge 2\alpha$

$$g_1 \geq B/2$$

$$\mathcal{J} = \frac{\mathbb{E}\left[\sum_{t=1}^{N} g_{t}^{2}\right]}{\mathbb{E} N}$$

$$\geq \frac{g_{1}^{2}}{\mathbb{E} N}$$

$$= \frac{B^{2}p}{4} \quad [\text{For } \alpha << 1, p \geq 2\alpha]$$

$$\therefore \mathcal{J} \geq \Theta\left(\frac{B^{2}p^{2}}{p+\alpha}\right)$$

▶ Recall:
$$\mathcal{J}_{\lambda} = \frac{B^2 p^2 (1-\alpha)^2}{1-(1-p)(1-\alpha)^2} \approx B^2 p$$
 [For $\alpha << p$]

$$p \leq 2\alpha$$

$$\begin{split} P[N \leq k] \left(B - \sum_{t=1}^k g_t\right) &\leq B\alpha \\ &\sum_{t=1}^k g_t \geq B\left(1 - \frac{\alpha}{pk}\right) \\ &\sum_{t=1}^k g_t \geq B/2 \quad \text{ choosing } k = \left\lceil \frac{2\alpha}{p} \right\rceil \end{split}$$

$$\begin{split} \mathcal{J} &= \frac{\mathbb{E}\left[\sum_{t=1}^{N} g_{t}^{2}\right]}{\mathbb{E}N} \\ &\geq p \cdot P(N \geq k)[g_{1}^{2} + g_{2}^{2} + \dots + g_{k}^{2}] \\ &\geq p(1 - pk) \cdot \frac{B^{2}}{4k} \\ &= \Theta\left(\frac{B^{2}p^{2}}{\alpha}\right) \\ &\therefore \mathcal{J} \geq \Theta\left(\frac{B^{2}p^{2}}{\alpha + p}\right) \end{split}$$