

DBEaver 25.2.5 - <.db> Script-1

File Edit Navigate Search SQL Editor Database Window Help

SQL Commit Rollback Auto .db

Database Navigator X Projects X <.db> Script-1 X

Filter connections by name

> .db

```
-- Groups rows by their 'occupation' value. Because no aggregate function is used, this effectively lists all unique occupations.
select occupation from dataset_1 group by occupation;

-- Groups rows by 'weather' and calculates the average of 'temperature' for each weather group, naming the new column 'avg_temp'.
select weather, avg(temperature) as avg_temp from dataset_1 group by weather;

-- Groups rows by 'weather' and counts the total number of 'temperature' entries within each group, naming the new column 'count_temp'.
select weather, count(temperature) as count_temp from dataset_1 group by weather;

-- Groups rows by 'weather' and counts the number of *distinct* 'temperature' values within each group, naming the new column 'count_distinct'.
select weather, count(distinct temperature) as count_distinct_temp from dataset_1 group by weather;

-- Groups rows by 'weather' and calculates the sum of 'temperature' for each weather group, naming the new column 'sum_temp'.
-- Usage: Calculating a total sum for each unique group.
select weather, sum(temperature) as sum_temp from dataset_1 group by weather;

-- Groups rows by 'weather' and finds the minimum 'temperature' value within each weather group, naming the new column 'min_temp'.
-- Usage: Finding the minimum value within each unique group.
select weather, min(temperature) as min_temp from dataset_1 group by weather;

-- Groups rows by 'weather' and finds the maximum 'temperature' value within each weather group, naming the new column 'max_temp'.
-- Usage: Finding the maximum value within each unique group.
select weather, max(temperature) as max_temp from dataset_1 group by weather;

-- Groups rows by 'occupation' and then filters those groups *after* aggregation to only include groups where the 'occupation' is 'Student'.
select occupation from dataset_1 group by occupation having occupation='Student';

-- Combines all rows from dataset_1 and table_to_union into a single result set, removes duplicates, and then selects the distinct 'destination'.
select distinct destination from (select * from dataset_1 union select * from table_to_union);
```

Files - General X

Name DataSource

Bookmarks

IST en Writable Smart Insert 34:1:1218 S...0

DBBeaver 25.2.5 - <.db> Script-1

File Edit Navigate Search SQL Editor Database Window Help

SQL Commit Rollback Auto .db

Database Navigator Projects <.db> Script-1

Filter connections by name

> .db

```
-- Selects all columns and all rows from the table named dataset_1.
select * from dataset_1;

-- Selects only the 'weather' and 'temperature' columns from dataset_1.
-- Usage: Selecting specific columns when not all data is needed.
select weather,temperature from dataset_1;

-- Selects all columns from dataset_1 but limits the results to the first 10 rows.
select * from dataset_1 limit 10;

-- Selects all unique (non-duplicate) values from the 'passanger' column.
select DISTINCT passanger from dataset_1 ;

-- Selects all rows from dataset_1 where the value in the 'destination' column is exactly 'Home'.
select * from dataset_1 where destination='Home';

-- Selects all rows from dataset_1 and orders the results in ascending order based on the 'coupon' column.
-- Usage: Sorting data by a specific column.
select * from dataset_1 order by coupon;

-- Selects the 'destination' column and renames it as 'Destination' in the result set.
select destination as Destination from dataset_1;

-- Groups rows by their 'occupation' value. Because no aggregate function is used, this effectively lists all unique occupations.
select occupation from dataset_1 group by occupation;

-- Groups rows by 'weather' and calculates the average of 'temperature' for each weather group, naming the new column 'avg_temp'.
select weather,avg(temperature) as avg_temp from dataset_1 group by weather;
```

Files - General

Name	DataSource
Bookmarks	

IST en Writable Smart Insert 21:1:685 S...0

DBeaver 25.2.5 - <.db> Script-1

File Edit Navigate Search SQL Editor Database Window Help

SQL Commit Rollback Auto .db

Database Navigator X Projects X <.db> Script-1 X

Filter connections by name

> .db

```
-- Groups rows by 'weather' and finds the minimum 'temperature' value within each weather group, naming the new column 'min_temp'.
-- Usage: Finding the minimum value within each unique group.
select weather,min(temperature) as min_temp from dataset_1 group by weather;

-- Groups rows by 'weather' and finds the maximum 'temperature' value within each weather group, naming the new column 'max_temp'.
-- Usage: Finding the maximum value within each unique group.
select weather,max(temperature) as max_temp from dataset_1 group by weather;

-- Groups rows by 'occupation' and then filters those groups *after* aggregation to only include groups where the 'occupation' is 'Student'.
select occupation from dataset_1 group by occupation having occupation='Student';

-- Combines all rows from dataset_1 and table_to_union into a single result set, removes duplicates, and then selects the distinct 'destination'.
select distinct destination from(select * from dataset_1 union select * from table_to_union);

-- Joins dataset_1 (aliased as 'a') and table_to_join (aliased as 'b') where their 'time' columns match, and selects the destination, time, and part_of_day.
select a.destination,a.time,b.part_of_day from dataset_1 a inner join table_to_join b on a.time=b.time;

-- Selects all rows from dataset_1 where the 'passanger' value is 'Alone', and then selects only the 'destination' and 'passanger' columns.
select destination,passanger from(select*from dataset_1 where passanger='Alone');

-- Selects all rows from dataset_1 where the 'weather' column starts with the characters 'Sun'.
select * from dataset_1 where weather like 'Sun%';

-- Selects all distinct 'temperature' values from dataset_1 where the temperature is inclusively between 29 and 75.
select distinct temperature from dataset_1 where temperature between 29 and 75;

-- Selects the 'occupation' column from dataset_1 where the occupation is one of the listed values ('Sales & Related' or 'Management').
select occupation from dataset_1 where occupation in('Sales & Related','Management');
```

Files - General X

Name DataSource

Bookmarks

IST en Writable Smart Insert 66:1:2960 S...0