

```

# --- VARIABLES & TYPES ---

x = 5          # an integer (whole number)
y = 3.14       # a float (decimal number)
name = "CGPA"  # a string (text) - always in quotes
is_placed = True # a boolean (True/False)

# type() tells you what kind of value a variable holds.
# You will use this constantly to sanity-check data you loaded from a CSV.
print(x, type(x))
print(y, type(y))
print(name, type(name))
print(is_placed, type(is_placed))

# --- ARITHMETIC OPERATORS ---
a = 7
b = 2
print("a + b =", a + b) # addition
print("a - b =", a - b) # subtraction
print("a * b =", a * b) # multiplication
print("a / b =", a / b) # division (always gives a float)
print("a ** 2 =", a ** 2) # exponent (a squared) - used in Mean Squared Error formulas

# --- COMPARISON OPERATORS ---
cgpa = 8.4
print("cgpa == 8.4 :", cgpa == 8.4) # equality check (note: double ==, not =)
print("cgpa > 8 :", cgpa > 8) # greater than
print("cgpa < 6 :", cgpa < 6) # less than

# --- LOGICAL OPERATORS: and / or / not ---
attendance = 85
placed = (cgpa > 8) and (attendance > 80) # both conditions must be true
print("placed :", placed)

# --- STRINGS & F-STRINGS ---

model_name = "Logistic Regression"
accuracy = 0.87345

# Old, clunky way (avoid this):
print("Accuracy of " + model_name + " is " + str(accuracy))

# f-string way (use this):
print(f"Accuracy of {model_name} is {accuracy}")

# '.3f' inside the braces rounds a float to 3 decimal places -
# you will use this in almost every experiment to print clean metrics.
print(f"Accuracy of {model_name} is {accuracy:.3f}")

# --- LISTS & INDEXING ---

features = ["CGPA", "AptitudeTestScore", "CodingTestScore", "MockInterviewScore"]

print(features) # the whole list
print(features[0]) # FIRST item - Python counts from 0, not 1
print(features[1]) # SECOND item
print(features[-1]) # LAST item - negative index counts from the end
print(len(features)) # how many items are in the list

# Slicing: features[start:end] gives you a sub-list (end is NOT included)
print(features[0:2]) # first two items

# Adding to a list
features.append("Internships")
print(features)

# --- DICTIONARIES ---

# key = model name (string), value = the actual model object
from sklearn.linear_model import Ridge, Lasso, ElasticNet

models = {
    "Ridge": Ridge(alpha=1.0),
    "Lasso": Lasso(alpha=0.01),
    "ElasticNet": ElasticNet(alpha=0.01),
}

print(models) # the whole dictionary
print(models["Ridge"]) # access one value by its key

# Looping over a dictionary's keys and values together:
for name, model in models.items():
    print(f"Model name: {name} > Object: {model}")

```

```

print(f"Model name: {name} / Object: {model}")

# --- IF / ELIF / ELSE ---

cgpa = 8.2

if cgpa >= 9:
    tier = "High"
elif cgpa >= 7:
    tier = "Mid"
else:
    tier = "Low"

print(f"CGPA {cgpa} falls into tier: {tier}")

# You can also use if/else to guard against bad data,
# e.g. before dividing or indexing:
missing_count = 0
if missing_count == 0:
    print("No missing values - safe to proceed.")
else:
    print("Missing values found - impute before modelling.")

# --- FOR LOOPS ---

depths = [2, 4, 6, 8, 10]

for depth in depths:
    print(f"Training a tree with max_depth = {depth}")

# range() generates a sequence of numbers without writing them all out
for epoch in range(5):          # 0, 1, 2, 3, 4
    print(f"Epoch {epoch}: computing gradient...")

# Looping with an index AND a value using enumerate()
for i, d in enumerate(depths):
    print(f"Sweep step {i}: depth={d}")

# --- FUNCTIONS ---

def classify_cgpa(cgpa):
    """Takes a CGPA value and returns a tier label."""
    if cgpa >= 9:
        return "High"
    elif cgpa >= 7:
        return "Mid"
    else:
        return "Low"

# Calling the function with different inputs:
print(classify_cgpa(9.5))
print(classify_cgpa(7.8))
print(classify_cgpa(5.2))

# A function with more than one input (parameter):
def describe_model(name, accuracy):
    return f"{name} achieved {accuracy:.1%} accuracy"

print(describe_model("Random Forest", 0.913))

# --- IMPORTING LIBRARIES ---

import pandas as pd                # gives pandas the short name "pd"
import numpy as np                 # gives numpy the short name "np"
from sklearn.linear_model import LogisticRegression # import ONE class from a big library
from sklearn.metrics import accuracy_score

# Colab-only: install a library that isn't there by default (note the leading !)
# !pip install xgboost

print("pandas version:", pd.__version__)
print("numpy version :", np.__version__)

# 9. IMPORTING LIBRARIES
import pandas as pd
from sklearn.model_selection import train_test_split
from sklearn.linear_model import LogisticRegression, Ridge
from sklearn.tree import DecisionTreeClassifier
from sklearn.metrics import accuracy_score

# 1. VARIABLES & TYPES
csv_path = "placement_predict_50k_Dataset.csv"    # a string
min_acceptable_accuracy = 0.7                    # a float

```

```
# 4. LISTS
features = ["CGPA", "AptitudeTestScore", "CodingTestScore", "AttendancePercent"]

df = pd.read_csv('/content/placement_predict_50k Dataset.csv')
df[features] = df[features].fillna(df[features].median()) # handle missing values
X, y = df[features], df["PlacementStatus"]
X_train, X_test, y_train, y_test = train_test_split(
    X, y, test_size=0.2, random_state=42, stratify=y)

# 5. DICTIONARIES - comparing two models by name
models = {
    "Logistic Regression": LogisticRegression(max_iter=1000),
    "Decision Tree": DecisionTreeClassifier(max_depth=5, random_state=42),
}

# 8. FUNCTION definition
def evaluate_model(model, X_train, y_train, X_test, y_test):
    """Fits a model and returns its test accuracy."""
    model.fit(X_train, y_train)
    preds = model.predict(X_test)
    return accuracy_score(y_test, preds)

# 7. FOR LOOP over the dictionary + 6. IF/ELIF/ELSE + 3. F-STRINGS
for name, model in models.items():
    acc = evaluate_model(model, X_train, y_train, X_test, y_test) # 2. uses arithmetic internally

    if acc >= min_acceptable_accuracy:
        verdict = "GOOD"
    else:
        verdict = "NEEDS WORK"

    print(f"{name:<20} accuracy={acc:.3f} -> {verdict}")
```

```
5 <class 'int'>
3.14 <class 'float'>
CGPA <class 'str'>
True <class 'bool'>
a + b = 9
a - b = 5
a * b = 14
a / b = 3.5
a ** 2 = 49
cgpa == 8.4 : True
cgpa > 8 : True
cgpa < 6 : False
placed : True
Accuracy of Logistic Regression is 0.87345
Accuracy of Logistic Regression is 0.87345
Accuracy of Logistic Regression is 0.873
['CGPA', 'AptitudeTestScore', 'CodingTestScore', 'MockInterviewScore']
CGPA
AptitudeTestScore
MockInterviewScore
4
['CGPA', 'AptitudeTestScore']
['CGPA', 'AptitudeTestScore', 'CodingTestScore', 'MockInterviewScore', 'Internships']
{'Ridge': Ridge(), 'Lasso': Lasso(alpha=0.01), 'ElasticNet': ElasticNet(alpha=0.01)}
Ridge()
Model name: Ridge -> Object: Ridge()
Model name: Lasso -> Object: Lasso(alpha=0.01)
Model name: ElasticNet -> Object: ElasticNet(alpha=0.01)
CGPA 8.2 falls into tier: Mid
No missing values - safe to proceed.
Training a tree with max_depth = 2
Training a tree with max_depth = 4
Training a tree with max_depth = 6
Training a tree with max_depth = 8
Training a tree with max_depth = 10
Epoch 0: computing gradient...
Epoch 1: computing gradient...
Epoch 2: computing gradient...
Epoch 3: computing gradient...
Epoch 4: computing gradient...
Sweep step 0: depth=2
Sweep step 1: depth=4
Sweep step 2: depth=6
Sweep step 3: depth=8
Sweep step 4: depth=10
High
Mid
Low
Random Forest achieved 91.3% accuracy
pandas version: 2.2.2
numpy version : 2.0.2
Logistic Regression accuracy=0.877 -> GOOD
Decision Tree accuracy=0.877 -> GOOD
```

Start coding or [generate](#) with AI.