

```
akshitha_reddy@Akshitha-Reddy:~$ sudo apt install tree
[sudo: authenticate] Password:
tree is already the newest version (2.3.1-1).
Summary:
  Upgrading: 0, Installing: 0, Removing: 0, Not Upgrading: 25
akshitha_reddy@Akshitha-Reddy:~$ tree
```

```
.
├── FileManagement
│   ├── a.tx
│   ├── b.txt
│   ├── file
│   ├── file1.txt
│   ├── hello
│   ├── newcopy.txt
│   └── numbers.txt
├── OSSP
│   ├── LICENSE
│   ├── Makefile
│   ├── README.md
│   ├── assets
│   │   └── architecture.png
│   ├── bin
│   ├── docs
│   │   ├── design.md
│   │   └── report.pdf
│   ├── include
│   │   ├── builtin.h
│   │   ├── executor.h
│   │   ├── parser.h
│   │   └── shell.h
│   ├── obj
│   ├── scripts
│   │   └── run.sh
│   └── src
│       ├── builtin.c
│       ├── executor.c
│       ├── main.c
│       ├── parser.c
│       └── shell.c
```

```
├── tests
│   ├── design.md
│   └── report.pdf
├── OS_LAB
│   ├── task1
│   └── task1.c
├── ProcessTask
│   ├── task2
│   └── task2.c
└── file.txt
```

13 directories, 30 files

akshitha_reddy@Akshitha-Reddy:~\$ |

This Terminal window is running as administrator

```
#include <unistd.h>
int main() {
    pid_t pid;
    pid = fork();    // Create a new process
    if (pid < 0) {
        printf("Fork failed!\n");
    }
    else if (pid == 0) {
        // Child Process
        printf("This is the Child Process.\n");
        printf("Child PID = %d\n", getpid());
    }
    else {
        // Parent Process
        printf("This is the Parent Process.\n");
        printf("Parent PID = %d\n", getpid());
        printf("Child PID = %d\n", pid);
    }
    return 0;
}
```

```
akshitha_reddy@Akshitha-Reddy:~$ cd ProcessTask
akshitha_reddy@Akshitha-Reddy:~/ProcessTask$ nano task2.c
akshitha_reddy@Akshitha-Reddy:~/ProcessTask$ gcc task2.c -o task2
akshitha_reddy@Akshitha-Reddy:~/ProcessTask$ ./task2
This is the Parent Process.
This is the Child Process.
Child PID = 2072
Parent PID = 2071
Child PID = 2072
akshitha_reddy@Akshitha-Reddy:~/ProcessTask$ |
```